

Image Matching System using Early Vision

Longbin Jin



Artificial Intelligence
& Computer Vision
Laboratory

Image Matching System

Image dataset

Preprocessing

- Point processing
 - Gray scale / HSI
 - Contrast stretching
- Area processing
 - Noise filtering
 - Edge
 - Sharpening
 - Morphological
- Deep Learning

Feature extraction

- Color
 - Color histogram
- Texture
 - LBP
 - GLCM
 - Law's texture
- Shape
 - Harris corner
 - SIFT
 - HoG
- Deep Learning


Classification

- Similarity
 - Distance
 - Cosine similarity
- ML classifier
 - KNN
 - SVM
 -
- Deep Learning


Dataset - reCAPTCHA



reCAPTCHA v1



reCAPTCHA v2



reCAPTCHA v3

Dataset

- link
 - git clone <https://github.com/folfcoder/recaptcha-dataset.git>
- Classes (without mountain)



Bicycle (800)



Bridge (553)



Bus (1229)




Car (3578)



Chimney (56)




Crosswalk (1260)




Hydrant (972)



Motorcycle (101)



Palm (932)



Traffic Light (811)

Dataset

- Remove outlier
 - You don't have to use all the data to fit your model



Bicycle?



Car?



Traffic light?


- Multi-labels
 - Some images may have multi objects



Crosswalk + Car




Crosswalk + Car+ Traffic light



Bicycle + Car

Dataset Split

- K-fold cross validation (k=5)



Dataset Split

- K-fold cross validation (k=5)




fold 1	fold 2	fold 3	fold 4	fold 5
Bicycle Bridge	Bus Car	Chimney Crosswalk	Hydrant Motorcycle	Palm Traffic Light



Bicycle (20%) Bridge (20%) Bus (20%) Car (20%) Chimney (20%) Crosswalk (20%) Hydrant (20%) Motorcycle (20%) Palm (20%) Traffic Light (20%)	Bicycle (20%) Bridge (20%) Bus (20%) Car (20%) Chimney (20%) Crosswalk (20%) Hydrant (20%) Motorcycle (20%) Palm (20%) Traffic Light (20%)	Bicycle (20%) Bridge (20%) Bus (20%) Car (20%) Chimney (20%) Crosswalk (20%) Hydrant (20%) Motorcycle (20%) Palm (20%) Traffic Light (20%)	Bicycle (20%) Bridge (20%) Bus (20%) Car (20%) Chimney (20%) Crosswalk (20%) Hydrant (20%) Motorcycle (20%) Palm (20%) Traffic Light (20%)	Bicycle (20%) Bridge (20%) Bus (20%) Car (20%) Chimney (20%) Crosswalk (20%) Hydrant (20%) Motorcycle (20%) Palm (20%) Traffic Light (20%)
---	---	---	---	---

Test Data

- Delayed delivery 
 - Test data will be made available at the end of the semester.
- Test data
 - 10 images per class
 - Total 100 images

Evaluation

- Confusion matrix

Total = TP + TN + FP + FN		Predicted Condition	
		Positive	Negative
Actual Condition	Positive	True Positive (TP)	False Negative (FN)
	Negative	False Positive (FP)	True Negative (TN)

- TP: You predicted positive and it's true.
- TN: You predicted negative and it's true.
- FP: You predicted positive and it's false.
- FN: You predicted negative and it's false.

Evaluation

- Accuracy

$$ACC = \frac{TP + TN}{TP + TN + FP + FN}$$

- Precision

$$Precision = \frac{TP}{TP + FP}$$

- Recall (Sensitivity)

$$Recall = \frac{TP}{TP + FN}$$

- F1 score (Harmonic mean of precision and recall)

$$\frac{1}{F_1} = \left(\frac{1}{precision} + \frac{1}{recall} \right) / 2$$

$$F_1 = 2 \times \frac{Precision \times Recall}{Precision + Recall} = \frac{2TP}{2TP + FP + FN}$$

Evaluation

- Confusion matrix

Total = TP + TN + FP + FN		Predicted Condition		
		Positive	Negative	
Actual Condition	Positive	True Positive (TP)	False Negative (FN)	Recall $\frac{TP}{TP + FN}$
	Negative	False Positive (FP)	True Negative (TN)	
		Precision $\frac{TP}{TP + FP}$		Accuracy $\frac{TP + TN}{TP + TN + FP + FN}$

Evaluation

- Confusion matrix for Multi-class

		Predicted Condition			
		Bicycle	Bridge	...	Traffic Light
Actual Condition	Bicycle	578	22	...	42
	Bridge	34	363	...	93

	Traffic Light	50	87	...	447

Image Matching System

Image dataset

Preprocessing

- Point processing
 - Gray scale / HSI
 - Contrast stretching
- Area processing
 - Noise filtering
 - Edge
 - Sharpening
 - Morphological
- Deep Learning

Feature extraction

- Color
 - Color histogram
- Texture
 - LBP
 - GLCM
 - Law's texture
- Shape
 - Harris corner
 - SIFT
 - HoG
- Deep Learning

Classification

- Similarity
 - Distance
 - Cosine similarity
- ML classifier
 - KNN
 - SVM
 -
- Deep Learning

Preprocessing


- Point processing
 - HIS
 - gray scale
 - contrast stretching (histogram equalization)
- Area processing
 - noise filtering (mean / gaussian / median)
 - edge (previtt / sobel / canny)
 - sharpening (high-boost filtering)
 - morphological operator (open / close)

Feature Extraction

- Color
 - color / gray scale histogram (3x256-d / 256-d or n-d)
- Texture
 - LBP histogram (256-d or n-d)
 - GLCM (6-d)
 - maximum probability, moments, contrast, homogeneity, entropy, correlation
 - Law's texture (9-d)
 - E5E5, S5S5, R5R5, E5L5, S5L5, R5L5, S5E5, R5E5, R5S5
- Shape
 - Harris
 - SIFT (128-d)
 - HOG

Dimensionality Reduction

- K-means for dimension reduction
 - n-dim \rightarrow k-dim
 - 1. Apply the K-means algorithm
 - 2. Calculate the distance of each data point from each cluster center
 - 3. We got k-dim features
 - Distance of point from cluster 1
 - Distance of point from cluster 2
 - ...
 - Distance of point from cluster k



Similarity

- Distance


$$P = [p_1, p_2, \dots, p_n], \quad Q = [q_1, q_2, \dots, q_n]$$

- Manhattan distance (L1 norm)

$$d(P, Q) = \sum_{i=1}^n (|p_i - q_i|) = |p_1 - q_1| + \dots + |p_n - q_n|$$

- Euclidean distance (L2 norm)

$$d(P, Q) = \left(\sum_{i=1}^n (|p_i - q_i|^2) \right)^{1/2} = \sqrt{|p_1 - q_1|^2 + \dots + |p_n - q_n|^2}$$




Similarity

- Distance

$$P = [p_1, p_2, \dots, p_n], \quad Q = [q_1, q_2, \dots, q_n]$$

- Mahalanobis Distance

$$d(P, Q) = \sqrt{(P - Q)\Sigma^{-1}(P - Q)^T}$$
$$\Sigma = \frac{1}{n} X^T X$$




Similarity

- Cosine Similarity

$$P = [p_1, p_2, \dots, p_n], \quad Q = [q_1, q_2, \dots, q_n]$$

$$\text{sim}(P, Q) = \cos(\theta) = \frac{P \cdot Q}{\|P\| \|Q\|}$$



Similarity

- Extract feature from test image
- Find the most similar feature from train data
 1. Bus
 2. Car
 3. Car
 4. Bus
 5. Bus
 6. Bus
- Top-1 class: Bus, Top-3 class: Car, Top-6: Bus



Test image

K-Nearest Neighbors (KNN)

- Lazy model
 - Non-parametric supervised learning
 - it is helpful to choose k to be an odd number
- Find the optimal parameter k using train data and validation data




Image Matching System

Image dataset

Preprocessing

- Point processing
 - Gray scale / HSI
 - Contrast stretching
- Area processing
 - Noise filtering
 - Edge
 - Sharpening
 - Morphological
- Deep Learning

Feature extraction

- Color
 - Color histogram
- Texture
 - LBP
 - GLCM
 - Law's texture
- Shape
 - Harris corner
 - SIFT
 - HoG
- Deep Learning

Classification

- Similarity
 - Distance
 - Cosine similarity
- ML classifier
 - KNN
 - SVM
 -
- Deep Learning