

Component Structure & Naming Guide

Salon Shizuka · React + TypeScript

Last updated: June 2026

Core Rule

Number sections. Don't number sub-components.

```
01.HeroSection/           ← numbered  (page order)
  HeroSection.tsx
  components/
    HeroHeadline.tsx      ← not numbered
    HeroCta.tsx           ← not numbered
```

Rationale

Numbering encodes **page order** — information that is stable and genuinely useful. Sub-component numbering encodes insertion order, which changes constantly. Every new sub-component shifts the sequence, causing rename churn, noisy git history, and broken imports across the codebase.

Top-Level Section Order

```
src/components/organisms/
├── 01.HeroSection/
├── 02.ConceptSection/
├── 03.GallerySlider/
├── 04.OwnerSection/
├── 05.StyleGuideTeaser/
├── 06.MenuSection/
├── 07.VoiceSection/
├── 08.NewsletterBanner/
├── 09.ReservationForm/
├── 10.MapHours/
└── 11.Footer/
```

The number at the section level gives an immediate visual map of the page from top to bottom. Renumbering is rare — sections move far less often than sub-components are added.

Inside Each Section

Sub-components are **not numbered**. They are named descriptively.

```
06.MenuSection/  
├─ MenuSection.tsx  
├─ MenuSection.module.scss  
│  
├─ components/  
│   ├─ MenuHeader.tsx  
│   ├─ MenuTabs.tsx  
│   ├─ CategoryList.tsx  
│   ├─ CategoryCard.tsx  
│   ├─ MenuList.tsx  
│   ├─ FootNotes.tsx  
│   └─ index.ts          ← barrel export  
│  
├─ hooks/  
│   ├─ useMenuTabs.ts  
│   └─ useMenuColumns.ts  
│  
├─ utils/  
│   └─ formatPrice.ts  
│  
├─ types.ts  
└─ index.ts
```

`MenuSection.tsx` is the **composition root** — it imports from `./components` and assembles the section. No business logic, no formatting, no data mapping lives here.

tsx

```
// MenuSection.tsx – composition only
import { MenuHeader, MenuTabs, MenuList, FootNotes } from './components';

export default function MenuSection() {
  return (
    <Section id="menu">
      <Container>
        <Stack gap="xl">
          <MenuHeader />
          <MenuTabs />
          <MenuList />
          <FootNotes />
        </Stack>
      </Container>
    </Section>
  );
}
```

Barrel Export Pattern

Every `components/index.ts` re-exports its siblings:

```
ts

// 06.MenuSection/components/index.ts
export { MenuHeader }    from './MenuHeader';
export { MenuTabs }      from './MenuTabs';
export { CategoryList }  from './CategoryList';
export { CategoryCard }  from './CategoryCard';
export { MenuList }       from './MenuList';
export { FootNotes }     from './FootNotes';
```

The parent imports cleanly:

```
tsx

import { MenuHeader, MenuTabs, MenuList, FootNotes } from './components';
```

Why Sub-Component Numbering Fails

Today

```
01.MenuHeader
```

```
02.MenuTabs
03.CategoryList
04.CategoryCard
05.MenuList
06.FootNotes
```

After adding one component mid-sequence

```
01.MenuHeader
02.MenuHeroBanner    ← new
03.MenuTabs          ← renamed
04.CategoryList       ← renamed
05.CategoryCard       ← renamed
06.MenuList           ← renamed
07.FootNotes          ← renamed
```

Every rename is a file move, an import update, and a git diff line. Multiply by 10+ sections and this becomes a real maintenance cost.

Atomic Design Layer Numbering (Exception)

Numbering top-level *category folders* is acceptable because categories rarely change:

```
src/components/
├── 01.primitives/
├── 02.atoms/
├── 03.molecules/
├── 04.organisms/
└── 05.templates/
```

Here the number acts as a **category rank**, not an insertion sequence. The distinction: if you could not imagine ever renumbering it, the number is probably encoding something stable and real.

Quick Reference

Level	Number?	Example
Page section	✅ Yes	06.MenuSection/
Atomic category	✅ Yes	03.molecules/
Sub-component	❌ No	MenuHeader.tsx

Level	Number?	Example
Hook	✗ No	useMenuTabs.ts
Util	✗ No	formatPrice.ts

Complete Section Template

```
NN.SectionName/
├─ SectionName.tsx           ← composition root
├─ SectionName.module.scss   ← section-level styles only
|
├─ components/
|   ├── SubComponentA.tsx
|   ├── SubComponentB.tsx
|   ├── SubComponentC.tsx
|   └─ index.ts              ← barrel export
|
├─ hooks/
|   └─ useSectionLogic.ts
|
├─ utils/
|   └─ helperFn.ts
|
├─ types.ts
└─ index.ts                  ← re-exports SectionName as default
```

This guide governs component naming and folder structure for Salon Shizuka. Update here when conventions change — do not maintain parallel notes.