

Platform — Spark, Bud, and UNIBUD

One combined reference document containing all three layers, in dependency order: **Spark** (frozen intelligence engine) -> **Bud** (frozen companion layer) -> **UNIBUD** (dashboard, the Assignments vertical slice, and the v1 design system foundation under `unibud/design/` — tokens, motion presets, accessibility checking, Bud voice/presence infrastructure, and Spark presence reporting).

This file is for reading/reference. It is not directly compilable — each `##` heading below gives the real file path; recreate that folder structure to actually build the project.

Contents

1. Spark — Universal Intelligence System
 2. Bud — Reusable Companion Layer
 3. UNIBUD — Dashboard, Assignments, Design System
-

Spark — Universal Intelligence System

`README.md`

```
# Spark — Universal Intelligence System
```

```
Spark is a standalone, product-agnostic intelligence platform. It is not a chatbot, not a UI, and not tied to any single product. Products (Bud, a future Realm Assistant, a future Orbit Assistant, etc.) consume Spark's intelligence through one stable SDK boundary while keeping their own personality and purpose.
```

```
```ts
```

```
import { createSpark } from "@lib/spark";
```

```
const spark = createSpark();
```

```
await spark.initialize();
```

```
spark.identity.createContext({ userId: "u1", sessionId: "s1", product: "bud" });
```

```
const results = await spark.search.search("refund policy");
```

```
const plan = spark.planning.createPlan("Answer the user's question", ["Search knowledge", "Draft reply
```

Consumers should only ever `import { ... } from "@lib/spark"`. Nothing under `spark/core/*`, `spark/memory/*`, `spark/intelligence/*`, etc. is a supported import path — those are internal and may change.

## Status

This is **Phase 1**: architecture, interfaces, and local (offline, no API key, no network call) implementations for every module. Real hosted model providers (OpenAI, Anthropic, Gemini) are wired as placeholder adapters

behind the `AIProvider` interface but are not yet implemented — Spark runs entirely on the built-in `MockProvider` until you register a real one.

Verified in this repo:

- `npm run typecheck` — passes with strict TypeScript
- `npm run smoke-test` — exercises all 18 services end to end

## Architecture

spark/	
container.ts	DI container (per-instance, lazy singletons)
events.ts	Internal event bus (memory.updated, search.completed, ...)
middleware.ts	Middleware pipeline (logging, auth, cache, rate-limit)
plugins.ts	Plugin registration (extend Spark without modifying core)
manifest.ts	Static metadata (version, capabilities)
types.ts	Health/metrics types
index.ts	Public SDK — the ONLY supported import path
core/	
identity/	User, session, product, locale, timezone, device context
reasoning/	Analysis and decisions, with explainable steps
planning/	Goals, task sequencing, dependency-aware plans
memory/	Short-term, long-term, semantic, episodic, workspace
context/	Session/environment awareness (separate from identity)
knowledge/	Document store + naive relevance query (swap for a real knowledge graph / embeddings store later)
intelligence/	
search/	Depends only on Knowledge (Search -> Knowledge)
recommendations/	Tag-overlap scoring
organization/	Grouping / sorting
personalization/	Per-user preference store
writing/	Delegates to AIProvider
translation/	Delegates to AIProvider
summaries/	Deterministic extractive summarizer
trust/	
privacy/	PII detection + redaction (regex-based)
security/	Heuristic injection/scam-pattern scanner
automation/	Named task registration + execution + history
learning/	Feedback capture + aggregate scoring
providers/	
types.ts	AIProvider interface — the ONLY thing services call
registry.ts	Registration, default selection, availability fallback
mock.ts	Default provider — deterministic, offline, always available
openai.ts / anthropic.ts /	Placeholder adapters. No SDK dependency, no network
gemini.ts / local.ts	calls. Implement complete() when ready to go live.

## Dependency direction

Services depend downward and never sideways in a way that would create cycles:

```
Search -> Knowledge
Writing / Translation / Reasoning -> ProviderRegistry (AIProvider interface)
```

Spark never imports any product (Bud, UNIBUD, My Realm, Orbit). Products only ever import `@/lib/spark`.

## Lifecycle

```
await spark.initialize(); // resolves every registered service once, eagerly
await spark.reset(); // clears the container and re-registers core services
await spark.shutdown(); // clears event listeners and middleware
```

## Introspection

```
spark.version(); // "0.1.0"
spark.modules(); // registered service tokens
spark.capabilities(); // ["identity", "reasoning", ..., "learning"]
spark.manifest(); // name, version, build, capabilities, modules, providers
spark.health(); // status, loaded modules, provider availability, diagnostics, warnings
spark.metrics(); // memory size, events emitted (extend as real counters are added)
```

## Adding a real provider

```
import { createSpark, OpenAIProvider } from "@/lib/spark";

const spark = createSpark();
spark.registerProvider(new OpenAIProvider(process.env.OPENAI_API_KEY), /* makeDefault */ true);
```

Until `OpenAIProvider.complete()` is implemented, `ProviderRegistry.resolve()` will keep silently falling back to `MockProvider` when the registered provider reports `isAvailable() === false` — Spark never throws just because a real provider isn't configured yet.

## Extending Spark

- **Middleware** — `spark.use(loggingMiddleware)` or write your own `(ctx, next) => Promise<T>` function for auth, caching, rate limiting.
- **Plugins** — `spark.registerPlugin({ name, install(ctx) { ... } })` to add services, providers, or middleware without touching Spark's core.
- **Events** — `spark.events.on("search.completed", handler)`. Note: no service currently emits domain events yet; wire `events.emit(...)` calls into individual services as needed.

## Explicitly out of scope for this phase

- No hosted model calls (all providers besides Mock throw until implemented)
- No persistence (everything is in-memory and resets on process restart)
- No product integration (Bud/UNIBUD/My Realm/Orbit are not referenced anywhere)

- No UI of any kind

```
`package.json`
```

```
``json
{
 "name": "@ecosystem/platform",
 "version": "0.1.0",
 "description": "Spark (intelligence engine), Bud (companion layer), and UNIBUD (student dashboard pr",
 "license": "UNLICENSED",
 "main": "dist/src/lib/spark/index.js",
 "types": "dist/src/lib/spark/index.d.ts",
 "exports": {
 ".": {
 "types": "./dist/src/lib/spark/index.d.ts",
 "default": "./dist/src/lib/spark/index.js"
 },
 "./bud": {
 "types": "./dist/src/lib/bud/index.d.ts",
 "default": "./dist/src/lib/bud/index.js"
 },
 "./unibud": {
 "types": "./dist/src/lib/unibud/index.d.ts",
 "default": "./dist/src/lib/unibud/index.js"
 }
 },
 "files": [
 "dist/src/lib",
 "README.md"
],
 "scripts": {
 "typecheck": "tsc --noEmit",
 "build": "tsc",
 "prepublishOnly": "npm run build",
 "smoke-test": "ts-node scripts/smoke-test.ts",
 "bud-verify": "ts-node scripts/bud-verify.ts",
 "unibud-verify": "ts-node scripts/unibud-verify.ts",
 "container-verify": "ts-node scripts/container-verify.ts"
 },
 "publishConfig": {
 "access": "restricted"
 },
 "devDependencies": {
 "typescript": "^5.5.4",
 "ts-node": "^10.9.2",
 "@types/node": "^20.14.0"
 }
}
```

**tsconfig.json**

```
{
 "compilerOptions": {
```

```

 "target": "ES2020",
 "module": "CommonJS",
 "moduleResolution": "node",
 "ignoreDeprecations": "6.0",
 "lib": ["ES2020", "DOM"],
 "declaration": true,
 "outDir": "dist",
 "strict": true,
 "esModuleInterop": true,
 "skipLibCheck": true,
 "forceConsistentCasingInFileNames": true,
 "resolveJsonModule": true,
 "baseUrl": ".",
 "paths": {
 "@lib/spark": ["src/lib/spark/index.ts"],
 "@lib/spark/*": ["src/lib/spark/*"]
 }
 },
 "include": ["src/**/*.ts", "scripts/**/*.ts"]
}

```

#### **scripts/smoke-test.ts**

```

import { createSpark, loggingMiddleware } from "../src/lib/spark";

async function main() {
 const spark = createSpark();
 spark.use(loggingMiddleware);
 await spark.initialize();

 console.log("=== manifest ===");
 console.log(JSON.stringify(spark.manifest(), null, 2));

 console.log("\n=== capabilities ===");
 console.log(spark.capabilities());

 // Identity
 const identity = spark.identity.createContext({
 userId: "user_1",
 sessionId: "session_1",
 product: "smoke-test",
 });
 console.log("\n=== identity ===", identity);

 // Memory
 spark.memory.remember({
 kind: "short_term",
 content: "The user asked about Spark's architecture.",
 sessionId: "session_1",
 userId: "user_1",
 });
 console.log("\n=== memory recall ===", spark.memory.recall({ sessionId: "session_1" }));

 // Context
 spark.context.setAttribute("session_1", "currentScreen", "dashboard");

```

```

console.log("\n=== context snapshot ===", spark.context.getSnapshot("session_1", "smoke-test"));

// Knowledge + Search
spark.knowledge.addDocument({
 title: "Spark Overview",
 content: "Spark is the Universal Intelligence System that powers products across the ecosystem.",
 tags: ["spark", "architecture"],
});
const searchResults = await spark.search.search("universal intelligence");
console.log("\n=== search ===", searchResults);

// Reasoning
const reasoning = await spark.reasoning.analyze({
 question: "Should Bud call Spark or an AI provider directly?",
 facts: ["Bud must not contain intelligence or business logic."],
});
console.log("\n=== reasoning ===", reasoning);

// Planning
const plan = spark.planning.createPlan("Ship Spark v1", [
 "Define public API",
 "Implement local services",
 "Run production review",
]);
console.log("\n=== planning ===", plan, spark.planning.nextTask(plan.id));

// Recommendations
console.log(
 "\n=== recommendations ===",
 spark.recommendations.recommend({
 candidateItems: [
 { id: "a", tags: ["spark"] },
 { id: "b", tags: ["unrelated"] },
],
 basedOnTags: ["spark"],
 })
);

// Organization
console.log(
 "\n=== organization ===",
 spark.organization.groupByTag([
 { id: "1", label: "doc a", tags: ["spark"] },
 { id: "2", label: "doc b", tags: ["bud"] },
])
);

// Personalization
spark.personalization.setPreference("user_1", "theme", "dark");
console.log("\n=== personalization ===", spark.personalization.getAllPreferences("user_1"));

// Writing / Translation / Summaries (mock provider)
console.log("\n=== writing ===", await spark.writing.draft({ prompt: "Say hello." }));
console.log(
 "\n=== translation ===",
 await spark.translation.translate({ text: "Hello", targetLocale: "es-ES" })
);

```

```

console.log(
 "\n=== summaries ===",
 spark.summaries.summarize({
 text: "Spark is the Universal Intelligence System. It powers Bud, Realm Assistant, and Orbit Ass
 maxSentences: 1,
 })
);

// Privacy / Security
console.log(
 "\n=== privacy scan ===",
 spark.privacy.scanForPii("Contact me at test@example.com")
);
console.log(
 "\n=== security check ===",
 spark.security.checkInput("Please verify your password immediately")
);

// Automation
spark.automation.registerTask("ping", async () => "pong");
console.log("\n=== automation ===", await spark.automation.run("ping"));

// Learning
spark.learning.recordFeedback({ subject: "writing", rating: "positive" });
console.log("\n=== learning score ===", spark.learning.score("writing"));

// Health
console.log("\n=== health ===", spark.health());

await spark.shutdown();
console.log("\nSmoke test completed successfully.");
}

main().catch((err) => {
 console.error("Smoke test failed:", err);
 throw err;
});

```

#### **scripts/container-verify.ts**

```

import { createSpark } from "../src/lib/spark";
import { Container } from "../src/lib/spark/container";
import { ServiceNotRegisteredError } from "../src/lib/spark/errors";

async function main() {
 const spark = createSpark();
 console.log("modules():", spark.modules());
 console.log("manifest().registeredModules:", spark.manifest().registeredModules);

 // registerValue + missing-token error behavior, isolated from Spark's own container
 const c = new Container();
 const sentinel = { ok: true };
 const token = Symbol("test.value");
 c.registerValue(token, sentinel);
 const resolved = c.resolve<typeof sentinel>(token);

```

```

 if (resolved !== sentinel) throw new Error("registerValue did not preserve identity");
 console.log("registerValue OK, resolved instance === original:", resolved === sentinel);

 try {
 c.resolve(Symbol("never.registered"));
 throw new Error("expected ServiceNotRegisteredError to be thrown");
 } catch (err) {
 if (!(err instanceof ServiceNotRegisteredError)) {
 throw new Error(`expected ServiceNotRegisteredError, got ${err}`);
 }
 console.log("ServiceNotRegisteredError thrown correctly:", err.message);
 }

 // Per-instance isolation: two Spark instances never share a container
 const sparkA = createSpark();
 const sparkB = createSpark();
 sparkA.memory.remember({ kind: "short_term", content: "only in A" });
 const crossLeak = sparkB.memory.recall({ text: "only in A" });
 if (crossLeak.length !== 0) throw new Error("Spark instances are leaking state!");
 console.log("Per-instance isolation OK: sparkB sees", crossLeak.length, "matching records");

 console.log("\nContainer verification completed successfully.");
}

main().catch((err) => {
 console.error("Container verification failed:", err);
 throw err;
});

```

#### **src/lib/spark/automation/interface.ts**

```

export interface AutomationTask {
 id: string;
 name: string;
 status: "pending" | "running" | "completed" | "failed";
 result?: unknown;
 error?: string;
}

export type AutomationHandler = (input?: unknown) => Promise<unknown>;

export interface AutomationService {
 registerTask(name: string, handler: AutomationHandler): void;
 run(name: string, input?: unknown): Promise<AutomationTask>;
 history(limit?: number): AutomationTask[];
}

```

#### **src/lib/spark/automation/local.ts**

```

import type {
 AutomationHandler,
 AutomationService,

```



```

 AutomationTask,
} from "../interface";

/**
 * In-process workflow/task runner. Registers named handlers and
 * executes them on demand, tracking status/result/error for diagnostics.
 * No external orchestration system is required at this stage.
 */
export class LocalAutomationService implements AutomationService {
 private handlers = new Map<string, AutomationHandler>();
 private tasks: AutomationTask[] = [];
 private counter = 0;

 registerTask(name: string, handler: AutomationHandler): void {
 this.handlers.set(name, handler);
 }

 async run(name: string, input?: unknown): Promise<AutomationTask> {
 const handler = this.handlers.get(name);
 const task: AutomationTask = {
 id: `task_${++this.counter}_${Date.now()}`,
 name,
 status: "pending",
 };
 this.tasks.push(task);

 if (!handler) {
 task.status = "failed";
 task.error = `No automation task registered under name "${name}"`;
 return task;
 }

 task.status = "running";
 try {
 task.result = await handler(input);
 task.status = "completed";
 } catch (err) {
 task.status = "failed";
 task.error = err instanceof Error ? err.message : String(err);
 }
 return task;
 }

 history(limit = 50): AutomationTask[] {
 return this.tasks.slice(-limit);
 }
}

```

#### **src/lib/spark/container.ts**

```

/**
 * Minimal dependency-injection container.
 *
 * Services are registered as factories and resolved lazily on first
 * use, then cached as singletons for the lifetime of the Spark instance

```

```

* that owns this container. Each `createSpark()` call constructs its
* own Container, so multiple Spark instances never share state - there
* is no module-level/global registry anywhere in this file.
*
* Canonical tokens live in ./tokens.ts - this file only consumes them.
*/

```

```

import type { Token } from "./tokens";
import { tokenLabel } from "./tokens";
import { ServiceNotRegisteredError } from "./errors";

```

```

type Factory<T> = (container: Container) => T;

```

```

export class Container {
 private factories = new Map<Token, Factory<unknown>>();
 private instances = new Map<Token, unknown>();

 /** Register a lazy factory. Only invoked on first resolve(). */
 register<T>(token: Token, factory: Factory<T>): void {
 this.factories.set(token, factory as Factory<unknown>);
 // Invalidate any cached instance so re-registration is respected.
 this.instances.delete(token);
 }

 /**
 * Register an already-constructed value directly (e.g. a shared
 * Logger or ProviderRegistry instance) without wrapping it in a
 * factory function. Still resolved lazily/cached like any other
 * token - resolve() doesn't distinguish how a token was registered.
 */
 registerValue<T>(token: Token, value: T): void {
 this.register(token, () => value);
 }

 has(token: Token): boolean {
 return this.factories.has(token);
 }

 resolve<T>(token: Token): T {
 if (this.instances.has(token)) {
 return this.instances.get(token) as T;
 }
 const factory = this.factories.get(token);
 if (!factory) {
 throw new ServiceNotRegisteredError(tokenLabel(token));
 }
 const instance = factory(this);
 this.instances.set(token, instance);
 return instance as T;
 }

 /** Tokens that currently have a registered factory. */
 registeredTokens(): Token[] {
 return Array.from(this.factories.keys());
 }

 /** Tokens that have actually been instantiated (lazy resolution check). */

```

```

 resolvedTokens(): Token[] {
 return Array.from(this.instances.keys());
 }

 reset(): void {
 this.instances.clear();
 }
}

```

#### **src/lib/spark/context/interface.ts**

```

export interface EnvironmentContext {
 platform?: string;
 appVersion?: string;
 networkQuality?: "offline" | "poor" | "good" | "excellent";
}

export interface SessionContextSnapshot {
 sessionId: string;
 product: string;
 environment?: EnvironmentContext;
 attributes: Record<string, unknown>;
 updatedAt: string;
}

export interface ContextService {
 setEnvironment(sessionId: string, env: EnvironmentContext): void;
 setAttribute(sessionId: string, key: string, value: unknown): void;
 getSnapshot(sessionId: string, product: string): SessionContextSnapshot;
 clear(sessionId: string): boolean;
}

```

#### **src/lib/spark/context/local.ts**

```

import type {
 ContextService,
 EnvironmentContext,
 SessionContextSnapshot,
} from "../interface";

/**
 * Tracks per-session environmental/product awareness (in addition to
 * the user/session identity owned by the Identity service). Kept
 * separate from Identity because context changes far more often
 * (network quality, current screen, ephemeral attributes) than
 * identity does.
 */
export class LocalContextService implements ContextService {
 private environments = new Map<string, EnvironmentContext>();
 private attributes = new Map<string, Record<string, unknown>>();

 setEnvironment(sessionId: string, env: EnvironmentContext): void {

```

```

 this.environments.set(sessionId, env);
 }

 setAttribute(sessionId: string, key: string, value: unknown): void {
 const existing = this.attributes.get(sessionId) ?? {};
 existing[key] = value;
 this.attributes.set(sessionId, existing);
 }

 getSnapshot(sessionId: string, product: string): SessionContextSnapshot {
 return {
 sessionId,
 product,
 environment: this.environments.get(sessionId),
 attributes: this.attributes.get(sessionId) ?? {},
 updatedAt: new Date().toISOString(),
 };
 }

 clear(sessionId: string): boolean {
 const hadEnv = this.environments.delete(sessionId);
 const hadAttrs = this.attributes.delete(sessionId);
 return hadEnv || hadAttrs;
 }
}

```

#### **src/lib/spark/core/identity/interface.ts**

```

export interface DeviceContext {
 type?: "desktop" | "mobile" | "tablet" | "server" | "unknown";
 os?: string;
}

export interface IdentityContext {
 userId: string;
 sessionId: string;
 product: string;
 locale: string;
 timezone: string;
 device?: DeviceContext;
 createdAt: string;
}

export interface IdentityService {
 /** Create (or overwrite) the identity context for a session. */
 createContext(input: {
 userId: string;
 sessionId: string;
 product: string;
 locale?: string;
 timezone?: string;
 device?: DeviceContext;
 }): IdentityContext;

 getContext(sessionId: string): IdentityContext | undefined;
}

```

```

updateContext(
 sessionId: string,
 patch: Partial<Omit<IdentityContext, "sessionId" | "createdAt">>
): IdentityContext | undefined;

clearContext(sessionId: string): boolean;

/** Number of active identity contexts currently tracked. */
size(): number;
}

```

#### **src/lib/spark/core/identity/local.ts**

```

import type { IdentityContext, IdentityService, DeviceContext } from "../interface";

/**
 * In-memory identity service. Provides user/session/product/locale/
 * timezone/device context for all other Spark services. No persistence
 * or network calls – state lives for the lifetime of the Spark instance.
 */
export class LocalIdentityService implements IdentityService {
 private contexts = new Map<string, IdentityContext>();

 createContext(input: {
 userId: string;
 sessionId: string;
 product: string;
 locale?: string;
 timezone?: string;
 device?: DeviceContext;
 }): IdentityContext {
 const context: IdentityContext = {
 userId: input.userId,
 sessionId: input.sessionId,
 product: input.product,
 locale: input.locale ?? "en-US",
 timezone: input.timezone ?? "UTC",
 device: input.device,
 createdAt: new Date().toISOString(),
 };
 this.contexts.set(input.sessionId, context);
 return context;
 }

 getContext(sessionId: string): IdentityContext | undefined {
 return this.contexts.get(sessionId);
 }

 updateContext(
 sessionId: string,
 patch: Partial<Omit<IdentityContext, "sessionId" | "createdAt">>
): IdentityContext | undefined {
 const existing = this.contexts.get(sessionId);
 if (!existing) return undefined;

```

```

 const updated = { ...existing, ...patch };
 this.contexts.set(sessionId, updated);
 return updated;
 }

 clearContext(sessionId: string): boolean {
 return this.contexts.delete(sessionId);
 }

 size(): number {
 return this.contexts.size;
 }
}

```

#### **src/lib/spark/core/planning/interface.ts**

```

export interface PlanTask {
 id: string;
 title: string;
 done: boolean;
 order: number;
 dependsOn?: string[];
}

export interface Plan {
 id: string;
 goal: string;
 tasks: PlanTask[];
 createdAt: string;
}

export interface PlanningService {
 createPlan(goal: string, taskTitles: string[]): Plan;
 getPlan(planId: string): Plan | undefined;
 completeTask(planId: string, taskId: string): Plan | undefined;
 nextTask(planId: string): PlanTask | undefined;
}

```

#### **src/lib/spark/core/planning/local.ts**

```

import type { Plan, PlanTask, PlanningService } from "../interface";

/**
 * In-memory planning service. Handles goal decomposition into ordered,
 * dependency-aware tasks. No AI provider is required for the core
 * sequencing logic; reasoning-assisted decomposition can be layered on
 * top later via the ReasoningService.
 */
export class LocalPlanningService implements PlanningService {
 private plans = new Map<string, Plan>();
 private counter = 0;
}

```

```

createPlan(goal: string, taskTitles: string[]): Plan {
 const id = `plan_${++this.counter}_${Date.now()}`;
 const tasks: PlanTask[] = taskTitles.map((title, index) => ({
 id: `${id}_task_${index}`,
 title,
 done: false,
 order: index,
 dependsOn: index > 0 ? [`${id}_task_${index - 1}`] : [],
 }));
 const plan: Plan = { id, goal, tasks, createdAt: new Date().toISOString() };
 this.plans.set(id, plan);
 return plan;
}

getPlan(planId: string): Plan | undefined {
 return this.plans.get(planId);
}

completeTask(planId: string, taskId: string): Plan | undefined {
 const plan = this.plans.get(planId);
 if (!plan) return undefined;
 const task = plan.tasks.find((t) => t.id === taskId);
 if (task) task.done = true;
 return plan;
}

nextTask(planId: string): PlanTask | undefined {
 const plan = this.plans.get(planId);
 if (!plan) return undefined;
 return plan.tasks
 .filter((t) => !t.done)
 .sort((a, b) => a.order - b.order)
 .find((t) =>
 (t.dependsOn ?? []).every(
 (depId) => plan.tasks.find((d) => d.id === depId)?.done
)
);
}
}

```

#### **src/lib/spark/core/reasoning/interface.ts**

```

export interface ReasoningInput {
 question: string;
 facts?: string[];
 context?: Record<string, unknown>;
}

export interface ReasoningStep {
 step: number;
 description: string;
}

export interface ReasoningResult {
 answer: string;
}

```

```

 confidence: number; // 0..1
 steps: ReasoningStep[];
 usedProvider: string;
}

export interface ReasoningService {
 /** Analyze input and produce a decision/answer with explainable steps. */
 analyze(input: ReasoningInput): Promise<ReasoningResult>;
}

```

#### **src/lib/spark/core/reasoning/local.ts**

```

import type {
 ReasoningInput,
 ReasoningResult,
 ReasoningService,
} from "../interface";
import type { ProviderRegistry } from "../../providers/registry";

/**
 * Deterministic local reasoning implementation. Produces a transparent,
 * step-by-step trace without requiring a hosted model. When a real
 * provider becomes available, this class can delegate to it through
 * ProviderRegistry without callers changing anything.
 */
export class LocalReasoningService implements ReasoningService {
 constructor(private readonly providers: ProviderRegistry) {}

 async analyze(input: ReasoningInput): Promise<ReasoningResult> {
 const provider = this.providers.resolve();
 const facts = input.facts ?? [];

 const steps = [
 {
 step: 1,
 description: `Parsed question: "${input.question}"`,
 },
 {
 step: 2,
 description: facts.length
 ? `Considered ${facts.length} supplied fact(s).`
 : "No supporting facts were supplied.",
 },
 {
 step: 3,
 description: `Delegated synthesis to provider "${provider.name}"`,
 },
];

 const completion = await provider.complete({
 messages: [
 { role: "system", content: "You are Spark's reasoning module." },
 {
 role: "user",
 content: `Question: ${input.question}\nFacts: ${facts.join("; ")}`,
 },
],
 });
 }
}

```



```

 return {
 answer: completion.text,
 confidence: facts.length > 0 ? 0.6 : 0.35,
 steps,
 usedProvider: provider.name,
 };
}
}

```

# **src/lib/spark/errors.ts**

```

/**
 * Spark's error hierarchy. Internal code should throw these instead of
 * generic `Error` so callers (and Kernel diagnostics) can distinguish
 * failure classes reliably.
 */

export class SparkError extends Error {
 constructor(message: string) {
 super(message);
 this.name = new.target.name;
 Object.setPrototypeOf(this, new.target.prototype);
 }
}

/** Thrown when Container.resolve() is called for an unregistered token. */
export class ServiceNotRegisteredError extends SparkError {
 constructor(public readonly tokenLabel: string) {
 super(`No service registered for token "${tokenLabel}".`);
 }
}

/** Thrown when a provider is looked up by name but was never registered. */
export class ProviderNotRegisteredError extends SparkError {
 constructor(public readonly providerName: string) {
 super(`Provider "${providerName}" is not registered.`);
 }
}

/** Thrown when a provider is resolved but cannot currently be used (e.g. no credentials). */
export class ProviderUnavailableError extends SparkError {
 constructor(public readonly providerName: string, reason?: string) {
 super(
 `Provider "${providerName}" is not available${reason ? `: ${reason}` : ""}`
);
 }
}

/** Thrown by services when given malformed input. */
export class ValidationError extends SparkError {
 constructor(message: string) {
 super(message);
 }
}

```

```

/** Thrown when an operation requires Spark to be initialized first. */
export class NotInitializedError extends SparkError {
 constructor() {
 super("Spark has not been initialized. Call initialize() first.");
 }
}

/** Thrown when a plugin name is registered more than once. */
export class PluginAlreadyRegisteredError extends SparkError {
 constructor(public readonly pluginName: string) {
 super(`Plugin "${pluginName}" is already registered.`);
 }
}

```

#### **src/lib/spark/events.ts**

```

/**
 * Lightweight internal event bus.
 *
 * Modules publish events instead of calling each other directly, which
 * keeps them decoupled. External consumers (e.g. Oracle) can subscribe
 * without Spark needing to know they exist.
 *
 * Example event names: "memory.updated", "search.completed",
 * "recommendation.generated", "translation.finished".
 */

export type SparkEventName = string;

export type SparkEventHandler<TPayload = unknown> = (
 payload: TPayload
) => void;

export interface SparkEventLogEntry {
 name: SparkEventName;
 payload: unknown;
 timestamp: string;
}

export class EventBus {
 private handlers = new Map<SparkEventName, Set<SparkEventHandler>>();
 private log: SparkEventLogEntry[] = [];
 private readonly maxLog = 200;

 on<TPayload = unknown>({
 name: SparkEventName,
 handler: SparkEventHandler<TPayload>
 }): () => void {
 if (!this.handlers.has(name)) {
 this.handlers.set(name, new Set());
 }
 this.handlers.get(name)!.add(handler as SparkEventHandler);
 return () => this.off(name, handler);
 }
}

```

```

off<TPayload = unknown>(
 name: SparkEventName,
 handler: SparkEventHandler<TPayload>
): void {
 this.handlers.get(name)?.delete(handler as SparkEventHandler);
}

emit<TPayload = unknown>(name: SparkEventName, payload?: TPayload): void {
 this.log.push({
 name,
 payload,
 timestamp: new Date().toISOString(),
 });
 if (this.log.length > this.maxLog) {
 this.log.shift();
 }
 this.handlers.get(name)?.forEach((handler) => {
 try {
 handler(payload);
 } catch (err) {
 // Event handlers must never break the emitting module.
 // eslint-disable-next-line no-console
 console.error(`[spark:events] handler for "${name}" threw`, err);
 }
 });
}

recentEvents(limit = 50): SparkEventLogEntry[] {
 return this.log.slice(-limit);
}

clear(): void {
 this.handlers.clear();
 this.log = [];
}
}

```

#### **src/lib/spark/index.ts**

```

/**
 * Public Spark SDK.
 *
 * Consumers should only ever import from here:
 *
 * import { createSpark } from "@lib/spark";
 *
 * Never import from spark/core/*, spark/memory/*, etc. directly -
 * those paths are internal implementation detail and may change.
 */

import { Container } from "../container";
import { TOKENS, tokenLabel } from "../tokens";
import { EventBus } from "../events";
import { MiddlewarePipeline, type Middleware } from "../middleware";

```

```

import { PluginManager, type SparkPlugin } from "./plugins";
import { ProviderRegistry } from "./providers/registry";
import type { AIProvider } from "./providers/types";
import {
 SPARK_CAPABILITIES,
 SPARK_BUILD,
 SPARK_VERSION,
 type SparkManifest,
} from "./manifest";
import type { SparkHealthReport, SparkMetrics } from "./types";

import { LocalIdentityService } from "./core/identity/local";
import { LocalReasoningService } from "./core/reasoning/local";
import { LocalPlanningService } from "./core/planning/local";
import { InMemoryMemoryService } from "./memory/local";
import { LocalContextService } from "./context/local";
import { LocalKnowledgeService } from "./knowledge/local";
import { LocalSearchService } from "./intelligence/search/local";
import { LocalRecommendationsService } from "./intelligence/recommendations/local";
import { LocalOrganizationService } from "./intelligence/organization/local";
import { LocalPersonalizationService } from "./intelligence/personalization/local";
import { LocalWritingService } from "./intelligence/writing/local";
import { LocalTranslationService } from "./intelligence/translation/local";
import { LocalSummariesService } from "./intelligence/summaries/local";
import { LocalPrivacyService } from "./trust/privacy/local";
import { LocalSecurityService } from "./trust/security/local";
import { LocalAutomationService } from "./automation/local";
import { LocalLearningService } from "./learning/local";

import type { IdentityService } from "./core/identity/interface";
import type { ReasoningService } from "./core/reasoning/interface";
import type { PlanningService } from "./core/planning/interface";
import type { MemoryService } from "./memory/interface";
import type { ContextService } from "./context/interface";
import type { KnowledgeService } from "./knowledge/interface";
import type { SearchService } from "./intelligence/search/interface";
import type { RecommendationsService } from "./intelligence/recommendations/interface";
import type { OrganizationService } from "./intelligence/organization/interface";
import type { PersonalizationService } from "./intelligence/personalization/interface";
import type { WritingService } from "./intelligence/writing/interface";
import type { TranslationService } from "./intelligence/translation/interface";
import type { SummariesService } from "./intelligence/summaries/interface";
import type { PrivacyService } from "./trust/privacy/interface";
import type { SecurityService } from "./trust/security/interface";
import type { AutomationService } from "./automation/interface";
import type { LearningService } from "./learning/interface";

export class Spark {
 readonly events = new EventBus();
 readonly middleware = new MiddlewarePipeline();

 private readonly container = new Container();
 private readonly providerRegistry = new ProviderRegistry();
 private readonly plugins = new PluginManager();
 private readonly startedAt = Date.now();
 private initialized = false;
 private readonly warnings: string[] = [];

```

```

constructor() {
 this.registerCoreServices();
}

// -----
// Lifecycle
// -----

async initialize(): Promise<void> {
 if (this.initialized) return;
 // Eagerly resolve every registered service once so configuration
 // errors surface immediately rather than on first use.
 for (const token of this.container.registeredTokens()) {
 this.container.resolve(token);
 }
 this.initialized = true;
 this.events.emit("spark.initialized", { at: new Date().toISOString() });
}

async shutdown(): Promise<void> {
 this.events.emit("spark.shutdown", { at: new Date().toISOString() });
 this.events.clear();
 this.middleware.clear();
 this.initialized = false;
}

async reset(): Promise<void> {
 this.container.reset();
 this.registerCoreServices();
 this.initialized = false;
}

// -----
// Providers & plugins
// -----

registerProvider(provider: AIProvider, makeDefault = false): void {
 this.providerRegistry.register(provider, makeDefault);
}

registerPlugin(plugin: SparkPlugin): void {
 this.plugins.register(plugin, {
 container: this.container,
 providers: this.providerRegistry,
 middleware: this.middleware,
 events: this.events,
 });
}

use(middleware: Middleware): void {
 this.middleware.use(middleware);
}

// -----
// Introspection
// -----

```

```

version(): string {
 return SPARK_VERSION;
}

modules(): string[] {
 return this.container.registeredTokens().map(tokenLabel);
}

capabilities(): readonly string[] {
 return SPARK_CAPABILITIES;
}

manifest(): SparkManifest {
 return {
 name: "Spark",
 version: SPARK_VERSION,
 build: SPARK_BUILD,
 capabilities: SPARK_CAPABILITIES,
 registeredModules: this.container.registeredTokens().map(tokenLabel),
 providers: this.providerRegistry.list(),
 };
}

health(): SparkHealthReport {
 const diagnostics: string[] = [];
 const providers = this.providerRegistry.list();

 if (!providers.some((p) => p.available)) {
 this.warnings.push(
 "No AI provider is currently available besides the mock provider."
);
 }

 diagnostics.push(
 `${this.container.resolvedTokens().length}/${
 this.container.registeredTokens().length
 } services resolved.`
);

 const status: SparkHealthReport["status"] = this.initialized
 ? "healthy"
 : "degraded";

 return {
 status,
 initialized: this.initialized,
 loadedModules: this.container.resolvedTokens().map(tokenLabel),
 registeredProviders: providers,
 diagnostics,
 warnings: [...new Set(this.warnings)],
 uptimeMs: Date.now() - this.startedAt,
 checkedAt: new Date().toISOString(),
 };
}

metrics(): SparkMetrics {

```

```

 const events = this.events.recentEvents(500);
 return {
 requestCounts: {},
 executionTimesMs: {},
 cacheHits: 0,
 cacheMisses: 0,
 memorySize: this.memory.size(),
 eventsEmitted: events.length,
 };
}

// -----
// Service accessors - this is the actual public surface products use
// -----

get identity(): IdentityService {
 return this.container.resolve(TOKENS.Identity);
}

get reasoning(): ReasoningService {
 return this.container.resolve(TOKENS.Reasoning);
}

get planning(): PlanningService {
 return this.container.resolve(TOKENS.Planning);
}

get memory(): MemoryService {
 return this.container.resolve(TOKENS.Memory);
}

get context(): ContextService {
 return this.container.resolve(TOKENS.Context);
}

get knowledge(): KnowledgeService {
 return this.container.resolve(TOKENS.Knowledge);
}

get search(): SearchService {
 return this.container.resolve(TOKENS.Search);
}

get recommendations(): RecommendationsService {
 return this.container.resolve(TOKENS.Recommendations);
}

get organization(): OrganizationService {
 return this.container.resolve(TOKENS.Organization);
}

get personalization(): PersonalizationService {
 return this.container.resolve(TOKENS.Personalization);
}

get writing(): WritingService {
 return this.container.resolve(TOKENS.Writing);
}

```

```

}

get translation(): TranslationService {
 return this.container.resolve(TOKENS.Translation);
}

get summaries(): SummariesService {
 return this.container.resolve(TOKENS.Summaries);
}

get privacy(): PrivacyService {
 return this.container.resolve(TOKENS.Privacy);
}

get security(): SecurityService {
 return this.container.resolve(TOKENS.Security);
}

get automation(): AutomationService {
 return this.container.resolve(TOKENS.Automation);
}

get learning(): LearningService {
 return this.container.resolve(TOKENS.Learning);
}

// -----
// Internal wiring
// -----

private registerCoreServices(): void {
 this.container.registerValue(TOKENS.ProviderRegistry, this.providerRegistry);

 this.container.register(TOKENS.Identity, () => new LocalIdentityService());
 this.container.register(
 TOKENS.Reasoning,
 () => new LocalReasoningService(this.providerRegistry)
);
 this.container.register(TOKENS.Planning, () => new LocalPlanningService());
 this.container.register(TOKENS.Memory, () => new InMemoryMemoryService());
 this.container.register(TOKENS.Context, () => new LocalContextService());
 this.container.register(TOKENS.Knowledge, () => new LocalKnowledgeService());

 // Search depends on Knowledge only – Search -> Knowledge, not Memory,
 // to keep the dependency graph shallow as Spark grows.
 this.container.register(
 TOKENS.Search,
 (c) => new LocalSearchService(c.resolve(TOKENS.Knowledge))
);

 this.container.register(
 TOKENS.Recommendations,
 () => new LocalRecommendationsService()
);
 this.container.register(
 TOKENS.Organization,
 () => new LocalOrganizationService()
);
}

```



```

);
 this.container.register(
 TOKENS.Personalization,
 () => new LocalPersonalizationService()
);
 this.container.register(
 TOKENS.Writing,
 () => new LocalWritingService(this.providerRegistry)
);
 this.container.register(
 TOKENS.Translation,
 () => new LocalTranslationService(this.providerRegistry)
);
 this.container.register(TOKENS.Summaries, () => new LocalSummariesService());
 this.container.register(TOKENS.Privacy, () => new LocalPrivacyService());
 this.container.register(TOKENS.Security, () => new LocalSecurityService());
 this.container.register(TOKENS.Automation, () => new LocalAutomationService());
 this.container.register(TOKENS.Learning, () => new LocalLearningService());
}
}

/**
 * Factory for a new, fully independent Spark instance. Each call
 * produces its own container/providers/events/middleware - instances
 * never share state.
 */
export function createSpark(): Spark {
 return new Spark();
}

// Re-export types consumers are expected to use.
export type { AIProvider } from "./providers/types";
export type { SparkPlugin, SparkPluginContext } from "./plugins";
export type { Middleware } from "./middleware";
export type { SparkManifest } from "./manifest";
export type { SparkHealthReport, SparkMetrics } from "./types";
export { loggingMiddleware } from "./middleware";
export { MockProvider } from "./providers/mock";
export { OpenAIProvider } from "./providers/openai";
export { AnthropicProvider } from "./providers/anthropic";
export { GeminiProvider } from "./providers/gemini";
export { LocalModelProvider } from "./providers/local";

```

#### **src/lib/spark/intelligence/organization/interface.ts**

```

export interface OrganizableItem {
 id: string;
 label: string;
 tags?: string[];
 createdAt?: string;
}

export interface OrganizedGroup {
 key: string;
 items: OrganizableItem[];
}

```

```

}

export interface OrganizationService {
 groupByTag(items: OrganizableItem[]): OrganizedGroup[];
 sortByRecency(items: OrganizableItem[]): OrganizableItem[];
}

```

#### **src/lib/spark/intelligence/organization/local.ts**

```

import type {
 OrganizableItem,
 OrganizedGroup,
 OrganizationService,
} from "../interface";

/** Deterministic local organization logic – grouping and sorting only. */
export class LocalOrganizationService implements OrganizationService {
 groupByTag(items: OrganizableItem[]): OrganizedGroup[] {
 const groups = new Map<string, OrganizableItem[]>();
 for (const item of items) {
 const tags = item.tags?.length ? item.tags : ["untagged"];
 for (const tag of tags) {
 if (!groups.has(tag)) groups.set(tag, []);
 groups.get(tag)!.push(item);
 }
 }
 return Array.from(groups.entries()).map(([key, groupItems]) => ({
 key,
 items: groupItems,
 }));
 }

 sortByRecency(items: OrganizableItem[]): OrganizableItem[] {
 return [...items].sort((a, b) => {
 const aTime = a.createdAt ? new Date(a.createdAt).getTime() : 0;
 const bTime = b.createdAt ? new Date(b.createdAt).getTime() : 0;
 return bTime - aTime;
 });
 }
}

```

#### **src/lib/spark/intelligence/personalization/interface.ts**

```

export interface UserPreference {
 key: string;
 value: unknown;
 updatedAt: string;
}

export interface PersonalizationService {
 setPreference(userId: string, key: string, value: unknown): UserPreference;
 getPreference(userId: string, key: string): UserPreference | undefined;
}

```

```

 getAllPreferences(userId: string): UserPreference[];
}

```

#### **src/lib/spark/intelligence/personalization/local.ts**

```

import type { PersonalizationService, UserPreference } from "../interface";

/** In-memory per-user preference store. */
export class LocalPersonalizationService implements PersonalizationService {
 private preferences = new Map<string, Map<string, UserPreference>>();

 setPreference(userId: string, key: string, value: unknown): UserPreference {
 if (!this.preferences.has(userId)) {
 this.preferences.set(userId, new Map());
 }
 const pref: UserPreference = { key, value, updatedAt: new Date().toISOString() };
 this.preferences.get(userId)!.set(key, pref);
 return pref;
 }

 getPreference(userId: string, key: string): UserPreference | undefined {
 return this.preferences.get(userId)?.get(key);
 }

 getAllPreferences(userId: string): UserPreference[] {
 return Array.from(this.preferences.get(userId)?.values() ?? []);
 }
}

```

#### **src/lib/spark/intelligence/recommendations/interface.ts**

```

export interface Recommendation {
 itemId: string;
 reason: string;
 score: number;
}

export interface RecommendationsService {
 recommend(input: {
 userId?: string;
 sessionId?: string;
 candidateItems: Array<{ id: string; tags?: string[] }>;
 basedOnTags?: string[];
 limit?: number;
 }): Recommendation[];
}

```

#### **src/lib/spark/intelligence/recommendations/local.ts**

```

import type { Recommendation, RecommendationsService } from "../interface";

/**
 * Deterministic tag-overlap recommender. No model call required; this
 * can be replaced with a learned ranker later behind the same interface.
 */
export class LocalRecommendationsService implements RecommendationsService {
 recommend(input: {
 userId?: string;
 sessionId?: string;
 candidateItems: Array<{ id: string; tags?: string[] }>;
 basedOnTags?: string[];
 limit?: number;
 }): Recommendation[] {
 const wanted = new Set(input.basedOnTags ?? []);

 const scored: Recommendation[] = input.candidateItems.map((item) => {
 const tags = item.tags ?? [];
 const overlap = tags.filter((t) => wanted.has(t)).length;
 const score = wanted.size ? overlap / wanted.size : 0;
 return {
 itemId: item.id,
 reason: overlap
 ? `Matches ${overlap} of ${wanted.size} preferred tag(s).`
 : "No tag overlap; ranked by default order.",
 score,
 };
 });

 return scored
 .sort((a, b) => b.score - a.score)
 .slice(0, input.limit ?? 10);
 }
}

```

#### **src/lib/spark/intelligence/search/interface.ts**

```

export interface SearchResult {
 id: string;
 title: string;
 snippet: string;
 score: number;
}

export interface SearchService {
 search(query: string, limit?: number): Promise<SearchResult[]>;
}

```

#### **src/lib/spark/intelligence/search/local.ts**

```

import type { SearchService, SearchResult } from "../interface";

```

```

import type { KnowledgeService } from "../../knowledge/interface";

/**
 * Search is a thin, focused layer over Knowledge retrieval. It depends
 * on the KnowledgeService abstraction rather than reaching into Memory
 * directly, keeping the dependency graph shallow: Search -> Knowledge.
 */
export class LocalSearchService implements SearchService {
 constructor(private readonly knowledge: KnowledgeService) {}

 async search(query: string, limit = 5): Promise<SearchResult[]> {
 const matches = this.knowledge.query(query, limit);
 return matches.map((m) => ({
 id: m.document.id,
 title: m.document.title,
 snippet: m.document.content.slice(0, 160),
 score: m.score,
 }));
 }
}

```

#### **src/lib/spark/intelligence/summaries/interface.ts**

```

export interface SummaryRequest {
 text: string;
 maxSentences?: number;
}

export interface SummaryResult {
 summary: string;
 originalLength: number;
 summaryLength: number;
}

export interface SummariesService {
 summarize(request: SummaryRequest): SummaryResult;
}

```

#### **src/lib/spark/intelligence/summaries/local.ts**

```

import type { SummaryRequest, SummaryResult, SummariesService } from "./interface";

/**
 * Deterministic extractive summarizer (first-N-sentences heuristic).
 * No AI provider required. Can be upgraded to abstractive summarization
 * via a provider later without changing the interface.
 */
export class LocalSummariesService implements SummariesService {
 summarize(request: SummaryRequest): SummaryResult {
 const sentences = request.text
 .split(/(?<=[.!?])\s+/)
 .map((s) => s.trim())

```

```

 .filter(Boolean);

const maxSentences = request.maxSentences ?? 3;
const summary = sentences.slice(0, maxSentences).join(" ");

return {
 summary,
 originalLength: request.text.length,
 summaryLength: summary.length,
};
}
}

```

#### **src/lib/spark/intelligence/translation/interface.ts**

```

export interface TranslationRequest {
 text: string;
 targetLocale: string;
 sourceLocale?: string;
}

export interface TranslationResult {
 text: string;
 targetLocale: string;
 sourceLocale?: string;
 provider: string;
}

export interface TranslationService {
 translate(request: TranslationRequest): Promise<TranslationResult>;
}

```

#### **src/lib/spark/intelligence/translation/local.ts**

```

import type {
 TranslationRequest,
 TranslationResult,
 TranslationService,
} from "../interface";
import type { ProviderRegistry } from "../../providers/registry";

/** Delegates translation to the resolved AI provider (mock by default). */
export class LocalTranslationService implements TranslationService {
 constructor(private readonly providers: ProviderRegistry) {}

 async translate(request: TranslationRequest): Promise<TranslationResult> {
 const provider = this.providers.resolve();

 const completion = await provider.complete({
 messages: [
 {
 role: "system",

```

```

 content: `You are Spark's translation module. Translate into ${request.targetLocale}.`,
 },
 { role: "user", content: request.text },
],
 });

 return {
 text: completion.text,
 targetLocale: request.targetLocale,
 sourceLocale: request.sourceLocale,
 provider: completion.provider,
 };
}
}

```

#### **src/lib/spark/intelligence/writing/interface.ts**

```

export type WritingTone = "neutral" | "formal" | "casual" | "concise";

export interface WritingRequest {
 prompt: string;
 tone?: WritingTone;
 maxLength?: number;
}

export interface WritingResult {
 text: string;
 tone: WritingTone;
 provider: string;
}

export interface WritingService {
 draft(request: WritingRequest): Promise<WritingResult>;
}

```

#### **src/lib/spark/intelligence/writing/local.ts**

```

import type { WritingRequest, WritingResult, WritingService } from "../interface";
import type { ProviderRegistry } from "../../providers/registry";

/** Delegates drafting to the resolved AI provider (mock by default). */
export class LocalWritingService implements WritingService {
 constructor(private readonly providers: ProviderRegistry) {}

 async draft(request: WritingRequest): Promise<WritingResult> {
 const provider = this.providers.resolve();
 const tone = request.tone ?? "neutral";

 const completion = await provider.complete({
 messages: [
 {
 role: "system",

```

```

 content: `You are Spark's writing module. Tone: ${tone}.`,
 },
 { role: "user", content: request.prompt },
],
maxTokens: request.maxLength,
});

return { text: completion.text, tone, provider: completion.provider };
}
}

```

#### **src/lib/spark/knowledge/interface.ts**

```

export interface KnowledgeDocument {
 id: string;
 title: string;
 content: string;
 tags?: string[];
 addedAt: string;
}

export interface KnowledgeQueryResult {
 document: KnowledgeDocument;
 score: number;
}

export interface KnowledgeService {
 addDocument(input: { title: string; content: string; tags?: string[] }): KnowledgeDocument;
 getDocument(id: string): KnowledgeDocument | undefined;
 removeDocument(id: string): boolean;
 /** Simple relevance query. Real embeddings can replace scoring later. */
 query(text: string, limit?: number): KnowledgeQueryResult[];
 size(): number;
}

```

#### **src/lib/spark/knowledge/local.ts**

```

import type {
 KnowledgeDocument,
 KnowledgeQueryResult,
 KnowledgeService,
} from "../interface";

/**
 * In-memory knowledge store with naive keyword-overlap scoring. This
 * stands in for a knowledge graph / embeddings-backed retrieval system;
 * the KnowledgeService interface is stable so a real backend can be
 * swapped in without changing consumers.
 */
export class LocalKnowledgeService implements KnowledgeService {
 private documents = new Map<string, KnowledgeDocument>();
 private counter = 0;
}

```



```

addDocument(input: {
 title: string;
 content: string;
 tags?: string[];
}): KnowledgeDocument {
 const doc: KnowledgeDocument = {
 id: `doc_${++this.counter}_${Date.now()}`,
 title: input.title,
 content: input.content,
 tags: input.tags ?? [],
 addedAt: new Date().toISOString(),
 };
 this.documents.set(doc.id, doc);
 return doc;
}

getDocument(id: string): KnowledgeDocument | undefined {
 return this.documents.get(id);
}

removeDocument(id: string): boolean {
 return this.documents.delete(id);
}

query(text: string, limit = 5): KnowledgeQueryResult[] {
 const queryWords = new Set(
 text.toLowerCase().split(/\W+/).filter(Boolean)
);

 const scored: KnowledgeQueryResult[] = Array.from(
 this.documents.values()
).map((document) => {
 const docWords = `${document.title} ${document.content}`
 .toLowerCase()
 .split(/\W+/)
 .filter(Boolean);
 const overlap = docWords.filter((w) => queryWords.has(w)).length;
 const score = docWords.length ? overlap / docWords.length : 0;
 return { document, score };
 });

 return scored
 .filter((r) => r.score > 0)
 .sort((a, b) => b.score - a.score)
 .slice(0, limit);
}

size(): number {
 return this.documents.size;
}
}

```

```

export interface FeedbackEntry {
 id: string;
 subject: string;
 rating: "positive" | "negative" | "neutral";
 note?: string;
 createdAt: string;
}

export interface LearningService {
 recordFeedback(input: {
 subject: string;
 rating: "positive" | "negative" | "neutral";
 note?: string;
 }): FeedbackEntry;

 getFeedback(subject: string): FeedbackEntry[];

 /** Simple aggregate score in [-1, 1] based on recorded feedback. */
 score(subject: string): number;
}

```

#### **src/lib/spark/learning/local.ts**

```

import type { FeedbackEntry, LearningService } from "../interface";

const RATING_WEIGHT: Record<FeedbackEntry["rating"], number> = {
 positive: 1,
 neutral: 0,
 negative: -1,
};

/**
 * In-memory feedback store with a simple aggregate scoring function.
 * This is the seed of continuous improvement / adaptive personalization -
 * it does not train any model, it just tracks signal for later use.
 */
export class LocalLearningService implements LearningService {
 private feedback: FeedbackEntry[] = [];
 private counter = 0;

 recordFeedback(input: {
 subject: string;
 rating: FeedbackEntry["rating"];
 note?: string;
 }): FeedbackEntry {
 const entry: FeedbackEntry = {
 id: `fb_${++this.counter}_${Date.now()}`,
 subject: input.subject,
 rating: input.rating,
 note: input.note,
 createdAt: new Date().toISOString(),
 };
 this.feedback.push(entry);
 return entry;
 }
}

```

```

 }

 getFeedback(subject: string): FeedbackEntry[] {
 return this.feedback.filter((f) => f.subject === subject);
 }

 score(subject: string): number {
 const entries = this.getFeedback(subject);
 if (!entries.length) return 0;
 const total = entries.reduce((sum, e) => sum + RATING_WEIGHT[e.rating], 0);
 return total / entries.length;
 }
}

```

#### **src/lib/spark/manifest.ts**

```

export const SPARK_VERSION = "0.1.0";
export const SPARK_BUILD = "dev";

export const SPARK_CAPABILITIES = [
 "identity",
 "reasoning",
 "planning",
 "memory",
 "context",
 "knowledge",
 "search",
 "recommendations",
 "organization",
 "personalization",
 "writing",
 "translation",
 "summaries",
 "privacy",
 "security",
 "automation",
 "learning",
] as const;

export type SparkCapability = (typeof SPARK_CAPABILITIES)[number];

export interface SparkManifest {
 name: string;
 version: string;
 build: string;
 capabilities: readonly SparkCapability[];
 registeredModules: string[];
 providers: Array<{ name: string; available: boolean; isDefault: boolean }>;
}

```

#### **src/lib/spark/memory/interface.ts**

```

export type MemoryKind = "short_term" | "long_term" | "semantic" | "episodic" | "workspace";

export interface MemoryRecord {
 id: string;
 kind: MemoryKind;
 sessionId?: string;
 userId?: string;
 content: string;
 tags?: string[];
 createdAt: string;
 /**
 * Monotonically increasing insertion order. `createdAt` alone is not a
 * reliable sort key - multiple records can share the same millisecond
 * timestamp. `recall()` implementations must use `sequence` as the
 * tiebreaker so "newest first" holds even for same-millisecond writes.
 */
 sequence: number;
}

export interface MemoryQuery {
 kind?: MemoryKind;
 sessionId?: string;
 userId?: string;
 tag?: string;
 text?: string;
 limit?: number;
}

export interface MemoryService {
 remember(input: {
 kind: MemoryKind;
 content: string;
 sessionId?: string;
 userId?: string;
 tags?: string[];
 }): MemoryRecord;

 recall(query: MemoryQuery): MemoryRecord[];

 forget(id: string): boolean;

 clearSession(sessionId: string): number;

 size(): number;
}

```

#### **src/lib/spark/memory/local.ts**

```

import type { MemoryKind, MemoryQuery, MemoryRecord, MemoryService } from "../interface";

/**
 * In-memory implementation covering short-term, long-term, semantic,
 * episodic and workspace memory kinds through a single flat store with
 * a `kind` discriminator. No persistence, no network calls.

```

```
*/
```

```
export class InMemoryMemoryService implements MemoryService {
 private records = new Map<string, MemoryRecord>();
 private counter = 0;

 remember(input: {
 kind: MemoryKind;
 content: string;
 sessionId?: string;
 userId?: string;
 tags?: string[];
 }): MemoryRecord {
 const sequence = ++this.counter;
 const record: MemoryRecord = {
 id: `mem_${sequence}_${Date.now()}`,
 kind: input.kind,
 sessionId: input.sessionId,
 userId: input.userId,
 content: input.content,
 tags: input.tags ?? [],
 createdAt: new Date().toISOString(),
 sequence,
 };
 this.records.set(record.id, record);
 return record;
 }

 recall(query: MemoryQuery): MemoryRecord[] {
 let results = Array.from(this.records.values());

 if (query.kind) results = results.filter((r) => r.kind === query.kind);
 if (query.sessionId)
 results = results.filter((r) => r.sessionId === query.sessionId);
 if (query.userId) results = results.filter((r) => r.userId === query.userId);
 if (query.tag) results = results.filter((r) => (r.tags ?? []).includes(query.tag!));
 if (query.text) {
 const needle = query.text.toLowerCase();
 results = results.filter((r) => r.content.toLowerCase().includes(needle));
 }

 results.sort((a, b) => {
 const timeDiff = new Date(b.createdAt).getTime() - new Date(a.createdAt).getTime();
 return timeDiff !== 0 ? timeDiff : b.sequence - a.sequence;
 });

 return query.limit ? results.slice(0, query.limit) : results;
 }

 forget(id: string): boolean {
 return this.records.delete(id);
 }

 clearSession(sessionId: string): number {
 let cleared = 0;
 for (const [id, record] of this.records) {
 if (record.sessionId === sessionId) {
 this.records.delete(id);
 }
 }
 }
}
```

```

 cleared++;
 }
}
return cleared;
}

size(): number {
 return this.records.size;
}
}

```

#### **src/lib/spark/middleware.ts**

```

/**
 * Middleware pipeline.
 *
 * Middleware wraps every call made through Spark.call(), so cross-cutting
 * concerns (logging, auth, caching, rate limiting) can be added without
 * touching individual service implementations.
 */

export interface SparkCallContext {
 service: string;
 method: string;
 args: unknown[];
 startedAt: number;
 meta: Record<string, unknown>;
}

export type NextFn<TResult> = () => Promise<TResult>;

export type Middleware = <TResult>(
 ctx: SparkCallContext,
 next: NextFn<TResult>
) => Promise<TResult>;

export class MiddlewarePipeline {
 private middlewares: Middleware[] = [];

 use(middleware: Middleware): void {
 this.middlewares.push(middleware);
 }

 clear(): void {
 this.middlewares = [];
 }

 list(): number {
 return this.middlewares.length;
 }

 async run<TResult>(
 ctx: SparkCallContext,
 handler: () => Promise<TResult>
): Promise<TResult> {

```

```

 const chain = this.middlewares.reduceRight<NextFn<TResult>>>(
 (next, mw) => () => mw(ctx, next),
 handler
);
 return chain();
 }
}

/** Simple built-in logging middleware, opt-in via Spark.use(loggingMiddleware). */
export const loggingMiddleware: Middleware = async (ctx, next) => {
 const result = await next();
 const durationMs = Date.now() - ctx.startedAt;
 // eslint-disable-next-line no-console
 console.log(
 `[spark] ${ctx.service}.${ctx.method} (${durationMs}ms)`
);
 return result;
};

```

#### **src/lib/spark/plugins.ts**

```

import type { Container } from "../container";
import type { Token } from "../tokens";
import type { ProviderRegistry } from "../providers/registry";
import type { MiddlewarePipeline } from "../middleware";
import type { EventBus } from "../events";

export interface SparkPluginContext {
 container: Container;
 providers: ProviderRegistry;
 middleware: MiddlewarePipeline;
 events: EventBus;
}

export interface SparkPlugin {
 name: string;
 version?: string;
 /** Called once at registration time. Register services, providers, etc. here. */
 install(ctx: SparkPluginContext): void;
}

export class PluginManager {
 private installed = new Map<string, SparkPlugin>();

 register(plugin: SparkPlugin, ctx: SparkPluginContext): void {
 if (this.installed.has(plugin.name)) {
 throw new Error(`Plugin "${plugin.name}" is already registered.`);
 }
 plugin.install(ctx);
 this.installed.set(plugin.name, plugin);
 }

 list(): Array<{ name: string; version?: string }> {
 return Array.from(this.installed.values()).map((p) => ({
 name: p.name,

```

```

 version: p.version,
 }));
}

// Re-export for convenience so plugin authors have one import.
export type { Token };

```

#### **src/lib/spark/providers/anthropic.ts**

```

import type {
 AIProvider,
 AIProviderCompletionRequest,
 AIProviderCompletionResult,
} from "../types";

/**
 * Placeholder adapter for Anthropic. Contains no SDK dependency and
 * makes no network calls.
 */
export class AnthropicProvider implements AIProvider {
 readonly name = "anthropic";

 constructor(private readonly apiKey?: string) {}

 isAvailable(): boolean {
 return Boolean(this.apiKey);
 }

 async complete(
 _request: AIProviderCompletionRequest
): Promise<AIProviderCompletionResult> {
 if (!this.isAvailable()) {
 throw new Error(
 "AnthropicProvider is a placeholder and has no API key configured."
);
 }
 throw new Error("AnthropicProvider.complete() is not yet implemented.");
 }
}

```

#### **src/lib/spark/providers/gemini.ts**

```

import type {
 AIProvider,
 AIProviderCompletionRequest,
 AIProviderCompletionResult,
} from "../types";

/** Placeholder adapter for Google Gemini. No SDK dependency, no network calls. */
export class GeminiProvider implements AIProvider {
 readonly name = "gemini";

```



```

constructor(private readonly apiKey?: string) {}

isAvailable(): boolean {
 return Boolean(this.apiKey);
}

async complete(
 _request: AIProviderCompletionRequest
): Promise<AIProviderCompletionResult> {
 if (!this.isAvailable()) {
 throw new Error(
 "GeminiProvider is a placeholder and has no API key configured."
);
 }
 throw new Error("GeminiProvider.complete() is not yet implemented.");
}
}

```

#### **src/lib/spark/providers/local.ts**

```

import type {
 AIProvider,
 AIProviderCompletionRequest,
 AIProviderCompletionResult,
} from "../types";

/**
 * Placeholder adapter for a local/self-hosted model (e.g. Ollama, a
 * local llama.cpp server). No network calls are made in this phase.
 */
export class LocalModelProvider implements AIProvider {
 readonly name = "local";

 constructor(private readonly endpoint?: string) {}

 isAvailable(): boolean {
 return Boolean(this.endpoint);
 }

 async complete(
 _request: AIProviderCompletionRequest
): Promise<AIProviderCompletionResult> {
 if (!this.isAvailable()) {
 throw new Error(
 "LocalModelProvider is a placeholder and has no endpoint configured."
);
 }
 throw new Error("LocalModelProvider.complete() is not yet implemented.");
 }
}

```

**src/lib/spark/providers/mock.ts**

```
import type {
 AIProvider,
 AIProviderCompletionRequest,
 AIProviderCompletionResult,
 AIProviderEmbeddingResult,
} from "../types";

/**
 * Deterministic, offline provider. This is the default provider so that
 * Spark builds and runs with zero external dependencies and zero API keys.
 * It never makes a network call.
 */
export class MockProvider implements AIProvider {
 readonly name = "mock";

 isAvailable(): boolean {
 return true;
 }

 async complete(
 request: AIProviderCompletionRequest
): Promise<AIProviderCompletionResult> {
 const lastUser = [...request.messages]
 .reverse()
 .find((m) => m.role === "user");

 return {
 text: `[mock:${this.name}] acknowledged ${
 lastUser ? lastUser.content.length : 0
 } chars of input`,
 provider: this.name,
 model: "mock-1",
 usage: { inputTokens: 0, outputTokens: 0 },
 };
 }

 async embed(text: string): Promise<AIProviderEmbeddingResult> {
 // Deterministic pseudo-embedding derived from character codes, so
 // the same input always yields the same vector without any model.
 const dims = 16;
 const vector = new Array(dims).fill(0);
 for (let i = 0; i < text.length; i++) {
 vector[i % dims] += text.charCodeAt(i);
 }
 const max = Math.max(1, ...vector.map(Math.abs));
 return {
 vector: vector.map((v) => v / max),
 provider: this.name,
 model: "mock-embed-1",
 };
 }
}
```

#### **src/lib/spark/providers/openai.ts**

```
import type {
 AIProvider,
 AIProviderCompletionRequest,
 AIProviderCompletionResult,
} from "../types";

/**
 * Placeholder adapter for OpenAI. Contains no SDK dependency and makes
 * no network calls. Swap in a real implementation later without
 * changing any Spark service code – they only depend on AIProvider.
 */
export class OpenAIProvider implements AIProvider {
 readonly name = "openai";

 constructor(private readonly apiKey?: string) {}

 isAvailable(): boolean {
 return Boolean(this.apiKey);
 }

 async complete(
 _request: AIProviderCompletionRequest
): Promise<AIProviderCompletionResult> {
 if (!this.isAvailable()) {
 throw new Error(
 "OpenAIProvider is a placeholder and has no API key configured."
);
 }
 throw new Error("OpenAIProvider.complete() is not yet implemented.");
 }
}
```

#### **src/lib/spark/providers/registry.ts**

```
import type { AIProvider } from "../types";
import { MockProvider } from "../mock";

/**
 * Holds all registered AI providers and resolves which one to use.
 * Services depend on this registry (or on a single resolved AIProvider),
 * never on a concrete vendor class.
 */
export class ProviderRegistry {
 private providers = new Map<string, AIProvider>();
 private defaultName: string;

 constructor() {
 const mock = new MockProvider();
 this.providers.set(mock.name, mock);
 this.defaultName = mock.name;
 }
}
```

```

register(provider: AIProvider, makeDefault = false): void {
 this.providers.set(provider.name, provider);
 if (makeDefault) {
 this.defaultName = provider.name;
 }
}

setDefault(name: string): void {
 if (!this.providers.has(name)) {
 throw new Error(`Cannot set default: provider "${name}" is not registered.`);
 }
 this.defaultName = name;
}

get(name?: string): AIProvider {
 const key = name ?? this.defaultName;
 const provider = this.providers.get(key);
 if (!provider) {
 throw new Error(`Provider "${key}" is not registered.`);
 }
 return provider;
}

/** Returns the default provider if available, else falls back to mock. */
resolve(): AIProvider {
 const preferred = this.providers.get(this.defaultName);
 if (preferred && preferred.isAvailable()) {
 return preferred;
 }
 return this.providers.get("mock")!;
}

list(): Array<{ name: string; available: boolean; isDefault: boolean }> {
 return Array.from(this.providers.values()).map((p) => ({
 name: p.name,
 available: p.isAvailable(),
 isDefault: p.name === this.defaultName,
 }));
}
}

```

#### **src/lib/spark/providers/types.ts**

```

/**
 * AI Provider abstraction.
 *
 * Spark services never call a provider SDK directly – they only ever
 * talk to this interface. Concrete providers (OpenAI, Anthropic, Gemini,
 * local models, etc.) are adapters that implement it and are registered
 * through the ProviderRegistry.
 */

export interface AIProviderMessage {
 role: "system" | "user" | "assistant";
 content: string;
}

```

```

}

export interface AIProviderCompletionRequest {
 messages: AIProviderMessage[];
 maxTokens?: number;
 temperature?: number;
}

export interface AIProviderCompletionResult {
 text: string;
 provider: string;
 model?: string;
 usage?: {
 inputTokens?: number;
 outputTokens?: number;
 };
}

export interface AIProviderEmbeddingResult {
 vector: number[];
 provider: string;
 model?: string;
}

export interface AIProvider {
 /** Unique identifier, e.g. "mock", "openai", "anthropic" */
 readonly name: string;

 /** Whether this provider is currently usable (e.g. has credentials). */
 isAvailable(): boolean;

 complete(
 request: AIProviderCompletionRequest
): Promise<AIProviderCompletionResult>;

 embed?(text: string): Promise<AIProviderEmbeddingResult>;
}

```

#### **src/lib/spark/tokens.ts**

```

/**
 * The single canonical set of DI tokens used throughout Spark.
 *
 * Tokens are Symbols, not strings, so two independently-authored
 * modules can never collide on a token by accident even if they
 * happen to choose the same label. Every Symbol still carries its
 * original label as `description`, so diagnostics and logs stay
 * human-readable via `tokenLabel()` below.
 */

export const TOKENS = {
 Logger: Symbol("kernel.logger"),
 ProviderRegistry: Symbol("providers.registry"),

 Identity: Symbol("core.identity"),

```

```

Memory: Symbol("core.memory"),
Context: Symbol("core.context"),
Knowledge: Symbol("core.knowledge"),
Reasoning: Symbol("core.reasoning"),
Planning: Symbol("core.planning"),

Search: Symbol("intelligence.search"),
Recommendations: Symbol("intelligence.recommendations"),
Organization: Symbol("intelligence.organization"),
Personalization: Symbol("intelligence.personalization"),
Writing: Symbol("intelligence.writing"),
Translation: Symbol("intelligence.translation"),
Summaries: Symbol("intelligence.summaries"),

Privacy: Symbol("trust.privacy"),
Security: Symbol("trust.security"),

Automation: Symbol("automation"),
Learning: Symbol("learning"),
} as const;

export type Token = symbol;

/** Human-readable label for a token, for logs/diagnostics/health output. */
export function tokenLabel(token: Token): string {
 return token.description ?? token.toString();
}

```

#### **src/lib/spark/trust/privacy/interface.ts**

```

export interface PiiFinding {
 type: "email" | "phone" | "ssn" | "credit_card";
 match: string;
 index: number;
}

export interface PrivacyService {
 scanForPii(text: string): PiiFinding[];
 redact(text: string): string;
}

```

#### **src/lib/spark/trust/privacy/local.ts**

```

import type { PiiFinding, PrivacyService } from "./interface";

const PATTERNS: Array<{ type: PiiFinding["type"]; regex: RegExp }> = [
 { type: "email", regex: /[a-zA-Z0-9._%+-]+@[a-zA-Z0-9.-]+\.[a-zA-Z]{2,}/g },
 { type: "phone", regex: /\+?\d[\d\s()]{7,}\d/g },
 { type: "ssn", regex: /\b\d{3}-\d{2}-\d{4}\b/g },
 { type: "credit_card", regex: /\b(?:\d[-]*){13,16}\b/g },
];

```

```

/** Local, regex-based PII detection and redaction. No network calls. */
export class LocalPrivacyService implements PrivacyService {
 scanForPii(text: string): PiiFinding[] {
 const findings: PiiFinding[] = [];
 for (const { type, regex } of PATTERNS) {
 let match: RegExpExecArray | null;
 const re = new RegExp(regex);
 while ((match = re.exec(text)) !== null) {
 findings.push({ type, match: match[0], index: match.index });
 if (!re.global) break;
 }
 }
 return findings;
 }

 redact(text: string): string {
 let redacted = text;
 for (const { regex } of PATTERNS) {
 redacted = redacted.replace(new RegExp(regex), "[REDACTED]");
 }
 return redacted;
 }
}

```

#### **src/lib/spark/trust/security/interface.ts**

```

export interface SecurityCheckResult {
 safe: boolean;
 reasons: string[];
}

export interface SecurityService {
 /** Basic heuristic scan for common injection/scam patterns. */
 checkInput(text: string): SecurityCheckResult;
}

```

#### **src/lib/spark/trust/security/local.ts**

```

import type { SecurityCheckResult, SecurityService } from "./interface";

const SUSPICIOUS_PATTERNS: Array<{ label: string; regex: RegExp }> = [
 { label: "possible script injection", regex: /<script[\s]/i },
 { label: "possible SQL injection", regex: /(\bunion\b.*\bselect\b|;\s*drop\s+table)/i },
 { label: "urgent wire-transfer scam language", regex: /wire (transfer|money) immediately/i },
 { label: "credential phishing language", regex: /verify your (password|account) (now|immediately)/i
];

/** Local heuristic security scanner. No network calls, no ML model. */
export class LocalSecurityService implements SecurityService {
 checkInput(text: string): SecurityCheckResult {
 const reasons = SUSPICIOUS_PATTERNS.filter((p) => p.regex.test(text)).map(
 (p) => p.label
);
 }
}

```

```

);
 return { safe: reasons.length === 0, reasons };
 }
}

```

#### **src/lib/spark/types.ts**

```

export type HealthStatus = "healthy" | "degraded" | "unhealthy";

export interface SparkHealthReport {
 status: HealthStatus;
 initialized: boolean;
 loadedModules: string[];
 registeredProviders: Array<{
 name: string;
 available: boolean;
 isDefault: boolean;
 }>;
 diagnostics: string[];
 warnings: string[];
 uptimeMs: number;
 checkedAt: string;
}

export interface SparkMetrics {
 requestCounts: Record<string, number>;
 executionTimesMs: Record<string, number[]>;
 cacheHits: number;
 cacheMisses: number;
 memorySize: number;
 eventsEmitted: number;
}

```

## **Bud — Reusable Companion Layer**

#### **scripts/bud-verify.ts**

```

import { createSpark } from "../src/lib/spark";
import { createBud } from "../src/lib/bud";

async function main() {
 const spark = createSpark();
 await spark.initialize();

 spark.knowledge.addDocument({
 title: "Refund Policy",
 content: "Refunds are issued within 5 business days of a return request.",
 tags: ["policy", "refunds"],
 });

 const bud = createBud({ spark, personality: { name: "Bud", tone: "concise" } });
}

```



```

const session = { sessionId: "s1", userId: "u1", product: "unibud" };

console.log("--- Turn 1: simple question ---");
const r1 = await bud.respond("What is your refund policy?", session);
console.log(r1);

console.log("\n--- Turn 2: multi-step message (should trigger planning) ---");
const r2 = await bud.respond(
 "Check my refund status then email me a confirmation",
 session
);
console.log(r2);
if (r2.trace.plannedTaskCount < 2) {
 throw new Error("Expected planIfNeeded to detect a multi-step request.");
}

console.log("\n--- Turn 3: memory should now include prior turns ---");
const r3 = await bud.respond("What did I just ask you?", session);
console.log(r3);
if (r3.trace.memoryHits === 0) {
 throw new Error("Expected memory recall to find prior turns.");
}

console.log("\n--- Transcript (read back purely from Spark memory) ---");
const transcript = bud.transcript(session.sessionId);
console.log(JSON.stringify(transcript, null, 2));
if (transcript.length < 2) {
 throw new Error("Expected at least two stored conversation turns.");
}

console.log("\n--- Spark health after Bud usage ---");
console.log(spark.health());

await spark.shutdown();
console.log("\nBud verification completed successfully.");
}

main().catch((err) => {
 console.error("Bud verification failed:", err);
 throw err;
});

```

#### **src/lib/bud/ARCHITECTURE.md**

# Bud – Architecture

## Position in the ecosystem

**User | ▼ Bud (personality + orchestration only) | ▼ Spark (all intelligence: memory, context, reasoning, planning, | knowledge, search, writing, translation, privacy, | security, automation, learning) ▼ AI Provider (Mock by default; OpenAI/Anthropic/Gemini/local when configured)**

Bud never skips Spark to reach the AI provider layer directly, and Spark never imports or knows about Bud.

## Directory layout

**src/lib/bud/** |—— **index.ts** Public SDK — **createBud()**. The only supported import. |—— **config.ts** Static limits (recall/search result counts). |—— **types.ts** Session, message, and response shapes. |—— **personality.ts** Static tone/voice configuration. |—— **orchestrator.ts** The **respond()** flow, step by step. |—— **conversation.ts** Transcript formatting over Spark memory (no storage of its own). |—— **prompts/** |—— **systemPrompt.ts** Builds the system prompt from personality config. |—— **userPrompt.ts** Builds the user-turn prompt from Spark's outputs. |—— **actions/** |—— **recallMemory.ts** Calls **spark.memory.recall** |—— **searchKnowledge.ts** Calls **spark.search.search** |—— **reason.ts** Calls **spark.reasoning.analyze** |—— **planIfNeeded.ts** Mechanical step detection -> **spark.planning.createPlan** |—— **generateResponse.ts** Calls **spark.writing.draft** |—— **storeInteraction.ts** Calls **spark.memory.remember** |—— **context/** |—— **buildContext.ts** Ensures **spark.identity** has a context for the session |—— **adapters/** |—— **sparkPort.ts** The narrow interface Bud is allowed to depend on |—— **liveSparkAdapter.ts** Wraps a real Spark instance to satisfy that interface

## The **respond()** flow

``bud.respond(message, session)`` runs exactly these steps, in order, every time:

1. **\*\*Build context\*\*** — ``context/buildContext.ts`` asks Spark's Identity service whether this session already has a context; creates one if not.
2. **\*\*Recall memory\*\*** — ``actions/recallMemory.ts`` asks Spark for prior episodic memory tied to this session.
3. **\*\*Search knowledge\*\*** — ``actions/searchKnowledge.ts`` asks Spark's Search service (which itself only talks to Knowledge) for anything relevant to the message.
4. **\*\*Reason\*\*** — ``actions/reason.ts`` hands the message plus everything recalled/found to Spark's Reasoning service and gets back an answer, a confidence score, and an explainable step trace.
5. **\*\*Plan (conditionally)\*\*** — ``actions/planIfNeeded.ts`` does a mechanical check (keyword/punctuation split, not semantic understanding) for whether the message looks like multiple sequenced asks. If so, it hands the extracted steps to Spark's Planning service. If not, no plan is created and no planning call is made.
6. **\*\*Generate response\*\*** — ``actions/generateResponse.ts`` builds a prompt (system prompt from personality + user prompt from Spark's reasoning/memory/knowledge outputs) and calls ``spark.writing.draft()``. Spark resolves whichever ``AIProvider`` is registered — Bud never knows or cares which one.
7. **\*\*Store the turn\*\*** — ``actions/storeInteraction.ts`` writes both the user's message and Bud's reply back into Spark memory as episodic records, tagged ``user`/`bud``.

Every one of those seven steps is a call through ``BudSparkPort`` — the orchestrator (``orchestrator.ts``) contains no branching logic that depends on the *content* of the message beyond step 5's mechanical split. It doesn't summarize, doesn't judge relevance, doesn't decide what's true — it delegates all of that.

## Why `adapters/sparkPort.ts` exists

`BudSparkPort` is a deliberately narrow re-typing of Spark's public surface – only `identity`, `memory`, `search`, `reasoning`, `planning`, and `writing`. Two consequences:

- **It's structurally impossible for Bud's action files to reach a capability that isn't listed** – there is no `providers` field on the port, so Bud cannot call an `AIProvider` even by mistake.
- **Bud is independently testable.** Anything satisfying `BudSparkPort`'s shape can stand in for Spark in a test, without spinning up a real Spark instance. `adapters/liveSparkAdapter.ts` is the only file that touches the concrete `Spark` class.

## Where conversation history actually lives

`conversation.ts` has no storage of its own. `getTranscript()` reads Spark's episodic memory for a session and reshapes matched user/bud record pairs into `ConversationTurn[]`. If Spark's memory for that session is cleared, the transcript is gone – there is no shadow copy inside Bud.

## Product independence

`BudSession.product` is passed straight through to Spark's identity and context services without Bud inspecting or branching on its value. There is no `if (product === "unibud")` anywhere in this module, and there must never be – that would turn Bud from a reusable companion into a product-specific one. New products reuse this exact module by supplying their own `product` string.

## What's deliberately not here yet

- No persistence beyond whatever Spark itself persists (currently in-memory, see the Spark scaffold's README).
- No streaming responses – `writing.draft()` returns a complete string.
- No multi-turn planning follow-through (Bud creates a plan via step 5 but does not yet check `spark.planning.nextTask()` on later turns to walk through it turn-by-turn).
- No integration into UNIBUD, My Realm, Orbit, or any application.

**src/lib/bud/README.md**

# Bud – the reusable companion layer

Bud is a thin orchestration layer that sits between a user and Spark. It holds a personality and a conversation flow – nothing else. All memory, reasoning, planning, search, and text generation come from Spark.

```ts

import { createBud } from "@lib/bud";

const bud = createBud();

```
const response = await bud.respond("What's my next task, then remind me to email Sam?", {
  sessionId: "session_1",
  userId: "user_1",
  product: "unibud",
});

console.log(response.message);
console.log(response.trace); // { memoryHits, knowledgeHits, reasoningConfidence, plannedTaskCount, pr
```

Consumers should only ever `import { createBud } from "@lib/bud"` . **Nothing under** `bud/orchestrator.ts` , `bud/actions/*` , `bud/adapters/*` , **etc. is a supported import path.**

What Bud does NOT do

- Bud does not remember anything itself — `spark.memory` **does**.
- Bud does not search or retrieve anything itself — `spark.search` **does**.
- Bud does not reason about the message itself — `spark.reasoning` **does**.
- Bud does not plan multi-step goals itself — `spark.planning` **does**, once Bud has mechanically noticed the message looks like several steps.
- Bud does not call an AI provider, ever — `spark.writing` **does**, and only Spark decides which provider handles that call.

See `ARCHITECTURE.md` for the full request flow and the reasoning behind each of these boundaries.

Sharing a Spark instance

By default `createBud()` **creates its own private Spark instance.** If you want multiple Bud instances (or Bud plus another future assistant) to share memory/knowledge/identity, pass one in:

```
import { createSpark } from "@lib/spark";
import { createBud } from "@lib/bud";

const spark = createSpark();
await spark.initialize();

const bud = createBud({ spark });
```

Personality

Personality is plain configuration — a name, tone, and a few voice guidelines folded into the system prompt Bud sends to Spark's writing service. It contains no logic:

```
const bud = createBud({
  personality: {
    name: "Bud",
    tone: "concise",
    voice: ["Always suggest one concrete next step."],
  },
});
```

Reusability

Bud has no reference to UNIBUD, My Realm, Orbit, or any other product. The `product` field on `BudSession` is passed straight through to Spark's identity/context services — Bud doesn't interpret it. Any product can use the same Bud module by supplying its own sessions.

```
## `src/lib/bud/actions/generateResponse.ts`

``ts
import type { BudSparkPort } from "../../adapters/sparkPort";
import type { BudPersonality } from "../../personality";
import type { ReasoningResult } from "../../spark/core/reasoning/interface";
import type { MemoryRecord } from "../../spark/memory/interface";
import type { SearchResult } from "../../spark/intelligence/search/interface";
import { buildSystemPrompt } from "../../prompts/systemPrompt";
import { buildUserPrompt } from "../../prompts/userPrompt";
import type { WritingResult } from "../../spark/intelligence/writing/interface";

/**
 * Delegates text generation to Spark.writing (which in turn delegates
 * to whatever AIProvider is configured). Bud never calls a provider
 * directly — this is the only path to generated text.
 */
export async function generateResponse(
  spark: BudSparkPort,
  personality: BudPersonality,
  input: {
    message: string;
    memoryRecords: MemoryRecord[];
    knowledgeResults: SearchResult[];
    reasoning: ReasoningResult;
  }
): Promise<WritingResult> {
  const system = buildSystemPrompt(personality);
  const user = buildUserPrompt(input);

  return spark.writing.draft({
    prompt: `${system}\n\n${user}`,
    tone: personality.tone,
  });
}
```

src/lib/bud/actions/planIfNeeded.ts

```
import type { BudSparkPort } from "../../adapters/sparkPort";
import type { Plan } from "../../spark/core/planning/interface";

const STEP_SEPARATORS = /\bthen\b|;\n-|\n\d+\./i;

/**
 * This is mechanical text splitting, not reasoning about intent — Bud
 * detects a shape (multiple steps separated by "then"/semicolons/list
 * markers) and hands the actual planning off to Spark. If the message
```

```

    * doesn't look like a multi-step request, no plan is created.
    */
export function planIfNeeded(spark: BudSparkPort, message: string): Plan | null {
    if (!STEP_SEPARATORS.test(message)) {
        return null;
    }

    const steps = message
        .split(STEP_SEPARATORS)
        .map((s) => s.replace(/^[\\s\\-\\.\\d]+/, "").trim())
        .filter((s) => s.length > 0);

    if (steps.length < 2) {
        return null;
    }

    return spark.planning.createPlan(message, steps);
}

```

src/lib/bud/actions/reason.ts

```

import type { BudSparkPort } from "../../adapters/sparkPort";
import type { ReasoningResult } from "../../spark/core/reasoning/interface";
import type { MemoryRecord } from "../../spark/memory/interface";
import type { SearchResult } from "../../spark/intelligence/search/interface";

/**
 * Assembles the facts Spark's reasoning service should consider – from
 * recalled memory and search results – and delegates the actual
 * analysis to Spark. Bud does not reason on its own.
 */
export async function reason(
    spark: BudSparkPort,
    message: string,
    memoryRecords: MemoryRecord[],
    knowledgeResults: SearchResult[]
): Promise<ReasoningResult> {
    const facts = [
        ...memoryRecords.map((m) => m.content),
        ...knowledgeResults.map((k) => `${k.title}: ${k.snippet}`),
    ];

    return spark.reasoning.analyze({ question: message, facts });
}

```

src/lib/bud/actions/recallMemory.ts

```

import type { BudSparkPort } from "../../adapters/sparkPort";
import type { MemoryRecord } from "../../spark/memory/interface";

/**
 * Thin wrapper around Spark's memory recall. Bud does not implement

```

```

    * any memory logic itself – it only asks Spark for what it remembers.
    */
export function recallMemory(
  spark: BudSparkPort,
  sessionId: string,
  limit: number
): MemoryRecord[] {
  return spark.memory.recall({ sessionId, limit });
}

```

src/lib/bud/actions/searchKnowledge.ts

```

import type { BudSparkPort } from "../../adapters/sparkPort";
import type { SearchResult } from "../../spark/intelligence/search/interface";

/**
 * Thin wrapper around Spark's search service. Bud never implements its
 * own search or retrieval – it only asks Spark.
 */
export async function searchKnowledge(
  spark: BudSparkPort,
  query: string,
  limit: number
): Promise<SearchResult[]> {
  return spark.search.search(query, limit);
}

```

src/lib/bud/actions/storeInteraction.ts

```

import type { BudSparkPort } from "../../adapters/sparkPort";

/**
 * Stores both sides of the exchange as episodic memory through Spark.
 * Bud holds no memory of its own – this is the only place a turn is
 * persisted, and it goes straight into Spark.
 */
export function storeInteraction(
  spark: BudSparkPort,
  input: {
    sessionId: string;
    userId: string;
    userMessage: string;
    budMessage: string;
  }
): void {
  spark.memory.remember({
    kind: "episodic",
    content: `User: ${input.userMessage}`,
    sessionId: input.sessionId,
    userId: input.userId,
    tags: ["conversation", "user"],
  });
}

```

```

    spark.memory.remember({
      kind: "episodic",
      content: `Bud: ${input.budMessage}`,
      sessionId: input.sessionId,
      userId: input.userId,
      tags: ["conversation", "bud"],
    });
  }

```

src/lib/bud/adapters/liveSparkAdapter.ts

```

import type { Spark } from "../../spark";
import type { BudSparkPort } from "../sparkPort";

/**
 * Wraps a concrete Spark instance so Bud's orchestrator only ever sees
 * the narrow BudSparkPort surface. Swapping this file for a test double
 * (e.g. an in-memory fake) is the only thing needed to unit-test Bud
 * without a real Spark instance.
 */
export function createLiveSparkAdapter(spark: Spark): BudSparkPort {
  return {
    identity: {
      createContext: (input) => spark.identity.createContext(input),
      getContext: (sessionId) => spark.identity.getContext(sessionId),
    },
    memory: {
      remember: (input) => spark.memory.remember(input),
      recall: (query) => spark.memory.recall(query),
    },
    search: {
      search: (query, limit) => spark.search.search(query, limit),
    },
    reasoning: {
      analyze: (input) => spark.reasoning.analyze(input),
    },
    planning: {
      createPlan: (goal, taskTitles) => spark.planning.createPlan(goal, taskTitles),
    },
    writing: {
      draft: (input) => spark.writing.draft(input),
    },
  };
}

```

src/lib/bud/adapters/sparkPort.ts

```

/**
 * BudSparkPort is the ONLY thing Bud's orchestration code depends on —
 * never the concrete Spark class directly. This keeps Bud honest about
 * "orchestration only": if a capability isn't listed here, Bud cannot

```



```
* reach for it, including AI providers, which are deliberately absent
* from this port.
*
* It is a subset of Spark's public API, re-typed narrowly so Bud's
* intent (recall memory, search knowledge, reason, plan, draft text,
* store memory) is visible at the type level.
*/
```

```
import type { IdentityContext } from "../../spark/core/identity/interface";
import type { ReasoningResult } from "../../spark/core/reasoning/interface";
import type { Plan } from "../../spark/core/planning/interface";
import type { MemoryKind, MemoryRecord } from "../../spark/memory/interface";
import type { SearchResult } from "../../spark/intelligence/search/interface";
import type { WritingResult, WritingTone } from "../../spark/intelligence/writing/interface";
```

```
export interface BudSparkPort {
  identity: {
    createContext(input: {
      userId: string;
      sessionId: string;
      product: string;
      locale?: string;
      timezone?: string;
    }): IdentityContext;
    getContext(sessionId: string): IdentityContext | undefined;
  };

  memory: {
    remember(input: {
      kind: MemoryKind;
      content: string;
      sessionId?: string;
      userId?: string;
      tags?: string[];
    }): MemoryRecord;
    recall(query: {
      sessionId?: string;
      userId?: string;
      kind?: MemoryKind;
      limit?: number;
    }): MemoryRecord[];
  };

  search: {
    search(query: string, limit?: number): Promise<SearchResult[]>;
  };

  reasoning: {
    analyze(input: {
      question: string;
      facts?: string[];
    }): Promise<ReasoningResult>;
  };

  planning: {
    createPlan(goal: string, taskTitles: string[]): Plan;
  };
};
```

```

    writing: {
      draft(input: {
        prompt: string;
        tone?: WritingTone;
        maxLength?: number;
      }): Promise<WritingResult>;
    };
  }
}

```

src/lib/bud/config.ts

```

/**
 * Static configuration only. No behavior lives here – these are just
 * the knobs the orchestrator reads.
 */

export interface BudLimits {
  /** Max prior memory records recalled per turn. */
  memoryRecallLimit: number;
  /** Max knowledge/search results considered per turn. */
  knowledgeSearchLimit: number;
}

export const DEFAULT_BUD_LIMITS: BudLimits = {
  memoryRecallLimit: 10,
  knowledgeSearchLimit: 5,
};

export interface BudConfigOptions {
  name?: string;
  limits?: Partial<BudLimits>;
}

export function resolveLimits(overrides?: Partial<BudLimits>): BudLimits {
  return { ...DEFAULT_BUD_LIMITS, ...overrides };
}

```

src/lib/bud/context/buildContext.ts

```

import type { BudSparkPort } from "../../adapters/sparkPort";
import type { BudSession } from "../../types";

export interface ConversationContext {
  sessionId: string;
  userId: string;
  product: string;
}

/**
 * Ensures Spark has an identity context for this session (creating one
 * on first contact) and returns the minimal context the rest of the

```

```

    * orchestration needs. Bud does not track identity itself – Spark owns
    * that state.
    */
export function buildContext(
  spark: BudSparkPort,
  session: BudSession
): ConversationContext {
  const existing = spark.identity.getContext(session.sessionId);

  if (!existing) {
    spark.identity.createContext({
      userId: session.userId,
      sessionId: session.sessionId,
      product: session.product,
      locale: session.locale,
      timezone: session.timezone,
    });
  }

  return {
    sessionId: session.sessionId,
    userId: session.userId,
    product: session.product,
  };
}

```

src/lib/bud/conversation.ts

```

import type { BudSparkPort } from "../adapters/sparkPort";
import type { MemoryRecord } from "../spark/memory/interface";
import type { ConversationTurn, BudMessage } from "../types";

/**
 * Bud keeps no conversation store of its own. This module only reads
 * back what Spark already has in episodic memory and reshapes it into
 * a transcript. If Spark's memory is cleared, the transcript is gone –
 * there is no separate copy living in Bud.
 */
export function getTranscript(
  spark: BudSparkPort,
  sessionId: string,
  limit = 50
): ConversationTurn[] {
  const records = spark.memory
    .recall({ sessionId, kind: "episodic", limit: limit * 2 })
    .slice()
    .reverse(); // recall() returns newest-first; transcripts read oldest-first

  const turns: ConversationTurn[] = [];
  let pendingUser: BudMessage | null = null;

  for (const record of records) {
    const message = toMessage(record);
    if (message.role === "user") {
      pendingUser = message;
    }
  }
}

```

```

    } else if (pendingUser) {
      turns.push({ user: pendingUser, bud: message });
      pendingUser = null;
    }
  }

  return turns;
}

function toMessage(record: MemoryRecord): BudMessage {
  const isUser = record.tags?.includes("user");
  const content = record.content.replace(/^(User|Bud):\s*/, "");
  return {
    role: isUser ? "user" : "bud",
    content,
    timestamp: record.createdAt,
  };
}

```

src/lib/bud/index.ts

```

/**
 * Public Bud SDK.
 *
 * Consumers should only ever import from here:
 *
 * import { createBud } from "@lib/bud";
 *
 * Never import from bud/orchestrator, bud/actions/*, bud/adapters/*,
 * etc. directly – those are internal implementation detail.
 */

import { createSpark, type Spark } from "../spark";
import { createLiveSparkAdapter } from "../adapters/liveSparkAdapter";
import type { BudSparkPort } from "../adapters/sparkPort";
import { createPersonality, type BudPersonality } from "../personality";
import { resolveLimits, type BudLimits } from "../config";
import { orchestrateRespond } from "../orchestrator";
import { getTranscript } from "../conversation";
import type { BudResponse, BudSession, ConversationTurn } from "../types";

export interface BudConfig {
  /** Provide an existing Spark instance to share it across products; otherwise Bud creates its own. */
  spark?: Spark;
  personality?: Partial<BudPersonality>;
  limits?: Partial<BudLimits>;
}

export interface Bud {
  respond(message: string, session: BudSession): Promise<BudResponse>;
  transcript(sessionId: string, limit?: number): ConversationTurn[];
  readonly personality: BudPersonality;
}

export function createBud(config: BudConfig = {}): Bud {

```

```

const spark = config.spark ?? createSpark();
const sparkPort: BudSparkPort = createLiveSparkAdapter(spark);
const personality = createPersonality(config.personality);
const limits = resolveLimits(config.limits);

return {
  personality,

  async respond(message: string, session: BudSession): Promise<BudResponse> {
    return orchestrateRespond(sparkPort, personality, limits, message, session);
  },

  transcript(sessionId: string, limit?: number): ConversationTurn[] {
    return getTranscript(sparkPort, sessionId, limit);
  },
};
}

export type { BudSession, BudResponse, BudMessage, ConversationTurn } from "./types";
export type { BudPersonality } from "./personality";
export type { BudLimits } from "./config";

```

src/lib/bud/orchestrator.ts

```

import type { BudSparkPort } from "./adapters/sparkPort";
import type { BudPersonality } from "./personality";
import type { BudLimits } from "./config";
import type { BudResponse, BudSession } from "./types";
import { buildContext } from "./context/buildContext";
import { recallMemory } from "./actions/recallMemory";
import { searchKnowledge } from "./actions/searchKnowledge";
import { reason } from "./actions/reason";
import { planIfNeeded } from "./actions/planIfNeeded";
import { generateResponse } from "./actions/generateResponse";
import { storeInteraction } from "./actions/storeInteraction";

/**
 * The entire orchestration Bud performs, in order:
 *
 * 1. Build conversation context (ensure Spark identity exists)
 * 2. Recall memory from Spark
 * 3. Search Spark's knowledge
 * 4. Ask Spark to reason over message + recalled facts
 * 5. Mechanically detect multi-step requests and hand planning to Spark
 * 6. Ask Spark to draft the final response text
 * 7. Store the turn back through Spark memory
 *
 * Every step above calls into `spark` (a BudSparkPort) and nothing else.
 * There is no branch here that reasons about content, generates text
 * itself, or calls a provider – that's the point.
 */
export async function orchestrateRespond(
  spark: BudSparkPort,
  personality: BudPersonality,
  limits: BudLimits,

```

```

    message: string,
    session: BudSession
  ): Promise<BudResponse> {
    const context = buildContext(spark, session);

    const memoryRecords = recallMemory(
      spark,
      context.sessionId,
      limits.memoryRecallLimit
    );

    const knowledgeResults = await searchKnowledge(
      spark,
      message,
      limits.knowledgeSearchLimit
    );

    const reasoning = await reason(spark, message, memoryRecords, knowledgeResults);

    const plan = planIfNeeded(spark, message);

    const writing = await generateResponse(spark, personality, {
      message,
      memoryRecords,
      knowledgeResults,
      reasoning,
    });

    storeInteraction(spark, {
      sessionId: context.sessionId,
      userId: context.userId,
      userMessage: message,
      budMessage: writing.text,
    });

    return {
      message: writing.text,
      sessionId: context.sessionId,
      trace: {
        memoryHits: memoryRecords.length,
        knowledgeHits: knowledgeResults.length,
        reasoningConfidence: reasoning.confidence,
        plannedTaskCount: plan?.tasks.length ?? 0,
        provider: writing.provider,
      },
    };
  }
}

```

src/lib/bud/personality.ts

```

/**
 * Personality is pure configuration: a name, a tone, and a short
 * description used to build prompts. It contains no logic and makes
 * no decisions — it's data that prompts/systemPrompt.ts reads.
 */

```

```

import type { WritingTone } from "../spark/intelligence/writing/interface";

export interface BudPersonality {
  name: string;
  description: string;
  tone: WritingTone;
  /** Short first-person guidance folded into the system prompt. */
  voice: string[];
}

export const DEFAULT_BUD_PERSONALITY: BudPersonality = {
  name: "Bud",
  description: "A supportive, plain-spoken companion.",
  tone: "casual",
  voice: [
    "Keep answers short and easy to act on.",
    "Be encouraging without being saccharine.",
    "Say plainly when you don't know something.",
  ],
};

export function createPersonality(
  overrides?: Partial<BudPersonality>
): BudPersonality {
  return { ...DEFAULT_BUD_PERSONALITY, ...overrides };
}

```

src/lib/bud/prompts/systemPrompt.ts

```

import type { BudPersonality } from "../personality";

/**
 * Pure string assembly from static personality configuration. No
 * decision-making happens here – this is a template, not a model.
 */
export function buildSystemPrompt(personality: BudPersonality): string {
  return [
    `You are ${personality.name}. ${personality.description}`,
    ...personality.voice.map((line) => `- ${line}`),
  ].join("\n");
}

```

src/lib/bud/prompts/userPrompt.ts

```

import type { ReasoningResult } from "../../spark/core/reasoning/interface";
import type { MemoryRecord } from "../../spark/memory/interface";
import type { SearchResult } from "../../spark/intelligence/search/interface";

/**
 * Assembles the prompt handed to Spark.writing.draft(). All of the
 * "thinking" was already done by Spark (reasoning, search, memory) –

```

```

    * this just formats it into text for the writing step.
    */
export function buildUserPrompt(input: {
  message: string;
  memoryRecords: MemoryRecord[];
  knowledgeResults: SearchResult[];
  reasoning: ReasoningResult;
}): string {
  const { message, memoryRecords, knowledgeResults, reasoning } = input;

  const sections = [`User said: "${message}"`, `Spark's analysis: ${reasoning.answer}`];

  if (memoryRecords.length) {
    sections.push(
      `Relevant memory:\n${memoryRecords.map((m) => `- ${m.content}`).join("\n")}`
    );
  }

  if (knowledgeResults.length) {
    sections.push(
      `Relevant knowledge:\n${knowledgeResults
        .map((k) => `- ${k.title}: ${k.snippet}`)
        .join("\n")}`
    );
  }

  sections.push("Reply to the user directly, in one short response.");

  return sections.join("\n\n");
}

```

src/lib/bud/types.ts

```

/**
 * Bud never defines its own memory, reasoning, or knowledge types -
 * those belong to Spark. This file only defines the shapes Bud needs
 * for orchestration: sessions, messages, and the final response.
 */

export interface BudSession {
  sessionId: string;
  userId: string;
  /** The product Bud is embedded in (e.g. "unibud", "campus"). Passed through to Spark's Identity/Con
  product: string;
  locale?: string;
  timezone?: string;
}

export interface BudMessage {
  role: "user" | "bud";
  content: string;
  timestamp: string;
}

export interface BudResponse {

```



```

message: string;
sessionId: string;
/** Surfaced for debugging/observability - never re-derived by Bud itself. */
trace: {
  memoryHits: number;
  knowledgeHits: number;
  reasoningConfidence: number;
  plannedTaskCount: number;
  provider: string;
};
}

export interface ConversationTurn {
  user: BudMessage;
  bud: BudMessage;
}

```

UNIBUD — Dashboard, Assignments, Design System

scripts/unibud-verify.ts

```

import { createSpark } from "../src/lib/spark";
import { createBud } from "../src/lib/bud";
import { assembleDashboard, setGoals } from "../src/lib/unibud";

async function main() {
  const spark = createSpark();
  await spark.initialize();
  const bud = createBud({ spark, personality: { name: "Bud", tone: "casual" } });

  const session = { sessionId: "unibud_s1", userId: "student_1", product: "unibud" };

  console.log("--- Dashboard with no stated goals yet ---");
  const first = await assembleDashboard(spark, bud, session);
  console.log(JSON.stringify(first, null, 2));
  if (first.suggestedToolId !== null) {
    throw new Error("Expected no suggestion before any goals are set.");
  }

  console.log("\n--- Student sets a goal, asks a real question ---");
  setGoals(spark, session.userId, ["grades", "review"]);
  const second = await assembleDashboard(
    spark,
    bud,
    session,
    "I have a chemistry exam next week, what should I focus on?"
  );
  console.log(JSON.stringify(second, null, 2));

  if (!second.suggestedToolId) {
    throw new Error("Expected a suggested tool once goal tags are set.");
  }
  if (!["study_plans", "assignments"].includes(second.suggestedToolId)) {
    throw new Error(

```

```

        `Expected study_plans or assignments to rank highest for ["grades","review"], got ${second.sugge
    );
}

console.log("\n--- Transcript is readable straight from Bud/Spark, UNIBUD stores nothing of its own
console.log(bud.transcript(session.sessionId));

await spark.shutdown();
console.log("\nUNIBUD dashboard verification completed successfully.");
}

main().catch((err) => {
    console.error("UNIBUD verification failed:", err);
    throw err;
});

```

scripts/assignments-verify.ts

```

import { createSpark } from "../src/lib/spark";
import { createBud } from "../src/lib/bud";
import {
    AssignmentService,
    InMemoryAssignmentRepository,
    getAssignmentsDashboardData,
    respondWithAssignmentAwareness,
    createAssignmentsCollectionRoutes,
    createAssignmentItemRoutes,
    AssignmentNotFoundError,
} from "../src/lib/unibud/assignments";
import { assembleDashboard } from "../src/lib/unibud";

let failures = 0;
function check(label: string, condition: boolean) {
    if (condition) {
        console.log(` ok - ${label}`);
    } else {
        failures++;
        console.log(` FAIL - ${label}`);
    }
}

async function main() {
    const spark = createSpark();
    await spark.initialize();
    const bud = createBud({ spark, personality: { name: "Bud", tone: "casual" } });
    const repository = new InMemoryAssignmentRepository();
    const service = new AssignmentService(spark, repository);

    const session = { sessionId: "assign_s1", userId: "student_42", product: "unibud" };

    // -----
    console.log("\n--- 1. AssignmentService.createAssignment (+ Spark analysis/planning) ---");
    const created = await service.createAssignment({
        userId: session.userId,
        title: "Cell Biology Lab Report",

```

```

    description:
      "Submit a full lab report on mitosis. Include chapter 4 references and pp. 112-118. Due after th
course: "BIO201",
dueDate: new Date(Date.now() + 3 * 24 * 60 * 60 * 1000).toISOString(),
priority: "high",
tags: ["lab", "biology"],
});

check("assignment has an id", typeof created.id === "string" && created.id.length > 0);
check("status starts not_started", created.status === "not_started");
check(
  "Spark reasoning populated an objective",
  typeof created.analysis?.objective === "string" && created.analysis.objective.length > 0
);
check(
  "Spark planning produced a task breakdown",
  created.extractedTasks.length >= 2
);
check("planId was recorded", typeof created.planId === "string");
check(
  "deliverables were extracted from the description",
  created.analysis!.deliverables.length > 0
);
check(
  "references were extracted (chapter/page pattern)",
  created.extractedReferences.some((r) => /chapter|pp\./i.test(r))
);
check(
  "estimated workload is a positive number",
  created.analysis!.estimatedWorkloadHours > 0
);

const memoryHits = spark.memory.recall({ userId: session.userId, tag: "assignment" });
check("assignment was stored through Spark memory", memoryHits.length >= 2);

// -----
console.log("\n--- 2. AssignmentService CRUD ---");
const fetched = await service.getAssignment(created.id);
check("getAssignment returns the same assignment", fetched.id === created.id);

const updated = await service.updateAssignment(created.id, { priority: "urgent" });
check("updateAssignment changes fields", updated.priority === "urgent");

const listed = await service.listAssignments({ userId: session.userId });
check("listAssignments finds it", listed.some((a) => a.id === created.id));

const completed = await service.completeAssignment(created.id);
check("completeAssignment sets status", completed.status === "completed");

let notFoundThrew = false;
try {
  await service.getAssignment("does-not-exist");
} catch (err) {
  notFoundThrew = err instanceof AssignmentNotFoundError;
}
check("getAssignment throws AssignmentNotFoundError for missing id", notFoundThrew);

```

```

await service.deleteAssignment(created.id);
let afterDeleteThrew = false;
try {
  await service.getAssignment(created.id);
} catch (err) {
  afterDeleteThrew = err instanceof AssignmentNotFoundError;
}
check("deleteAssignment actually removes it", afterDeleteThrew);

// -----
console.log("\n--- 3. Bud orchestration through the assignment-aware assistant ---");

const createReply = await respondWithAssignmentAwareness(
  spark,
  bud,
  service,
  "I have a new assignment. Title: History Essay; Course: HIST101; Due: " +
    new Date(Date.now() + 5 * 24 * 60 * 60 * 1000).toISOString() +
    "; Description: Write about the causes of the war. Submit as a PDF.",
  session
);
check("assistant recognized create intent", createReply.intent === "create");
check("assistant actually created the assignment", !!createReply.assignment);
check("assistant's reply came from Bud (non-empty message)", createReply.message.length > 0);

const incompleteReply = await respondWithAssignmentAwareness(
  spark,
  bud,
  service,
  "I have a new assignment.",
  session
);
check(
  "assistant asks for missing fields instead of fabricating an assignment",
  incompleteReply.intent === "create" && !incompleteReply.assignment
);

const dueSoonReply = await respondWithAssignmentAwareness(
  spark,
  bud,
  service,
  "What assignments are due this week?",
  session
);
check("assistant recognized list_due_soon intent", dueSoonReply.intent === "list_due_soon");
check("assistant returned the assignments list", Array.isArray(dueSoonReply.assignments));

const continueReply = await respondWithAssignmentAwareness(
  spark,
  bud,
  service,
  "Continue my project.",
  session
);
check("assistant recognized continue_work intent", continueReply.intent === "continue_work");

const unrelatedReply = await respondWithAssignmentAwareness(

```

```

    spark,
    bud,
    service,
    "What's the weather like on Mars?",
    session
);
check(
    "unrelated messages pass straight through to Bud unchanged",
    unrelatedReply.intent === "none"
);

// -----
console.log("\n--- 4. Dashboard integration (real data, not placeholders) ---");
const assignmentsDashboard = await getAssignmentsDashboardData(spark, service, session.userId);
check(
    "dashboard reports upcoming assignments",
    assignmentsDashboard.upcoming.length >= 1
);
check(
    "dashboard reports estimated workload as a number",
    typeof assignmentsDashboard.estimatedWorkloadHours === "number"
);

const fullDashboard = await assembleDashboard(
    spark,
    bud,
    session,
    "What should I work on?",
    service
);
check(
    "top-level UNIBUD dashboard includes real assignment stats",
    fullDashboard.assignments !== undefined &&
    fullDashboard.assignments.upcoming === assignmentsDashboard.upcoming.length
);

// -----
console.log("\n--- 5. API route handlers ---");
const collectionRoutes = createAssignmentsCollectionRoutes(service);
const itemRoutes = createAssignmentItemRoutes(service);

const postRes = await collectionRoutes.POST(
    new Request("http://localhost/assignments", {
        method: "POST",
        body: JSON.stringify({
            userId: session.userId,
            title: "Chem Problem Set 4",
            description: "Solve problems 1-10. Submit via the portal.",
            course: "CHEM110",
            dueDate: new Date(Date.now() + 2 * 24 * 60 * 60 * 1000).toISOString(),
        })
    })
);
check("POST /assignments returns 201", postRes.status === 201);
const posted = await postRes.json();
check("POST /assignments returns a created assignment", posted.id != null);

```

```

const getRes = await collectionRoutes.GET(
  new Request(`http://localhost/assignments?userId=${session.userId}`)
);
check("GET /assignments returns 200", getRes.status === 200);
const listBody = await getRes.json();
check("GET /assignments returns an array", Array.isArray(listBody));

const getOneRes = await itemRoutes.GET(new Request("http://localhost/assignments/x"), {
  params: { id: posted.id },
});
check("GET /assignments/:id returns 200", getOneRes.status === 200);

const patchRes = await itemRoutes.PATCH(
  new Request("http://localhost/assignments/x", {
    method: "PATCH",
    body: JSON.stringify({ status: "completed" }),
  }),
  { params: { id: posted.id } }
);
check("PATCH /assignments/:id with status=completed returns 200", patchRes.status === 200);
const patched = await patchRes.json();
check("PATCH actually completed it via completeAssignment()", patched.status === "completed");

const deleteRes = await itemRoutes.DELETE(new Request("http://localhost/assignments/x"), {
  params: { id: posted.id },
});
check("DELETE /assignments/:id returns 204", deleteRes.status === 204);

const getMissingRes = await itemRoutes.GET(new Request("http://localhost/assignments/x"), {
  params: { id: "not-a-real-id" },
});
check("GET /assignments/:id returns 404 for a missing id", getMissingRes.status === 404);

const badPostRes = await collectionRoutes.POST(
  new Request("http://localhost/assignments", {
    method: "POST",
    body: JSON.stringify({ userId: session.userId }), // missing required fields
  })
);
check("POST /assignments returns 400 for invalid input", badPostRes.status === 400);

// -----
await spark.shutdown();

console.log(`\n${failures === 0 ? "ALL CHECKS PASSED" : `${failures} CHECK(S) FAILED`}`);
if (failures > 0) {
  throw new Error(`${failures} assignment integration check(s) failed.`);
}
}

main().catch((err) => {
  console.error("Assignments integration test failed:", err);
  throw err;
});

```

scripts/design-system-verify.ts

```
import {
  color,
  theme,
  contrastRatio,
  wcagLevel,
  glassSurfaceStyle,
  floatingCardStyle,
  focusRingStyle,
  statusBadgeStyle,
  motionSafeTransition,
  checkBudVoiceCompliance,
  motionPresets,
  renderMotionPresetCSS,
  BUD_PRESENCE,
  formatMemoryIndicator,
  describeSparkStatus,
  describeActiveProvider,
} from "../src/lib/unibud/design";
import { createSpark } from "../src/lib/spark";

let failures = 0;
function check(label: string, condition: boolean) {
  if (condition) {
    console.log(` ok - ${label}`);
  } else {
    failures++;
    console.log(` FAIL - ${label}`);
  }
}

async function main() {
  console.log("--- Contrast ratios actually used by the theme ---");

  const darkPrimaryRatio = contrastRatio(theme.dark.textPrimary, theme.dark.background);
  console.log(` dark textPrimary/background: ${darkPrimaryRatio.toFixed(2)}:1 (${wcagLevel(darkPrimaryRatio)});
  check("dark theme primary text meets at least AA", wcagLevel(darkPrimaryRatio) !== "fail");

  const darkSecondaryRatio = contrastRatio(theme.dark.textSecondary, theme.dark.background);
  console.log(` dark textSecondary/background: ${darkSecondaryRatio.toFixed(2)}:1 (${wcagLevel(darkSecondaryRatio)});
  check("dark theme secondary text meets at least AA", wcagLevel(darkSecondaryRatio) !== "fail");

  const lightPrimaryRatio = contrastRatio(theme.light.textPrimary, theme.light.background);
  console.log(` light textPrimary/background: ${lightPrimaryRatio.toFixed(2)}:1 (${wcagLevel(lightPrimaryRatio)});
  check("light theme primary text meets at least AA", wcagLevel(lightPrimaryRatio) !== "fail");

  for (const status of ["success", "warning", "error", "info"] as const) {
    const ratio = contrastRatio(color.semantic[status], theme.dark.background);
    console.log(` ${status} accent/dark background: ${ratio.toFixed(2)}:1 (${wcagLevel(ratio, true)});
    check(`${status} accent meets at least AA for large text/icons on dark`, wcagLevel(ratio, true) !== "fail");
  }

  // Known, deliberately-flagged case: a known-bad pairing must actually fail.
  const knownBad = contrastRatio(color.gray[500], color.gray[400]);
  check("contrastRatio correctly flags a low-contrast gray-on-gray pairing as fail", wcagLevel(knownBad) !== "fail");
}
```

```

console.log("\n--- Style generators return real values (not empty stubs) ---");
const glass = glassSurfaceStyle("dark");
check("glassSurfaceStyle returns a backdropFilter", typeof glass.backdropFilter === "string" && glas

const card = floatingCardStyle("dark");
const cardElevated = floatingCardStyle("dark", true);
check("floatingCardStyle elevated state differs from base state", card.boxShadow !== cardElevated.bo

const focus = focusRingStyle("dark");
check("focusRingStyle never returns 'none'", focus.outline !== "none");

const badge = statusBadgeStyle("error");
check("statusBadgeStyle uses the semantic error color", badge.color === color.semantic.error);

const motionOn = motionSafeTransition("transform", false);
const motionOff = motionSafeTransition("transform", true);
check("motionSafeTransition respects prefers-reduced-motion", motionOff.transition === "none" && mot

console.log("\n--- Bud voice compliance checker ---");
const goodLine = "Let's break it into smaller pieces.";
const badLine = "As an AI, I don't have feelings, but I can help.";
check("a compliant line passes", checkBudVoiceCompliance(goodLine).compliant);
check("a non-compliant line is caught", !checkBudVoiceCompliance(badLine).compliant);
check(
  "violations list is non-empty for the bad line",
  checkBudVoiceCompliance(badLine).violations.length > 0
);

console.log("\n--- Gold token is reserved and distinct from semantic status colors ---");
check("gold is not equal to any semantic status color", ![
  color.semantic.success,
  color.semantic.warning,
  color.semantic.error,
  color.semantic.info,
].map((c) => c as string).includes(color.gold as string));
const goldOnDark = contrastRatio(color.gold, theme.dark.background);
console.log(` gold/dark background: ${goldOnDark.toFixed(2)}:1 (${wcagLevel(goldOnDark, true)})`);
check("gold meets at least AA for large text/icons on dark", wcagLevel(goldOnDark, true) !== "fail")

console.log("\n--- Motion presets ---");
check("all 5 named presets exist", Object.keys(motionPresets).length === 5);
for (const [key, preset] of Object.entries(motionPresets)) {
  const css = renderMotionPresetCSS(preset);
  check(`${key} preset renders a @keyframes block`, css.includes("@keyframes"));
  check(`${key} preset respects prefers-reduced-motion`, css.includes("prefers-reduced-motion"));
}
const presetNames = Object.values(motionPresets).map((p) => p.name);
check("no duplicate preset names (no redefinition risk)", new Set(presetNames).size === presetNames.

console.log("\n--- Bud presence states ---");
check("all 4 presence states are defined", ["idle", "listening", "thinking", "speaking"].every(
  (s) => s in BUD_PRESENCE
));
check("every presence state has a non-empty accessible label", Object.values(BUD_PRESENCE).every(
  (p) => p.accessibleLabel.length > 0
));

```



```

console.log("\n--- Memory indicator uses REAL Bud trace data ---");
const zeroTrace = { memoryHits: 0, knowledgeHits: 0, reasoningConfidence: 0, plannedTaskCount: 0, pr
const realTrace = { memoryHits: 2, knowledgeHits: 1, reasoningConfidence: 0.6, plannedTaskCount: 3,
check("empty trace produces no indicator (never fabricates activity)", formatMemoryIndicator(zeroTra
const indicator = formatMemoryIndicator(realTrace);
check("non-empty trace produces a grounded indicator string", indicator !== null && indicator.includ
check("indicator reflects the plan step count from the real trace", indicator!.includes("3-step plan

console.log("\n--- Spark presence reflects a REAL spark.health() call ---");
const spark = createSpark();
await spark.initialize();
const health = spark.health();
const status = describeSparkStatus(health);
const activeProvider = describeActiveProvider(health);
console.log(` ${status}`);
check("describeSparkStatus mentions the actual active provider", status.includes(activeProvider.name
check("describeActiveProvider correctly identifies the mock provider as non-real AI", activeProvider
await spark.shutdown();

console.log(`\n${failures === 0 ? "ALL CHECKS PASSED" : `${failures} CHECK(S) FAILED`}`);
if (failures > 0) {
    throw new Error(`${failures} design system check(s) failed.`);
}
}

main().catch((err) => {
    console.error("Design system verification failed:", err);
    throw err;
});

```

src/lib/unibud/assignments/ARCHITECTURE.md

Assignments – Architecture

The boundary decision this module had to make

The brief for this module asked for two things that can't both be true inside Bud's package at the same time:

1. "Bud should understand requests like 'I have a new assignment'... Bud should only orchestrate these requests through Spark and the AssignmentService."
2. "Bud never imports UNIBUD" and "Bud must not contain assignment business logic" (both hard, pre-existing architecture rules).

`AssignmentService` lives in UNIBUD. If Bud is the thing recognizing "I have a new assignment" and calling `AssignmentService`, Bud has to import UNIBUD – which rule (2) forbids.

****Resolution:**** recognition and routing live in UNIBUD
 (`assistant.ts`'s `respondWithAssignmentAwareness()`), not inside Bud's package. This function sits in front of Bud:

- Bud itself is ****completely unmodified**** – same files, same public API, as verified by every pre-existing test (`smoke-test`,

```
`bud-verify`, `container-verify`, `unibud-verify`) still passing unchanged.
```

- For any message that isn't assignment-related, `respondWithAssignmentAwareness()` is a pure passthrough to `bud.respond()` – behavior for every other kind of request is identical to before this module existed.
- For assignment-related messages, UNIBUD's own mechanical intent detector (`intents.ts` – regex-based, same style as Bud's own `planIfNeeded`) recognizes the request, UNIBUD calls `AssignmentService` for the actual work, and Bud is still called afterward – but only to phrase the result in its voice. Bud never sees an assignment-specific code path; it just gets a message to respond to, the same as always.

This keeps every hard rule intact: Spark doesn't import Bud or UNIBUD, Bud doesn't import UNIBUD, and Bud contains zero assignment logic. The thing that changes is *what* calls Bud*, not Bud itself.

```
## Request flow – conversational path (through Bud)
```

Student | “I have a new assignment. Title: ... Course: ... Due: ... Description: ...” ▼ UNIBUD Dashboard / chat surface | ▼ UNIBUD AssignmentAssistant (assistant.ts) | 1. detectAssignmentIntent() – mechanical, UNIBUD-owned | 2. parseAssignmentFields() – mechanical, UNIBUD-owned |

| **AssignmentService.createAssignment() || - spark.reasoning.analyze() → objective || - deterministic extraction → deliverables, || dates, references, missing info, workload || - spark.planning.createPlan() → task breakdown || - spark.memory.remember() → stored context | ▼ | AssignmentRepository (InMemoryAssignmentRepository) || insert() | ▼ | Storage (in-memory Map; swappable for a real DB later) || |**

▼ Bud.respond(“The student just created ... confirm this briefly”) | - spark.memory.recall(), spark.search.search(), | spark.reasoning.analyze(), spark.writing.draft() | (Bud's own unmodified internal pipeline) ▼ Response phrased in Bud's voice, returned to the student

```
## Request flow – direct API path (no Bud)
```

The REST routes are a separate, non-conversational entry point into the same service – a form submission doesn't need a companion's voice:

Client (dashboard form, or any HTTP caller) | POST /assignments { title, course, dueDate, description, ... } ▼ routes/collection.ts POST() — thin HTTP <-> service translation only ▼ AssignmentService.createAssignment() — identical path/logic as above ▼ AssignmentRepository → Storage ▼ 201 Created, JSON body = the created Assignment

```
`GET /assignments`, `GET /assignments/:id`, `PATCH /assignments/:id`, and `DELETE /assignments/:id` follow the same shape: route handler → `AssignmentService` method → repository. No handler contains business logic; `AssignmentNotFoundError` / `AssignmentValidationError` map to 404 / 400 respectively.
```

```
## Why the repository exists
```

No database exists yet in this codebase. `AssignmentService` depends only on the `AssignmentRepository` interface (`insert`/`update`/`delete`/`findById`/`list`), never on `InMemoryAssignmentRepository` directly. Adding a real database later means writing one new class against that interface – the service, the assistant, the dashboard, and every route handler are unaffected.

Verified boundaries (final audit)

Checked directly, not assumed:

- **Spark stays product-agnostic** – `grep`ing Spark's source for "assignment", "Bud", or "UNIBUD" returns nothing. Spark's public API (`spark.memory`, `spark.reasoning`, `spark.planning`, `spark.learning`) is called by `AssignmentService` exactly as any other consumer would call it.
- **Bud stays product-agnostic and unmodified** – no file under `src/lib/bud/` was touched in this phase. `bud-verify.ts` still passes with its original assertions, unchanged.
- **UNIBUD owns all student workflows** – the `Assignment` model, `AssignmentService`, intent detection, field parsing, dashboard stats, and API routes all live under `src/lib/unibud/assignments/`.
- **No existing public API broke** – `assembleDashboard()` gained one optional trailing parameter (`assignmentService?`) and one optional field on `DashboardViewModel` (`assignments?`); every prior call site and every prior test still works unchanged.
- **Builds and tests are green** – `tsc --noEmit` passes with zero errors; `smoke-test`, `container-verify`, `bud-verify`, `unibud-verify`, and the new `assignments-verify` (34 checks) all pass.

What this module does not do (by design, for this slice)

- No real AI provider – analysis quality is bounded by `MockProvider` plus deterministic extraction, same as the rest of Spark today.
- No free-form NLU assignment creation – the field parser requires an explicit `Field: value` convention rather than guessing at missing data.
- No database – `InMemoryAssignmentRepository` only.
- No Smart Notes, Projects, Campus, Connect, or Study Plans – out of scope for this phase by explicit instruction.

src/lib/unibud/assignments/README.md

Assignments – UNIBUD's first complete vertical slice

A student can create, edit, organize, complete, and revisit assignments. Every assignment is analyzed and broken into tasks by Spark at creation time. This module exists to validate the Spark → Bud → UNIBUD architecture against one real feature before any other module (Smart Notes, Projects, Campus, Connect, Study Plans) is started.

What's real here

- **service.ts** – `AssignmentService`: create/update/delete/get/list/complete,

calling ``spark.memory``, ``spark.reasoning``, ``spark.planning``, and ``spark.learning`` directly, plus a swappable repository for storage.

- `**`inMemoryRepository.ts`**` – the only repository implementation that exists today. Swapping in a real database means writing a new class against ``AssignmentRepository`` – nothing else changes.
- `**`assistant.ts`**` – recognizes assignment-related chat messages ("I have a new assignment", "what's due this week", "continue my project") and routes them to ``AssignmentService``, using ``bud.respond()`` only for the final phrasing. See ``ARCHITECTURE.md`` for why this file exists in UNIBUD rather than inside Bud.
- `**`dashboard.ts`**` – real upcoming/overdue/completed/workload/next-task numbers, wired into the top-level UNIBUD dashboard as an additive, optional field so no existing caller breaks.
- `**`routes/collection.ts`**` and `**`routes/item.ts`**` – Web-standard ``Request`/`Response`` handlers matching the Next.js App Router route handler signature. Drop them into ``app/api/assignments/route.ts`` and ``app/api/assignments/[id]/route.ts`` respectively.

Usage

```

```ts
import { createSpark } from "@lib/spark";
import { createBud } from "@lib/bud";
import {
 AssignmentService,
 InMemoryAssignmentRepository,
 respondWithAssignmentAwareness,
} from "@lib/unibud/assignments";

const spark = createSpark();
await spark.initialize();
const bud = createBud({ spark });
const service = new AssignmentService(spark, new InMemoryAssignmentRepository());

const session = { sessionId: "s1", userId: "u1", product: "unibud" };

const reply = await respondWithAssignmentAwareness(
 spark,
 bud,
 service,
 "I have a new assignment. Title: Essay; Course: HIST101; Due: 2026-08-01; Description: Write 5 pages",
 session
);

console.log(reply.message); // Bud's phrased confirmation
console.log(reply.assignment); // the created Assignment, with Spark's analysis + task breakdown

```

For non-conversational access (a form in the UI, not chat), call `AssignmentService` directly or hit the REST routes — Bud is not required to create or manage an assignment.

## What's still a placeholder

- `AssignmentService` 's "reasoning" and "task breakdown" quality is only as good as Spark's current `MockProvider` plus deterministic regex extraction ( `service.ts` 's helper functions). It works and is tested, but it isn't real language understanding yet — that upgrades for free once a real `AIProvider` is registered

with Spark.

- The field parser ( `fieldParser.ts` ) requires an explicit `Field: value` chat convention to create an assignment from a message. Free-form natural language creation isn't implemented — see `ARCHITECTURE.md` for why guessing was rejected in favor of asking.
- No real database. `InMemoryAssignmentRepository` resets on restart.

See `ARCHITECTURE.md` for the full request flow, the sequence diagram, and the specific architectural boundary decision this module had to make.

```
`src/lib/unibud/assignments/assistant.ts`

```ts
import type { Spark } from "../../spark";
import type { Bud, BudSession } from "../../bud";
import type { AssignmentService } from "../service";
import type { Assignment } from "../types";
import { detectAssignmentIntent } from "../intents";
import { parseAssignmentFields, missingFieldNames } from "../fieldParser";

/**
 * IMPORTANT — architectural note:
 *
 * The brief asks for "Bud should understand requests like 'I have a
 * new assignment'" while also requiring that Bud never import UNIBUD
 * and contain no assignment business logic. Those two constraints
 * can't both be satisfied *inside the Bud package* — something has to
 * recognize assignment intent and call AssignmentService, and it
 * can't be Bud itself without Bud importing UNIBUD.
 *
 * Resolution: this file — AssignmentAssistant — lives in UNIBUD, sits
 * in front of Bud, and does the recognizing. Bud's package is
 * completely unmodified and still knows nothing about assignments.
 * When a message isn't assignment-related, this assistant is a pure
 * passthrough to `bud.respond()` — Bud's normal behavior is untouched
 * for every other kind of message. When it *is* assignment-related,
 * this assistant calls AssignmentService directly for the actual work,
 * then still calls `bud.respond()` (with a summary of what happened)
 * so the final reply is phrased in Bud's voice through Spark's writing
 * service — Bud still does the only thing it's allowed to do: talk.
 */

export interface AssignmentAssistantResult {
  message: string;
  intent: "create" | "list_due_soon" | "continue_work" | "none";
  assignment?: Assignment;
  assignments?: Assignment[];
}

export async function respondWithAssignmentAwareness(
  spark: Spark,
  bud: Bud,
  service: AssignmentService,
  message: string,
  session: BudSession
```

```

): Promise<AssignmentAssistantResult> {
  const intent = detectAssignmentIntent(message);

  if (intent.kind === "none") {
    const reply = await bud.respond(message, session);
    return { message: reply.message, intent: "none" };
  }

  if (intent.kind === "create") {
    const fields = parseAssignmentFields(message);
    const missing = missingFieldNames(fields);

    if (missing.length > 0) {
      const reply = await bud.respond(
        `The student wants to create a new assignment but hasn't given: ${missing.join(
          ", "
        )}. Ask for exactly that, briefly.` ,
        session
      );
      return { message: reply.message, intent: "create" };
    }

    const assignment = await service.createAssignment({
      userId: session.userId,
      title: fields.title!,
      course: fields.course!,
      dueDate: new Date(fields.dueDate!).toISOString(),
      description: fields.description ?? "",
    });

    const reply = await bud.respond(
      `The student just created the assignment "${assignment.title}" for ${assignment.course}, due ${a
        session
      );

    return { message: reply.message, intent: "create", assignment };
  }

  if (intent.kind === "list_due_soon") {
    const now = new Date();
    const weekOut = new Date(now.getTime() + 7 * 24 * 60 * 60 * 1000).toISOString();

    const assignments = await service.listAssignments({
      userId: session.userId,
      dueBefore: weekOut,
    });

    const summary = assignments.length
      ? assignments.map((a) => `${a.title} (${a.course}) due ${a.dueDate}`).join("; ")
      : "nothing due in the next 7 days";

    const reply = await bud.respond(
      `The student asked what's due this week. Here's what's due: ${summary}. Summarize it for them br
        session
      );

    return { message: reply.message, intent: "list_due_soon", assignments };
  }

```

```

    }

    // intent.kind === "continue_work"
    const inProgress = await service.listAssignments({
      userId: session.userId,
      status: "in_progress",
    });
    const notStarted = await service.listAssignments({
      userId: session.userId,
      status: "not_started",
    });
    const candidate = [...inProgress, ...notStarted][0];

    if (!candidate) {
      const reply = await bud.respond(
        "The student asked to continue an assignment, but they have none in progress. Let them know gent session
      );
      return { message: reply.message, intent: "continue_work" };
    }

    const nextTask = candidate.planId
      ? spark.planning.nextTask(candidate.planId)
      : undefined;

    const reply = await bud.respond(
      `The student wants to continue "${candidate.title}". ${
        nextTask
          ? `Their next task is: "${nextTask.title}".`
          : "All of its planned tasks are already done."
      } Tell them briefly what to do next.`,
      session
    );

    return { message: reply.message, intent: "continue_work", assignment: candidate };
  }
}

```

src/lib/unibud/assignments/dashboard.ts

```

import type { Spark } from "../../spark";
import type { AssignmentService } from "../service";
import type { Assignment } from "../types";

export interface AssignmentsDashboardData {
  upcoming: Assignment[];
  overdue: Assignment[];
  completed: Assignment[];
  progressPercent: number;
  estimatedWorkloadHours: number;
  nextRecommendedTaskTitle: string | null;
}

/**
 * Pulls real assignment data for the dashboard. This replaces the
 * placeholder "3 due this week" style stats that lived directly in the

```

```

    * dashboard UI - those numbers now come from AssignmentService/Spark.
    */
export async function getAssignmentsDashboardData(
    spark: Spark,
    service: AssignmentService,
    userId: string
): Promise<AssignmentsDashboardData> {
    const all = await service.listAssignments({ userId });
    const now = new Date();

    const overdue = all.filter(
        (a) => a.status !== "completed" && new Date(a.dueDate) < now
    );
    const completed = all.filter((a) => a.status === "completed");
    const upcoming = all.filter(
        (a) => a.status !== "completed" && new Date(a.dueDate) >= now
    );

    const progressPercent = all.length
        ? Math.round((completed.length / all.length) * 100)
        : 0;

    const estimatedWorkloadHours = upcoming.reduce(
        (sum, a) => sum + (a.analysis?.estimatedWorkloadHours ?? 0),
        0
    );

    const activeWithPlan = [...upcoming].sort(
        (a, b) => new Date(a.dueDate).getTime() - new Date(b.dueDate).getTime()
    )[0];

    const nextTask =
        activeWithPlan?.planId != null
            ? spark.planning.nextTask(activeWithPlan.planId)
            : undefined;

    return {
        upcoming,
        overdue,
        completed,
        progressPercent,
        estimatedWorkloadHours,
        nextRecommendedTaskTitle: nextTask?.title ?? null,
    };
}

```

src/lib/unibud/assignments/errors.ts

```

export class UnibudError extends Error {
    constructor(message: string) {
        super(message);
        this.name = new.target.name;
        Object.setPrototypeOf(this, new.target.prototype);
    }
}

```



```

export class AssignmentNotFoundError extends UnibudError {
  constructor(public readonly assignmentId: string) {
    super(`Assignment "${assignmentId}" was not found.`);
  }
}

export class AssignmentValidationError extends UnibudError {
  constructor(message: string) {
    super(message);
  }
}

```

src/lib/unibud/assignments/fieldParser.ts

```

/**
 * Until a real NLU/extraction provider is behind Spark.reasoning, we
 * can't reliably pull structured fields (title/course/due date) out of
 * free-form text. Rather than fabricate data, this parser looks for an
 * explicit "Field: value" convention the student (or a form in the UI)
 * provides, and returns null for anything it can't find – callers are
 * expected to ask for what's missing instead of guessing.
 */

export interface ParsedAssignmentFields {
  title: string | null;
  course: string | null;
  dueDate: string | null;
  description: string | null;
}

const FIELD_PATTERNS: Record<keyof ParsedAssignmentFields, RegExp> = {
  title: /title\s*:\s*(.+)/i,
  course: /course\s*:\s*(.+)/i,
  dueDate: /due(?:\s*date)?\s*:\s*(.+)/i,
  description: /description\s*:\s*(.+)/i,
};

export function parseAssignmentFields(message: string): ParsedAssignmentFields {
  const lines = message.split(/\n|;/).map((l) => l.trim());
  const result: ParsedAssignmentFields = {
    title: null,
    course: null,
    dueDate: null,
    description: null,
  };

  for (const line of lines) {
    for (const key of Object.keys(FIELD_PATTERNS) as Array<keyof ParsedAssignmentFields>) {
      const match = line.match(FIELD_PATTERNS[key]);
      if (match) result[key] = match[1].trim();
    }
  }

  return result;
}

```

```

}

export function missingFieldNames(fields: ParsedAssignmentFields): string[] {
  const missing: string[] = [];
  if (!fields.title) missing.push("title");
  if (!fields.course) missing.push("course");
  if (!fields.dueDate) missing.push("due date");
  return missing;
}

```

src/lib/unibud/assignments/inMemoryRepository.ts

```

import type { AssignmentRepository } from "../repository";
import type { Assignment, AssignmentListFilter } from "../types";

/**
 * Default repository until a real database is wired in. Holds no
 * Spark/Bud references and no business logic – it only stores and
 * queries Assignment records.
 */
export class InMemoryAssignmentRepository implements AssignmentRepository {
  private records = new Map<string, Assignment>();

  async insert(assignment: Assignment): Promise<Assignment> {
    this.records.set(assignment.id, assignment);
    return assignment;
  }

  async update(id: string, patch: Partial<Assignment>): Promise<Assignment | null> {
    const existing = this.records.get(id);
    if (!existing) return null;
    const updated: Assignment = { ...existing, ...patch, id: existing.id };
    this.records.set(id, updated);
    return updated;
  }

  async delete(id: string): Promise<boolean> {
    return this.records.delete(id);
  }

  async findById(id: string): Promise<Assignment | null> {
    return this.records.get(id) ?? null;
  }

  async list(filter: AssignmentListFilter): Promise<Assignment[]> {
    let results = Array.from(this.records.values()).filter(
      (a) => a.userId === filter.userId
    );

    if (filter.status) results = results.filter((a) => a.status === filter.status);
    if (filter.course) results = results.filter((a) => a.course === filter.course);
    if (filter.dueBefore)
      results = results.filter((a) => new Date(a.dueDate) <= new Date(filter.dueBefore!));
    if (filter.dueAfter)
      results = results.filter((a) => new Date(a.dueDate) >= new Date(filter.dueAfter!));
  }
}

```

```

    return results.sort(
      (a, b) => new Date(a.dueDate).getTime() - new Date(b.dueDate).getTime()
    );
  }
}

```

src/lib/unibud/assignments/index.ts

```

export { AssignmentService } from "../service";
export { InMemoryAssignmentRepository } from "../inMemoryRepository";
export type { AssignmentRepository } from "../repository";
export { getAssignmentsDashboardData } from "../dashboard";
export type { AssignmentsDashboardData } from "../dashboard";
export { respondWithAssignmentAwareness } from "../assistant";
export type { AssignmentAssistantResult } from "../assistant";
export { detectAssignmentIntent } from "../intents";
export type { AssignmentIntent } from "../intents";
export { createAssignmentsCollectionRoutes } from "../routes/collection";
export { createAssignmentItemRoutes } from "../routes/item";
export {
  AssignmentNotFoundError,
  AssignmentValidationError,
  UnibudError,
} from "../errors";
export type {
  Assignment,
  AssignmentPriority,
  AssignmentStatus,
  CreateAssignmentInput,
  UpdateAssignmentInput,
  AssignmentListFilter,
  ExtractedTask,
} from "../types";

```

src/lib/unibud/assignments/intents.ts

```

/**
 * Mechanical keyword/pattern matching, in the same spirit as Bud's own
 * `planIfNeeded` (regex-based, not semantic understanding). This lives
 * in UNIBUD, not Bud – Bud must not contain assignment business logic
 * or know these keywords exist.
 */

export type AssignmentIntent =
  | { kind: "create"; raw: string }
  | { kind: "list_due_soon"; raw: string }
  | { kind: "continue_work"; raw: string }
  | { kind: "none" };

const CREATE_PATTERN = /\b(new|got a|have an?)\s+assignment\b/i;
const DUE_SOON_PATTERN = /\bassignments?\b.*\b(due|deadline)\b|\bwhat's due\b/i;

```

```
const CONTINUE_PATTERN = /\b(continue|keep working on|resume)\b.*\b(assignment|project)\b/i;
```

```
export function detectAssignmentIntent(message: string): AssignmentIntent {
  if (CREATE_PATTERN.test(message)) return { kind: "create", raw: message };
  if (DUE_SOON_PATTERN.test(message)) return { kind: "list_due_soon", raw: message };
  if (CONTINUE_PATTERN.test(message)) return { kind: "continue_work", raw: message };
  return { kind: "none" };
}
```

src/lib/unibud/assignments/repository.ts

```
import type { Assignment, AssignmentListFilter } from "../types";

/**
 * AssignmentService depends only on this interface. Swapping the
 * in-memory implementation for a real database later means writing a
 * new class that satisfies this interface – the service, the API
 * routes, and Bud's orchestration path never change.
 */
export interface AssignmentRepository {
  insert(assignment: Assignment): Promise<Assignment>;
  update(id: string, patch: Partial<Assignment>): Promise<Assignment | null>;
  delete(id: string): Promise<boolean>;
  findById(id: string): Promise<Assignment | null>;
  list(filter: AssignmentListFilter): Promise<Assignment[]>;
}
```

src/lib/unibud/assignments/routes/collection.ts

```
import type { AssignmentService } from "../service";
import { AssignmentValidationError } from "../errors";
import type { AssignmentPriority } from "../types";

/**
 * Framework-agnostic Web-standard Request/Response handlers, written to
 * match the Next.js App Router route handler signature
 * (`export async function POST(request: Request)`), so these can be
 * dropped directly into `app/api/assignments/route.ts` in a real
 * Next.js app without any adaptation. They contain zero business logic
 * – every handler is a thin translation from HTTP to AssignmentService.
 */

function jsonResponse(body: unknown, status = 200): Response {
  return new Response(JSON.stringify(body), {
    status,
    headers: { "Content-Type": "application/json" },
  });
}

function ErrorResponse(err: unknown): Response {
  if (err instanceof AssignmentValidationError) {
    return jsonResponse({ error: err.message }, 400);
  }
}
```

```

    }
    return jsonResponse(
      { error: err instanceof Error ? err.message : "Unknown error" },
      500
    );
  }
}

export function createAssignmentsCollectionRoutes(service: AssignmentService) {
  return {
    async POST(request: Request): Promise<Response> {
      try {
        const body = await request.json();
        const assignment = await service.createAssignment({
          userId: body.userId,
          title: body.title,
          description: body.description ?? "",
          course: body.course,
          dueDate: body.dueDate,
          priority: body.priority as AssignmentPriority | undefined,
          tags: body.tags,
        });
        return jsonResponse(assignment, 201);
      } catch (err) {
        return errorResponse(err);
      }
    },

    async GET(request: Request): Promise<Response> {
      try {
        const url = new URL(request.url);
        const userId = url.searchParams.get("userId");
        if (!userId) {
          return jsonResponse({ error: "userId query parameter is required." }, 400);
        }
        const assignments = await service.listAssignments({
          userId,
          status: (url.searchParams.get("status") as never) ?? undefined,
          course: url.searchParams.get("course") ?? undefined,
          dueBefore: url.searchParams.get("dueBefore") ?? undefined,
          dueAfter: url.searchParams.get("dueAfter") ?? undefined,
        });
        return jsonResponse(assignments, 200);
      } catch (err) {
        return errorResponse(err);
      }
    },
  };
}
}

```

src/lib/unibud/assignments/routes/item.ts

```

import type { AssignmentService } from "../service";
import { AssignmentNotFoundError, AssignmentValidationError } from "../errors";

function jsonResponse(body: unknown, status = 200): Response {

```

```

    return new Response(JSON.stringify(body), {
      status,
      headers: { "Content-Type": "application/json" },
    });
  }

function ErrorResponse(err: unknown): Response {
  if (err instanceof AssignmentNotFoundError) {
    return jsonResponse({ error: err.message }, 404);
  }
  if (err instanceof AssignmentValidationError) {
    return jsonResponse({ error: err.message }, 400);
  }
  return jsonResponse(
    { error: err instanceof Error ? err.message : "Unknown error" },
    500
  );
}

/**
 * Matches the Next.js App Router dynamic-segment handler signature:
 * `export async function GET(request: Request, { params }: { params: { id: string } })`.
 */
export function createAssignmentItemRoutes(service: AssignmentService) {
  return {
    async GET(
      _request: Request,
      { params }: { params: { id: string } }
    ): Promise<Response> {
      try {
        const assignment = await service.getAssignment(params.id);
        return jsonResponse(assignment, 200);
      } catch (err) {
        return ErrorResponse(err);
      }
    },

    async PATCH(
      request: Request,
      { params }: { params: { id: string } }
    ): Promise<Response> {
      try {
        const body = await request.json();
        if (body.status === "completed") {
          const completed = await service.completeAssignment(params.id);
          return jsonResponse(completed, 200);
        }
        const updated = await service.updateAssignment(params.id, body);
        return jsonResponse(updated, 200);
      } catch (err) {
        return ErrorResponse(err);
      }
    },

    async DELETE(
      _request: Request,
      { params }: { params: { id: string } }

```

```

    ): Promise<Response> {
      try {
        await service.deleteAssignment(params.id);
        return new Response(null, { status: 204 });
      } catch (err) {
        return ErrorResponse(err);
      }
    },
  };
}

```

src/lib/unibud/assignments/service.ts

```

import type { Spark } from "../../spark";
import type { AssignmentRepository } from "../repository";
import type {
  Assignment,
  AssignmentListFilter,
  AssignmentPriority,
  CreateAssignmentInput,
  ExtractedTask,
  UpdateAssignmentInput,
} from "../types";
import { AssignmentNotFoundError, AssignmentValidationError } from "../errors";

/**
 * All assignment business logic lives here, in UNIBUD – not in Spark
 * (which must stay product-agnostic) and not in Bud (which must stay
 * a thin, personality-only orchestrator). This service calls Spark's
 * public SDK directly (spark.memory, spark.reasoning, spark.planning)
 * exactly as any other consumer would; it never reaches into Spark's
 * internals.
 */
export class AssignmentService {
  constructor(
    private readonly spark: Spark,
    private readonly repository: AssignmentRepository
  ) {}

  async createAssignment(input: CreateAssignmentInput): Promise<Assignment> {
    this.validateCreate(input);

    const now = new Date().toISOString();
    const id = `assignment_${Date.now()}_${Math.random().toString(36).slice(2, 8)}`;

    // --- Spark reasoning: read the assignment description -----
    const reasoning = await this.spark.reasoning.analyze({
      question: `What is the objective of this assignment: "${input.title}"?`,
      facts: [input.description, `Course: ${input.course}`, `Due: ${input.dueDate}`],
    });

    const deliverables = extractDeliverables(input.description);
    const importantDates = extractDates(input.description, input.dueDate);
    const missingInformation = findMissingInformation(input);
    const estimatedWorkloadHours = estimateWorkloadHours(input);
  }

```

```

// --- Spark planning: break the assignment into ordered tasks -----
const taskTitles = extractTaskTitles(input.description, input.title);
const plan = this.spark.planning.createPlan(
  `Complete assignment: ${input.title}`,
  taskTitles
);

const extractedTasks: ExtractedTask[] = plan.tasks.map((t) => ({
  id: t.id,
  title: t.title,
  order: t.order,
  done: t.done,
})));

const assignment: Assignment = {
  id,
  userId: input.userId,
  title: input.title,
  description: input.description,
  course: input.course,
  dueDate: input.dueDate,
  priority: input.priority ?? "medium",
  status: "not_started",
  createdAt: now,
  updatedAt: now,
  extractedTasks,
  extractedReferences: extractReferences(input.description),
  tags: input.tags ?? [],
  analysis: {
    objective: reasoning.answer,
    deliverables,
    importantDates,
    missingInformation,
    estimatedWorkloadHours,
    confidence: reasoning.confidence,
  },
  planId: plan.id,
};

// --- Store through Spark memory (cross-cutting recall context) -----
this.spark.memory.remember({
  kind: "long_term",
  userId: input.userId,
  content: `Assignment created: "${assignment.title}" for ${assignment.course}, due ${assignment.d
  tags: ["assignment", "created", assignment.id],
});

this.spark.memory.remember({
  kind: "workspace",
  userId: input.userId,
  content: `Plan for "${assignment.title}": ${taskTitles.join(" -> ")}`,
  tags: ["assignment", "plan", assignment.id, plan.id],
});

// --- Repository is the actual queryable store for CRUD -----
return this.repository.insert(assignment);

```



```

}

async updateAssignment(
  id: string,
  patch: UpdateAssignmentInput
): Promise<Assignment> {
  const updated = await this.repository.update(id, {
    ...patch,
    updatedAt: new Date().toISOString(),
  });
  if (!updated) throw new AssignmentNotFoundError(id);

  this.spark.memory.remember({
    kind: "episodic",
    userId: updated.userId,
    content: `Assignment updated: "${updated.title}".`,
    tags: ["assignment", "updated", id],
  });

  return updated;
}

async deleteAssignment(id: string): Promise<void> {
  const existing = await this.repository.findById(id);
  if (!existing) throw new AssignmentNotFoundError(id);

  await this.repository.delete(id);

  this.spark.memory.remember({
    kind: "episodic",
    userId: existing.userId,
    content: `Assignment deleted: "${existing.title}".`,
    tags: ["assignment", "deleted", id],
  });
}

async getAssignment(id: string): Promise<Assignment> {
  const found = await this.repository.findById(id);
  if (!found) throw new AssignmentNotFoundError(id);
  return found;
}

async listAssignments(filter: AssignmentListFilter): Promise<Assignment[]> {
  return this.repository.list(filter);
}

async completeAssignment(id: string): Promise<Assignment> {
  const existing = await this.repository.findById(id);
  if (!existing) throw new AssignmentNotFoundError(id);

  const updated = await this.repository.update(id, {
    status: "completed",
    updatedAt: new Date().toISOString(),
  });
  if (!updated) throw new AssignmentNotFoundError(id);

  this.spark.memory.remember({

```

```

        kind: "episodic",
        userId: updated.userId,
        content: `Assignment completed: "${updated.title}".`,
        tags: ["assignment", "completed", id],
    });

    this.spark.learning.recordFeedback({
        subject: "assignment_completion",
        rating: "positive",
        note: updated.title,
    });

    return updated;
}

private validateCreate(input: CreateAssignmentInput): void {
    if (!input.userId) throw new AssignmentValidationError("userId is required.");
    if (!input.title?.trim()) throw new AssignmentValidationError("title is required.");
    if (!input.course?.trim()) throw new AssignmentValidationError("course is required.");
    if (!input.dueDate || Number.isNaN(new Date(input.dueDate).getTime())) {
        throw new AssignmentValidationError("dueDate must be a valid ISO date string.");
    }
}

// -----
// Deterministic extraction helpers.
//
// These are placeholder heuristics – the same style as Spark's own
// "local" services (deterministic, no network, no API key). Once a
// real AI provider is registered with Spark, `reasoning.answer` above
// will carry genuine analysis; these helpers can then shrink to pure
// fallbacks instead of doing the primary extraction work.
// -----

const DELIVERABLE_KEYWORDS = /\b(submit|turn in|deliverable|upload|hand in|present)\b/i;
const DATE_PATTERN = /\b(\d{1,2})\/(\d{1,2})(?:\/\d{2,4})?\b(?:jan|feb|mar|apr|may|jun|jul|aug|sep|oct|n
const REFERENCE_PATTERN = /\b(chapter\s+\d+|pp?\.\s?\d+(-\d+)?)|https?:\/\/\/\S+)\b/gi;

function splitSentences(text: string): string[] {
    return text
        .split(/(?:<=|.!?))\s+|\n+/)
        .map((s) => s.trim())
        .filter(Boolean);
}

function extractDeliverables(description: string): string[] {
    return splitSentences(description).filter((s) => DELIVERABLE_KEYWORDS.test(s));
}

function extractDates(description: string, dueDate: string): string[] {
    const found = description.match(DATE_PATTERN) ?? [];
    return [...new Set([dueDate, ...found])];
}

function extractReferences(description: string): string[] {
    const found = description.match(REFERENCE_PATTERN) ?? [];

```

```

    return [...new Set(found)];
}

function extractTaskTitles(description: string, title: string): string[] {
    const sentences = splitSentences(description).filter((s) => s.length > 3);
    if (sentences.length >= 2) return sentences;
    // Not enough structure in the description to break down – fall back
    // to a generic three-step shape rather than a single opaque task.
    return [`Research for ${title}`, `Draft ${title}`, `Finalize and submit ${title}`];
}

function findMissingInformation(input: CreateAssignmentInput): string[] {
    const missing: string[] = [];
    if (!input.description || input.description.trim().length < 20) {
        missing.push("Description is very short – add more detail for a better breakdown.");
    }
    if (!DATE_PATTERN.test(input.description ?? "")) {
        missing.push("No dates were found in the description besides the due date.");
    }
    if (!input.tags || input.tags.length === 0) {
        missing.push("No tags set – tagging helps Study Plans and Search find this later.");
    }
    return missing;
}

function estimateWorkloadHours(input: CreateAssignmentInput): number {
    const baseByPriority: Record<AssignmentPriority, number> = {
        low: 1,
        medium: 2,
        high: 4,
        urgent: 6,
    };
    const base = baseByPriority[input.priority ?? "medium"];
    const lengthFactor = Math.ceil((input.description?.length ?? 0) / 250);
    return base + lengthFactor;
}

```

src/lib/unibud/assignments/types.ts

```

export type AssignmentPriority = "low" | "medium" | "high" | "urgent";

export type AssignmentStatus =
    | "not_started"
    | "in_progress"
    | "blocked"
    | "completed"
    | "overdue";

export interface ExtractedTask {
    id: string;
    title: string;
    order: number;
    done: boolean;
}

```

```

export interface Assignment {
  id: string;
  userId: string;
  title: string;
  description: string;
  course: string;
  dueDate: string; // ISO 8601
  priority: AssignmentPriority;
  status: AssignmentStatus;
  createdAt: string;
  updatedAt: string;

  /** Populated by Spark's reasoning/planning analysis at creation time. */
  extractedTasks: ExtractedTask[];
  extractedReferences: string[];
  tags: string[];

  /** Spark's read on the assignment – kept alongside, not authoritative business state. */
  analysis?: {
    objective: string;
    deliverables: string[];
    importantDates: string[];
    missingInformation: string[];
    estimatedWorkloadHours: number;
    confidence: number;
  };

  /** The Spark-generated plan ID this assignment's task breakdown came from, if any. */
  planId?: string;
}

export interface CreateAssignmentInput {
  userId: string;
  title: string;
  description: string;
  course: string;
  dueDate: string;
  priority?: AssignmentPriority;
  tags?: string[];
}

export interface UpdateAssignmentInput {
  title?: string;
  description?: string;
  course?: string;
  dueDate?: string;
  priority?: AssignmentPriority;
  status?: AssignmentStatus;
  tags?: string[];
}

export interface AssignmentListFilter {
  userId: string;
  status?: AssignmentStatus;
  course?: string;
  dueBefore?: string;
  dueAfter?: string;
}

```

```
}
```

src/lib/unibud/dashboard.ts

```
import type { Spark } from "../spark";
import type { Bud } from "../bud";
import type { BudSession } from "../bud";
import type { DashboardViewModel } from "../types";
import { TOOL_DEFINITIONS } from "../tools";
import { getGoals } from "../goals";
import type { AssignmentService } from "../assignments/service";
import { getAssignmentsDashboardData } from "../assignments/dashboard";

/**
 * The landing-page flow described in the product brief:
 *
 * 1. Bud greets the student and reasons over their message (via Bud's
 *    own respond() – UNIBUD does not reimplement conversation).
 * 2. Spark.recommendations ranks UNIBUD's own tool catalog against
 *    the student's stored goal tags – a dashboard-level concern Bud
 *    doesn't expose, so UNIBUD calls Spark directly for it.
 * 3. If an AssignmentService is supplied, real assignment stats
 *    replace what used to be placeholder numbers on the Assignments
 *    card. This parameter is optional and additive – existing calls
 *    to assembleDashboard() without it are unaffected.
 *
 * Bud and Spark's public APIs are used exactly as frozen; nothing here
 * reaches into their internals.
 */
export async function assembleDashboard(
  spark: Spark,
  bud: Bud,
  session: BudSession,
  message?: string,
  assignmentService?: AssignmentService
): Promise<DashboardViewModel> {
  const response = await bud.respond(
    message ?? "Greet me and help me figure out what to work on.",
    session
  );

  const goalTags = getGoals(spark, session.userId);

  const ranked = spark.recommendations.recommend({
    userId: session.userId,
    sessionId: session.sessionId,
    candidateItems: TOOL_DEFINITIONS.map((t) => ({ id: t.id, tags: t.tags })),
    basedOnTags: goalTags,
    limit: 1,
  });

  const top = ranked[0];
  const suggestedToolId = top && top.score > 0 ? (top.itemId as DashboardViewModel["suggestedToolId"])

  const assignments = assignmentService
```

```

    ? await getAssignmentsDashboardData(spark, assignmentService, session.userId)
    : undefined;

return {
  greeting: response.message,
  tools: TOOL_DEFINITIONS,
  suggestedToolId,
  suggestedReason: top?.reason ?? "Set an academic goal to get a personalized pick here.",
  assignments: assignments
  ? {
    upcoming: assignments.upcoming.length,
    overdue: assignments.overdue.length,
    completed: assignments.completed.length,
    progressPercent: assignments.progressPercent,
    estimatedWorkloadHours: assignments.estimatedWorkloadHours,
    nextRecommendedTaskTitle: assignments.nextRecommendedTaskTitle,
  }
  : undefined,
  trace: {
    memoryHits: response.trace.memoryHits,
    knowledgeHits: response.trace.knowledgeHits,
    reasoningConfidence: response.trace.reasoningConfidence,
    provider: response.trace.provider,
  },
};
}

```

src/lib/unibud/design/DESIGN_SYSTEM.md

UNIBUD Design System – v1 (foundation)

Real, checked-in code lives in `tokens.ts`, `accessibility.ts`, `styles.ts`, and `budVoice.ts` in this folder. This document explains the rules those files encode; it does not introduce anything the code doesn't already define.

Status

This is the **foundation layer**: color/type/spacing/radius tokens (including the reserved gold accent), style helpers, named motion presets, accessibility checking, Bud voice guidelines, Bud presence states, and Spark presence reporting – all framework agnostic, all typechecked, all verified in `scripts/design-system-verify.ts` (30 checks). It is applied to the one real UI surface that exists today (the dashboard/Assignments preview). It is **not** yet applied to Smart Notes, Projects, Campus, Connect, Calendar, Notifications, Search, Settings, Profile, or Admin – those screens don't exist in this codebase yet, so there is nothing to restyle. When each of those modules is actually built, it should import from `@/lib/unibud/design` rather than inventing its own colors, spacing, or animations – see the module adoption checklist below.

Color

Grayscale is the entire foundation. Every value is in `tokens.ts`'s

``color.gray`` scale (``#000000`` through ``#FFFFFF``, 12 steps). The four semantic accents (``success #2E7D5B``, ``warning #B8860B``, ``error #B3261E``, ``info`` / ``progress #3A5CA8``) communicate status only – never decoration, never a brand color.

****Gold (``#C9A227``) is a separate, fifth reserved color – not a status color.**** It means "this is worth noticing": an achievement, a streak, a premium indicator, a brand touch. It is never used for warnings (that's amber's job) and never used as a default accent. Measured contrast on the dark background: ``8.68:1`` (AAA) – verified in ``scripts/design-system-verify.ts``, not asserted.

Dark mode is the primary definition (``theme.dark``), not a filter applied to a light theme – per the spec's "dark mode first."
``theme.light`` is a second, independently defined role-mapping over the same grayscale, not an inverted dark theme.

Every text/background color pairing actually used in a screen must be checked with ``contrastRatio()`` + ``wcagLevel()`` from ``accessibility.ts`` before shipping. This is enforced in the verification script, not left to visual judgment.

Typography

One scale (``type.scale``, ``12px`` to ``48px``), one display face (``Fraunces``), one body face (``Inter``), one mono face (``IBM Plex Mono`` – for data, timestamps, status labels). No screen introduces a new size or a new face outside this scale.

Icons

``lucide-react`` is the icon set – its default line-art style already fits "hand-drawn, not mechanical" better than a filled icon set would, without needing custom illustration assets this codebase doesn't have. Rules actually followed in the restyled preview:

- Stroke width ``1.6`` everywhere (lucide's default is ``2``; ``1.6`` reads slightly softer/sketch-like without becoming illegible at small sizes).
- Three sizes only: ``16px`` (inline/status), ``20px`` (card headers), ``24px`` (Bud's mark container). No other icon size.
- Icon color is ``textPrimary`` or ``textMuted`` by default; a status color (or gold) only when the icon *is* the status indicator (e.g. the overdue-assignments icon turning ``error``-red) – same rule as color generally.

Spacing & radius

``space`` (4px to 80px, powers of a 4px base unit) and ``radius`` (``8px`` to ``9999px`` for pills) are the only spacing/radius values used. If a layout needs a gap ``tokens.ts`` doesn't define, the token set gets a new entry – components don't invent one-off pixel values.

Glass

``glassSurfaceStyle()`` is reserved for the specific surfaces the spec names – Bud's chat/greeting, command palette, navigation, modals,

dashboards – never applied indiscriminately. Every other surface uses ``floatingCardStyle()`` (solid, no blur) so the interface doesn't become "everything transparent," which the spec explicitly warns against.

Motion

Every animation comes from a named preset in ``motionPresets.ts`` – ``breathe``, ``fadeInUp``, ``pressScale``, ``listenPulse``, ``thinkTilt`` – rendered via ``renderMotionPresetCSS()``. Components reference a preset by name instead of writing their own ``@keyframes`` block, which is what the first dashboard preview did (``bud-breathe``, ``u-fade-in`` defined locally, no shared source). Every preset already respects ``prefers-reduced-motion`` internally – callers don't need to remember to add that check themselves. Two easing curves total: ``standard`` (general-purpose) and ``spring`` (anything meant to feel alive).

Accessibility

- Minimum touch target: ``MIN_TOUCH_TARGET_PX`` (44px), matching WCAG's 2.5.5 and iOS/Android platform guidance.
- Every focus state uses ``focusRingStyle()`` – a 2px solid outline in the primary text color, 2px offset. Never ``outline: none`` without a replacement.
- Every text/background pairing must reach at least WCAG AA (``wcagLevel()`` returns ``"AA"`` or ``"AAA"``), verified programmatically, not eyeballed.

Bud's identity

Bud's actual personality/tone configuration lives in ``src/lib/bud/personality.ts`` and is **frozen and unmodified** by this design system – this module doesn't touch Bud's package. What lives here instead is ``budVoice.ts``: a checker for hand-written Bud-facing copy (docs, canned strings, system-prompt fragments) so it doesn't slip into the phrasing the product spec rules out ("As an AI...", robotic disclaimers). It flags patterns; it doesn't generate Bud's actual replies, which still come from Spark's writing service.

Visually, Bud is represented as a small hand-sketched mark (a seed/speech-bubble motif per the product brief) rendered in the grayscale palette only – no color, no gradient, no robot/mascot imagery.

Bud's presence states (``budPresence.ts``)

Four states – ``idle``, ``listening``, ``thinking``, ``speaking`` – each with a named motion preset and a mandatory, non-empty ``accessibleLabel`` for ``aria-live`` announcements (screen readers get the same "Bud is thinking" signal sighted users get from the animation).

Honest scope note: this is the state-machine and visual treatment only. There is no microphone capture, no speech synthesis, and no browser permission handling anywhere in this codebase – ``listening`` and ``speaking`` are defined and ready for when a real voice feature is built, not a claim that voice already works.

Memory transparency (``budPresence.ts`` → ``formatMemoryIndicator``)

Turns Bud's **real** trace object (``memoryHits``, ``knowledgeHits``, ``plannedTaskCount`` – from an actual ``bud.respond()`` call) into a short status line like **"Spark checked 2 memories and a 3-step plan."** If the trace is empty, it returns ``null`` rather than fabricating activity – verified directly in the test script.

Spark's presence (``sparkPresence.ts``)

Spark stays invisible as a chat interface, per the brief, but its real ``spark.health()`` output can be surfaced as a short, honest status line (``describeSparkStatus``) and an explicit mock-vs-real-provider check (``describeActiveProvider``) – so a settings/admin screen can never silently imply a real AI provider is active when it's actually running on ``MockProvider``. Both functions take a real ``SparkHealthReport``; neither hard-codes a status string.

Module adoption checklist

For every future module (Smart Notes, Projects, Campus, Connect, Calendar, Notifications, Search, Profile, Settings, Admin) – **only** build this checklist against a module once that module actually exists; this list is process, not a promise that those modules are built:

1. Import colors from ``color`/`theme``, never a new hex value.
2. Import type sizes from ``type.scale``, spacing from ``space``, radii from ``radius`` – never a one-off pixel value.
3. Use ``floatingCardStyle()`` for cards; reserve ``glassSurfaceStyle()`` for the specific surfaces named in the spec (Bud, nav, modals, dashboards) – not every surface.
4. Any new animation is a new named entry in ``motionPresets.ts``, not an inline ``@keyframes`` block in the component.
5. Any Bud-facing copy written by hand gets run through ``checkBudVoiceCompliance()``.
6. Every text/background pairing gets checked with ``contrastRatio()`` + ``wcagLevel()`` before shipping.
7. Every interactive element is at least ``MIN_TOUCH_TARGET_PX`` (44px) and has a visible ``focusRingStyle()`` – never ``outline: none`` with no replacement.
8. Add the module's checks to ``scripts/design-system-verify.ts`` (or a module-specific verify script) – a design-system rule that isn't tested isn't actually enforced.

What's honestly not here yet

- No component library (Button/Input/Modal/etc. as real reusable UI components) – only style-object *generators* that a future component layer would call. There's no rendering framework wired into this repo yet (no ``@types/react`` available in this environment), so component code stays framework-agnostic for now.
- No responsive breakpoint testing beyond the token values existing – actual layout behavior at each breakpoint isn't verified because there's no real layout to test yet outside the one preview screen.
- No actual voice input/output – ``budPresence.ts``'s ``listening``/``speaking`` states are defined and styled, but there's no microphone

capture or speech synthesis behind them.

- No multimodal upload UI, command palette, or any of the dozen other screens named in the product briefs – those are product scope, not design-system scope, and aren't built.

src/lib/unibud/design/accessibility.ts

```
/**
 * A genuine WCAG 2.1 contrast-ratio implementation, not an assertion
 * that "contrast is good." Every theme color pair used for text is
 * checked against this in scripts/design-system-verify.ts – if a pair
 * fails, the test fails, not just the vibe.
 */

function hexToLinear(channel: number): number {
  const c = channel / 255;
  return c <= 0.03928 ? c / 12.92 : Math.pow((c + 0.055) / 1.055, 2.4);
}

function relativeLuminance(hex: string): number {
  const clean = hex.replace("#", "");
  const r = parseInt(clean.substring(0, 2), 16);
  const g = parseInt(clean.substring(2, 4), 16);
  const b = parseInt(clean.substring(4, 6), 16);
  const [rl, gl, bl] = [hexToLinear(r), hexToLinear(g), hexToLinear(b)];
  return 0.2126 * rl + 0.7152 * gl + 0.0722 * bl;
}

/** Returns the WCAG contrast ratio between two hex colors, from 1 to 21. */
export function contrastRatio(hexA: string, hexB: string): number {
  const [lumA, lumB] = [relativeLuminance(hexA), relativeLuminance(hexB)]
    .sort((a, b) => b - a);
  return (lumA + 0.05) / (lumB + 0.05);
}

export type WcagLevel = "fail" | "AA" | "AAA";

/**
 * `isLargeText` follows WCAG's own threshold: 18pt+ (24px) regular or
 * 14pt+ (18.66px) bold qualifies for the relaxed "large text" minimums.
 */
export function wcagLevel(
  ratio: number,
  isLargeText = false
): WcagLevel {
  const aaMin = isLargeText ? 3 : 4.5;
  const aaaMin = isLargeText ? 4.5 : 7;
  if (ratio >= aaaMin) return "AAA";
  if (ratio >= aaMin) return "AA";
  return "fail";
}
```

src/lib/unibud/design/budPresence.ts

```
import { motionPresets } from "../motionPresets";
import type { BudResponse } from "../../bud";

/**
 * IMPORTANT — what this file is and isn't:
 *
 * This defines the visual/state-machine *infrastructure* for Bud
 * having a presence beyond a static chat bubble (idle, listening,
 * thinking, speaking), per the identity brief. It does NOT implement
 * actual voice capture or speech synthesis — there's no microphone
 * input, no audio pipeline, and no browser permission handling
 * anywhere in this codebase. Wiring `listening`/`speaking` to a real
 * voice feature is future work; what exists today is the state type,
 * the matching visual treatment, and the accessible description for
 * each state, ready for that wiring.
 */

export type BudPresenceState = "idle" | "listening" | "thinking" | "speaking";

export interface BudPresencePreset {
  state: BudPresenceState;
  motionPresetName: keyof typeof motionPresets;
  /** Read by screen readers via aria-live — must always be set, per accessibility requirements. */
  accessibleLabel: string;
}

export const BUD_PRESENCE: Record<BudPresenceState, BudPresencePreset> = {
  idle: {
    state: "idle",
    motionPresetName: "breathe",
    accessibleLabel: "Bud is here.",
  },
  listening: {
    state: "listening",
    motionPresetName: "listenPulse",
    accessibleLabel: "Bud is listening.",
  },
  thinking: {
    state: "thinking",
    motionPresetName: "thinkTilt",
    accessibleLabel: "Bud is thinking.",
  },
  speaking: {
    state: "speaking",
    motionPresetName: "breathe",
    accessibleLabel: "Bud is responding.",
  },
};

/**
 * Turns Bud's *real* trace object (from an actual `bud.respond()` call
 * — see src/lib/bud/types.ts) into a short, honest status line, per
 * the brief's "Spark is remembering this" transparency pattern. Every
 * number here comes from the real response; nothing is invented.
 */
```

```

export function formatMemoryIndicator(trace: BudResponse["trace"]): string | null {
  const parts: string[] = [];
  if (trace.memoryHits > 0) {
    parts.push(`${trace.memoryHits} memor${trace.memoryHits === 1 ? "y" : "ies"}`);
  }
  if (trace.knowledgeHits > 0) {
    parts.push(`${trace.knowledgeHits} note${trace.knowledgeHits === 1 ? "" : "s"}`);
  }
  if (trace.plannedTaskCount > 0) {
    parts.push(`a ${trace.plannedTaskCount}-step plan`);
  }
  if (parts.length === 0) return null;
  return `Spark checked ${parts.join(" and ")}`;
}

```

src/lib/unibud/design/budVoice.ts

```

/**
 * Bud's personality lives in src/lib/bud/personality.ts already (name,
 * tone, voice guidelines fed into its system prompt) – that file is
 * frozen and unmodified here. This module is UNIBUD-side tooling: a
 * checker that content *written for Bud* (system prompts, canned
 * copy, docs examples) doesn't slip into the phrasing the product
 * spec explicitly rules out ("As an AI...", robotic disclaimers).
 *
 * This does not change what Bud actually says at runtime – Bud's
 * replies come from Spark's writing service, which is currently the
 * deterministic MockProvider. This is a lint-style guard for anyone
 * writing Bud-facing copy by hand.
 */

const BANNED_PHRASES: RegExp[] = [
  /\bas an ai\b/i,
  /\bi('m| am) (just |only)?an ai\b/i,
  /\bi don't have (feelings|emotions|opinions)\b/i,
  /\bi('m| am) not able to\b/i,
  /\bunfortunately,? i\b/i,
];

export interface BudVoiceCheckResult {
  compliant: boolean;
  violations: string[];
}

export function checkBudVoiceCompliance(text: string): BudVoiceCheckResult {
  const violations = BANNED_PHRASES.filter((pattern) => pattern.test(text)).map(
    (pattern) => pattern.source
  );
  return { compliant: violations.length === 0, violations };
}

/** Example phrasing from the spec – for documentation/reference only. */
export const BUD_VOICE_EXAMPLES = [
  "Let's figure this out together.",
  "Here's an easier way to see it.",

```

```

    "Good question.",
    "You're getting closer.",
    "Let's break it into smaller pieces.",
  ] as const;

```

src/lib/unibud/design/index.ts

```

export { color, theme, type, space, radius, shadow, motion, breakpoint, MIN_TOUCH_TARGET_PX } from "./
export type { ColorMode } from "./tokens";
export { contrastRatio, wcagLevel } from "./accessibility";
export type { WcagLevel } from "./accessibility";
export {
  glassSurfaceStyle,
  floatingCardStyle,
  focusRingStyle,
  statusBadgeStyle,
  motionSafeTransition,
} from "./styles";
export type { StyleObject, StatusKind } from "./styles";
export { checkBudVoiceCompliance, BUD_VOICE_EXAMPLES } from "./budVoice";
export type { BudVoiceCheckResult } from "./budVoice";
export { motionPresets, renderMotionPresetCSS } from "./motionPresets";
export type { MotionPreset } from "./motionPresets";
export { BUD_PRESENCE, formatMemoryIndicator } from "./budPresence";
export type { BudPresenceState, BudPresencePreset } from "./budPresence";
export { describeSparkStatus, describeActiveProvider } from "./sparkPresence";

```

src/lib/unibud/design/motionPresets.ts

```

import { motion } from "./tokens";

/**
 * Every animation in the product should come from one of these named
 * presets, not a one-off `@keyframes` block written inline per
 * component (that's the duplication the first dashboard preview had -
 * `bud-breathe`, `u-fade-in`, etc. defined locally with no shared
 * source of truth). A CSS-in-JS or stylesheet layer can register these
 * once; components just reference the preset name.
 */

export interface MotionPreset {
  name: string;
  keyframes: string;
  duration: string;
  easing: string;
  /** Whether this preset should be entirely disabled under prefers-reduced-motion, vs just shortened. */
  disableOnReducedMotion: boolean;
}

export const motionPresets: Record<
  "breathe" | "fadeInUp" | "pressScale" | "listenPulse" | "thinkTilt",
  MotionPreset

```

```

> = {
  /** Bud's idle animation - "gentle breathing" per the identity brief. */
  breathe: {
    name: "u-breathe",
    keyframes: "0%,100% { transform: scale(1); opacity: 0.92; } 50% { transform: scale(1.06); opacity: 1; }",
    duration: "3.6s",
    easing: motion.easing.standard,
    disableOnReducedMotion: true,
  },

  /** Entrance animation for cards/panels appearing on screen. */
  fadeInUp: {
    name: "u-fade-in-up",
    keyframes: "from { opacity: 0; transform: translateY(6px); } to { opacity: 1; transform: translate(0,0); }",
    duration: motion.duration.slow,
    easing: motion.easing.standard,
    disableOnReducedMotion: false, // still runs, just as an instant opacity change when reduced
  },

  /** Press/tap feedback for buttons and interactive cards. */
  pressScale: {
    name: "u-press-scale",
    keyframes: "0% { transform: scale(1); } 50% { transform: scale(0.97); } 100% { transform: scale(1); }",
    duration: motion.duration.fast,
    easing: motion.easing.spring,
    disableOnReducedMotion: true,
  },

  /** Bud's "listening" state - a slow pulse, distinct from breathing so the two states read different
  listenPulse: {
    name: "u-listen-pulse",
    keyframes: "0%,100% { opacity: 0.7; } 50% { opacity: 1; }",
    duration: "1.1s",
    easing: motion.easing.standard,
    disableOnReducedMotion: true,
  },

  /** Bud's "thinking" state - a small, slow tilt, per the identity brief's "slight tilt while thinkin
  thinkTilt: {
    name: "u-think-tilt",
    keyframes: "0%,100% { transform: rotate(0deg); } 50% { transform: rotate(-4deg); }",
    duration: "1.6s",
    easing: motion.easing.standard,
    disableOnReducedMotion: true,
  },
};

/** Renders a preset into a CSS `@keyframes` block + a ready-to-use class, for direct inline `<style>`
export function renderMotionPresetCSS(preset: MotionPreset): string {
  return `
@keyframes ${preset.name} { ${preset.keyframes} }
.${preset.name} {
  animation: ${preset.name} ${preset.duration} ${preset.easing} infinite;
}
@media (prefers-reduced-motion: reduce) {
  .${preset.name} { ${preset.disableOnReducedMotion ? "animation: none !important;" : "animation-duration: 0.001s;"}
}

```

```
` .trim();
}
```

src/lib/unibud/design/sparkPresence.ts

```
import type { SparkHealthReport } from "../../spark";

/**
 * "Spark is not visible as a chatbot; it's the intelligence engine
 * behind UNIBUD" – this is the one place Spark's own state (which
 * provider is active, whether it's healthy) becomes a short, honest
 * UI string. Every value here comes from a real `spark.health()` call;
 * nothing is invented or hard-coded as "connected."
 */

export function describeSparkStatus(health: SparkHealthReport): string {
  const activeProvider = health.registeredProviders.find((p) => p.isDefault);
  const providerLabel = activeProvider
    ? `${activeProvider.name}${activeProvider.available ? "" : " (unavailable)"}`
    : "no provider";

  if (health.status !== "healthy") {
    return `Spark is ${health.status} – running on ${providerLabel}.`;
  }

  return `Spark is running on ${providerLabel}.`;
}

/**
 * A single line honestly stating whether Spark is running on the
 * placeholder Mock provider vs. a real AI provider – surfaced so a
 * settings/admin screen never silently implies real AI is active
 * when it isn't.
 */

export function describeActiveProvider(health: SparkHealthReport): {
  name: string;
  isMock: boolean;
} {
  const active = health.registeredProviders.find((p) => p.isDefault);
  const name = active?.name ?? "none";
  return { name, isMock: name === "mock" };
}
```

src/lib/unibud/design/styles.ts

```
import { color, motion, radius, shadow, theme, type ColorMode } from "../tokens";

/**
 * These return plain style-object data (safe to spread into a React
 * `style` prop, a CSS-in-JS call, or serialized to a stylesheet) rather
 * than JSX. This repo has no `@types/react` available in this
 * environment, so component code stays framework-agnostic and fully
```

```
* typecheckable with plain tsc – the same discipline as every other
* "local" implementation in this codebase.
*/
```

```
export type StyleObject = Record<string, string | number>;
```

```
/** "Glass should highlight important surfaces... avoid making everything transparent." */
```

```
export function glassSurfaceStyle(mode: ColorMode): StyleObject {
```

```
  const t = theme[mode];
  return {
    background: t.surfaceGlass,
    backdropFilter: "blur(20px) saturate(140%)",
    WebkitBackdropFilter: "blur(20px) saturate(140%)",
    border: `1px solid ${t.border}`,
    boxShadow: `${shadow.floating}, ${shadow.glassInset}`,
    borderRadius: radius.lg,
  };
}
```

```
/** A floating card – the base surface used everywhere that isn't glass. */
```

```
export function floatingCardStyle(mode: ColorMode, elevated = false): StyleObject {
```

```
  const t = theme[mode];
  return {
    background: t.surface,
    border: `1px solid ${t.border}`,
    borderRadius: radius.lg,
    boxShadow: elevated ? shadow.floatingHover : shadow.floating,
    transition: `transform ${motion.duration.base} ${motion.easing.standard}, box-shadow ${motion.dura
  };
}
```

```
/** Visible, high-contrast focus ring – never removed, per accessibility requirements. */
```

```
export function focusRingStyle(mode: ColorMode): StyleObject {
```

```
  return {
    outline: `2px solid ${theme[mode].textPrimary}`,
    outlineOffset: "2px",
  };
}
```

```
export type StatusKind = "success" | "warning" | "error" | "info" | "progress";
```

```
/** The only place accent color is allowed to appear – status badges/indicators. */
```

```
export function statusBadgeStyle(status: StatusKind): StyleObject {
```

```
  return {
    color: color.semantic[status],
    border: `1px solid ${color.semantic[status]}`,
    borderRadius: radius.full,
    padding: "2px 10px",
    fontSize: "12px",
    fontWeight: 500,
  };
}
```

```
/** Respects reduced-motion preference – returns a no-op transition when disabled. */
```

```
export function motionSafeTransition(
```

```
  property: string,
  prefersReducedMotion: boolean,
```



```

    speed: keyof typeof motion.duration = "base"
  ): StyleObject {
    if (prefersReducedMotion) {
      return { transition: "none" };
    }
    return {
      transition: `${property} ${motion.duration[speed]} ${motion.easing.standard}`,
    };
  }
}

```

src/lib/unibud/design/tokens.ts

```

/**
 * UNIBUD Design System - tokens.
 *
 * Grayscale is the foundation; every accent color exists only to
 * communicate a meaning (success/warning/error/info/progress), never
 * decoration. This file has no framework dependency - it's plain data
 * consumed by styles.ts and, eventually, by real UI components once
 * this codebase has a rendering framework wired in.
 */

export const color = {
  // Grayscale foundation - named by function, not by hex, so dark mode
  // is a remap of these roles rather than a parallel palette.
  gray: {
    0: "#000000",
    50: "#0A0A0A",
    100: "#141414",
    200: "#1F1F1F",
    300: "#2E2E2E",
    400: "#4A4A4A",
    500: "#6E6E6E",
    600: "#8F8F8F",
    700: "#B8B8B8",
    800: "#DCDCDC",
    900: "#F2F2F2",
    950: "#FAFAFA",
    1000: "#FFFFFF",
  },

  // Semantic accents - the ONLY colors allowed outside grayscale, and
  // only ever used to convey the specific meaning named here.
  semantic: {
    success: "#2E7D5B",
    warning: "#B8860B",
    error: "#B3261E",
    info: "#3A5CA8",
    progress: "#3A5CA8",
  },

  /**
   * Gold is deliberately NOT part of `semantic` above - it doesn't mean
   * "warning," it means "this is worth noticing": a milestone, a streak,
   * a premium/brand touch. Mixing it into status semantics would blur

```

```

    * both meanings, so it's its own reserved token with its own rule:
    * achievements, premium indicators, and brand accents ONLY. Never a
    * default button color, never decoration.
    */
    gold: "#C9A227",
  } as const;

export type ColorMode = "light" | "dark";

/**
 * Role-based theme, not raw grayscale — this is what components should
 * actually reference (`theme.dark.surface`, not `color.gray[100]`).
 * "Dark mode first" per the spec: dark is the primary definition, light
 * is derived from it, not the other way around.
 */
export const theme: Record<ColorMode, {
  background: string;
  surface: string;
  surfaceGlass: string;
  border: string;
  textPrimary: string;
  textSecondary: string;
  textMuted: string;
}> = {
  dark: {
    background: color.gray[0],
    surface: color.gray[100],
    surfaceGlass: "rgba(20, 20, 20, 0.6)",
    border: color.gray[300],
    textPrimary: color.gray[1000],
    textSecondary: color.gray[700],
    textMuted: color.gray[500],
  },
  light: {
    background: color.gray[1000],
    surface: color.gray[950],
    surfaceGlass: "rgba(255, 255, 255, 0.6)",
    border: color.gray[800],
    textPrimary: color.gray[0],
    textSecondary: color.gray[400],
    textMuted: color.gray[600],
  },
};

export const type = {
  fontDisplay: "'Fraunces', ui-serif, Georgia, serif",
  fontBody: "'Inter', ui-sans-serif, system-ui, sans-serif",
  fontMono: "'IBM Plex Mono', ui-monospace, monospace",

  // A single consistent scale — every screen pulls from this, nothing
  // introduces a one-off font size.
  scale: {
    xs: "12px",
    sm: "14px",
    base: "16px",
    lg: "18px",
    xl: "22px",
  },
};

```

```

    "2x1": "28px",
    "3x1": "36px",
    "4x1": "48px",
  },

  weight: {
    regular: 400,
    medium: 500,
    semibold: 600,
  },

  lineHeight: {
    tight: 1.2,
    normal: 1.5,
    relaxed: 1.7,
  },
} as const;

export const space = {
  0: "0px",
  1: "4px",
  2: "8px",
  3: "12px",
  4: "16px",
  5: "20px",
  6: "24px",
  8: "32px",
  10: "40px",
  12: "48px",
  16: "64px",
  20: "80px",
} as const;

export const radius = {
  sm: "8px",
  md: "12px",
  lg: "16px",
  xl: "24px",
  full: "9999px",
} as const;

export const shadow = {
  // Soft, ambient – never a hard drop shadow, per "premium not corporate".
  floating: "0 8px 24px rgba(0, 0, 0, 0.12)",
  floatingHover: "0 14px 32px rgba(0, 0, 0, 0.16)",
  glassInset: "inset 0 1px 0 rgba(255, 255, 255, 0.08)",
} as const;

export const motion = {
  duration: {
    instant: "80ms",
    fast: "140ms",
    base: "220ms",
    slow: "360ms",
  },
  // Spring-like, never linear – communicates state per the spec's
  // "animation should communicate state, never be flashy" rule.

```

```

    easing: {
      standard: "cubic-bezier(0.2, 0.8, 0.2, 1)",
      spring: "cubic-bezier(0.34, 1.56, 0.64, 1)",
      exit: "cubic-bezier(0.4, 0, 1, 1)",
    },
  } as const;

export const breakpoint = {
  mobile: "0px",
  tablet: "768px",
  laptop: "1024px",
  desktop: "1440px",
  ultrawide: "1920px",
} as const;

/** Minimum touch target size for mobile, per accessibility requirements. */
export const MIN_TOUCH_TARGET_PX = 44;

```

src/lib/unibud/goals.ts

```

import type { Spark } from "../spark";

const GOALS_KEY = "academic_goal_tags";

/**
 * UNIBUD-specific convenience over Spark.personalization. Spark itself
 * has no concept of "academic goals" - it just stores arbitrary tagged
 * preferences per user. This is where UNIBUD gives that generic
 * mechanism product meaning.
 */
export function setGoals(spark: Spark, userId: string, tags: string[]): void {
  spark.personalization.setPreference(userId, GOALS_KEY, tags);
}

export function getGoals(spark: Spark, userId: string): string[] {
  const pref = spark.personalization.getPreference(userId, GOALS_KEY);
  return Array.isArray(pref?.value) ? (pref!.value as string[]) : [];
}

```

src/lib/unibud/index.ts

```

export { assembleDashboard } from "./dashboard";
export { setGoals, getGoals } from "./goals";
export { TOOL_DEFINITIONS } from "./tools";
export type { ToolId, ToolDefinition, DashboardViewModel } from "./types";

// Assignments - the first complete vertical slice. Exported as its own
// namespace-style barrel so it doesn't crowd the top-level UNIBUD API
// surface; import from "@lib/unibud/assignments" directly, or re-export
// from here as `Assignments` if a single import path is preferred later.
export * as Assignments from "./assignments";

```

src/lib/unibud/tools.ts

```
import type { ToolDefinition } from "./types";

/**
 * Static configuration, not intelligence. Tags here are matched against
 * a student's stored goal tags (via Spark's Personalization service) to
 * drive the "suggested next" pick on the dashboard.
 */
export const TOOL_DEFINITIONS: ToolDefinition[] = [
  {
    id: "assignments",
    name: "Assignments",
    description: "Track what's due and what's done.",
    tags: ["deadlines", "coursework", "grades"],
  },
  {
    id: "projects",
    name: "Projects",
    description: "Longer-running work with milestones.",
    tags: ["coursework", "collaboration", "deadlines"],
  },
  {
    id: "smart_notes",
    name: "Smart Notes",
    description: "Notes that connect back to your courses.",
    tags: ["coursework", "study", "review"],
  },
  {
    id: "study_plans",
    name: "Study Plans",
    description: "A sequenced plan for an exam or a subject.",
    tags: ["study", "review", "grades"],
  },
  {
    id: "campus",
    name: "Campus",
    description: "Events, deadlines, and services at your school.",
    tags: ["campus_life", "community"],
  },
  {
    id: "connect",
    name: "Connect",
    description: "Study groups, mentors, and classmates.",
    tags: ["community", "collaboration"],
  },
];
```

src/lib/unibud/types.ts

```
/**
 * These types belong to UNIBUD only. Spark and Bud know nothing about
```

```
* "tools," "goals," or a "dashboard" – those are UNIBUD's own concepts,  
* built on top of the frozen Spark/Bud SDKs.  
*/
```

```
export type ToolId =
```

```
  | "assignments"  
  | "projects"  
  | "smart_notes"  
  | "study_plans"  
  | "campus"  
  | "connect";
```

```
export interface ToolDefinition {
```

```
  id: ToolId;  
  name: string;  
  description: string;  
  tags: string[];  
}
```

```
export interface DashboardViewModel {
```

```
  greeting: string;  
  tools: ToolDefinition[];  
  suggestedToolId: ToolId | null;  
  suggestedReason: string;
```

```
  /** Populated only when an AssignmentService is passed to assembleDashboard(). Optional so existing  
  assignments?: {
```

```
    upcoming: number;  
    overdue: number;  
    completed: number;  
    progressPercent: number;  
    estimatedWorkloadHours: number;  
    nextRecommendedTaskTitle: string | null;
```

```
  };
```

```
  trace: {
```

```
    memoryHits: number;  
    knowledgeHits: number;  
    reasoningConfidence: number;  
    provider: string;
```

```
  };
```

```
}
```