Last Time



- Client-server architecture vs. P2P architecture
- Sockets, socket identifier = IP + Port number
- TCP: connection-oriented, reliable data transfer, flow and congestion control
- UDP: connectionless, unreliable data transfer
- HTTP: client-server architecture, request/response, TCP, "stateless"



HTTP connections

non-persistent HTTP

- at most one object sent over TCP connection
 - connection then closed
- downloading multiple objects required multiple connections

persistent HTTP

multiple objects can
be sent over single
TCP connection
between client, server

Non-persistent HTTP

suppose user enters URL:

www.someSchool.edu/someDepartment/home.index re

(contains text, references to 10 jpeg images)

- Ia. HTTP client initiates TCP connection to HTTP server (process) at www.someSchool.edu on port 80
- 2. HTTP client sends HTTP request message (containing URL) into TCP connection socket.

 Message indicates that client wants object someDepartment/home.index
- Ib. HTTP server at host
 www.someSchool.edu waiting
 for TCP connection at port 80.
 "accepts" connection, notifying client
- 3. HTTP server receives request message, forms response message containing requested object, and sends message into its socket

Non-persistent HTTP (cont.)



5. HTTP client receives response message containing html file, displays html. Parsing html file, finds 10 referenced jpeg objects

4. HTTP server closes TCP connection.




6. Steps 1-5 repeated for each of 10 jpeg objects

Non-persistent HTTP: response time

RTT (definition): time for a small packet to travel from client to server and back

HTTP response time:

- one RTT to initiate TCP connection
- one RTT for HTTP request and first few bytes of HTTP response to return
- file transmission time
- non-persistent HTTP
 response time =
 2RTT+ file transmission
 time



Persistent HTTP

non-persistent HTTP issues:

- requires 2 RTTs per object
- OS overhead for each TCP connection

persistent HTTP:

- server leaves connection open after sending response
- subsequent HTTP
 messages between same
 client/server sent over
 open connection
- client sends requests as soon as it encounters a referenced object
- as little as one RTT for all the referenced objects

User-server state: cookies


many Web sites use cookies four components:

- I) cookie header line of HTTP response message
- 2) cookie header line in next HTTP request message
- 3) cookie file kept on user's host, managed by user's browser
- 4) back-end database at Web site

example:

- Susan always access Internet from PC
- visits specific e-commerce site for first time
- when initial HTTP requests arrives at site, site creates:
 - unique ID
 - entry in backend database for ID


Cookies: keeping "state" (cont.)



Web caches (proxy server)

goal: satisfy client request without involving origin server

- user sets browser: Web accesses via cache
- browser sends all HTTP requests to cache
 - object in cache: cache returns object
 - else cache requests object from origin server, then returns object to client



why Web caching?

- reduce response time for client request
- reduce traffic on an institution's access link


Conditional GET

- Goal: don't send object if cache has up-to-date cached version
- cache: specify date of cached copy in HTTP request

If-modified-since:
 <date>

origin server: response contains no object if cached copy is up-to-date:

HTTP/1.0 304 Not Modified




Chapter 2: outline

- 2.1 principles of network applications
 - app architectures
 - app requirements
- 2.2 Web and HTTP
- 2.3 FTP
- 2.4 electronic mail
 - SMTP, POP3, IMAP
- 2.5 DNS

- 2.6 P2P applications
- 2.7 socket programming with UDP and TCP


FTP: file transfer protocol



- transfer file to/from remote host
- client/server model
 - client: side that initiates transfer (either to/from remote)
 - server: remote host
- * ftp: RFC 959
- ftp server: port 21

FTP: separate control, data connections

- FTP client contacts FTP server at port 21, using TCP
- client authorized over control connection
- client browses remote directory, sends commands over control connection
- when server receives file transfer command, server opens 2nd TCP data connection (for file) to client
- after transferring one file, server closes data connection



- server opens another TCP data connection to transfer another file
- control connection: "out of band"
- FTP server maintains
 "state": current directory,
 earlier authentication

FTP commands, responses

sample commands:

- sent as ASCII text over control channel
- * PASS password
- LIST return list of file in current directory
- * RETR filename retrieves (gets) file
- STOR filename stores (puts) file onto remote host

sample return codes

- status code and phrase (as in HTTP)
- * 331 Username OK, password required
- 125 data
 connection
 already open;
 transfer starting
- * 425 Can't open data connection
- 452 Error writing
 file

Chapter 2: outline

- 2.1 principles of network applications
 - app architectures
 - app requirements
- 2.2 Web and HTTP
- 2.3 FTP
- 2.4 electronic mail
 - SMTP, POP3, IMAP
- 2.5 DNS

- 2.6 P2P applications
- 2.7 socket programming with UDP and TCP


Electronic mail

Three major components:

- user agents
- mail servers
- simple mail transfer protocol: SMTP

User Agent


- * a.k.a. "mail reader"
- composing, editing, reading mail messages
- e.g., Outlook, Thunderbird, iPhone mail client
- outgoing, incoming messages stored on server



Electronic mail: mail servers

mail servers:

- mailbox contains incoming messages for user
- message queue of outgoing (to be sent) mail messages
- SMTP protocol between mail servers to send email messages
 - client: sending mail server
 - "server": receiving mail server




Electronic Mail: SMTP [RFC 2821]

- uses TCP to reliably transfer email message from client to server, port 25
- direct transfer: sending server to receiving server
- three phases of transfer
 - handshaking (greeting)
 - transfer of messages
 - closure
- command/response interaction (like HTTP, FTP)
 - commands: ASCII text
 - response: status code and phrase
- messages must be in 7-bit ASCII

Scenario: Alice sends message to Bob

- I) Alice uses UA to compose message "to" bob@someschool.edu
- 2) Alice's UA sends message to her mail server; message placed in message queue
- 3) client side of SMTP opens TCP connection with Bob's mail server

- 4) SMTP client sends Alice's message over the TCP connection
- 5) Bob's mail server places the message in Bob's mailbox
- 6) Bob invokes his user agent to read message




Sample SMTP interaction


```
S: 220 hamburger.edu
C: HELO crepes.fr
S: 250 Hello crepes.fr, pleased to meet you
C: MAIL FROM: <alice@crepes.fr>
S: 250 alice@crepes.fr... Sender ok
C: RCPT TO: <bob@hamburger.edu>
S: 250 bob@hamburger.edu ... Recipient ok
C: DATA
S: 354 Enter mail, end with "." on a line by itself
C: Do you like ketchup?
C: How about pickles?
C: .
S: 250 Message accepted for delivery
C: QUIT
S: 221 hamburger.edu closing connection
```

Mail message format

ASCII characters only



Mail access protocols



- * SMTP: delivery/storage to receiver's server
- mail access protocol: retrieval from server
 - POP: Post Office Protocol [RFC 1939]: authorization, download
 - IMAP: Internet Mail Access Protocol [RFC 1730]: more features, including manipulation of stored msgs on server
 - HTTP: gmail, Hotmail, Yahoo! Mail, etc.

Chapter 2: outline

- 2.1 principles of network applications
 - app architectures
 - app requirements
- 2.2 Web and HTTP
- 2.3 FTP
- 2.4 electronic mail
 - SMTP, POP3, IMAP
- 2.5 DNS

- 2.6 P2P applications
- 2.7 socket programming with UDP and TCP

DNS: domain name system

people: many identifiers:

SSN, name, passport #

Internet hosts, routers:

- IP address (32 bit) used for addressing datagrams
- "name", e.g.,www.yahoo.com -used by humans
- Q: how to map between IP address and name, and vice versa?

Domain Name System:

- distributed database implemented in hierarchy of many name servers
- application-layer protocol: hosts, name servers communicate to resolve names (address/name translation)
 - note: core Internet function, implemented as applicationlayer protocol
 - complexity at network's "edge"

DNS: services, structure

DNS services

- hostname to IP address translation
- host aliasing
 - canonical, alias names
- mail server aliasing
- load distribution
 - replicated Web servers: many IP addresses correspond to one name

why not centralize DNS?

- single point of failure
- traffic volume
- distant centralized database
- maintenance

A: doesn't scale!

DNS Servers

root servers:

direct queries to top-level domain servers


top-level domain (TLD) servers:

- responsible for com, org, net, edu, aero, jobs, museums, and all top-level country domains, e.g.: uk, fr, ca, jp
- Network Solutions maintains servers for .com TLD
- Educause for .edu TLD

authoritative DNS servers:

- organization's own DNS server(s), providing authoritative hostname to IP mappings for organization's named hosts
- can be maintained by organization or service provider

DNS: a distributed, hierarchical database



Local DNS name server


- does not strictly belong to hierarchy
- each ISP (residential ISP, company, university) has one
 - also called "default name server"
- when host makes DNS query, query is sent to its local DNS server
 - has local cache of recent name-to-address translation pairs (but may be out of date!)
 - acts as proxy, forwards query into hierarchy

DNS name resolution example

 host at cis.poly.edu wants IP address for gaia.cs.umass.edu

iterated query:

- contacted server replies with name of server to contact
- "I don't know this name, but ask this server"



root DNS server

DNS: caching, updating records

- once (any) name server learns mapping, it caches mapping
 - cache entries timeout (disappear) after some time (TTL)
 - TLD servers typically cached in local name servers
 - thus root name servers not often visited
- cached entries may be out-of-date (best effort name-to-address translation!)
 - if name host changes IP address, may not be known Internet-wide until all TTLs expire
- update/notify mechanisms proposed IETF standard
 - RFC 2136

DNS records

DNS: distributed db storing resource records (RR)

RR format: (name, value, type, ttl)

type=A

- name is hostname
- value is IP address

type=NS

- name is domain (e.g., foo.com)
- value is hostname of authoritative name server for this domain

type=CNAME

- name is alias name for some "canonical" (the real) name
- www.ibm.com is really servereast.backup2.ibm.com
- value is canonical name

type=MX

 value is name of mailserver associated with name

Chapter 2: outline

- 2.1 principles of network applications
 - app architectures
 - app requirements
- 2.2 Web and HTTP
- 2.3 FTP
- 2.4 electronic mail
 - SMTP, POP3, IMAP
- 2.5 DNS


- 2.6 P2P applications
- 2.7 socket programming with UDP and TCP

Pure P2P architecture

- no always-on server
- arbitrary end systems directly communicate
- peers are intermittently connected and change IP addresses

examples:


- file distribution (BitTorrent)
- Streaming (KanKan)
- VoIP (Skype)



File distribution: client-server vs P2P

Question: how much time to distribute file (size F) from one server to N peers?


peer upload/download capacity is limited resource



File distribution time: client-server

- server transmission: must sequentially send (upload) N file copies:
 - time to send one copy: F/u_s
 - time to send N copies: NF/u_s
- client: each client must download file copy
 - d_{min} = min client download rate
 - min client download time: F/d_{min}

time to distribute F to N clients using client-server approach




$$D_{c-s} \ge max\{NF/u_{s,}, F/d_{min}\}$$

increases linearly in N

File distribution time: P2P

- server transmission: must upload at least one copy
 - time to send one copy: F/u_s
- client: each client must download file copy
 - min client download time: F/d_{min}



- * clients: as aggregate must download NF bits
 - max upload rate (limting max download rate) is $u_s + \sum u_i$

time to distribute F to N clients using P2P approach

$$D_{P2P} \ge max\{F/u_{s,},F/d_{min,},NF/(u_{s} + \Sigma u_{i})\}$$

increases linearly in N ...

... but so does this, as each peer brings service capacity

Client-server vs. P2P: example

client upload rate = u, F/u = 1 hour, $u_s = 10u$, $d_{min} \ge u_s$

