DOCS / FOOTBALL API FREE

Leagues, seasons & standings#

Everything competition-level lives here. The one habit to build: **resolve the current season through the API** (`/leagues/{id}/season/`) instead of hardcoding season ids.

List leagues

```
GET /api/v2/leagues/
```
copy

PARAM	TYPE	DESCRIPTION
`country`	string	Country name filter, e.g. `Argentina`
`is_women`	bool	Women's competitions only
`include_inactive`	bool	Also return leagues we no longer sync (hidden by default)
`limit` / `offset`	int	Pagination

Any other parameter is a `400` , not a silent no-op — the body names what you sent and lists the ones we accept, so a typo (or a `?search=` we do not support) fails instead of handing back the unfiltered list. There is no name search: filter by `country` and page the result.

```
curl -H "Authorization: Token YOUR_API_KEY" \
     "https://sports.bzzoiro.com/api/v2/leagues/?country=Argentina"
```
copy

League detail

GETTING STARTED
Overview
Authentication
Conventions & limits
Data usage & license FREE

GUIDES
Quickstart: first request
Build a league page
Football player profile
Tennis player profile
Connect to live WebSockets
Working with images
Use BSD from AI agents

FOOTBALL API
Overview FREE
Events & live scores
Leagues, seasons & standings
Competition structure FREE
Teams, players & transfers


```
GET /api/v2/leagues/{id}/seasons/  # all seasons, cached 60 min
GET /api/v2/leagues/{id}/season/   # current season only, cached 30 min
```
copy

```
{ "id": 1635, "name": "Primera LPF 2026", "year": 2026,
  "start_date": "2026-01-01", "end_date": "2026-12-31", "is_current": true,
  "stages": [
    {"stage": "regular-season", "stage_name": "Regular season",
     "matches": 306, "rounds": 34,
     "start_date": "2026-01-24", "end_date": "2026-12-06"}
  ] }
```
copy

Season ids feed the `season_id` filter on events, standings and leaderboards.

`stages` is the competition's structure in the order it is played — qualifying, group or league phase, then knockouts — with the match and matchday counts of each. It is the list of values the `stage` filter on events accepts, so you never have to guess a slug. See Competition structure.

Standings

```
GET /api/v2/leagues/{id}/standings/?season_id=1635    # cached 10 min
```
copy

List leagues
League detail
Seasons
Qualification & relegation zones
Standings
Qualification & relegation zones
Leaderboards
Best XI
Competition venues
See also

Managers, referees & venues
Odds & predictions
TV, broadcasts & social
v1 API (legacy)

MORE SPORTS APIS
Tennis API PRO
Padel API PRO
CS2 API PRO
Darts API PRO
Hockey API PRO
Basketball API PRO
Horse Racing API PRO

WEIGHT OF MONEY
Weight of Money API ADDON

WEBSOCKETS
Overview ADDON
Football live channel
Tennis live channel
Arena 3D

AI & AGENTS
MCP servers

IMAGES & DATA
Image API
Static datasets
OpenAPI explorer

LEGAL
Terms of Service
Privacy Policy
Cookie Notice

Rows carry position, `team_id`, team name, played, won/drawn/lost, goals for/against, points and recent form. Cup-style competitions return a `groups` array (one table per group) instead of a single table — handle both.

Qualification & relegation zones

Every row carries a `zone` describing what that position leads to, and the response carries a `zones` legend so you can colour a table without walking it. For a flat table `zones` is an array; for a grouped competition it is a map keyed by group name, matching `groups`.

```
{
  "standings": [
    { "position": 1, "team_name": "Sporting CP", "pts": 82,
      "zone": { "key": "cl", "label": "Champions League", "type": "qualification" } }
    { "position": 9, "team_name": "Estoril", "pts": 41, "zone": null }
  ],
  "zones": [
    { "key": "cl", "label": "Champions League", "type": "qualification", "from": 1, "
    { "key": "rel", "label": "Relegation", "type": "relegation", "from": 17, "to": 18
  ]
}
```

copy

FIELD	DESCRIPTION
`label`	The competition's own wording, verbatim — `Champions League`, `Promotion Playoffs`, `Championship round`, `Copa Sudamericana`
`type`	Coarse bucket: `qualification` · `promotion` · `playoff` · `relegation` · `other`. Colour and reason against this, not against the label
`key`	Stable short slug for the label (`cl`, `elq`, `promo`, `rel`, …). Useful as a CSS class
`from` / `to`	Legend only — the first and last position the band covers, 1-based and inclusive

`zone` is `null` where the position leads nowhere in particular, and on the handful of competitions that publish no zones at all and for which we have declared none — some North American leagues, where qualification is decided in a conference table rather than the overall one, and some women's competitions. Treat a missing zone as "unknown", not as "no objective".

Zones describe the season total table. A team is labelled by the position it holds in the table you are reading, which for a few hours after a matchday can run ahead of the official one.

Whether a team has already secured or lost an objective mathematically is not part of this response.

Leaderboards

```
GET /api/v2/leagues/{id}/top/{stat}/    # cached 10 min
```

copy

PARAM	TYPE	DESCRIPTION
`stat` (path)	string	`scorers` · `assists` · `yellowcards` · `redcards` · `fouls`
`season_id`	int	Defaults to the current season
`team_id`	int	Rank one squad instead of the whole league
`limit`	int	Default 20, max 50

Each row: `rank`, `player_id`, `player_name`, `position`, `team_id`, `team_name`, `value`, `matches`. The response echoes `team_id` — null when you did not filter.

One team's scorers. Use `team_id` rather than pulling the league table and filtering it yourself. `limit` caps at 50, so a striker who is nowhere near his league's top 50 is simply absent from that list, and an absence reads exactly like a player who has not scored. With `team_id` the ranking is computed inside the squad, so rank 1 is that club's leading scorer.

```
GET /api/v2/leagues/85/top/scorers/?team_id=1042&season_id=1635
```

copy

Best XI

```
GET /api/v2/leagues/{id}/bestxi/{season_id}/                  # season best XI, cach
GET /api/v2/leagues/{id}/bestxi/{season_id}/{round_number}/   # matchday best XI, ca
```

Best-rated eleven in a formation layout — render straight onto a pitch graphic (combine with the Image API for faces).

Competition venues

```
GET /api/v2/leagues/{id}/venues/?season_id=…
GET /api/v2/leagues/{id}/seasons/{season_id}/venues/
```

The second form is for tournament-style competitions and supports `host_country_code`, `hosts_final`, `hosts_opening`, `hosts_third_place` and `round` filters — built for World-Cup-style venue pages.

See also

- Build a league page — these endpoints assembled into a working page
- Season objects are also queryable globally: `GET /api/seasons/?league=85` and `?current=true` on the v1 API

← PREVIOUS
Events & live scores

NEXT →
Competition structure

View this page as Markdown · Found a mistake? Tell us

© 2026 Bzzoiro LLC — sports.bzzoiro.com