Search docs...

GETTING STARTED
Overview
Authentication
Conventions & limits
Data usage & license FREE

GUIDES
Quickstart: first request
Build a league page
Football player profile
Tennis player profile
Connect to live WebSockets
Working with images
Use BSD from AI agents

FOOTBALL API
Overview FREE
Events & live scores
Leagues, seasons & standings
Competition structure FREE
Teams, players & transfers
Managers, referees & venues
Odds & predictions
TV, broadcasts & social
v1 API (legacy)

MORE SPORTS APIS
Tennis API PRO
Padel API PRO
CS2 API PRO
Darts API PRO
Hockey API PRO
Basketball API PRO
Horse Racing API PRO

WEIGHT OF MONEY
Weight of Money API ADDON

WEBSOCKETS
Overview ADDON
Football live channel
Tennis live channel
Arena 3D

AI & AGENTS
MCP servers

IMAGES & DATA
Image API
Static datasets
OpenAPI explorer

LEGAL
Terms of Service

Teams, players & transfers#

Teams

```
GET /api/v2/teams/
```
copy

PARAM	TYPE	DESCRIPTION
`country_code`	string	ISO country code, e.g. `AR`
`league_id` / `season_id`	int	Teams competing in a league/season
`in_competition`	bool	Only teams currently in an active competition
`is_women`	bool	Women's teams
`name`	string	Name search
`limit` / `offset`	int	Pagination

```
GET /api/v2/teams/{id}/           # profile: venue, coach, colours, country
GET /api/v2/teams/{id}/squad/     # current squad, ordered by position then shirt num
GET /api/v2/teams/{id}/fixtures/  # date_from, date_to, league_id, status
GET /api/v2/teams/{id}/form/      # last, league_id, venue — see Rolling form
GET /api/v2/teams/{id}/social/    # curated tweets/videos (type filter)
```
copy

```
curl -H "Authorization: Token YOUR_API_KEY" \
  "https://sports.bzzoiro.com/api/v2/teams/755/fixtures/?status=upcoming&limit=5"
```
copy

Matching a team to a country

Every team carries `country_code` next to `country`:

```
{"id": 932, "name": "Türkiye", "country": "Turkey", "country_code": "TR"}
```
copy

Match on the code, not the name. The name moves — "Turkey" became "Türkiye" and every name-matching integration broke the day it did. The code does not.

Two things it is not, so nobody builds on a wrong assumption:

- **It is not strictly ISO 3166-1**, and we are not going to call it that. It agrees with ISO wherever ISO has a code, and uses the customary one where it does not: England `EN`, Scotland `SX`, Wales `WA`, Northern Ireland `NX` — all four of which are `GB` in ISO.
- **It identifies the country, not the team.** Argentina and Argentina U23 both carry `AR`. Use `id` to identify a team.

Empty string when we have no code. That is 1,856 clubs that have never appeared in a fixture carrying country data, plus a handful of historical national sides — USSR, Yugoslavia, East Germany — which have none to give.

Rolling form

`/api/v2/teams/{id}/form/` returns a team's last N finished matches already averaged, instead of you fetching the fixtures and then a stats call per match.

PARAM	TYPE	DESCRIPTION
`last`	int	Window size, 1–40. Default 10.
`league_id`	int	Restrict the window to one competition. Without it every competition counts, which is usually not what you want for league form.

ON THIS PAGE

Matching a team to a country
Rolling form
Squad availability
Teams
Matching a team to a country
Rolling form
Squad availability
Players
Transfers feed
Transfer ledger
Transfer routes
World Cup squads
Images

PARAM	TYPE	DESCRIPTION
`venue`	string	`all` (default), `home` or `away` — narrows the window itself.


```
{"team_id": 8, "team_name": "West Ham United", "requested": 10, "matches": 10,
 "from_date": "2026-08-16T15:00:00+00:00", "to_date": "2026-09-19T11:30:00+00:00",
 "overall": {"matches": 10, "won": 5, "drawn": 3, "lost": 2,
             "goals_for": 28, "goals_against": 15,
             "points_per_match": 1.8, "form": "DLWWWWDWLD",
             "stats": {"ball_possession": {"average": 54.2, "total": 542.0, "matches"
                       "dribbles": {"average": 9.0, "total": 36.0, "matches": 4}}},
 "home": {"...": "same shape"}, "away": {"...": "same shape"},
 "vs_stronger": {"...": "same shape"}, "vs_weaker": {"...": "same shape"}}
```


Read the denominators. Every statistic carries its own `matches` count. In the example above possession is averaged over ten matches and dribbles over four, because only four reported dribbles — averaging them over ten would be inventing six zeroes. `overall.matches` is the window; `stats.<key>.matches` is how much of it that statistic covers.

`form` is most recent first.

`vs_stronger` and `vs_weaker` compare the two sides' published positions in the table of the competition that match belonged to. When either position is missing — a cup tie between two divisions, or a table we do not carry — the match is left out of both strength splits rather than guessed at. It still counts in `overall`, so the strength splits will not always add up to it.

Only finished matches count. A match in progress has half its statistics, and it would drag a form average down without saying so.

Squad availability

Every player in the squad response carries their current availability:

FIELD	TYPE	DESCRIPTION
`availability`	string	`available` · `injured` · `doubtful` · `suspended`
`injury_type`	string	Reason, e.g. `Knee Injury`. Empty when available or unpublished
`injury_expected_return`	date	Expected return, or `null`

For an injured flag, test `availability == "injured"` — a boolean would fold `doubtful` and `suspended` into "not injured".

The status is refreshed several times a day from the team news published for each side's next fixture. `available` is the default value, so it means *not currently listed as missing* rather than *confirmed fit*, and a club with no upcoming fixture in a covered competition is not re-checked until it has one.

Players

```
GET /api/v2/players/
```

PARAM	TYPE	DESCRIPTION
`name`	string	Name search
`team_id`	int	Current club
`national_team_id`	int	Current national-team squad
`nationality_code`	string	ISO code, e.g. `AR`
`position`	string	`G` · `D` · `M` · `F`
`limit` / `offset`	int	Pagination

```
GET /api/v2/players/{id}/               # bio, market value, skills
GET /api/v2/players/{id}/stats/         # per-match log — season_id, team_id, league
GET /api/v2/players/{id}/transfers/     # transfer history with fees
GET /api/v2/players/{id}/career/        # season-by-season summary
```

```
GET /api/v2/players/{id}/national-team/  # international record
GET /api/v2/players/{id}/social/         # tweets/videos
```

The full workflow with examples: Get a football player profile.

Transfers feed

```
GET /api/v2/transfers/
```
copy

PARAM	TYPE	DESCRIPTION
`league_id`	int	Either club has played in this league
`player_id`	int	One player's transfer history
`team_id`	int	In **or** out of this club
`from_team_id` / `to_team_id`	int	Direction-specific
`date_from` / `date_to`	date	Transfer date window
`min_fee`	int	Minimum fee (EUR)
`has_fee`	bool	Only transfers with a disclosed fee
`ordering`	string	Sort field, prefix `-` for descending

`league_id` takes the id from `/api/v2/leagues/` and matches a transfer when **either** side of the move is a club from that league — so an Argentine club selling to Europe and buying from Europe both show up:

```
GET /api/v2/transfers/?league_id=85&limit=10
```
copy

> **Unknown parameters are rejected.** This endpoint answers `400` if you pass a filter it does not recognise, listing what it accepts. A typo like `?league=85` fails loudly instead of quietly returning the unfiltered global feed.
> **Note:** the dataset includes forward-dated moves (announced loans/returns that haven't happened yet). For a "latest transfers" widget, always cap `date_to` at today.

Transfer ledger

The feed answers who moved. The ledger answers what it cost.

```
GET /api/v2/transfers/ledger/?team_id=…
GET /api/v2/transfers/ledger/?league_id=…      # every club in the league, max 40
```
copy

PARAM	TYPE	DESCRIPTION
`team_id`	int	One club. Mutually exclusive with `league_id`
`league_id`	int	Every club in that league
`date_from`	date	Window start (ISO)
`date_to`	date	Window end. Never reaches past today whatever you pass

Each club comes back with `incoming` and `outgoing` blocks — moves, how many were permanent, loans, free and undisclosed, the fees that were published, and the average age — plus `gross_spend_eur`, `gross_income_eur`, `net_spend_eur`, `loan_dependency_pct`, `squad_size`, `turnover_pct`, `age_in` and `age_out`.

Three things decide these numbers, and you should know them before quoting one:

Money only counts where a fee was published. A move with no figure lands in `undisclosed`, not as a zero. Summing the blanks as zeroes reports a tenth of what the big leagues actually spend. `free` is the separate, known case of a fee of nothing.

A loan return is not a signing. A player coming back from a loan is the same player returning to where he already belonged. Counting him as an arrival inflates the arrivals of every club that lends

anyone out, and the raw feed gives you no warning that it happened.

`turnover_pct` **is measured against today's squad.** We do not keep historical squad sizes, so a long window can exceed 100%. That is not a bug — it means the club moved more players than it currently holds.

Transfer routes

```
GET /api/v2/transfers/routes/?team_id=…&min_moves=3
```

copy

PARAM	TYPE	DESCRIPTION
`team_id` / `league_id`	int	Scope, same rules as the ledger
`date_from` / `date_to`	date	Window
`min_moves`	int	Minimum moves for a pair to count (default 2)
`limit`	int	Default 50, max 200

The club pairs that repeat, ranked: `moves`, `loans`, `fees_eur` and up to five of the players who walked it.

Only moves with a real club at both ends are counted. "No team" is how the dataset spells free agency, not a destination, and it is excluded — without that it is the busiest route of almost every club on earth.

A club's own academy does count as a route, so the top line for a big club is often its own under-21s. That is the same question asked of the one feeder it controls.

World Cup squads

```
GET /api/v2/worldcup/squads/              # team, group, status, has_player
GET /api/v2/worldcup/squads/{team_id}/
```

copy

Tournament squad lists with per-player status — built for tournament hub pages.

Images

Badges and photos come from ids, no extra calls: `/img/team/{id}/`, `/img/player/{id}/?sor=true&bg=transparent` — see Working with images.

← PREVIOUS
Competition structure

NEXT →
Managers, referees & venues

View this page as Markdown · Found a mistake? Tell us

Terms of Service · Privacy · Cookies · Refunds · Data licence

© 2026 Bzzoiro LLC — sports.bzzoiro.com