Search docs...

GETTING STARTED
Overview
Authentication
Conventions & limits
Data usage & license FREE

GUIDES
Quickstart: first request
Build a league page
Football player profile
Tennis player profile
Connect to live WebSockets
Working with images
Use BSD from AI agents

FOOTBALL API
Overview FREE
Events & live scores
Leagues, seasons & standings
Competition structure FREE
Teams, players & transfers
Managers, referees & venues
Odds & predictions
TV, broadcasts & social
v1 API (legacy)

MORE SPORTS APIS
Tennis API PRO
Padel API PRO
CS2 API PRO
Darts API PRO
Hockey API PRO
Basketball API PRO
Horse Racing API PRO

WEIGHT OF MONEY
Weight of Money API ADDON

WEBSOCKETS
Overview ADDON
Football live channel
Tennis live channel
Arena 3D

AI & AGENTS
MCP servers

IMAGES & DATA
Image API
Static datasets
OpenAPI explorer

LEGAL
Terms of Service

v1 API (legacy)#

The original football API lives at `/api/` and keeps working — its URLs are frozen for compatibility. **New projects should use v2**: v2 has more resources (transfers, referees' matches, best XI, comparison grids), cleaner shapes and better caching.

What v1 offers
Player references in shotmap, average positions and incidents
Differences that bite when migrating
Player references in shotmap, average positions and incidents

What v1 offers

```
Base URL:  https://sports.bzzoiro.com/api/
```
copy

ENDPOINT	NOTES
`GET /api/leagues/` · `/{id}/` · `/{id}/standings/`	`standings` takes `?season=`
`GET /api/teams/` · `/{id}/`	`country`, `league`, `in_competition`
`GET /api/events/` (aliases `/fixtures/`, `/matches/`)	`league`, `season`, `team`, `status`, `date_from/to`, `full=true` expands lineups/stats, `tz` shifts datetimes
`GET /api/live/`	Live matches, `full`, `tz`
`GET /api/predictions/`	`league`, `upcoming`, `date_from/to`
`GET /api/players/` · `/{id}/`	`search`, `team`, `nationality`, `position`
`GET /api/player-stats/`	`player`, `event`, `team`
`GET /api/odds/` + `/compare/` + `/best/` + `/bookmakers/` + `/polymarket/`	Decimal odds
`GET /api/managers/` · `/{id}/`	`search`, `team_id`, `profile`, `team_style`
`GET /api/seasons/`	`league`, `current=true` — also handy from v2 code
`GET /api/venues/` · `/{id}/`	`city`, `country`, `min_capacity`
`GET /api/tv-channels/` · `/broadcasts/`	TV data
`GET /api/referees/`	`league`, `name`
`GET /api/predicted-lineup/{event_id}/`	Predicted XI with confidence
`GET /api/social/`	**Deprecated** — use `/api/v2/social/` (v1 allowed anonymous access and extra types; v2 restricts to `tweet` / `video`)

v1 uses page-number pagination (`?page=`) with page size 50, unlike v2's `limit` / `offset`.

Differences that bite when migrating

TOPIC	V1	V2
Pagination	`?page=`	`?limit=&offset=` (max 200)
Timezones	`?tz=` shifts datetimes	Always UTC
Filters	`league`, `season`, `team`	`league_id`, `season_id`, `team_id`
Expansion	`?full=true` inlines lineups/stats	Explicit sub-resources per concern
Social	Anonymous, includes news	Token required, `tweet` / `video` only
Players in spatial data	`player_id` — same ids as v2	`player_id`

Player references in shotmap, average positions and incidents

Both versions now name players by **our** player id — the one `/api/players/{id}/` and `/api/v2/players/{id}/` answer to — under the key `player_id`, and `null` when the player is not in our database.

v1 used to publish a `pid` key instead, holding an internal reference that was never a valid player id here: joining it against `/api/players/` returned either nothing or, in about one case in twenty, a completely unrelated player with no error to show for it. If you built against `pid`, read `player_id` and the join works. The same applies to `incidents`, where `player_id`, `player_in_id`, `player_out_id` and each `sequence` step now hold our ids too.

The complete v1 surface is browsable in Swagger UI and ReDoc.

← PREVIOUS
TV, broadcasts & social

NEXT →
Tennis API

View this page as Markdown · Found a mistake? Tell us

© 2026 Bzzoiro LLC — sports.bzzoiro.com