

# Computer Vision for HCI

## 2-D Shape

1

## Region Representations/Properties

- Once regions have been identified, properties of regions can be input to higher-level decision-making procedures
  - Recognition or inspection
- Common geometric properties of region useful for simple shape description
  - Boundary, bounding box, extremal points, area, perimeter, compactness/circularity, moments, etc.
- We will examine geometric and shape representation/properties for **binary** images [(0,1) or (0, 255)]
  - Assumes have segmented out pixels for the object of interest

2

2

## Boundary Coding

- Regions can be represented by their boundaries instead of an image
- Simplest form is linear list of border pixels of each region




3


3

## Chain Code Representation


- Simple technique for representing shape of contour
- Each directed line segment is assigned code
- Chain code is string of those ordered codes



Binary image



Chain code:  
"001003332221211"



4

4

## Shape Number

- Chain codes dependent upon:
  - Orientation and start point of contour
- Invariance to rotation by integer multiples of quantization ( $90^\circ$ )
  - Take “circular” first-difference of chain code:  $f(x)-f(x-1)$   
Chain code: 0010033332221211  
First-diff: 3013030003003130 (1-2=3!)
  - Could also align grid to main axes of object
- Invariance to starting point
  - Circular shift first-diff number to be minimal integer  
First-diff: **3013030003003130**  
Shape #: 0003003130**301303**

5

5

## Internal/External Boundaries

- When region has one or more hole boundaries, represented by chain code for each of them
  - Spatial relation between contours?



6

6


## Quadtree Representation

- Quadtree encodes entire region (not just boundary)
  - Binary image
- Each node of quadtree represents a square region in the image
  - Has one of 3 labels: FULL, EMPTY, MIXED
- Subdivide nodes until either FULL or EMPTY

7

7

## Quadtree Example



8

8

## Quadtree

- Tree/graph matching for recognition
- Previous example is “blocky”
  - Small image grid
  - Need many more levels/cells (resolution) to approximate curves
- Quadtrees have been used to represent map regions in geographic information systems (GIS)

9

9

## Medial Axis Transform


- “Skeleton” representation of binary region
- Steps
  - Original binary image is  $f^0$
  - Iteratively compute (until no change):
$$f^k(x, y) = f^0(x, y) + \min(f^{k-1}(p, q))$$
$$\forall (p, q) \text{ 4-connected to } (x, y)$$
  - Medial axis given by all points  $(x, y)$  such that:

$$f^k(x, y) \geq f^k(p, q)$$

10

10

## Medial Axis Example



11

## Medial Axis Extras

- Also can recover shape from medial axis with iterative algorithm
- Matlab code available for skeletonization
  - *Skel* function (bwmorph)
  - Also has morphological functions

12


12

# Medial Axis of 3-D Surface

(Prof. Tamal Dey)




KNOT



HEART




HAND



MANNEQUIN



DINOSAUR




FEMALE

13

## Bounding Box

- Often useful to have rough idea of where region located (e.g., for tracking)
- Bounding box is enclosing rectangle that touches topmost, bottommost, leftmost, and rightmost points in region
- As shown, can include much of background

Bounding box




14

14

## Extremal Points

- Examine where region touches bounding box
- At most 8 distinct “extremal” points/pixels for region on bounding box
  - Topmost left/right
  - Rightmost top/bottom
  - Leftmost top/bottom
  - Bottommost left/right
- Extremals occur in opposite pairs
  - Defines axis for each pair
- Compute approximations of
  - Axis **length**
  - Axis **orientation**




15

15

## Area

- Area  $A$  of binary region  $R$  simply defined as:

$$A = \sum_{(x,y) \in R} 1$$



Binary image

Area = 15 (pixels)

16

16



## Perimeter and Compactness

- Perimeter  $P$  of binary region  $R$  is sum of its border pixels
  - Border pixel has at least 1 background pixel in its neighborhood
- Compactness/Circularity  $C$  of region is defined as follows:

$$C = 4\pi \frac{A}{P^2}$$

$$\text{Circle: } A = \pi r^2 \quad P = 2\pi r$$

$$C = 1$$

$$\text{Square: } A = L^2 \quad P = 4L$$


$$C = \frac{\pi}{4} \quad 17$$

17

## Centroid

- Centroid of binary region is average location of pixels in  $R$ :

$$x_c = \bar{x} = \frac{1}{N} \sum_{(x,y) \in R} x \quad y_c = \bar{y} = \frac{1}{N} \sum_{(x,y) \in R} y$$



Binary image

$$x_c = \frac{1}{15} [2 + (2 \cdot 3) + (3 \cdot 4) + (4 \cdot 5) + (5 \cdot 6)]$$

$$= 4.67$$

$$y_c = \frac{1}{15} [(5 \cdot 2) + (4 \cdot 3) + (3 \cdot 4) + (2 \cdot 5) + 6]$$

$$= 3.34$$

*Useful for target tracking!*

18

18

## Signatures


- Useful for finding preliminary landmarks
- Horizontal signature of binary image
  - Projection of image onto the x-axis

$$s_x = \sum_y B[x, y]$$

- Vertical signature of binary image
  - Projection of image onto the y-axis

$$s_y = \sum_x B[x, y]$$

(consider figure-8 shape)



19

19

## Spatial Moments

- Spatial moments often used to describe region shape

$$m_{pq} = \sum \sum x^p y^q I[x, y]$$

“Area”  $\rightarrow$   $A = m_{00} = \sum \sum x^0 y^0 I[x, y]$  } “Zeroth order”

[for binary (0,1) image]  $m_{10} = \sum \sum x^1 y^0 I[x, y]$  } “First order”

$m_{01} = \sum \sum x^0 y^1 I[x, y]$  }

“Centroid”  $\rightarrow \bar{x} = \frac{m_{10}}{m_{00}} \quad \bar{y} = \frac{m_{01}}{m_{00}}$

20

20

## Central Moments

- Central moments (translation invariant)

$$\mu_{pq} = \sum \sum (x - \bar{x})^p (y - \bar{y})^q I[x, y]$$

$$\bar{x} = \frac{m_{10}}{m_{00}} \quad \bar{y} = \frac{m_{01}}{m_{00}}$$

21

21

## Second-Order Central Moments

- Three second-order central moments

$$\mu_{20} = \sum \sum (x - \bar{x})^2 (y - \bar{y})^0 I[x, y]$$

$$\mu_{11} = \sum \sum (x - \bar{x})^1 (y - \bar{y})^1 I[x, y]$$

$$\mu_{02} = \sum \sum (x - \bar{x})^0 (y - \bar{y})^2 I[x, y]$$

22

22

## Moment Ellipse Orientation

- If region is ellipse, second-order central moments have useful algebraic description of orientation

Let,

$$a = \mu_{20} = \sum \sum (x - \bar{x})^2 (y - \bar{y})^0 I[x, y]$$

$$b = \mu_{11} = \sum \sum (x - \bar{x})^1 (y - \bar{y})^1 I[x, y]$$

$$c = \mu_{02} = \sum \sum (x - \bar{x})^0 (y - \bar{y})^2 I[x, y]$$

23

23

## Moment Ellipse Orientation

- Resulting orientation relationship

$$\tan(2\theta) = \frac{2b}{a - c}$$

- If ( $b = 0$ ) and ( $a = c$ )
  - Object is too symmetric to allow definition of axis
- *Can also use eigenvalues and eigenvectors to determine ellipse [more on this later...]*

24

24

## Similitude Moments (Invariant to translation and scale)

$$\eta_{ij} = \frac{\mu_{ij}}{(m_{00})^{\frac{i+j}{2}+1}} = \frac{\sum \sum (x - \bar{x})^i (y - \bar{y})^j I[x, y]}{(\sum \sum I[x, y])^{\frac{i+j}{2}+1}}$$

Not integer division operator

for  $2 \leq (i + j) \leq 3$ :

$$N = [\eta_{02} \quad \eta_{03} \quad \eta_{11} \quad \eta_{12} \quad \eta_{20} \quad \eta_{21} \quad \eta_{30}]$$

M.K. Hu, "Visual pattern recognition by moment invariants", Information Theory, IRE Transactions, 1962, pp. 179-187

<http://www.sci.utah.edu/~gerig/CS7960-S2010/handouts/CS7960-AdvImProc-MomentInvariants.pdf>

25


25

## *"Per-pixel"* Moment Visualization ONLY...


Would need to sum all of these values  
across the image to get the actual  
moment value for the image

26


26




27




28




29



30




31




32





33




34

## Works for Binary Images Only?

- NO!
- Can use equations for grayscale (or real-valued) image

$$\eta_{ij} = \frac{\mu_{ij}}{(m_{00})^{\frac{i+j}{2}+1}} = \frac{\sum \sum (x - \bar{x})^i (y - \bar{y})^j I[x, y]}{(\sum \sum I[x, y])^{\frac{i+j}{2}+1}}$$

use grayscale value



for  $2 \leq (i + j) \leq 3$ :

35

35

## Summary

- Given a 2-D binary shape, use representations/properties to characterize the region
  - Recognition or matching
- Methods
  - Chain code
  - Quadtree
  - Medial axis
  - Bounding box, extremal points
  - Area, centroid
  - Perimeter, compactness, circularity
  - Signatures
  - Moments

36

36