```
Thread2(Table t){
this.t=t;
}
public void run(){
t.printTable(10);
}
}
public class SynchronizationDemo{
public static void main(String[] args){
Table obj=new Table();
Thread1 t1=new Thread1(obj);
Thread2 t2=new Thread2(obj);
t1.start();
t2.start();
}
}
```

Slip 20

1) Write a Java program to accept a number using the BufferedReader class and generate the multiplication table of the given number.

```
import java.io.*;
public class MultiplicationTable{
public static void main(String[] args)throws IOException{
BufferedReader br=new BufferedReader(new InputStreamReader(System.in));
System.out.print("Enter a number: ");
int n=Integer.parseInt(br.readLine());
for(int i=1;i<=10;i++)
System.out.println(n+" x "+i+" = "+(n*i));
```

```
}
}
```

2) Write a java program to show Multiple Threads Execution.

```
class Thread1 extends Thread{
public void run(){
for(int i=1;i<=5;i++)
System.out.println("Thread 1: "+i);
}
}
class Thread2 extends Thread{
public void run(){
for(int i=1;i<=5;i++)
System.out.println("Thread 2: "+i);
}
}
class Thread3 extends Thread{
public void run(){
for(int i=1;i<=5;i++)
System.out.println("Thread 3: "+i);
}
}
public class MultipleThreads{
public static void main(String[] args){
Thread1 t1=new Thread1();
Thread2 t2=new Thread2();
Thread3 t3=new Thread3();
t1.start();
```

```
t2.start();
t3.start();
}
}
```

OR

2) Write a Java program to store city names and their STD codes using an appropriate collection and perform following operations:

i. Add a new city and its code (No duplicates)

ii. Remove a city from the collection

iii. Search for a city name and display the code.

```
import java.util.*;
public class CityCode{
public static void main(String[] args){
TreeMap<String,Integer> map=new TreeMap<>();
map.put("Pune",20);
map.put("Mumbai",22);
map.put("Delhi",11);
System.out.println("City and STD Code: "+map);
if(!map.containsKey("Nagpur"))
map.put("Nagpur",712);
System.out.println("After adding: "+map);
map.remove("Delhi");
System.out.println("After removing: "+map);
String city="Pune";
if(map.containsKey(city))
System.out.println("STD Code: "+map.get(city));
else
```