```
public static void main(String[] args){
Scanner sc=new Scanner(System.in);
Student[] s=new Student[5];
for(int i=0;i<5;i++){
System.out.println("Enter details of student "+(i+1));
System.out.print("Roll No: ");
int rollno=sc.nextInt();
System.out.print("Name: ");
String name=sc.next();
System.out.print("Percentage: ");
float percentage=sc.nextFloat();
s[i]=new Student(rollno,name,percentage);
}
System.out.println("\nRollNo\tName\tPercentage");
for(int i=0;i<5;i++){
s[i].display();
}
}
}
```

**Slip 9**

**1) Write a java program to calculate area of Cylinder and Circle. (use super keyword).**

```
import java.util.Scanner;


class Circle {
   double radius;


   Circle(double radius) {
```

```
        this.radius = radius;
    }

    void area() {
        double result = Math.PI * radius * radius;
        System.out.println("Area of Circle = " + result);
    }
}

class Cylinder extends Circle {
    double height;

    Cylinder(double radius, double height) {
        super(radius);
        this.height = height;
    }

    void area() {
        double result = 2 * Math.PI * radius * (radius + height);
        System.out.println("Area of Cylinder = " + result);
    }

    void display() {
        System.out.println("Radius = " + super.radius);
        super.area();
        area();
    }
}
```

```
public class CylinderCircle {
   public static void main(String args[]) {

      Scanner sc = new Scanner(System.in);

      System.out.print("Enter radius of Circle: ");
      double radius = sc.nextDouble();

      System.out.print("Enter height of Cylinder: ");
      double height = sc.nextDouble();

      Circle c = new Circle(radius);
      Cylinder cy = new Cylinder(radius, height);

      System.out.println("\nCircle Details");
      System.out.println("----------------------");
      c.area();

      System.out.println("\nCylinder Details");
      System.out.println("----------------------");
      cy.display();

      sc.close();
   }
}
```

**2) Write a java program to accept ‘n’ integers from the user and store them in a collection. Display them in the sorted order. The collection should not accept**

**duplicate elements. (Use a suitable collection). Search for a element using predefined search method in the Collection framework.**

```
import java.util.Scanner;
import java.util.TreeSet;
public class SortedCollection {
   public static void main(String args[]) {
      Scanner sc = new Scanner(System.in);


      TreeSet<Integer> numbers = new TreeSet<Integer>();
      System.out.print("Enter number of integers: ")
      int n = sc.nextInt();
      System.out.println("Enter " + n + " integers:");
      for (int i = 0; i < n; i++) {
         int num = sc.nextInt();
         numbers.add(num);
      }
      System.out.println("\nElements in Sorted Order:");
      System.out.println(numbers);
      System.out.print("\nEnter element to search: ");
      int search = sc.nextInt();
      if (numbers.contains(search)) {
         System.out.println(search + " is present in the collection.");
      } else {
         System.out.println(search + " is not present in the collection.");
      }
      sc.close();
   }
}
```

**OR**

**2) Write a Java program to create a class MyDate with data members dd, mm, and yy. Implement default and parameterized constructors. Display the date in dd-mm-yy format using this keyword.**

```
import java.util.Scanner;
class MyDate {
   int dd;
   int mm;
   int yy;
MyDate() {
      this.dd = 1;
      this.mm = 1;
      this.yy = 2000;
   }
   MyDate(int dd, int mm, int yy) {
      this.dd = dd;
      this.mm = mm;
      this.yy = yy;
   }
   void displayDate() {
      System.out.println("Date: " + this.dd + "-" + this.mm + "-" + this.yy);
   }
}
public class MyDateDemo {
   public static void main(String args[]) {
      Scanner sc = new Scanner(System.in);
      System.out.print("Enter day: ");
      int dd = sc.nextInt();
```