


The proven technology



JAIN POLYMER CO.

FEP EXTRUDED WIRES

extruded fluorinated ethylene propylene wire

Features :

1. Excellent Thermal Stability : Most importantly **FEP** wires and cables have a wide range of service temperature ranging from - 65°C to +260°C. They withstand overheating due to transient current overload. This greatly reduces the hazards of flash over in tightly bundled wiring.
2. Fire Proof : **FEP** does not propagate flame or serve as fuel for fire. It is self extinguishing and non toxic.
3. Wide Frequency : Suitable for very frequency range (D.C. to above 10,000 Mhz) over wide temperature range.
4. Good mechanical strength and flexibility.
5. Low dielectric constant and dissipation factor not altered by heat aging.
6. Due to **FEP** high insulating properties, **FEP** wires and cables are compact compared to conventional materials therefore more circuits per conduit are possible.
7. **FEP** insulated wires and cables are unaffected by long term exposure to virtually all chemical and Corrosive environments including acids, bases, paints, lacquers and fuels etc.
8. P. Extruded up to 10 colours strips for large colour identification for insulation also available for sheath
9. Allow use of Bare, Tin-plate, Copper for FEP-200C.

Applications

Our Stringent quality control procedures have enabled us to develop zero-defect products used in a variety of electronic industries across the country. Some of the application areas are :

- Computer
- Refrigeration Equipments
- Electronic Test Equipments
- Communication Equipments (Mobile and Wireless Sets)
- Electronic Equipments for Aircraft, Radar, Navigation, Electra-Mechanical Application
- Flight Simulators.
- Electronic Control Equipments for Atomic Energy, Satellite Launching, Ground Control, Reactor and Process Control, Telephone Exchange, Lifts
- High performance motors, transformer and rectifiers
- High temperature control valves, Furnance and oven wiring.
- Load cells and pressure transducers
- Infra Red sensing equipments
- Air field lighting equipments
- Thermocouple and heat sensing leads
- Control panel wiring

FEP is a Fluorinated Ethylene Propylene resin that meets the ASTM standard specification for Fep-Fluoro carbon Extrusion Materials under ASTM designation D2116-95a. It is available as pellets. Applications for this family of resins include melt extrusion, coating and impregnating. Products made from FEP are known for their excellent chemical resistance, superior electrical properties and high service temperatures of up to 200C. In addition, FEP provides outstanding low-temperature toughness and unique flame resistance.

Tetra Fluor Ethylene Perfluorpropylene(FEP) is procopolymerization of tetrafluoroethylene and hexafluorpropylene. It is a relatively soft thermoplastic with lower tensile strength, wear resistance, and creep resistance than many other engineering plastics. However, it is chemically inert and has a resistance, a low coefficient of friction, exceptional dielectric properties, heat resistance, retention of properties after service at 400°F with useful properties at -454°F.

FEP fluoropolymer resins are processed by conventional melt-extrusion techniques. High melt strength and draw down capability of these resins facilitates the use of large dies and draw-down tooling to increase production rates. Equipments in contact with molten resin should be made of corrosion resistant metals.

Larger length over diameter extruder barrels are used to provide enough residence time at high production rates to melt these high temperature polymers. Precipitating screw injection molding machines are recommended.

FEP has high transparency (with good transmittance of Ultra Violet and visible wave lengths.). It has long term weather ability and excellent resistance to ozone, sunlight and weather. FEP offers the lowest refractive index of all thermoplastics with low light reflection.

Jain Polymer Co.

Manufacturers of : PTFE/TEFLON WIRE, CABLE, SLEEVE & TAPE

565/32, Cicular Road, Rohtak - 124001 (Haryana)

Tele/Fax : 01262-248604, 248679 • Mobile : 9999995556, 9810046627

E-mail : jainpoly@vsnl.com Website : www.jainpolymers.com

