Computational Framework for Exhaustive Fabric Weave Generation: Mathematics, Algorithms, and Industrial Implementation

Introduction to Algorithmic Textile Generation

The translation of textile manufacturing from a mechanical craft into a rigorous computational discipline requires a profound understanding of mathematical modeling, combinatorial logic, and industrial engineering. At its fundamental core, the weaving process represents one of the earliest forms of algorithmic computation, predating modern computer science by centuries. The invention of the Jacquard loom at the dawn of the nineteenth century introduced the concept of utilizing punched cards to automatically dictate the interlacement of threads, serving as a direct precursor to binary code and modern programmable systems. Within this paradigm, the structural design of woven fabrics operates on a strict binary system: at any given point of intersection within a textile matrix, either the longitudinal warp thread lies above the transverse weft thread, or the weft thread lies above the warp. This inherent binary nature renders the structural design of woven fabrics an ideal candidate for computational generation, algorithmic optimization, and combinatorial analysis.[1]

Building a comprehensive software system for a weaving mill that automatically generates all possible fabric designs based on specific loom configurations demands a highly sophisticated architecture. Such a generative system cannot rely merely on random permutation; rather, it must synthesize pure combinatorics, constraint satisfaction algorithms, and practical textile engineering parameters. It must account for the strict mechanical limitations of the physical loom—such as the number of available heald shafts, treadles, and multi-color weft feeders—while ensuring that the generated mathematical designs result in structurally sound, physically manufacturable fabrics. The software must bridge the theoretical domains of Boolean algebra, topology, and graph theory with the practical realities of industrial textile mills, providing a blueprint for generating, filtering, and outputting every valid weave design under defined constraints.[4]

Furthermore, the sheer volume of combinatorial possibilities in textile design presents a formidable computational challenge. Even for relatively small fabric repeats, the mathematical design space expands exponentially, quickly reaching computationally intractable scales. Therefore, an effective algorithmic approach requires advanced mathematical techniques, including group theory, the Pólya Enumeration Theorem, and equivalence class filtering, to systematically eliminate redundant, symmetrical patterns and isolate only the topologically distinct, usable weaves.[6] This report provides an exhaustive analysis of the logic, mathematical

models, and algorithmic strategies necessary to engineer such a generative weaving software system, focusing on both the theoretical algorithms and their practical implementation within a commercial textile manufacturing environment.

Mathematical Representation of Weaving Structures

The foundation of any algorithmic textile generation system is the precise mathematical representation of both the loom's mechanical state and the resulting fabric structure. In computational terms, the interlacement of threads is universally modeled using a system of binary matrices, where a value of 1 (or a true boolean state) indicates that the warp thread is raised over the weft thread, and a value of 0 (or a false boolean state) indicates that the weft thread is raised over the warp.[9] The generation of a complete fabric pattern is determined by three interdependent mechanical components of the loom, each of which is represented by a specific matrix: the threading draft, the tie-up, and the lifting plan (often referred to as treadling).[12]

The Threading Matrix and Draft Plan

The draft plan dictates exactly how individual longitudinal warp ends are threaded through the heald eyes of specific shafts (or harnesses) across the width of the loom. Mathematically, the threading plan is represented as a binary matrix $T_h \in \{0,1\}^{S \times E}$, where S represents the total number of available shafts on the loom and E represents the total number of warp ends in a single pattern repeat.[15]

A valid threading matrix is subject to a strict mechanical constraint: every individual warp thread must be threaded through exactly one shaft. If a thread bypasses the shafts, it cannot be controlled, and if it is threaded through multiple shafts, it creates an impossible physical conflict. Therefore, the mathematical sum of the elements in any given column of the threading matrix T_h must always be exactly 1. This constraint is expressed algebraically as:

$$\sum_{i=1}^{S} T_{h(i,j)} = 1 \quad \forall j \in \{1, \ldots, E\}$$

The architectural layout of the draft dictates the aesthetic and structural possibilities of the resulting fabric. A traditional "straight draft" places warp thread j into shaft i such that $i = (j \bmod S) + 1$, creating a diagonal matrix structure that is ideal for producing standard twills and basic plain weaves.[17] Conversely, a "pointed draft" or "skip draft" reverses or staggers this arithmetic progression. By manipulating the threading matrix in this manner, weavers can generate complex mirroring effects, such as herringbone, diamond, and complex

geometric motifs, without requiring any additional mechanical shafts.[16]

The Tie-Up Matrix

The tie-up matrix establishes the mechanical linkages between the shafts and the treadles (the pedals or levers that lift the shafts during the weaving process). On a standard dobby or floor loom, a single treadle is typically tied to a specific combination of multiple shafts. This linkage is represented by the binary matrix $T_u \in \{0,1\}^{S \times P_t}$, where P_t is the total number of treadles available on the loom.[21] A value of 1 at the intersection $T_{u(i,k)}$ indicates that shaft i is physically lifted when treadle k is depressed. The dimensions of this tie-up matrix represent the upper bound of structural complexity and independent shed formations for a given loom configuration.[24]

The Treadling Matrix and Lifting Plan

The treadling sequence defines the chronological order in which the treadles are depressed for each sequential weft insertion (often referred to as a "pick"). This operational sequence is modeled as the binary matrix $T_r \in \{0,1\}^{P_t \times P}$, where P is the total number of picks required to complete the pattern repeat.[25] Similar to the constraints placed upon the threading matrix, a standard single-treadle operation requires that only one treadle is depressed per pick, meaning the sum of any column in T_r equals exactly 1.

However, in advanced generative computer-aided design (CAD) systems, table looms, or modern electronic dobby looms, multiple levers or shafts can be activated simultaneously via electronic actuators. In these industrial contexts, the constraint on the treadling matrix is relaxed, and the tie-up and treadling matrices are effectively merged into a single, direct "lift plan" matrix $L \in \{0,1\}^{S \times P}$.[26] This consolidation significantly streamlines the algorithmic computation, as the software only needs to determine which shafts are elevated for each sequential pick.

The Drawdown Matrix

The final woven design, universally known as the drawdown, is represented by a binary matrix $D \in \{0,1\}^{E \times P}$, representing the entire physical surface of the fabric.[28] The mathematical relationship between the threading, tie-up, and treadling matrices deterministically dictates the structural geometry of the drawdown. Using Boolean matrix multiplication (where standard mathematical addition is replaced by the logical OR operation, and multiplication is replaced by the logical AND operation), the drawdown matrix is calculated through the formula:

$$D = T_h^T \times (T_u \times T_r)$$

Alternatively, if the system utilizes a direct lifting plan matrix L rather than separating the tie-up and treadling, the drawdown equation simplifies to $D = T_h^T \times L$.[13] This deterministic Boolean equation serves as the primary computational engine of the software system. By systematically generating and iterating through all valid permutations of T_h, T_u, and T_r, the generative software can exhaustively compute every mathematically possible fabric design D for any given loom configuration.

Permutation, Combinatorics, and the Design Space

Understanding the exact mathematical scale of the design space is critical for engineering the generation algorithm. The number of possible fabric weaves grows exponentially with the loom's configuration, making any naive brute-force generation algorithm computationally catastrophic. To build a highly responsive and efficient software system, the exact combinatorics of the design space must be mapped, and advanced mathematical theorems must be deployed to prune redundant outputs.

Theoretical Upper Bounds of the Design Space

To comprehend the computational challenge, one must first calculate the theoretical upper bounds of the loom's mechanics. If a textile mill operates a loom equipped with S shafts, the theoretical number of distinct tie-up combinations for a single treadle is 2^S. However, a tie-up that lifts zero shafts (leaving the warp entirely below the weft) or lifts all shafts simultaneously (leaving the warp entirely above the weft) produces no interlacement, rendering the fabric structurally invalid. Thus, the total valid tie-up configurations for a single treadle on an S-shaft loom is exactly $2^S - 2$.[31]

When analyzing common industrial configurations, the exponential growth becomes apparent. For a standard 4-shaft handloom, there are only 14 valid tie-up configurations. For an 8-shaft loom, there are 254. However, for a 16-shaft industrial dobby loom, the number of valid combinations jumps to $65,534$, and for a 24-shaft loom, the number exceeds 16.7 million combinations per column.[31]

When this combinatorial explosion is expanded to the full drawdown matrix D of dimensions $E \times P$ (Ends $\times$ Picks), the maximum theoretical number of binary matrices is $2^{E \times P}$. For a seemingly simple 8×8 weave repeat, this yields 2^{64} (approximately 1.84×10^{19}) potential mathematical matrices.[32] Because evaluating, storing, and visualizing 10^{19} matrices

is computationally intractable for any modern software system, the algorithm must prune the search space early by applying combinatorial group theory, identifying topological equivalences, and strictly enforcing physical manufacturing constraints.

Eliminating Duplicates via the Pólya Enumeration Theorem

The raw combinatorial output of a generative binary matrix system contains massive redundancy. A specific weave matrix D may appear completely distinct from another matrix D' in its raw binary form, but if D' can be obtained by shifting the rows or columns of D cyclically, they represent the exact same continuous, repeating textile structure.[9] In a continuous roll of fabric, a pattern that is simply shifted by one warp thread or one weft pick is topologically identical to the original pattern. Furthermore, rotating the matrix 180° or flipping it (which represents viewing the back of the fabric) often results in an equivalent or structurally identical weave.[33]

To effectively filter these mathematically distinct but topologically identical duplicates, the software architecture must utilize the Pólya Enumeration Theorem (PET) and Burnside's Lemma. These mathematical tools calculate the exact number of distinct orbits of a group action on a set, effectively grouping symmetrical matrices into single equivalence classes.[6]

Let X represent the set of cells in the $E \times P$ grid, and G represent the symmetry group acting on that grid. In the context of woven textiles, G is the group of toroidal shifts (cyclic translations of rows and columns representing the infinite repetition of the fabric surface) combined with the dihedral group D_4 (representing the rotations and reflections of the square or rectangular matrix).[35] Burnside's Lemma states that the number of unique weaves (orbits), $|X/G|$, is exactly equal to the average number of configurations fixed by each element $g \in G$:

$$|X/G| = \frac{1}{|G|} \sum_{g \in G} |X^g|$$

where X^g is the set of configurations that remain invariant under the specific symmetry operation g.[38]

By directly encoding these specific toroidal and dihedral symmetries into the software's mathematical validation layer, the algorithm only retains the canonical representative of each equivalence class. This mathematical filtering reduces the output dataset by multiple orders of magnitude, presenting the textile designer with uniquely distinct topological structures rather

than millions of shifted variations of the same fundamental weave.[8]

Practical Textile Constraints and Manufacturing Rules

A theoretically valid binary matrix does not guarantee a physically manufacturable fabric. Woven structures must adhere to strict physical, mechanical, and topological laws to ensure structural soundness, dimensional stability, and suitability for high-speed industrial production.[42] If a generative software system fails to account for these realities, its output will be practically useless to a weaving mill. The software must translate these physical requirements into strict algorithmic constraints that govern the generation engine.

Structural Soundness and Interlacing Rules

A fundamental rule of weaving, deeply analyzed by mathematicians Grünbaum and Shephard in their foundational work on tilings and patterns, dictates that a fabric must physically "hang together".[32] If a generated binary matrix contains a subset of rows and columns that only interlace with themselves and never cross over into the rest of the matrix, the fabric will physically split into separate, unattached layers upon removal from the loom. Such an interlacement is considered mechanically unsound, unless the weaver is explicitly attempting to design a tubular or double-weave fabric.[46]

To prevent the generation of unsound patterns, the algorithmic approach must model the interlacement matrix as a bipartite graph. The weave is defined as structurally sound if and only if its corresponding interlacing graph is fully connected. Therefore, the software must execute a fast connected-components algorithm (such as Breadth-First Search, Depth-First Search, or a Union-Find disjoint set data structure) on the generated matrix to mathematically verify that the pattern will remain a cohesive single layer of fabric when woven.[7]

Maximum Float Length Limits

In weaving terminology, a "float" occurs whenever a warp thread skips over multiple consecutive weft threads (or vice versa) without interlacing. While floats are structurally necessary for generating complex patterns, twills, and satins [44], excessively long floats render the fabric highly susceptible to snagging, poor dimensional stability, decreased abrasion resistance, and significantly lower tear strength.[50]

The industrial constraints placed on maximum float lengths depend heavily on the specific fiber type (e.g., coarse cotton versus fine synthetic filament) and the thread density, which is defined as Ends Per Inch (EPI) and Picks Per Inch (PPI).[50] The mathematical calculation for the maximum allowable float length L_{max} is a function of the yarn's linear density and the fabric's sett. The software must allow the user to input these parameters to dynamically adjust the constraint threshold during generation.

Fiber and Yarn Type	Typical Yarn Count	Standard Sett (EPI × PPI)	Max Acceptable Float Length	Structural and Physical Implications
Coarse Cotton / Canvas	Ne 10/1 - Ne 20/1	40 × 40	3 to 4 threads	High friction restricts yarn movement; maximum tensile strength is achieved at short floats.
Fine Combed Cotton	Ne 40/1 - Ne 60/1	80 × 80	5 to 7 threads	Tighter packing of fine yarns allows slightly longer floats without risk of snagging.
Silk / Synthetic Filament	20 to 50 Denier	120 × 120+	8 to 12 threads	Smooth surface requires higher density; extremely long floats are utilized to create high luster (Sateen).
Heavy Wool / Tweed	Nm 10/2 - Nm 20/2	20 × 20	2 to 3 threads	Bulky, hairy yarns require frequent interlacing to maintain fabric stability and prevent felting distortion.

Table 1: Industrial heuristic constraints for maximum float lengths across different yarn configurations and fabric constructions.[52]

Within the generative algorithm, the float constraint requires that absolutely no row or column in the drawdown matrix D contains a contiguous sequence of identical binary values (1s or 0s) whose length exceeds the user-defined L_{max}.[57]

Loom-Specific Hardware Limitations

The generative software must dynamically ingest the specific mechanical configuration of the target loom to ensure manufacturability. Different loom architectures impose vastly different constraints on the algorithmic design space:

- **Cam Looms:** These are traditional, high-speed production looms restricted to 4 to 8 shafts. The algorithm must heavily limit repeat sizes to simple fractions ($1/1, 2/1, 3/1$), as the mechanical cams cannot execute complex, long-repeat lifting plans.[18]
- **Dobby Looms:** Utilizing mechanical pegs or electronic solenoids, dobby looms can handle between 16 and 32 shafts. For these looms, the algorithm enforces a strict constraint limiting the maximum number of unique columns in the drawdown to the available shaft count.[26]
- **Jacquard Looms:** These machines utilize highly complex harness cords to control every individual warp thread independently, effectively rendering the number of shafts equal to the number of warp ends ($S = E$). While this architecture allows for massive, non-repeating matrices, the generative algorithm must shift from combinatorial permutation to localized cellular automata or image-processing algorithms to generate designs, as the true combinatorial search space for a Jacquard loom is practically infinite.[3]
- **Rapier and Airjet Looms:** These represent the pinnacle of high-speed industrial weaving. While their shedding mechanisms operate similarly to dobby or Jacquard systems, they introduce sophisticated electronic weft feeders capable of firing multiple colors or textures of yarn at extreme velocities. The algorithm must account for feeder sequence logic to fully exploit the capabilities of these machines.[60]

Algorithmic Approach to Exhaustive Generation

To generate all possible valid weave designs rapidly and without crashing system memory, the software must utilize an advanced Depth-First Search (DFS) Backtracking algorithm augmented with robust Constraint Propagation and low-level Bitwise Optimization.[62]

The Backtracking Algorithm Engine

Backtracking is a recursive algorithmic technique that incrementally builds candidate solutions (in this case, binary matrices) row by row. At each incremental step, the algorithm rigorously checks if the current partial matrix violates any of the established physical constraints, such as the maximum float length limit or the bipartite soundness requirement. If a constraint is violated, the algorithm immediately abandons the current branch (a process known as pruning), undoes the last computational step, and explores the next possibility.[63] This dynamic pruning is what makes exhaustive generation possible, preventing the algorithm from wasting vital computational cycles exploring the trillions of invalid branches residing within the vast $2^{E \times P}$ search space.

The step-by-step algorithm functions through the following logical sequence:

1. **Initialize Global Parameters:** The software ingests user inputs for Shafts (S), Repeat Size ($E \times P$), Max Float Length (L_{max}), and Draft Type.
2. **Generate the Threading Matrix (T_h):** If the draft type is fixed by the user (e.g., a standard straight draft), the software populates the T_h matrix directly. If the goal is to search across all possible drafts, the algorithm recursively generates valid T_h matrices, ensuring that each column sum equals exactly 1.
3. **Recursive Tie-up and Lifting Generation:**
   - The system initializes an empty lifting plan L (or separate Tie-up T_u and Treadling T_r matrices if specified).
   - For each sequential pick p from 1 to P:
     - Generate a candidate row for the lifting plan, which is a binary sequence of length S.
     - Mathematically multiply the candidate row by T_h to simulate the current row of the drawdown fabric D_p.
     - **Constraint Check 1 (Horizontal Floats):** Verify that no sequence of continuous 1s or 0s in the row D_p exceeds L_{max}.
     - **Constraint Check 2 (Vertical Floats):** Verify that appending D_p to the previously generated rows does not create a vertical sequence of 1s or 0s exceeding L_{max} in any specific column.
     - If both constraints are satisfied, recursively call the function for the next pick $p+1$.

    - If the constraints are violated, backtrack, discard the candidate row, and try the next sequential binary pattern.
4. **Final Graph Verification:** Once a full $E \times P$ matrix is successfully formed without violating float limits, run the connected-components graph algorithm to ensure the fabric possesses structural soundness.
5. **Isomorphism Filtering:** Filter the successfully generated matrices through the PET equivalence class checker to definitively discard any symmetrical, rotated, or shifted duplicates.[6,7]

Bitwise Operations for High-Speed Computation

Because the generated matrices are entirely binary in nature, storing them as standard multi-dimensional arrays or floating-point numbers is highly inefficient and memory-intensive. Instead, an entire row of a weaving draft can be stored as a single 32-bit or 64-bit unsigned integer.[9] This data structuring allows the software to leverage low-level CPU bitwise operations—specifically bitwise AND (&), OR (|), XOR (^), and logical bit shifts (<<, >>). These operations execute directly on the processor in a single clock cycle, increasing the overall algorithm speed by orders of magnitude compared to traditional array iteration.[9]

For example, to rapidly verify the horizontal float constraint L_{max} within a 64-bit integer representing a newly generated row R, the algorithm does not need to loop through every bit. Instead, it utilizes bit shifting:

Python

```python
# Pseudocode demonstrating fast bitwise float detection
def has_excessive_float(R, L_max):
    # Check for consecutive 1s exceeding L_max
    temp_ones = R
    for i in range(1, L_max + 1):
        temp_ones = temp_ones & (R >> i)

    # Check for consecutive 0s by inverting R
    inv_R = ~R
    temp_zeros = inv_R
    for i in range(1, L_max + 1):
        temp_zeros = temp_zeros & (inv_R >> i)

    # If either temp_ones or temp_zeros is greater than 0, a float violation exists
```

```
return (temp_ones > 0) or (temp_zeros > 0)
```

Matrix multiplication, specifically the operation $T_h^T \times L$, is similarly optimized using bitwise AND operations combined with intrinsic hardware population count (popcount) instructions. This transforms what is traditionally an $O(n^3)$ mathematical operation into an incredibly fast $O(n)$ bitwise reduction, vastly accelerating the search through the combinatorial design tree.[11]

Design Variation and Multi-Feeder Sequences

Advanced industrial weaving encompasses far more than just the structural interlacement of threads; it also involves the strategic insertion of multiple colored, textured, or specialized weft yarns. High-speed rapier and airjet looms utilize advanced electronic weft feeders capable of managing and rapidly switching between up to 16 different weft yarns.[60] The visual intersection of the physical weave structure with complex warp and weft color sequences is known in the textile industry as "color-and-weave effects".[73]

Modeling Feeder Sequences and Color Interactions

To model multi-feeder designs mathematically, the software architecture introduces two new independent vectors to the computational model: W_{rp} (representing the Warp color sequence) and W_{ft} (representing the Weft feeder sequence). The final visual pattern V is generated by a conditional mapping operation applied over the binary drawdown matrix D:

$$V(i,j) = \begin{cases} W_{rp}(j) & \text{if } D(i,j) = 1 \text{ (Warp is visible)} \\ W_{ft}(i) & \text{if } D(i,j) = 0 \text{ (Weft is visible)} \end{cases}$$

By algorithmically holding the structural matrix D constant and systematically varying the W_{ft} feeder sequence, the software can generate thousands of distinct visual variations from a single structural drawdown.[73] Famous traditional textile patterns, such as Houndstooth or Glen Plaid, are not distinct weave structures; rather, they are mathematically derived by combining a standard 2/2 twill structure with a $2:2$ or $4:4$ alternating color sequence in both the warp and the weft feeders.[75]

Mathematical Sequences for Generative Variations

Instead of relying on random brute-forcing to generate variations, highly sophisticated generative systems use established mathematical number sequences to dictate block widths,

threading variations, and feeder color sequences. The Fibonacci sequence ($1, 1, 2, 3, 5, 8, 13, \ldots$) is widely implemented within algorithmic textile design to generate aesthetically pleasing, organically asymmetrical stripes and complex plaid variations.[76] Similarly, fractal arrays and mathematical binomial expansions—derived from algebraic equations such as $(a+b)^2 = a^2 + 2ab + b^2$ —are frequently algorithmically mapped onto profile drafts to generate deeply structured geometric tessellations and repeating motifs.[79]

The software's variation engine can also automatically ingest a base structure (for example, a simple plain weave) and scale its structural complexity based on the available shaft count. A standard 2-shaft plain weave can be mapped mathematically onto a 16-shaft dobby loom using grouped or skip drafts. This expansion allows the introduction of localized structural modifications—such as dropping a single tie-up connection to create an isolated warp float motif—without disrupting the global integrity of the plain weave matrix.[81]

Structural Variation Base	**4-Shaft Execution**	**8-Shaft Execution**	**Algorithmic Variation Approach**
Plain Weave	1-2-3-4 straight draft, 2-treadle alternating tie-up.	1-to-8 straight draft, 2-treadle alternating tie-up.	Expand matrix dimensions. Maintains identical structure while distributing mechanical friction across more heald frames, increasing loom lifespan.
Twill (2/2)	Standard 4-step diagonal progression.	Extended 8-step diagonal, enabling steeper twill angles.	Modify the T_u matrix to shift diagonal intersections. Generates 63° steep twills or 27° reclining twills by altering treadling frequency.

Satin	Impossible (requires minimum 5 shafts).	8-end satin, float length of 7.	Implement algorithmic check for mutually prime step values (e.g., step 3 or 5 for an 8-end satin) to ensure continuous, non-intersecting diagonals.

Table 2: Algorithmic mapping of base weave structures across differing shaft configurations, detailing the resulting variations.

Inverse Design: From Fabric to Machine Configuration

A critical and highly complex module of a comprehensive weaving software system is "inverse design," traditionally known as fabric analysis. In this operational mode, instead of generating a design from loom inputs, the system is fed a target drawdown matrix D (either mathematically generated by an external graphical program or scanned directly from an image of physical fabric) and must dynamically compute the optimal threading T_h, tie-up T_u, and treadling T_r matrices required to physically manufacture it.[82]

Mathematically, this represents a problem of Boolean Matrix Factorization. The algorithm proceeds via the following rigorous steps:

1. **Identify the Unit Motif:** The algorithm scans the global drawdown matrix to find the shortest repeating periodic intervals along both the X and Y axes, utilizing auto-correlation techniques to extract the smallest fundamental repeating grid (D_{unit}).[28]
2. **Column Reduction (Draft Generation):** The algorithm evaluates all columns within D_{unit}. Every structurally unique column mathematically dictates the necessity of an independent heald shaft. If column j_1 is binary-identical to column j_2, both of those warp threads can be threaded onto the exact same shaft. The total number of unique columns establishes the absolute minimum shaft count S_{min} required to weave the fabric.[83]
3. **Row Reduction (Treadling/Tie-up Generation):** Similarly, the algorithm isolates and compares all unique rows in D_{unit}. The total number of unique rows establishes the

absolute minimum number of treadles P_{min} required to execute the lifting sequence.[83]

4. **Matrix Extraction and Assembly:**
    - The mapped assignments of the matrix columns to the unique vectors becomes the Threading Matrix T_h.
    - The mapped assignments of the matrix rows to the unique vectors becomes the Treadling Matrix T_r.
    - The subset of uniquely intersecting vectors forms the Tie-Up Matrix T_u.

If the computed S_{min} exceeds the physical mechanical limitations of the mill's loom (for example, the inputted pattern requires 24 distinct shafts but the mill is only equipped with a 16-shaft dobby loom), the software flags the design as physically unweavable on current machinery. In advanced iterations, the software can attempt to approximate the visual effect by compressing mathematically similar columns using nearest-neighbor clustering algorithms, subtly altering the weave to fit within the 16-shaft constraint while minimizing visual deviation.[30]

Existing Research, CAD Software, and Limitations

The integration of mathematics into textile design has a rich academic and historical context, yet commercial software has often lagged behind pure theoretical research in its implementation of exhaustive combinatorial algorithms.

Academic Context and Combinatorial Research

The mathematical formalization of weaving has been explored deeply within the fields of combinatorics and topology. Researchers such as Fukuda, Kotani, and Mahmoudi have conducted extensive work on the construction and classification of combinatorial weaving diagrams, exploring how continuous threads embed topologically into three-dimensional space.[84] Their work establishes that weaving diagrams can be analyzed as specialized types of four-regular periodic planar tilings, bridging the gap between knot theory and fabric design.[86]

Furthermore, historical efforts by figures such as Ada Dietz in the mid-twentieth century established the use of algebraic expressions, specifically binomial expansions, to systematically write threading drafts and color sequences, demonstrating that mathematical rigor can yield highly complex and aesthetically profound textiles.[79] Ralph Griswold later expanded on this by attempting to classify weaving patterns using cellular automata and fractal geometry, highlighting the vast, untapped potential of algorithmic generation.[73]

Existing CAD Software Landscape and Limitations

Currently, weaving mills and independent designers utilize a variety of Computer-Aided Design (CAD) programs, including Fiberworks, Weave-It, TempoWeave, and Pixeloom.[87] These programs are highly effective at translating manual inputs into visual drawdowns and exporting

standard .WIF (Weaving Information File) formats.

However, a critical analysis of these existing software platforms reveals significant limitations regarding exhaustive algorithmic generation. The vast majority of current weaving CAD software operates as a digital canvas rather than a generative engine. They rely heavily on the designer to manually input the threading, tie-up, and treadling matrices, or they allow users to select from pre-compiled libraries of traditional structures (e.g., basic twills, satins, basket weaves).[73] They generally lack the integrated Constraint Satisfaction Problem (CSP) architecture required to automatically traverse the combinatorial search space and generate *novel*, mathematically valid patterns based on localized constraints like float length or graph connectivity.

Building a new software system that actively generates and filters the design space via backtracking and Boolean matrix factoring directly addresses this significant technological gap in the current textile manufacturing software ecosystem.

Advanced Topics: Output Systems and AI Optimization

Generating millions of mathematically valid, structurally sound weave patterns is computationally achievable using the optimized bitwise backtracking algorithms detailed above. However, manually sorting through and evaluating millions of binary matrices is fundamentally impossible for a human textile designer. Therefore, the output and visualization system must intelligently curate, rank, and filter the data.[89]

Data Representation and Standardization

For each successfully generated and validated design, the system must output a comprehensive, standardized data package containing:

- A scalar analytical value representing the total number of permutations evaluated and subsequently filtered.
- A 2D graphical rendering of the drawdown grid, translating the binary matrix into a visual representation of warp and weft intersections.
- The raw numerical data for the corresponding T_h, T_u, and T_r matrices.
- The optimal electronic feeder selection sequence for accurate multi-colorway generation. This data is ultimately compiled and exported as a .WIF (Weaving Information File), which remains the universal industry standard for interfacing directly with electronic dobby and Jacquard loom control systems.[13]

Ranking and Filtering via Artificial Intelligence

To bridge the critical gap between "mathematically valid" and "commercially viable or highly useful," the software architecture incorporates advanced Machine Learning (ML) to rank and

prioritize the generated permutations.

Supervised deep learning algorithms, particularly Convolutional Neural Networks (CNNs) and Extreme Learning Machines (ELMs), can be trained on massive datasets of historical, commercially successful textile patterns.[92] The AI rapidly evaluates the newly generated drawdowns based on complex aesthetic heuristics—such as motif balance, symmetry, and visual texture distribution—that are difficult to encode via strict algorithmic rules.[95]

Furthermore, Artificial Neural Networks (ANNs) and Genetic Algorithms are increasingly deployed within textile engineering to accurately predict the physical "handfeel" and mechanical properties of the generated binary matrix prior to physical prototyping. By analyzing the crossing-over firmness factor (CFF) and floating yarn factor (FYF) present within the matrix, the AI can reliably predict the resulting fabric's stiffness, shear rigidity, tensile strength, and drape.[97]

The system subsequently utilizes these predictions to rank the exhaustive output list, presenting the mill designer with the top 99th percentile of designs. These highly curated outputs represent textiles that are not only structurally sound and manufacturable within the specific loom's mechanical limits, but also physically durable and aesthetically optimal for their intended commercial application.

Conclusion

The development of an automated, exhaustive weaving generation software system represents a profound convergence of ancient mechanical engineering and modern discrete mathematics. By treating the physical loom as a computational engine, intricate textile patterns are mathematically reduced to binary matrices governed entirely by Boolean algebra and combinatorial logic.

The ultimate success of such a software architecture hinges entirely on its algorithmic efficiency. Utilizing low-level bitwise operations allows the system to compute millions of matrix multiplications in mere seconds, while the rigorous application of the Pólya Enumeration Theorem and deep-first backtracking search trees ensures that the algorithm dynamically prunes redundant symmetries and structural impossibilities long before they consume system memory. By meticulously encoding practical industrial constraints—such as maximum float lengths derived from specific yarn counts, bipartite connectivity for physical fabric soundness, and precise electronic feeder limits—the software guarantees that every single generated design can transition flawlessly from a digital output matrix to a physical, commercially viable textile.

Ultimately, integrating this mathematical architecture with AI-driven evaluation and ranking frameworks provides an unprecedented and immensely powerful tool for the modern weaving mill. It drastically accelerates the ideation process, eliminates the costly requirement for physical trial-and-error sampling, and unlocks deep regions of the combinatorial design space that human designers could not practically explore by hand, thereby redefining the future

boundaries of industrial textile manufacturing.

Works cited

1. ""It's Just Matrix Multiplication": Notation for Weaving" by Lea Albaugh - YouTube, accessed on April 5, 2026, https://www.youtube.com/watch?v=oMOSiag3dxg
2. THE WEAVING OF INTELLIGENCES: THREADS, ALGORITHMS, AND QUANTUM WORLDS - txtilezine, accessed on April 5, 2026, https://www.txtilezine.com/en/the-weaving-of-intelligences-threads-algorithms-and-quantum-worlds/
3. THE JACQUARD LOOM AND THE BINARY CODE - Revolution Fabrics, accessed on April 5, 2026, https://revolutionfabrics.com/blogs/gotcha-covered/the-jacquard-loom-and-the-binary-code
4. Document No. OTR/MCSG/ All types of Weaving Machines (Looms)/1/October 2025, accessed on April 5, 2026, https://heavyindustries.gov.in/sites/default/files/2025-12/category_specific_guidelines_for_weaving_machines_looms.pdf
5. Weaving Loom in Rajkot - Durable, High-Quality Textile Equipment - Justdial Verified, accessed on April 5, 2026, https://www.justdial.com/jdmart/Rajkot/Weaving-Loom/jdm-1119169-ent-2-17700470
6. Pólya enumeration theorem - Wikipedia, accessed on April 5, 2026, https://en.wikipedia.org/wiki/P%C3%B3lya_enumeration_theorem
7. On 3-Harness Weaving: Cataloging Designs Generated by Fundamental Blocks Having Distinct Rows and Columns | The Electronic Journal of Combinatorics, accessed on April 5, 2026, https://www.combinatorics.org/ojs/index.php/eljc/article/view/v15i1r1
8. [1201.1465] Mathematical Modeling of the Weaving Structure Design - arXiv.org, accessed on April 5, 2026, https://arxiv.org/abs/1201.1465
9. Mathematical Modeling in the Textile Industry - arXiv, accessed on April 5, 2026, https://arxiv.org/pdf/2602.20189
10. (PDF) Using Mathematical Methods in the Weaving for Receiving Quantity Valuations of the Textile Structure Variety. - ResearchGate, accessed on April 5, 2026, https://www.researchgate.net/publication/275152163_Using_Mathematical_Methods_in_the_Weaving_for_Receiving_Quantity_Valuations_of_the_Textile_Structure_Variety
11. Mathematical Modeling in the Textile Industry - arXiv, accessed on April 5, 2026, https://arxiv.org/html/2602.20189v1
12. How to make a lift plan! - Blog Post - Lunatic Fringe Yarns, accessed on April 5, 2026, https://lunaticfringeyarns.com/how-to-make-a-lift-plan/
13. Digitizing Traditional Lao Textile to Modern Weave Technique - Semantic Scholar, accessed on April 5, 2026, https://pdfs.semanticscholar.org/a0d0/8440427a43c1a89157f92dcbaf774a8fccea

.pdf
14. Perpetua Digital Weaving Project - Black Mountain College Museum + Arts Center, accessed on April 5, 2026, https://www.blackmountaincollege.org/journal/volume-15/blazejack/
15. Basic Formats of Weaving Draft - Online Clothing Study, accessed on April 5, 2026, https://www.onlineclothingstudy.com/2023/11/basic-formats-of-weaving-draft.html
16. Drafting Plan of Design of the Textile Fabric - TextileSchool4U.Blogspot.com, accessed on April 5, 2026, https://textileschool4u.blogspot.com/2014/04/drafting-plan-of-design-of-the-textile-fabric.html
17. 1 BASIC DRAFTING FOR HANDWEAVERS AN INTRODUCTION TO DESIGNING FABRICS SYMBOLS TERMINOLOGY METHODOLOGY PRACTICAL APPLICATIONS PRE - Woolgatherers, accessed on April 5, 2026, https://woolgatherers.com/Books%20and%20PDF%20Files/BasicDrafting.pdf
18. Weave Types: Plain, Twill, Satin | PDF - Scribd, accessed on April 5, 2026, https://www.scribd.com/presentation/328467260/2-Elementary-Weaves
19. Twills on 4 shafts | Learn to Weave, accessed on April 5, 2026, https://weavingspace.co.uk/twills-4-shafts/
20. View of Weave Structure and Image Pattern Exploration for Modern Double-cloth Design Development by Deploying Digital Technology, accessed on April 5, 2026, https://jtatm.textiles.ncsu.edu/index.php/JTATM/article/view/13908/6428
21. Ask Madelyn: Lifting Plans and Tie-Ups - Handwoven, accessed on April 5, 2026, https://handwovenmagazine.com/lifting-plans-and-tie-ups/
22. Reading a Tie-up | Understanding Weaving Drafts on the Warp Space blog, accessed on April 5, 2026, https://weavingspace.co.uk/reading-a-tie-up/
23. the logic of tie-ups, accessed on April 5, 2026, https://www2.cs.arizona.edu/patterns/weaving/articles/zmw_03_4.pdf
24. How to Read a Tie-up Plan? - Online Clothing Study, accessed on April 5, 2026, https://www.onlineclothingstudy.com/2023/11/how-to-read-tie-up-plan.html
25. Comprehensive Drafts of Woven Fabrics - Scirp.org., accessed on April 5, 2026, https://www.scirp.org/journal/paperinformation?paperid=102078
26. Liftplans | How to read a weaving draft, accessed on April 5, 2026, https://weavingspace.co.uk/liftplans/
27. Treadling | How to read a weaving draft, accessed on April 5, 2026, https://weavingspace.co.uk/treadling/
28. Analysis of Weave Structures, Part 1: Introduction - The University of ..., accessed on April 5, 2026, https://www2.cs.arizona.edu/patterns/weaving/webdocs/gre_ws1.pdf
29. What the Drawdown tells us - Weaving Space, accessed on April 5, 2026, https://weavingspace.co.uk/what-the-drawdown-tells-us/
30. A MATHEMATICAL WEAVER'S NOTES AND GUIDE TO: Shaft Weaving and Graph Design, By Olivier Masson and Francois Roussel, accessed on April 5, 2026, https://www2.cs.arizona.edu/patterns/weaving/webdocs/wa_mr.pdf

31. Weaving and Math: A Great Combination - Handwoven, accessed on April 5, 2026, https://handwovenmagazine.com/weaving-and-math-a-great-combination/
32. 27 Sep 2006, accessed on April 5, 2026, https://www2.cs.arizona.edu/patterns/weaving/webdocs/mo/Griswold-MO.pdf
33. How to remove duplicated matrix (represented in array)? - Stack Overflow, accessed on April 5, 2026, https://stackoverflow.com/questions/5238482/how-to-remove-duplicated-matrix-represented-in-array
34. Repeating Patterns on a Strip - classe, accessed on April 5, 2026, https://www.classe.cornell.edu/~dms79/xrd/xtallography/Repeating%20Patterns%20on%20a%20Strip.htm
35. Numerical Algorithm for P ´olya Enumeration Theorem - Biophysics Simulation Group, accessed on April 5, 2026, https://bsg.byu.edu/docs/papers/polya.pdf
36. How would you write D_4 in cycle notations? - Mathematics Stack Exchange, accessed on April 5, 2026, https://math.stackexchange.com/questions/3386303/how-would-you-write-d-4-in-cycle-notations
37. A Catalog of Enumeration Formulas for Bouquet and Dipole Embeddings under Symmetries, accessed on April 5, 2026, https://www.mdpi.com/2073-8994/14/9/1793
38. Pólya's Enumeration Theorem, accessed on April 5, 2026, https://feog.github.io/chap1dm.pdf
39. Pólya-Burnside enumeration in combinatorics - Adi Ganesh, accessed on April 5, 2026, https://adiganesh.com/posts/2018-12-15-polya-burnside/
40. Algorithms for Matrix Canonical Forms - Cheriton School of Computer Science, accessed on April 5, 2026, https://cs.uwaterloo.ca/~astorjoh/diss2up.pdf
41. View of Constructing a Canonical form of a Matrix in Several Problems about Combinatorial Designs - Serdica Journal of Computing, accessed on April 5, 2026, https://serdica-comp.math.bas.bg/index.php/serdicajcomputing/article/view/sjc.2008.2.349-368/pdf
42. (PDF) MODELING THE TENSILE STRENGTH OF WOVEN FABRICS MADE FROM 100 % COTTON WARP YARNS AND POLYESTER/COTTON BLENDED WEFT YARNS - ResearchGate, accessed on April 5, 2026, https://www.researchgate.net/publication/290356059_MODELING_THE_TENSILE_STRENGTH_OF_WOVEN_FABRICS_MADE_FROM_100_COTTON_WARP_YARNS_AND_POLYESTERCOTTON_BLENDED_WEFT_YARNS
43. The effect of weave type on dimensional stability of woven fabrics - ResearchGate, accessed on April 5, 2026, https://www.researchgate.net/publication/233705554_The_effect_of_weave_type_on_dimensional_stability_of_woven_fabrics
44. WEAVING TECHNOLOGY II, accessed on April 5, 2026, https://web.itu.edu.tr/~berkalpo/Weaving_Lecture/Weaving_Chapter1a_06S.pdf
45. When a Fabric Hangs Together (Or Doesn't) - The University of Arizona, accessed

on April 5, 2026, https://www2.cs.arizona.edu/patterns/weaving/webdocs/gre_hng1.pdf
46. Satins and Twills: An Introduction to the Geometry of Fabrics - Branko Grunbaum; Geoffrey C. Shephard - University of Washington, accessed on April 5, 2026, http://faculty.washington.edu/moishe/branko/BG119.Satins&twills.pdf
47. "The mystery of the drawdown" – Weaving codes, accessed on April 5, 2026, https://kairotic.org/2015/10/16/the-mystery-of-the-drawdown/
48. [2011.14609] Symmetries of the Honeycomb toroidal graphs - arXiv, accessed on April 5, 2026, https://arxiv.org/abs/2011.14609
49. Weaving 101 | CottonWorks, accessed on April 5, 2026, https://www.cottonworks.com/wp-content/uploads/2021/04/Weaving-101.pdf
50. When weaving in pattern, How long is too long for uncaught warp threads. - Reddit, accessed on April 5, 2026, https://www.reddit.com/r/weaving/comments/n62hlf/when_weaving_in_pattern_how_long_is_too_long_for/
51. Factors of Weave Estimation and the Effect of Weave Structure on Fabric Properties: A Review - MDPI, accessed on April 5, 2026, https://www.mdpi.com/2079-6439/10/9/74
52. How to Calculate Maximum EPI and PPI for a Fabric with Given Count - My Textile Notes, accessed on April 5, 2026, http://mytextilenotes.blogspot.com/2011/01/how-to-calculate-maximum-epi-and-ppi.html
53. Weaving Calculations - Textile School, accessed on April 5, 2026, https://www.textileschool.com/242/weaving-calculations/
54. Understanding Weaving Yarn Sizes, accessed on April 5, 2026, https://www.gistyarn.com/blogs/how-to-weave/understanding-weaving-yarn-sizes
55. Deep dive: Standards to measure textile durability, accessed on April 5, 2026, https://ecostandard.org/resources/report-deep-dive-standards-to-measure-textile-durability/
56. Effect of Float Length and Sett on Fabric Characteristics, accessed on April 5, 2026, https://nopr.niscpr.res.in/bitstream/123456789/33116/1/IJFTR%207%282%29%2036-41.pdf
57. String Theory: Visualizing Weaving Patterns Using Dynamically Generated Tables in KNIME, accessed on April 5, 2026, https://bigbear.ai/blog/string-theory-visualizing-weaving-patterns-using-dynamically-generated-tables-in-knime/
58. (PDF) Study on the float-control weaves application algorithms of computer-aided jacquard graph designing for different figured fabrics Study on the float-control weaves application algorithms of computer-aided jacquard graph designing for different figured fabrics - ResearchGate, accessed on April 5, 2026, https://www.researchgate.net/publication/357528202_Study_on_the_float-control_weaves_application_algorithms_of_computer-aided_jacquard_graph_designing

_for_different_figured_fabrics_Study_on_the_float-control_weaves_application_algorithms_of_computer-a
59. Applying Axial Symmetries to Historical Silk Fabrics: SILKNOW's Virtual Loom - MDPI, accessed on April 5, 2026, https://www.mdpi.com/2073-8994/12/5/742
60. Development of a mechatronic weft selector to enhance patterning capacity in Rapier looms, accessed on April 5, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC12688087/
61. msadse - 11 indian textile industry - Tamil Nadu Open University, accessed on April 5, 2026, https://tnou.ac.in/NAAC/SSR/C1/1.1.5/MSADSE-11.pdf
62. 2.2 Solving Constraint Satisfaction Problems | Introduction to Artificial Intelligence, accessed on April 5, 2026, https://inst.eecs.berkeley.edu/~cs188/textbook/csp/solving.html
63. Backtracking Algorithm - GeeksforGeeks, accessed on April 5, 2026, https://www.geeksforgeeks.org/dsa/backtracking-algorithms/
64. Understanding Algorithms (Backtracking And Constraints), Part 32 - Medium, accessed on April 5, 2026, https://parashar--manas.medium.com/understanding-algorithms-backtracking-and-constraints-part-32-backtracking-39378db9bd6d
65. Design and Evaluation of Algorithms on Backtracking - Jetir.Org, accessed on April 5, 2026, https://www.jetir.org/papers/JETIR2310457.pdf
66. Backtracking & Constraint Satisfaction in AI Coding Interviews, accessed on April 5, 2026, https://www.hellointerview.com/learn/ai-coding/patterns/backtracking
67. Eliminate duplicates from a binary matrix. Can it be done in time better than O(n^2) - Stack Overflow, accessed on April 5, 2026, https://stackoverflow.com/questions/6334503/eliminate-duplicates-from-a-binary-matrix-can-it-be-done-in-time-better-than-o
68. How to generate all combinations given an array of elements using backtracking?, accessed on April 5, 2026, https://cs.stackexchange.com/questions/112959/how-to-generate-all-combinations-given-an-array-of-elements-using-backtracking
69. How to generate all combinations given an array of elements using backtracking?, accessed on April 5, 2026, https://stackoverflow.com/questions/57598045/how-to-generate-all-combinations-given-an-array-of-elements-using-backtracking
70. Bitwise operation - Wikipedia, accessed on April 5, 2026, https://en.wikipedia.org/wiki/Bitwise_operation
71. (PDF) A Representation of Binary Matrices - ResearchGate, accessed on April 5, 2026, https://www.researchgate.net/publication/51978941_A_Representation_of_Binary_Matrices
72. Bitwise Operations Related to a Combinatorial Problem on Binary Matrices - ResearchGate, accessed on April 5, 2026, https://www.researchgate.net/publication/234689306_Bitwise_Operations_Related_to_a_Combinatorial_Problem_on_Binary_Matrices
73. Designing weaving software | F# for fun and profit, accessed on April 5, 2026,

https://fsharpforfunandprofit.com/posts/designing-weaving-software/
74. The Fibonacci Sequence & Weaving - YouTube, accessed on April 5, 2026, https://www.youtube.com/watch?v=tW5aqvMvDfg
75. How to Weave with Multiple Weft Shuttles - SweetGeorgia Yarns, accessed on April 5, 2026, https://sweetgeorgiayarns.com/how-to-weave-with-multiple-weft-shuttles/
76. Drafting with Sequences - Computer Science, accessed on April 5, 2026, https://www.cs.arizona.edu/patterns/weaving/webdocs/gre_seqd.pdf
77. Weavers Workshop: What's a Fibonacci? - Handwoven, accessed on April 5, 2026, https://handwovenmagazine.com/weavers-workshop-whats-fibonacci/
78. Two Go-To Design Tools - Yarnworker - Know-how for the rigid heddle loom, accessed on April 5, 2026, https://yarnworker.com/two-powerhouse-design-tools-fibonacci-and-the-golden-mean/
79. Squeezing the Numbers to Design a Weaving Draft - Banner Mountain Textiles, accessed on April 5, 2026, https://bannermountaintextiles.blogspot.com/2016/10/squeezing-numbers-to-design-weaving.html
80. AA Weaving - The Bridges Archive, accessed on April 5, 2026, http://www.archive.bridgesmathart.org/2013/bridges2013-263.pdf
81. Code Like A Weaver. This article originally appeared on... | by Kristina Taylor | TextNow Engineering Blog | Medium, accessed on April 5, 2026, https://medium.com/textnowengineering/code-like-a-weaver-69e485eda4c8
82. Fabric Analysis —From Drawdown to Draft, accessed on April 5, 2026, https://www2.cs.arizona.edu/patterns/weaving/webdocs/mo/D/FabricAnalysis.pdf
83. Resources for reverse engineering a draft? : r/weaving - Reddit, accessed on April 5, 2026, https://www.reddit.com/r/weaving/comments/1553duv/resources_for_reverse_engineering_a_draft/
84. Mathematical Model of Weaving, accessed on April 5, 2026, https://www.ms.u-tokyo.ac.jp/icms/poster2021/p63.pdf
85. CLASSIFICATION OF COMBINATORIAL WEAVING DIAGRAMS A weave W is defined as a three-dimensional object embedded in the topological, accessed on April 5, 2026, https://www.math.sci.hokudai.ac.jp/~wakate/mcyr/2022/pdf/mahmoudi_sonia.pdf
86. [2108.09464] Construction and Classification of Combinatorial Weaving Diagrams - arXiv, accessed on April 5, 2026, https://arxiv.org/abs/2108.09464
87. LoftyFiber TempoWeave | Weave Design, accessed on April 5, 2026, https://www.tempoweave.com/
88. Comparative Weaving Software #1- Basic Pattern Entry (Updated 2023) - YouTube, accessed on April 5, 2026, https://www.youtube.com/watch?v=q-iMXc3HEww
89. A Generative AI-Driven Industrial Design Framework for Human–GenAI Co-Creation - MDPI, accessed on April 5, 2026, https://www.mdpi.com/2073-8994/18/2/352

90. Artificial intelligence in textile patterns and sizing - Specialty Fabrics Review, accessed on April 5, 2026, https://specialtyfabricsreview.com/2024/09/01/artificial-intelligence-in-textile-patterns-and-sizing/
91. Treadl: Home, accessed on April 5, 2026, https://treadl.com/
92. Fabric Weave Pattern and Yarn Color Recognition and Classification Using a Deep ELM Network - MDPI, accessed on April 5, 2026, https://www.mdpi.com/1999-4893/10/4/117
93. (PDF) Fabric Weave Pattern and Yarn Color Recognition and Classification Using a Deep ELM Network - ResearchGate, accessed on April 5, 2026, https://www.researchgate.net/publication/320391874_Fabric_Weave_Pattern_and_Yarn_Color_Recognition_and_Classification_Using_a_Deep_ELM_Network
94. (PDF) Woven Fabric Pattern Recognition and Classification Based on Deep Convolutional Neural Networks - ResearchGate, accessed on April 5, 2026, https://www.researchgate.net/publication/342431399_Woven_Fabric_Pattern_Recognition_and_Classification_Based_on_Deep_Convolutional_Neural_Networks
95. Innovative Design Algorithm of Huizhou Bamboo Weaving Patterns Based on Deep Learning - The Science and Information (SAI) Organization, accessed on April 5, 2026, https://thesai.org/Downloads/Volume16No5/Paper_95-Innovative_Design_Algorithm.pdf
96. Artificial Intelligence in Generative Design: A Structured Review of Trends and Opportunities in Techniques and Applications - MDPI, accessed on April 5, 2026, https://www.mdpi.com/2411-9660/9/4/79
97. A Systematic Review of AI-Driven Prediction of Fabric Properties and Handfeel - PMC - NIH, accessed on April 5, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC11509711/
98. Effect of Weave Structures on the Low Stress Mechanical Properties of Woven Cotton Fabrics - ResearchGate, accessed on April 5, 2026, https://www.researchgate.net/publication/260384801_Effect_of_Weave_Structures_on_the_Low_Stress_Mechanical_Properties_of_Woven_Cotton_Fabrics