Corner Extraction

Week - 3

Some slides of this lecture are courtesy of profs. S. Lazebnik & K. Grauman

Image Feature Extraction

- Edge detection

- Interest Point Detection (Corner, SIFT)

Image Feature Extraction

- Edge detection

- Interest Point Detection (Corner, SIFT)

Three levels of Vision Processing

- **Low-level vision:**

    – image processing, denoise, filtering, image restoration.

- **Mid-level vision:**

    – <mark>image feature detection</mark>, image segmentation, edge,   contour extraction, perceptual organization,

    – 3D vision reconstruction: Multiview Geometry: 2-1/2D representation, 3D information recovery.

- **High level vision:**

    – visual recognition, classification, object localisation, semantic understanding and labelling, action, activity, event detection.

Three levels of Vision Processing

- Low-level vision:
  - image processing, denoise, filtering, image restoration.
- **Mid-level vision:**
  - <mark>image feature detection</mark>, image segmentation, edge, contour extraction, perceptual organization,
  - 3D vision reconstruction: Multiview Geometry: 2-1/2D representation, 3D information recovery.
- High level vision:
  - visual recognition, classification, object localisation, semantic understanding and labelling, action, activity, event detection.

Content

- Harris Corner Detector
  - The most widely used corner point detector
- SIFT - Scale Invariant Feature Transform (next lecture)

Motivation

- Find "interesting" parts/pieces inside an image
  - e.g. corners, salient patches
  - Focus of attention, fixation.
  - Speed up computation.
  - Compress/extraction of information.
- Applications of interest points
  - Image Matching, Search
  - Object Detection, Object Recognition
  - Image Alignment & Stitching
 - Stereo
  - Tracking

Interest Points

isotropic structure: flat region
➡ not interesting, 0D, not useful for matching

linear structure: edges, lines
➡ edge, can be localized in 1D, subject to the aperture problem

**bi-directional structure:** corners
➡ corner, or **interest point**, can be localised in 2D, good for matching

Interest Points have 2-directional structure.

Application: Corner Detection
(for camera calibration)

courtesy of B. Wilburn

# Application: Robot navigation

courtesy of S. Smith

Application: Matching between two images

Interest points extracted with Harris (~ 500 points)

Content Based Image Retrieval (CBIR)

Query Image

2. Query Database

Query

Answer

Extract

Match

...

1. Extract SIFT features

Candidate matches

Harris Corner Detector

Reference

*Chris Harris & Mike Stephens*, CVIU, 1988

"A Combined Corner and Edge Detector"

Harris Corner: Intuition

- We should easily recognize a corner point by looking through a small window

- Shifting a window in *any direction* should give *a large change* in intensity

# Corner detector



Flat

Corner detector

Flat

Edge

Corner detector

Flat

Edge

Corner

Harris Corner: Mathematics

Change of intensity for the shift $[u,v]$
(local auto-correlation analysis):

$$E(u,v) = \sum_{x,y} w(x,y) \left[I(x+u, y+v) - I(x,y) \right]^2$$

Window function

Shifted intensity

Intensity

Window function $w(x,y) =$

1 in window, 0 outside

Gaussian

Harris Corner: Mathematics

- For small shifts [u,v], we have first-order Tylor approximation for I(x+u,y+v)

$$I(x + u, y + v) \approx I(x, y) + uI_x + vI_y$$

Harris Corner: Mathematics

$$E(u, v) = \sum_{x,y} w(x, y)(I(x + u, y + v) - I(x, y))^2$$

$$= \sum_{x,y} w(x, y)(I(x, y) + uI_x + vI_y - I(x, y))^2$$

$$= \sum_{x,y} w(x, y)(uI_x + vI_y)^2$$

$$= \sum_{x,y} w(x, y)(u^2 I_x^2 + v^2 I_y^2 + 2uv I_x I_y)$$

$$= [u, v] \, M \begin{bmatrix} u \\ v \end{bmatrix}$$

Harris Corner: Mathematics

- For small shift [u,v], we have 1st order Tylor approximation

$$E(u, v) \approx [u, v] \, M \begin{bmatrix} u \\ v \end{bmatrix}$$

- Where M is a 2x2 matrix computed from image derivatives:

$$M = \sum_{x,y} w(x, y) \begin{bmatrix} I_x^2 & I_x I_y \\ I_x I_y & I_y^2 \end{bmatrix}$$

M is called the second order moments (or auto correlation) matrix of gradients.

Harris Corner: Mathematics

Intensity change in shifting window: eigenvalue analysis

$$E(u,v) \cong [u,v] \ M \begin{bmatrix} u \\ v \end{bmatrix}$$

$\lambda_1, \lambda_2 -$ eigenvalues of M

If we try every possible orientation $\mathbf{n}$,
the biggest change and smallest changes in intensity happen in λs.

Corners as distinctive interest points

$$M = \sum w(x,y) \begin{bmatrix} I_x I_x & I_x I_y \\ I_x I_y & I_y I_y \end{bmatrix}$$

2 x 2 matrix of image derivatives (averaged in neighborhood of a point).

Notation:

$$I_x \Leftrightarrow \frac{\partial I}{\partial x} \qquad I_y \Leftrightarrow \frac{\partial I}{\partial y} \qquad I_x I_y \Leftrightarrow \frac{\partial I}{\partial x} \frac{\partial I}{\partial y}$$

What does this matrix reveal?

First, consider an axis-aligned corner:

What does this matrix reveal?

First, consider an axis-aligned corner:

$$M = \sum \begin{bmatrix} I_x^2 & I_x I_y \\ I_x I_y & I_y^2 \end{bmatrix} = \begin{bmatrix} \lambda_1 & 0 \\ 0 & \lambda_2 \end{bmatrix}$$

This means dominant gradient directions align with x or y axis

Look for locations where **both** λ's are large.

If either λ is close to 0, then this is **not** corner-like.

What if we have a corner that is not aligned with the image axes?

General Case

- Since M is symmetric, we have $$M = X \begin{pmatrix} \lambda_1 & 0 \\ 0 & \lambda_2 \end{pmatrix} X^T$$

- (eigen value decomposition)

- We can visualize M as an eclipse with axis length determined by the eigenvalues and orientation determined by X

Direction of the fastest change

Direction of the slowest change

$(\lambda_{max})^{-1/2}$

$(\lambda_{min})^{-1/2}$

Explanation

- X = I (identity matrix)
-

$$\begin{pmatrix} u & v \end{pmatrix} \begin{pmatrix} \lambda_1 & 0 \\ 0 & \lambda_2 \end{pmatrix} \begin{pmatrix} u \\ v \end{pmatrix} = \lambda_1 u^2 + \lambda_2 v^2 = 1$$

What does this matter reveal?

Since *M* is symmetric, we have $M = X \begin{bmatrix} \lambda_1 & 0 \\ 0 & \lambda_2 \end{bmatrix} X^T$

$$Mx_i = \lambda_i x_i$$

The *eigenvalues* of *M* reveal the amount of intensity change in the two principal orthogonal gradient directions in the window.

Corner response function

"edge":
$\lambda_1 \gg \lambda_2$
$\lambda_2 \gg \lambda_1$

"corner":
λ_1 and λ_2 are large,
$\lambda_1 \sim \lambda_2$;

"flat" region
λ_1 and λ_2 are small;

Harris Corner Detector: Mathematics

Measure of corner response: (Cornerness)

$$R = \det M - k\left(\operatorname{trace} M\right)^2$$

$$\det M = \lambda_1 \lambda_2$$
$$\operatorname{trace} M = \lambda_1 + \lambda_2$$

$(k-$ empirical constant, $k = 0.01\text{-}0.1)$

Harris corner detector

1) Compute M matrix for each image window to get their *cornerness* scores.

2) Find points whose surrounding window gave large corner response ($R>$ threshold)

3) Take the points of local maxima, i.e., perform non-maximum suppression

Harris Corner Detector

Classification of image points using eigenvalues of M:

"Edge"
$\lambda_2 \gg \lambda_1$

"Corner"
λ_1 and λ_2 are both large,
$\lambda_1 \sim \lambda_2$;
E increases in all directions

λ_1 and λ_2 are small;
E is almost constant in all directions

"Flat" region

"Edge"
$\lambda_1 \gg \lambda_2$

Harris Corner Detector: Mathematics

- R depends only on eigenvalues of M

- R is large for a corner

- R is negative with large magnitude for an edge

- $|R|$ is small for a flat region

λ_2

"Edge"
$R < 0$

"Corner"

$R > d$

"Flat"
$|R|$ small

"Edge"
$R < 0$

λ_1

Harris Detector: Steps

Harris Detector: Steps

Compute corner response *R (i.e. the "cornerness")*

Harris Detector: Steps

Find points with large corner response: $R >$ threshold

Harris Detector: Steps

Take only the points of local maxima of R

Harris Detector: Steps

Recap: Harris Corner

- Compute the moment (auto-correlation) matrix M
  - captures the structure of the local neighborhood
  - measure based on **eigenvalues** of M
    - 2 strong eigenvalues => interest point
    - 1 strong eigenvalue   => edge or contour
    - 0 or very weak eigenvalues => flat region

- Interest point detection
  - threshold on the eigenvalues
  - local maximum for localization

Recap: Harris Corner

- Corner strength $R = \det(M) - k \, \text{Tr}(M)^2$
- Let α and β be the two eigenvalues. We don't have to calculate them! Instead, use trace and determinant:

$$\mathbf{A} = \begin{bmatrix} a_{11} & a_{12} \\ a_{21} & a_{22} \end{bmatrix} \qquad \begin{aligned} \det(\mathbf{A}) &= a_{11}a_{22} - a_{12}a_{21} \\ \text{tr}(\mathbf{A}) &= a_{11} + a_{22} \end{aligned}$$

- R is positive for corners, negative for edges, and small for flat regions
- **Non-maximal suppression**: select corners that are 8-way local maxima

Expected Learning Outcome

- Understand why and where we need to use interest point detector.

- Learn how to implement Harris corner detector and how to use it.

Reference

- Section 7.1.1: Feature Detector (Computer Vision: Algorithms and Applications 2nd Edition)