

BROWSE & NAVIGATE / NO LLM P. 4

mem status / mem pwd / mem contexts / mem list / mem show / mem switch / mem checkout / mem rename

CREATE, COPY & CONNECT / NO LLM P. 5

mem init / mem add / mem copy / mem branch / mem reference / mem embed

SEARCH & EXPLAIN / MIXED P. 6

mem find / mem search / mem query / mem summarize

DETERMINISTIC CONTENT CHANGES / NO LLM P. 6-7

mem edit / mem move / mem replace / mem chunk / mem delete / mem clear / mem merge / mem dedup

SEMANTIC TRANSFORMATIONS / LLM-BASED P. 8-9

mem atomize / mem distill / mem elaborate / mem forget / mem resolve / mem dedun / mem update / mem meld / mem sever

CHECK, COMPARE & REVIEW / MIXED P. 9-10

mem compare / mem find-duplicates / mem find-redundancies / mem find-ambiguities / mem find-conflicts / mem audit / mem impact / mem review / mem fit / mem check-conformance

HISTORY & RECOVERY / MIXED P. 11

mem log / mem diff / mem trace / mem rationale / mem checkpoint / mem undo / mem redo / mem revert

PROFILES / NO LLM P. 12

mem profile

SHARING & PROTECTION / NO LLM P. 12

mem share / mem lock / mem unlock

SYSTEM & STUDY TOOLS P. 12

mem help

USING HELP**mem help**

Enter the interactive command browser and open syntax help.

mem help "WHAT YOU WANT TO DO"

Describe the action in your own words to see three candidate operations.

CORE CONCEPTS

MEMORY	The basic record unit stored inside a Context and independently selected, reviewed, or changed by Memory-level operations.
CONTEXT	A named hierarchical workspace that contains Memories and organizes child Contexts. The / separator expresses hierarchy in names such as task-1/participant; operations with descendant scope can treat a Context and its descendant Contexts as one subtree. Commands use the current Context when none is specified.
PROFILE	An isolated ownership and storage boundary containing Contexts; different Profiles may contain the same Context name.
OPERATION	A reusable action that reads, analyzes, or changes selected Memories or Contexts through defined inputs and behavior.
GRANT	A permission relationship that can be given or received, selectively allowing someone without direct ownership to read or query a Context and its Memories, or run permitted operations on them, while the Grant remains valid.
SESSION	Stores an analysis or review workflow so it can be reopened and continued. Apply results and checkpoint history separately show whether Context changes were made.
CHECKPOINT	A recoverable history boundary created for each applied operation and recorded per affected Context.

COMMON LOCATORS

NAME	A bare existing Context name is canonical and global, never relative.
.	The current Context captured once when the command starts.
..	The parent of that captured current Context.
./CHILD	A child path relative to that captured current Context.
../PATH	A path relative to the parent of that captured current Context.
UID	A full UID or accepted prefix. In supported direct-Memory operations, scan ordinary local Contexts; exactly one direct owner must match, or ambiguity stops and lists qualified candidates.
CONTEXT:UID	In supported direct-Memory operations, : separates the direct owner Context from its Memory UID or prefix; the Context may be relative, as in ../3:ca562047.

COMMON KEYS

↑/↓	Move by row or Form; hold to accelerate through long lists.
←/→	Change Language or View, or expand and collapse command Forms.
PgUp / PgDn	Jump 10 rows backward or forward in the scrolling Help list.
Home / End	Move to the first Help row or the final command.
Tab / Shift-Tab	Move focus across Language, View, and visible operation groups.
Enter	Open command Forms, then select or inspect the focused Form.
H	Open full command help, or hide Help while exploring from a waiting session.
Esc / Q / Ctrl-C	Close Help, cancel selection, or return to the waiting session.

INPUT RESOLUTION + OMISSION

REQUIRED	The semantic role must be resolved before execution.
TUI	Omission opens an interactive chooser in a TTY.
CURRENT	Omission resolves that endpoint to the current Context.
ERROR	Omission stops instead of inventing an input.
OPTIONAL	A modifier changes otherwise complete default behavior.
CONDITIONAL	Required only in a particular Form or mode.
mem update	TUI picks SOURCE and TARGET.
--from SOURCE	TARGET becomes CURRENT.
--to TARGET	SOURCE becomes CURRENT.
mem distill	SOURCE and TARGET both become CURRENT.
mem merge	TTY picks SOURCE, TARGET, and reach.
merge SOURCE	TARGET becomes CURRENT.
copy UID	TARGET becomes CURRENT.
mem copy	Missing MEMORY causes ERROR.
move UID	TARGET becomes CURRENT.
mem move	Missing MEMORY causes ERROR.

BROWSE & NAVIGATE / NO LLM

mem status

DESCRIPTION Show the current Context's inventory, first five direct Memories, relationships, and latest checkpoints.

USE WHEN Getting oriented to what the current Context contains, how it is connected, and which operations were recently applied.

COMMON INPUTS --short --branch --recursive

mem pwd

DESCRIPTION Print the current canonical Context name without loading its contents.

USE WHEN Confirming the active Context in a script or terminal.

mem contexts

DESCRIPTION List local Contexts and readable cross-Profile Context views.

USE WHEN Exploring every Context currently available to the Profile.

mem list (ls)

DESCRIPTION List a Context's direct items—Memories, Memory references, query views, and embedded Contexts—and its readable child Contexts. Use -r to recursively include items from descendant and embedded Contexts; ls is the compact alias.

USE WHEN Inspecting the structure and direct contents of a Context.

COMMON INPUTS [CONTEXT] -R --copy -r --paste

BROWSE & NAVIGATE / NO LLM / CONTINUED

mem show

DESCRIPTION Show a Memory, reference, embedded Context, or complete Context contents. Use -r to include readable descendants and embedded Contexts as separate owner-preserving blocks.

USE WHEN Reading the complete content of a known item or Context.

COMMON INPUTS [TARGET] --context

NOTE The positional target auto-types an existing Context, UUID-shaped direct item, or CONTEXT:UID. --context remains the explicit Context route and also qualifies a direct-item selector.

mem switch

DESCRIPTION Enter the interactive Context picker, or switch to an explicit Context.

USE WHEN Moving the working position to another existing Context.

COMMON INPUTS [CONTEXT]

mem checkout

DESCRIPTION Switch Contexts using Git-style syntax; with -b, create and switch to a new Context branch.

USE WHEN Using a Git-like workflow to switch or create a branch.

COMMON INPUTS [CONTEXT] -b -r

mem rename

DESCRIPTION Rename an ordinary Context namespace and all lexical descendants while preserving their stable identities.

USE WHEN Correcting the organizational name of an existing Context namespace.

COMMON INPUTS OLD_CONTEXT NEW_CONTEXT --force

CREATE, COPY & CONNECT / NO LLM

mem init

DESCRIPTION Create a new empty Context and make it the current working Context.

USE WHEN Starting a separate workspace for a new topic, task, or group of Memories.

COMMON INPUTS [CONTEXT] --parents

mem add

DESCRIPTION Add one or more Memories to the current or explicit Context.

USE WHEN Adding one or more facts, instructions, or notes directly to a Context.

COMMON INPUTS "MEMORY" --context --memory --input --paste

mem copy

DESCRIPTION Copy one or more directly owned Memories into an existing local Context.

USE WHEN Reusing selected directly owned Memories as independent editable values inside another existing local Context.

COMMON INPUTS UID... --from --to --into --memory

mem branch

DESCRIPTION Copy a Context or subtree into a new branch and switch to it.

USE WHEN Editing a Context or subtree independently while preserving the original.

COMMON INPUTS NEW_CONTEXT --from -r --source-root-only

CREATE, COPY & CONNECT / NO LLM / CONTINUED

mem reference

DESCRIPTION Copy one Source Memory version or direct/recursive Context scope into a Target as an immutable read-only snapshot.

USE WHEN Retaining one exact Memory version or Context scope even if its Source later changes or disappears.

COMMON INPUTS SOURCE --from --to --into --recursive

mem embed

DESCRIPTION Place a live link to one Memory or Context inside a local Target while retaining Source ownership.

USE WHEN Reusing a Memory or Context in another Context while following later Source changes.

COMMON INPUTS SOURCE --from --to --into --before

DISTINCTIONS

REFERENCE Frozen snapshot; later Source changes do not follow.

EMBED Live connection; the Target follows later Source changes.

SEARCH & EXPLAIN / MIXED

mem find

DESCRIPTION Find exact text or explicit regular-expression (regex) matches in readable Memories.

USE WHEN Locating exact words, identifiers, or text patterns within a selected Context scope.

COMMON INPUTS "TEXT" --context -r -a --regex

mem search

DESCRIPTION Semantically rank Memories relevant to a natural-language request across selected Contexts.

USE WHEN Finding relevant Memories through meaning and context, including related content without obvious keyword overlap.

COMMON INPUTS "QUERY" --context -r -a --descendants

mem query

DESCRIPTION Generate an LLM-based answer from readable Context knowledge or an authorized concealed query-only view.

USE WHEN Getting a grounded natural-language answer instead of a list of matching Memories.

COMMON INPUTS "QUESTION" --context -r -a --language

mem summarize

DESCRIPTION Show an LLM-derived overview of ordinary Memories in a readable Context scope.

USE WHEN Obtaining a concise overview of a Context or subtree.

COMMON INPUTS [CONTEXT] -r --tui --copy

DETERMINISTIC CONTENT CHANGES / NO LLM

mem edit

DESCRIPTION Directly replace the content of one or more Memories selected by UID or prefix.

USE WHEN Directly correcting or replacing the content of specific existing Memories.

COMMON INPUTS UID "NEW_CONTENT" --context --input

mem move

DESCRIPTION Move one or more directly owned Memories into another existing local Context.

USE WHEN Changing which local Context directly owns selected Memories while preserving their content and identity.

COMMON INPUTS UID... --from --to --into --memory

mem replace

DESCRIPTION Immediately replace every literal or explicit regular-expression match in ordinary local Memories as one Undoable command.

USE WHEN Correcting, renaming, or redacting exact text throughout a known local Context scope.

COMMON INPUTS "TEXT" "REPLACEMENT" --context --regex --delete-match

DISTINCTIONS

FIND Exact text or regular-expression matching.

SEARCH Semantic ranking by meaning and context.

DETERMINISTIC CONTENT CHANGES / NO LLM / CONTINUED**mem chunk**

DESCRIPTION Mechanically split all splittable direct Memories in one Context, or one selected Memory, at configured sentence, clause, structural, literal, or size boundaries.

USE WHEN One or more direct Memories already have clear sentence or structural boundaries that should become separate Memories.

COMMON INPUTS [TARGET] --context --method
--break-on --min-chars

mem delete (remove)

DESCRIPTION Select a Context or direct item to delete, or name it by locator, name, or UID.

USE WHEN Removing a specific Context or item that is no longer needed.

COMMON INPUTS ITEM --context

mem clear

DESCRIPTION Immediately remove all direct items from one Context or, with --recursive, its local lexical subtree; Undo can restore the command.

USE WHEN Emptying a Context or local lexical subtree while retaining every Context.

COMMON INPUTS [CONTEXT] -r

DETERMINISTIC CONTENT CHANGES / NO LLM / CONTINUED**mem merge**

DESCRIPTION Add Source-only items to a selected Target, leave exact matches unchanged, and choose Source or Target for stored-item conflicts.

USE WHEN Appending Source-only items or bringing a copied or branched Context into a selected Target Context without semantic synthesis.

COMMON INPUTS SOURCE [TARGET] --from --to --into

mem dedup

DESCRIPTION Remove same-role exact duplicates (dup) immediately, retaining the first existing UID for each role-specific identity group.

USE WHEN Removing same-role exact duplicate Memories, Embeds, or References while preserving the first existing UID.

COMMON INPUTS [CONTEXT] -r

DISTINCTIONS

MERGE Deterministic structural union; no synthesis.

MELD Semantic reconciliation of overlap or conflict; may synthesize.

DEDUP Remove exact matches within the same role.

DEDUN Remove exact matches plus semantic redundancy.

CHUNK Mechanical split at existing boundaries.

ATOMIZE Semantic separation into independently reviewable propositions.

SEMANTIC TRANSFORMATIONS / LLM-BASED

mem atomize

DESCRIPTION Immediately atomize the current Context into independently reviewable Memories and save the full analysis for Review.

USE WHEN Untangling requirements or claims that were written together so each can be reviewed and revised independently.

COMMON INPUTS [TARGET] --context --sessions
--evaluate

mem distill

DESCRIPTION Derive higher-level Rules or condition propositions from Case or Example propositions in a bounded Context, optionally guided by a Goal.

USE WHEN Inferring more general Rules or condition propositions from several concrete cases or examples.

COMMON INPUTS --from --to --goal -r

mem elaborate

DESCRIPTION Expand an abstract Goal, Rule, or condition into multiple more specific candidate propositions.

USE WHEN Generating several more concrete candidate Rules or Cases from an abstract concept or condition.

COMMON INPUTS --from --to --rule --goal

SEMANTIC TRANSFORMATIONS / LLM-BASED / CONTINUED

mem forget

DESCRIPTION Apply one complete keep/edit/delete decision batch for an instruction.

USE WHEN Removing or rewriting Memories according to a natural-language instruction whose meaning must be interpreted.

COMMON INPUTS "INSTRUCTION" --context

mem resolve

DESCRIPTION Automatically interpret incompatibility Issues in one complete direct-Memory Context frame and verify one small Fit-YES plan.

USE WHEN Deciding how to repair semantic conflicts or ambiguities within a bounded Context frame.

COMMON INPUTS [CONTEXT] [UID] --context --plain
--memory

mem dedun

DESCRIPTION Immediately resolve role-aware exact plus direct-Memory semantic redundancies (dun), retaining the first existing UID in each group.

USE WHEN Removing role-aware exact plus direct-Memory semantic redundancy while preserving one existing UID in each complete DUN group.

COMMON INPUTS [CONTEXT] --context -d -r

DISTINCTIONS

DISTILL Concrete Cases or Examples to a higher-level Rule.

ELABORATE Abstract Rule or Goal to concrete candidates.

SEMANTIC TRANSFORMATIONS / LLM-BASED / CONTINUED

mem update

DESCRIPTION Update a Target Context from a Source Context, resolving required execution decisions before atomic Apply.

USE WHEN Updating an existing Context using newly verified Memories.

COMMON INPUTS SOURCE TARGET --from --to -r --sessions

mem meld

DESCRIPTION Semantically incorporate an incoming Context into an authoritative baseline, or derive a separate Result from two equal peers.

USE WHEN Combining two bodies of work when overlap, conflicts, and newly synthesized content must be reviewed semantically.

COMMON INPUTS LEFT RIGHT [RESULT] --from --to --into

mem sever

DESCRIPTION Save a Result by selecting, transforming, or excluding Source Memories according to a Criteria Context.

USE WHEN Selecting or transforming Source content according to defined criteria.

COMMON INPUTS SOURCE CRITERIA [RESULT] --from --against --to

NOTE Positional form: 'mem sever SOURCE CRITERIA [RESULT]'. Omitting RESULT self-saves into SOURCE; an explicit fresh RESULT saves elsewhere. --source/--from, --criteria/--against, and --save-as/--to are equivalent role aliases.

CHECK, COMPARE & REVIEW / MIXED

mem compare

DESCRIPTION Compare Memories in two Contexts and report what they share, what differs, and what appears only on one side.

USE WHEN Comparing two Contexts as a whole to understand where they align and differ.

COMMON INPUTS PEER [PEER] -r --sessions --ledger

mem find-duplicates

DESCRIPTION Report same-role exact duplicate direct items.

USE WHEN Inspecting same-role exact duplicate direct items without applying cleanup.

COMMON INPUTS [CONTEXT] -r --context

mem find-redundancies

DESCRIPTION Report same-role exact direct items and semantically redundant direct Memories.

USE WHEN Inspecting complete exact and semantic redundancy before cleanup.

COMMON INPUTS [CONTEXT] --context -d -r

mem find-ambiguities

DESCRIPTION Report ambiguous direct Memories in the current, explicit, or all readable Contexts.

USE WHEN Finding Memories that permit unclear or multiple interpretations.

COMMON INPUTS [CONTEXT] --context --select -a

DISTINCTIONS

UPDATE Revise an existing Target from verified Source changes, then Apply the reviewed plan atomically.

MELD Closer to a semantic merge: reconcile overlap and conflicts into a Baseline or separate Result, with synthesis when needed.

CHECK, COMPARE & REVIEW / MIXED / CONTINUED

mem find-conflicts

DESCRIPTION Report conflicting direct Memory pairs in the current, explicit, or all readable Contexts.

USE WHEN Finding mutually incompatible claims or instructions.

COMMON INPUTS [CONTEXT] --context --select -a

mem audit

DESCRIPTION Run Duplicate, Ambiguity, and Conflict checks plus optional Rule Conformance, save the result, and print its Review receipt.

USE WHEN Performing a combined quality review before revising a Context.

COMMON INPUTS [CONTEXT] --context --select
--against --rule

mem impact

DESCRIPTION Preview or inspect an operation's expected Context effects without applying them.

USE WHEN Verifying an operation's proposed effects before its separate Apply action.

COMMON INPUTS OPERATION --from --to --context
--sessions

CHECK, COMPARE & REVIEW / MIXED / CONTINUED

mem review

DESCRIPTION Inspect terminal execution evidence or a saved report and, where supported, record report responses. Review never applies Memories.

USE WHEN Inspecting applied evidence or revisiting a saved report state.

COMMON INPUTS --context --session --receipt

mem fit

DESCRIPTION Judge whether a defined set of Memories or other propositions is jointly compatible under ordinary interpretation, returning YES, MAY, or NO.

USE WHEN Checking whether a defined set of Memories, Rules, Goals, Examples, or other propositions can jointly hold.

COMMON INPUTS "PROPOSITION"... --ground
--background --receipt

mem check-conformance

DESCRIPTION Check one Context or saved Ground Examples against explicit Rules or condition propositions and report conformance issues.

USE WHEN Verifying whether existing Memories or Examples satisfy stated Rules or condition propositions.

COMMON INPUTS TARGET --against --ground --rule
--example

DISTINCTIONS

AUDIT Run duplicate/redundancy, ambiguity, conflict, and optional conformance together.

FIT Ask whether one set is jointly compatible.

INDIVIDUAL CHECKS Use one find-* or check-conformance operation when only one issue class matters.

CHECK-CONFORMANCE Ask whether subjects follow stated Rules. Neither operation establishes external truth.

HISTORY & RECOVERY / MIXED

mem log

DESCRIPTION Print or search recorded Context, Memory, and Profile history.

USE WHEN Investigating previous operations, checkpoints, or Memory history.

COMMON INPUTS "QUERY" --context --memory
--operations --actions

mem diff

DESCRIPTION Show the differences recorded by a Context checkpoint or the active Update.

USE WHEN Verifying exactly what a recorded operation changed.

COMMON INPUTS [CONTEXT] --raw --stat --verbose

mem trace

DESCRIPTION Trace one retained Memory through its recorded lineage.

USE WHEN Determining where a Memory came from and how it changed.

COMMON INPUTS MEMORY --context --memory --plain

mem rationale

DESCRIPTION Explain where one Memory came from and how it changed over time.

USE WHEN Understanding the source context and lifecycle of one Memory.

COMMON INPUTS MEMORY --context

HISTORY & RECOVERY / MIXED / CONTINUED

mem checkpoint

DESCRIPTION Save the current or an explicit local Context as a manual recovery point for Diff or Revert.

USE WHEN Creating a recovery point before risky work.

COMMON INPUTS "MESSAGE" --context -m --message
--direct

mem undo

DESCRIPTION Undo the most recent recorded command as one unit.

USE WHEN Reversing the latest recorded mutation as one operation.

mem redo

DESCRIPTION Redo the most recently undone recorded Context command.

USE WHEN Reapplying a command that was undone accidentally.

mem revert

DESCRIPTION Restore the current or an explicit local Context to a selected checkpoint after reviewing that revision's complete result.

USE WHEN Restoring a Context to a deliberately saved recovery point.

COMMON INPUTS [CHECKPOINT] --context
--discard-newer --keep

DISTINCTIONS

TRACE Follow recorded lineage step by step.

RATIONALE Read a contextual origin and lifecycle summary in one paragraph.

PROFILES / NO LLM

mem profile

DESCRIPTION Create, select, and manage local MemoryStore Profiles. Profiles can be renamed or permanently removed, and Study headings can be renamed through the picker or explicit profile subcommands.

USE WHEN Managing separate users, environments, or Memory stores.

COMMON INPUTS [PROFILE] --allow --into --from
--recursive

SHARING & PROTECTION / NO LLM

mem share

DESCRIPTION Send one exact Context or lexical Context subtree through a grant-backed receiver endpoint.

USE WHEN Delivering an owned Context to an authorized receiver.

COMMON INPUTS [SOURCE] --to

mem lock

DESCRIPTION Lock the current Context, an auto-typed Context or direct Memory target, a recursive Context set, or the explicit Profile.

USE WHEN Preventing accidental modification of stable material.

COMMON INPUTS [TARGET] --recursive --context
--memory --profile

mem unlock

DESCRIPTION Unlock the current Context, an auto-typed Context or direct Memory target, a recursive Context set, or the explicit Profile.

USE WHEN Reopening protected material for intentional revision.

COMMON INPUTS [TARGET] --recursive --context
--memory --profile

SYSTEM & STUDY TOOLS

mem help

DESCRIPTION Enter the interactive command browser and open syntax help.

USE WHEN Discovering available operations and their invocation forms.