

Blockchain Development

Week: 6

Title: Node.js and TX

Dr Ian Mitchell



Middlesex University,
Dept. of Computer Science,
London

September 26, 2019



Aims

There are four components to hyperledger's composer playground:

- 1 Data
- 2 Access
- 3 Logic
- 4 Query

After last week's introduction to Node.js, this week we will investigate how node.js can be applied to fit the logic of a blockchain application, and essentially work towards transaction completion.



Knowledge

- Retrieving registers
- Updating registers
- Transaction Completion
- Composer API



- ACL
- CTO
- Javascript ES6
 - ECMAScript 2015
 - ECMA is a an organisation for the standardisation of information and communication systems
 - ECMA was founded in 1961
 - www.ecma-international.org
- Netscape submitted Javascript to ECMA for standardisation
- Result ECMAScript
- ES1 - 1997
- ES6 - 2015
- ES8 - 2017

Hyperledger Composer API

Registry Classes



- AssetRegistry
- ParticipantRegistry
- IdentityRegistry
- TransactionRegistry
- Historian



- Add one or more items
- Update one or more items
- Remove one or all items
- Get one or all items
- Check if an item exists
- Resolve one or all items



header

```
/**  
 * Create a transaction  
 * @param {namespace.TransactionName} tx - further comment  
 * @transaction  
 */
```



```
1 /**
2  * Sample business network definition.
3  */
4 namespace org.t4.net
5
6 asset Commodity identified by tradingSymbol {
7   o String tradingSymbol
8   o String description
9   o Double quantity
10  --> Trader owner
11 }
12
13 participant Trader identified by tradeId {
14   o String tradeId
15   o String firstName
16   o String lastName
17 }
18
19 transaction Trade {
20   --> Commodity commodity
21   --> Trader newOwner
22 }
```

¹adapted from hyperledger.org tutorials

Trader² |

ACL



```
1 /**
2  * Sample access control list.
3  */
4
5 rule SystemACL {
6     description: "System ACL to permit all access"
7     participant: "org.hyperledger.composer.system.Participant"
8     operation: ALL
9     resource: "org.hyperledger.composer.system.*)"
10    action: ALLOW
11 }
12
13 rule NetworkAdminUser {
14     description: "Grant business network administrators full access to user resources"
15     participant: "org.hyperledger.composer.system.NetworkAdmin"
16     operation: ALL
17     resource: "*"
18     action: ALLOW
19 }
20
21 rule NetworkAdminSystem {
22     description: "Grant business network administrators full access to system resources"
23     participant: "org.hyperledger.composer.system.NetworkAdmin"
24     operation: ALL
25     resource: "org.hyperledger.composer.system.*)"
26     action: ALLOW
27 }
```

²adapted from hyperledger.org tutorials



```
1 /**
2  * transaction of a commodity from one trader to another
3  * This check could be completed with ACL and is an exercise
4  * @param {org.t4.net.Trade} trade - the trade to be processed
5  * @transaction
6  */
7 async function tradeCommodity(tx) {
8   var ns="org.t4.net.";
9   tx.commodity.owner=tx.newOwner;
10   const commodityRegister = await getAssetRegistry(ns+"Commodity");
11   await commodityRegister.update(tx.commodity);
12 }
```

³adapted from hyperledger.org tutorials

Compare CTO and JS



```
/**
 * Sample business network definition.
 */
namespace org.t4.net

asset Commodity identified by
    tradingSymbol {
    o String tradingSymbol
    o String description
    o Double quantity
    --> Trader owner
}

participant Trader identified by tradeId {
    o String tradeId
    o String firstName
    o String lastName
}

transaction Trade {
    --> Commodity commodity
    --> Trader newOwner
}
```

```
/**
 * transaction of a commodity from one
 * trader to another
 * This check could be completed with ACL
 * and is an exercise
 * @param {org.t4.net.Trade} trade - the
 * trade to be processed
 * @transaction
 */
async function tradeCommodity(tx) {
    var ns="org.t4.net.";
    tx.commodity.owner=tx.newOwner;
    const commodityRegister = await
    getAssetRegistry(ns+"Commodity");
    await commodityRegister.update(tx.
    commodity);
}
```



```
1 /**
2  * transaction of a commodity from one
3  * trader to another
4  * This check could be completed with ACL
5  * and is an exercise
6  * @param {org.t4.net.Trade} trade - the
7  * trade to be processed
8  * @transaction
9  */
10 async function tradeCommodity(tx) {
11   var ns="org.t4.net.";
12   tx.commodity.owner=tx.newOwner;
13   const commodityRegister = await
14     getAssetRegistry(ns+"Commodity");
15   await commodityRegister.update(tx.
16     commodity);
17 }
```

- 1-5 comments
- @param has namespace, followed by transaction name
- @transaction identifies the following function as a TX
- 6 function name is unique and does not match transaction name. It does take transaction as a parameter.
- 7 changes ownership, owner replaced by newOwner
- 8 get Commodity registry
- 9 update Commodity registry

Traders Example

Output Trader



Web t4

PARTICIPANTS

SampleParticipant

Trader

ASSETS

SampleAsset

Commodity

TRANSACTIONS

All Transactions

Submit Transaction

Define

Test

Participant registry for org.t4.net.Trader

ID	Data
0816	<pre>{ "\$class": "org.t4.net.Trader", "tradeId": "0816", "firstName": "", "lastName": "" }</pre>
2490	<pre>{ "\$class": "org.t4.net.Trader", "tradeId": "2490", "firstName": "", "lastName": "" }</pre>

Traders Example

Output Commodity



Web t4

PARTICIPANTS

SampleParticipant

Trader

ASSETS

SampleAsset

Commodity

Define

Test

Asset registry for org.t4.net.Commodity

ID	Data
7058	<pre>{ "\$class": "org.t4.net.Commodity", "tradingSymbol": "7058", "description": "", "quantity": 10, "owner": "resource:org.t4.net.Trader#5800" }</pre>



Traders

```
{
  "$class": "org.t4.net.Trader",
  "tradeId": "0816",
  "firstName": "",
  "lastName": ""
}
{
  "$class": "org.t4.net.Trader",
  "tradeId": "2490",
  "firstName": "",
  "lastName": ""
}
```

Commodity

```
{
  "$class": "org.t4.net.Commodity",
  "tradingSymbol": "7058",
  "description": "",
  "quantity": 10,
  "owner": "resource:org.t4.net.Trader#5800"
}
```



```
1 /**
2  * transaction of a commodity from one trader to another
3  * @param {org.t4.net.Trade} trade - the trade to be processed
4  * @transaction
5  */
6 async function tradeCommodity(tx) {
7   var ns="org.t4.net.";
8   var newOwner = tx.newOwner;
9   return getParticipantRegistry(ns+"Trader")
10    .then(function (traderRegistry){
11      return traderRegistry.exists(newOwner.getIdentifier());
12    })
13    .then(function (exists){
14      if (exists){
15        tx.commodity.owner=tx.newOwner;
16        return getAssetRegistry(ns+"Commodity")
17          .then( function(commodityRegistry){
18            return commodityRegistry.update(tx.commodity)
19          })
20      }
21      else
22      {
23        throw new Error("New Owner, "+newOwner.getIdentifier()+" , does not exist as
24        a Trader. Enter an existing new Owner");
25      }
26    })
27 }
```




- use of promise chains
- first get all traders
- then call method exists
- if exists evaluates to true, the trader exists
- the get asset registry
- and update
- else throw an error

Exist

- inherited from Registry
- Determines whether a specific resource exists
- Returns - a promise that will be resolved with true or false depending on whether the resource exists



SuperType	Name	Return	Description
Registry	add	Promise	Adds a new resource to the registry
Registry	addAll	Promise	Adds a list of new resources to the registry
Registry	exists	Promise	Determines whether a specific resource exists in the registry
Registry	get	Promise	Get a specific resource in the registry
Registry	getAll	Promise	Get all the resources in the registry
Registry	remove	Promise	Remove a resource with a given id from the registry
Registry	removeAll	Promise	Remove a list of resources from the registry



SuperType	Name	Return	Description
Registry	resolve	Promise	Get a specific resource in the registry, and resolve all of the relationships to other assets, participants and transactions
Registry	resolveAll	Promise	Get all the resources in the registry and resolve all their relationships to other assets, participants and transactions
Registry	update	Promise	Updates a resource in the registry
Registry	updateAll	Promise	Updates a list of resources in the registry



Scenario

- Create a transaction that allows managers to add and remove staff
- Check the status of the current participant
- Create a new participant
- Then allow them to add a participant to the registry

Requirements

- status for participant
- need factory to create a new resource
- use of add method



Name	Return	Description
newConcept	Concept	Creates a new concept with a given namespace, type and identifier
newEvent	Resource	Create a new type with a given namespace and type
newRelationship	Relationship	Create a new relationship with a given namespace, type and identifier
newResource	Resource	Create a new resource (an instance of an asset, participant or transaction)



```
1 /**
2  * Sample business network definition.
3  */
4 namespace org.t4.net
5
6 enum Grade {
7     o manager
8     o consultant
9     o intern
10    o clerk
11 }
```

```

:
:
32 transaction AddStaff{
33     o Trader newTrader
34 }
```



```
27  /*
28  * transaction to add new member of staff
29  * @param {org.t4.net.AddStaff} AddStaff - add new staff
30  * @transaction
31  */
32  async function addNewStaff(tx){
33    var ns1='org.t4.net';
34    var me=getCurrentParticipant();
35    if (me.Status === 'manager') {
36      return getParticipantRegistry(ns1+'.Trader')
37        .then( function(traderRegistry){
38          //console.log('me.status value: '+me.Status);
39          var factory = getFactory();
40          var newStaff = factory.newResource(ns1, 'Trader', tx.newTrader.tradeId);
41          console.log('new factory: complete');
42          newStaff=tx.newTrader;
43          console.log('new trader:'+newStaff.tradeId);
44          return traderRegistry.add(newStaff);
45        })
46      }
47    else
48    {
49      throw new Error("You have insufficient privileges to add a member of staff");
50    }
51  }
```



- Notice namespace variable declared differently
- See enumerator type in CTO
- Note transaction AddStaff in CTO
- Mainly to do with using both Factory and Registry methods
- Ideally, have a global variable for namespace
- triple equals sign
- console.log
- allows for debugging
- different browsers have different methods for display
- Currently, Firefox uses CTRL+I
- newStaff is created on lines 39-40
- newStaff is populated on line 42
- Finally, added to the trade registry on line 44



⋮

```
36 transaction RemoveStaff{  
37     o Trader removedStaff  
38 }
```



⋮

```
53 /*  
54  * transaction to remove staff from registry  
55  * @param {org.t4.net.RemoveStaff} RemoveStaff - remove staff member  
56  * @transaction  
57  */  
58 async function removeStaff(tx){  
59   var ns='org.t4.net';  
60   var me=getCurrentParticipant();  
61   if (me.Status=== 'manager'){  
62     return getParticipantRegistry(ns+'.Trader')  
63     .then( function(traderRegistry){  
64       var factory=getFactory();  
65       var leavingStaff=factory.newResource(ns, 'Trader',tx.removedStaff.tradeId);  
66       leavingStaff=tx.removedStaff;  
67       return traderRegistry.remove(leavingStaff);  
68     })  
69   }  
70   else  
71   {  
72     throw new Error('Insufficient Privileges: Managers only to remove staff');  
73   }  
74 }
```



- Exactly same as Add
 - namespace
 - get Current participant
 - test for status
 - if match to manager then remove
 - else display error message
- get the appropriate registry
 - create factory
 - pass the values from the transaction variable to the factory
 - remove the staff entry from the registry
 - All so easy?



- Exactly same as Add
 - namespace
 - get Current participant
 - test for status
 - if match to manager then remove
 - else display error message
- get the appropriate registry
 - create factory
 - pass the values from the transaction variable to the factory
 - remove the staff entry from the registry
 - All so easy?
 - Any commodities the removed Staff member is in ownership?
 - How does this impact the trading scenario
 - Is there a solution?



- Promises
- Transactions
- Get Registry
- Update Registry
- Add Registry
- Exist Registry
- Get Current Participant
- Console Log
- Errors



- [1] *Hyperledger Architecture, Volume 1.* 2017.
- [2] *Hyperledger Architecture, Volume 2.* 2018.



- <http://hyperledger.org>
- <https://nodejs.org>
- <https://hyperledger.github.io/composer/latest/api/runtime-factory>