

---

# **NISTtheDocs2Death**

**Jonathan E. Guyer**

**Aug 29, 2023**



**CONTENTS:**

<b>1</b>	<b>Usage</b>	<b>3</b>
<b>2</b>	<b>Indices and tables</b>	<b>19</b>
	<b>Python Module Index</b>	<b>21</b>
	<b>Index</b>	<b>23</b>



This [GitHub action](#)<sup>1</sup> uses the [Sphinx](#) tool to build documentation in <https://github.com/usnistgov> projects and then host that documentation on <https://pages.nist.gov>, as an approximation of [ReadTheDocs](#).

---

<sup>1</sup> Certain commercial firms and trade names are identified in this document in order to specify the installation and usage procedures adequately, or to provide context. Such identification is not intended to imply recommendation or endorsement by the [National Institute of Standards and Technology](#), nor is it intended to imply that related products are necessarily the best available for the purpose.



## USAGE

- Configure your repo for publishing on [pages.nist.gov](https://pages.nist.gov).
- [Enable GitHub Actions for your repo](#) and select “Allow all actions and reusable workflows” (you may need to submit a request to [devops@nist.gov](mailto:devops@nist.gov) to enable this for you).
- For each branch of your repository where you want to host documentation, add a workflow, such as `.github/workflows/NISTtheDocs2Death.yml`:

```
name: "Build Documentation"

on: [push, pull_request, delete]

jobs:
  docs:
    runs-on: ubuntu-latest
    steps:
      - uses: usnistgov/NISTtheDocs2Death@0.4
        with:
          docs-folder: docs/
          formats: |-
            epub
            pdf
```

See *NISTtheDocs2Death Action* for more information about configuration of this workflow.

## 1.1 Customization

NISTtheDocs2Death uses two sets of templates that determine the appearance of the hosted documentation.

### 1.1.1 Assimilation templates

The first set of templates is used by `assimilate_theme()` to modify the Sphinx configuration.

These templates can be customized by forking this repository.

### `conf.py`

This template file overlays the `html_theme` you chose for your documentation with the `ntd2d` theme, described next.

### `ntd2d/`

This template directory provides a `Sphinx theme` that modifies your chosen documentation theme.

### `ntd2d/layout.html`

This template file inserts standard NIST headers and footers and a dropdown menu that allows selecting different versions of your documentation.

### `ntd2d/static/ntd2d.css_t`

This template file controls the appearance of the dropdown menu.

## 1.1.2 Pages templates

The second set of templates is used by `update_pages()` to create the pages on the hosting site that enable switching between different documentation variants.

You can customize any of these templates by copying them to a `_templates/` directory at the root of your *nist-pages* branch and editing them to suit.

These templates use `Python string format syntax` (Sphinx and pages.nist.gov already fight over Jekyll templating, so we're not getting fancy, here).

### `downloads.html`

A section inserted into `menu.html` if a documentation variant has any downloadable output, e.g., PDF or ePUB.

Available substitution keywords are:

- `downloads`: A pre-formatted string with each downloadable output formatted by `download_item.html`.

### `download_item.html`

Formats a link to a single downloadable output.

Available substitution keywords are:

- `href`: URL of the downloadable output.
- `kind`: Type of downloadable output, e.g., PDF or ePUB.



### `index.html`

The default page for your documentation displayed at <https://pages.nist.gov/{repository}>.

Available substitution keywords are:

- `owner`: The GitHub [user](#) or [organization](#) for your repository.
- `repository`: The name of your repository.
- `variants`: The result of filling the [variants.html](#) template.

### `menu.html`

The dropdown menu that allows selecting different branches and tags of your documentation.

Available substitution keywords are:

- `downloads`: The result of filling the [downloads.html](#) template.
- `tree_url`: The GitHub URL corresponding to the active tag or branch.
- `variant`: The name of the active tag or branch.
- `variants`: The result of filling the [variants.html](#) template.

### `ntd2d_active.css`

Style sheet that controls the appearance of the active tag or branch in the dropdown menu.

Available substitution keywords are:

- `variant`: The name of the active tag or branch.

### `variants.html`

Lists tags and branches that are [configured](#) to serve documentation with this Action.

Available substitution keywords are:

- `branches`: A pre-formatted string with each git branch formatted by [variant\\_item.html](#).
- `latest`: A pre-formatted string with the HEAD of the default GitHub branch formatted by [variant\\_item.html](#).
- `stable`: A pre-formatted string with the `stable_version` that has the highest version identifier, as formatted by [variant\\_item.html](#).
- `stable_versions`: A pre-formatted string with the tags or branches that satisfy the **PEP 440** version specification and aren't [pre-releases](#), each formatted by [variant\\_item.html](#).
- `versions`: A pre-formatted string with the tags or branches that satisfy the **PEP 440** version specification, each formatted by [variant\\_item.html](#).

### `variant_item.html`

Formats a link to a single tag or branch.

Available substitution keywords are:

- `href`: URL of the downloadable output.
- `kind`: Type of downloadable output, e.g., PDF or ePUB.

## 1.2 Q & A

### 1.2.1 Can't I just use Read the Docs?

Nope.

### 1.2.2 Is there a reason?

Yep.

### 1.2.3 Is it a good reason?

Nope.

## 1.3 API

---

<code>ntd2d_action</code>	Workhorse code for modifying and building documentation.
---------------------------	--

### 1.3.1 `ntd2d_action`

Workhorse code for modifying and building documentation.

#### Modules

---

<code>ntd2d_action.files</code>	Representations of file objects.
<code>ntd2d_action.repository</code>	Interface to a git/GitHub repositories.
<code>ntd2d_action.sphinxdocs</code>	Sphinx configuration directory.
<code>ntd2d_action.variants</code>	Representations of a branches and tags.

## ntd2d\_action.files

Representations of file objects.

### Modules

*ntd2d\_action.files.borgedconffile*

*ntd2d\_action.files.conffile*

*ntd2d\_action.files.cssfile*

*ntd2d\_action.files.file*

*ntd2d\_action.files.indexfile*

*ntd2d\_action.files.menufile*

*ntd2d\_action.files.nojekyllfile*

*ntd2d\_action.files.pagesfile*

*ntd2d\_action.files.sphinxlog*

*ntd2d\_action.files.template*

*ntd2d\_action.files.templatehierarchy*

*ntd2d\_action.files.variantsfile*

## ntd2d\_action.files.borgedconffile

### Classes

**class** `ntd2d_action.files.borgedconffile.BorgedConfFile`(*source\_dir*, *original\_docs*)

Bases: *ConfFile*

Sphinx configuration file that overlays the html theme.

**property configuration**

Text of configuration file.

**property html\_theme**

*html\_theme* Sphinx configuration value.

**property html\_theme\_path**

*html\_theme\_path* Sphinx configuration value.

**property language**

*language* Sphinx configuration value.

**property project**

`project` Sphinx configuration value.

**read()**

Evaluate Sphinx configuration values.

The Sphinx docs says that it reads `conf.py` with `importlib.import_module()`. It doesn't.

**Returns**

**namespace** – Configuration values.

**Return type**

dict

**ntd2d\_action.files.conffile****Classes**

**class** `ntd2d_action.files.conffile.ConfFile(source_dir)`

Bases: *File*

Sphinx configuration file.

**property configuration**

Text of configuration file.

**property html\_theme**

`html_theme` Sphinx configuration value.

**property html\_theme\_path**

`html_theme_path` Sphinx configuration value.

**property language**

`language` Sphinx configuration value.

**property project**

`project` Sphinx configuration value.

**read()**

Evaluate Sphinx configuration values.

The Sphinx docs says that it reads `conf.py` with `importlib.import_module()`. It doesn't.

**Returns**

**namespace** – Configuration values.

**Return type**

dict

## ntd2d\_action.files.cssfile

### Classes

**class** ntd2d\_action.files.cssfile.CSSFile(*variant*)

Bases: *PagesFile*

## ntd2d\_action.files.file

### Classes

**class** ntd2d\_action.files.file.File

Bases: object

Base file class

## ntd2d\_action.files.indexfile

### Classes

**class** ntd2d\_action.files.indexfile.IndexFile(*repo*, *variants\_url*)

Bases: *PagesFile*

**get\_contents()**

build index.html with available documentation variants

## ntd2d\_action.files.menufile

### Classes

**class** ntd2d\_action.files.menufile.MenuFile(*variant*, *variants\_url*)

Bases: *PagesFile*

## ntd2d\_action.files.nojekyllfile

### Classes

**class** ntd2d\_action.files.nojekyllfile.NoJekyllFile(*repo*)

Bases: *PagesFile*

## ntd2d\_action.files.pagesfile

### Classes

```
class ntd2d_action.files.pagesfile.PagesFile(repo)
```

Bases: *File*

## ntd2d\_action.files.sphinxlog

### Classes

```
class ntd2d_action.files.sphinxlog.SphinxLog(docs, path)
```

Bases: *File*

```
parse_sphinx_warnings()
```

Parse and emit a sphinx file containing warnings and errors.

**Inputs look like this:**

/media/sf\_shared/workspace/sphinx-action/tests/test\_projects/warnings\_and\_errors/index.rst:19:

WARNING: Error in “code-block” directive: maximum 1 argument(s) allowed, 2 supplied.

/cpython/Doc/distutils/\_setuptools\_disclaimer.rst: WARNING: document isn’t included in any toctree

/cpython/Doc/contents.rst:5: WARNING: toctree contains reference to nonexistent document ‘ayyl-mao’

## ntd2d\_action.files.template

### Classes

```
class ntd2d_action.files.template.FileTemplate(name)
```

Bases: *Template*

---

```
class ntd2d_action.files.template.PagesTemplate(working_dir, name)
```

Bases: *FileTemplate*

---

```
class ntd2d_action.files.template.Template(template_path)
```

Bases: object

## ntd2d\_action.files.templatehierarchy

### Classes

```
class ntd2d_action.files.templatehierarchy.TemplateHierarchy(name, destination_dir,  
                                                             **substitutions)
```

Bases: *FileTemplate*

## ntd2d\_action.files.variantsfile

### Classes

**class** ntd2d\_action.files.variantsfile.**VariantsFile**(*repo*, *variants*, *pages\_url*)

Bases: [PagesFile](#)

## ntd2d\_action.repository

Interface to a git/GitHub repositories.

### Classes

**class** ntd2d\_action.repository.**Repository**(*server\_url*, *repository*, *branch*, *default\_branch*, *docs*, *pages\_url*)

Bases: object

Interface to a git/GitHub repository.

#### Parameters

- **server\_url** (*url*) – The URL of the GitHub server (GITHUB\_SERVER\_URL).
- **repository** (*str*) – The owner and repository name (GITHUB\_REPOSITORY).
- **branch** (*str*) – The branch linked to your documentation server ([pages-branch](#)).
- **default-branch** (*str*) – The default branch configured in GitHub ([default-branch](#)).
- **docs** ([SphinxDocs](#)) – The documentation being built.
- **pages\_url** (*url*) – URL of the web server for served documentation ([pages-url](#)).

**update\_pages**(*branch*, *sha*)

Commit built documentation to [pages-branch](#).

#### Parameters

- **branch** (*str*) – The sanitized (‘/’ removed) short ref name of the branch or tag that triggered the workflow (GITHUB\_REF\_NAME).
- **sha** (*str*) – The commit SHA that triggered the workflow (GITHUB\_SHA).

## ntd2d\_action.sphinxdocs

Sphinx configuration directory.

## Classes

**class** `ntd2d_action.sphinxdocs.BorgedSphinxDocs`(*original\_docs*)

Bases: [\*SphinxDocs\*](#)

Sphinx configuration directory modified by NISTtheDocs2Death.

### Parameters

**original\_docs** ([\*SphinxDocs\*](#)) – The configuration directory stored in the [\*Repository\*](#).

**assimilate\_theme**(*name*)

Replace configuration directory with customized html theme.

**build\_docs**(*build\_command*)

Build Sphinx Documentation

Adapted from [https://github.com/ammaskar/sphinx-action/blob/master/sphinx\\_action/action.py](https://github.com/ammaskar/sphinx-action/blob/master/sphinx_action/action.py)  
(Apache-2.0).

---

**class** `ntd2d_action.sphinxdocs.SphinxDocs`(*docs\_dir*)

Bases: `object`

Sphinx configuration directory.

**build\_docs**(*build\_command*)

Build Sphinx Documentation

Adapted from [https://github.com/ammaskar/sphinx-action/blob/master/sphinx\\_action/action.py](https://github.com/ammaskar/sphinx-action/blob/master/sphinx_action/action.py)  
(Apache-2.0).

## `ntd2d_action.variants`

Representations of a branches and tags.

## Classes

**class** `ntd2d_action.variants.Variant`(*repo*, *name*, *rebuild\_menu*=*False*, *true\_name*=*None*)

Bases: `object`

Representation of a branch or tag.

### Parameters

- **repo** ([\*Repository\*](#)) – Git repository containing this branch or tag.
- **name** (*str*) – Ref name of branch or tag.
- **rebuild\_menu** (*bool*) – Whether to rebuild variant menu after updating variants (default: *False*).
- **true\_name** (*str*) – Name of actual branch or tag associated with *stable* or *latest* variants.

**property** `css_name`

Escape ref name to satisfy css class naming requirements

Used to escape characters that are - allowed by *man git-check-ref-format* - disallowed by <https://www.w3.org/International/questions/qa-escapes#cssescapes>



---

```
class ntd2d_action.variants.VariantCollection(initlist=None)
```

Bases: `UserList`

A collection of `Variant` objects.

**append**(*item*)

S.append(value) – append value to the end of the sequence

**clear**() → None -- remove all items from S

**count**(*value*) → integer -- return number of occurrences of value

**extend**(*other*)

S.extend(iterable) – extend sequence by appending elements from the iterable

**index**(*value*[, *start*[, *stop* ] ] ) → integer -- return first index of value.

Raises `ValueError` if the value is not present.

Supporting start and stop arguments is optional, but recommended.

**insert**(*i*, *item*)

S.insert(index, value) – insert value before index

**pop**([*index* ] ) → item -- remove and return item at index (default last).

Raise `IndexError` if list is empty or index is out of range.

**remove**(*item*)

S.remove(value) – remove first occurrence of value. Raise `ValueError` if the value is not present.

**reverse**()

S.reverse() – reverse *IN PLACE*

---

```
class ntd2d_action.variants.VariantCollector(repo, current_variant)
```

Bases: `object`

Tool that aggregates branches and versions.

**Parameters**

- **repo** (`Repository`) – Git repository to be scanned for branches and tags.
  - **current\_variant** (`Variant`) – Branch or tag which triggered the workflow.
- 

```
class ntd2d_action.variants.Version(repo, name, rebuild_menu=False)
```

Bases: `Variant`

A `Variant` that satisfies the **PEP 440** version specification

**Raises**

**InvalidVersion** – If the name is not parsable by `packaging.version`.

**property** `css_name`

Escape ref name to satisfy css class naming requirements

Used to escape characters that are - allowed by *man git-check-ref-format* - disallowed by <https://www.w3.org/International/questions/qa-escapes#cssescapes>

## 1.4 NISTtheDocs2Death Action

This [GitHub action](#) uses the [Sphinx](#) tool to build documentation in <https://github.com/usnistgov> projects and then host on <https://pages.nist.gov> as an approximation of [ReadTheDocs](#).

### 1.4.1 Usage

This action is invoked by adding a workflow file to your repository, such as `.github/workflows/NISTtheDocs2Death.yml`:

```
name: "Build Documentation"

on: [push, pull_request, delete]

jobs:
  docs:
    runs-on: ubuntu-latest
    steps:
      - uses: usnistgov/NISTtheDocs2Death@0.4
        with:
          docs-folder: docs/
          pages-branch: 'nist-pages'
          pages-url: 'https://pages.nist.gov'
          formats: ''
          build-html-command: make html
          build-epub-command: make epub
          build-pdf-command: make latexpdf
          pre-build-command: ''
          apt-packages: ''
          pip-requirements: ''
          conda-environment: ''
```

### 1.4.2 Inputs

#### `docs-folder`

The folder containing your Sphinx configuration.

#### `pages-branch`

The branch linked to your documentation server.

**pages-url**

URL of the web server for served documentation.

**formats**

Type(s) of output desired in addition to html (pdf, and/or epub).

---

**Note:** GitHub Actions' YAML implementation does not support list or array elements, so use a multiline string to declare formats, e.g.,

```
formats: | -  
  epub  
  pdf
```

---

**build-html-command**

The command used by [usnistgov/sphinx-action](#) to build your html documentation.

**build-epub-command**

The command used by [usnistgov/sphinx-action](#) to build your ePUB documentation.

**build-pdf-command**

The command used by [usnistgov/sphinx-action](#) to build your PDF documentation.

**pre-build-command**

Run by [usnistgov/sphinx-action](#) before the build command. You can use this to install system level dependencies, for example, with “`apt-get update -y && apt-get install -y perl`”, although those are better installed with *apt-packages*.

**apt-packages**

List of any [APT](#) packages that should be installed.

**pip-requirements**

The path to the pip requirements file, relative to the root of the project.

## conda-environment

The path to the Conda environment file, relative to the root of the project.

### 1.4.3 Implementation

This action implements a [composite workflow](#) with the following major steps:

1. [actions/checkout](#)
2. *ntd2d Sub-Action*
3. [ad-m/github-push-action](#)
4. [actions/upload-artifact](#)

## 1.5 ntd2d Sub-Action

This [GitHub action](#) is invoked by the main *NISTtheDocs2Death Action* to move built documentation into your designated *pages-branch*.

### 1.5.1 Usage

This action is invoked as a step of the composite workflow of the *NISTtheDocs2Death Action*. There is no reason to invoke this action yourself.

```
- name: Commit documentation changes
  uses: ../../../../_actions/current/ntd2d
  with:
    docs-folder: docs/
    default-branch: 'main'
    pages-branch: 'nist-pages'
    pages-url: 'https://pages.nist.gov'
    formats: ''
    build-html-command: make html
    build-epub-command: make epub
    build-pdf-command: make epub
    pre-build-command: ''
    apt-packages: ''
    pip-requirements: ''
    conda-environment: ''
```

---

**Note:** This action must be synchronized with the invoked version of the *NISTtheDocs2Death Action*, but “`usnistgov/NISTtheDocs2Death/borg_the_docs@${{ github.action_ref }}`” doesn’t work, hence the clumsy `uses:` statement.

---

## 1.5.2 Inputs

### `docs-folder`

The folder containing your Sphinx configuration.

### `default-t-branch`

The default branch [configured in GitHub](#).

### `pages-branch`

The branch linked to your documentation server.

### `pages-url`

URL of the web server for served documentation.

### `formats`

Type(s) of output desired in addition to html (pdf, and/or epub).

---

**Note:** [GitHub Actions' YAML implementation](#) does not support list or array elements, so use a multiline string to declare formats, e.g.,

```
formats: |-  
  epub  
  pdf
```

---

### `build-html-command`

The command used to build your html documentation.

### `build-epub-command`

The command used to build your ePUB documentation.

### `build-pdf-command`

The command used to build your PDF documentation.

**pre-build-command**

Run before the build command. You can use this to install system level dependencies, for example, with “`apt-get update -y && apt-get install -y perl`”, although those are better installed with *apt-packages*.

**apt-packages**

List of any *APT* packages that should be installed.

**pip-requirements**

The path to the pip requirements file, relative to the root of the project.

**conda-environment**

The path to the Conda environment file, relative to the root of the project.

## 1.5.3 Outputs

**borged-build-folder**

The folder containing the Sphinx build outputs.

## 1.5.4 Implementation

This action implements a *Docker workflow step*. The Docker ENTRYPOINT

- installs any specified *apt-packages*, *pip-requirements*, and *conda-environment*,
- wraps the Sphinx configuration directory in a *BorgedSphinxDocs* object,
- invokes *assimilate\_theme()*
- executes any *pre-build-command*,
- invokes *build\_docs()* for html and any other formats specified in *formats*,
- wraps the GITHUB\_REPOSITORY in a *Repository* object,
- invokes *update\_pages()*.

## INDICES AND TABLES

- `genindex`
  - `modindex`
  - `search`
-





## PYTHON MODULE INDEX

### n

- [ntd2d\\_action](#), 6
- [ntd2d\\_action.files](#), 7
  - [ntd2d\\_action.files.borgedconffile](#), 7
  - [ntd2d\\_action.files.conffile](#), 8
  - [ntd2d\\_action.files.cssfile](#), 9
  - [ntd2d\\_action.files.file](#), 9
  - [ntd2d\\_action.files.indexfile](#), 9
  - [ntd2d\\_action.files.menufile](#), 9
  - [ntd2d\\_action.files.nojekyllfile](#), 9
  - [ntd2d\\_action.files.pagesfile](#), 10
  - [ntd2d\\_action.files.sphinxlog](#), 10
  - [ntd2d\\_action.files.template](#), 10
  - [ntd2d\\_action.files.templatehierarchy](#), 10
  - [ntd2d\\_action.files.variantsfile](#), 11
- [ntd2d\\_action.repository](#), 11
- [ntd2d\\_action.sphinxdocs](#), 11
- [ntd2d\\_action.variants](#), 12



## INDEX

### A

`append()` (*ntd2d\_action.variants.VariantCollection* method), 13  
`assimilate_theme()` (*ntd2d\_action.sphinxdocs.BorgedSphinxDocs* method), 12

### B

`BorgedConfFile` (class in *ntd2d\_action.files.borgedconf*), 7  
`BorgedSphinxDocs` (class in *ntd2d\_action.sphinxdocs*), 12  
`build_docs()` (*ntd2d\_action.sphinxdocs.BorgedSphinxDocs* method), 12  
`build_docs()` (*ntd2d\_action.sphinxdocs.SphinxDocs* method), 12

### C

`clear()` (*ntd2d\_action.variants.VariantCollection* method), 13  
`ConfFile` (class in *ntd2d\_action.files.conf*), 8  
`configuration` (*ntd2d\_action.files.borgedconf.BorgedConfFile* property), 7  
`configuration` (*ntd2d\_action.files.conf.ConfFile* property), 8  
`count()` (*ntd2d\_action.variants.VariantCollection* method), 13  
`css_name` (*ntd2d\_action.variants.Variant* property), 12  
`css_name` (*ntd2d\_action.variants.Version* property), 13  
`CSSFile` (class in *ntd2d\_action.files.css*), 9

### E

environment variable  
    GITHUB\_REF\_NAME, 11  
    GITHUB\_REPOSITORY, 11, 18  
    GITHUB\_SERVER\_URL, 11  
    GITHUB\_SHA, 11  
`extend()` (*ntd2d\_action.variants.VariantCollection* method), 13

### F

`File` (class in *ntd2d\_action.files*), 9

`FileTemplate` (class in *ntd2d\_action.files.template*), 10

### G

`get_contents()` (*ntd2d\_action.files.indexfile.IndexFile* method), 9  
GITHUB\_REF\_NAME, 11  
GITHUB\_REPOSITORY, 11, 18  
GITHUB\_SERVER\_URL, 11  
GITHUB\_SHA, 11

### H

`html_theme` (*ntd2d\_action.files.borgedconf.BorgedConfFile* property), 7  
`html_theme` (*ntd2d\_action.files.conf.ConfFile* property), 8  
`html_theme_path` (*ntd2d\_action.files.borgedconf.BorgedConfFile* property), 7  
`html_theme_path` (*ntd2d\_action.files.conf.ConfFile* property), 8

### I

`index()` (*ntd2d\_action.variants.VariantCollection* method), 13  
`IndexFile` (class in *ntd2d\_action.files.index*), 9  
`insert()` (*ntd2d\_action.variants.VariantCollection* method), 13

### L

`language` (*ntd2d\_action.files.borgedconf.BorgedConfFile* property), 7  
`language` (*ntd2d\_action.files.conf.ConfFile* property), 8

### M

`MenuFile` (class in *ntd2d\_action.files.menu*), 9  
module  
    ntd2d\_action, 6  
    ntd2d\_action.files, 7  
    ntd2d\_action.files.borgedconf, 7  
    ntd2d\_action.files.conf, 8  
    ntd2d\_action.files.css, 9  
    ntd2d\_action.files.file, 9

ntd2d\_action.files.indexfile, 9  
 ntd2d\_action.files.menufile, 9  
 ntd2d\_action.files.nojekyllfile, 9  
 ntd2d\_action.files.pagesfile, 10  
 ntd2d\_action.files.sphinxlog, 10  
 ntd2d\_action.files.template, 10  
 ntd2d\_action.files.templatehierarchy, 10  
 ntd2d\_action.files.variantsfile, 11  
 ntd2d\_action.repository, 11  
 ntd2d\_action.sphinxdocs, 11  
 ntd2d\_action.variants, 12

## N

NoJekyllFile (*class in ntd2d\_action.files.nojekyllfile*), 9  
 ntd2d\_action  
   module, 6  
 ntd2d\_action.files  
   module, 7  
 ntd2d\_action.files.borgedconffile  
   module, 7  
 ntd2d\_action.files.conffile  
   module, 8  
 ntd2d\_action.files.cssfile  
   module, 9  
 ntd2d\_action.files.file  
   module, 9  
 ntd2d\_action.files.indexfile  
   module, 9  
 ntd2d\_action.files.menufile  
   module, 9  
 ntd2d\_action.files.nojekyllfile  
   module, 9  
 ntd2d\_action.files.pagesfile  
   module, 10  
 ntd2d\_action.files.sphinxlog  
   module, 10  
 ntd2d\_action.files.template  
   module, 10  
 ntd2d\_action.files.templatehierarchy  
   module, 10  
 ntd2d\_action.files.variantsfile  
   module, 11  
 ntd2d\_action.repository  
   module, 11  
 ntd2d\_action.sphinxdocs  
   module, 11  
 ntd2d\_action.variants  
   module, 12

## P

PagesFile (*class in ntd2d\_action.files.pagesfile*), 10  
 PagesTemplate (*class in ntd2d\_action.files.template*),  
   10

parse\_sphinx\_warnings()  
   (*ntd2d\_action.files.sphinxlog.SphinxLog*  
   *method*), 10  
 pop() (*ntd2d\_action.variants.VariantCollection*  
   *method*), 13  
 project (*ntd2d\_action.files.borgedconffile.BorgedConfFile*  
   *property*), 7  
 project (*ntd2d\_action.files.conffile.ConfFile* *property*),  
   8  
 Python Enhancement Proposals  
   PEP 440, 5, 13

## R

read() (*ntd2d\_action.files.borgedconffile.BorgedConfFile*  
   *method*), 8  
 read() (*ntd2d\_action.files.conffile.ConfFile* *method*), 8  
 remove() (*ntd2d\_action.variants.VariantCollection*  
   *method*), 13  
 Repository (*class in ntd2d\_action.repository*), 11  
 reverse() (*ntd2d\_action.variants.VariantCollection*  
   *method*), 13

## S

SphinxDocs (*class in ntd2d\_action.sphinxdocs*), 12  
 SphinxLog (*class in ntd2d\_action.files.sphinxlog*), 10

## T

Template (*class in ntd2d\_action.files.template*), 10  
 TemplateHierarchy (*class in*  
   *ntd2d\_action.files.templatehierarchy*), 10

## U

update\_pages() (*ntd2d\_action.repository.Repository*  
   *method*), 11

## V

Variant (*class in ntd2d\_action.variants*), 12  
 VariantCollection (*class in ntd2d\_action.variants*),  
   13  
 VariantCollector (*class in ntd2d\_action.variants*), 13  
 VariantsFile (*class in ntd2d\_action.files.variantsfile*),  
   11  
 Version (*class in ntd2d\_action.variants*), 13