

foieGras an R package for rapid quality control, behavioural estimation and simulation of animal track data

Ian D. Jonsen^{1,*}, Toby A. Patterson², and ²

¹Department of Biological Sciences, Macquarie University, Sydney, NSW, Australia

²CSIRO Ocean and Atmosphere Research, Hobart, TAS, Australia

*Corresponding author. Email: ian.jonsen@mq.edu.au

Abstract

text...

1 | Introduction

The R package `foieGras`, pronounced “*fwah grah*”, ...

2 | foieGras Overview

The workflow for `foieGras` is deliberately simple, with much of the usual track data processing checks and formatting handled automatically. The main functions are listed in Table 1. When fitting a model, `foieGras` automatically detects the type of tracking data location quality classes designations that are typical of Argos data and that can be added to the data by the researcher for other types of track data. Based on the location quality classes and other, optional information on observation errors contained in the data, `foieGras` chooses an appropriate measurement error model for each observation. This capability allows for combinations of different tracking data types, e.g., Argos and GPS, in a single input data frame and to be fit in a single state-space model.

2.1 | Data preparation

Animal tracking data, consisting of a time-series of location coordinates, can be read into R as a data frame using standard functions such as `read.csv`. The canonical data format for Argos tracks consists of a data frame with 5 columns corresponding to the following named variables: `id` (individual id), `date` (date and time), `lc` (location class), `lon` (longitude), `lat` (latitude). Optionally, an additional 3 columns, `smaj` (semi-major axis), `smin` (semi-minor axis), `eor` (ellipse orientation), providing Argos error ellipse information may be included.

Other types of track data can be accommodated, for example, by including the `lc` column where all `lc = "G"` for GPS data. In this case, measurement error in the GPS locations is assumed to have a standard deviation of 0.1 x Argos class 3 locations (approximately 30 m). Other types of track data can be considered in a similar manner (see the package vignette for further details).

Table 1: Main functions for the R package `foieGras`

Function	Description
<code>fit_mpm</code>	Fit a Move Persistence Model to location data
<code>fit_ssm</code>	Fit a State-Space Model to location data
<code>fmap</code>	Plot fitted/predicted locations on a map with or without a defined projection
<code>grab</code>	Extract fitted/predicted/observed locations from a <code>foieGras</code> model, with or without projection information
<code>osar</code>	Estimate One-Step-Ahead Residuals from a <code>foieGras</code> SSM
<code>plot.fG_mpm</code>	Plot move persistence estimates as 1-D or 2-D (along track) time-series
<code>plot.fG_osar</code>	Plot One-Step-Ahead Residuals from a <code>foieGras</code> SSM
<code>plot.fG_ssm</code>	Visualise the fit of a <code>foieGras</code> SSM to data

2.2 | State-space model fitting - `fit_ssm`

State-space models are fit using `fit_ssm`. There are a large number of options that can be set in `fit_ssm` (see Suppl for details). We focus only the essential options here:

- `data` the input data structured as described in 2.1
- `vmax` a maximum threshold speed (ms^{-1}) to help identify potential outlier locations
- `model` the process model to be used
- `time.step` the prediction time interval (h)

The function first invokes an automated data processing stage where the following occurs: 1) data type (Argos Least-Squares, Argos Kalman Filter/Smoothing, GPS, or General (e.g., processed light-level geolocations, acoustic telemetry, coded VHF telemetry) is determined; 2) datetimes are converted to POSIXt format, chronological order is ensured, and duplicate datetime records are removed; 3) observations occurring less than `min.dt` seconds after a prior observation are removed; 4) a speed filter (Freitas et al., 2008) is used to identify potential outlier locations; 5) locations are projected from spherical lon-lat coordinates to planar x,y coordinates in km.

The function then fits a state-space model to the processed data, where the process model (currently, either a continuous-time `rw` or a continuous-time `crw`) is specified by the user and the measurement model(s) (Jonsen et al., 2020) are selected automatically. The model is fit by numerical optimization of the likelihood using either the `optim` or `nlmminb` R function. The R package `TMB`, Template Model Builder (Kristensen et al., 2016), is used to compute the gradient function in C++ via reverse-mode auto-differentiation and the Laplace Approximation is used to integrate out the latent states (random effects). Fits to a single versus multiple individuals are handled automatically.

`fit_ssm` returns a `foieGras` fit object (a nested data frame with class `fG_ssm`). The outer data frame lists the individual id(s), basic convergence information and a list with class `ssm`. This list contains dense information on the model parameter and state estimates, predictions, input data, optimizer results, and other diagnostic information. Users can extract a simple data frame of SSM fitted (location estimates corresponding to the, typically irregular, observation times) or predicted values (locations predicted at regular `time.step` intervals) using the `grab` function.

2.3 | Model checking and visualisation

2.4 | Behavioural estimation

2.5 | Simulation

3 | Examples

Extending the behavioural model using `mpmm`

4 | Discussion

Acknowledgements

We thank xx, xx for providing data used in the examples, and xx, xx for helpful comments on an earlier draft of this manuscript. We thank Marie Auger-Méthé for contributing code to the movement persistence models. IDJ acknowledges support from a Macquarie University co-Funded Fellowship and from partners: the US Office of Naval Research, Marine Mammal Program (grant N00014-18-1-2405); the Integrated Marine Observing System (IMOS Australia); Taronga Conservation Society; the Ocean Tracking Network; Birds Canada; and Innovasea/VEMCO. TAP was supported by CSIRO Oceans & Atmosphere internal research funding scheme.

Author's Contributions

IDJ developed the R package; IDJ and TAP developed the state-space models and wrote the manuscript.

Data Accessibility

All code mentioned here is provided in the `foieGras` package for R available on CRAN at <https://CRAN.R-project.org/package=foieGras>. The development version of the package is available on GitHub at <https://github.com/ianjensen/foieGras>. Data used in the examples are available at...

ORCID

Ian D Jonsen <https://orcid.org/0000-0001-5423-6076>
Toby A Patterson <https://orcid.org/0000-0002-7150-9205>

Bibliography

Freitas, C., Lydersen, C., Fedak, M. A., & Kovacs, K. M. (2008). A simple new algorithm to filter marine mammal argos locations. *Marine Mammal Science*, 24, 315–325.

- 85 Jonsen, I. D., Patterson, T. A., Costa, D. P., Doherty, P. D., Godley, B. J., Grecian, W. J., Guinet,
86 C., Hoenner, X., Kienle, S. S., Robinson, P. W., Votier, S. C., Whiting, S., Witt, M. J., Hindell, M. A.,
87 Harcourt, R. G., & McMahon, C. R. (2020). A continuous-time state-space model for rapid quality
88 control of Argos locations from animal-borne tags. *Movement Ecology*, 8, 31.
- 89 Kristensen, K., Nielsen, A., Berg, C. W., Skaug, H., & Bell, B. M. (2016). TMB: Automatic differen-
90 tiation and Laplace approximation. *Journal of Statistical Software*, 70, 1–21.