## LAMPIRAN A KONFIGURASI ROUTER 1

```
1:
     Building configuration...
2:
3 :
     Current configuration: 3843 bytes
4:
5:
     version 12.4
6 :
     service timestamps debug datetime msec
7:
     service timestamps log datetime msec
8:
     no service password-encryption
9:
     !
10 : hostname R1
11:
12: boot-start-marker
13: boot-end-marker
14:
15 : no logging buffered
16:
17 : no aaa new-model
18:
     ip cef
19 :
20:
     ip auth-proxy max-nodata-conns 3
22:
    ip admission max-nodata-conns 3
23:
24:
25 :
     vpdn enable
26:
27:
28:
29:
     crypto pki trustpoint TP-self-signed-305686875
30 :
      enrollment selfsigned
31 :
      subject-name cn=IOS-Self-Signed-Certificate-305686875
32:
      revocation-check none
33:
      rsakeypair TP-self-signed-305686875
34 :
35 :
     crypto pki certificate chain TP-self-signed-305686875
36:
37 :
      certificate self-signed 01
       30820238 308201A1 A0030201 02020101 300D0609 2A864886
38:
     F70D0101 04050030
       30312E30 2C060355 04031325 494F532D 53656C66 2D536967
39:
     6E65642D 43657274
40:
       69666963 6174652D 33303536 38363837 35301E17 0D313230
     39313030 31343732
41 :
       335A170D 32303031 30313030 30303030 5A303031 2E302C06
     03550403 1325494F
42:
       532D5365 6C662D53 69676E65 642D4365 72746966 69636174
     652D3330 35363836
       38373530 819F300D 06092A86 4886F70D 01010105 0003818D
43 :
     00308189 02818100
       C3F4A036 4E93E05B DF5F0998 759B1ACB 8DA04C2A A3EE51F5
44:
     30A631EE AAFA7034
       7CB1DF3E 3C7951D5 7D4D62F5 BB57A336 926B46DF 414F5177
45:
     0104AC59 00B18E09
46:
       B976619A 48080411 E2C1B48F 28446505 278C146C 02D4658E
     B923658B DD5089EB
```

```
58DC2DA2 561AC6D0 45E54AD6 C556EEBF 89694B12 272EB45A
47 :
     8DDC9F6A CD8D9937
       02030100 01A36230 60300F06 03551D13 0101FF04 05300301
48:
     01FF300D 0603551D
49:
       11040630 04820252 31301F06 03551D23 04183016 80149ED5
     995A6185 03E06819
50:
       5734F7CA A4199BFF 313B301D 0603551D 0E041604 149ED599
     5A618503 E0681957
       34F7CAA4 199BFF31 3B300D06 092A8648 86F70D01 01040500
51:
     03818100 1FAE1795
52:
       64A40590 F5067A20 25F5E041 2530D540 97E3555B 59B054CC
     F6DAB1EC F6875F5C
       0344D621 26DBE2C6 835A3BD0 DC746685 FB5E2D08 3AB8FE18
53:
     B878C457 6BF64B95
54:
      A89AE763 042457C9 613DB9E1 CA41B1CA FE61C692 19C46813
     4D8291CD DBB6D970
55:
       A5CE4748 5979C454 0A36A37D FA2327FF 065D1367 5BFE6064
     36471DDC
56:
       quit
     username cisco privilege 15 secret 5
     $1$D/nu$hfWouI3qDDr.L4rV3zWtZ0
59:!
60 : !
61:
62 : crypto isakmp policy 1
63 :
     encr 3des
64:
     authentication pre-share
65 :
      group 2
66 : !
67: crypto isakmp policy 10
      encr aes 256
68:
69 :
     hash md5
70:
      authentication pre-share
71:
      group 5
72 : crypto isakmp key cisco address 125.164.4.31
73:
     crypto isakmp key cisco address 0.0.0.0 0.0.0.0
74:
75 :
76:
     crypto ipsec transform-set stts transform-set esp-aes 256
     esp-md5-hmac
77 :
78 : crypto map SDM_CMAP_1 1 ipsec-isakmp
79 :
     description Tunnel to125.164.4.31
      set peer 125.164.4.31
     set transform-set stts transform-set
82:
      match address 100
83:
84:
85:
86 : interface FastEthernet0/0
87 : ip address 202.154.17.1 255.255.255.0
88 : ip nat inside
89 : ip virtual-reassembly
90 : duplex auto
91 : speed auto
```

```
92 : !
93 : interface FastEthernet0/1
     ip address 192.168.3.2 255.255.255.0
95:
      ip nat inside
96:
     ip virtual-reassembly
97 :
     duplex auto
98 : speed auto
99 : pppoe enable group global
100 : pppoe-client dial-pool-number 1
101 : !
102 : interface Dialer1
103: ip address negotiated
104 : ip mtu 1492
105 : ip nat outside
106 : ip virtual-reassembly
107 : encapsulation ppp
108 : no ip mroute-cache
109 : dialer pool 1
110 : dialer-group 1
111 : ppp authentication pap callin
112 : ppp chap hostname 152320204***@telkom.net
113 : ppp chap password 0 G***n***r*
114 : ppp pap sent-username 152320204***@telkom.net password 0
     G***n***r*
115 : crypto map SDM_CMAP_1
116 : !
117 : ip forward-protocol nd
118 : ip route 0.0.0.0 0.0.0.0 Dialer1
119 : !
120 : ip http server
121 : ip http authentication local
122 : ip http secure-server
123 : ip http timeout-policy idle 600 life 86400 requests 10000
124 : ip nat inside source list NAT interface Dialer1 overload
125 : !
126 : ip access-list extended NAT
127 : permit ip 202.154.17.0 0.0.0.255 any
128 : !
129 : access-list 1 permit any
130 : access-list 100 remark CCP ACL Category=4
131 : access-list 100 remark IPSec Rule
132 : access-list 100 permit ip 202.154.17.0 0.0.0.255
      202.154.18.0 0.0.0.255
133 : dialer-list 1 protocol ip permit
134 : !
135 : !
136 : control-plane
137 : !
138 : !
139 : line con 0
140 : line aux 0
141 : line vty 0 4
142 : privilege level 15
143 : login local
144 : transport input telnet ssh
145 : !
```

146 : scheduler allocate 20000 1000 147 : end