Regular expressions

ian.mcloughlin@gmit.ie

Regular expressions

$$(0.0|1.1).(0.1)*.(0.0|1.1)$$

- Regular expressions are strings that represent patterns of text.
- The strings can contain special characters.
- Brackets can be used to group characters together.
- Regular expressions are used to search other strings for patterns.

Special characters

- . means concatenate. So, a.b means an a followed by a b.
- means or. So, a|b means an a or a b.
- * means zero of more times. So, a^* means zero or more a's.

Examples of regular expressions

- a.b.c a single a followed by a single b followed by a single c.
- $a.b.c^*$ an a followed by a b followed by zero or more c's.
 - a|b.c an a, or a b followed by a c.
- (a|b).c an a or a b, followed by a c.
- $0.0.(0|1)^*$ all strings of 0's and 1' that begin with two zeros.
 - 1* any number of 1's (including empty string).

Precedence

- 1. Always apply * first.
- 2. Apply . after * but before |.
- 3. Apply | last.
- 4. Treat bracketed groups as individual characters.

Infix and postfix

It is sometimes convenient to re-write expressions in postfix. This applies to lots of different expressions, not just regular expressions.

Example

The infix mathematical expression " $(3+4)\times 5$ " is " $3~4~+5\times$ " in postfix.

Example

The infix regular expression "a.(b.b)*.a" is "abb.*.a." in postfix. Note we often omit the . in infix notation: "a(bb)*a" but can't in postfix. However, the brackets aren't needed in postfix.

5