Lab 02

LCD and Seven Segment Display

Logan Barber, Ian Nail

January 28, 2022

Ian Nail

Logan Barber

ME-4370 - Stephen Canfield

1 Executive Summary

In this lab, the objective is to output a recipe to a Liquid Crystal Display (LCD) and include a seven segment display as a timer. The minimum objectives were:

1. Tell the user what recipe is to follow.
2. Provide the recipe steps in order, timed.
3. Provide a countdown timer for any timed events in the recipe.
4. Display all instructions on the LCD screen
5. Display countdown time on one or more 7-segment displays
6. Test your product on someone outside the class, record their use of your product.

For objective 1, 2, and 4. the recipe is displayed on the LCD one item at a time. The next recipe item is displayed with the push button. For objective 3 and 5 the timed portion the timer will start and stop with a push button. The 4 digit seven segment display is used for the timer. The first two digits are the minutes, and the second two digits are the seconds.

An I2C module was used for the LCD to cut down on wires and ports needed from the Arduino Mega. The library LiquidCrystal_I2C.h was utilized. Communication happens over 4 wires. Power, ground, and 2 communication lines.

On wiring the seven segment that has 4 displays. 12 GPIO pins are required from the Arduino. 8 are required for the segments (7 segments + 1 for the decimal point). The other 4 GPIO pins select which display to turn on. Only one display should be on at a time (unless you want the same digit to be written to other displays). This means that we have to continuously write to each display faster than we can visually see. This gives the appearance that each display is being on all at ounce. To use the GPIO pins, the registers were written to directly. PORTB GPIO pins were used. This happen is lines 92 to 94 in the C code.

```
0   *       PORT PIN: 2
    *
2   * PIN 10:
```

Lab02.ino

AutoCad was used to draw up the circuit diagram of all the connections, components, and devices used.



Figure 1: Circuit Diagram

2 Source Code

```
// AUTHORS: A. LOGAN BARBER; IAN NAIL
<<<<<<< HEAD
// FILE NAME: LCD_Dpad.ino
// LAST UPDATED: 19 JANUARY 2022
//
//  PURPOSE: THIS FILE IS THE MAIN FILE FOR DISPLAYING A RECIPE ON AN LCD AND BEING ABLE TO SCROLL USING TWO BUTTONS.
//
=======
// FILE NAME: Lab02.ino
// LAST UPDATED: 28 JANUARY 2022
/*
 *  PURPOSE: THIS FILE IS THE MAIN FILE FOR DISPLAYING A RECIPE ON AN LCD AND BEING ABLE TO SCROLL USING TWO BUTTONS.
 *        THIS FILE ALSO UTILIZES AND 4-7 SEGMENT DISPLAY AS A 10 MINUTE TIMER.
 */

/*
 * BUTTON0:
 *
 * DIGITAL PIN: 27
 *
 * PORT: A
 *
 * PORT PIN: 5
 */

 /*
 * BUTTON1:
 *
 * DIGITAL PIN: 28
 *
 * PORT: A
 *
 * PORT PIN: 6
 */

 /*
 * BUTTON2:
 *
 * DIGITAL PIN: 29
 *
 * PORT: A
 *
 * PORT PIN: 7
 */

 /*
  * LCD 4-7 SEGMENT DISPLAY
  *
  * PIN 1:
  *       DIGITAL PIN: 10
  *       PORT: B
  *       PORT PIN: 4
  *
  * PIN 2:
  *       DIGITAL PIN: 50
```

```
   *       PORT: B
   *       PORT PIN: 3
   *
   * PIN 3:
   *       DIGITAL PIN: 13
   *       PORT: B
   *       PORT PIN: 7
   *
   * PIN 4:
   *       DIGITAL PIN: 51
   *       PORT: B
   *       PORT PIN: 2
   *
   * PIN 5:
   *       DIGITAL PIN: 12
   *       PORT: B
   *       PORT PIN: 6
   *
   * PIN 6:
   *       DIGITAL PIN: 22
   *       PORT: A
   *       PORT PIN: 0
   *
   * PIN 7:
   *       DIGITAL PIN: 52
   *       PORT: B
   *       PORT PIN: 1
   *
   * PIN 8:
   *       DIGITAL PIN: 23
   *       PORT: A
   *       PORT PIN: 1
   *
   * PIN 9:
   *       DIGITAL PIN: 24
   *       PORT: A
   *       PORT PIN: 2
   *
   * PIN 10:
   *       DIGITAL PIN: 11
   *       PORT: B
   *       PORT PIN: 5
   *
   * PIN 11:
   *       DIGITAL PIN: 53
   *       PORT: B
   *       PORT PIN: 0
   *
   * PIN 12:
   *       DIGITAL PIN: 25
   *       PORT: A
   *       PORT PIN: 3
   */
>>>>>>> refs/remotes/origin/master

// INCLUDE LIBRARIES
#include <LiquidCrystal_I2C.h>

// DEFINE PIN NUMBERS
#define ADDRESS 0x27
```

```
#define COLS 16
#define ROWS 2

// TIMER PARAMTERS
uint8_t buttonState = 0;
uint8_t minutes = 10; //start time -> CAN CHANGE TO WHATEVER TIME YOU WANT
uint8_t seconds = 0;  //start time -> CAN CHANGE TO WHATEVER TIME YOU WANT
uint8_t totalMinutes = 0;
uint8_t minutesTens = 0;
uint8_t minutesOnes = 0;
uint8_t secondsTens = 0;
uint8_t secondsOnes = 0;
uint8_t secondsTemp = 0;
float totalSeconds = minutes*60 + seconds;
float totalMilliseconds = totalSeconds*1000;
float totalMicroseconds = totalMilliseconds*1000;

// DEFINE LETTERS FOR 7 SEGMENT DISPLAY
const uint8_t ZERO = 0x3F;
const uint8_t ZERO_DEV = 0xBF;
const uint8_t ONE = 0x06;
const uint8_t ONE_DEC = 0x86;
const uint8_t TWO = 0x5B;
const uint8_t TWO_DEC = 0xDB;
const uint8_t THREE = 0x4F;
const uint8_t THREE_DEC = 0xCF;
const uint8_t FOUR = 0x66;
const uint8_t FOUR_DEC = 0xE6;
const uint8_t FIVE = 0x6D;
const uint8_t FIVE_DEC = 0xED;
const uint8_t SIX = 0x7D;
const uint8_t SIX_DEC = 0xFD;
const uint8_t SEVEN = 0x07;
const uint8_t SEVEND_DEC = 0x87;
const uint8_t EIGHT = 0x7F;
const uint8_t EIGHT_DEC = 0xFF;
const uint8_t NINE = 0x67;
const uint8_t NINE_DEC = 0xE7;

// DEFINE THE DISPLAY SELECTION NUMBERS
const uint8_t D1 = 0xE7; // 0b11100111
const uint8_t D2 = 0xEB; // 0b11101011
const uint8_t D3 = 0xED; // 0b11101101
const uint8_t D4 = 0xEE; // 0b11101110
const uint8_t arrD[4] = {D4, D3, D2, D1};

// MESSAGE TO PRINT
char message0[] = "Hello World!";
char message1[] = "Hallo!";
char message2[] = "Wie gehts";
const uint8_t msgArrSize = 3;
char* msgArr[msgArrSize] = {message0, message1, message2};

// INDEX VARIABLES
uint8_t index = 0; // HOLDS INDEX FOR MESSAGE
uint8_t i = 0; // HOLDS INDEX IN for LOOPS FOR SCROLLING
uint8_t t = 0; // HOLDS INDEX IN for LOOP FOR THE TIMER

// CREATE LiquidCrystal OBJECT
LiquidCrystal_I2C lcd(ADDRESS, COLS, ROWS);
```

```
176 // RUN THIS PROGRAM
    void setup()
178 {
        // INITIALIZE THE LCD SCREEN
180     lcd.begin();

182     // PRINT MESSAGE
        lcd.print(msgArr[0]);
184     lcd.setCursor(0, 1);
        lcd.print(msgArr[1]);
186
        // SETUP BUTTON PINS AS INPUTS
188     // SETUP 7-SEGMENT SELECTOR PINS AS OUTPUT
        DDRA = 0x0F; // 0b00001111
190
        // ENABLE INTERNAL PULL-UP RESISTOR FOR BUTTONS
192     PORTA = 0xE0; // 0b11100000

194     // SETUP PORT B AS OUTPUT FOR THE LCD
        DDRB = 0xFF;
196     PORTB = 0x00;

198     // CALCULATE INDIVIDUAL DIGITS
        totalMinutes = totalSeconds/60;
200     minutesTens = totalMinutes/10;
        minutesOnes = totalMinutes%10;
202     secondsTemp = int(totalSeconds)%60;
        secondsTens = secondsTemp/10;
204     secondsOnes = secondsTemp%10;
    }
206
    // LOOP FOREVER
208 void loop()
    {
210     // ELSE IF BUTTON0 IS LOW SCROLL DOWN
        if((PINA & 0xE0) == 0xC0)
212     {
            // DEBOUNCE BUTTON2
214         delay(100);
            if((PINA & 0xE0) == 0xC0)
216         {
              scroll_down();
218         }
        }
220
        // IF BUTTON1 IS LOW THEN SCROLL UP
222     else if((PINA & 0xE0) == 0xA0)
        {
224         // DEBOUNCE THE BUTTON1
            delay(100);
226         if((PINA & 0xE0) == 0xA0)
            {
228           scroll_up();
            }
230     }

232     // IF BUTTON 2 IS LOW CHANGE THE BUTTON STATE
        else if((PINA & 0xE0) == 0x60)
234     {
```

```
        delay(100);
        if((PINA & 0xE0) == 0x60)
        {
            switch(buttonState)
            {
                case 0:
                    buttonState = 1;
                    break;

                case 1:
                    buttonState = 2;
                    break;

                case 2:
                    buttonState = 0;

                    // RESET TIME
                    totalSeconds = minutes*60 + seconds;
                    totalMilliseconds = totalSeconds*1000;
                    totalMicroseconds = totalMilliseconds*1000;

                    // CALCULATE INDIVIDUAL DIGITS
                    totalMinutes = totalSeconds/60;
                    minutesTens = totalMinutes/10;
                    minutesOnes = totalMinutes%10;
                    secondsTemp = int(totalSeconds)%60;
                    secondsTens = secondsTemp/10;
                    secondsOnes = secondsTemp%10;
                    break;
            }
        }
    }

    // RUN TIMER IF BUTTON STATE IS IN STATE 1
    if(buttonState == 1)
    {
        // TIME CALCULATIONS
        totalMicroseconds = totalMicroseconds - 2000; //totalMilliseconds++'
  for stopwatch
        totalMilliseconds = totalMicroseconds/1000;
        totalSeconds = (totalMilliseconds/1000+1);

        // CALCULATE INDIVIDUAL DIGITS
        totalMinutes = totalSeconds/60;
        minutesTens = totalMinutes/10;
        minutesOnes = totalMinutes%10;
        secondsTemp = int(totalSeconds)%60;
        secondsTens = secondsTemp/10;
        secondsOnes = secondsTemp%10;
    }

    // TIMER
    for(t = 0; t < 4; ++t)
    {
        switch(t)
        {
            case 0:
                PORTA = arrD[t];
                pickNumber(minutesTens);
                delayMicroseconds(500);
```

```
                    break;

                case 1:
                    PORTA = arrD[t];
                    pickNumber(minutesOnes);
                    PORTB |= 0x80;
                    delayMicroseconds(500);
                    break;

                case 2:
                    PORTA = arrD[t];
                    pickNumber(secondsTens);
                    delayMicroseconds(500);
                    break;

                case 3:
                    PORTA = arrD[t];
                    pickNumber(secondsOnes);
                    delayMicroseconds(500);
                    break;
            }
        }
}

/*
 * TYPE: FUNCTION
 * NAME: scroll_up
 * RETURN: void
 * NUMBER OF PARAMETERS: 2
 * PARAMETER NAMES: char* messagePtr, uint8_t sizeOfArray
 * PURPOSE: THIS FUNCTION SCROLLS THROUGH THE RECEIPE DISPLAYED ON THE LCD
 */
void scroll_up()
{
    // DECREMENT INDEX BY ONE
    --index;

    // CHECK THE BOUNDS OF INDEX (REMEMBER index IS UNSIGNED)
    if(index > (msgArrSize - 2))
        index = 0;

    // CLEAR THE LCD SCREEN AND PRINT MESSAGES TO THE LCD
    lcd.clear();
    for(i = 0; i < 2; ++i)
    {
        lcd.setCursor(0, i);
        delayMicroseconds(1000);
        lcd.print(msgArr[index + i]);
        delayMicroseconds(1000);
    }
}

/*
 * TYPE: FUNCTION
 * NAME: scroll_down
 * RETURN: void
 * NUMBER OF PARAMETERS: 2
 * PARAMETER NAMES: char* messagePtr, uint8_t sizeOfArray
 * PURPOSE: THIS FUNCTION SCROLLS THROUGH THE RECEIPE DISPLAYED ON THE LCD
 */
```

```
354 void scroll_down()
{
356       // INCREMENT INDEX
      ++index;
358
      // CHECK THE BOUNDS OF INDEX
360       if(index > (msgArrSize - 2))
            index = msgArrSize - 2;
362
      // CLEAR THE LCD SCREEN AND PRINT MESSAGES TO THE LCD
364       lcd.clear();
      for(i = 0; i < 2; ++i)
366       {
            lcd.setCursor(0, i);
368             delayMicroseconds(1000);
            lcd.print(msgArr[index + i]);
370             delayMicroseconds(1000);
      }
372 }

374 /*
 * TYPE: FUNCTION
376  * NAME: pickNumber
 * RETURN: void
378  * NUMBER OF PARAMETERS: 1
 * PARAMETER NAMES: int x
380  * PURPOSE: THIS FUNCTION PICK THE NUMBER FOR THE LCD
 */
382 void pickNumber(int x) //changes value of number
{
384       switch(x)
      {
386             default:
                  PORTB = ZERO;
388                   break;
            case 1:
390                   PORTB = ONE;
                  break;
392             case 2:
                  PORTB = TWO;
394                   break;
            case 3:
396                   PORTB = THREE;
              break;
398             case 4:
                  PORTB = FOUR;
400                   break;
            case 5:
402                   PORTB = FIVE;
                  break;
404             case 6:
                  PORTB = SIX;
406                   break;
            case 7:
408                   PORTB = SEVEN;
                  break;
410             case 8:
                  PORTB = EIGHT;
412                   break;
            case 9:
```

```
414                     PORTB = NINE;
                        break;
416             }
}
```

Lab02.ino