

API Specification

Introduction

This specification documents the API as it is currently implemented. This file, and other associated documentation, will be updated as the API changes and is added to.

Posting XML API Requests

You must have a valid account in order to use the XML API.

The API URL is:

`https://api.stgi.net/api-xml`

Invoking this URL must be done by an HTTP POST.

Posting Forms and Authentication

Prior to calling other API functions, a call to `GetAuthTokenRequest` **must** be made to get an authentication token for subsequent calls.

For the `GetAuthTokenRequest`, the required post variables will be email, password, and xml.

(Note: these form variable names are case sensitive)

Example:

```
<form action="https://api.stgi.net/api-xml" method="post">
  <input type="hidden" name="email"
value="myemail@email.com">
  <input type="hidden" name="password"
value="mypassword234">
  <input type="hidden" name="xml" value="(URI encoded XML
for GetAuthTokenRequest goes here)">
</form>
```

(note: you would not want to put your password in the clear on a real web page)

For other requests, the post variables would be email, auth_token and xml.

The auth_token would be the token returned from the GetAuthTokenRequest call in GetAuthTokenResponse.

Example:

```
<form action="https://api.stgi.net/api-xml" method="post">
  <input type="hidden" name="email"
value="myemail@email.com">
  <input type="hidden" name="auth_token" value="(auth
token returned in previous call)">
  <input type="hidden" name="xml" value="(URI encoded XML
for your request goes here)">
</form>
```

XML Function Format

Each XML function will have a Request which is used as input and a Response. The general format of these are:

Requests

```
<FunctionnameRequest>
```

.

.

(Parameters vary per function)

•
•

</FunctionnameRequest>

Responses

Responses vary depending on whether the function call was successful or not. In the event of a failure, the response is standard across function calls and is shown below. Since these are similar across function calls, only successful responses will be shown in the individual API functions.

Successful Response

```
<FunctionnameResponse>
  <Result>Success</Result>
  •
  •
  (Output data varies per function)
  •
  •
</FunctionnameResponse>
```

Unsuccessful Response

```
<FunctionnameResponse>
  <Result>Error</Result>
  <ErrorCode>(A numeric error code)</ErrorCode>
  <ErrorText>(Text for this particular error)</ErrorText>
</FunctionnameResponse>
```

Input Parser

The parser used by the API server to process the input data is a XML parser. Only XML entities are supported, HTML entities are not supported.

For example, £ sign will trigger an "Your XML is valid, however, we do not recognize the top-level request element..." response from the API server. £ should be used instead.

For input elements that support HTML output, the ampersand sign can be escaped so that it could be shown properly in the web app. For example, &pound;

Example request:

```
<AddTicketUpdateRequest ticket_id='50'>
  <TicketUpdate>
    <ContactID>123</ContactID>
    <Detail>&lt;p&gt;The total amount should be
&#163;50.00. The grand total is &amp;pound;150.00.&lt;/p&gt;</Detail>
    <Status>Open</Status>
    <EmailClient>N</EmailClient>
    <EmailSupportTeam>N</EmailSupportTeam>
  </TicketUpdate>
</AddTicketUpdateRequest>
```

Basic XML entities are supported, they are:

- <
- >
- &
- '
- "

Reference list can be found [here](#).

API Functions

GetAuthTokenRequest

This function generates an auth token to be used in subsequent XML API calls.

The auth token issued does not expire.

To create an auth token that expires, pass the 'expiryMinutes' argument in the GetAuthTokenRequest XML.

If an XML API call returns an expired token error, a new one can be fetched by calling GetAuthTokenRequest again with the email and password for the account.

To return additional data in GetAuthTokenResponse, pass the showMore argument.

Input

- email (from the form variables; not part of the XML)
- password (from the form variables; not part of the XML)
- expiryMinutes (within the GetAuthTokenRequest XML)
- showMore (true/false, optional, for returning additional data like IsOwner)

Output

- Token (the auth token to be passed in subsequent calls)
- IssuedAt (the epoch seconds the auth token is issued)
- ExpiresIn (the duration in seconds that the auth token will be valid)
- IsOwner (Y/N, only returned if showMore is true)

Example Request

```
<GetAuthTokenRequest></GetAuthTokenRequest>
```

Successful Response

```
<GetAuthTokenResponse>
```

```
<Result>Success</Result>
  <Token>(returned auth token)</Token>
</GetAuthTokenResponse>
```

Example Request (Creating an auth token that expires)

```
<GetAuthTokenRequest expiryMinutes="30"></
GetAuthTokenRequest>
```

Successful Response

```
<GetAuthTokenResponse>
  <Result>Success</Result>
  <Token>(returned auth token)</Token>
  <IssuedAt>1692978467</IssuedAt>
  <ExpiresIn>1800</ExpiresIn>
</GetAuthTokenResponse>
```

Example Request (To know if token is an account owner or shared access user)

```
<GetAuthTokenRequest showMore="true"></GetAuthTokenRequest>
```

Successful Response

```
<GetAuthTokenResponse>
  <Result>Success</Result>
  <Token>(returned auth token)</Token>
  <IsOwner>Y</IsOwner>
</GetAuthTokenResponse>
```

GetAuthTokenRequest curl example:

```
curl -d
"email=me@example.com&password=foobar&xml=<GetAuthTokenRequest />" https://api.stgi.net/api-xml
```

This is a curl example that calls the GetAuthTokenRequest API endpoint.

```
curl -d
"email=me@example.com&password=foobar&xml=<GetAuthTokenRequest expiryMinutes="30"/>" https://api.stgi.net/api-xml
```

This is a curl example that calls the GetAuthTokenRequest request to create an auth token that expires in 30 minutes.

Accessing API As Power User

Power users (not an account owner) shares the same permission level as an account owner.

To make a user a power user, login to the web app. Go to Settings > Shared Access. Then click on the 'power users' link to add an user email as a power user.

For power users, calling the API requires that the account number to be passed.

If account number is not provided when it is required, the API will return an error similar to:

```
<Result>Error</Result>
<ErrorCode>1013</ErrorCode>
<ErrorText>Not an account owner and no account id found in
xml</ErrorText>
```

Account number can be fetched by calling the <GetAccountsWithAccessRequest/> API after the auth token has been obtained from <GetAuthTokenRequest/>.

Examples of <GetAccountsWithAccessRequest/> usage can be found in the [Users](#) documentation.

After obtaining account number, pass the account number into the XML request tag in the 'account_id' parameter. For example:

```
<GetContactsRequest account_id="<ACCOUNT_ID>"></
GetContactsRequest>
```

Caveat: Not all API accepts the 'account_id' parameter in the XML request parent tag. Some API calls require that the 'account_id' argument to be passed down in the child(ren) element. For example:

```
<AddContactsRequest>
  <Contacts>
    <Contact account_id="123456">
      .
      .
      .
  </AddContactsRequest>
```

Refer to each API documentation on how to pass the 'account_id' parameter.

Accessing API As Shared Access User

For shared access user (not an account owner), calling the API requires that the account number to be passed.

If account number is not provided when it is required, the API will return an error similar to:

```
<Result>Error</Result>
<ErrorCode>1013</ErrorCode>
<ErrorText>Not an account owner and no account id found in
xml</ErrorText>
```

Account number can be fetched by calling the
<GetAccountsWithAccessRequest/> API after the auth token has been obtained from <GetAuthTokenRequest/>.

Examples of <GetAccountsWithAccessRequest/> usage can be found in the [Users](#) documentation.

Other than returning the account number, the
<GetAccountsWithAccessRequest/> API also returns information about the account limitation of the shared access user:

- IsOwner - determines if the account number is an owner's account or a shared access user account
- Contact_id - the contact ID for the user under the account number
- Groups - list all the groups that the user has access to
- Permissions - list of permissions that the shared access users has access too, useful for performing frontend validation before calling the API

After obtaining account number, pass the account number into the XML request tag in the 'account_id' parameter. For example:

```
<GetContactsRequest
account_id="<SHARED_ACCESS_USER_ACCOUNT_ID>"></
GetContactsRequest>
```

Caveat: Not all API accepts the 'account_id' parameter in the XML request parent tag. Some API calls require that the 'account_id' argument to be passed down in the child(ren) element. For example:

```
<AddContactsRequest>
  <Contacts>
    <Contact account_id="123456">
      .
      .
      .
  </AddContactsRequest>
```

Refer to each API documentation on how to pass the 'account_id' parameter.

Fetching API Response In JSON Format

The API server supports response to be returned in JSON format. To do so, just pass the response="json" parameter into each request in the XML header.

For example, passing the response="json" in GetGroupsRequest header XML:

<GetGroupsRequest response="json"></GetGroupsRequest>
This will yield a JSON response:

```
{
  "getgroupsresponse":{
    "groups":{
      "group":[
        {
          "group_type":"Private",
          "accountnumber":"38193",
          "group_id":"1",
          "includeloginlink":"Yes",
          "emailphysicaladdress":"",
          "emailssentfromemail":"test@test.org",
          "emailssentfromname":"Test",
          "name":"My Group",
          "totalmatchingcontacts":"15"
        },
        {
          "group_type":"Private",
          "accountnumber":"38193",
          "group_id":"2",
          "includeloginlink":"No",
          "emailphysicaladdress":"",
          "emailssentfromemail":"",
          "emailssentfromname":"",
          "name":"No Contact Access",
          "totalmatchingcontacts":"7"
        },
        {
          "group_type":"Private",
          "accountnumber":"38193",
          "group_id":"6",
          "includeloginlink":"No",
          "emailphysicaladdress":"",
          "emailssentfromemail":"",
          "emailssentfromname":"",
          "name":"Social Users",
          "totalmatchingcontacts":"1"
        }
      ]
    }
  }
}
```

```

    ]
  },
  "result": "Success"
},
"@encoding": "UTF-8",
"@version": "1.0"
}

```

request_id Token Passthrough

The API server has a 'request_id' parameter passthrough feature that can be used to match/identify the request data to the response data.

All Add/Edit/Delete APIs that require XML list elements to be passed in the request have the 'request_id' parameter support. They are indicated in the API documentation in each their own Input section.

For example, to match the contacts in the request to the contacts in the response:

```

<AddContactsRequest>
  <Contacts>
    <Contact request_id="12345">
      ...
    </Contact>
    <Contact request_id="23456">
      ...
    </Contact>
  </Contacts>
</AddContactsRequest>

```

The corresponding response would be:

```

<AddContactsResponse>
  <Contacts>
    <Contact request_id="12345">
      <Result>Success</Result>
      ...
    </Contact>
  </Contacts>

```

```

        <Contact request_id="23456">
            <Result>Error</Result>
            <ErrorCode>1020</ErrorCode>
            ...
        </Contact>
    </Contacts>
</AddContactsResponse>

```

If response="json" is passed, the corresponding response would be:

```

{
  "@encoding": "UTF-8",
  "@version": "1.0",
  "addcontactsresponse": {
    "contacts": {
      "contact": [
        {
          "@request_id": "12345",
          "result": "Success",
          ...
        },
        {
          "@request_id": "23456",
          "result": "Success",
          ...
        }
      ]
    }
  }
}

```

API Rate Limit

The API server has a **300 requests per minute per account** rate limit. An error message of 'Too many requests, 300 per minute max' will be returned if the limit has been reached.

Table Of Contents

- [Broadcasts](#)
- [Calendars](#)
- [Companies](#)
- [Contacts](#)
- [CRM Activities](#)
- [Custom Objects](#)
- [Events](#)
- [Groups](#)
- [Invoices](#)
- [Journeys](#)
- [Media Library](#)
- [Opportunities](#)
- [Projects](#)
- [SMS](#)
- [Store](#)
- [Tags](#)
- [Tickets](#)
- [Users](#)
- [Website Conversions](#)
- [Wiki](#)
- [Workflows](#)

TLS Version Support

We recently disabled TLS 1.0 on our SSL-offload load balancers. TLS 1.0 is currently considered weak and as a requirement for PCI compliance, it should be disabled. The currently allowed ciphers are below. If your HTTP client is having trouble connecting, please investigate updating your tools to support TLS 1.1 or TLS1.2.

PORT	STATE	SERVICE
------	-------	---------

443/tcp	open	https
---------	------	-------

```
| ssl-enum-ciphers:
```

| TLSv1.1:

| ciphers:

| TLS_DHE_RSA_WITH_AES_128_CBC_SHA - strong

| TLS_DHE_RSA_WITH_AES_256_CBC_SHA - strong

| TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA - strong

| TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA - strong

| compressors:

| NULL

| TLSv1.2:

| ciphers:

| TLS_DHE_RSA_WITH_AES_128_CBC_SHA - strong

| TLS_DHE_RSA_WITH_AES_128_CBC_SHA256 - strong

| TLS_DHE_RSA_WITH_AES_128_GCM_SHA256 - strong

| TLS_DHE_RSA_WITH_AES_256_CBC_SHA - strong

| TLS_DHE_RSA_WITH_AES_256_CBC_SHA256 - strong

| TLS_DHE_RSA_WITH_AES_256_GCM_SHA384 - strong

| TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA - strong

| TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256 - strong

| TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256 - strong

| TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA - strong

```
|      TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA384 - strong
|      TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384 - strong
|      compressors:
|      NULL
|_  least strength: strong
```

Spec - Broadcasts

Table Of Contents

- Get Broadcasts
- Get Broadcast Stats
- Get Broadcast Body
- Queue Mail
- Send Test Mail
- Reset Contact Drip Campaign

Get Broadcasts

This function allows the caller to get all of the broadcasts for a group.

Input

Group ID and Contact ID. If omitted, return all broadcasts for the account.

To get broadcasts sent after a sent date/time obtained earlier, pass `Datetime_sent = "(senttimevalue)"`. To get broadcasts modified after a modified date/time obtained earlier, pass `update_timestamp="(updatedtimevalue)"`.

Specify `account_id` for shared access to broadcasts in another account. Specify `get_all="true"` to return all broadcasts that the user has access to, including shared access.

Specify `message_type` to filter the types of broadcasts. Values accepted are 'drip' to filter drip campaigns broadcasts; 'journeys' to filter broadcasts sent from journeys; default to 'Broadcasts' message type if not specified.

Output

Broadcast ID, Status (Queued or Sent), Subject, Account Number, GroupID, GroupName, NumberOfRecipients, DatetimeQueued, DatetimeScheduledForDelivery, DateTimeSent, RecipientFiltersUsed, NumberOfClicks, NumberOfReads, UpdatedTimestamp for each broadcast, JourneyID and JourneyName if broadcast belongs to a journey.

Example Request 1

```
<GetBroadcastsRequest Group_id="9224"></  
GetBroadcastsRequest>
```

Example Request 2

```
<GetBroadcastsRequest Datetime_sent="2012-03-01  
12:00:00"></GetBroadcastsRequest>
```

Example Request 3

```
<GetBroadcastsRequest updated_timestamp="2012-12-03  
13:54:23"></GetBroadcastsRequest>
```

Example Request 4 (shared access)

```
<GetBroadcastsRequest account_id="1392"></  
GetBroadcastsRequest>
```

Example Request 5 (shared access with get_all)

```
<GetBroadcastsRequest get_all="true"></  
GetBroadcastsRequest>
```

Example Request 6 (filter by contact_id)

```
<GetBroadcastsRequest Group_id="9224" Contact_id="123"></  
GetBroadcastsRequest>
```

Example Request 7 (to get Drip Campaigns only)

```
<GetBroadcastsRequest Group_id="9224"
message_type="drip"></GetBroadcastsRequest>
```

Example Request 8 (to get Journeys only)

```
<GetBroadcastsRequest Group_id="9224"
message_type="journeys"></GetBroadcastsRequest>
```

Example Response

```
<GetBroadcastsResponse>
  <Result>Success</Result>
  <Broadcasts>
    <Broadcast>
      <Broadcast_id>389</Broadcast_id>
      <Status>Sent</Status>
      <Subject>Sample Subject</Subject>
      <AccountNumber>23</AccountNumber>
      <GroupID>54</GroupID>
      <GroupName>My Group 1</GroupName>
      <NumberOfRecipients>230</NumberOfRecipients>
      <DatetimeQueued>2010-08-31 14:23:56</
DatetimeQueued>
      <DatetimeScheduledForDelivery>2010-09-03
12:00:00</DatetimeScheduledForDelivery>
      <DatetimeSent>2010-09-03 12:05:00</
DatetimeSent>
      <RecipientFiltersUsed>All Contacts</
RecipientFiltersUsed>
      <NumberOfClicks>329</NumberOfClicks>
      <NumberOfReads>892</NumberOfReads>
      <UpdatedTimestamp>2012-11-24 12:34:56</
UpdatedTimestamp>
    </Broadcast>
    <Broadcast>
      <Broadcast_id>393</Broadcast_id>
      <Status>Queued</Status>
      <Subject>AnotherSubject</Subject>
      <AccountNumber>23</AccountNumber>
      <GroupID>55</GroupID>
      <GroupName>My Group 2</GroupName>
```

```

        <JourneyID>5</JourneyID>
        <JourneyName>Test Journey</JourneyName>
        <NumberOfRecipients>786</NumberOfRecipients>
        <DatetimeQueued>2012-11-21 01:23:45</
DatetimeQueued>
        <DatetimeScheduledForDelivery>2013-01-02
13:30:00</DatetimeScheduledForDelivery>
        <DatetimeSent></DatetimeSent>
        <RecipientFiltersUsed>All Active Contacts in
Group</RecipientFiltersUsed>
        <NumberOfClicks>493</NumberOfClicks>
        <NumberOfReads>1027</NumberOfReads>
        <UpdatedTimestamp>2012-11-23 10:43:21</
UpdatedTimestamp>
    </Broadcast>
</Broadcasts>
</GetBroadcastsResponse>

```

Get Broadcast Stats

This function allows the caller to get stats for a broadcast

Input

Broadcast ID (required).

Specify order_by (optional) for the sort sequence of the contacts returned. Order by can be Name, Company, LastRead, or ClicksPlusReads (default). Name and company are in ascending alphanumeric order with blanks last. LastRead and ClicksPlusReads are in descending numeric order.

Pass limit=n to return the first n matching contacts.

Pass message_type='drip' along with the drip campaign broadcast_id to get drip campaign stats.

Pass message_type='personal_email' along with the broadcast_id to get email stats.

Pass start_chunk_size=n to change the default pagination chunk size to n (default 10000).

Pass start_chunk_page=n to get the nth page of results (numbering starts at 0).

Output

For each contact in the broadcasts - contact ID, send data, read data, click data, bounce data.

Journey ID and journey name if the broadcast belongs to a journey.

Example Request 1

```
<GetBroadcastStatsRequest broadcast_id="994"
order_by="Company" limit="100"></GetBroadcastStatsRequest>
```

Example Request 2 (to get Drip Campaign stats)

```
<GetBroadcastStatsRequest broadcast_id="995"
message_type="drip"></GetBroadcastStatsRequest>
```

Example Request 3 (to get Personal Email stats)

```
<GetBroadcastStatsRequest broadcast_id="996"
message_type="personal_email"></GetBroadcastStatsRequest>
```

Example Request 4 (get the second page of 1000 contacts)

```
<GetBroadcastStatsRequest broadcast_id="994"
start_chunk_size=1000 start_chunk_page=1></
GetBroadcastStatsRequest>
```

Example Response

```

<GetBroadcastStatsResponse>
  <Result>Success</Result>
  <Broadcast_id>343567</Broadcast_id>
  <AccountNumber>78</AccountNumber>
  <JourneyID>4</JourneyID>
  <JourneyName>Test Journey</JourneyName>
  <Contacts>
    <Contact>
      <Contact_id>994</Contact_id>
      <Contact_firstname>John</Contact_firstname>
      <Contact_lastname>Smith</Contact_lastname>
      <Contact_email>john.smith@gmail.com</
Contact_email>
      <Company>JS Co</Company>
      <Send_data>
        <DatetimeSent>2010-09-03 12:00:00</
DatetimeSent>
      </Send_data>
      <Read_data>
        <DatetimeRead>2010-09-05 13:45:45</
DatetimeRead>
      <DatetimeRead>2010-09-07 08:00:00</
DatetimeRead>
      </Read_data>
      <Click_data>
        <Click>
          <LinkClicked>http://www.mysite.com/
mylink1.html</LinkClicked>
          <DatetimeClicked>2010-09-05 13:47:08</
DatetimeClicked>
        </Click>
        <Click>
          <LinkClicked>http://www.mysite.com/
mylink2.html</LinkClicked>
          <DatetimeClicked>2010-09-05 13:48:18</
DatetimeClicked>
        </Click>
      </Click_data>
      <Bounce_data></Bounce_data>
    </Contact>
  </Contacts>
</GetBroadcastStatsResponse>

```

```

    <Contact>
      <Contact_id>995</Contact_id>
      <Contact_firstname>Jane</Contact_firstname>
      <Contact_lastname>Doe</Contact_lastname>
      <Contact_email>jane.doe@gmail.com</
Contact_email>
      <Send_data>
        <DatetimeSent>2010-09-03 12:00:01</
DatetimeSent>
      </send_data>
      <read_data>
        <datetimeread>2010-09-05 15:25:15</
datetimeread>
        <datetimeread>2010-09-05 18:01:30</
datetimeread>
      </read_data>
      <click_data>
        <click>
          <linkclicked>http://www.mysite.com/
mylink2.html</linkclicked>
          <datetimeclicked>2010-09-05 16:47:08</
datetimeclicked>
        </click>
        <click>
          <linkclicked>http://www.mysite.com/
mylink4.html</linkclicked>
          <datetimeclicked>2010-09-05 19:18:28</
datetimeclicked>
        </click>
      </click_data>
      <bounce_data></Bounce_data>
    </Contact>
    <Contact>
      <Contact_id>996</Contact_id>
      <Contact_firstname>Johnny</Contact_firstname>
      <Contact_lastname>English</Contact_lastname>
      <Contact_email>johnny.english@gmail.com</
Contact_email>
      <Company>JE Co</Company>
      <Send_data>

```

```

        <DatetimeSent>2010-09-03 12:00:01</
DatetimeSent>
        </Send_data>
        <Read_data></Read_data>
        <Click_data></Click_data>
        <Bounce_data>
            <Bounce>
                <BounceCode>B</BounceCode>
                <BounceReasonShort>routing-errors</
BounceReasonShort>
                <BounceReasonLong>4.4.4 (unable to
route: dns lookup failure) </BounceReasonLong>
            </Bounce>
        </Bounce_data>
    </Contact>
</Contacts>
</GetBroadcastStatsResponse>

```

Get Broadcast Body

This function allows the caller to get HTML message and text message of a broadcast

Input

- broadcast_id (required)
- account_id (required for shared access users)
- group_id (required for shared access users)
- include_rfc822 (true to return broadcast message in RFC822 format)
- contact_id (required when passing include_rfc822)

Output

- AccountNum
- GroupID
- GroupName

- BroadcastID
- FromName
- FromEmail
- Contact_id (if contact_id passed)
- Contact_firstname (if contact_id passed)
- Contact_lastname (if contact_id passed)
- Contact_email (if contact_id passed)
- Subject
- Action
- DatetimeQueued
- DatetimeSent
- MessageHTML
- MessageText
- RFC822 (if include_rfc822 passed)

Example Request

```
<GetBroadcastBodyRequest broadcast_id="646064"/>
```

Example Request (include RFC822)

```
<GetBroadcastBodyRequest broadcast_id="646064"
contact_id="7" include_rfc822="true"/>
```

Example Request (Shared Access)

```
<GetBroadcastBodyRequest broadcast_id="646064"
account_id="1" group_id="1"/>
```

Example Response

```
<GetBroadcastBodyResponse>
  <Result>Success</Result>
  <AccountNum>38193</AccountNum>
  <GroupID>1</GroupID>
  <GroupName>My Group</GroupName>
  <BroadcastID>646064</BroadcastID>
  <FromName>support</FromName>
  <FromEmail>support@company.org</FromEmail>
```



```

<Contact_id>123</Contact_id>
<Contact_firstname>John</Contact_firstname>
<Contact_lastname>Smith</Contact_lastname>
<Contact_email>john.smith@gmail.com</Contact_email>
<Subject>Happy Birthday</Subject>
<Action>Sent Email</Action>
<DatetimeQueued>2014-06-25 21:06:00</DatetimeQueued>
<DatetimeSent>2014-06-30 21:05:00</DatetimeSent>
<MessageHTML>&lt;html&gt;
&lt;head&gt;
    &lt;title&gt;Message for you&lt;/title&gt;
&lt;/head&gt;
&lt;body style="cursor: auto;"&gt;
&lt;table id="Background" width="100%"&gt;
    &lt;tbody&gt;
        &lt;tr&gt;
            &lt;td&gt;
                &lt;p&gt;Write your email
message here.&lt;/p&gt;

                &lt;p&gt;You can also import
any saved email or one of our professional templates using
the "Template" button above.&lt;/p&gt;
            &lt;/td&gt;
        &lt;/tr&gt;
    &lt;/tbody&gt;
&lt;/table&gt;
&lt;/body&gt;
&lt;/html&gt;</MessageHTML>
<MessageText>Message for you

    Write your email message here.

    You can also import any saved email or one of our
professional
    templates using the "Template" button above.</
MessageText>
<RFC822>
From: test@test.org
To: receiver@gmail.com

```

Subject: Queue

Message for you

Write your email message here.

You can also import any saved email or one of our professional

templates using the "Template" button above.

</RFC822>

</GetBroadcastBodyResponse>

Queue Mail

This function allows the caller to queue mail to a group.

Input

Group ID or Group Name in request tag, From Name, From Email, Subject, Message HTML or Media ID, DeliveryDateTime

Output

Success or Failure

Example Request 1

```
<QueueMailRequest group_name="MyTeam">
  <From_name>My Organization</From_name>
  <From_email>myorganization@my.org</From_email>
  <Subject>A Cool Test Email</Subject>
  <Message><![CDATA<html><head>(etc. continue HTML)</
body></html>]]></Message>
  <Delivery_date_time>2010-05-01T11:00:00</
Delivery_date_time>
</QueueMailRequest>
```

Example Request 2

```
<QueueMailRequest Group_id="8903">
  <From_name>My Organization</From_name>
  <From_email><myorganization@my.org</From_email>
  <Subject>A Cool Test Email</Subject>
  <Message MediaID="5"></Message>
  <Delivery_date_time>2010-05-01T11:00:00</
Delivery_date_time>
</QueueMailRequest>
```

Example Response

```
<QueueMailResponse>
  <Result>Success</Result>
</QueueMailResponse>
```

Send Test Mail

This function allows the caller to send a test email to up to five addresses.

Input

From Name, From Email, Group ID or Group Name (test recipients will be added to this group if they are not already members), Subject, Message HTML or Media ID, up to 5 recipients.

Output

Success or Failure

Example Request

```
<SendTestMailRequest Group_id="9">
  <From_name>My Organization</From_name>
  <From_email>myorganization@my.org</From_email>
  <Subject>A Cool Test Email</Subject>
  <Message><![CDATA<html><head>(etc. continue HTML)</
body></html>]]></Message>
```

```
<Recipients>
  <Recipient>testmail1@testdomain.com</Recipient>
  <Recipient>testmail2@testdomain.com</Recipient>
</Recipients>
</SendTestMailRequest>
```

Example Response

```
<SendTestMailResponse>
  <Result>Success</Result>
</SendTestMailResponse>
```

Reset Contact Drip Campaign

This function allows the caller to reset the drip campaign for the specified contact. Search criteria can be group_id, contact_id, firstname, lastname, email. Each group and each contact search criteria must return a single unique. drip_campaign_id is also required.

Input

Group ID or Group name for Group search criteria, must return a single unique group. Contact IDs of Contacts to reset, or search criteria for Contacts to reset. Search criteria can be contact_id, firstname, lastname, email. Each contact's search criteria must return a single unique contact. Drip campaign ID is also required. Account ID for shared access.

Output

Success or failure.

Example Request 1

```
<ResetContactDripCampaignRequest group_id='4'
drip_campaign_id='1' contact_id='123'></
ResetContactDripCampaignRequest>
```

Example Request 2

```
<ResetContactDripCampaignRequest group_id='4'  
drip_campaign_id='1' contact_id='123' account_id='38193'></  
ResetContactDripCampaignRequest>
```

Example Response

```
<ResetContactDripCampaignResponse>  
  <Result>Success</Result>  
</ResetContactDripCampaignResponse>
```

Spec - Calendars

Table Of Contents

- Get Calendars
- Get Calendar Ics Link

Get Calendars

This function allows the caller to retrieve a list of calendars of a group.

Input

- account_id
- group_id
- group_name

Output

Success or failure. On success returns a list of calendars of a group.

Example Request

```
<GetCalendarsRequest group_id="4"></GetCalendarsRequest>
```

Successful Response

```
<GetCalendarsResponse>  
  <Result>Success</Result>  
  <Calendars>  
    <Calendar>  
      <Calendar_id>4</Calendar_id>  
      <Title>2014-2015</Title>  
      <ActiveNow>Y</ActiveNow>  
      <TotalActiveContacts>501</TotalActiveContacts>  
    </Calendar>  
  </Calendars>  
</GetCalendarsResponse>
```

```
<Calendar>
  <Calendar_id>6</Calendar_id>
  <Title>Fall 2014</Title>
  <ActiveNow>Y</ActiveNow>
  <TotalActiveContacts>501</TotalActiveContacts>
</Calendar>
</Calendars>
</GetCalendarsResponse>
```

Get Calendar Ics Link

This function allows the caller to retrieve a link to download all of the events on a user's private calendar. The link specifies a URL to an .ics file which can be used by most calendaring programs.

Input

group_id and user_email of the user owning the calendar being request.
account_id if shared_access. If missing, account id defaults to account the caller is an owner of.

Output

Success or failure. On success IcsURL specifying the URL (without http:// or webcal://) of the calendar for download.

Example Request 1

```
<GetCalendarIcsLinkRequest group_id="8"
user_email="useremail@yourdomain.com"></
GetCalendarIcsLinkRequest>
```

Example Request 2 (shared access)

```
<GetCalendarIcsLinkRequest account_id="1234" group_id="8"
user_email="useremail@yourdomain.com"></
GetCalendarIcsLinkRequest>
```

Successful Response

```
<GetCalendarIcsLinkResponse>  
  <Result>Success</Result>  
  <IcsURL>app.domain.com/privcal2.ics?  
d482a0998c22a0999bc279105be151269804c52</IcsURL>  
</GetCalendarIcsLinkResponse>
```


Spec - Companies

Table Of Contents

- Get Companies
- Add Companies
- Edit Companies
- Delete Companies
- Get Company-Level CRM Activities
- Add Company-Level CRM Activities
- Edit Company-Level CRM Activities
- Delete Company-Level CRM Activities
- Get Company Contacts
- Get Company CRM Activities
- Get Company Events Attended By Type

Get Companies

This function allows the caller to retrieve a list of companies from the database.

Search parameters should be specified inside the tag.

‘scope’ returns companies from all the groups by default. Specify the ‘group_id’ and ‘scope’ to ‘group’ to return companies for contacts under this group.

‘has_contacts’ filters companies that only has contacts in them.

‘scope’ and ‘has_contacts’ can be used together.

Input

- group_id (required)
- account_id (required for shared access)
- company_id
- search
- scope (all/group)
- has_contacts (true/false)
- include_user_defined_fields (true/false)

Output

Success or failure. List of companies.

Example Request

```
<GetCompaniesRequest group_id="4"></GetCompaniesRequest>
```

Example Request

```
<GetCompaniesRequest group_id="4" company_id="5"></GetCompaniesRequest>
```

Example Request (search company name)

```
<GetCompaniesRequest group_id="4" search='Appl'></GetCompaniesRequest>
```

Example Request (filter companies within this group)

```
<GetCompaniesRequest group_id="4" scope="group"></GetCompaniesRequest>
```

Example Request (filter companies that has contacts)

```
<GetCompaniesRequest group_id="4" has_contacts="true"></GetCompaniesRequest>
```

Example Request (filter companies within this group that has contacts)

```
<GetCompaniesRequest group_id="4" scope="group" has_contacts="true"></GetCompaniesRequest>
```

Example Request (include company user-defined fields)

```
<GetCompaniesRequest group_id="4"
include_user_defined_fields="true"></GetCompaniesRequest>
```

Successful Response

```
<GetCompaniesResponse>
  <Result>Success</Result>
  <Companies>
    <Company>
      <CompanyID>1</CompanyID>
      <CompanyName>Test Company 1</CompanyName>
      <CompanyEmail>testcompany@gmail.com</
CompanyEmail>
      <Address>test</Address>
      <City>Test City</City>
      <State>Test State</State>
      <Zip>31900</Zip>
      <Country>United States</Country>
      <Website>http://google.com</Website>
      <Phone>012321321</Phone>
      <PrimaryContactID></PrimaryContactID>
      <SecondaryContactID></SecondaryContactID>
      <ParentCompany></ParentCompany>

      <CompanyInfo>&lt;p&gt;&lt;em&gt;&lt;strong&gt;The quick
brown fox jumps over the lazy dog.&lt;/strong&gt;&lt;/em&gt;&lt;/p&gt;</CompanyInfo>
      <NumberOfContacts>2</NumberOfContacts>
      <NumberOfCompanyLevelCRMActivities>0</
NumberOfCompanyLevelCRMActivities>
      <NumberOfTickets>0</NumberOfTickets>
      <NumberOfOpportunities>0</
NumberOfOpportunities>
      <NumberOfCRMActivities>0</
NumberOfCRMActivities>
      <NumberOfEventsAttendedByType>0</
NumberOfEventsAttendedByType>
      <UserDefinedFields>
```

```

        <UserDefinedField>
            <UserFieldID>1</UserFieldID>
            <FieldName>Fruit</FieldName>
            <FieldValue>Apple</FieldValue>
        </UserDefinedField>
        <UserDefinedField>
            <UserFieldID>14</UserFieldID>
            <FieldName>Animal</FieldName>
            <FieldValue>Dog</FieldValue>
        </UserDefinedField>
    </UserDefinedFields>
</Company>
<Company>
    <CompanyID>2</CompanyID>
    <CompanyName>Waveright CO.</CompanyName>
    <CompanyEmail></CompanyEmail>
    <Address></Address>
    <City></City>
    <State></State>
    <Zip></Zip>
    <Country></Country>
    <Website></Website>
    <Phone></Phone>
    <PrimaryContactID></PrimaryContactID>
    <SecondaryContactID></SecondaryContactID>
    <ParentCompany></ParentCompany>
    <CompanyInfo></CompanyInfo>
    <NumberOfContacts>1</NumberOfContacts>
    <NumberOfCompanyLevelCRMActivities>0</
NumberOfCompanyLevelCRMActivities>
    <NumberOfTickets>0</NumberOfTickets>
    <NumberOfOpportunities>0</
NumberOfOpportunities>
    <NumberOfCRMActivities>0</
NumberOfCRMActivities>
    <NumberOfEventsAttendedByType>0</
NumberOfEventsAttendedByType>
    <UserDefinedFields>
        <UserDefinedField>
            <UserFieldID>1</UserFieldID>

```

```

        <FieldName>Fruit</FieldName>
        <FieldValue>Apple</FieldValue>
    </UserDefinedField>
    <UserDefinedField>
        <UserFieldID>14</UserFieldID>
        <FieldName>Animal</FieldName>
        <FieldValue>Dog</FieldValue>
    </UserDefinedField>
</UserDefinedFields>
</Company>
<Company>
    <CompanyID>3</CompanyID>
    <CompanyName>Acme Widgets, LLC</CompanyName>
    <CompanyEmail></CompanyEmail>
    <Address></Address>
    <City></City>
    <State></State>
    <Zip></Zip>
    <Country></Country>
    <Website></Website>
    <Phone></Phone>
    <PrimaryContactID></PrimaryContactID>
    <SecondaryContactID></SecondaryContactID>
    <ParentCompany></ParentCompany>
    <CompanyInfo></CompanyInfo>
    <NumberOfContacts>1</NumberOfContacts>
    <NumberOfCompanyLevelCRMActivities>0</
NumberOfCompanyLevelCRMActivities>
    <NumberOfTickets>0</NumberOfTickets>
    <NumberOfOpportunities>0</
NumberOfOpportunities>
    <NumberOfCRMActivities>0</
NumberOfCRMActivities>
    <NumberOfEventsAttendedByType>0</
NumberOfEventsAttendedByType>
    <UserDefinedFields>
        <UserDefinedField>
            <UserFieldID>1</UserFieldID>
            <FieldName>Fruit</FieldName>
            <FieldValue>Apple</FieldValue>

```

```
        </UserDefinedField>
        <UserDefinedField>
            <UserFieldID>14</UserFieldID>
            <FieldName>Animal</FieldName>
            <FieldValue>Dog</FieldValue>
        </UserDefinedField>
    </UserDefinedFields>
</Company>
</Companies>
</GetCompaniesResponse>
```

Add Companies

This function allows the caller to add companies.

Search parameters should be specified inside the tag.

The caller must have contacts access permissions to an account in order to this action.

Input

- account_id
- group_id
- request_id (optional)
- Company Name
- Email
- Address
- City
- State
- Zip
- Country
- Website
- Phone
- Primary Contact ID
- Secondary Contact ID

- Parent Company
- Company Info
- UserDefinedFields (fieldnum/fieldname)

Output

Success or failure for each companies. Company ID.

Example Request

```
<AddCompaniesRequest group_id="4">
  <Companies>
    <Company request_id="a1b2c3">
      <CompanyName>Sample Company</CompanyName>
      <CompanyEmail>testcompany@gmail.com</
CompanyEmail>
      <Address>123, Address 1</Address>
      <City>City</City>
      <State>State</State>
      <Zip>12345</Zip>
      <Country>United States</Country>
      <Website>google.com</Website>
      <Phone>1231234</Phone>
      <ParentCompany></ParentCompany>
      <CompanyInfo>Sample company info</CompanyInfo>
      <UserDefinedFields>
        <UserDefinedField fieldnum="123">Apple</
UserDefinedField>
        <UserDefinedField fieldname="Animal">Dog</
UserDefinedField>
      </UserDefinedFields>
    </Company>
  </Companies>
</AddCompaniesRequest>
```

Successful Response

```
<AddCompaniesResponse>
  <Companies>
    <Company request_id="a1b2c3">
```

```
        <Result>Success</Result>
        <CompanyID>15</CompanyID>
    </Company>
</Companies>
</AddCompaniesResponse>
```

Edit Companies

This function allows the caller to modify one or more companies already in the database.

Search parameters should be specified inside the tag, while parameters to change to would be specified individually.

The caller must have contacts access permissions to an account in order to this action.

Input

- account_id
- group_id
- company_id
- request_id (optional)
- Company Name
- Email
- Address
- City
- State
- Zip
- Country
- Website
- Phone
- Primary Contact ID
- Secondary Contact ID
- Parent Company

- Company Info
- UserDefinedFields (fieldnum/fieldname)

Output

Success or failure for each companies. Company ID.

Example Request

```
<EditCompaniesRequest group_id="4">
  <Companies>
    <Company company_id="15" request_id="a1b2c3">
      <CompanyName>Edited Sample Company</
CompanyName>
      <CompanyEmail>testcompany@gmail.com</
CompanyEmail>
      <Address>123, Address 1</Address>
      <City>City</City>
      <State>State</State>
      <Zip>12345</Zip>
      <Country>United States</Country>
      <Website>google.com</Website>
      <Phone>1231234</Phone>
      <ParentCompany></ParentCompany>
      <CompanyInfo>&lt;p>Sample company
info&lt;/p>&#x2F;p>&lt;/CompanyInfo>
      <UserDefinedFields>
        <UserDefinedField fieldnum="123">Apple</
UserDefinedField>
        <UserDefinedField fieldname="Animal">Dog</
UserDefinedField>
      </UserDefinedFields>
    </Company>
  </Companies>
</EditCompaniesRequest>
```

Example Response

```
<EditCompaniesResponse>
  <Companies>
```

```
        <Company request_id="a1b2d3">
            <Result>Success</Result>
            <CompanyID>15</CompanyID>
        </Company>
    </Companies>
</EditCompaniesResponse>
```

Delete Companies

This function allows the caller to delete one or more companies from the database.

Search parameters should be specified inside the tag.

The caller must have contacts access permissions to an account in order to this action.

Input

- account_id
- group_id
- company_id
- request_id (optional)

Output

Success or failure for each companies. Company ID.

Example Request

```
<DeleteCompaniesRequest group_id="4">
    <Companies>
        <Company company_id="15" request_id="a1b2c3"/>
    </Companies>
</DeleteCompaniesRequest>
```

Example Response

```
<DeleteCompaniesResponse>
  <Companies>
    <Company request_id="a1b2c3">
      <Result>Success</Result>
      <CompanyID>15</CompanyID>
    </Company>
  </Companies>
</DeleteCompaniesResponse>
```

Get Company-Level CRM Activities

This function allows the caller to retrieve company-level CRM activities from the database.

Search parameters should be specified inside the tag.

The caller must have contacts access permissions to an account in order to this action.

Input

- account_id (required for shared access)
- group_id
- company_id
- activity_id
- show_assignables

Output

Success or failure. A list of company-level CRM activities.

Example Request

```
<GetCompanyLevelCRMActivitiesRequest group_id="4"
company_id="1" show_assignables="true"></
GetCompanyLevelCRMActivitiesRequest>
```

Example Request

```
<GetCompanyLevelCRMActivitiesRequest group_id="4"
activity_id="49"></GetCompanyLevelCRMActivitiesRequest>
```

Successful Response

```
<GetCompanyLevelCRMActivitiesResponse>
  <Result>Success</Result>
  <CRMActivities>
    <CRMActivity>
      <ActivityID>49</ActivityID>
      <Activity>Make Note</Activity>
      <GroupID>1</GroupID>
      <CompanyID>1</CompanyID>
      <OpportunityID></OpportunityID>
      <DoneByContactID>0</DoneByContactID>
      <DoneByFirstname></DoneByFirstname>
      <DoneByLastname></DoneByLastname>
      <DoneDate>2015-03-09 11:10:00</DoneDate>
      <DueDate>2015-03-14 11:45:00</DueDate>
      <Priority>Normal</Priority>
      <Notes>Tset</Notes>
    </CRMActivity>
  </CRMActivities>
  <AssignableContacts>
    <AssignableContact>
      <ContactID>0</ContactID>
      <Name>Todd Wade</Name>
      <Email></Email>
    </AssignableContact>
    <AssignableContact>
      <ContactID>5</ContactID>
      <Name>NCA Wade</Name>
      <Email>someone.nca@gmail.com</Email>
    </AssignableContact>
  </AssignableContacts>
</GetCompanyLevelCRMActivitiesResponse>
```

Add Company-Level CRM Activities

This function allows the caller to add one or more company-level CRM activities.

The caller must have contacts access permissions to an account in order to this action.

Input

- account_id
- group_id
- request_id (optional)
- Company ID
- Done By Contact ID
- Group ID
- Done Date (YYYYMMDDHHMM format)
- Due Date (YYYYMMDDHHMM format)
- Activity
- Notes

Output

Success or failure for each company-level CRM activities. Company-level CRM activity ID.

Example Request

```
<AddCompanyLevelCRMActivitiesRequest group_id="4">
  <CRMActivities>
    <CRMActivity request_id="a1b2c3">
      <CompanyID>1</CompanyID>
      <DoneByContactID>0</DoneByContactID>
      <GroupID>4</GroupID>
      <DoneDate>202206220257</DoneDate>
      <DueDate>202206220257</DueDate>
      <Activity>Make Note</Activity>
      <Notes>Sample notes</Notes>
    </CRMActivity>
  </CRMActivities>
</AddCompanyLevelCRMActivitiesRequest>
```

```
        </CRMActivity>
    </CRMActivities>
</AddCompanyLevelCRMActivitiesRequest>
```

Successful Response

```
<AddCompanyLevelCRMActivitiesResponse>
    <CRMActivities>
        <CRMActivity request_id="a1b2c3">
            <Result>Success</Result>
            <ActivityID>51</ActivityID>
        </CRMActivity>
    </CRMActivities>
</AddCompanyLevelCRMActivitiesResponse>
```

Edit Company-Level CRM Activities

This function allows the caller to modify one or more company-level CRM activities already in the database.

Search parameters should be specified inside the tag, while parameters to change to would be specified individually.

The caller must have contacts access permissions to an account in order to this action.

Input

- account_id
- group_id
- activity_id
- company_id
- request_id (optional)
- Group ID
- Done Date (YYYYMMDDHHMM format)
- Due Date (YYYYMMDDHHMM format)
- Activity

- Notes

Output

Success or failure for each company-level CRM activities. Company-level CRM activity ID.

Example Request

```
<EditCompanyLevelCRMActivitiesRequest group_id="4">
  <CRMActivities>
    <CRMActivity activity_id="51" company_id="1"
request_id="alb2c3">
      <DoneByContactID>0</DoneByContactID>
      <GroupID>4</GroupID>
      <DoneDate>202206220257</DoneDate>
      <DueDate>202206220257</DueDate>
      <Activity>Make Note</Activity>
      <Notes>Sample notes</Notes>
    </CRMActivity>
  </CRMActivities>
</EditCompanyLevelCRMActivitiesRequest>
```

Example Response

```
<EditCompanyLevelCRMActivitiesResponse>
  <CRMActivities>
    <CRMActivity request_id="alb2c3">
      <Result>Success</Result>
      <ActivityID>51</ActivityID>
      <CompanyID>1</CompanyID>
    </CRMActivity>
  </CRMActivities>
</EditCompanyLevelCRMActivitiesResponse>
```

Delete Company-Level CRM Activities

This function allows the caller to delete one or more company-level CRM activities from the database.

Search parameters should be specified inside the tag.

The caller must have contacts access permissions to an account in order to this action.

Input

- account_id
- group_id
- activity_id
- company_id
- request_id (optional)

Output

Success or failure for each company-level CRM activities. List of company-level CRM activities.

Example Request

```
<DeleteCompanyLevelCRMActivitiesRequest group_id="4">
  <CRMActivities>
    <CRMActivity activity_id="51" company_id="1"
request_id="alb2c3"/>
  </CRMActivities>
</DeleteCompanyLevelCRMActivitiesRequest>
```

Example Response

```
<DeleteCompanyLevelCRMActivitiesResponse>
  <CRMActivities>
    <CRMActivity request_id="alb2c3">
      <Result>Success</Result>
      <ActivityID>51</ActivityID>
      <CompanyID>1</CompanyID>
    </CRMActivity>
  </CRMActivities>
</DeleteCompanyLevelCRMActivitiesResponse>
```


Get Company Contacts

This function allows the caller to retrieve a company's contacts from the database.

Search parameters should be specified inside the tag.

The caller must have contacts access permissions to an account in order to this action.

Input

- account_id (required for shared access)
- group_id
- company_id

Output

Success or failure. A list of company's contacts.

Example Request

```
<GetCompanyContactsRequest group_id="4" company_id="1"></GetCompanyContactsRequest>
```

Successful Response

```
<GetCompanyContactsResponse>
  <Result>Success</Result>
  <Contacts>
    <Contact>
      <Contact_id>123</Contact_id>
      <Firstname>Testfirst1 & and " '</Firstname>
      <Lastname>Test1 & 2</Lastname>
      <Email>contact+test1@gmail.com</Email>
      <Title></Title>
      <Phone>(012) 111-111</Phone>
```

```
</Contact>
<Contact>
  <Contact_id>2</Contact_id>
  <Firstname>Test</Firstname>
  <Lastname>Wade</Lastname>
  <Email>another+contact@gmail.com</Email>
  <Title></Title>
  <Phone>330 555 1212</Phone>
</Contact>
</Contacts>
</GetCompanyContactsResponse>
```

Get Company CRM Activities

This function allows the caller to retrieve a company's CRM activities from the database.

Search parameters should be specified inside the tag.

The caller must have contacts access permissions to an account in order to this action.

Input

- account_id (required for shared access)
- group_id
- activity_id
- company_id

Output

Success or failure. A list of company's CRM activities.

Example Request

```
<GetCompanyCRMActivitiesRequest group_id="4"
company_id="1"></GetCompanyCRMActivitiesRequest>
```

Example Request

```
<GetCompanyCRMActivitiesRequest group_id="4"
activity_id="46"></GetCompanyCRMActivitiesRequest>
```

Successful Response

```
<GetCompanyCRMActivitiesResponse>
  <Result>Success</Result>
  <CRMActivities>
    <CRMActivity>
      <ActivityID>46</ActivityID>
      <Activity>Make Note</Activity>
      <ContactID>123</ContactID>
      <ContactFirstname>Testfirst1 & and " ' </
ContactFirstname>
      <ContactLastname>Test1 & 2</
ContactLastname>
      <GroupID>4</GroupID>
      <CompanyID>1</CompanyID>
      <OpportunityID>0</OpportunityID>
      <DoneByContactID>0</DoneByContactID>
      <DoneByFirstname></DoneByFirstname>
      <DoneByLastname></DoneByLastname>
      <DoneDate>201503171020</DoneDate>
      <DueDate></DueDate>
      <Priority>Normal</Priority>
      <Notes></Notes>
    </CRMActivity>
    <CRMActivity>
      <ActivityID>47</ActivityID>
      <Activity>Follow-Up</Activity>
      <ContactID>123</ContactID>
      <ContactFirstname>Testfirst1 & and " ' </
ContactFirstname>
      <ContactLastname>Test1 & 2</
ContactLastname>
      <GroupID>1</GroupID>
      <CompanyID>1</CompanyID>
      <OpportunityID></OpportunityID>
```

```

    <DoneByContactID>5</DoneByContactID>
    <DoneByFirstname>NCA</DoneByFirstname>
    <DoneByLastname>Wade</DoneByLastname>
    <DoneDate></DoneDate>
    <DueDate>201502191102</DueDate>
    <Priority>Normal</Priority>
    <Notes>Reply to his email about studs</Notes>
  </CRMActivity>
  <CRMActivity>
    <ActivityID>4</ActivityID>
    <Activity>Phone Call</Activity>
    <ContactID>2</ContactID>
    <ContactFirstname>Test</ContactFirstname>
    <ContactLastname>Wade</ContactLastname>
    <GroupID>1</GroupID>
    <CompanyID></CompanyID>
    <OpportunityID></OpportunityID>
    <DoneByContactID>0</DoneByContactID>
    <DoneByFirstname></DoneByFirstname>
    <DoneByLastname></DoneByLastname>
    <DoneDate>20140420061000</DoneDate>
    <DueDate></DueDate>
    <Priority>Normal</Priority>
    <Notes>gave user a call; again</Notes>
  </CRMActivity>
</CRMActivities>
</GetCompanyCRMActivitiesResponse>

```

Get Company Events Attended By Type

This function allows the caller to retrieve a company's events attend by type from the database.

Search parameters should be specified inside the tag.

The caller must have contacts access permissions to an account in order to this action.

Input

- account_id (required for shared access)
- group_id
- company_id

Output

Success or failure. A list of company's events attended by type.

Example Request

```
<GetCompanyEventsAttendedByTypeRequest group_id="4"
company_id="1"></GetCompanyEventsAttendedByTypeRequest>
```

Successful Response

```
<GetCompanyEventsAttendedByTypeResponse>
  <Result>Success</Result>
  <EventsAttendedByType>
    <Event>
      <EventType>Course</EventType>
      <Attendees>1</Attendees>
    </Event>
  </EventsAttendedByType>
</GetCompanyEventsAttendedByTypeResponse>
```

Spec - Contacts

Table Of Contents

- Get Contacts
- Add Contacts
- Edit Contacts
- Delete Contacts
- Search Contacts
- Unsubscribe Contacts
- Get Contact Groups
- Get User Defined Fields
- Add User Defined Field
- Edit User Defined Field
- Delete User Defined Field

Get Contacts

This function allows the caller to retrieve contacts from the database. Search parameters should be specified inside the tag. Contacts can be retrieved by group, individual contacts can be searched for, or all contacts in the account can be returned.

Input

Specify search criteria within GetContactsRequest tag. Search criteria can be group_id (return all contacts belonging to group), contact_id, firstname, lastname, email. If no search criteria, return all contacts in account.

Specify get_all="true" to return all contacts that the account has access to, including shared access. Note that when passing get_all="true" and

response="json" arguments altogether, results are paginated by default and only the first 100 contacts will be returned. To fetch the next page, pass the 'start_chunk_page' parameter. To use a different result size other than the default 100, pass the 'start_chunk_size' parameter. Automatic pagination only applies when requesting JSON response, XML response is not paginated.

To return unsubscribes only, include Unsubscribed="true" in the main tag. If a group is specified with the Unsubscribed tag, all unsubscribes from that group will be returned. If not, unsubscribes at the account level will be returned.

Specify Unsubscribed_startdate or Unsubscribed_enddate (YYYYMMDD) to filter unsubscribed contacts within a specific date range. Unsubscribed="true" must be passed together to work.

To return bounced only, include Bounced="true" in the main tag. If a group is specified with the Bounced tag, all bounced from that group will be returned. If not, bounced at the account level will be returned.

Specify Bounced_startdate or Bounced_enddate (YYYYMMDD) to filter bounced contacts within a specific date range. Bounced="true" must be passed together to work.

To get contacts that were updated after a certain timestamp, pass the updated_timestamp parameter in "YYYY-MM-DD HH:mm:ss" format.

To get contacts within a last name range, specify start_lastname and/or end_lastname. Pass do_lead_scoring="true" to have lead scoring information about each contact included in the output.

Use the 'search' parameter to widen the search scope which searches the contact's firstname, lastname, company, title and email. The 'search' parameter does not work with the 'get_all' parameter.

Only account owner or power user has the permission to fetch contacts that are not in any groups.

Pagination

GetContactsRequest allows pagination. It can be done by passing the following parameters inside the GetContactsRequest tag:

- start_chunk_page (integer, first page starts from 0, eg. 0/1/2/...)
- start_chunk_size (integer, optional, defaults to 100 if empty)

Pagination can be used in conjunction with any search parameters like 'get_all', 'group_id', 'firstname', 'search' and etc.

Refer to example requests 11, 12, and 13 on how to use these parameters.

Output

Success or failure. Total number of contacts matching search. For each contact found: Contact id, first name, last name, title, company, address1, address2, city, state, zip, country, phone, mobile, fax, website, email, birthdate, gender, hometown, height, weight, skills and interests, bio, notes, created datetime, updated time stamp, account number, user-defined fields, groups. DemographicLeadScore and ActivityLeadScore if do_lead_scoring="true" was passed.

The contacts are sorted in the order of AccountNumber, Lastname, Firstname, Email then Contact_id.

Example Request

```
<GetContactsRequest></GetContactsRequest>
```

Example Request


```
<GetContactsRequest group_id="9985"></GetContactsRequest>
```

Example Request

```
<GetContactsRequest firstname="samuel" lastname="Barthman"
email="sbarthman@acmewidgetsllc.com"></GetContactsRequest>
```

Example Request

```
<GetContactsRequest updated_timestamp="2012-01-01
07:00:34"></GetContactsRequest>
```

Example Request

```
<GetContactsRequest start_lastname="D"
end_lastname="Jzzzzzzzzzzzzzzzz"></GetContactsRequest>
```

Example Request

```
<GetContactsRequest search="john"></GetContactsRequest>
```

Example Request (unsubscribed contacts only)

```
<GetContactsRequest Unsubscribed="true"></
GetContactsRequest>
```

Example Request (unsubscribed contacts within date range)

```
<GetContactsRequest Unsubscribed="true"
Unsubscribed_startdate="20180101"
Unsubscribed_enddate="20180131"></GetContactsRequest>
```

Example Request (bounced contacts only)

```
<GetContactsRequest Bounced="true"></GetContactsRequest>
```

Example Request (bounced contacts within date range)

```
<GetContactsRequest Bounced="true"
Bounced_startdate="20180101" Bounced_enddate="20180131"></
GetContactsRequest>
```

Example Request (shared access - single account)

```
<GetContactsRequest account_id="123456"></  
GetContactsRequest>
```

Example Request (all contacts from all accounts including shared access)

```
<GetContactsRequest get_all="true"></GetContactsRequest>
```

Example Request (when requesting JSON response with ‘get_all’, only the first page of 100 contacts from all accounts are returned)

```
<GetContactsRequest get_all="true" response="json"></  
GetContactsRequest>
```

Example Request (to fetch subsequent pages when requesting JSON response with ‘get_all’, pass ‘start_chunk_page’, first page starts at 0)

```
<GetContactsRequest get_all="true" response="json"  
start_chunk_page="1"></GetContactsRequest>
```

Example Request (to override the default 100 chunk size)

```
<GetContactsRequest get_all="true" response="json"  
start_chunk_page="0" start_chunk_size="200"></  
GetContactsRequest>
```

Example Request (shared access - all contacts with lead scoring)

```
<GetContactsRequest get_all="true"  
do_lead_scoring="true"></GetContactsRequest>
```

Example Request (pagination - get the first page results with default 100 contact size)

```
<GetContactsRequest start_chunk_page="0"></  
GetContactsRequest>
```

Example Request (pagination - get the third page results with default 100 contact size for contacts with firstname ‘John’)

```
<GetContactsRequest firstname="John"
start_chunk_page="2"></GetContactsRequest>
```

Example Request (pagination - get the second page results with custom 50 contact size for contacts in group_id 4)

```
<GetContactsRequest group_id="4" start_chunk_page="1"
start_chunk_size="50"></GetContactsRequest>
```

Example Request (power user - get contacts, including those not in any group)

```
<GetContactsRequest account_id="4" start_chunk_page="0"
start_chunk_size="50"></GetContactsRequest>
```

Successful Response

```
<GetContactsResponse>
  <Result>Success</Result>
  <Contacts>
    <Contact>
      <Contact_id>8923</Contact_id>
      <Firstname>Jefferey</Firstname>
      <Lastname>Johnson</Lastname>
      <Title>CEO</Title>
      <Company>Acme Widgets, LLC</Company>
      <Address1>101 First Street</Address1>
      <Address2>Suite 234</Address2>
      <City>Naperville</City>
      <State>IL</State>
      <Zip>60565</Zip>
      <Country>USA</Country>
      <Phone>630-305-9999</Phone>
      <Mobile>708-555-6565</Mobile>
      <Fax>630-305-9988</Fax>
      <Website>http://www.acmewidgetsllc.com</
Website>
      <Email>jjohnson@acmewidgetsllc.com</Email>
      <Unsubscribed>0</Unsubscribed>
      <CreatedDatetime>2012-07-01 12:34:56</
CreatedDatetime>
```

```

        <UpdatedTimeStamp>2012-08-29 12:34:56</
UpdatedTimeStamp>
        <Birthdate>19890302</Birthdate>
        <Gender>male</Gender>
        <Hometown>Peoria, IL</Hometown>
        <Height>73</Height>
        <Weight>185</Weight>
        <SkillsAndInterests>Pinochle, Basket Weaving</
SkillsAndInterests>
        <Bio>(Biographical Information here)</Bio>
        <Notes>Notes from account owner</Notes>
        <AccountNumber>91234</AccountNumber>
        <UserDefinedFields>
            <UserDefinedField>
                <UserFieldID>932</UserFieldID>
                <FieldName>Favorite Animal</FieldName>
                <FieldValue>Dog</FieldValue>
            </UserDefinedField>
            <UserDefinedField>
                <UserFieldID>1023</UserFieldID>
                <FieldName>Fruits</FieldName>
                <FieldValue>Apple</FieldValue>
            </UserDefinedField>
            <UserDefinedField>
                <UserFieldID>1024</UserFieldID>
                <FieldName>Checkboxes Type Example</
FieldName>
                <FieldValue>Football,Basketball,Tennis</FieldValue>
            </UserDefinedField>
        </UserDefinedFields>
        <Groups>
            <Group>
                <Group_id>9985</Group_id>
                <GroupName>groupname1</GroupName>
            </Group>
            <Group>
                <Group_id>9986</Group_id>
                <GroupName>groupname2</GroupName>
            </Group>
        </Groups>
    </User>

```

```

        <DemographicLeadScore>50</
DemographicLeadScore>
        <ActivityLeadScore>329.9</
ActivityLeadScore>
    </Groups>
    <Tags>
        <Tag>
            <TagID>182746</TagID>
            <TagName>Chief Operating Officer</
TagName>
                <Abbreviation>COO</Abbreviation>
            </Tag>
            <Tag>
                <TagID>193802</TagID>
                <TagName>Twitter User</TagName>
                <Abbreviation>TW</Abbreviation>
            </Tag>
        </Tags>
        <SecondaryCompanies>
            <SecondaryCompany>
                <CompanyID>1</CompanyID>
                <CompanyName>Company ABC</CompanyName>
            </SecondaryCompany>
            <SecondaryCompany>
                <CompanyID>2</CompanyID>
                <CompanyName>Company DEF</CompanyName>
            </SecondaryCompany>
        </SecondaryCompanies>
    </Contact>
    <Contact>
        <Firstname>Sam</Firstname>
        <Lastname>Bartman</Lastname>
        <Title>CFO</Title>
        <Company>Acme Widgets, LLC</Company>
        <Address1>101 First Street</Address1>
        <Address2>Suite 234</Address2>
        <City>Naperville</City>
        <State>IL</State>
        <Zip>60565</Zip>
        <Country>USA</Country>

```

```

        <Phone>630-305-9999</Phone>
        <Mobile>708-555-6565</Mobile>
        <Fax>630-305-9988</Fax>
        <Website>http://www.acmewidgetsllc.com</
Website>
        <Email>jjohnson@acmewidgets.com</Email>
        <Unsubscribed>1</Unsubscribed>
        <Birthdate>19720230</Birthdate>
        <Gender>male</Gender>
        <Hometown>Youngstown, OH</Hometown>
        <Height>70</Height>
        <Weight>170</Weight>
        <SkillsAndInterests>Piano, Finances</
SkillsAndInterests>
        <Bio>(Biographical Information here)</Bio>
        <Notes>Notes from account owner</Notes>
        <CreatedDatetime>2012-07-01 12:34:56</
CreatedDatetime>
        <UpdatedTimeStamp>2012-08-29 12:34:56</
UpdatedTimeStamp>
        <AccountNumber>91234</AccountNumber>
        <UserDefinedFields>
            <UserDefinedField>
                <UserFieldID>571</UserFieldID>
                <FieldName>Favorite Animal</FieldName>
                <FieldValue>Dog</FieldValue>
            </UserDefinedField>
            <UserDefinedField>
                <UserFieldID>823</UserFieldID>
                <FieldName>Fruits</FieldName>
                <FieldValue>Apple</FieldValue>
            </UserDefinedField>
            <UserDefinedField>
                <UserFieldID>824</UserFieldID>
                <FieldName>Checkboxes Type Example</
FieldName>
                <FieldValue>Football,Basketball,Tennis</FieldValue>
            </UserDefinedField>
        </UserDefinedFields>

```

```

    <Groups>
      <Group>
        <ID>9985</ID>
        <Name>groupname1</Name>
      </Group>
      <Group>
        <ID>9986</ID>
        <Name>groupname2</Name>
      </Group>
    </Groups>
    <Tags>
      <Tag>
        <TagID>182746</TagID>
        <TagName>Chief Executive Officer</
TagName>
        <Abbreviation>CEO</Abbreviation>
      </Tag>
      <Tag>
        <TagID>193802</TagID>
        <TagName>Facebook User</TagName>
        <Abbreviation>FB</Abbreviation>
      </Tag>
    </Tags>
    <DemographicLeadScore>75</DemographicLeadScore>
    <ActivityLeadScore>422.2</ActivityLeadScore>
    <SecondaryCompanies>
      <SecondaryCompany>
        <CompanyID>3</CompanyID>
        <CompanyName>Company XYZ</CompanyName>
      </SecondaryCompany>
      <SecondaryCompany>
        <CompanyID>2</CompanyID>
        <CompanyName>Company DEF</CompanyName>
      </SecondaryCompany>
    </SecondaryCompanies>
  </Contact>
</Contacts>
  <TotalMatchingContacts>2</TotalMatchingContacts>
</GetContactsResponse>

```

Add Contacts

This function allows the caller to add one or more contacts. For shared access, specify the account number to be added to within the contact tag. The caller must have contacts access permissions to an account in order to add a contact.

Input

- account_id (required for shared access users)
- request_id (optional)
- Firstname
- Lastname
- Title
- Company (or CompanyID)
- Address1
- Address2
- City
- State
- Zip
- Country
- Phone
- Mobile
- Fax
- Website
- Email
- Birthdate (YYYYMMDD)
- Gender
- Hometown
- Height
- Weight
- SkillsAndInterests
- Bio

- Notes
- UserDefinedFields (fieldnum/fieldname) (YYYYMMDD format for Date type user fields)
- Groups
- Tags (tag name, not tag abbreviation), only appends new tags if not already assigned to contact. To remove tags from contact, use DeleteTagsFromContactRequest from [Spec - Tags](#).
- SecondaryCompanies (primary Company/CompanyID is required before secondary companies can be added)
- WorkflowID

Pass update="true" as a request parameter to make use of the add-or-update function. If a contact already exists (matched by email or firstname-lastname), AddContactsRequest will update the existing contact with the newly submitted data instead of adding a new contact.

AddContactsRequest will add the contact into the 'Groups' specified in the request data if the contact is currently NOT inside them.

To activate a workflow when adding a new contact, pass a valid WorkflowID tag.

Output

For each Contact ID, success or failure

Example Request 1

```
<AddContactsRequest>
  <Contacts>
    <Contact request_id="a1b2c3">
      <Firstname>Jefferey</Firstname>
      <Lastname>Johnson</Lastname>
      <Title>CEO</Title>
      <Company>Acme Widgets, LLC</Company>
      <Address1>101 First Street</Address1>
```

```

        <Address2>Suite 234</Address2>
        <City>Naperville</City>
        <State>IL</State>
        <Zip>60565</Zip>
        <Country>USA</Country>
        <Phone>630-305-9999</Phone>
        <Mobile>708-555-6565</Mobile>
        <Fax>630-305-9988</Fax>
        <Website>http://www.acmewidgetsllc.com</
Website>
        <Email>jjohnson@acmewidgetsllc.com</Email>
        <Birthdate>19690823</Birthdate>
        <Gender>male</Gender>
        <Hometown>Abbotsville</Hometown>
        <Height>73</Height>
        <Weight>220</Weight>
        <SkillsAndInterests>Stock car racing,
football</SkillsAndInterests>
        <Bio>Some biographical information</Bio>
        <Notes>Some notes</Notes>
        <UserDefinedFields>
            <UserDefinedField fieldnum="123">Dog</
UserDefinedField>
            <UserDefinedField
fieldname="Fruits">Apple</UserDefinedField>
            <UserDefinedField fieldname="Checkboxes
Type Example">Football,Basketball,Tennis</UserDefinedField>
            <UserDefinedField fieldname="Date Type
Example">20231023</UserDefinedField>
        </UserDefinedFields>
        <Groups>
            <Group>groupname1</Group>
            <Group>groupname2</Group>
        </Groups>
        <Tags>
            <Tag>Tag Name</Tag>
            <Tag>Long Tag Name</Tag>
        </Tags>
        <SecondaryCompanies>
            <SecondaryCompany>

```

```

        <CompanyID>3</CompanyID>
    </SecondaryCompany>
    <SecondaryCompany>
        <CompanyName>Company DEF</CompanyName>
    </SecondaryCompany>
</SecondaryCompanies>
</Contact>
<Contact request_id="d4e5f6">
    <Firstname>Sam</Firstname>
    <Lastname>Bartman</Lastname>
    <Title>CFO</Title>
    <CompanyID>1</CompanyID>
    <Address1>101 First Street</Address1>
    <Address2>Suite 234</Address2>
    <City>Naperville</City>
    <State>IL</State>
    <Zip>60565</Zip>
    <Country>USA</Country>
    <Phone>630-305-9999</Phone>
    <Mobile>708-555-6565</Mobile>
    <Fax>630-305-9988</Fax>
    <Website>http://www.acmewidgetsllc.com</
Website>
    <Email>jjohnson@acmewidgetsllc.com</Email>
    <Birthdate>19830623</Birthdate>
    <Gender>male</Gender>
    <Hometown>Flint, MI</Hometown>
    <Height>70</Height>
    <Weight>182</Weight>
    <SkillsAndInterests>Accounting, taxes</
SkillsAndInterests>
    <Bio>Some more biographical information</Bio>
    <Notes>Some more notes</Notes>
    <UserDefinedFields>
        <UserDefinedField fieldnum="123">Dog</
UserDefinedField>
        <UserDefinedField
fieldname="Fruits">Apple</UserDefinedField>
        <UserDefinedField fieldname="Checkboxes
Type Example">Football,Basketball,Tennis</UserDefinedField>

```

```

        <UserDefinedField fieldname="Date Type
Example">20231023</UserDefinedField>
    </UserDefinedFields>
    <Groups>
        <Group>groupname3</Group>
        <Group>groupname4</Group>
    </Groups>
    <Tags>
        <Tag>Tag Name</Tag>
        <Tag>Long Tag Name</Tag>
    </Tags>
    <SecondaryCompanies>
        <SecondaryCompany>
            <CompanyID>3</CompanyID>
        </SecondaryCompany>
        <SecondaryCompany>
            <CompanyName>Company DEF</CompanyName>
        </SecondaryCompany>
    </SecondaryCompanies>
    <WorkflowID>4</WorkflowID>
</Contact>
</Contacts>
</AddContactsRequest>

```

Example Request 2 (shared access)

```

<AddContactsRequest>
    <Contacts>
        <Contact account_id="123456">
            <Firstname>Jefferey</Firstname>
            <Lastname>Johnson</Lastname>
            <Title>CEO</Title>
            <Company>Acme Widgets, LLC</Company>
            <Address1>101 First Street</Address1>
            <Address2>Suite 234</Address2>
            <City>Naperville</City>
            <State>IL</State>
            <Zip>60565</Zip>
            <Country>USA</Country>
            <Phone>630-305-9999</Phone>
        </Contact>
    </Contacts>
</AddContactsRequest>

```

```

        <Mobile>708-555-6565</Mobile>
        <Fax>630-305-9988</Fax>
        <Website>http://www.acmewidgetsllc.com</
Website>
        <Email>jjohnson@acmewidgetsllc.com</Email>
        <Birthdate>19891119</Birthdate>
        <Gender>male</Gender>
        <Hometown>Mobile, AL</Hometown>
        <Height>72</Height>
        <Weight>195</Weight>
        <SkillsAndInterests>Race car driving,
manufacturing</SkillsAndInterests>
        <Bio>Some biographical information</Bio>
        <Notes>Some notes</Notes>
        <UserDefinedFields>
            <UserDefinedField fieldnum="123">Dog</
UserDefinedField>
            <UserDefinedField
fieldname="Fruits">Apple</UserDefinedField>
            <UserDefinedField fieldname="Checkboxes
Type Example">Football,Basketball,Tennis</UserDefinedField>
            <UserDefinedField fieldname="Date Type
Example">20231023</UserDefinedField>
        </UserDefinedFields>
        <Groups>
            <Group>groupname1</Group>
            <Group>groupname2</Group>
        </Groups>
        <Tags>
            <Tag>Tag Name</Tag>
            <Tag>Long Tag Name</Tag>
        </Tags>
    </Contact>
</Contacts>
</AddContactsRequest>

```

Example Request 3

```

<AddContactsRequest update="true">
    <Contacts>

```

```

    <Contact>
      <Firstname>Jefferey</Firstname>
      <Lastname>Johnson</Lastname>
      <Title>CEO</Title>
      <CompanyID>1</CompanyID>
      <Address1>101 First Street</Address1>
      <Address2>Suite 234</Address2>
      <City>Naperville</City>
      <State>IL</State>
      <Zip>60565</Zip>
      <Country>USA</Country>
      <Phone>630-305-9999</Phone>
      <Mobile>708-555-6565</Mobile>
      <Fax>630-305-9988</Fax>
      <Website>http://www.acmewidgetsllc.com</
Website>
      <Email>jjohnson@acmewidgetsllc.com</Email>
      <Birthdate>19891119</Birthdate>
      <Gender>male</Gender>
      <Hometown>Mobile, AL</Hometown>
      <Height>72</Height>
      <Weight>195</Weight>
      <SkillsAndInterests>Race car driving,
manufacturing</SkillsAndInterests>
      <Bio>Some biographical information</Bio>
      <Notes>Some notes</Notes>
      <UserDefinedFields>
        <UserDefinedField fieldnum="123">Dog</
UserDefinedField>
        <UserDefinedField
fieldname="Fruits">Apple</UserDefinedField>
        <UserDefinedField fieldname="Checkboxes
Type Example">Football,Basketball,Tennis</UserDefinedField>
        <UserDefinedField fieldname="Date Type
Example">20231023</UserDefinedField>
      </UserDefinedFields>
      <Groups replace="true">
        <Group>groupname1</Group>
        <Group>groupname2</Group>
      </Groups>

```

```

        <Tags>
            <Tag>Tag Name</Tag>
            <Tag>Long Tag Name</Tag>
        </Tags>
    </Contact>
</Contacts>
</AddContactsRequest>

```

Successful Response

```

<AddContactsResponse>
    <Contacts>
        <Contact request_id="a1b2c3">
            <Result>Success</Result>
            <AccountNumber>91234</AccountNumber>
            <Contact_id>8984</Contact_id>
            <UpdatedTimeStamp>2012-08-29 12:34:34</
UpdatedTimeStamp>
        </Contact>
        <Contact request_id="d4e5f6">
            <Result>Success</Result>
            <AccountNumber>91234</AccountNumber>
            <Contact_id>8985</Contact_id>
            <UpdatedTimeStamp>2012-08-29 12:36:00</
UpdatedTimeStamp>
        </Contact>
    </Contacts>
</AddContactsResponse>

```

Edit Contacts

This function allows the caller to modify one or more contacts already in the database. Search parameters should be specified inside the tag, while parameters to change to would be specified individually.

Input

Specify search criteria within each Contact tag. Search criteria can be:

- account_id (required for shared access users)
- contact_id
- firstname
- lastname
- email
- request_id (optional)

Each contact's search criteria must return a single unique contact to modify.

Parameters to change can include:

- Firstname
- Lastname
- Title
- Company (or CompanyID)
- Address1
- Address2
- City
- State
- Zip
- Country
- Phone
- Mobile
- Fax
- Website
- Email
- Birthdate (YYYYMMDD)
- Gender
- Hometown
- Height
- Weight
- SkillsAndInterests
- Bio
- Notes

- Groups
- Tags (tag name, not tag abbreviation), only appends new tags if not already assigned to contact. To remove tags from contact, use DeleteTagsFromContactRequest from [Spec - Tags](#).
- UserDefinedFields (fieldnum/fieldname, only the variables that are being changed need to be passed) (YYYYMMDD format for Date type user fields)
- SecondaryCompanies (primary Company/CompanyID is required before secondary companies can be added. To remove the secondary company from contact, pass the 'remove' argument)

Pass 'replace="true"' parameter to the Groups tag to replace the contact's group entirely. Default case will always append new group into existing groups if 'replace' parameter is not specified. (See Example Request 3)

For shared access, include account number within the contact tag. Caller must have contacts permissions in the account to edit contacts.

Pass Updated Time Stamp in order to have comparison with timestamp on server before making change. If server timestamp is later, change will be rejected. If timestamp is not included in the request, change is always made.

Output

For each Contact ID, success or failure

Example Request 1

```
<EditContactsRequest>
  <Contacts>
    <Contact contact_id="8984" request_id="a1b2c3">
      <Firstname>Jefferey</Firstname>
      <Lastname>Johnson</Lastname>
      <Title>CEO</Title>
```

```

    <Company>Acme Widgets, LLC</Company>
    <Address1>101 First Street</Address1>
    <Address2>Suite 234</Address2>
    <City>Naperville</City>
    <State>IL</State>
    <Zip>60565</Zip>
    <Country>USA</Country>
    <Phone>630-305-9999</Phone>
    <Mobile>708-555-6565</Mobile>
    <Fax>630-305-9988</Fax>
    <Website>http://www.acmewidgetsllc.com</
Website>
    <Email>jjohnson@acmewidgetsllc.com</Email>
    <Birthdate>19870501</Birthdate>
    <Gender>male</Gender>
    <Hometown>Mobile, AL</Hometown>
    <Height>72</Height>
    <Weight>195</Weight>
    <SkillsAndInterests>Race car driving,
manufacturing</SkillsAndInterests>
    <Bio>Some biographical information</Bio>
    <Notes>Some notes</Notes>
    <UserDefinedFields>
        <UserDefinedField fieldnum="123">Dog</
UserDefinedField>
        <UserDefinedField
fieldname="Fruits">Apple</UserDefinedField>
        <UserDefinedField fieldname="Checkboxes
Type Example">Football,Basketball,Tennis</UserDefinedField>
        <UserDefinedField fieldname="Date Type
Example">20231023</UserDefinedField>
    </UserDefinedFields>
    <Tags>
        <Tag>Tag Name</Tag>
        <Tag>Long Tag Name</Tag>
    </Tags>
    <SecondaryCompanies>
        <SecondaryCompany remove="true">
            <CompanyID>3</CompanyID>
        </SecondaryCompany>

```

```

        <SecondaryCompany>
            <CompanyName>Company DEF</CompanyName>
        </SecondaryCompany>
    </SecondaryCompanies>
</Contact>
<Contact firstname="samuel" lastname="Barthman"
email="sbarthman@acmewidgetsllc.com" request_id="d4e5f6">
    <Firstname>Sam</Firstname>
    <Lastname>Bartman</Lastname>
    <Title>CFO</Title>
    <CompanyID>1</CompanyID>
    <Address1>101 First Street</Address1>
    <Address2>Suite 234</Address2>
    <City>Naperville</City>
    <State>IL</State>
    <Zip>60565</Zip>
    <Country>USA</Country>
    <Phone>630-305-9999</Phone>
    <Mobile>708-555-6565</Mobile>
    <Fax>630-305-9988</Fax>
    <Website>http://www.acmewidgetsllc.com</
Website>
    <Email>sbarthman@acmewidgetsllc.com</Email>
    <Birthdate>19910323</Birthdate>
    <Gender>male</Gender>
    <Hometown>Mobile, AL</Hometown>
    <Height>72</Height>
    <Weight>195</Weight>
    <SkillsAndInterests>Race car driving,
manufacturing</SkillsAndInterests>
    <Bio>Some biographical information</Bio>
    <Notes>Some notes</Notes>
    <UserDefinedFields>
        <UserDefinedField fieldnum="123">Dog</
UserDefinedField>
        <UserDefinedField
fieldname="Fruits">Apple</UserDefinedField>
        <UserDefinedField fieldname="Checkboxes
Type Example">Football,Basketball,Tennis</UserDefinedField>

```

```

        <UserDefinedField fieldname="Date Type
Example">20231023</UserDefinedField>
    </UserDefinedFields>
    <Tags>
        <Tag>Tag Name</Tag>
        <Tag>Long Tag Name</Tag>
    </Tags>
    <SecondaryCompanies>
        <SecondaryCompany remove="true">
            <CompanyID>3</CompanyID>
        </SecondaryCompany>
        <SecondaryCompany>
            <CompanyName>Company DEF</CompanyName>
        </SecondaryCompany>
    </SecondaryCompanies>
</Contact>
</Contacts>
</EditContactsRequest>

```

Example Request 2 (Shared access, timestamp checking)

```

<EditContactsRequest>
    <Contacts>
        <Contact account_id="12345" contact_id="8984">
            <UpdatedTimeStamp>2012-08-30 12:12:33</
UpdatedTimeStamp>
            <Firstname>Jefferey</Firstname>
            <Lastname>Johnson</Lastname>
            <Title>CEO</Title>
            <Company>Acme Widgets, LLC</Company>
            <Address1>101 First Street</Address1>
            <Address2>Suite 234</Address2>
            <City>Naperville</City>
            <State>IL</State>
            <Zip>60565</Zip>
            <Country>USA</Country>
            <Phone>630-305-9999</Phone>
            <Mobile>708-555-6565</Mobile>
            <Fax>630-305-9988</Fax>
        </Contact>
    </Contacts>
</EditContactsRequest>

```

```

Website>      <Website>http://www.acmewidgetsllc.com</
Website>      <Email>jjohnson@acmewidgetsllc.com</Email>
              <Birthdate>19840823</Birthdate>
              <Gender>male</Gender>
              <Hometown>Mobile, AL</Hometown>
              <Height>72</Height>
              <Weight>195</Weight>
              <SkillsAndInterests>Race car driving,
manufacturing</SkillsAndInterests>
              <Bio>Some biographical information</Bio>
              <Notes>Some notes</Notes>
              <UserDefinedFields>
                <UserDefinedField fieldnum="123">Dog</
UserDefinedField>
                <UserDefinedField
fieldname="Fruits">Apple</UserDefinedField>
                <UserDefinedField fieldname="Checkboxes
Type Example">Football,Basketball,Tennis</UserDefinedField>
                <UserDefinedField fieldname="Date Type
Example">20231023</UserDefinedField>
              </UserDefinedFields>
              <Tags>
                <Tag>Tag Name</Tag>
                <Tag>Long Tag Name</Tag>
              </Tags>
            </Contact>
          </Contacts>
        </EditContactsRequest>

```

Example Request 3 (Groups replace)

```

<EditContactsRequest>
  <Contacts>
    <Contact contact_id="817">
      <Firstname>Jefferey</Firstname>
      <Lastname>Johnson</Lastname>
      <Email>jjohnson@acmewidgetsllc.com</Email>
      <Groups replace="true">
        <Group>Group A</Group>
      </Groups>
    </Contact>
  </Contacts>
</EditContactsRequest>

```

```

        <Group>Group B</Group>
    </Groups>
</Contact>
<Contact contact_id="818">
    <Firstname>Sam</Firstname>
    <Lastname>Bartman</Lastname>
    <Email>sbartman@acmewidgetsllc.com</Email>
    <Groups>
        <Group>Group A</Group>
    </Groups>
</Contact>
</Contacts>
</EditContactsRequest>

```

Successful Response

```

<EditContactsResponse>
    <Contacts>
        <Contact request_id="a1b2c3">
            <Result>Success</Result>
            <AccountNumber>91234</AccountNumber>
            <Contact_id>8984</Contact_id>
            <UpdatedTimeStamp>2012-08-30 14:23:03</
UpdatedTimeStamp>
        </Contact>
        <Contact request_id="d4e5f6">
            <Result>Success</Result>
            <AccountNumber>91234</AccountNumber>
            <Contact_id>8985</Contact_id>
            <UpdatedTimeStamp>2012-08-30 14:24:09</
UpdatedTimeStamp>
        </Contact>
    </Contacts>
</EditContactsResponse>

```

Delete Contacts

This function allows the caller to delete one or more contacts from the database.

Input

Specify search criteria within each Contact tag. Search criteria can be:

- account_id (required for shared access users)
- contact_id
- firstname
- lastname
- email
- request_id (optional)

Each contact's search criteria must return a single unique contact to delete. For shared access, include account number within the contact tag. Caller must have contacts permissions in the account to delete contacts.

Output

For each Contact ID, success or failure.

Example Request 1

```
<DeleteContactsRequest>
  <Contacts>
    <Contact contact_id="8984" request_id="a1b2c3" />
    <Contact contact_id="8983" request_id="d4e5f6" />
  </Contacts>
</DeleteContactsRequest>
```

Example Request 2 (shared access)

```
<DeleteContactsRequest>
  <Contacts>
    <Contact account_id="12345" contact_id="8984" />
    <Contact account_id="12346" contact_id="8983" />
  </Contacts>
</DeleteContactsRequest>
```

Successful Response

```

<DeleteContactsResponse>
  <Contacts>
    <Contact request_id="a1b2c3">
      <AccountNumber>91234</AccountNumber>
      <Contact_id>8984</Contact_id>
      <Result>Success</Result>
    </Contact>
    <Contact request_id="d4e5f6">
      <AccountNumber>91236</AccountNumber>
      <Contact_id>8983</Contact_id>
      <Result>Success</Result>
    </Contact>
  </Contacts>
</DeleteContactsResponse>

```

Search Contacts

This function allows the caller to search for contacts from the database. Search parameters should be specified inside the tag.

Input

- group_id
- From (all, single, multiple) groups
- Groups (group IDs)
- Filter (none, any, all)
- Rules
 - Field (ID, Email, Firstname, Lastname, Title, Company, Address1, Address2, City, State, Zip, Country, Phone, Mobile, Fax, Website, Gender, Birthdate, Hometown, DefaultJerseyNum, Height, Weight, ParentsName, ParentsEmail, ParentsMobile, ParentsName2, ParentsEmail2, ParentsMobile2, Bio, SkillsInterests, ForumModerator, Notes, Picture, CompanyID)
 - Operator (contains, notcontains, is, isnt, gt, lt)
 - Value

- Rules (for date filters)
 - Field (ContactCreated, LastModified)
 - Range (on, before, after, between)
 - Date (YYYY/MM/DD or YYYY/MM/DD HH:mm:ss)
 - Date2 (required if Range value is 'between', YYYY/MM/DD or YYYY/MM/DD HH:mm:ss)
- Includes (Unsubscribers, BouncedContacts, SpamComplaints, DuplicateEmails, ActiveMembers, ProspectMembers, InactiveMembers)
- OrderBy (Email, Lastname, Firstname, Title, Company, Address1, Address2, City, State, Zip, Country, Phone, Mobile, Fax, Website, Gender, Birthdate, Hometown, DefaultJerseyNum, Height, Weight, ParentsName, ParentsEmail, ParentsMobile, ParentsName2, ParentsEmail2, ParentsMobile2, Bio, SkillsInterests, ForumModerator, Notes, ContactCreated, LastModified)
- OrderDirection (asc, desc)
- Page (1, 2, 3...)

Output

Success or failure. Total number of contacts matching search. For each contact found: Contact ID, firstname, lastname, email, phone and mobile.

Example Request 1

```
<SearchContactsRequest group_id='4'>
  <From>single</From>
  <Groups>
    <Group>4</Group>
  </Groups>
  <Filter>any</Filter>
  <Rules>
    <Rule>
      <Field>ID</Field>
      <Operator>contains</Operator>
```

```

        <Value>123</Value>
    </Rule>
    <Rule>
        <Field>ID</Field>
        <Operator>contains</Operator>
        <Value>124</Value>
    </Rule>
    <Rule>
        <Field>LastModified</Field>
        <Range>after</Range>
        <Date>2017/08/20</Date>
    </Rule>
    <Rule>
        <Field>ContactCreated</Field>
        <Range>between</Range>
        <Date>2017/08/20 10:00:00</Date>
        <Date2>2017/08/25 14:00:00</Date2>
    </Rule>
</Rules>
<Includes>
    <Unsubscribers>Y</Unsubscribers>
    <BouncedContacts>Y</BouncedContacts>
    <SpamComplaints>Y</SpamComplaints>
    <DuplicateEmails>Y</DuplicateEmails>
    <ActiveMembers>Y</ActiveMembers>
    <ProspectMembers>Y</ProspectMembers>
    <InactiveMembers>Y</InactiveMembers>
</Includes>
<OrderBy>ID</OrderBy>
<OrderDirection>desc</OrderDirection>
<Page>1</Page>
</SearchContactsRequest>

```

Successful Response

```

<SearchContactsResponse>
    <Result>Success</Result>
    <TotalMatchingContacts>2</TotalMatchingContacts>
    <Contacts>
        <Contact>

```

```

        <ID>124</ID>
        <Firstname>Testfirst2</Firstname>
        <Lastname>Test2</Lastname>
        <Phone>012-111-111</Phone>
        <Mobile>11111</Mobile>
        <Email>customer+test2@gmail.com</Email>
    </Contact>
    <Contact>
        <ID>123</ID>
        <Firstname>Testfirst1 & and " ' P</
Firstname>
        <Lastname>Test1 & 2</Lastname>
        <Phone>(012) 111-111</Phone>
        <Mobile>1111-1</Mobile>
        <Email>customer+test1@gmail.com</Email>
    </Contact>
</Contacts>
</SearchContactsResponse>

```

Unsubscribe Contacts

This function allows the caller to unsubscribe one or more contacts from the database.

Input

Specify search criteria within each Contact tag. Search criteria can be:

- account_id (required for shared access users)
- contact_id
- firstname
- lastname
- email
- request_id (optional)

Each contact's search criteria must return a single unique contact to unsubscribe. For shared access, include account number within the

contact tag. Caller must have contacts permissions in the account to unsubscribe contacts.

Output

For each Contact ID, success or failure.

Example Request 1

```
<UnsubscribeContactsRequest>
  <Contacts>
    <Contact contact_id="8984" request_id="a1b2c3" />
    <Contact contact_id="8983" request_id="d4e5f6" />
  </Contacts>
</UnsubscribeContactsRequest>
```

Example Request 2 (shared access)

```
<UnsubscribeContactsRequest>
  <Contacts>
    <Contact account_id="12345" contact_id="8984" />
    <Contact account_id="12346" contact_id="8983" />
  </Contacts>
</UnsubscribeContactsRequest>
```

Successful Response

```
<UnsubscribeContactsResponse>
  <Contacts>
    <Contact request_id="a1b2c3">
      <Contact_id>8984</Contact_id>
      <Result>Success</Result>
    </Contact>
    <Contact request_id="d4e5f6">
      <Contact_id>8983</Contact_id>
      <Result>Success</Result>
    </Contact>
  </Contacts>
</UnsubscribeContactsResponse>
```

Get Contact Groups

This function allows the caller to get all of the groups that a contact belongs or to get all of the groups available in the account.

Input

Contact search criteria. Search criteria can be contact_id, firstname, lastname, email. If omitted, return all groups in the account

Output

List of group IDs and names the contact belongs to or all the groups in the account

Example Request

```
<GetContactGroupsRequest contact_id="8984"></  
GetContactGroupsRequest>
```

Successful Response

```
<GetContactGroupsResponse>  
  <Result>Success</Result>  
  <ContactGroups>  
    <ContactGroup>  
      <Group_id>9902</Group_id>  
      <GroupName>My Mailing List 2</GroupName>  
    </ContactGroup>  
    <ContactGroup>  
      <Group_id>9903</Group_id>  
      <GroupName>My Mailing List 3</GroupName>  
    </ContactGroup>  
  </ContactGroups>  
</GetContactGroupsResponse>
```

Get User Defined Fields

This function allows the caller to fetch contact user-defined fields for an account.

Input

AccountID (optional - required for shared access. If missing, will be account owned by the user). To get events after a timestamp obtained earlier, pass `updated_timestamp = ("timestampvalue")`.

Output

Success or failure. For each user-defined field, Group (a group ID or "All"), UserFieldID, FieldName, FieldType, PossibleValues (a comma-delimited list), ContactEditable, UpdatedTimeStamp.

Example Request 1

```
<GetUserDefinedFieldsRequest></GetUserDefinedFieldsRequest>
```

Example Request 2 (shared access)

```
<GetUserDefinedFieldsRequest account_id="1392"></  
GetUserDefinedFieldsRequest>
```

Example Request 3

```
<GetUserDefinedFieldsRequest updated_timestamp="2012-08-01  
12:00:00"></GetUserDefinedFieldsRequest>
```

Successful Response

```
<GetUserDefinedFieldsResponse>  
  <Result>Success</Result>  
  <UserDefinedFields>  
    <UserDefinedField>  
      <Group>2</Group>  
      <UserFieldID>93</UserFieldID>  
      <FieldName>Favorite Animal</FieldName>
```

```

        <FieldType>Checkbox</FieldType>
        <PossibleValues>Dog,Cat,Monkey</PossibleValues>
        <ContactEditable>Editable</ContactEditable>
        <UpdatedTimeStamp>2012-12-06 10:52:17</
UpdatedTimeStamp>
    </UserDefinedField>
    <UserDefinedField>
        <Group>5</Group>
        <UserFieldID>154</UserFieldID>
        <FieldName>Fruits</FieldName>
        <FieldType>Select</FieldType>
        <PossibleValues>Apple,Orange,Banana</
PossibleValues>
        <ContactEditable>Visible</ContactEditable>
        <UpdatedTimeStamp>2012-12-06 14:59:29</
UpdatedTimeStamp>
    </UserDefinedField>
</UserDefinedFields>
</GetUserDefinedFieldsResponse>

```

Add User Defined Field

This function allows the caller to add a user-defined field for contacts belonging to a group, or universally for all groups in the account.

Input

Group ID to add to. Use 0 for Group ID to make the user-defined field available to all groups. Field name. Field type (Select, Checkbox, Text, or ShortText) (optional - defaults to Text). Possible values (should be separated by commas) (optional). Contact editable (Hidden, Visible, or Editable)(optional - defaults to Hidden).

Output

Success or failure. If successful, UserFieldID, AccountNumber, UpdatedTimeStamp.

Example Request 1

```
<AddUserDefinedFieldRequest group_id="9902">
  <FieldName>Fruits</FieldName>
  <FieldType>Select</FieldType>
  <PossibleValues>Orange,Apple,Banana</PossibleValues>
  <ContactEditable>Visible</ContactEditable>
</AddUserDefinedFieldRequest >
```

Example Request 2

```
<AddUserDefinedFieldRequest group_id="0">
  <FieldName>MyUserDefinedField2</FieldName>
</AddUserDefinedFieldRequest >
```

Successful Response

```
<AddUserDefinedFieldResponse>
  <Result>Success</Result>
  <UserFieldID>8</UserFieldID>
  <AccountNumber>19821</AccountNumber>
  <UpdatedTimeStamp>2012-12-09 13:23:52</
UpdatedTimeStamp>
</AddUserDefinedFieldResponse>
```

Edit User Defined Field

This function allows the caller to edit a user-defined field.

Input

Group ID to assign the user id to. Use 0 for Group ID to make the user-defined field available to all groups. Field name. Field type (Select, Checkbox, Text, or ShortText). Possible values (should be separated by commas). Contact editable (Hidden, Visible, or Editable). Field name is required to identify the field. All other parameters are optional and only need to be passed if they are going to be changed.

Output

Success or failure. If successful, UserFieldID, AccountNumber, UpdatedTimeStamp.

Example Request 1

```
<EditUserDefinedFieldRequest group_id="9902">
  <FieldName>Favorite Animal</FieldName>
  <FieldType>Checkbox</FieldType>
  <PossibleValues>Dog,Cat,Monkey</PossibleValues>
  <ContactEditable>Editable</ContactEditable>
</EditUserDefinedFieldRequest>
```

Example Request 2

```
<EditUserDefinedFieldRequest group_id="0">
  <FieldName>MyUserDefinedField2</FieldName>
</EditUserDefinedFieldRequest>
```

Successful Response

```
<EditUserDefinedFieldResponse>
  <Result>Success</Result>
  <UserFieldID>8</UserFieldID>
  <AccountNumber>19821</AccountNumber>
  <UpdatedTimeStamp>2012-12-09 13:23:52</
UpdatedTimeStamp>
</EditUserDefinedFieldResponse>
```

Delete User Defined Field

This function allows the caller to delete a user-defined field.

Input

Field name to delete.

Output

Success or failure.

Example Request

```
<DeleteUserDefinedFieldRequest>  
  <FieldName>Favorite Animal</FieldName>  
</DeleteUserDefinedFieldRequest>
```

Successful Response

```
<DeleteUserDefinedFieldResponse>  
  <Result>Success</Result>  
</DeleteUserDefinedFieldResponse>
```

Spec - CRM Activities

Table Of Contents

- Get CRM Activities
- Get CRM Activities Emails
- Get CRM Activities Website Visits
- Get All CRM Activities Emails
- Get All CRM Activities Website Visits
- Add CRM Activities
- Edit CRM Activities
- Delete CRM Activities
- Get CRM Activity Types
- Edit CRM Activity Types
- Get CRM Assignables

Get CRM Activities

This function allows the caller to retrieve CRM activities from the database. Search parameters should be specified inside the tag. CRM activities can be retrieved by activity ID, contact (ID or name), done by contact ID, group (ID or Name), or activity. Leaving all search criteria blank would return all of the CRM activities in the account. Dates and times for CRM activities are all in the account time zone set in Settings > Account.

Input

Specify search criteria within the GetCRMActivitiesRequest tag. Search criteria can be

- activity_id
- contact_id
- done_by_contact_id (to filter the activities done by the account owner, pass the value '0')
- group_id (return all CRM activities belonging to group)
- group_name
- due_date_start (YYYYMMDD)
- due_date_end(YYYYMMDD)
- done_date_start (YYYYMMDD)
- done_date_end (YYYYMMDD)
- activity
- page (integer, first page starts from 0, eg. 0/1/2/...)
- chunk_size (integer, optional, defaults to 100 if empty)
- Activities (filter by activities)
- deleted (set to true to return deleted activities only)

If no search criteria, return all CRM activities in the account.

To get CRM activities after a timestamp obtained earlier, pass `updated_timestamp="(timestampvalue)"`.

Specify `account_id` for shared access to another account.

Specify `get_all="true"` to return all CRM activities that the account has access to, including shared access. Note that when passing `get_all="true"` and `response="json"` arguments altogether, results are paginated by default and only the first 100 CRM activities will be returned. To fetch the next page, pass the 'page' parameter. To use a different result size other than the default 100, pass the 'chunk_size' parameter. Automatic pagination only applies when requesting JSON response, XML response is not paginated.

To get chunks of 250 CRM activities, specify `start_chunk_id` - an Activity ID to get all CRM activities with a greater ID up to 250 contacts. Specify `start_chunk_id = '0'` to get the first chunk.

Note: to use chunking in conjunction with get_all="true", a start_chunk_acctno must also be passed, because it is possible that CRM activities from multiple accounts will be fetched with overlapping ID numbers like start_chunk_id, start_chunk_acctno = '0' can be passed to get the first chunk.

show_assignables = 'true' can be passed to show a list of contacts assignable to the CRM activities.

Specify get_last_x_activities="(integer)" to retrieve the last 'x' amount of CRM activities. Note that 'get_last_x_activities' parameter does not work if 'get_all' parameter is passed.

Output

Success or failure. Total number of CRM Activities matching search. For each CRM activity found: Activity_id, Contact_id, Contact_firstname, Contact_lastname, Done_by_contact_id, Group_id, Group_name, Done_date, Due_date, Activity, Notes, UpdatedTimeStamp, AccountNumber.

Example Request

```
<GetCRMActivitiesRequest></GetCRMActivitiesRequest>
```

Example Request

```
<GetCRMActivitiesRequest group_name="MyTestGroup"></GetCRMActivitiesRequest>
```

Example Request

```
<GetCRMActivitiesRequest updated_timestamp="2012-01-06 14:02:34"></GetCRMActivitiesRequest>
```

Example Request (shared access)

```
<GetCRMActivitiesRequest account_id="143996"></  
GetCRMActivitiesRequest>
```

Example Request (shared access with get_all)

```
<GetCRMActivitiesRequest get_all="true"></  
GetCRMActivitiesRequest>
```

Example Request (when requesting JSON response with ‘get_all’, only the first page of 100 CRM activities from all accounts are returned)

```
<GetCRMActivitiesRequest get_all="true" response="json"></  
GetCRMActivitiesRequest>
```

Example Request (to fetch subsequent pages when requesting JSON response with ‘get_all’, pass ‘page’, first page starts at 0)

```
<GetCRMActivitiesRequest get_all="true" response="json"  
page="1"></GetCRMActivitiesRequest>
```

Example Request (to override the default 100 chunk size)

```
<GetCRMActivitiesRequest get_all="true" response="json"  
page="0" chunk_size="200"></GetCRMActivitiesRequest>
```

Example Request (shared access with get_all and chunking)

```
<GetCRMActivitiesRequest get_all="true"  
start_chunk_acctno="0" start_chunk_id="0"></  
GetCRMActivitiesRequest>
```

Example Request (get the latest 5 activities)

```
<GetCRMActivitiesRequest get_last_x_activities="5"></  
GetCRMActivitiesRequest>
```

Example Request (filter by activity)

```
<GetCRMActivitiesRequest activity="Phone Call"></  
GetCRMActivitiesRequest>
```

Example Request (filter by activities)

```

<GetCRMActivitiesRequest>
  <Activities>
    <Activity>Phone Call</Activity>
    <Activity>Left Message</Activity>
  </Activities>
</GetCRMActivitiesRequest>

```

Example Request (activities deleted after timestamp - note only activities deleted after 2023/03/24 when this feature was added are returned)

```

<GetCRMActivitiesRequest deleted="true"
updated_timestamp="2023-03-24 12:00:00"></
GetCRMActivitiesRequest>

```

Successful Response

```

<GetCRMActivitiesResponse>
  <Result>Success</Result>
  <CRMActivities>
    <CRMActivity>
      <Activity_id>23</Activity_id>
      <Contact_id>443</Contact_id>
      <Contact_firstname>Jeff</Contact_firstname>
      <Contact_lastname>Gordon</Contact_lastname>
      <Done_by_contact_id>447</Done_by_contact_id>
      <Group_id>443</Group_id>
      <Group_name>My Test Team</Group_name>
      <Date>2011-07-12 08:55:00</Date>
      <Due_date>2011-07-10 09:03:00</Due_date>
      <Activity>Meeting</Activity>
      <Notes>Had a really awesome meeting with
Jeff.</Notes>
      <UpdatedTimeStamp>2012-06-23 10:43:12</
UpdatedTimeStamp>
      <AccountNumber>91234</AccountNumber>
      <TimeZone>America/Los_Angeles</TimeZone>
      <Opportunity_id></Opportunity_id>
      <Opportunity_title></Opportunity_title>
      <Completed_by_contact_id></
Completed_by_contact_id>

```

```

        <Completed_by_firstname></
Completed_by_firstname>
        <Completed_by_lastname></Completed_by_lastname>
        <Completed_by_email></Completed_by_email>
        <Workflow_id></Workflow_id>
        <Workflow_name></Workflow_name>
        <Send_reminder_hour_before_due>Y</
Send_reminder_hour_before_due>
        <Send_reminder_24_hours_before_due>Y</
Send_reminder_24_hours_before_due>
    </CRMActivity>
    <CRMActivity>
        <Activity_id>26</Activity_id>
        <Contact_id>446</Contact_id>
        <Contact_firstname>Steve</Contact_firstname>
        <Contact_lastname>Johnson</Contact_lastname>
        <Done_by_contact_id>453</Done_by_contact_id>
        <Group_id>572</Group_id>
        <Group_name>Another Test Team</Group_name>
        <Date>2011-11-01 13:00</Date>
        <Due_date>2011-11-02 07:25</Due_date>
        <Activity>Phone Call</Activity>
        <Notes>Touched base with Steve regarding our
latest product.</Notes>
        <UpdatedTimeStamp>2012-06-23 10:43:12</
UpdatedTimeStamp>
        <AccountNumber>91234</AccountNumber>
        <TimeZone>America/Los_Angeles</TimeZone>
        <Opportunity_id></Opportunity_id>
        <Opportunity_title></Opportunity_title>
        <Completed_by_contact_id></
Completed_by_contact_id>
        <Completed_by_firstname></
Completed_by_firstname>
        <Completed_by_lastname></Completed_by_lastname>
        <Completed_by_email></Completed_by_email>
        <Workflow_id>1</Workflow_id>
        <Workflow_name>Workflow A</Workflow_name>
        <Send_reminder_hour_before_due>N</
Send_reminder_hour_before_due>

```



```
        <Send_reminder_24_hours_before_due>Y</
Send_reminder_24_hours_before_due>
    </CRMActivity>
</CRMActivities>
    <TotalMatchingActivities>2</TotalMatchingActivities>
</GetCRMActivitiesResponse>
```

Get CRM Activities Emails

This function allows the caller to retrieve CRM activities emails from the database. These would include broadcasts or other emails sent through the system, as well as queued emails for future sends.

Input

- contact_id (required).
- account_id (required if shared access, otherwise account owned by user will be searched)
- start_date (yyyy-mm-dd hh:mm:ss)
- end_date (yyyy-mm-dd hh:mm:ss)
- read_start_date (yyyy-mm-dd hh:mm:ss)
- read_end_date (yyyy-mm-dd hh:mm:ss)
- click_start_date (yyyy-mm-dd hh:mm:ss)
- click_end_date (yyyy-mm-dd hh:mm:ss)
- chunk_size
- page (0, 1, 2...)

If no parameters other than ‘contact_id’ is passed, all results for the contact will be returned.

Specify ‘account_id’ for shared access to another account.

Pass the ‘start_date’ or/and ‘end_date’ parameters to filter the results by ‘Datetime_sent’ and ‘Scheduled_for_delivery’.

Pass the 'read_start_date' or/and 'read_end_date' parameters to filter the results by 'DatetimeRead'.

Pass the 'click_start_date' or/and 'click_end_date' parameters to filter the results by 'DatetimeClicked'.

Read and click parameters can both be passed together to filter results that satisfy either one ('OR' relationship).

To paginate the results, pass the 'chunk_size' and 'page' parameters. First page starts with 0.

Output

Success or failure. AccountNumber, Contact_id. For each email sent - Broadcast_id, Message_type, Subject, Datetime_sent, Read_data, Click_data. For each broadcast queued - Broadcast_id, Subject, Scheduled_for_delivery.

Example Request 1

```
<GetCRMActivitiesEmailsRequest contact_id="3432" ></GetCRMActivitiesEmailsRequest>
```

Example Request 2 (shared access with date range)

```
<GetCRMActivitiesEmailsRequest account_id="2341" contact_id="8493" start_date="2012-01-01 00:00:00" end_date="2012-12-31 23:59:59"></GetCRMActivitiesEmailsRequest>
```

Example Request 3 (filter by read datetime)

```
<GetCRMActivitiesEmailsRequest account_id="2341" contact_id="8493" read_start_date="2018-01-01 00:00:00" read_end_date="2018-01-31 23:59:59"></GetCRMActivitiesEmailsRequest>
```

Example Request 4 (filter by click datetime)

```
<GetCRMActivitiesEmailsRequest account_id="2341"
contact_id="8493" click_start_date="2018-01-01 00:00:00"
click_end_date="2018-01-31 23:59:59"></
GetCRMActivitiesEmailsRequest>
```

Example Request 5 (filter by read datetime OR click datetime)

```
<GetCRMActivitiesEmailsRequest account_id="2341"
contact_id="8493" read_start_date="2018-01-01 00:00:00"
click_start_date="2018-01-01 00:00:00"></
GetCRMActivitiesEmailsRequest>
```

Successful Response

```
<GetCRMActivitiesEmailsResponse>
  <Result>Success</Result>
  <AccountNumber>2341</AccountNumber>
  <Contact_id>8493</Contact_id>
  <SentEmails>
    <SentEmail>
      <Broadcast_id>98403</Broadcast_id>
      <Message_type>Sent Email</Message_type>
      <Subject>Message 1</Subject>
      <Datetime_sent>2012-11-09 10:34:56</
Datetime_sent>
      <Read_data>
        <DatetimeRead>2012-11-09 13:45:45</
DatetimeRead>
        <DatetimeRead>2012-11-19 08:00:00</
DatetimeRead>
      </Read_data>
      <Click_data>
        <Click>
          <LinkClicked>http://www.mysite.com/
mylink1.html</LinkClicked>
          <DatetimeClicked>2012-11-09 13:47:08</
DatetimeClicked>
        </Click>
```

```
        <Click>
            <LinkClicked>http://www.mysite.com/
mylink2.html</LinkClicked>
            <DatetimeClicked>2012-11-19 08:10:18</
DatetimeClicked>
        </Click>
    </Click_data>
</SentEmail>
<SentEmail>
    <Broadcast_id>98434</Broadcast_id>
    <Message_type>Personal Email</Message_type>
    <Subject>Message 2</Subject>
    <Datetime_sent>2012-11-12 13:14:23</
Datetime_sent>
        <Read_data>
            <DatetimeRead>2012-11-12 13:45:45</
DatetimeRead>
                <DatetimeRead>2012-11-13 08:00:00</
DatetimeRead>
        </Read_data>
        <Click_data>
            <Click>
                <LinkClicked>http://www.mysite.com/
mylink3.html</LinkClicked>
                <DatetimeClicked>2012-11-18 13:47:08</
DatetimeClicked>
            </Click>
            <Click>
                <LinkClicked>http://www.mysite.com/
mylink4.html</LinkClicked>
                <DatetimeClicked>2012-11-19 13:48:18</
DatetimeClicked>
            </Click>
        </Click_data>
    </SentEmail>
</SentEmails>
<QueuedBroadcasts>
    <QueuedBroadcast>
        <Broadcast_id>98774</Broadcast_id>
        <Subject>Message 3</Subject>
```

```

        <Scheduled_for_delivery>2012-12-01 03:42:34</
Scheduled_for_delivery>
    </QueuedBroadcast>
    <QueuedBroadcast>
        <Broadcast_id>98798</Broadcast_id>
        <Subject>Message 4</Subject>
        <Scheduled_for_delivery>2012-12-01 04:00:00</
Schedule_for_delivery>
    </QueuedBroadcast>
</QueuedBroadcasts>
</GetCRMActivitiesEmailsResponse>

```

Get CRM Activities Website Visits

This function allows the caller to retrieve CRM activities website visits from the database.

Input

Contact_id (required). account_id required if shared access, otherwise account owned by user will be searched. start_date, end_date both optional, yy-mm-dd hh:mm:ss format.

Output

Success or failure. AccountNumber, Contact_id. For each website visit - Datetime_visited, Page_visited, Points_for_visit, Referring_page.

Example Request 1

```

<GetCRMActivitiesWebsiteVisitsRequest contact_id="3432" ></
GetCRMActivitiesWebsiteVisitsRequest>

```

Example Request 2 (shared access with date range)

```

<GetCRMActivitiesWebsiteVisitsRequest account_id="2341"
contact_id="8493" start_date="2012-01-01 00:00:00"

```

```
end_date="2012-12-31 23:59:59"></  
GetCRMActivitiesWebsiteVisitsRequest>
```

Successful Response

```
<GetCRMActivitiesWebsiteVisitsResponse>  
  <Result>Success</Result>  
  <AccountNumber>2341</AccountNumber>  
  <Contact_id>8493</Contact_id>  
  <WebsiteVisits>  
    <WebsiteVisit>  
      <Datetime_visited>2012-11-06 07:30:00</  
Datetime_visited>  
      <Page_visited>mysite.com</Page_visited>  
      <Points_for_visit>1</Points_for_visit>  
      <Referring_page>www.google.com</Referring_page>  
    </WebsiteVisit>  
  </WebsiteVisits>  
</GetCRMActivitiesWebsiteVisitsResponse>
```

Get All CRM Activities Emails

This function allows the caller to retrieve all CRM activities emails sent from the database.

Input

- account_id (required if shared access, otherwise account owned by user will be searched)
- group_id (required if shared access)
- group_name
- Contact_id
- start_date (yyyy-mm-dd hh:mm:ss)
- end_date (yyyy-mm-dd hh:mm:ss)
- read_start_date (yyyy-mm-dd hh:mm:ss)
- read_end_date (yyyy-mm-dd hh:mm:ss)
- click_start_date (yyyy-mm-dd hh:mm:ss)

- click_end_date (yyyy-mm-dd hh:mm:ss)
- chunk_size
- page (0, 1, 2...)

If no parameter is passed, all sent emails data will be returned.

Specify 'account_id' for shared access to another account. 'group_id' is required too.

Pass the 'group_id' or 'group_name' parameter to filter the results by group.

Pass an array of 'Contact_id' request tags to filter by contacts.

Pass the 'start_date' or/and 'end_date' parameters to filter the results by 'Datetime_sent'.

Pass the 'read_start_date' or/and 'read_end_date' parameters to filter the results by 'DatetimeRead'.

Pass the 'click_start_date' or/and 'click_end_date' parameters to filter the results by 'DatetimeClicked'.

To paginate the results, pass the 'chunk_size' and 'page' parameters. First page starts with 0.

Output

Success or failure. Email read and click data.

Example Request 1

```
<GetAllCRMActivitiesEmailsRequest></  
GetAllCRMActivitiesEmailsRequest>
```

Example Request 2 (For shared access users)

```
<GetAllCRMActivitiesEmailsRequest account_id="45159"
group_id="1"></GetAllCRMActivitiesEmailsRequest>
```

Example Request 3 (To filter by group)

```
<GetAllCRMActivitiesEmailsRequest group_id="1"></
GetAllCRMActivitiesEmailsRequest>
```

```
<GetAllCRMActivitiesEmailsRequest group_name="My Group"></
GetAllCRMActivitiesEmailsRequest>
```

Example Request 4 (To filter by contacts)

```
<GetAllCRMActivitiesEmailsRequest>
  <Contacts>
    <Contact_id>12</Contact_id>
  </Contacts>
</GetAllCRMActivitiesEmailsRequest>
```

```
<GetAllCRMActivitiesEmailsRequest>
  <Contacts>
    <Contact_id>12</Contact_id>
    <Contact_id>13</Contact_id>
    <Contact_id>14</Contact_id>
  </Contacts>
</GetAllCRMActivitiesEmailsRequest>
```

Example Request 5 (Pagination)

```
<GetAllCRMActivitiesEmailsRequest page="0"
chunk_size="50"></GetAllCRMActivitiesEmailsRequest>
```

```
<GetAllCRMActivitiesEmailsRequest page="1"
chunk_size="50"></GetAllCRMActivitiesEmailsRequest>
```

Example Request 6 (To filter by email sent datetime)

```
<GetAllCRMActivitiesEmailsRequest start_date="2018-01-01
00:00:00"></GetAllCRMActivitiesEmailsRequest>
```

```
<GetAllCRMActivitiesEmailsRequest end_date="2018-01-31
00:00:00"></GetAllCRMActivitiesEmailsRequest>
```



```
<GetAllCRMActivitiesEmailsRequest start_date="2018-01-01
00:00:00" end_date="2018-01-31 00:00:00"></
GetAllCRMActivitiesEmailsRequest>
```

Example Request 7 (To filter by email read datetime)

```
<GetAllCRMActivitiesEmailsRequest
read_start_date="2018-01-01 00:00:00"></
GetAllCRMActivitiesEmailsRequest>
```

```
<GetAllCRMActivitiesEmailsRequest read_end_date="2018-01-31
00:00:00"></GetAllCRMActivitiesEmailsRequest>
```

```
<GetAllCRMActivitiesEmailsRequest
read_start_date="2018-01-01 00:00:00"
read_end_date="2018-01-31 00:00:00"></
GetAllCRMActivitiesEmailsRequest>
```

Example Request 8 (To filter by email link clicked datetime)

```
<GetAllCRMActivitiesEmailsRequest
click_start_date="2018-01-01 00:00:00"></
GetAllCRMActivitiesEmailsRequest>
```

```
<GetAllCRMActivitiesEmailsRequest
click_end_date="2018-01-31 00:00:00"></
GetAllCRMActivitiesEmailsRequest>
```

```
<GetAllCRMActivitiesEmailsRequest
click_start_date="2018-01-01 00:00:00"
click_end_date="2018-01-31 00:00:00"></
GetAllCRMActivitiesEmailsRequest>
```

Successful Response

```
<GetAllCRMActivitiesEmailsResponse>
  <Result>Success</Result>
  <SentEmails>
    <SentEmail>
      <AccountNum>38193</AccountNum>
```

```
<GroupID>1</GroupID>
<GroupName>My Group</GroupName>
<Broadcast_id>698409</Broadcast_id>
<FromName>John Connor</FromName>
<FromEmail>john.connor@gmail.com</FromEmail>
<Subject>Test</Subject>
<Message_type>Sent Email</Message_type>
<DatetimeQueued>2014-08-04 12:00:00</
DatetimeQueued>
<DatetimeSent>2014-08-04 13:49:00</
DatetimeSent>
<Contacts>
  <Contact>
    <Contact_id>623</Contact_id>
    <Contact_firstname>John</
Contact_firstname>
    <Contact_lastname>Smith</
Contact_lastname>
    <Contact_email>john.smith@gmail.com</
Contact_email>
    <Read_data>
      <DatetimeRead>2014-08-04 13:50:23</
DatetimeRead>
      </Read_data>
      <Click_data>
        <Click>
          <DatetimeClicked>2017-03-21
12:56:00</DatetimeClicked>
          <LinkClicked>http://
www.mysite.com/mylink1.html</LinkClicked>
        </Click>
        <Click>
          <DatetimeClicked>2017-03-21
12:56:00</DatetimeClicked>
          <LinkClicked>http://
www.mysite.com/mylink2.html</LinkClicked>
        </Click>
      </Click_data>
    </Contact>
  </Contacts>
```

```
</SentEmail>
<SentEmail>
  <AccountNum>38193</AccountNum>
  <GroupID>1</GroupID>
  <GroupName>My Group</GroupName>
  <Broadcast_id>698411</Broadcast_id>
  <FromName>John Connor</FromName>
  <FromEmail>john.connor@gmail.com</FromEmail>
  <Subject>Test</Subject>
  <Message_type>Sent Email</Message_type>
  <DatetimeQueued>2014-08-04 12:00:00</
DatetimeQueued>
  <DatetimeSent>2014-08-04 13:52:00</
DatetimeSent>
  <Contacts>
    <Contact>
      <Contact_id>623</Contact_id>
      <Contact_firstname>John</
Contact_firstname>
      <Contact_lastname>Smith</
Contact_lastname>
      <Contact_email>john.smith@gmail.com</
Contact_email>
      <Read_data>
        <DatetimeRead>2014-08-04 13:53:40</
DatetimeRead>
      </Read_data>
      <Click_data></Click_data>
    </Contact>
  </Contacts>
</SentEmail>
<SentEmail>
  <AccountNum>38193</AccountNum>
  <GroupID>4</GroupID>
  <GroupName>Members Group</GroupName>
  <Broadcast_id>867662</Broadcast_id>
  <FromName>John Connor</FromName>
  <FromEmail>john.connor@gmail.com</FromEmail>
  <Subject>Test Subject</Subject>
  <Message_type>Sent Email</Message_type>
```

```

        <DatetimeQueued>2014-08-04 12:00:00</
DatetimeQueued>
        <DatetimeSent>2014-12-09 07:34:00</
DatetimeSent>
        <Contacts>
            <Contact>
                <Contact_id>566</Contact_id>
                <Contact_firstname>John</
Contact_firstname>
                <Contact_lastname>Smith</
Contact_lastname>
                <Contact_email>john.smith@gmail.com</
Contact_email>
                <Read_data>
                    <DatetimeRead>2014-12-29 10:13:03</
DatetimeRead>
                </Read_data>
                <Click_data></Click_data>
            </Contact>
        </Contacts>
    </SentEmail>
</SentEmails>
    <TotalSentEmails>3</TotalSentEmails>
</GetAllCRMActivitiesEmailsResponse>

```

Get All CRM Activities Website Visits

This function allows the caller to retrieve all CRM activities website visits from the database.

Input

- account_id (required if shared access, otherwise account owned by user will be searched)
- group_id (required if shared access)
- group_name
- Contact_id
- start_date (yyyy-mm-dd hh:mm:ss)

- end_date (yyyy-mm-dd hh:mm:ss)
- chunk_size
- page (0, 1, 2...)

If no parameter is passed, all website visits data will be returned.

Specify 'account_id' for shared access to another account. 'group_id' is required too.

Pass the 'group_id' or 'group_name' parameter to filter the results by group.

Pass an array of 'Contact_id' request tags to filter by contacts.

Pass the 'start_date' or/and 'end_date' parameters to filter the results by 'Datetime_visited'.

To paginate the results, pass the 'chunk_size' and 'page' parameters. First page starts with 0.

Output

Success or failure. Website visits data.

Example Request 1

```
<GetAllCRMActivitiesWebsiteVisitsRequest></GetAllCRMActivitiesWebsiteVisitsRequest>
```

Example Request 2 (For shared access users)

```
<GetAllCRMActivitiesWebsiteVisitsRequest account_id="45159" group_id="1"></GetAllCRMActivitiesWebsiteVisitsRequest>
```

Example Request 3 (To filter by group)

```
<GetAllCRMActivitiesWebsiteVisitsRequest group_id="1"></GetAllCRMActivitiesWebsiteVisitsRequest>
```

```
<GetAllCRMActivitiesWebsiteVisitsRequest group_name="My Group"></GetAllCRMActivitiesWebsiteVisitsRequest>
```

Example Request 4 (To filter by contacts)

```
<GetAllCRMActivitiesWebsiteVisitsRequest>  
  <Contacts>  
    <Contact_id>12</Contact_id>  
  </Contacts>  
</GetAllCRMActivitiesWebsiteVisitsRequest>
```

```
<GetAllCRMActivitiesWebsiteVisitsRequest>  
  <Contacts>  
    <Contact_id>12</Contact_id>  
    <Contact_id>13</Contact_id>  
    <Contact_id>14</Contact_id>  
  </Contacts>  
</GetAllCRMActivitiesWebsiteVisitsRequest>
```

Example Request 5 (Pagination)

```
<GetAllCRMActivitiesWebsiteVisitsRequest page="0"  
chunk_size="50"></GetAllCRMActivitiesWebsiteVisitsRequest>
```

```
<GetAllCRMActivitiesWebsiteVisitsRequest page="1"  
chunk_size="50"></GetAllCRMActivitiesWebsiteVisitsRequest>
```

Example Request 6 (To filter by website visited datetime)

```
<GetAllCRMActivitiesWebsiteVisitsRequest  
start_date="2018-01-01 00:00:00"></  
GetAllCRMActivitiesWebsiteVisitsRequest>
```

```
<GetAllCRMActivitiesWebsiteVisitsRequest  
end_date="2018-01-31 00:00:00"></  
GetAllCRMActivitiesWebsiteVisitsRequest>
```

```
<GetAllCRMActivitiesWebsiteVisitsRequest  
start_date="2018-01-01 00:00:00" end_date="2018-01-31  
00:00:00"></GetAllCRMActivitiesWebsiteVisitsRequest>
```

Successful Response

```
<GetAllCRMActivitiesWebsiteVisitsResponse>
  <Result>Success</Result>
  <AccountNum>38193</AccountNum>
  <WebsiteVisits>
    <WebsiteVisit>
      <Contact_id>123</Contact_id>
      <Contact_email>john.smith@gmail.com</
Contact_email>
      <Datetime_visited>2016-02-19 07:07:00</
Datetime_visited>
      <Page_visited>http://www.mysite.com/
mylink1.html</Page_visited>
      <Points_for_visit></Points_for_visit>
      <Referrer>Manually added by Workflow A</
Referrer>
    </WebsiteVisit>
    <WebsiteVisit>
      <Contact_id>123</Contact_id>
      <Contact_email>john.smith@gmail.com</
Contact_email>
      <Datetime_visited>2016-04-10 03:07:00</
Datetime_visited>
      <Page_visited>http://www.mysite.com/
mylink2.html</Page_visited>
      <Points_for_visit></Points_for_visit>
      <Referrer>Manually added by Workflow A</
Referrer>
    </WebsiteVisit>
    <WebsiteVisit>
      <Contact_id>623</Contact_id>
      <Contact_email>jane.smith@gmail.com</
Contact_email>
      <Datetime_visited>2017-03-21 17:44:00</
Datetime_visited>
      <Page_visited>http://www.mysite.com/
mylink3.html</Page_visited>
      <Points_for_visit>1</Points_for_visit>
```

```

        <Referrer></Referrer>
    </WebsiteVisit>
    <WebsiteVisit>
        <Contact_id>623</Contact_id>
        <Contact_email>jane.smith@gmail.com</
Contact_email>
        <Datetime_visited>2017-03-21 17:45:00</
Datetime_visited>
        <Page_visited>http://www.mysite.com/
mylink4.html</Page_visited>
        <Points_for_visit>1</Points_for_visit>
        <Referrer>wordpress.com</Referrer>
    </WebsiteVisit>
    <WebsiteVisit>
        <Contact_id>623</Contact_id>
        <Contact_email>jane.smith@gmail.com</
Contact_email>
        <Datetime_visited>2017-03-21 17:45:00</
Datetime_visited>
        <Page_visited>http://www.mysite.com/
mylink5.html</Page_visited>
        <Points_for_visit>1</Points_for_visit>
        <Referrer></Referrer>
    </WebsiteVisit>
</WebsiteVisits>
<TotalWebsiteVisits>47</TotalWebsiteVisits>
</GetAllCRMActivitiesWebsiteVisitsResponse>

```

Add CRM Activities

This function allows the caller to add one or more CRM Activities. Passing a Workflow_id will activate the workflow if the CRM activity is marked as complete.

Input

- account_id (required for shared access user)

- notify_assignee (optional, 'true', send a notification email to Done_by_contact_id instantly)
- request_id (optional)
- Contact_id (required)
- Group_id (required)
- Activity (required)
- Done_by_contact_id (Account owner ID assigned if omitted)
- Done_date (optional, YYYYMMDDHHMM format)
- Due_date (optional, YYYYMMDDHHMM format)
- Notes (optional)
- Opportunity_id (optional)
- Completed_by_contact_id (optional)
- Workflow_id (optional)
- Send_reminder_hour_before_due (optional, Y or N, set email reminder to be sent an hour before the due datetime)
- Send_reminder_24_hours_before_due (optional, Y or N, set email reminder to be sent a day before the due datetime)

Output

For each CRM Activity ID, success or failure.

Example Request

```
<AddCRMActivitiesRequest>
  <CRMActivities>
    <CRMActivity request_id="a1b2c3">
      <Contact_id>37</Contact_id>
      <Done_by_contact_id>39</Done_by_contact_id>
      <Group_id>3</Group_id>
      <Due_date>201109011100</Due_date>
      <Activity>Meeting</Activity>
      <Notes>Meet with George regarding contracts.</
Notes>
      <Opportunity_id></Opportunity_id>
      <Completed_by_contact_id>0</
Completed_by_contact_id>
```

```

        <Workflow_id>7</Workflow_id>
        <Send_reminder_hour_before_due>Y</
Send_reminder_hour_before_due>
        <Send_reminder_24_hours_before_due>Y</
Send_reminder_24_hours_before_due>
    </CRMActivity>
    <CRMActivity request_id="d4e5f6">
        <Contact_id>32</Contact_id>
        <Group_id>4</Group_id>
        <Activity>Phone Call</Activity>
        <Opportunity_id></Opportunity_id>
        <Completed_by_contact_id>0</
Completed_by_contact_id>
    </CRMActivity>
</CRMActivities>
</AddCRMActivitiesRequest>

```

Example Request (Shared Access)

```

<AddCRMActivitiesRequest>
    <CRMActivities>
        <CRMActivity account_id="91234">
            <Contact_id>37</Contact_id>
            <Done_by_contact_id>39</Done_by_contact_id>
            <Group_id>3</Group_id>
            <Due_date>201109011100</Due_date>
            <Activity>Meeting</Activity>
            <Notes>Meet with George regarding contracts.</
Notes>
            <Send_reminder_hour_before_due>Y</
Send_reminder_hour_before_due>
            <Send_reminder_24_hours_before_due>Y</
Send_reminder_24_hours_before_due>
        </CRMActivity>
        <CRMActivity account_id="91234">
            <Contact_id>32</Contact_id>
            <Group_id>4</Group_id>
            <Activity>Phone Call</Activity>
        </CRMActivity>
    </CRMActivities>

```

</AddCRMActivitiesRequest>

Example Request (send email notification to assignee #39)

<AddCRMActivitiesRequest>

<CRMActivities>

<CRMActivity notify_assignee="true">

<Contact_id>37</Contact_id>

<Done_by_contact_id>39</Done_by_contact_id>

<Group_id>3</Group_id>

<Due_date>201109011100</Due_date>

<Activity>Meeting</Activity>

<Notes>Meet with George regarding contracts.</

Notes>

<Opportunity_id></Opportunity_id>

<Completed_by_contact_id>0</

Completed_by_contact_id>

<Workflow_id>7</Workflow_id>

<Send_reminder_hour_before_due>Y</

Send_reminder_hour_before_due>

<Send_reminder_24_hours_before_due>Y</

Send_reminder_24_hours_before_due>

</CRMActivity>

<CRMActivity>

<Contact_id>32</Contact_id>

<Group_id>4</Group_id>

<Activity>Phone Call</Activity>

<Opportunity_id></Opportunity_id>

<Completed_by_contact_id>0</

Completed_by_contact_id>

</CRMActivity>

</CRMActivities>

</AddCRMActivitiesRequest>

Successful Response

<AddCRMActivitiesResponse>

<CRMActivities>

<CRMActivity request_id="a1b2c3">

<Activity_id>21</Activity_id>

<Result>Success</Result>

```
        <AccountNumber>91234</AccountNumber>
        <UpdatedTimeStamp>2012-08-30 14:24:09</
UpdatedTimeStamp>
    </CRMActivity>
    <CRMActivity request_id="d4e5f6">
        <Activity_id>22</Activity_id>
        <Result>Success</Result>
        <AccountNumber>91234</AccountNumber>
        <UpdatedTimeStamp>2012-08-30 14:24:09</
UpdatedTimeStamp>
    </CRMActivity>
</CRMActivities>
</AddCRMActivitiesResponse>
```

Edit CRM Activities

This function allows the caller to modify one or more CRM activities already in the database. Search parameters should be specified inside the tag, while parameters to change to would be specified individually. Passing a Workflow_id will activate the workflow if the CRM activity is marked as complete.

Input

Specify search criteria within each CRMActivity tag. Each activity's search criteria must return a single unique activity to modify.

Search criteria can be:

- activity_id
- contact_id
- contact_firstname
- contact_lastname
- done_by_contact_id
- activity
- request_id (optional)

Parameters to change can include:

- account_id (required for shared access user)
- Contact_id
- Group_id
- Activity
- Done_by_contact_id
- Done_date (YYYYMMDDHHMM format)
- Due_date (YYYYMMDDHHMM format)
- Notes
- Opportunity_id
- Completed_by_contact_id
- Workflow_id
- Send_reminder_hour_before_due (Y or N, set email reminder to be sent an hour before the due datetime)
- Send_reminder_24_hours_before_due (Y or N, set email reminder to be sent a day before the due datetime)

Output

For each CRM Activity ID, success or failure

Example Request

```
<EditCRMActivitiesRequest>
  <CRMActivities>
    <CRMActivity activity_id="47" request_id="a1b2c3">
      <Contact_id>33</Contact_id>
      <Done_by_contact_id>29</Done_by_contact_id>
      <Group_id>2</Group_id>
      <Done_date>201110210830</Done_date>
      <Due_date>201110231430</Due_date>
      <Activity>Meeting</Activity>
      <Notes>Meet with Jeff regarding next tasks.</
Notes>
      <Opportunity_id></Opportunity_id>
```

```

        <Completed_by_contact_id>0</
Completed_by_contact_id>
        <Workflow_id>7</Workflow_id>
        <Send_reminder_hour_before_due>Y</
Send_reminder_hour_before_due>
        <Send_reminder_24_hours_before_due>Y</
Send_reminder_24_hours_before_due>
        </CRMActivity>
        <CRMActivity contact_firstname="Joey"
contact_lastname="Patrick" activity="Meeting"
request_id="d4e5f6">
        <Activity>Phone Call</Activity>
        </CRMActivity>
    </CRMActivities>
</EditCRMActivitiesRequest>

```

Example Request (Shared Access)

```

<EditCRMActivitiesRequest>
    <CRMActivities>
        <CRMActivity activity_id="47" account_id="91234">
            <Contact_id>33</Contact_id>
            <Done_by_contact_id>29</Done_by_contact_id>
            <Group_id>2</Group_id>
            <Done_date>201110210830</Done_date>
            <Due_date>201110231430</Due_date>
            <Activity>Meeting</Activity>
            <Notes>Meet with Jeff regarding next tasks.</

```

Notes>

```

        </CRMActivity>
        <CRMActivity contact_firstname="Joey"
contact_lastname="Patrick" activity="Meeting"
account_id="91234">
            <Activity>Phone Call</Activity>
        </CRMActivity>
    </CRMActivities>
</EditCRMActivitiesRequest>

```

Successful Response

```

<EditCRMActivitiesResponse>

```

```
<CRMActivities>
  <CRMActivity request_id="a1b2c3">
    <Activity_id>47</Activity_id>
    <Result>Success</Result>
    <AccountNumber>91234</AccountNumber>
    <UpdatedTimeStamp>2012-08-30 14:24:09</
UpdatedTimeStamp>
  </CRMActivity>
  <CRMActivity request_id="d4e5f6">
    <Activity_id>28</Activity_id>
    <Result>Success</Result>
    <AccountNumber>91234</AccountNumber>
    <UpdatedTimeStamp>2012-08-30 14:24:09</
UpdatedTimeStamp>
  </CRMActivity>
</CRMActivities>
</EditCRMActivitiesResponse>
```

Delete CRM Activities

This function allows the caller to delete one or more CRM Activities from the database.

Input

Specify search criteria within each CRMActivity tag. Search criteria can be:

- activity_id
- contact_id
- contact_firstname
- contact_lastname
- done_by_contact_id
- activity
- request_id (optional)

Each activity's search criteria must return a single unique activity to delete.

Output

For each CRM Activity ID, success or failure.

Example Request

```
<DeleteCRMActivitiesRequest>
  <CRMActivities>
    <CRMActivity activity_id="45" request_id="a1b2c3" /
  >
    <CRMActivity activity_id="25" request_id="d4e5f6" /
  >
  </CRMActivities>
</DeleteCRMActivitiesRequest>
```

Successful Response

```
<DeleteCRMActivitiesResponse>
  <CRMActivities>
    <CRMActivity request_id="a1b2c3">
      <Activity_id>45</Activity_id>
      <Result>Success</Result>
    </CRMActivity>
    <CRMActivity request_id="d4e5f6">
      <Activity_id>25</Activity_id>
      <Result>Success</Result>
    </CRMActivity>
  </CRMActivities>
</DeleteCRMActivitiesResponse>
```

Get CRM Activity Types

This function allows the caller to retrieve valid CRM Activity Types for an account.

Input

Account ID (optional - required for shared access. If missing, will be account owned by the user). Pass get_all=true to get CRM Activity Types for all accounts for which the user has contacts permissions.

Output

Success or failure. On success, a list of valid CRM Activity Types for the account.

Example Request 1

```
<GetCRMActivityTypesRequest></GetCRMActivityTypesRequest>
```

Example Request 2 (shared access)

```
<GetCRMActivityTypesRequest account_id="1392"></  
GetCRMActivityTypesRequest>
```

Example Request 2 (get all)

```
<GetCRMActivityTypesRequest get_all="true"></  
GetCRMActivityTypesRequest>
```

Successful Response

```
<GetCRMActivityTypesResponse>  
  <Result>Success</Result>  
  <CRMActivityTypes>  
    <CRMActivityType>  
      <AccountNumber>1392</AccountNumber>  
      <Label>Make Note</Label>  
    </CRMActivityType>  
    <CRMActivityType>  
      <AccountNumber>1392</AccountNumber>  
      <Label>Phone Call</Label>  
    </CRMActivityType>  
    <CRMActivityType>  
      <AccountNumber>1392</AccountNumber>  
      <Label>Left Message</Label>
```

```

    </CRMActivityType>
    <CRMActivityType>
        <AccountNumber>1392</AccountNumber>
        <Label>Sent SMS</Label>
    </CRMActivityType>
    <CRMActivityType>
        <AccountNumber>1392</AccountNumber>
        <Label>Meeting</Label>
    </CRMActivityType>
    <CRMActivityType>
        <AccountNumber>1392</AccountNumber>
        <Label>Received Email</Label>
    </CRMActivityType>
</CRMActivityTypes>
</GetCRMActivityTypesResponse>

```

Edit CRM Activity Types

This function allows the caller to edit the current existing CRM Activity Types by adding new activity types or replacing the whole existing copy.

When replace="true" argument is passed, the existing list of activity types will be fully replaced.

When replace="false" argument is passed or absent, the new <CRMActivityTypes> will be added to the end of the activity types list instead.

To reorder the activity types list, fetch the existing activity types list using the GetCRMActivityTypesRequest API and order accordingly, then submit the new order with EditCRMActivityTypesRequest plus the replace="true" argument.

When an activity type is removed, it does not change existing CRM activities. Those remain as their original activity type.

Only account owner has permission to edit the activity types of the account.

Input

- replace (true/false)
- Label (comma is a delimiter and usage is prohibited)

Output

Success or failure. Account number.

Example Request (add new activity types to the end of the current existing list)

```
<EditCRMActivityTypesRequest>
  <CRMActivityTypes>
    <CRMActivityType>
      <Label>New Activity A</Label>
    </CRMActivityType>
    <CRMActivityType>
      <Label>New Activity B</Label>
    </CRMActivityType>
  </CRMActivityTypes>
</EditCRMActivityTypesRequest>
```

Example Request (fully replace existing activity types)

```
<EditCRMActivityTypesRequest replace="true">
  <CRMActivityTypes>
    <CRMActivityType>
      <Label>Make Note</Label>
    </CRMActivityType>
    <CRMActivityType>
      <Label>Phone Call</Label>
    </CRMActivityType>
    <CRMActivityType>
      <Label>Left Message</Label>
    </CRMActivityType>
  </CRMActivityTypes>
</EditCRMActivityTypesRequest>
```

```

    <CRMActivityType>
      <Label>Sent SMS</Label>
    </CRMActivityType>
    <CRMActivityType>
      <Label>Meeting</Label>
    </CRMActivityType>
    <CRMActivityType>
      <Label>Received Email</Label>
    </CRMActivityType>
    <CRMActivityType>
      <Label>Sent Email</Label>
    </CRMActivityType>
    <CRMActivityType>
      <Label>Sent Mail</Label>
    </CRMActivityType>
    <CRMActivityType>
      <Label>Signup Form</Label>
    </CRMActivityType>
    <CRMActivityType>
      <Label>Follow-Up</Label>
    </CRMActivityType>
    <CRMActivityType>
      <Label>Presentation</Label>
    </CRMActivityType>
  </CRMActivityTypes>
</EditCRMActivityTypesRequest>

```

Successful Response

```

<EditCRMActivityTypesResponse>
  <Result>Success</Result>
  <AccountNumber>3819</AccountNumber>
</EditCRMActivityTypesResponse>

```

Get CRM Assignables

This function allows the caller to retrieve a list of contacts assignable to a contact's CRM Activities.

Input

- account_id
- contact_id

Output

Success or failure. On success, a list of contacts assignable.

Example Request

```
<GetCRMAssignablesRequest contact_id="123"></GetCRMAssignablesRequest>
```

Successful Response

```
<GetCRMAssignablesResponse>  
  <Result>Success</Result>  
  <AssignableContacts>  
    <AssignableContact>  
      <ContactID>0</ContactID>  
      <Name>Todd Wade</Name>  
      <Email></Email>  
    </AssignableContact>  
  </AssignableContacts>  
</GetCRMAssignablesResponse>
```

Spec - Custom Objects

Table Of Contents

- Get Custom Object Definitions List
- Get Object Definition
- List Custom Objects
- Create New Custom Object
- Update Custom Object
- Delete Custom Object

Get Custom Object Definitions List

This API retrieves the list of custom object definitions under the user account. This only returns a summary for each custom object definitions. To get the full definition for each custom object definitions use the `GetObjectDefinitionRequest` API below.

Input

- `account_id` (required for shared access users)
- `group_id` (required for shared access users)

Output

Success or failure. List of custom object definitions under the user account.

- `MaxObjectsPerEntity` (0 = unlimited)

Example Request

```
<GetCustomObjectDefinitionsListRequest/>
```

Example Request (Shared Access)

```
<GetCustomObjectDefinitionsListRequest account_id="12345"  
group_id="1"/>
```

Example Response

```
<GetCustomObjectDefinitionsListResponse>  
  <Result>Success</Result>  
  <CustomObjectDefinitions>  
    <CustomObjectDefinition>  
      <ObjectDefinitionID>1</ObjectDefinitionID>  
      <ObjectName>Test Object</ObjectName>  
      <MaxObjectsPerEntity>0</MaxObjectsPerEntity>  
    </CustomObjectDefinition>  
    <CustomObjectDefinition>  
      <ObjectDefinitionID>2</ObjectDefinitionID>  
      <ObjectName>Test Object 2</ObjectName>  
      <MaxObjectsPerEntity>5</MaxObjectsPerEntity>  
    </CustomObjectDefinition>  
  </CustomObjectDefinitions>  
</GetCustomObjectDefinitionsListResponse>
```

Get Object Definition

This API retrieves the full definition along with the attributes for a custom object definition under the user account. Use the DefinitionJSON as a schema on how generate the input for CreateNewCustomObjectRequest and UpdateCustomObjectRequest.

Input

- account_id (required for shared access users)
- group_id (required for shared access users)
- object_definition_id (required)

Output

Success or failure. Returns the object definition for the specified custom object.

- MaxObjectsPerEntity (0 = unlimited)

Example Request

```
<GetObjectDefinitionRequest object_definition_id="1"/>
```

Example Request (Shared Access)

```
<GetObjectDefinitionRequest account_id="12345" group_id="1"
object_definition_id="1"/>
```

Example Response

```
<GetObjectDefinitionResponse>
  <Result>Success</Result>
  <ObjectDefinition>
    <ObjectDefinitionID>1</ObjectDefinitionID>
    <EntityAttachments>
      <EntityAttachment>Company</EntityAttachment>
      <EntityAttachment>Contact</EntityAttachment>
    </EntityAttachments>
    <DefinitionJSON>
      <Name>Test Object</Name>
      <SortByAttribute>Text Attribute</
SortByAttribute>
      <SortDirection>asc</SortDirection>
      <MaxObjectsPerEntity>0</MaxObjectsPerEntity>
      <Description>This is a description of the test
object</Description>
      <Attributes>
        <Attribute>
          <ShowOnInitialLoad>No</
ShowOnInitialLoad>
          <PseudoName>attr1</PseudoName>
          <MaxLength></MaxLength>
          <Name>Text Attribute</Name>
          <Default></Default>
          <Type>text</Type>
```



```
        <Placeholder></Placeholder>
      </Attribute>
    </Attributes>
  </DefinitionJSON>
</ObjectDefinition>
</GetObjectDefinitionResponse>
```

List Custom Objects

This API retrieves the list of custom objects for an entity (contact/company).

Input

- account_id (required for shared access users)
- group_id (required for shared access users)
- entity (required, [Contact/Company] + [ContactID/CompanyID], eg. Contact123, Company123)

Output

Success or failure. List of custom objects for an entity specified. The DefinitionJSON is the definition for ObjectJSON data for the entity.

For image type and file type attributes, the data are returned in Base64 Data URI format.

Example Request (Contact entity)

```
<ListCustomObjectsRequest entity="Contact123"/>
```

Example Request (Company entity)

```
<ListCustomObjectsRequest entity="Company123"/>
```

Example Request (Shared Access)

```
<ListCustomObjectsRequest account_id="12345" group_id="1"
entity="Contact123"/>
```

Example Response

```
<ListCustomObjectsResponse>
  <Result>Success</Result>
  <CustomObjects>
    <CustomObject>
      <ObjectID>1</ObjectID>
      <ObjectName>Test Object</ObjectName>
      <ObjectJSON>
        <Object>
          <PseudoName>attr1</PseudoName>
          <AttributeValue>text attribute value</
AttributeValue>
        </Object>
        <Object>
          <PseudoName>attr2</PseudoName>
          <AttributeValue>1</AttributeValue>
          <MimeType>image/png</MimeType>
          <ImageBase64>...</ImageBase64>
        </Object>
        <Object>
          <PseudoName>attr3</PseudoName>
          <AttributeValue>2</AttributeValue>
          <MimeType>text/plain</MimeType>
          <FileBase64>data:text/
plain;base64,dGhlIHFlaWNrIGJyb3duIGZveCBqdWlwcYBvd mVyIHRobzS
BsYXp5IGRvZw==</FileBase64>
        </Object>
      </ObjectJSON>
      <ObjectDefinitionID>1</ObjectDefinitionID>
      <DefinitionJSON>
        <Name>Test Object</Name>
        <SortByAttribute>Text Attribute</
SortByAttribute>
        <SortDirection>asc</SortDirection>
```

```

        <MaxObjectsPerEntity>0</
MaxObjectsPerEntity>
        <Description>This is a description of the
test object</Description>
        <Attributes>
            <Attribute>
                <ShowOnInitialLoad>No</
ShowOnInitialLoad>
                <PseudoName>attr1</PseudoName>
                <MaxLength></MaxLength>
                <Name>Text Attribute</Name>
                <Default></Default>
                <Type>text</Type>
                <Placeholder></Placeholder>
            </Attribute>
            <Attribute>
                <ShowOnInitialLoad>No</
ShowOnInitialLoad>
                <PseudoName>attr2</PseudoName>
                <MaxLength></MaxLength>
                <Name>Image Attribute</Name>
                <Default></Default>
                <Type>image</Type>
                <Placeholder></Placeholder>
            </Attribute>
            <Attribute>
                <ShowOnInitialLoad>No</
ShowOnInitialLoad>
                <PseudoName>attr3</PseudoName>
                <MaxLength></MaxLength>
                <Name>File Attribute</Name>
                <Default></Default>
                <Type>file</Type>
                <Placeholder></Placeholder>
            </Attribute>
        </Attributes>
    </DefinitionJSON>
</CustomObject>
</CustomObjects>
</ListCustomObjectsResponse>

```

Create New Custom Object

This API call adds a new custom object for an entity.

Input

- account_id (required for shared access users)
- group_id (required for shared access users)
- object_definition_id (required)
- entity (required, [Contact/Company] + [ContactID/CompanyID], eg. Contact123, Company123)
- ObjectJSON (required)
 - PseudoName (the input data must match the <PseudoName> data from ListCustomObjectsResponse)
 - AttributeValue ('|' delimited list of options if attribute type is 'set' or 'enum'. For attributes that are image type or file type, the attribute value must be in Base64 Data URI format.)

Output

Success or failure.

Example Request

```
<CreateNewCustomObjectRequest object_definition_id="1"
entity="Contact623">
  <ObjectJSON>
    <Object>
      <PseudoName>attr1</PseudoName>
      <AttributeValue>the quick brown fox</
AttributeValue>
    </Object>
    <Object>
      <PseudoName>attr2</PseudoName>
      <AttributeValue>1|2|3|4</AttributeValue>
    </Object>
```

```

    <Object>
      <PseudoName>attr3</PseudoName>
      <AttributeValue>...</AttributeValue>
    </Object>
    <Object>
      <PseudoName>attr4</PseudoName>
      <AttributeValue>data:text/
plain;base64,dGhlIHFlaWNrIGJyb3duIGZveCBqdWlwcyBvdmVyIHRoZS
BsYXp5IGRvZw==</AttributeValue>
    </Object>
  </ObjectJSON>
</CreateNewCustomObjectRequest>

```

Example Request (Shared Access)

```

<CreateNewCustomObjectRequest account_id="12345"
group_id="1" object_definition_id="1" entity="Contact623">
  <ObjectJSON>
    <Object>
      <PseudoName>attr1</PseudoName>
      <AttributeValue>the quick brown fox</
AttributeValue>
    </Object>
    <Object>
      <PseudoName>attr2</PseudoName>
      <AttributeValue>1|2|3|4</AttributeValue>
    </Object>
  </ObjectJSON>
</CreateNewCustomObjectRequest>

```

Example Response

```

<CreateNewCustomObjectResponse>
  <Result>Success</Result>
  <ObjectID>1</ObjectID>
  <ObjectDefinitionID>1</ObjectDefinitionID>
  <Entity>Contact623</Entity>
</CreateNewCustomObjectResponse>

```

Update Custom Object

This API call updates an existing custom object for an entity.

Input

- account_id (required for shared access users)
- group_id (required for shared access users)
- object_id (required)
- entity (required, [Contact/Company] + [ContactID/CompanyID], eg. Contact123, Company123)
- ObjectJSON (required)
 - PseudoName (the input data must match the <PseudoName> data from ListCustomObjectsResponse)
 - AttributeValue ('|' delimited list of options if attribute type is 'set' or 'enum'. For attributes that are image type or file type, the attribute value must be in Base64 Data URI format.)

Output

Success or failure.

Example Request

```
<UpdateCustomObjectRequest object_id="1"
entity="Contact123">
  <ObjectJSON>
    <Object>
      <PseudoName>attr1</PseudoName>
      <AttributeValue>the quick brown fox</
AttributeValue>
    </Object>
    <Object>
      <PseudoName>attr2</PseudoName>
      <AttributeValue>1|2|3|4</AttributeValue>
    </Object>
    <Object>
      <PseudoName>attr3</PseudoName>
```

```

        <AttributeValue>...</AttributeValue>
    </Object>
    <Object>
        <PseudoName>attr4</PseudoName>
        <AttributeValue>data:text/
plain;base64,dGhlIHFlaWNrIGJyb3duIGZveCBqdWlwcyBvdmVyIHRoZS
BsYXp5IGRvZw==</AttributeValue>
    </Object>
</ObjectJSON>
</UpdateCustomObjectRequest>

```

Example Request (Shared Access)

```

<UpdateCustomObjectRequest account_id="12345" group_id="1"
object_id="1" entity="Contact123">
    <ObjectJSON>
        <Object>
            <PseudoName>attr1</PseudoName>
            <AttributeValue>the quick brown fox</
AttributeValue>
        </Object>
        <Object>
            <PseudoName>attr2</PseudoName>
            <AttributeValue>1|2|3|4</AttributeValue>
        </Object>
    </ObjectJSON>
</UpdateCustomObjectRequest>

```

Example Response

```

<UpdateCustomObjectResponse>
    <Result>Success</Result>
    <ObjectID>1</ObjectID>
    <Entity>Contact123</Entity>
</UpdateCustomObjectResponse>

```

Delete Custom Object

This API call removes a custom object for an entity.

Input

- account_id (required for shared access users)
- group_id (required for shared access users)
- object_id (required)
- entity (required, [Contact/Company] + [ContactID/CompanyID], eg. Contact123, Company123)

Output

Success or failure.

Example Request

```
<DeleteCustomObjectRequest object_id="1"
entity="Contact123"/>
```

Example Request (Shared Access)

```
<DeleteCustomObjectRequest account_id="12345" group_id="1"
object_id="1" entity="Contact123"/>
```

Example Response

```
<DeleteCustomObjectResponse>
  <Result>Success</Result>
  <ObjectID>1</ObjectID>
  <Entity>Contact123</Entity>
</DeleteCustomObjectResponse>
```


Spec - Events

Table Of Contents

- List Events
- Add New Event
- Modify Existing Event
- Delete Events
- Get Event Types
- Update Attendees Attendance
- Get Event Locations
- Add Event Location
- Edit Event Location
- Delete Event Location
- Get Events And CRM Activities
- Get Event Contacts Attending
- Get Event Contacts Not Attending
- Get Event Contacts Unsure
- Get Event Contacts Not Yet Responded

List Events

This function allows the caller to list events for a period of time for a specified group or all groups.

Input

Group ID (if omitted, show events from all groups), Event ID (if omitted, show all events that meet criteria), Show Attendees (Y or N), Max Records, Start Date (YYYYMMDD), and/or End Date(YYYYMMDD).

If neither Start Date nor End Date is specified, return requested amount of future events, sorted ascending by Start Date and Time. If the Max Records is not specified, the function will return all of the records meeting the criteria specified.

To get events after a timestamp obtained earlier, pass `updated_timestamp = ("timestampvalue")`.

Specify `get_all="true"` to return all events from the account the user owns, plus events from any groups in other accounts of which the user is a member., To request events from an account that the user is a member of, specify `account_id = (AccountID)`

Output

List of Events or Failure Message

Example Request

```
<GetEventsRequest></GetEventsRequest>
```

Example Request (filter by event ID)

```
<GetEventsRequest>  
  <EventID>20</EventID>  
</GetEventsRequest>
```

Example Request (show attendees, filter by group)

```
<GetEventsRequest>  
  <GroupID>1</GroupID>  
  <ShowAttendees>Y</ShowAttendees>  
</GetEventsRequest>
```

Example Request (filter by date range and max records)

```
<GetEventsRequest>  
  <StartDate>20090105</StartDate>
```

```
<EndDate>20090626</EndDate>
<MaxRecords>2</MaxRecords>
</GetEventsRequest>
```

Example Request (filter by updated timestamp)

```
<GetEventsRequest updated_timestamp="2012-08-01
12:00:00"></GetEventsRequest>
```

Example Request (get all)

```
<GetEventsRequest get_all="true"></GetEventsRequest>
```

Example Request (shared access)

```
<GetEventsRequest account_id="12345"></GetEventsRequest>
```

Example Response

```
<GetEventsResponse>
  <Response>Success</Response>
  <Event>
    <EventID>17</EventID>
    <ChargeNoShows>N</ChargeNoShows>
    <Date>20090105</Date>
    <EndDate>20090105</EndDate>
    <EndTime>2100</EndTime>
    <EventFee>0.00</EventFee>
    <EventType>Party</EventType>
    <FacilityName>Dan's House</FacilityName>
    <GroupID>1</GroupID>
    <GroupName>My Group Name 1</GroupName>
    <LocationID>223</LocationID>
    <Notes>This is a note 1</Notes>
    <PublicEvent>N</PublicEvent>
    <StartTime>1700</StartTime>
    <AccountNumber>11055</AccountNumber>
    <UpdatedTimeStamp>2012-08-21 11:19:33</
UpdatedTimeStamp>
    <StartDateTime>2009-01-05 17:00:00</StartDateTime>
    <EndDateTime>2009-01-05 21:00:00</EndDateTime>
```

```
<AppointmentOpportunityID>359</
AppointmentOpportunityID>
  <AppointmentOpportunityCloseDateLinked>Y</
AppointmentOpportunityCloseDateLinked>
    <AppointmentDoneWorkflowID>51</
AppointmentDoneWorkflowID>
      <AppointmentDoneWorkflowActivated>2025-11-01
01:23:45</AppointmentDoneWorkflowActivated>
    </Event>
    <Event>
      <EventID>18</EventID>
      <ChargeNoShows>N</ChargeNoShows>
      <Date>20090626</Date>
      <EndDate>20090626</EndDate>
      <EndTime>1500</EndTime>
      <EventFee>0.00</EventFee>
      <EventType>Meeting</EventType>
      <FacilityAddress>999 Washington Dr.</
FacilityAddress>
        <FacilityCity>Naperville</FacilityCity>
        <FacilityCountry>USA</FacilityCountry>
        <FacilityName>Test Location</FacilityName>
        <FacilityState>IL</FacilityState>
        <FacilityZip>60565</FacilityZip>
        <GroupID>1</GroupID>
        <GroupName>My Group Name 1</Group Name>
        <LocationID>229</LocationID>
        <Notes>This is a note 2</Notes>
        <PublicEvent>N</PublicEvent>
        <StartTime>1400</StartTime>
        <AccountNumber>12655</AccountNumber>
        <UpdatedTimeStamp>2012-08-13 11:19:33</
UpdatedTimeStamp>
          <StartDateTime>2009-06-26 14:00:00</StartDateTime>
          <EndDateTime>2009-06-26 15:00:00</EndDateTime>
          <AppointmentOpportunityID>0</
AppointmentOpportunityID>
            <AppointmentOpportunityCloseDateLinked>N</
AppointmentOpportunityCloseDateLinked>
```

```
        <AppointmentDoneWorkflowID>0</
AppointmentDoneWorkflowID>
    </Event>
</GetEventsResponse>
```

Example Response (show attendees)

```
<GetEventsResponse>
  <Response>Success</Response>
  <Event>
    <EventID>1</EventID>
    <Attendees>
      <Attendee>jgordon@yahoo.com</Attendee>
      <Attendee>sjohnson@gmail.com</Attendee>
    </Attendees>
    <ChargeNoShows>N</ChargeNoShows>
    <Date>20090105</Date>
    <EndDate>20090105</EndDate>
    <EndTime>2100</EndTime>
    <EventFee>0.00</EventFee>
    <EventType>Party</EventType>
    <FacilityName>Dan's House</FacilityName>
    <GroupID>1</GroupID>
    <GroupName>My Group Name 1</GroupName>
    <LocationID>203</LocationID>
    <Notes>This is a note 1</Notes>
    <PublicEvent>N</PublicEvent>
    <StartTime>1700</StartTime>
    <AccountNumber>12655</AccountNumber>
    <UpdatedTimeStamp>2009-01-05 12:19:33</
UpdatedTimeStamp>
    <StartDateTime>2009-01-05 17:00:00</StartDateTime>
    <EndDateTime>2009-01-05 21:00:00</EndDateTime>
    <AppointmentOpportunityID>0</
AppointmentOpportunityID>
    <AppointmentOpportunityCloseDateLinked>N</
AppointmentOpportunityCloseDateLinked>
    <AppointmentDoneWorkflowID>0</
AppointmentDoneWorkflowID>
  </Event>
```

```
<Event>
  <EventID>2</EventID>
  <Attendees>
    <Attendee>jgordon@yahoo.com</Attendee>
    <Attendee>sjohnson@gmail.com</Attendee>
    <Attendee>rstevens@aol.com</Attendee>
  </Attendees>
  <ChargeNoShows>N</ChargeNoShows>
  <CheckIns>
    <CheckIn>jgordon@yahoo.com</CheckIn>
    <Checkin>kwatson@gmail.com</CheckIn>
    <CheckIn>lgoldburg@aol.com</CheckIn>
  </CheckIns>
  <Date>20090626</Date>
  <EndDate>20090626</EndDate>
  <EndTime>1500</EndTime>
  <EventFee>0.00</EventFee>
  <EventType>Meeting</EventType>
  <FacilityAddress>999 WashingtonDrive</
FacilityAddress>
  <FacilityCity>Naperville</FacilityCity>
  <FacilityCountry>USA</FacilityCountry>
  <FacilityName>Test Location</FacilityName>
  <FacilityState>IL</FacilityState>
  <FacilityZip>60565</FacilityZip>
  <GroupID>1</GroupID>
  <GroupName>My Group Name 1</GroupName>
  <LocationID>22</LocationID>
  <NoShows>
    <NoShow>jsimpson@gmail.com</NoShow>
    <NoShow>sjones@gmail.com</NoShow>
  </NoShows>
  <Notes>This is a note 2</Notes>
  <PublicEvent>N</PublicEvent>
  <StartTime>1400</StartTime>
  <Unsure>
    <Unsure>tthompson@aol.com</Unsure>
    <Unsure>ajefferson@hotmail.com</Unsure>
  </Unsure>
  <AccountNumber>12655</AccountNumber>
```

```

    <UpdatedTimeStamp>2012-08-22 02:01:13</
UpdatedTimeStamp>
    <StartDateTime>2009-06-26 14:00:00</StartDateTime>
    <EndDateTime>2009-06-26 15:00:00</EndDateTime>
    <AppointmentOpportunityID>0</
AppointmentOpportunityID>
    <AppointmentOpportunityCloseDateLinked>N</
AppointmentOpportunityCloseDateLinked>
    <AppointmentDoneWorkflowID>0</
AppointmentDoneWorkflowID>
</Event>
<Event>
    <EventID>3</EventID>
    <Attendees>
        <Attendee>sjohnson@gmail.com</Attendee>
        <Attendee>rstevens@aol.com</Attendee>
    </Attendees>
    <ChargeNoShows></ChargeNoShows>
    <Date>20090422</Date>
    <EndDate>20090422</EndDate>
    <EndTime>1700</EndTime>
    <EventFee>0.00</EventFee>
    <EventTitle>Another Test Event</EventTitle>
    <EventType>Meeting</EventType>
    <FacilityName>Dan's House</FacilityName>
    <GroupID>1</GroupID>
    <GroupName>My Group Name 1>
    <Notes>This is a note 3</Notes>
    <PublicEvent></PublicEvent>
    <StartTime>1600</StartTime>
    <AccountNumber>10435</AccountNumber>
    <UpdatedTimeStamp>2012-08-02 09:09:08</
UpdatedTimeStamp>
    <StartDateTime>2009-04-22 16:00:00</StartDateTime>
    <EndDateTime>2009-04-22 17:00:00</EndDateTime>
    <AppointmentOpportunityID>0</
AppointmentOpportunityID>
    <AppointmentOpportunityCloseDateLinked>N</
AppointmentOpportunityCloseDateLinked>

```

```
        <AppointmentDoneWorkflowID>0</
AppointmentDoneWorkflowID>
    </Event>
</GetEventsResponse>
```

Add New Event

This function allows the caller to add events for a period of time for the specified group.

Input

- account_id (required for shared access users)
- request_id (optional)
- TeamID
- Event Title
- Event Type
- Public Event
- Start Time
- End Date
- End Time
- Event Fee
- Charge No-shows
- Location ID
- Attendees
- Reminders
- AppointmentOpportunityID (The opportunity to be linked with the event. Can only be set when there is only one attendee and when there is opportunity assigned to the attendee)
- AppointmentOpportunityCloseDateLinked (Y/N. The opportunity's close date must be the same as the event's date to be able to set to Y. If set to Y, updating the event date will also update the linked opportunity's close date and vice versa)
- AppointmentDoneWorkflowID (Trigger a workflow at the end of appointment)

Output

Success (and EventID) or Failure Message

Example Request

```
<AddEventsRequest>
  <Event request_id="alb2c3">
    <TeamID>7</TeamID>
    <EventTitle>Bob's Cookout!</EventTitle>
    <EventType>Dinner</EventType>
    <PublicEvent>N</PublicEvent>
    <Date>2010-04-01</Date>
    <StartTime>6:30PM</StartTime>
    <EndDate>2010-04-01</EndDate>
    <EndTime>11:30PM</EndTime>
    <EventFee>Free!</EventFee>
    <ChargeNoShows>N</ChargeNoShows>
    <LocationID>839</LocationID>
    <Attendees>
      <Attendee>Joe Shmoe</Attendee>
      <Attendee>fred@yahoo.com</Attendee>
      <Attendee>biff@yahoo.com</Attendee>
      <Attendee>bill@alcoholic.org</Attendee>
      <Attendee>bob@ex-alcoholic.net</Attendee>
    </Attendees>
    <Reminders>N</Reminders>
  </Event>
</AddEventsRequest>
```

Example Request (shared access)

```
<AddEventsRequest>
  <Event account_id="12345">
    <TeamID>7</TeamID>
    <EventTitle>Bob's Cookout!</EventTitle>
    <EventType>Dinner</EventType>
    <PublicEvent>N</PublicEvent>
    <Date>2010-04-01</Date>
```

```

    <StartTime>6:30PM</StartTime>
    <EndDate>2010-04-01</EndDate>
    <EndTime>11:30PM</EndTime>
    <EventFee>Free!</EventFee>
    <ChargeNoShows>N</ChargeNoShows>
    <LocationID>839</LocationID>
    <Attendees>
        <Attendee>Joe Shmoe</Attendee>
        <Attendee>fred@yahoo.com</Attendee>
        <Attendee>biff@yahoo.com</Attendee>
        <Attendee>bill@alcoholic.org</Attendee>
        <Attendee>bob@ex-alcoholic.net</Attendee>
    </Attendees>
    <Reminders>N</Reminders>
</Event>
</AddEventsRequest>

```

Example Request (1 attendee with appointment opportunity linked)

```

<AddEventsRequest>
    <Event>
        <TeamID>4</TeamID>
        <EventTitle>Colonoscopy</EventTitle>
        <EventType>Checkup</EventType>
        <PublicEvent>N</PublicEvent>
        <Date>2025-11-01</Date>
        <StartTime>6:30PM</StartTime>
        <EndDate>2025-11-01</EndDate>
        <EndTime>07:30PM</EndTime>
        <ChargeNoShows>N</ChargeNoShows>
        <EventFee>10</EventFee>
        <Attendees>
            <Attendee>john.smith@gmail.com</Attendee>
        </Attendees>
        <Reminders>N</Reminders>
        <AppointmentOpportunityID>336</
AppointmentOpportunityID>
        <AppointmentOpportunityCloseDateLinked>Y</
AppointmentOpportunityCloseDateLinked>
    </Event>
</AddEventsRequest>

```

```
        <AppointmentDoneWorkflowID>2</
AppointmentDoneWorkflowID>
    </Event>
</AddEventsRequest>
```

Example Response

```
<AddEventsResponse>
    <Events>
        <Event request_id="a1b2c3">
            <EventID>42</EventID>
            <Result>Success</Result>
            <AccountNumber>91234</AccountNumber>
            <UpdatedTimeStamp>2012-08-30 14:24:09</
UpdatedTimeStamp>
        </Event>
        <Event request_id="d4e5f6">
            <EventID>43</EventID>
            <Result>Success</Result>
            <AccountNumber>91234</AccountNumber>
            <UpdatedTimeStamp>2012-08-30 14:24:09</
UpdatedTimeStamp>
        </Event>
    </Events>
</AddEventsResponse>
```

Modify Existing Event

This function allows the caller to modify an event's times, dates, and other information relevant to the event.

Input

- account_id (required for shared access users)
- EventID
- TeamID
- Event Title
- Event Type

- Public Event
- Date
- Start Time
- End Date
- End Time
- Event Fee
- Location ID
- Charge No-shows
- AppointmentOpportunityID (The opportunity to be linked with the event. Can only be set when there is only one attendee and when there is opportunity assigned to the attendee)
- AppointmentOpportunityCloseDateLinked (Y/N. The opportunity's close date must be the same as the event's date to be able to set to Y. If set to Y, updating the event date will also update the linked opportunity's close date and vice versa)
- AppointmentDoneWorkflowID (Trigger a workflow at the end of appointment)

Output

Success or Failure Message

Example Request

```
<ModifyEventRequest EventID="42">
  <EventType>Brunch / Cookout</EventType>
  <Date>2010-04-01</Date>
  <StartTime>10:30AM</StartTime>
  <EndDate>2010-04-01</EndDate>
  <EndTime>2:30PM</EndTime>
  <LocationID>932</LocationID>
  <AppointmentOpportunityID>336</
AppointmentOpportunityID>
  <AppointmentOpportunityCloseDateLinked>Y</
AppointmentOpportunityCloseDateLinked>
  <AppointmentDoneWorkflowID>2</
AppointmentDoneWorkflowID>
```

</ModifyEventRequest>

Example Request (shared access)

```
<ModifyEventRequest EventID="42" account_id="12345">
  <EventType>Brunch / Cookout</EventType>
  <Date>2010-04-01</Date>
  <StartTime>10:30AM</StartTime>
  <EndDate>2010-04-01</EndDate>
  <EndTime>2:30PM</EndTime>
  <LocationID>932</LocationID>
</ModifyEventRequest>
```

Example Response

```
<ModifyEventsResponse>
  <Result>Success</Result>
  <EventID>42</EventID>
  <AccountNumber>91234</AccountNumber>
  <UpdatedTimeStamp>2012-08-30 14:24:09</
UpdatedTimeStamp>
</ModifyEventsResponse>
```

Delete Events

This function allows the caller to delete one or more Events from the database.

Input

- account_id (required for shared access users)
- request_id (optional)
- Event ID

Output

For each Event, Event_id, Success or Failure Message

Example Request

```
<DeleteEventsRequest>
  <Events>
    <Event EventID="25" request_id="a1b2c3"/>
    <Event EventID="45" request_id="d4e5f6"/>
  </Events>
</DeleteEventsRequest>
```

Example Request (shared access)

```
<DeleteEventsRequest>
  <Events>
    <Event EventID="25" account_id="12345"/>
  </Events>
</DeleteEventsRequest>
```

Example Response

```
<DeleteEventsResponse>
  <Events>
    <Event request_id="a1b2c3">
      <Event_id>45</Event_id>
      <Result>Success</Result>
    </Event>
    <Event request_id="d4e5f6">
      <Event_id>25</Event_id>
      <Result>Success</Result>
    </Event>
  </Events>
</DeleteEventsResponse>
```

Get Event Types

This function allows the caller to retrieve valid Event Types for a group in an account.

Input

Group ID (required). Account ID (optional - required for shared access. If missing, will be account owned by the user).

Use `get_all` to get all the event types groups that the user is a member of.

Output

Success or failure. On success, a list of valid Event Types for the account.

Example Request

```
<GetEventTypesRequest group_id="9985"></  
GetEventTypesRequest>
```

Example Request (shared access)

```
<GetEventTypesRequest group_id="5023" account_id="12345"></  
GetEventTypesRequest>
```

Example Request (shared access with `get_all`)

```
<GetEventTypesRequest get_all="true"></  
GetEventTypesRequest>
```

Example Response

```
<GetEventTypesResponse>  
  <Result>Success</Result>  
  <EventTypes>  
    <EventType>  
      <AccountNumber>12345</AccountNumber>  
      <Group_id>5023</Group_id>  
      <Label>Meeting</Label>  
    </EventType>  
    <EventType>  
      <AccountNumber>12345</AccountNumber>  
      <Group_id>5023</Group_id>  
      <Label>Conference</Label>  
    </EventType>  
    <EventType>  
      <AccountNumber>12345</AccountNumber>  
      <Group_id>5023</Group_id>
```

```
        <Label>Seminar</Label>
    </EventType>
    <EventType>
        <AccountNumber>12345</AccountNumber>
        <Group_id>5023</Group_id>
        <Label>Course</Label>
    </EventType>
    <EventType>
        <AccountNumber>12345</AccountNumber>
        <Group_id>5023</Group_id>
        <Label>Training</Label>
    </EventType>
    <EventType>
        <AccountNumber>12345</AccountNumber>
        <Group_id>5023</Group_id>
        <Label>Trip</Label>
    </EventType>
</EventTypes>
</GetEventTypesResponse>
```

Update Attendees Attendance

This function allows the caller to modify an event by updating attendees' RSVP statuses.

Attendees statuses can be changed or new attendees can be added to the attend, noshow, unsure, or checked in lists.

Input

- EventID
- account_id (required for shared access users)
- group_id (required for shared access users)
- RSVP statuses (Attend/Noshow/Unsure/CheckIn)
- attendee emails

Output

Result (Success or Failure), EventID, Failure Message and/or Number Attending.

Example Request

```
<UpdateEventAttendeesRequest EventID="42">
  <Attend>
    <Email>fred@tester.com</Email>
    <Email>ted@tester.com</Email>
  </Attend>
  <Noshow>
    <Email>jim@tester.com</Email>
    <Email>jeff@tester.com</Email>
  </Noshow>
  <Unsure>
    <Email>biff@tester.com</Email>
    <Email>bob@tester.com</Email>
  </Unsure>
  <CheckIn>
    <Email>joet@tester.com</Email>
    <Email>jakel@tester.com</Email>
  </CheckIn>
</UpdateEventAttendeesRequest>
```

Example Request (shared access)

```
<UpdateEventAttendeesRequest EventID="42"
account_id="12345" group_id="1">
  <Attend>
    <Email>fred@tester.com</Email>
    <Email>ted@tester.com</Email>
  </Attend>
  <Noshow>
    <Email>jim@tester.com</Email>
    <Email>jeff@tester.com</Email>
  </Noshow>
  <Unsure>
    <Email>biff@tester.com</Email>
    <Email>bob@tester.com</Email>
  </Unsure>
```

```
<CheckIn>
  <Email>joet@tester.com</Email>
  <Email>jakel@tester.com</Email>
</CheckIn>
</UpdateEventAttendeesRequest>
```

Example Response

```
<UpdateEventAttendeesResponse>
  <EventID>42</EventID>
  <Result>Success</Result>
  <Attending>3</Attending>
</UpdateEventAttendeesResponse>
```

Get Event Locations

This function allows the caller to retrieve locations for events for an account.

Input

account_id (optional - required for shared access. If missing, will be account owned by the user).

To get events after a timestamp obtained earlier, pass updated_timestamp = (“timestampvalue”).

Pass get_all = “true” to get all event locations for accounts where user has events permissions.

Output

Success or failure. For each location, ID, Name, Address, City, State, Zip, Country, Phone, Website.

Example Request

```
<GetEventLocationsRequest></GetEventLocationsRequest>
```

Example Request (get all)

```
<GetEventLocationsRequest get_all="true"></  
GetEventLocationsRequest>
```

Example Request

```
<GetEventLocationsRequest updated_timestamp="2012-08-01  
12:00:00"></GetEventLocationsRequest>
```

Example Request (shared access)

```
<GetEventLocationsRequest account_id="12345"></  
GetEventLocationsRequest>
```

Example Response

```
<GetEventLocationsResponse>  
  <Result>Success</Result>  
  <EventLocations>  
    <EventLocation>  
      <AccountNumber>12345</AccountNumber>  
      <ID>78</ID>  
      <Name>My Event Location 1</Name>  
      <Address>123 Sample Street</Address>  
      <City>My City</City>  
      <State>IL</State>  
      <Zip>98765</Zip>  
      <Country>USA</Country>  
      <Phone>123-456-7890</Phone>  
      <Website>www.mysite.com</Website>  
      <UpdatedTimeStamp>2012-12-06 10:52:17</  
UpdatedTimeStamp>  
    </EventLocation>  
    <EventLocation>  
      <AccountNumber>12345</AccountNumber>  
      <ID>79</ID>  
      <Name>My Event Location 2</Name>  
      <Address>456 Another Street</Address>  
      <City>Anothercity</City>
```

```
        <State>MI</State>
        <Zip>54321</Zip>
        <Country>USA</Country>
        <Phone>709-342-3454</Phone>
        <Website>www.anothersite.com</Website>
        <UpdatedTimeStamp>2012-12-06 14:59:29</
UpdatedTimeStamp>
    </EventLocation>
</EventLocations>
</GetEventLocationsResponse>
```

Add Event Location

This function allows the caller to add a location for events for an account.

Input

- account_id (optional - required for shared access. If missing, will be account owned by the user).
- Name (required)
- Address (required)
- City (required)
- State (required)
- Zip
- Country (required)
- Phone
- Website

Output

Success or failure. LocationID, AccountNumber, and UpdatedTimeStamp for new location if successful.

Example Request

```
<AddEventLocationRequest>
```

```
<Name>My Location</Name>
<Address>123 My Street</Address>
<City>My City</City>
<State>IL</State>
<Zip>60054</Zip>
<Country>USA</Country>
</AddEventLocationRequest>
```

Example Request (shared access)

```
<AddEventLocationRequest account_id="12345">
  <Name>My Location2</Name>
  <Address>456 Another Street</Address>
  <City>New City</City>
  <State>MI</State>
  <Zip>49857</Zip>
  <Country>USA</Country>
  <Phone>923-232-2323</Phone>
  <Website>www.mywebsite.com</Website>
</AddEventLocationRequest>
```

Example Response

```
<AddEventLocationResponse>
  <Result>Success</Result>
  <LocationID>98</LocationID>
  <AccountNumber>34521</AccountNumber>
  <UpdatedTimeStamp>2012-12-06 14:15:15</
UpdatedTimeStamp>
</AddEventLocationResponse>
```

Edit Event Location

This function allows the caller to edit a location for events for an account.

Input

account_id (optional - required for shared access. If missing, will be account owned by the user).

location_id of event to edit.

Fields to change (Name, Address, City, State, Zip, Country, Phone, Website).

Output

Success or failure. LocationID for edited location if successful.

Example Request

```
<EditEventLocationRequest location_id="87">
  <Name>My Location</Name>
  <Address>124 My Street</Address>
  <City>This City</City>
  <State>KY</State>
  <Zip>69382</Zip>
  <Country>USA</Country>
</EditEventLocationRequest>
```

Example Request (shared access)

```
<EditEventLocationRequest location_id="91"
account_id="12345">
  <Name>My New Location 2</Name>
  <Address>458 Another Street</Address>
  <City>Rapid City</City>
  <State>SD</State>
  <Zip>89039</Zip>
  <Country>USA</Country>
  <Phone>923-232-3323</Phone>
  <Website>www.mywebsite2.com</Website>
</EditEventLocationRequest>
```

Example Response

```
<EditEventLocationResponse>
  <Result>Success</Result>
  <LocationID>91</LocationID>
```

```
<AccountNumber>35987</AccountNumber>
  <UpdatedTimeStamp>2012-12-07 09:12:21</
UpdatedTimeStamp>
</EditEventLocationResponse>
```

Delete Event Location

This function allows the caller to delete a location for events for an account.

Input

account_id (optional - required for shared access. If missing, will be account owned by the user).

location_id of event to delete.

Output

Success or failure. LocationID for deleted location if successful.

Example Request

```
<DeleteEventLocationRequest location_id="87"></
DeleteEventLocationRequest>
```

Example Request (shared access)

```
<DeleteEventLocationRequest location_id="91"
account_id="12345"></DeleteEventLocationRequest>
```

Example Response

```
<DeleteEventLocationResponse>
  <Result>Success</Result>
  <LocationID>91</LocationID>
</DeleteEventLocationResponse>
```

Get Events And CRM Activities

This function allows the caller to retrieve all the events and CRM activities.

Input

- group_id
- start_date
- end_date

Output

Success or failure. List of events and CRM activities within date range.

Example Request

```
<GetEventsAndCRMActivitiesRequest group_id="4"
start_date="20150417" end_date="20150417"/>
```

Example Response

```
<GetEventsAndCRMActivitiesResponse>
  <Result>Success</Result>
  <Events>
    <Event>
      <ChargeNoShows></ChargeNoShows>
      <FacilityCountry></FacilityCountry>
      <FacilityZip>98765</FacilityZip>
      <PublicEvent></PublicEvent>
      <FacilityState>CA</FacilityState>
      <FacilityAddress>123 Main Street</
FacilityAddress>
      <EventType>Meeting</EventType>
      <StartTime>1000</StartTime>
      <EndDateTime>2015-04-17 15:00:00</EndDateTime>
      <LocationID>19</LocationID>
      <EndDate>20150417</EndDate>
```



```

        <NoShows>
            <NoShow>ryan@yourdomain.com</NoShow>
            <NoShow>jason@yourdomain.com</NoShow>
        </NoShows>
        <Notes>&lt;p&gt;At 1pm, Vince will provide
training for anti-virus/anti-spyware, as well as defense
against socially-engineered attacks. &nbsp;&lt;/p&gt;
        &lt;p&gt;Google Hangout will be provided for
remote peeps.&lt;/p&gt;</Notes>
        <AccountNumber>12345</AccountNumber>
        <FacilityCity>Some City</FacilityCity>
        <FacilityName>Meeting Place</FacilityName>
        <EventTitle>Meeting and Security Training</
EventTitle>
        <Attendees>
            <Attendee>austin@yourdomain.com</Attendee>
            <Attendee>keith@yourdomain.com</Attendee>
            <Attendee>rmax@yourdomain.com</Attendee>
            <Attendee>bjorn@yourdomain.com</Attendee>
            <Attendee>support@yourdomain.com</Attendee>
            <Attendee>vince@yourdomain.com</Attendee>
            <Attendee>tom@yourdomain.com</Attendee>
            <Attendee>melissa@yourdomain.com</Attendee>
        </Attendees>
        <StartDateTime>2015-04-17 10:00:00</
StartDateTime>
        <EventID>1467</EventID>
        <Date>20150417</Date>
        <Unsuers></Unsuers>
        <GroupID>20</GroupID>
        <GroupName>Teamr Management</GroupName>
        <EventFee>0.00</EventFee>
        <EndTime>1500</EndTime>
        <UpdatedTimeStamp>2015-04-16 12:11:49</
UpdatedTimeStamp>
        <CheckIns></CheckIns>
    </Event>
</Events>
<CRMActivities>
    <CRMActivity>

```

```

        <Activity_id>47</Activity_id>
        <Contact_id>123</Contact_id>
        <Contact_firstname>Testfirst1 & and " ' </
Contact_firstname>
        <Contact_lastname>Test1 & 2</
Contact_lastname>
        <Done_by_contact_id>0</Done_by_contact_id>
        <Done_by_lastname>Smith</Done_by_lastname>
        <Done_by_firstname>Todd</Done_by_firstname>
        <Group_id>1</Group_id>
        <Group_name>My Group</Group_name>
        <Done_date>2015-04-18 16:20:00</Done_date>
        <Due_date>2015-02-19 11:00:00</Due_date>
        <Activity>Follow-Up</Activity>
        <Notes>Reply to his email about the meeting</
Notes>
        <UpdatedTimeStamp>2015-04-17 13:20:05</
UpdatedTimeStamp>
        <Opportunity_id></Opportunity_id>
        <Opportunity_title></Opportunity_title>
        <Completed_by_contact_id>0</
Completed_by_contact_id>
        <Completed_by_firstname></
Completed_by_firstname>
        <Completed_by_lastname></Completed_by_lastname>
        <Completed_by_email></Completed_by_email>
    </CRMActivity>
</CRMActivities>
</GetEventsAndCRMActivitiesResponse>

```

Get Event Contacts Attending

This function allows the caller to retrieve all the contacts who RSVPed 'Attending' for an event

Input

- group_id (required)
- event_id (required)

- account_id (required for shared access users)

Output

Success or failure. List of contacts attending the specified event.

Example Request

```
<GetEventContactsAttendingRequest group_id="4"
event_id="100"/>
```

Example Request (shared access)

```
<GetEventContactsAttendingRequest group_id="4"
event_id="100" account_id="12345"/>
```

Example Response

```
<GetEventContactsAttendingResponse>
  <Result>Success</Result>
  <EventID>100</EventID>
  <Contacts>
    <Contact>
      <ContactID></ContactID>
      <Firstname>Testfirst1 & and " ' P</
Firstname>
      <Lastname>Test1 & 2</Lastname>
      <Email>contact+test1@gmail.com</Email>
      <Phone>(012) 111-111</Phone>
      <Mobile>1111-1</Mobile>
      <Comment></Comment>
    </Contact>
    <Contact>
      <ContactID></ContactID>
      <Firstname>Testfirst101</Firstname>
      <Lastname>Test101</Lastname>
      <Email>contact+test101@gmail.com</Email>
      <Phone>012-111-111</Phone>
      <Mobile>11111</Mobile>
      <Comment></Comment>
```

```
        </Contact>
    </Contacts>
    <TotalContactsAttending>2</TotalContactsAttending>
</GetEventContactsAttendingResponse>
```

Get Event Contacts Not Attending

This function allows the caller to retrieve all the contacts who RSVPed 'Not Attending' for an event

Input

- group_id (required)
- event_id (required)
- account_id (required for shared access users)

Output

Success or failure. List of contacts not attending the specified event.

Example Request

```
<GetEventContactsNotAttendingRequest group_id="4"
event_id="100"/>
```

Example Request (shared access)

```
<GetEventContactsNotAttendingRequest group_id="4"
event_id="100" account_id="12345"/>
```

Example Response

```
<GetEventContactsNotAttendingResponse>
  <Result>Success</Result>
  <EventID>100</EventID>
  <Contacts>
    <Contact>
      <ContactID>132</ContactID>
      <Firstname>Testfirst10</Firstname>
```

```

        <Lastname>Test10</Lastname>
        <Email>contact+test10@gmail.com</Email>
        <Phone>012-111-111</Phone>
        <Mobile>11111</Mobile>
        <Comment></Comment>
    </Contact>
    <Contact>
        <ContactID>222</ContactID>
        <Firstname>Testfirst100</Firstname>
        <Lastname>Test100</Lastname>
        <Email>contact+test100@gmail.com</Email>
        <Phone>012-111-111</Phone>
        <Mobile>11111</Mobile>
        <Comment></Comment>
    </Contact>
</Contacts>
<TotalContactsNotAttending>2</
TotalContactsNotAttending>
</GetEventContactsNotAttendingResponse>

```

Get Event Contacts Unsure

This function allows the caller to retrieve all the contacts who RSVPed ‘Unsure’ for an event

Input

- group_id (required)
- event_id (required)
- account_id (required for shared access users)

Output

Success or failure. List of contacts who are unsure for the specified event.

Example Request

```
<GetEventContactsUnsureRequest group_id="4" event_id="100"/>
```

Example Request (shared access)

```
<GetEventContactsUnsureRequest group_id="4" event_id="100" account_id="12345"/>
```

Example Response

```
<GetEventContactsUnsureResponse>
  <Result>Success</Result>
  <EventID>100</EventID>
  <Contacts>
    <Contact>
      <ContactID>228</ContactID>
      <Firstname>Testfirst106</Firstname>
      <Lastname>Test106</Lastname>
      <Email>contact+test106@gmail.com</Email>
      <Phone>012-111-111</Phone>
      <Mobile>11111</Mobile>
      <Comment></Comment>
    </Contact>
  </Contacts>
  <TotalContactsUnsure>1</TotalContactsUnsure>
</GetEventContactsUnsureResponse>
```

Get Event Contacts Not Yet Responded

This function allows the caller to retrieve all the contacts who have not RSVP for an event

Input

- group_id (required)
- event_id (required)
- account_id (required for shared access users)

Output

Success or failure. List of contacts whom not yet responded to the specified event.

Example Request

```
<GetEventContactsNotYetRespondedRequest group_id="4"
event_id="100"/>
```

Example Request (shared access)

```
<GetEventContactsNotYetRespondedRequest group_id="4"
event_id="100" account_id="12345"/>
```

Example Response

```
<GetEventContactsNotYetRespondedResponse>
  <Result>Success</Result>
  <EventID>100</EventID>
  <Contacts>
    <Contact>
      <ContactID>221</ContactID>
      <Firstname>Testfirst99</Firstname>
      <Lastname>Test99</Lastname>
      <Email>contact+test99@gmail.com</Email>
      <Phone>012-111-111</Phone>
      <Mobile>11111</Mobile>
    </Contact>
    <Contact>
      <ContactID>131</ContactID>
      <Firstname>Testfirst9</Firstname>
      <Lastname>Test9</Lastname>
      <Email>contact+test9@gmail.com</Email>
      <Phone>012-111-111</Phone>
      <Mobile>11111</Mobile>
    </Contact>
  </Contacts>
  <TotalContactsNotYetResponded>2</
TotalContactsNotYetResponded>
</GetEventContactsNotYetRespondedResponse>
```

Spec - Groups

Table Of Contents

- Create Group
- Get Groups
- Edit Groups
- Delete Groups
- Add Contacts to Group
- Delete Contacts from Group

Create Group

This function allows the caller to create a new group in the account.

Input

- Name of Group
- Type of Group (optional, should be Public, Private, or Hidden)
- EmailsSentFromName (optional)
- EmailsSentFromEmail (optional)
- EmailPhysicalAddress (optional)
- EventsTimeZone (optional)

For shared access user to create a group, include account_id (shared access user will need to have New Group Permissions).

Output

Success or error, ID of new group

Example Request


```
<CreateGroupRequest>
  <Name>MyNewGroup</Name>
  <GroupType>Hidden</GroupType>
  <EmailsSentFromName>Sally Simpson</EmailsSentFromName>
  <EmailsSentFromEmail>ssimpson@sample.com</
EmailsSentFromEmail>
  <EmailPhysicalAddress>999 South Avenue, Coal City, KS,
70045, USA</EmailPhysicalAddress>
  <EventsTimeZone>America/Los_Angeles</EventsTimeZone>
</CreateGroupRequest>
```

Example Request (shared access)

```
<CreateGroupRequest account_id="123456">
  <Name>MyNewGroup</Name>
  <GroupType>Hidden</GroupType>
  <EmailsSentFromName>Joe Jackson</EmailsSentFromName>
  <EmailsSentFromEmail>jjackson@example.com</
EmailsSentFromEmail>
  <EmailPhysicalAddress>333 First Avenue, Anytown, AL,
30221, USA</EmailPhysicalAddress>
  <EventsTimeZone>America/Los_Angeles</EventsTimeZone>
</CreateGroupRequest>
```

Successful Response

```
<CreateGroupResponse>
  <Result>Success</Result>
  <Group_id>9989</Group_id>
</CreateGroupResponse>
```

Get Groups

This function allows the caller to retrieve groups from the database. Search parameters should be specified inside the tag. Groups can be retrieved by ID or Name.

Input

Specify search criteria within GetGroupsRequest tag. Search criteria can be group_id or group_name. If no search criteria, return all groups in account. If not account owner, must pass account number. All groups that a shared user is a member of in that account would be passed.

Output

Success or failure. For each group found: Group_id, Name, Group_type, EmailsSentFromName, EmailsSentFromEmail, EmailPhysicalAddress, EventsTimeZone.

Example Request 1

```
<GetGroupsRequest></GetGroupsRequest>
```

Example Request 2

```
<GetGroupsRequest group_id="9985"></GetGroupsRequest>
```

Example Request 3

```
<GetGroupsRequest group_name="My Group"></GetGroupsRequest>
```

Example Request 4 (shared access)

```
<GetGroupsRequest account_id="123456" group_name="My Group"></GetGroupsRequest>
```

Successful Response

```
<GetGroupsResponse>
  <Result>Success</Result>
  <Groups>
    <Group>
      <AccountNumber>91234</AccountNumber>
      <Group_id>7</Group_id>
      <Name>TestQueueMail</Name>
      <Group_type>Private</Group_type>
      <EmailsSentFromName>Jeffery Samuels</
EmailsSentFromName>
```

```

        <EmailsSentFromEmail>jsamuels@testco.com</
EmailsSentFromEmail>
        <EmailPhysicalAddress>123 My Street, Mycity,
CO, 90021, USA</EmailPhysicalAddress>
        <IncludeLoginLink>Yes</IncludeLoginLink>
        <EventsTimeZone>America/Los_Angeles</
EventsTimeZone>
        <TotalMatchingContacts>28</
TotalMatchingContacts>
    </Group>
    <Group>
        <AccountNumber>91234</AccountNumber>
        <Group_id>11</Group_id>
        <Name>MyTestGroupWithHiddenType</Name>
        <Group_type>Hidden</Group_type>
        <EmailsSentFromName>David Handler</
EmailsSentFromName>
        <EmailsSentFromEmail>dhandler@anotherco.com</
EmailsSentFromEmail>
        <EmailPhysicalAddress>456 Another Street,
Altcity, MT, 89002, USA</EmailPhysicalAddress>
        <IncludeLoginLink>No</IncludeLoginLink>
        <EventsTimeZone>America/Los_Angeles</
EventsTimeZone>
        <TotalMatchingContacts>54</
TotalMatchingContacts>
    </Group>
</Groups>
</GetGroupsResponse>

```

Edit Groups

This function allows the caller to edit one or more groups in the database. For a shared access user to edit a group, include `account_id` (shared access user will need to have New Group permissions).

Input

Specify search criteria within each Group tag. Search criteria can be:

- account_id (required for shared access users)
- group_id
- group_name
- request_id (optional)
- Name
- GroupType
- EmailsSentFromName
- EmailsSentFromEmail
- EmailPhysicalAddress
- EventsTimeZone

Each group's search criteria must return a single unique group to edit.
Any fields not sent will stay at their current values.

Output

For each Group ID, success or failure.

Example Request

```
<EditGroupsRequest>
  <Groups>
    <Group account_id="123456" group_id="5"
request_id="a1b2c3">
      <Name>New Name</Name>
      <GroupType>Hidden</GroupType>
      <EmailsSentFromName>Joe Smith</
EmailsSentFromName>
      <EmailsSentFromEmail>jsmith@mydomain.com</
EmailsSentFromEmail>
      <EmailPhysicalAddress>123 First Street,
Anytown, VA, 20345, USA</EmailPhysicalAddress>
      <EventsTimeZone>America/New_York</
EventsTimeZone>
    </Group>
    <Group account_id="123456"
group_name="MyTestGroup222" request_id="d4e5f6">
```

```

        <Name>Another Name</Name>
        <EmailsSentFromName>Sam Smith</
EmailsSentFromName>
        <EmailsSentFromEmail>ssmith@mydomain.com</
EmailsSentFromEmail>
    </Group>
</Groups>
</EditGroupsRequest>

```

Successful Response

```

<EditGroupsResponse>
  <Groups>
    <Group request_id="a1b2c3">
      <Group_id>5</Group_id>
      <Result>Success</Result>
    </Group>
    <Groups request_id="d4e5f6">
      <Group_id>6</Group_id>
      <Result>Success</Result>
    </Groups>
  </Groups>
</EditGroupsResponse>

```

Delete Groups

This function allows the caller to delete one or more groups from the database. For a shared access user to delete a group, include `account_id` (shared access user will need to have New Group permissions).

Input

Specify search criteria within each Group tag. Search criteria can be:

- `account_id` (required for shared access users)
- `group_id`
- `group_name`
- `request_id` (optional)

Each group's search criteria must return a single unique group to delete.

Output

For each Group ID, success or failure.

Example Request 1

```
<DeleteGroupsRequest>
  <Groups>
    <Group group_id="5" request_id="a1b2c3" />
    <Group group_name="MyTestGroup222"
request_id="d4e5f6" />
  </Groups>
</DeleteGroupsRequest>
```

Example Request 2 (Shared Access)

```
<DeleteGroupsRequest>
  <Groups>
    <Group account_id="123456" group_id="5" />
    <Group account_id="123456"
group_name="MyTestGroup222" />
  </Groups>
</DeleteGroupsRequest>
```

Successful Response

```
<DeleteGroupsResponse>
  <Groups>
    <Group request_id="a1b2c3">
      <Group_id>5</Group_id>
      <Result>Success</Result>
    </Group>
    <Group request_id="d4e5f6">
      <Group_id>6</Group_id>
      <Result>Success</Result>
    </Group>
  </Groups>
```

</DeleteGroupsResponse>

Add Contacts to Group

This function allows the caller to add contacts to a group.

Input

- account_id (required for shared access users)
- group_id
- group_name
- request_id (optional)
- Contact
- contact_id
- firstname
- lastname
- email

Each contact's search criteria must return a single unique contact to add to the group.

Output

For each Contact ID, success or failure.

Request Example 1

```
<AddContactsToGroupRequest group_id="9902">
  <Contacts>
    <Contact contact_id="8903" request_id="a1b2c3" />
    <Contact firstname="James" lastname="Johnson"
request_id="d4e5f6" />
  </Contacts>
</AddContactsToGroupRequest>
```

Request Example 2 - shared access

```
<AddContactsToGroupRequest account_id="1234" group_name="My
Group Name">
  <Contacts>
    <Contact contact_id="8903" />
    <Contact firstname="James" lastname="Johnson" />
  </Contacts>
</AddContactsToGroupRequest>
```

Successful Response

```
<AddContactsToGroupResponse>
  <Contacts>
    <Contact request_id="a1b2c3">
      <Contact_id>8903</Contact_id>
      <Result>Success</Result>
    </Contact>
    <Contact request_id="d4e5f6">
      <Contact_id>8904</Contact_id>
      <Result>Success</Result>
    </Contact>
  </Contacts>
</AddContactsToGroupResponse>
```

Delete Contacts from Group

This function allows the caller to delete contacts from a group.

Input

- account_id (required for shared access users)
- group_id
- group_name
- request_id (optional)
- Contact
- contact_id
- firstname
- lastname
- email

Each contact's search criteria must return a single unique contact to delete from the group.

Output

For each Contact ID, success or failure.

Example Request 1:

```
<DeleteContactsFromGroupRequest group_id="9902">
  <Contacts>
    <Contact contact_id="8903" request_id="a1b2c3" />
    <Contact firstname="James" lastname="Johnson"
request_id="d4e5f6" />
  </Contacts>
</DeleteContactsFromGroupRequest>
```

Request Example 2 - shared access:

```
<DeleteContactsFromGroupRequest account_id="1234"
group_name="My Group Name">
  <Contacts>
    <Contact contact_id="8903" />
    <Contact firstname="James" lastname="Johnson" />
  </Contacts>
</DeleteContactsFromGroupRequest>
```

Successful Response

```
<DeleteContactsFromGroupResponse>
  <Contacts>
    <Contact request_id="a1b2c3">
      <Contact_id>8903</Contact_id>
      <Result>Success</Result>
    </Contact>
    <Contact request_id="d4e5f6">
      <Contact_id>8904</Contact_id>
      <Result>Success</Result>
    </Contact>
  </Contacts>
</DeleteContactsFromGroupResponse>
```

```
</Contacts>  
</DeleteContactsFromGroupResponse>
```

Spec - Invoices

Table Of Contents

- Get Invoices
- Add Invoices
- Edit Invoices
- Delete Invoices

Get Invoices

This function allows the caller to retrieve Invoices from the database. Search parameters should be specified inside the tag. Invoices can be retrieved by invoice ID, contact (ID or name), or group (ID or Name). Leaving all search criteria blank would return all of the invoices in the account.

Input

- invoice_id
- contact_id
- contact_firstname
- contact_lastname
- group_id (return all invoices sent to group)
- group_name
- opened_date (YYYYMMDDHHmm format)
- external_id

If no search criteria, return all invoices in the account.

Output

Success or failure. For each Invoice found:

- Invoice_id
- Contact_id
- Contact_firstname
- Contact_lastname
- Contact_email
- Contact_company
- Contact_address1
- Contact_address2
- Contact_city
- Contact_state
- Contact_zip
- Contact_country
- Contact_phone
- Contact_mobile
- Contact_fax
- Group_id
- Group_name
- CreatedDatetime
- Sent_date
- Opened_date
- Due_date
- Description
- InvoiceFooter
- Paid_date
- TransactionID (the transaction ID of the invoice payment)
- Payment_amount
- QuoteOrInvoice
- ExternalID
- SalesRepContactID
- SalesRepFirstname
- SalesRepLastname
- SalesRepEmail
- ShipmentDate
- ShipmentAdvancedDaysWorkflow

- ShipmentWorkflowID
- ShippingMethod
- ShipToName
- ShipToAddress
- ShipToCity
- ShipToState
- ShipToZip
- ShipToCountry
- ShipToPhone
- InvoiceType
- InvoiceStatus
- InvoiceTotal
- InvoiceLineItems
 - Lineitem_id
 - Description
 - Unit_cost
 - Quantity
 - SKU
 - Event_id
 - Total_unit_cost

Example Request

```
<GetInvoicesRequest></GetInvoicesRequest>
```

Example Request

```
<GetInvoicesRequest contact_firstname="Jeff"
contact_lastname="Gordon"></GetInvoicesRequest>
```

Example Request

```
<GetInvoicesRequest invoice_id="73"></GetInvoicesRequest>
```

Example Request

```
<GetInvoicesRequest opened_date="201312040000"></
GetInvoicesRequest>
```

Example Request

```
<GetInvoicesRequest sent_date="20120201"></GetInvoicesRequest>
```

Example Request (filter by ExternalID)

```
<GetInvoicesRequest external_id="47217"></GetInvoicesRequest>
```

Successful Response

```
<GetInvoicesResponse>
  <Result>Success</Result>
  <Invoices>
    <Invoice>
      <Invoice_id>83</Activity_id>
      <Contact_id>443</Contact_id>
      <Contact_firstname>Jeff</Contact_firstname>
      <Contact_lastname>Gordon</Contact_lastname>
      <Contact_email>jeff@gordon.com</Contact_email>
      <Contact_company>Gordon Tech</Contact_company>
      <Contact_address1>1 Gordon Road</Contact_address1>
      <Contact_address2>Gordon Street</Contact_address2>
      <Contact_city>East Gordon</Contact_city>
      <Contact_state>CA</Contact_state>
      <Contact_zip>12345</Contact_zip>
      <Contact_country>USA</Contact_country>
      <Contact_phone>+101115035435</Contact_phone>
      <Contact_mobile>+101115035436</Contact_mobile>
      <Contact_fax>+101115035437</Contact_fax>
      <Group_id>8</Group_id>
      <Group_name>Test Team</Group_name>
```

```

        <CreatedDatetime>2023-06-12 10:00:48</
CreatedDatetime>
        <Sent_date>201204120855</Sent_date>
        <Opened_date>201203120915</Opened_date>
        <Due_date>20120412</Due_date>
        <Description>Invoice for Parts Delivered
January, 2012</Description>
        <InvoiceFooter><![CDATA[<p>The
<strong>quick </strong><em>brown </em><u>fox </u>jumps over
the lazy dog.</p>
        <p>The <strong>quick </strong><em>brown
</em><u>fox </u>jumps over the lazy dog.</p>
]]></InvoiceFooter>
        <Paid_date>201204120855</Paid_date>
        <TransactionID>1234554321</TransactionID>
        <Payment_amount>61.93</Payment_amount>
        <QuoteOrInvoice>Invoice</QuoteOrInvoice>
        <ExternalID>1234</ExternalID>
        <SalesRepContactID>123</SalesRepContactID>
        <SalesRepFirstname>Bob</SalesRepFirstname>
        <SalesRepLastname>Bobbington</
SalesRepLastname>
        <SalesRepEmail>bob@bobbington.com</
SalesRepEmail>
        <ShipmentDate>2012-04-01</ShipmentDate>
        <ShipmentAdvancedDaysWorkflow>2</
ShipmentAdvancedDaysWorkflow>
        <ShipmentWorkflowID>22</ShipmentWorkflowID>
        <ShippingMethod>USPS</ShippingMethod>
        <ShipToName>Jeff Gordon</ShipToName>
        <ShipToAddress>1 Gordon Road, Gordon
Street</ShipToAddress>
        <ShipToCity>Easy Gordon</ShipToCity>
        <ShipToState>CA</ShipToState>
        <ShipToZip>12345</ShipToZip>
        <ShipToCountry>United States</
ShipToCountry>
        <ShipToPhone>+12015550123</ShipToPhone>
        <InvoiceType>30 Day</InvoiceType>
        <InvoiceStatus>PAID</InvoiceStatus>

```

```

    <InvoiceTotal>62.00</InvoiceTotal>
    <InvoiceLineItems>
        <InvoiceLineItem>
            <Lineitem_id>23</Lineitem_id>
            <Event_id>12</Event_id>
            <Quantity>2</Quantity>
            <Description>Test Widget</
Description>

            <Sku>11111</Sku>
            <Unit_cost>6.00</Unit_cost>
            <Total_unit_cost>12.00</
Total_unit_cost>

        </InvoiceLineItem>
        <InvoiceLineItem>
            <Lineitem_id>24</Lineitem_id>
            <Event_id></Event_id>
            <Quantity>5</Quantity>
            <Description>Another Test
Widget</Description>

            <Sku>22222</Sku>
            <Unit_cost>10.00</Unit_cost>
            <Total_unit_cost>50.00</
Total_unit_cost>

        </InvoiceLineItem>
    </InvoiceLineItems>
</Invoice>
<Invoice>
    <Invoice_id>84</Activity_id>
    <Contact_id>444</Contact_id>
    <Contact_firstname>Steve</
Contact_firstname>

    <Contact_lastname>Watson</Contact_lastname>
    <Contact_email>steve@watson.com</
Contact_email>

    <Contact_company>Watson Tech</
Contact_company>

    <Contact_address1>1 Watson Road</
Contact_address1>

    <Contact_address2>Watson Street</
Contact_address2>

```



```
<Contact_city>East Watson</Contact_city>
<Contact_state>CA</Contact_state>
<Contact_zip>12345</Contact_zip>
<Contact_country>USA</Contact_country>
<Contact_phone>+102115035435</
Contact_phone>
<Contact_mobile>+102115035436</
Contact_mobile>
<Contact_fax>+102115035437</Contact_fax>
<Group_id>12</Group_id>
<Group_name>Test Team 2</Group_name>
<CreatedDatetime>2023-06-12 10:00:48</
CreatedDatetime>
<Sent_date>201206111301</Sent_date>
<Opened_date>201206111331</Opened_date>
<Due_date>20120711</Due_date>
<Description>Invoice for Services</
Description>
<InvoiceFooter></InvoiceFooter>
<Paid_date>201207131354</Paid_date>
<TransactionID>1234554321</TransactionID>
<Payment_amount>70.00</Payment_amount>
<QuoteOrInvoice>Quote</QuoteOrInvoice>
<ExternalID></ExternalID>
<SalesRepContactID>123</SalesRepContactID>
<SalesRepFirstname>Bob</SalesRepFirstname>
<SalesRepLastname>Bobbington</
SalesRepLastname>
<SalesRepEmail>bob@bobbington.com</
SalesRepEmail>
<ShipmentDate>2012-07-01</ShipmentDate>
<ShipmentAdvancedDaysWorkflow>2</
ShipmentAdvancedDaysWorkflow>
<ShipmentWorkflowID>22</ShipmentWorkflowID>
<ShippingMethod>USPS</ShippingMethod>
<ShipToName>Test Ship</ShipToName>
<ShipToAddress>Address 1, Street 2</
ShipToAddress>
<ShipToCity>City</ShipToCity>
<ShipToState>State</ShipToState>
```

```

        <ShipToZip>01011</ShipToZip>
        <ShipToCountry>United States</
ShipToCountry>
        <ShipToPhone>+12015550123</ShipToPhone>
        <InvoiceType>30 Day</InvoiceType>
        <InvoiceStatus>PAID</InvoiceStatus>
        <InvoiceTotal>70.00</InvoiceTotal>
        <InvoiceLineItems>
            <InvoiceLineItem>
                <Lineitem_id>45</Lineitem_id>
                <Event_id></Event_id>
                <Quantity>1</Quantity>
                <Description>Test Service</
Description>
                <Sku>33333</Sku>
                <Unit_cost>45.00</Unit_cost>
                <Total_unit_cost>45.00</
Total_unit_cost>
            </InvoiceLineItem>
            <InvoiceLineItem>
                <Lineitem_id>48</Lineitem_id>
                <Event_id></Event_id>
                <Quantity>1</Quantity>
                <Description>Test Service 2</
Description>
                <Sku>44444</Sku>
                <Unit_cost>25.00</Unit_cost>
                <Total_unit_cost>25.00</
Total_unit_cost>
            </InvoiceLineItem>
        </InvoiceLineItems>
    </Invoice>
</Invoices>
</GetInvoicesResponse>

```

Add Invoices

This function allows the caller to add one or more invoices.

To mark an invoice as paid, pass the Paid_date, TransactionID and Payment_amount arguments.

To make the invoice be sent after being created, pass the SendInvoice argument. The SendInvoiceCCEmails argument can be used to include CC recipients when sending the invoice.

Input

- request_id (optional)
- Contact_id (required)
- Group_id (required)
- QuoteOrInvoice (required, 'Quote', 'Invoice', 'Purchase Order')
- Sent_date (optional, YYYYMMDDHHmm format)
- Due_date (optional, YYYYMMDD format)
- Description (required)
- InvoiceFooter (optional)
- Paid_date (optional, YYYYMMDDHHmm format)
- TransactionID (optional, the transaction ID, for example the PayPal ID, of the invoice payment. Max length is 32 characters)
- Payment_amount (optional)
- ExternalID (optional)
- SalesRepContactID (optional)
- ShipmentDate (optional)
- ShipmentAdvancedDaysWorkflow (optional)
- ShipmentWorkflowID (optional)
- ShippingMethod (optional)
- ShipToName (optional)
- ShipToAddress (optional)
- ShipToCity (optional)
- ShipToState (optional)
- ShipToZip (optional)
- ShipToCountry (optional)
- ShipToPhone (optional)

- InvoiceType (optional)
- InvoiceStatus (optional)
- SendInvoice (optional, true/false)
- SendInvoiceCCEmails (optional, separated by comma)
- InvoiceLineItems
 - Description (required)
 - Unit_cost (required)
 - Quantity (required)
 - Sku (optional)
 - Event_id (optional)

Output

For each Invoice ID, success or failure.

Example Request

```
<AddInvoicesRequest>
  <Invoices>
    <Invoice request_id="a1b2c3">
      <Contact_id>788</Contact_id>
      <Group_id>8</Group_id>
      <QuoteOrInvoice>Invoice</QuoteOrInvoice>
      <ExternalID>1234</ExternalID>
      <Sent_date>201202210855</Sent_date>
      <Due_date>20120321</Due_date>
      <Description>Sample Invoice 1</Description>
      <InvoiceFooter><![CDATA[<p>The
<strong>quick </strong><em>brown </em><u>fox </u>jumps over
the lazy dog.</p>
      <p>The <strong>quick </strong><em>brown </
em><u>fox </u>jumps over the lazy dog.</p>]]></
InvoiceFooter>
      <Paid_date>201203121423</Paid_date>
      <TransactionID>1234554321</TransactionID>
      <Payment_amount>50.00</Payment_amount>
      <SalesRepContactID>123</SalesRepContactID>
      <ShipmentDate>2012-03-01</ShipmentDate>
```

```

        <ShipmentAdvancedDaysWorkflow>2</
ShipmentAdvancedDaysWorkflow>
        <ShipmentWorkflowID>1</ShipmentWorkflowID>
        <ShippingMethod>USPS</ShippingMethod>
        <ShipToName>Jeff Gordon</ShipToName>
        <ShipToAddress>1 Gordon Road, Gordon
Street</ShipToAddress>
        <ShipToCity>Easy Gordon</ShipToCity>
        <ShipToState>CA</ShipToState>
        <ShipToZip>12345</ShipToZip>
        <ShipToCountry>United States</
ShipToCountry>
        <ShipToPhone>+12015550123</ShipToPhone>
        <InvoiceType>30 Day</InvoiceType>
        <InvoiceStatus>PAID</InvoiceStatus>
        <SendInvoice>true</SendInvoice>

<SendInvoiceCCEmails>ccrecipient1@gmail.com,
ccrecipient2@gmail.com</SendInvoiceCCEmails>
        <InvoiceLineItems>
            <InvoiceLineItem>
                <Event_id>21</Event_id>
                <Quantity>1</Quantity>
                <Description>My Test Widget</
Description>
                <Sku>55555</Sku>
                <Unit_cost>15.00</Unit_cost>
            </InvoiceLineItem>
            <InvoiceLineItem>
                <Quantity>7</Quantity>
                <Description>My Other Test
Widget</Description>
                <Sku>66666</Sku>
                <Unit_cost>5.00</Unit_cost>
            </InvoiceLineItem>
        </InvoiceLineItems>
    </Invoice>
    <Invoice request_id="d4e5f6">
        <Contact_id>791</Contact_id>
        <Group_id>9</Group_id>

```

```

        <QuoteOrInvoice>Quote</QuoteOrInvoice>
        <Due_date>20120323</Due_date>
        <Description>Sample Invoice 2</Description>
        <InvoiceFooter>The quick brown fox jumps
over the lazy dog.</InvoiceFooter>
        <SalesRepContactID>123</SalesRepContactID>
        <ShipmentDate>2012-03-01</ShipmentDate>
        <ShipmentAdvancedDaysWorkflow>2</
ShipmentAdvancedDaysWorkflow>
        <ShipmentWorkflowID>1</ShipmentWorkflowID>
        <ShippingMethod>USPS</ShippingMethod>
        <InvoiceType>30 Day</InvoiceType>
        <InvoiceStatus>UNPAID</InvoiceStatus>
        <InvoiceLineItems>
            <InvoiceLineItem>
                <Quantity>1</Quantity>
                <Description>My Test Service</
Description>
                <Sku>77777</Sku>
                <Unit_cost>60.00</Unit_cost>
            </InvoiceLineItem>
            <InvoiceLineItem>
                <Quantity>1</Quantity>
                <Description>My Other Test
Service</Description>
                <Sku>88888</Sku>
                <Unit_cost>75.00</Unit_cost>
            </InvoiceLineItem>
        </InvoiceLineItems>
    </Invoice>
</Invoices>
</AddInvoicesRequest>

```

Successful Response

```

<AddInvoicesResponse>
    <Invoices>
        <Invoice request_id="a1b2c3">
            <Invoice_id>741</Invoice_id>
            <Result>Success</Result>
        </Invoice>
    </Invoices>
</AddInvoicesResponse>

```

```
        </Invoice>
        <Invoice request_id="d4e5f6">
            <Invoice_id>742</Invoice_id>
            <Result>Success</Result>
        </Invoice>
    </Invoices>
</AddInvoicesResponse>
```

Edit Invoices

This function allows the caller to update one or more invoices. To mark an invoice as paid, pass the Paid_date, TransactionID and Payment_amount arguments.

Input

- invoice_id (required)
- request_id (optional)
- QuoteOrInvoice (optional, 'Quote', 'Invoice', 'Purchase Order')
- ExternalID (optional)
- SalesRepContactID (optional)
- Group_id (optional)
- Due_date (optional, YYYYMMDD format)
- InvoiceType (optional)
- InvoiceStatus (optional)
- ShipmentAdvancedDaysWorkflow (optional)
- ShipmentWorkflowID (optional)
- ShipmentDate (optional, YYYY-MM-DD format)
- ShipToName (optional)
- ShipToAddress (optional)
- ShipToCity (optional)
- ShipToState (optional)
- ShipToZip (optional)
- ShipToCountry (optional)
- ShipToPhone (optional)

- ShippingMethod (optional)
- Description (optional)
- InvoiceFooter (optional)
- Paid_date (optional, YYYYMMDDHHmm format)
- TransactionID (optional, the transaction ID, for example the PayPal ID, of the invoice payment. Max length is 32 characters)
- Payment_amount (optional)
- AddInvoiceLineItems (optional)
 - Quantity (required)
 - Sku (optional)
 - Description (required)
 - Unit_cost (required)
 - Event_id (optional)
- EditInvoiceLineItems (optional)
 - line_item_id (required)
 - Quantity (required)
 - Sku (optional)
 - Description (required)
 - Unit_cost (required)
 - Event_id (optional)
- DeleteInvoiceLineItems (optional)
 - line_item_id (required)

Output

For each Invoice ID, success or failure.

Example Request

```
<EditInvoicesRequest>
  <Invoices>
    <Invoice invoice_id="741" request_id="a1b2c3">
      <QuoteOrInvoice>Invoice</QuoteOrInvoice>
      <ExternalID>1234</ExternalID>
      <SalesRepContactID>123</SalesRepContactID>
      <Group_id>8</Group_id>
```



```

        <Due_date>20120321</Due_date>
        <InvoiceType>30 Day</InvoiceType>
        <InvoiceStatus>PAID</InvoiceStatus>
        <ShipmentAdvancedDaysWorkflow>2</
ShipmentAdvancedDaysWorkflow>
        <ShipmentWorkflowID>1</ShipmentWorkflowID>
        <ShipmentDate>2012-03-01</ShipmentDate>
        <ShipToName>Jeff Gordon</ShipToName>
        <ShipToAddress>1 Gordon Road, Gordon
Street</ShipToAddress>
        <ShipToCity>Easy Gordon</ShipToCity>
        <ShipToState>CA</ShipToState>
        <ShipToZip>12345</ShipToZip>
        <ShipToCountry>United States</
ShipToCountry>
        <ShipToPhone>+12015550123</ShipToPhone>
        <ShippingMethod>USPS</ShippingMethod>
        <Description>Sample Invoice 1</Description>
        <InvoiceFooter><![CDATA[<p>The
<strong>quick </strong><em>brown </em><u>fox </u>jumps over
the lazy dog.</p><p>The <strong>quick </strong><em>brown </
em><u>fox </u>jumps over the lazy dog.</p>]]></
InvoiceFooter>
        <Paid_date>201203121423</Paid_date>
        <TransactionID>1234554321</TransactionID>
        <Payment_amount>50.00</Payment_amount>
        <AddInvoiceLineItems>
            <InvoiceLineItem>
                <Quantity>3</Quantity>
                <Description>My Test Service</
Description>
                <Sku>1111</Sku>
                <Unit_cost>10.00</Unit_cost>
            </InvoiceLineItem>
            <InvoiceLineItem>
                <Quantity>3</Quantity>
                <Description>Another Test Service</
Description>
                <Sku>2222</Sku>
                <Unit_cost>10.00</Unit_cost>

```

```

        </InvoiceLineItem>
    </AddInvoiceLineItems>
    <EditInvoiceLineItems>
        <InvoiceLineItem line_item_id="68">
            <Quantity>3</Quantity>
            <Description>My Test Service</
Description>
                <Sku>1111</Sku>
                <Unit_cost>10.00</Unit_cost>
            </InvoiceLineItem>
            <InvoiceLineItem line_item_id="69">
                <Quantity>3</Quantity>
                <Description>My Other Test
Service</Description>
                    <Sku>2222</Sku>
                    <Unit_cost>10.00</Unit_cost>
                </InvoiceLineItem>
            </EditInvoiceLineItems>
            <DeleteInvoiceLineItems>
                <InvoiceLineItem line_item_id="70"></
InvoiceLineItem>
                    <InvoiceLineItem line_item_id="71"></
InvoiceLineItem>
                        </DeleteInvoiceLineItems>
                    </Invoice>
                <Invoice invoice_id="742" request_id="d4e5f6">
                    <QuoteOrInvoice>Quote</QuoteOrInvoice>
                    <SalesRepContactID>123</SalesRepContactID>
                    <Group_id>9</Group_id>
                    <Due_date>20120323</Due_date>
                    <InvoiceType>30 Day</InvoiceType>
                    <InvoiceStatus>UNPAID</InvoiceStatus>
                    <ShipmentAdvancedDaysWorkflow>2</
ShipmentAdvancedDaysWorkflow>
                        <ShipmentWorkflowID>1</ShipmentWorkflowID>
                        <ShipmentDate>2012-03-01</ShipmentDate>
                        <ShippingMethod>USPS</ShippingMethod>
                        <Description>Sample Invoice 2</Description>
                        <InvoiceFooter>The quick brown fox jumps
over the lazy dog.</InvoiceFooter>

```

```
        </Invoice>
    </Invoices>
</EditInvoicesRequest>
```

Example Request (Mark an invoice as paid)

```
<EditInvoicesRequest>
  <Invoices>
    <Invoice invoice_id="741">
      <Paid_date>201203121423</Paid_date>
      <TransactionID>1234554321</TransactionID>
      <Payment_amount>50.00</Payment_amount>
    </Invoice>
  </Invoices>
</EditInvoicesRequest>
```

Successful Response

```
<EditInvoicesResponse>
  <Invoices>
    <Invoice request_id="a1b2c3">
      <Result>Success</Result>
      <InvoiceID>741</InvoiceID>
      <AddInvoiceLineItems>
        <InvoiceLineItem>
          <Result>Success</Result>
          <LineItemID>73</LineItemID>
        </InvoiceLineItem>
        <InvoiceLineItem>
          <Result>Success</Result>
          <LineItemID>74</LineItemID>
        </InvoiceLineItem>
      </AddInvoiceLineItems>
      <EditInvoiceLineItems>
        <InvoiceLineItem>
          <Result>Success</Result>
          <LineItemID>68</LineItemID>
        </InvoiceLineItem>
        <InvoiceLineItem>
          <Result>Error</Result>
          <ErrorCode>3401</ErrorCode>
        </InvoiceLineItem>
      </EditInvoiceLineItems>
    </Invoice>
  </Invoices>
</EditInvoicesResponse>
```

```

                                <ErrorText>Line item #69 does not
exists</ErrorText>
                                </InvoiceLineItem>
                            </EditInvoiceLineItems>
                        <DeleteInvoiceLineItems>
                            <InvoiceLineItem>
                                <Result>Success</Result>
                                <LineItemID>70</LineItemID>
                            </InvoiceLineItem>
                            <InvoiceLineItem>
                                <Result>Success</Result>
                                <LineItemID>71</LineItemID>
                            </InvoiceLineItem>
                        </DeleteInvoiceLineItems>
                    </Invoice>
                <Invoice request_id="d4e5f6">
                    <Result>Success</Result>
                    <InvoiceID>742</InvoiceID>
                </Invoice>
            </Invoices>
        </EditInvoicesResponse>

```

Delete Invoices

This function allows the caller to delete one or more invoices from the database.

Input

Specify search criteria within each invoice tag. Search criteria can be:

- request_id (optional)
- invoice_id
- contact_id
- contact_firstname
- contact_lastname

Each invoice's search criteria must return a single unique invoice to modify.

Output

For each Invoice ID, success or failure.

Example Request

```
<DeleteInvoicesRequest>
  <Invoices>
    <Invoice invoice_id="1221" request_id="a1b2c3" /
  >
    <Invoice invoice_id="1222" request_id="d4e5f6" /
  >
  </Invoices>
</DeleteInvoicesRequest>
```

Successful Response

```
<DeleteInvoicesResponse>
  <Invoices>
    <Invoice request_id="a1b2c3">
      <Invoice_id>1221</Invoice_id>
      <Result>Success</Result>
    </Invoice>
    <Invoice request_id="d4e5f6">
      <Invoice_id>1222</Invoice_id>
      <Result>Success</Result>
    </Invoice>
  </Invoices>
</DeleteInvoicesResponse>
```

Spec - Journeys

Table Of Contents

- Get Journeys
- Pause Journey
- Resume Journey
- Get All Journeys

Get Journeys

This API fetches the journeys for an account.

Input

- account_id (required for shared access users)
- group_id (required for shared access users)

Output

Success or failure. List of journeys.

- JourneyID
- JourneyName

Example Request

```
<GetJourneysRequest></GetJourneysRequest>
```

Example Request (shared access users)

```
<GetJourneysRequest account_id="12345" group_id="1"></  
GetJourneysRequest>
```

Successful Response

```
<GetJourneysResponse>
```

```

<Result>Success</Result>
<Journeys>
  <Journey>
    <JourneyID>1</JourneyID>
    <JourneyName>Journey Users</JourneyName>
  </Journey>
  <Journey>
    <JourneyID>2</JourneyID>
    <JourneyName>Send Postcard</JourneyName>
  </Journey>
  <Journey>
    <JourneyID>3</JourneyID>
    <JourneyName>Requested Demo</JourneyName>
  </Journey>
</Journeys>
</GetJourneysResponse>

```

Pause Journey

This API pauses the journey for one or more contacts.

Input

- account_id (required for shared access users)
- group_id (required for shared access users)
- journey_id (required)
- request_id (optional)
- Contact_id (required)

Output

Success or failure. List of contacts with their JourneyID and ContactID.

Example Request (single contact)

```

<PauseJourneyRequest journey_id="1">
  <Contacts>
    <Contact_id>123</Contact_id>
  </Contacts>
</PauseJourneyRequest>

```

```
    </Contacts>
</PauseJourneyRequest>
```

Example Request (multiple contacts)

```
<PauseJourneyRequest journey_id="1">
  <Contacts>
    <Contact_id request_id="a1b2c3">123</Contact_id>
    <Contact_id request_id="d4e5f6">623</Contact_id>
  </Contacts>
</PauseJourneyRequest>
```

Example Request (shared access users)

```
<PauseJourneyRequest account_id="12345" group_id="1"
journey_id="1">
  <Contacts>
    <Contact_id>123</Contact_id>
    <Contact_id>623</Contact_id>
  </Contacts>
</PauseJourneyRequest>
```

Successful Response

```
<PauseJourneyResponse>
  <Contacts>
    <Contact request_id="a1b2c3">
      <Result>Success</Result>
      <JourneyID>1</JourneyID>
      <ContactID>123</ContactID>
    </Contact>
    <Contact request_id="d4e5f6">
      <Result>Success</Result>
      <JourneyID>1</JourneyID>
      <ContactID>623</ContactID>
    </Contact>
  </Contacts>
</PauseJourneyResponse>
```

Resume Journey

This API resumes the journey for one or more contacts.

Input

- account_id (required for shared access users)
- group_id (required for shared access users)
- journey_id (required)
- request_id (optional)
- Contact_id (required)

Output

Success or failure. List of contacts with their JourneyID and ContactID.

Example Request (single contact)

```
<ResumeJourneyRequest journey_id="1">
  <Contacts>
    <Contact_id>123</Contact_id>
  </Contacts>
</ResumeJourneyRequest>
```

Example Request (multiple contacts)

```
<ResumeJourneyRequest journey_id="1">
  <Contacts>
    <Contact_id request_id="a1b2c3">123</Contact_id>
    <Contact_id request_id="d4e5f6">623</Contact_id>
  </Contacts>
</ResumeJourneyRequest>
```

Example Request (shared access users)

```
<ResumeJourneyRequest account_id="12345" group_id="1"
journey_id="1">
  <Contacts>
    <Contact_id>123</Contact_id>
    <Contact_id>623</Contact_id>
  </Contacts>
```

```
</ResumeJourneyRequest>
```

Successful Response

```
<ResumeJourneyResponse>
  <Contacts>
    <Contact request_id="a1b2c3">
      <Result>Success</Result>
      <JourneyID>1</JourneyID>
      <ContactID>123</ContactID>
    </Contact>
    <Contact request_id="d4e5f6">
      <Result>Success</Result>
      <JourneyID>1</JourneyID>
      <ContactID>623</ContactID>
    </Contact>
  </Contacts>
</ResumeJourneyResponse>
```

Get All Journeys

This API fetches the journeys and journeys progress for a single contact.

Input

- contact_id (required)
- account_id (required for shared access users)
- group_id (required for shared access users)

Output

Success or failure. List of journeys and journey progress items.

Example Request

```
<GetAllJourneysRequest contact_id="1"></
GetAllJourneysRequest>
```

Example Request (shared access users)

```
<GetAllJourneysRequest account_id="12345" group_id="1"
contact_id="1"></GetAllJourneysRequest>
```

Successful Response

```
<GetAllJourneysResponse>
  <Result>Success</Result>
  <Journeys>
    <Journey>
      <JourneyID>12</JourneyID>
      <JourneyName>JourneyFlow Users</JourneyName>
      <JourneysProgress>
        <JourneyProgress>
          <OperatorTitle>Start Journey</
OperatorTitle>

          <DatetimeReachedCurrentOperator>20170315152210</
DatetimeReachedCurrentOperator>
          <Notes></Notes>
          <Paused>N</Paused>
        </JourneyProgress>
      <JourneyProgress>
        <OperatorTitle>Decision :: User160
(Account Status) contains Active</OperatorTitle>

        <DatetimeReachedCurrentOperator>20170315152506</
DatetimeReachedCurrentOperator>
        <Notes></Notes>
        <Paused>N</Paused>
      </JourneyProgress>
    <JourneyProgress>
      <OperatorTitle>Action :: Send Email ::
Media File #7092 :: DRIP #1</OperatorTitle>

      <DatetimeReachedCurrentOperator>20170315152610</
DatetimeReachedCurrentOperator>
      <Notes></Notes>
      <Paused>N</Paused>
      <Read>Y</Read>
      <Click>N</Click>
```

```

        <Unsub>N</Unsub>
        <Bounce>N</Bounce>
    </JourneyProgress>
    <JourneyProgress>
        <OperatorTitle>Delay :: 48 Hours</
OperatorTitle>

<DatetimeReachedCurrentOperator>20170315152905</
DatetimeReachedCurrentOperator>
        <Notes>Email sent successfully</Notes>
        <Paused>N</Paused>
    </JourneyProgress>
    <JourneyProgress>
        <OperatorTitle>Decision :: Read
Previous Email</OperatorTitle>

<DatetimeReachedCurrentOperator>20170317153014</
DatetimeReachedCurrentOperator>
        <Notes></Notes>
        <Paused>N</Paused>
    </JourneyProgress>
    <JourneyProgress>
        <OperatorTitle>Action :: Send Email ::
Media File #7098 :: DRIP #2</OperatorTitle>

<DatetimeReachedCurrentOperator>20170317153305</
DatetimeReachedCurrentOperator>
        <Notes></Notes>
        <Paused>N</Paused>
        <Read>Y</Read>
        <Click>N</Click>
        <Unsub>N</Unsub>
        <Bounce>N</Bounce>
    </JourneyProgress>
    <JourneyProgress>
        <OperatorTitle>Delay :: 48 Hours</
OperatorTitle>

<DatetimeReachedCurrentOperator>20170317153410</
DatetimeReachedCurrentOperator>
```

```
        <Notes></Notes>
        <Paused>N</Paused>
    </JourneyProgress>
</JourneysProgress>
</Journey>
</Journeys>
</GetAllJourneysResponse>
```

Spec - Media Library

Table Of Contents

- Upload Media
- Get Media Library Request

Upload Media

This function allows the caller to upload media into the account.

Input

- account_id (required for shared access users)
- group_id (required)
- MediaFolder (required)
- Filename (required)
- Content (required)
- Type (Files, Images, Videos, Articles, Documents)
- Description
- ContactsCanView (Y/N)
- PublicCanView (Y/N)

Output

Success or error. MediaID.

Example Request

```
<UploadMediaRequest group_id="1">
  <Type>Images</Type>
  <MediaFolder>Social Uploads</MediaFolder>
  <Filename>27384.jpg</Filename>
  <Content>(base64 encoded file contents)</Content>
```

```
<Description>Logo</Description>
<ContactsCanView>Y</ContactsCanView>
<PublicCanView>Y</PublicCanView>
</UploadMediaRequest>
```

Example Request (shared access)

```
<UploadMediaRequest account_id="38193" group_id="1">
  <Type>Images</Type>
  <MediaFolder>Social Uploads</MediaFolder>
  <Filename>27384.jpg</Filename>
  <Content>(base64 encoded file contents)</Content>
  <Description>Logo</Description>
  <ContactsCanView>Y</ContactsCanView>
  <PublicCanView>Y</PublicCanView>
</UploadMediaRequest>
```

Successful Response

```
<UploadMediaResponse>
  <Result>Success</Result>
  <MediaID>30</MediaID>
</UploadMediaResponse>
```

Get Media Library Request

This function allows the caller to get info about a group's media library.

Input

- account_id (required for shared access users)
- group_id (required)

Output

Returns a list of media file metadata for the group.

- MediaID
- Filename

- Description
- Folder
- Type
- Size (KB)

Example Request

```
<GetMediaLibraryRequest group_id="1"></
GetMediaLibraryRequest>
```

Example Request (shared access)

```
<GetMediaLibraryRequest account_id="38193" group_id="1"></
GetMediaLibraryRequest>
```

Successful Response

```
<GetMediaLibraryResponse>
  <Result>Success</Result>
  <Media>
    <MediaID>25</MediaID>
    <Filename>Media25.png</Filename>
    <Description>some file</Description>
    <Folder>My Files</Folder>
    <Type>Files</Type>
    <Size>1</Size>
  </Media>
  <Media>
    <MediaID>1</MediaID>
    <Filename>Media1.png</Filename>
    <Description>my picture</Description>
    <Folder>Social Uploads</Folder>
    <Type>Images</Type>
    <Size>12</Size>
  </Media>
</GetMediaLibraryResponse>
```


Spec - Opportunities

Table Of Contents

- Get Opportunities
- Add Opportunities
- Edit Opportunities
- Delete Opportunities
- Get Sources
- Add Sources
- Edit Sources
- Delete Sources
- Get Phases
- Add Phases
- Edit Phases
- Delete Phases
- Get Phase Paths
- Get Products
- Add Products
- Edit Products
- Delete Products
- Get Custom Fields
- Add Custom Fields
- Edit Custom Fields
- Delete Custom Fields

Get Opportunities

This function allows the caller to retrieve a contact's opportunities from the database.

Search parameters should be specified inside the tag.

Contacts permission is required for shared access users.

phase_id is a unique ID assigned to that particular phase. It is NOT the phase number, which is used to organize phases into a sequence. You can find both when you log into your GreenRope account and go to Settings - Opportunity Settings.

Input

- account_id (required for shared access)
- opportunity_id
- contact_id
- company_id
- group_id
- phase ('closed' for filtering closed opportunities)
- phase_id
- phase_path_id
- get_all (get opportunities and associated opportunities for a contact, contact_id required)
- close_date_start
- close_date_end
- managed_by_contact_id
- show_associated (show associated opportunities)
- show_assignables (show list of assignable contacts to an opportunity)

Output

Success or failure. A list of opportunities.

Example Request

```
<GetOpportunitiesRequest contact_id="123"></GetOpportunitiesRequest>
```

Example Request

```
<GetOpportunitiesRequest contact_id="123" get_all="true"
show_assignables="true"></GetOpportunitiesRequest>
```

Example Request

```
<GetOpportunitiesRequest contact_id="123"
close_date_start="20150101" close_date_end="20150131"></
GetOpportunitiesRequest>
```

Example Request

```
<GetOpportunitiesRequest opportunity_id="13"></
GetOpportunitiesRequest>
```

Example Request

```
<GetOpportunitiesRequest group_id="4" company_id="123"></
GetOpportunitiesRequest>
```

Example Request

```
<GetOpportunitiesRequest contact_id="123"
show_associated="true"></GetOpportunitiesRequest>
```

Example Request (filter by phase_path_id)

```
<GetOpportunitiesRequest contact_id="123"
phase_path_id="5"></GetOpportunitiesRequest>
```

Example Request (filter by managed_by_contact_id)

```
<GetOpportunitiesRequest managed_by_contact_id="0"></
GetOpportunitiesRequest>
```

Example Request (filter only the opportunities that are closed (Closed - Deal Won and Closed - Deal Lost))

```
<GetOpportunitiesRequest phase="closed"></
GetOpportunitiesRequest>
```

Example Request (shared access)

```
<GetOpportunitiesRequest contact_id="123"
account_id="12345"></GetOpportunitiesRequest>
```

Successful Response

```
<GetOpportunitiesResponse>
  <Result>Success</Result>
  <Opportunities>
    <Opportunity>
      <OpportunityID>8</OpportunityID>
      <Title>test</Title>
      <GroupID>0</GroupID>
      <AssignedToContactID>123</AssignedToContactID>
      <AssignedToCompanyID>13</AssignedToCompanyID>
      <AssignedToFirstname>Testfirst1 & and " ' </
AssignedToFirstname>
      <AssignedToLastname>Test1 & 2</
AssignedToLastname>
      <AssignedToEmail>contact+test1@gmail.com</
AssignedToEmail>
      <ManagedByContactID>0</ManagedByContactID>
      <Firstname></Firstname>
      <Lastname></Lastname>
      <Email></Email>
      <SourceID>4</SourceID>
      <Source>Networking</Source>
      <PhaseID>4</PhaseID>
      <Phase>Proposal</Phase>
      <PhaseNumber>4</PhaseNumber>
      <PhasePathID>2</PhasePathID>
      <PhasePathName>Sales Pipeline</PhasePathName>
      <WarningDays>10</WarningDays>
      <DatetimeCreated>2024-03-07 07:19:53</
DatetimeCreated>
      <AssociatedContacts>
        <AssociatedContact>
          <ContactID>7</ContactID>
          <Firstname>Bob</Firstname>
          <Lastname>Associated</Lastname>
          <Email>associated@contact.com</Email>
          <Notes>A note</Notes>
        </AssociatedContact>
```

```

</AssociatedContacts>
<CustomFields>
  <CustomField>
    <CustomFieldID>1</CustomFieldID>
    <FieldName>My Custom Field</FieldName>
    <FieldValue>yellow</FieldValue>
  </CustomField>
  <CustomField>
    <CustomFieldID>9</CustomFieldID>
    <FieldName>Age</FieldName>
    <FieldValue>11 years, 2 months, 20
days</FieldValue>
  </CustomField>
</CustomFields>
<Products>
  <Product>
    <ProductID>1</ProductID>
    <Product>Sample Product</Product>
    <ProductNotes></ProductNotes>
    <ProductValue>0.00</ProductValue>
    <DefaultValue></DefaultValue>
  </Product>
  <Product>
    <ProductID>2</ProductID>
    <Product>Sample Service</Product>
    <ProductNotes>good test</ProductNotes>
    <ProductValue>100.00</ProductValue>
    <DefaultValue></DefaultValue>
  </Product>
</Products>
<Quality>A</Quality>
<OpportunityCurrency>USD</OpportunityCurrency>
<OpportunityValue>0.00</OpportunityValue>
<OpportunityProfit>0.00</OpportunityProfit>
<PercentWin>10</PercentWin>
<InvoiceID></InvoiceID>
<CloseDate>20150124</CloseDate>
<Notes>The quick brown fox jumps over the lazy
dog.</Notes>
</Opportunity>

```

```
</Opportunities>
</GetOpportunitiesResponse>
```

Add Opportunities

This function allows the caller to add one or more opportunities for a contact.

Contacts permission is required for shared access users.

If an opportunity phase is paired with a workflow, the specified workflow will be activated.

Input

- account_id (required for shared access)
- request_id (optional)
- Title
- GroupID
- ContactID
- ManagedByContactID
- Quality
- SourceID / Source (uses the first matching source title)
- PhaseID / Phase (uses the first matching phase title) /
PhaseNumber (uses the first matching phase number)
- PhasePathID / PhasePath (uses the first matching phase path title)
- OpportunityCurrency
- OpportunityValue
- OpportunityProfit
- PercentWin
- CloseDate
- AssociatedContacts
 - ContactID
 - Notes
- CustomFields

- fieldnum / fieldname (uses the first matching field title)
- value
- Products
 - ProductID / Title (uses the first matching product title)
 - ProductNotes
 - ProductValue
- Notes

Output

Success or failure for each opportunities. List of opportunities.

Example Request

```
<AddOpportunitiesRequest>
  <Opportunities>
    <Opportunity request_id="a1b2c3">
      <Title>Test</Title>
      <GroupID>1</GroupID>
      <ContactID>123</ContactID>
      <ManagedByContactID>0</ManagedByContactID>
      <Quality>A</Quality>
      <SourceID>1</SourceID>
      <PhaseID>1</PhaseID>
      <OpportunityValue>5.12</OpportunityValue>
      <OpportunityProfit>12.34</OpportunityProfit>
      <PercentWin>10</PercentWin>
      <CloseDate>20150414</CloseDate>
      <AssociatedContacts>
        <AssociatedContact>
          <ContactID>7</ContactID>
          <Notes>A note</Notes>
        </AssociatedContact>
      </AssociatedContacts>
      <CustomFields>
        <CustomField fieldnum=\"1\">b</CustomField>
        <CustomField fieldname=\"My Custom
Field\">c</CustomField>
```

```

        </CustomFields>
        <Products>
            <Product>
                <ProductID>2</ProductID>
                <ProductNotes>Sample product notes</
ProductNotes>
                <ProductValue>3</ProductValue>
            </Product>
        </Products>
        <Notes>The quick brown fox jumps over the lazy
dog.</Notes>
    </Opportunity>
</Opportunities>
</AddOpportunitiesRequest>

```

Example Request (lookup source/phase/product by title)

```

<AddOpportunitiesRequest>
    <Opportunities>
        <Opportunity>
            <Title>Test</Title>
            <GroupID>1</GroupID>
            <ContactID>123</ContactID>
            <ManagedByContactID>0</ManagedByContactID>
            <Quality>A</Quality>
            <Source>Networking</Source>
            <Phase>New Lead</Phase>
            <PhasePath>Path A</PhasePath>
            <OpportunityCurrency>GBP</OpportunityCurrency>
            <OpportunityValue>5.12</OpportunityValue>
            <OpportunityProfit>12.34</OpportunityProfit>
            <PercentWin>10</PercentWin>
            <CloseDate>20150414</CloseDate>
            <AssociatedContacts>
                <AssociatedContact>
                    <ContactID>7</ContactID>
                    <Notes>A note</Notes>
                </AssociatedContact>
            </AssociatedContacts>
            <CustomFields>

```



```

        <CustomField fieldnum=\"1\">b</CustomField>
        <CustomField fieldname=\"My Custom
Field\">c</CustomField>
    </CustomFields>
    <Products>
        <Product>
            <Title>Sample Product</Title>
            <ProductNotes>Sample product notes</
ProductNotes>
            <ProductValue>3</ProductValue>
        </Product>
    </Products>
    <Notes>The quick brown fox jumps over the lazy
dog.</Notes>
</Opportunity>
</Opportunities>
</AddOpportunitiesRequest>

```

Example Request (shared access)

```

<AddOpportunitiesRequest>
    <Opportunities>
        <Opportunity account_id="12345">
            <Title>Test</Title>
            <GroupID>1</GroupID>
            <ContactID>123</ContactID>
            <ManagedByContactID>0</ManagedByContactID>
            <Quality>A</Quality>
            <Source>Networking</Source>
            <PhaseNumber>1</PhaseNumber>
            <PhasePath>Path A</PhasePath>
            <OpportunityCurrency>GBP</OpportunityCurrency>
            <OpportunityValue>5.12</OpportunityValue>
            <OpportunityProfit>12.34</OpportunityProfit>
            <PercentWin>10</PercentWin>
            <CloseDate>20150414</CloseDate>
            <AssociatedContacts>
                <AssociatedContact>
                    <ContactID>7</ContactID>
                    <Notes>A note</Notes>
                </AssociatedContact>
            </AssociatedContacts>
        </Opportunity>
    </Opportunities>
</AddOpportunitiesRequest>

```

```

        </AssociatedContact>
    </AssociatedContacts>
    <CustomFields>
        <CustomField fieldnum=\"1\">b</CustomField>
        <CustomField fieldname=\"My Custom
Field\">c</CustomField>
    </CustomFields>
    <Products>
        <Product>
            <Title>Sample Product</Title>
            <ProductNotes>Sample product notes</
ProductNotes>
            <ProductValue>3</ProductValue>
        </Product>
    </Products>
    <Notes>The quick brown fox jumps over the lazy
dog.</Notes>
</Opportunity>
</Opportunities>
</AddOpportunitiesRequest>

```

Successful Response

```

<AddOpportunitiesResponse>
    <Opportunities>
        <Opportunity request_id="a1b2c3">
            <Result>Success</Result>
            <OpportunityID>22</OpportunityID>
            <Title>Test</Title>
            <GroupID>1</GroupID>
            <ManagedByContactID>0</ManagedByContactID>
            <Quality>A</Quality>
            <SourceID>1</SourceID>
            <PhaseID>1</PhaseID>
            <PhasePathID>2</PhasePathID>
            <OpportunityCurrency>USD</OpportunityCurrency>
            <OpportunityValue>5.12</OpportunityValue>
            <OpportunityProfit>12.34</OpportunityProfit>
            <PercentWin>10</PercentWin>
            <CloseDate>20150414</CloseDate>
        </Opportunity>
    </Opportunities>
</AddOpportunitiesResponse>

```

```

    <AssociatedContacts>
      <AssociatedContact>
        <ContactID>7</ContactID>
        <Notes>A note</Notes>
      </AssociatedContact>
    </AssociatedContacts>
    <CustomFields>
      <CustomField>
        <CustomFieldID>1</CustomFieldID>
        <FieldName>My Custom Field</FieldName>
        <FieldValue>b</FieldValue>
      </CustomField>
      <CustomField>
        <CustomFieldID>1</CustomFieldID>
        <FieldName>My Custom Field</FieldName>
        <FieldValue>c</FieldValue>
      </CustomField>
    </CustomFields>
    <Products>
      <Product>
        <ProductID>2</ProductID>
        <ProductNotes></ProductNotes>
        <ProductValue></ProductValue>
      </Product>
    </Products>
  </Opportunity>
</Opportunities>
</AddOpportunitiesResponse>

```

Edit Opportunities

This function allows the caller to modify one or more opportunities already in the database.

Search parameters should be specified inside the tag, while parameters to change to would be specified individually.

If no Products or CustomFields tags are passed, any pre-existing opportunity product and custom field data is left in place. If empty

AssociatedContacts, Products or CustomFields tags are passed, pre-existing opportunity associated contact, product and custom field data is removed. If new associated contacts, products or customfields are passed any existing ones will be removed and replaced with the new ones.

Contacts permission is required for shared access users.

If an opportunity phase is paired with a workflow, the specified workflow will be activated.

If the opportunity is linked to event(s), updating the CloseDate will also update the linked event's date.

Input

- account_id (required for shared access)
- opportunity_id
- request_id (optional)
- Title
- GroupID
- ManagedByContactID
- Quality
- SourceID / Source (uses the first matching source title)
- PhaseID / Phase (uses the first matching phase title) /
PhaseNumber (uses the first matching phase number)
- PhasePathID / PhasePath (uses the first matching phase title)
- OpportunityValue
- OpportunityProfit
- PercentWin
- CloseDate
- AssociatedContacts
 - ContactID
 - Notes
- CustomFields

- fieldnum / fieldname (uses the first matching field title)
- value
- Products
 - ProductID / Title (uses the first matching product title)
 - ProductNotes
 - ProductValue
- Notes

Output

Success or failure for each opportunities. List of opportunities.

Example Request

```
<EditOpportunitiesRequest>
  <Opportunities>
    <Opportunity opportunity_id="20"
request_id="a1b2c3">
      <Title>Test</Title>
      <GroupID>1</GroupID>
      <ManagedByContactID>0</ManagedByContactID>
      <Quality>A</Quality>
      <SourceID>1</SourceID>
      <PhaseID>1</PhaseID>
      <PhasePathID>1</PhasePathID>
      <OpportunityValue>5.12</OpportunityValue>
      <OpportunityProfit>12.34</OpportunityProfit>
      <PercentWin>10</PercentWin>
      <CloseDate>20150414</CloseDate>
      <AssociatedContacts>
        <AssociatedContact>
          <ContactID>7</ContactID>
          <Notes>B note</Notes>
        </AssociatedContact>
      </AssociatedContacts>
      <CustomFields>
        <CustomField fieldnum=\"1\">b</CustomField>
```

```

        <CustomField fieldname=\"My Custom
Field\">c</CustomField>
    </CustomFields>
    <Products>
        <Product>
            <ProductID>2</ProductID>
            <ProductNotes>edited sample product
notes</ProductNotes>
            <ProductValue>4</ProductValue>
        </Product>
    </Products>
    <Notes>The quick brown fox jumps over the lazy
dog.</Notes>
</Opportunity>
</Opportunities>
</EditOpportunitiesRequest>

```

Example Request (lookup source/phase/product by title)

```

<EditOpportunitiesRequest>
    <Opportunities>
        <Opportunity opportunity_id="20">
            <Title>Test</Title>
            <GroupID>1</GroupID>
            <ManagedByContactID>0</ManagedByContactID>
            <Quality>A</Quality>
            <Source>Networking</Source>
            <Phase>New Lead</Phase>
            <PhasePath>Path 1</PhasePath>
            <OpportunityValue>5.12</OpportunityValue>
            <OpportunityProfit>12.34</OpportunityProfit>
            <PercentWin>10</PercentWin>
            <CloseDate>20150414</CloseDate>
            <AssociatedContacts>
                <AssociatedContact>
                    <ContactID>7</ContactID>
                    <Notes>B note</Notes>
                </AssociatedContact>
            </AssociatedContacts>
        </Opportunity>
    </Opportunities>
    <CustomFields>

```

```

        <CustomField fieldnum=\"1\">b</CustomField>
        <CustomField fieldname=\"My Custom
Field\">c</CustomField>
    </CustomFields>
    <Products>
        <Product>
            <Title>Sample Product</Title>
            <ProductNotes>edited sample product
notes</ProductNotes>
            <ProductValue>4</ProductValue>
        </Product>
    </Products>
    <Notes>The quick brown fox jumps over the lazy
dog.</Notes>
</Opportunity>
</Opportunities>
</EditOpportunitiesRequest>

```

Example Request (shared access)

```

<EditOpportunitiesRequest>
    <Opportunities>
        <Opportunity opportunity_id="20"
account_id="12345">
            <Title>Test</Title>
            <GroupID>1</GroupID>
            <ManagedByContactID>0</ManagedByContactID>
            <Quality>A</Quality>
            <Source>Networking</Source>
            <PhaseNumber>1</PhaseNumber>
            <PhasePathID>1</PhasePathID>
            <OpportunityValue>5.12</OpportunityValue>
            <OpportunityProfit>12.34</OpportunityProfit>
            <PercentWin>10</PercentWin>
            <CloseDate>20150414</CloseDate>
            <AssociatedContacts>
                <AssociatedContact>
                    <ContactID>7</ContactID>
                    <Notes>B note</Notes>
                </AssociatedContact>
            </AssociatedContacts>
        </Opportunity>
    </Opportunities>
</EditOpportunitiesRequest>

```

```

        </AssociatedContacts>
        <CustomFields>
            <CustomField fieldnum=\"1\">b</CustomField>
            <CustomField fieldname=\"My Custom
Field\">c</CustomField>
        </CustomFields>
        <Products>
            <Product>
                <Title>Sample Product</Title>
                <ProductNotes>edited sample product
notes</ProductNotes>
                <ProductValue>4</ProductValue>
            </Product>
        </Products>
        <Notes>The quick brown fox jumps over the lazy
dog.</Notes>
    </Opportunity>
</Opportunities>
</EditOpportunitiesRequest>

```

Example Response

```

<EditOpportunitiesResponse>
    <Opportunities>
        <Opportunity request_id="a1b2c3">
            <Result>Success</Result>
            <OpportunityID>22</OpportunityID>
            <Title>Test</Title>
            <GroupID>1</GroupID>
            <ManagedByContactID>0</ManagedByContactID>
            <Quality>A</Quality>
            <SourceID>1</SourceID>
            <PhaseID>1</PhaseID>
            <PhasePathID>1</PhasePathID>
            <OpportunityValue>5.12</OpportunityValue>
            <OpportunityProfit>12.34</OpportunityProfit>
            <PercentWin>10</PercentWin>
            <CloseDate>20150414</CloseDate>
            <AssociatedContacts>
                <AssociatedContact>

```



```

        <ContactID>7</ContactID>
        <Notes>B note</Notes>
    </AssociatedContact>
</AssociatedContacts>
<CustomFields>
    <CustomField>
        <CustomFieldID>1</CustomFieldID>
        <FieldName>My Custom Field</FieldName>
        <FieldValue>b</FieldValue>
    </CustomField>
    <CustomField>
        <CustomFieldID>1</CustomFieldID>
        <FieldName>My Custom Field</FieldName>
        <FieldValue>c</FieldValue>
    </CustomField>
</CustomFields>
<Products>
    <Product>
        <ProductID>2</ProductID>
        <ProductNotes>edited sample product
notes</ProductNotes>
        <ProductValue>4</ProductValue>
    </Product>
</Products>
</Opportunity>
</Opportunities>
</EditOpportunitiesResponse>

```

Delete Opportunities

This function allows the caller to delete one or more opportunities from the database.

Search parameters should be specified inside the tag.

Contacts permission is required for shared access users.

Input

- opportunity_id
- request_id (optional)

Output

Success or failure for each opportunities. List of opportunities.

Example Request

```
<DeleteOpportunitiesRequest>
  <Opportunities>
    <Opportunity opportunity_id="20"
request_id="a1b2c3"/>
  </Opportunities>
</DeleteOpportunitiesRequest>
```

Example Response

```
<DeleteOpportunitiesResponse>
  <Opportunities>
    <Opportunity request_id="a1b2c3">
      <Result>Success</Result>
      <OpportunityID>22</OpportunityID>
    </Opportunity>
  </Opportunities>
</DeleteOpportunitiesResponse>
```

Get Sources

This function allows the caller to retrieve a contact's opportunity sources from the database.

Search parameters should be specified inside the tag.

Contacts permission is required for shared access users.

Input

- account_id (required for shared access)
- source_id
- source_title

Output

Success or failure. A list of sources.

Example Request

```
<GetSourcesRequest></GetSourcesRequest>
```

Example Request

```
<GetSourcesRequest source_id="1"></GetSourcesRequest>
```

Example Request

```
<GetSourcesRequest source_title="Networking"></GetSourcesRequest>
```

Example Request (shared access)

```
<GetSourcesRequest account_id="12345"></GetSourcesRequest>
```

Successful Response

```
<GetSourcesResponse>
  <Result>Success</Result>
  <Sources>
    <Source>
      <SourceID>5</SourceID>
      <Title>Cold Call</Title>
    </Source>
    <Source>
      <SourceID>2</SourceID>
      <Title>Internet Search</Title>
    </Source>
    <Source>
      <SourceID>4</SourceID>
      <Title>Networking</Title>
    </Source>
  </Sources>
</GetSourcesResponse>
```

```
</Source>
<Source>
  <SourceID>1</SourceID>
  <Title>Referral</Title>
</Source>
<Source>
  <SourceID>3</SourceID>
  <Title>Social Network</Title>
</Source>
<Source>
  <SourceID>7</SourceID>
  <Title>Test Source</Title>
</Source>
<Source>
  <SourceID>12</SourceID>
  <Title>tttt</Title>
</Source>
</Sources>
</GetSourcesResponse>
```

Add Sources

This function allows the caller to add one or more opportunity sources.

Contacts permission is required for shared access users.

Input

- account_id (required for shared access)
- request_id (optional)
- Title

Output

Success or failure for each sources. List of sources.

Example Request

```
<AddSourcesRequest>
  <Sources>
    <Source request_id="alb2c3">
      <Title>Sample Title</Title>
    </Source>
  </Sources>
</AddSourcesRequest>
```

Successful Response

```
<AddSourcesResponse>
  <Sources>
    <Source request_id="alb2c3">
      <Result>Success</Result>
      <SourceID>15</SourceID>
      <Title>Sample Title</Title>
    </Source>
  </Sources>
</AddSourcesResponse>
```

Edit Sources

This function allows the caller to modify one or more opportunity sources already in the database.

Search parameters should be specified inside the tag, while parameters to change to would be specified individually.

Contacts permission is required for shared access users.

Input

- account_id (required for shared access)
- source_id
- request_id (optional)
- Title

Output

Success or failure for each sources. List of sources.

Example Request

```
<EditSourcesRequest>
  <Sources>
    <Source source_id="12" request_id="alb2c3">
      <Title>Edited Sample Title</Title>
    </Source>
  </Sources>
</EditSourcesRequest>
```

Example Response

```
<EditSourcesResponse>
  <Sources>
    <Source request_id="alb2c3">
      <Result>Success</Result>
      <SourceID>12</SourceID>
      <Title>Edited Sample Title</Title>
    </Source>
  </Sources>
</EditSourcesResponse>
```

Delete Sources

This function allows the caller to delete one or more opportunity sources from the database.

Search parameters should be specified inside the tag.

Contacts permission is required for shared access users.

Input

- account_id (required for shared access)
- source_id
- request_id (optional)

Output

Success or failure for each sources. List of sources.

Example Request

```
<DeleteSourcesRequest>
  <Sources>
    <Source source_id="12" request_id="a1b2c3"/>
  </Sources>
</DeleteSourcesRequest>
```

Example Response

```
<DeleteSourcesResponse>
  <Sources>
    <Source request_id="a1b2c3">
      <Result>Success</Result>
      <SourceID>12</SourceID>
    </Source>
  </Sources>
</DeleteSourcesResponse>
```

Get Phases

This function allows the caller to retrieve a contact's opportunity phases from the database.

Search parameters should be specified inside the tag.

Contacts permission is required for shared access users.

Input

- account_id (required for shared access)
- phase_id
- phase_title

- phase_number

Output

Success or failure. A list of phases.

Example Request

```
<GetPhasesRequest></GetPhasesRequest>
```

Example Request

```
<GetPhasesRequest phase_id="1"></GetPhasesRequest>
```

Example Request

```
<GetPhasesRequest phase_title="New Lead"></  
GetPhasesRequest>
```

Example Request

```
<GetPhasesRequest phase_number="1"></GetPhasesRequest>
```

Example Request (shared access)

```
<GetPhasesRequest account_id="12345"></GetPhasesRequest>
```

Successful Response

```
<GetPhasesResponse>  
  <Result>Success</Result>  
  <Phases>  
    <Phase>  
      <PhaseID>1</PhaseID>  
      <Title>New Lead</Title>  
      <PhaseNumber>1</PhaseNumber>  
      <WarningDays>5</WarningDays>  
    </Phase>  
    <Phase>  
      <PhaseID>2</PhaseID>  
      <Title>Qualified Lead</Title>  
      <PhaseNumber>2</PhaseNumber>
```



```
        <WarningDays>5</WarningDays>
    </Phase>
    <Phase>
        <PhaseID>3</PhaseID>
        <Title>Prospect</Title>
        <PhaseNumber>3</PhaseNumber>
        <WarningDays>5</WarningDays>
    </Phase>
    <Phase>
        <PhaseID>4</PhaseID>
        <Title>Proposal</Title>
        <PhaseNumber>4</PhaseNumber>
        <WarningDays>10</WarningDays>
    </Phase>
    <Phase>
        <PhaseID>5</PhaseID>
        <Title>Proposal Evaluation</Title>
        <PhaseNumber>5</PhaseNumber>
        <WarningDays>10</WarningDays>
    </Phase>
    <Phase>
        <PhaseID>6</PhaseID>
        <Title>Closed - Deal Lost</Title>
        <PhaseNumber>6</PhaseNumber>
        <WarningDays>0</WarningDays>
    </Phase>
    <Phase>
        <PhaseID>7</PhaseID>
        <Title>Closed - Deal Won</Title>
        <PhaseNumber>7</PhaseNumber>
        <WarningDays>0</WarningDays>
    </Phase>
    <Phase>
        <PhaseID>9</PhaseID>
        <Title>Test</Title>
        <PhaseNumber>8</PhaseNumber>
        <WarningDays>2</WarningDays>
    </Phase>
</Phases>
</GetPhasesResponse>
```

Add Phases

This function allows the caller to add one or more opportunity phases.

Contacts permission is required for shared access users.

Input

- account_id (required for shared access)
- request_id (optional)
- Title
- Warning Days

Output

Success or failure for each phases. List of phases.

Example Request

```
<AddPhasesRequest>
  <Phases>
    <Phase request_id="a1b2c3">
      <Title>Sample</Title>
      <WarningDays>1</WarningDays>
    </Phase>
  </Phases>
</AddPhasesRequest>
```

Successful Response

```
<AddPhasesResponse>
  <Phases>
    <Phase request_id="a1b2c3">
      <Result>Success</Result>
      <PhaseID>18</PhaseID>
      <Title>Sample</Title>
      <WarningDays>1</WarningDays>
```

```
        </Phase>
    </Phases>
</AddPhasesResponse>
```

Edit Phases

This function allows the caller to modify one or more opportunity phases already in the database.

Search parameters should be specified inside the tag, while parameters to change to would be specified individually.

Contacts permission is required for shared access users.

Input

- account_id (required for shared access)
- phase_id
- request_id (optional)
- Title
- Warning Days
- Phase Number

Output

Success or failure for each phases. List of phases.

Example Request

```
<EditPhasesRequest>
  <Phases>
    <Phase phase_id="17" request_id="a1b2c3">
      <Title>Edited Sample</Title>
      <WarningDays>1</WarningDays>
      <PhaseNumber>9</PhaseNumber>
    </Phase>
  </Phases>
```

</EditPhasesRequest>

Example Response

```
<EditPhasesResponse>
  <Phases>
    <Phase request_id="a1b2c3">
      <Result>Success</Result>
      <PhaseID>17</PhaseID>
      <Title>Edited Sample</Title>
      <PhaseNumber>9</PhaseNumber>
      <WarningDays>1</WarningDays>
    </Phase>
  </Phases>
</EditPhasesResponse>
```

Delete Phases

This function allows the caller to delete one or more opportunity phases from the database.

Search parameters should be specified inside the tag.

Contacts permission is required for shared access users.

Input

- account_id (required for shared access)
- phase_id
- request_id (optional)

Output

Success or failure for each phases. List of phases.

Example Request

```
<DeletePhasesRequest>
```

```
<Phases>
  <Phase phase_id="17" request_id="a1b2c3"/>
</Phases>
</DeletePhasesRequest>
```

Example Response

```
<DeletePhasesResponse>
  <Phases>
    <Phase request_id="a1b2c3">
      <Result>Success</Result>
      <PhaseID>17</PhaseID>
    </Phase>
  </Phases>
</DeletePhasesResponse>
```

Get Phase Paths

This function allows the caller to retrieve the opportunity phase paths from the database.

Contacts permission is required for shared access users.

Input

- account_id (required for shared access)

Output

Success or failure. A list of phase paths.

Example Request

```
<GetPhasePathsRequest></GetPhasePathsRequest>
```

Example Request (shared access)

```
<GetPhasePathsRequest account_id="12345"></
GetPhasePathsRequest>
```

Successful Response

```
<GetPhasePathsResponse>
  <PhasePaths>
    <PhasePath>
      <PhasePathID>1</PhasePathID>
      <PhasePathName>Phase 1</PhasePathName>
      <Phases>
        <Phase>
          <PhaseID>1</PhaseID>
          <Title>New Lead</Title>
        </Phase>
        <Phase>
          <PhaseID>6</PhaseID>
          <Title>Closed - Deal Lost</Title>
        </Phase>
        <Phase>
          <PhaseID>7</PhaseID>
          <Title>Closed - Deal Won</Title>
        </Phase>
      </Phases>
    </PhasePath>
  </PhasePaths>
</GetPhasePathsResponse>
```

Get Products

This function allows the caller to retrieve a contact's opportunity products from the database.

Search parameters should be specified inside the tag.

Contacts permission is required for shared access users.

Input

- account_id (required for shared access)
- product_id

- product_title

Output

Success or failure. A list of products.

Example Request

```
<GetProductsRequest></GetProductsRequest>
```

Example Request

```
<GetProductsRequest product_id="1"></GetProductsRequest>
```

Example Request

```
<GetProductsRequest product_title="Sample Product"></GetProductsRequest>
```

Example Request (shared access)

```
<GetProductsRequest account_id="12345"></GetProductsRequest>
```

Successful Response

```
<GetProductsResponse>
  <Result>Success</Result>
  <Products>
    <Product>
      <ProductID>1</ProductID>
      <Title>Product A</Title>
      <DefaultValue>10</DefaultValue>
      <Description><![CDATA[<p>The <b>quick</b> brown
fox</p>]]></Description>
      <ProductCategories>
        <ProductCategory>
          <ProductCategoryID>0</ProductCategoryID>
          <ProductCategoryName>Uncategorized</ProductCategoryName>
```

```

        </ProductCategory>
      </ProductCategories>
    </Product>
    <Product>
      <ProductID>2</ProductID>
      <Title>Product B</Title>
      <DefaultValue>20</DefaultValue>
      <Description><![CDATA[<p>Jumps over the lazy
dog</p>]]></Description>
      <ProductCategories>
        <ProductCategory>
          <ProductCategoryID>1</
ProductCategoryID>
          <ProductCategoryName>Category A</
ProductCategoryName>
        </ProductCategory>
        <ProductCategory>
          <ProductCategoryID>2</
ProductCategoryID>
          <ProductCategoryName>Category B</
ProductCategoryName>
        </ProductCategory>
      </ProductCategories>
    </Product>
  </Products>
</GetProductsResponse>

```

Add Products

This function allows the caller to add one or more opportunity products.

Contacts permission is required for shared access users.

Input

- account_id (required for shared access)
- request_id (optional)
- Title (required)

- DefaultValue
- Description (HTML/text format)
- ProductCategoryIDs (pass 0 to set as Unrecognized)

Output

Success or failure for each products. List of products.

Example Request

```
<AddProductsRequest>
  <Products>
    <Product request_id="a1b2c3">
      <Title>Product A</Title>
      <DefaultValue>10</DefaultValue>
      <Description><![CDATA[<p>The <b>quick</b> brown
fox</p>]]></Description>
      <ProductCategoryIDs>
        <ProductCategoryID>1</ProductCategoryID>
        <ProductCategoryID>2</ProductCategoryID>
      </ProductCategoryIDs>
    </Product>
  </Products>
</AddProductsRequest>
```

Successful Response

```
<AddProductsResponse>
  <Products>
    <Product request_id="a1b2c3">
      <Result>Success</Result>
      <ProductID>3</ProductID>
    </Product>
  </Products>
</AddProductsResponse>
```

Edit Products

This function allows the caller to modify one or more opportunity products already in the database.

Search parameters should be specified inside the tag, while parameters to change to would be specified individually.

Contacts permission is required for shared access users.

Input

- account_id (required for shared access)
- request_id (optional)
- product_id (required)
- Title
- DefaultValue
- Description (HTML/text format)
- ProductCategoryIDs (replace wholly the categories that the product are in, pass 0 to set as Unrecognized)

Output

Success or failure for each products. List of products.

Example Request

```
<EditProductsRequest>
  <Products>
    <Product product_id="13" request_id="a1b2c3">
      <Title>Edited Sample</Title>
      <DefaultValue>2</DefaultValue>
      <Description><![CDATA[<p>The <b>quick</b> brown
fox</p>]]></Description>
      <ProductCategoryIDs>
        <ProductCategoryID>1</ProductCategoryID>
        <ProductCategoryID>2</ProductCategoryID>
      </ProductCategoryIDs>
    </Product>
  </Products>
</EditProductsRequest>
```

```
    </Products>
</EditProductsRequest>
```

Example Response

```
<EditProductsResponse>
  <Products>
    <Product request_id="a1b2c3">
      <Result>Success</Result>
      <ProductID>13</ProductID>
    </Product>
  </Products>
</EditProductsResponse>
```

Delete Products

This function allows the caller to delete one or more opportunity products from the database.

Search parameters should be specified inside the tag.

Contacts permission is required for shared access users.

Input

- account_id (required for shared access)
- product_id
- request_id (optional)

Output

Success or failure for each products. List of products.

Example Request

```
<DeleteProductsRequest>
  <Products>
    <Product product_id="13" request_id="a1b2c3"/>
  </Products>
</DeleteProductsRequest>
```

```
    </Products>
</DeleteProductsRequest>
```

Example Response

```
<DeleteProductsResponse>
  <Products>
    <Product request_id="a1b2c3">
      <Result>Success</Result>
      <ProductID>13</ProductID>
    </Product>
  </Products>
</DeleteProductsResponse>
```

Get Custom Fields

This function allows the caller to fetch opportunity custom fields for an account.

Contacts permission is required for shared access users.

For age field type, the AgeReference value refers to the date field type CustomFieldID that will be used to calculate the age. The PossibleValues shows a list of date field type custom fields that is eligible to be set as the AgeReference.

Input

- account_id (required for shared access)

Output

Success or failure. A list of custom fields.

Example Request

```
<GetOpportunityFieldsRequest></GetOpportunityFieldsRequest>
```

Example Request

```
<GetOpportunityFieldsRequest account_id="1392"></GetOpportunityFieldsRequest>
```

Successful Response

```
<GetOpportunityFieldsResponse>
  <Result>Success</Result>
  <CustomFields>
    <CustomField>
      <PhasePathID>2</PhasePathID>
      <CustomFieldID>93</CustomFieldID>
      <FieldName>Favorite Animal</FieldName>
      <FieldType>Checkbox</FieldType>
      <PossibleValues>Dog,Cat,Monkey</PossibleValues>
      <RequiredField>N</RequiredField>
      <LastModified>2012-12-06 10:52:17</LastModified>
    </CustomField>
    <CustomField>
      <PhasePathID>5</PhasePathID>
      <CustomFieldID>154</CustomFieldID>
      <FieldName>Fruits</FieldName>
      <FieldType>Select</FieldType>
      <PossibleValues>Apple,Orange,Banana</PossibleValues>
      <RequiredField>Y</RequiredField>
      <LastModified>2012-12-06 14:59:29</LastModified>
    </CustomField>
    <CustomField>
      <AgeReference>OppField5</AgeReference>
      <FieldName>Child's Age</FieldName>
      <CustomFieldID>9</CustomFieldID>
      <FieldOrder>8</FieldOrder>
      <FieldType>Age</FieldType>
      <LastModified>2025-11-20 06:38:47</LastModified>
    </CustomField>
    <CustomField>
      <OnlyShowIfProductID>0</OnlyShowIfProductID>
      <PossibleValues>OppField5,OppField10</PossibleValues>
    </CustomField>
  </CustomFields>
</GetOpportunityFieldsResponse>
```

```

        <RequiredField>N</RequiredField>
        <ShowOnKanbanCard>N</ShowOnKanbanCard>
    </CustomField>
</CustomFields>
</GetOpportunityFieldsResponse>

```

Add Custom Fields

This function allows the caller to add a custom field for opportunities, for specific phase paths or for all phase paths.

Contacts permission is required for shared access users.

Input

- account_id (required for shared access)
- request_id (optional)
- FieldName
- PhasePathID (use 0 for PhasePath ID to make the custom field available to all phase paths. 0 is default is omitted)
- FieldType (Select, Checkbox, Text, ShortText, Integer, Decimal, Date, Age or File) (optional - defaults to Text)
- PossibleValues (should be separated by commas) (optional)
- RequiredField (Y or N)
- FieldOrder (display order, defaults to next highest number)
- ShowOnKanbanCard (Y or N)
- AgeReference (required for Age FieldType. Must be a date field type custom field ID, eg. OppField<CustomFieldID>)

Output

Success or failure for each custom field. List of custom fields.

Example Request

```
<AddOpportunityFieldsRequest>
```

```

    <CustomFields>
      <CustomField>
        <FieldName>Fruits</FieldName>
        <FieldType>Select</FieldType>
        <PossibleValues>Orange,Apple,Banana</
PossibleValues>
        <RequiredField>N</RequiredField>
        <PhasePathID>0</PhasePathID>
      </CustomField>
      <CustomField>
        <FieldName>Child's Age</FieldName>
        <FieldType>Age</FieldType>
        <AgeReference>OppField5</AgeReference>
        <RequiredField>N</RequiredField>
      </CustomField>
    </CustomFields>
  </AddOpportunityFieldsRequest>

```

Example Request

```

<AddOpportunityFieldsRequest>
  <CustomFields>
    <CustomField>
      <FieldName>MyTextField</FieldName>
    </CustomField>
  </CustomFields>
</AddOpportunityFieldsRequest>

```

Successful Response

```

<AddOpportunityFieldsResponse>
  <CustomFields>
    <CustomField>
      <Result>Success</Result>
      <CustomFieldID>8</CustomFieldID>
      <FieldName>MyTextField</FieldName>
      <FieldOrder>11</FieldOrder>
      <FieldType>Text</FieldType>
      <PossibleValues></PossibleValues>
      <RequiredField>N</RequiredField>
      <PhasePathID>0</PhasePathID>
    </CustomField>
  </CustomFields>

```

```
        </CustomField>
    </CustomFields>
</AddOpportunityFieldsResponse>
```

Edit Custom Fields

This function allows the caller to edit custom fields.

Contacts permission is required for shared access users.

Any fields not passed will retain their original values. If one of more PhasePathIDs are passed then any existing PhasePathIDs are replaced.

Input

- account_id (required for shared access)
- request_id (optional)
- FieldName (this or CustomFieldID is required)
- CustomFieldID (this or FieldName is required)
- PhasePathID (use 0 for PhasePath ID to make the custom field available to all phase paths. 0 is default is omitted)
- FieldType (Select, Checkbox, Text, ShortText, Integer, Decimal, Date or File) (optional - defaults to Text)
- PossibleValues (should be separated by commas) (optional)
- RequiredField (Y or N)
- FieldOrder (display order, defaults to next highest number)
- ShowOnKanbanCard (Y or N)
- AgeReference (for Age FieldType. Must be a date field type custom field ID, eg. OppField<CustomFieldID>)

Output

Success or failure for each custom field. List of custom fields.

Example Request


```

<EditOpportunityFieldsRequest>
  <CustomFields>
    <CustomField>
      <CustomFieldID>2</CustomFieldID>
      <FieldType>Checkbox</FieldType>
      <PossibleValues>Dog,Cat,Monkey</
PossibleValues>
      <RequiredField>Y</RequiredField>
    </CustomField>
  </CustomFields>
  <CustomField>
    <FieldName>Child's Age</FieldName>
    <FieldType>Age</FieldType>
    <AgeReference>OppField5</AgeReference>
    <RequiredField>N</RequiredField>
  </CustomField>
</EditOpportunityFieldsRequest>

```

Example Request

```

<EditOpportunityFieldsRequest>
  <CustomFields>
    <CustomField>
      <FieldName>Favorite Animal</FieldName>
      <FieldType>Checkbox</FieldType>
      <PossibleValues>Dog,Cat,Monkey</
PossibleValues>
      <RequiredField>Y</RequiredField>
    </CustomField>
  </CustomFields>
</EditOpportunityFieldsRequest>

```

Example Response

```

<EditOpportunityFieldsResponse>
  <CustomFields>
    <CustomField>
      <Result>Success</Result>
      <CustomFieldID>2</CustomFieldID>
      <AccountNumber>19821</AccountNumber>
      <PossibleValues>A,B,C</PossibleValues>
    </CustomField>
  </CustomFields>
</EditOpportunityFieldsResponse>

```

```
        </CustomField>
    </CustomFields>
</EditOpportunityFieldsResponse>
```

Delete Custom Fields

This function allows the caller to delete custom fields.

Contacts permission is required for shared access users.

Input

- account_id (required for shared access)
- product_id
- FieldName (this or CustomFieldID is required)
- CustomFieldID (this or FieldName is required)

Output

Success or failure for each products. List of products.

Example Request

```
<DeleteOpportunityFieldsRequest>
  <CustomFields>
    <CustomField>
      <FieldName>Favorite Animal</FieldName>
    </CustomField>
  </CustomFields>
</DeleteOpportunityFieldsRequest>
```

Example Request

```
<DeleteOpportunityFieldsRequest>
  <CustomFields>
    <CustomField>
      <CustomFieldID>5</CustomFieldID>
    </CustomField>
  </CustomFields>
</DeleteOpportunityFieldsRequest>
```

```
    </CustomFields>
</DeleteOpportunityFieldsRequest>
```

Example Response

```
<DeleteOpportunityFieldsResponse>
  <CustomFields>
    <CustomField>
      <Result>Success</Result>
    </CustomField>
  </CustomFields>
</DeleteOpportunityFieldsResponse>
```

Spec - Projects

Table Of Contents

- Get Project Categories
- Add Project Category
- Get Projects
- Add Projects
- Edit Projects
- Delete Projects
- Get Project Updates
- Add Project Updates
- Edit Project Updates
- Activate Project Players
- Deactivate Project Players
- Get Project Tasks
- Add Project Tasks
- Edit Project Tasks
- Delete Project Tasks
- Get Projects Power-Users
- Add Projects Power-Users
- Remove Projects Power-Users

Get Project Categories

This function allows the caller to get a list of project categories for a given group.

Input

Pass either the group name or group ID on the root element of the request.

Output

Returns an array of categories for the given group.

Example Request 1

```
<GetProjectCategoriesRequest group_name="MyTestGroup"></GetProjectCategoriesRequest>
```

Example Request 2

```
<GetProjectCategoriesRequest group_id="12345"></GetProjectCategoriesRequest>
```

Successful Response

```
<GetProjectCategoriesResponse>
  <Categories group_id="12345">
    <Category category_name="My First Category"
category_id="12345"></Category>
    <Category category_name="My Second Category"
category_id="12346"></Category>
  </Categories>
</GetProjectCategoriesResponse>
```

Add Project Category

This function allows the caller to add a category to the given group.

Input

The category name is required. Either the group name or id can be specified. If neither the group name or id is provided, the category will be available to all groups.

Output

Returns a status for each category that was added.

Example Request 1 (specify group name)

```
<AddProjectCategoryRequest group_name="MyTestGroup"
category_name="My Category"></AddProjectCategoryRequest>
```

Example Request 2 (specify group id)

```
<AddProjectCategoryRequest group_id="12345"
category_name="My Category"></AddProjectCategoryRequest>
```

Example Request 3 (make available to all groups)

```
<AddProjectCategoryRequest category_name="My Category"></
AddProjectCategoryRequest>
```

Successful Response

```
<AddProjectCategoryResponse>
  <Categories>
    <Category>
      <Category_id>322</Category_id>
      <Result>Success</Result>
    </Category>
    <Category>
      <Category_id>324</Category_id>
      <Result>Success</Result>
    </Category>
  </Categories>
</AddProjectCategoryResponse>
```

Get Projects

This function allows the caller to retrieve projects from the database. Search parameters should be specified inside the tag. Projects can be retrieved by Project ID, Project Name, Group (ID or name), Project Manager ID, Project Start Date/Time, Project Due Date/Time, Category ID, and Priority. Leaving all search criteria blank would return all of the projects in the account (for the account owner).

Input

Specify search criteria within the GetProjectsRequest tag. Search criteria can be project_id, project_name, group_id (return all Projects belonging to group), group_name, project_manager_id, project_category_id, priority. If no search criteria, return all projects in the account (if an account owner). Specify account_id and group_name or group_id for shared access to another account. Specify get_all="true" to return all projects that the caller has access to, including shared access.

Output

Success or failure. Total number of Projects matching search. For each Project found: Project ID, Group_id, Group_name, Project_name, Project_start_datetime (yyyy-mm-dd hh:mm format), Project_due_datetime (yyyy-mm-dd hh:mm format), Project_category_id, Project_category_name, Project_manager_id, Project_manager_firstname, Project_manager_lastname, Priority, Project_percent_complete, Project_status, Waiting_on_id, Waiting_on_firstname, Waiting_on_lastname, Description, Weekly_email_updates, Allocated_hours.

Example Request 1

```
<GetProjectsRequest></GetProjectsRequest>
```

Example Request 2

```
<GetProjectsRequest group_name="MyTestGroup"></  
GetProjectsRequest>
```

Example Request 3

```
<GetProjectsRequest project_category_id="78"></  
GetProjectsRequest>
```

Example Request 4 (shared access)

```
<GetProjectsRequest account_id="143996" group_id="321" ></
GetProjectsRequest>
```

Example Request 5 (shared access with get_all)

```
<GetProjectsRequest get_all="true"></GetProjectsRequest>
```

Successful Response

```
<GetProjectsResponse>
  <Result>Success</Result>
  <Projects>
    <Project>
      <AccountNumber>143996</AccountNumber>
      <Group_id>321</Group_id>
      <Group_name>MyTestGroup</Group_name>
      <Project_id>983</Project_id>
      <Project_name>My Test Project</Project_name>
      <Project_start_datetime>2014-02-12 08:55</
Project_start_datetime>
      <Project_due_datetime>2014-05-10 09:00</
Project_due_datetime>
      <Project_category_id>32</Project_category_id>
      <Project_category_name>My Test Project
Category</Project_category_name>
      <Project_manager_id>32</Project_manager_id>
      <Project_manager_firstname>John</
Project_manager_firstname>
      <Project_manager_lastname>Sullivan</
Project_manager_lastname>
      <Priority>High</Priority>
      <Project_percent_complete>70</
Project_percent_complete>
      <Project_status>In development</Project_status>
      <Waiting_on_id>87</Waiting_on_id>
      <Waiting_on_firstname>Steve</
Waiting_on_firstname>
      <Waiting_on_lastname>Simpson</
Waiting_on_lastname>
      <Description>A description of my test project</
Description>
```



```

        <Weekly_email_updates>Y</Weekly_email_updates>
        <Allocated_hours>200</Allocated_hours>
    </Project>
    <Project>
        <AccountNumber>143886</AccountNumber>
        <Group_id>343</Group_id>
        <Group_name>AnotherTestGroup</Group_name>
        <Project_id>1023</Project_id>
        <Project_name>Another Test Project</
Project_name>
        <Project_start_datetime>2014-03-12 08:55</
Project_start_datetime>
        <Project_due_datetime>2014-12-31 09:00</
Project_due_datetime>
        <Project_category_id>34</Project_category_id>
        <Project_category_name>Another Test Project
Category</Project_category_name>
        <Project_manager_id>39</Project_manager_id>
        <Project_manager_firstname>Megan</
Project_manager_firstname>
        <Project_manager_lastname>Johnson</
Project_manager_lastname>
        <Priority>Normal</Priority>
        <Project_percent_complete>5</
Project_percent_complete>
        <Project_status>Waiting for Approval</
Project_status>
        <Waiting_on_id>32</Waiting_on_id>
        <Waiting_on_firstname>Jacob</
Waiting_on_firstname>
        <Waiting_on_lastname>Jefferson</
Waiting_on_lastname>
        <Description>Another description of another
test project</Description>
        <Weekly_email_updates>N</Weekly_email_updates>
        <Allocated_hours>1500</Allocated_hours>
    </Project>
</Projects>
<TotalMatchingProjects>2</TotalMatchingProjects>
</GetProjectsResponse>

```

Add Projects

This function allows the caller to add one or more projects.

Input

- request_id (optional)
- Group_id (required)
- Project_name (required)
- Project_start_datetime (yyyy-mm-dd hh:mm format)
- Project_due_datetime (yyyy-mm-dd hh:mm format)
- Project_category_id
- Project_manager_id (required)
- Priority (High, Normal, or Low)
- Project_percent_complete (0 default)
- Project_status
- Waiting_on_id (optional)
- Description
- Weekly_email_updates (Y or N, default Y)
- Allocated_hours (0 default).

Output

For each project, success or failure, Project_id if successful,
AccountNumber, Group_id

Example Request 1

```
<AddProjectsRequest>
  <Projects>
    <Project request_id="a1b2c3">
      <Group_id>6</Group_id>
      <Project_name>My Test Project</Project_name>
      <Project_start_datetime>2014-04-23 14:00</
Project_start_datetime>
```

```

        <Project_due_datetime>2014-06-23 19:00</
Project_due_datetime>
        <Project_category_id>9</Project_category_id>
        <Project_manager_id>23</Project_manager_id>
        <Priority>High</Priority>
        <Project_percent_complete>0</
Project_percent_complete>
        <Project_status>In Development</Project_status>
        <Waiting_on_id>92</Waiting_on_id>
        <Description>Description for Test Project 1.</
Description>
        <Weekly_email_updates>Y</Weekly_email_updates>
        <Allocated_hours>320</Allocated_hours>
    </Project>
    <Project request_id="d4e5f6">
        <Group_id>25</Group_id>
        <Project_name>My Second Test Project</
Project_name>
        <Project_start_datetime>2014-04-12 08:00</
Project_start_datetime>
        <Project_due_datetime>2014-05-15 19:00</
Project_due_datetime>
        <Project_category_id>3</Project_category_id>
        <Project_manager_id>26</Project_manager_id>
        <Priority>Normal</Priority>
        <Project_percent_complete>5</
Project_percent_complete>
        <Project_status>Starting Phase</Project_status>
        <Description>Description for Test Project 2.</
Description>
        <Weekly_email_updates>N</Weekly_email_updates>
        <Allocated_hours>240</Allocated_hours>
    </Project>
</Projects>
</AddProjectsRequest>

```

Example Request 2 (Shared Access)

```

<AddProjectsRequest>
    <Projects>

```

```

    <Project account_id="83920">
      <Group_id>19</Group_id>
      <Project_name>My Test Project</Project_name>
      <Project_start_datetime>2014-02-12 09:00</
Project_start_datetime>
      <Project_due_datetime>2014-04-10 19:30</
Project_due_datetime>
      <Project_category_id>2</Project_category_id>
      <Project_manager_id>37</Project_manager_id>
      <Priority>Low</Priority>
      <Project_percent_complete>0</
Project_percent_complete>
      <Project_status>Complete</Project_status>
      <Description>Description for Test Project 1.</
Description>
    </Project>
    <Project account_id="9212">
      <Group_id>21</Group_id>
      <Project_name>My Test Project 2</Project_name>
      <Project_start_datetime>2014-05-01 07:30</
Project_start_datetime>
      <Project_due_datetime>2014-08-31 19:30</
Project_due_datetime>
      <Project_category_id>4</Project_category_id>
      <Project_manager_id>21</Project_manager_id>
      <Priority>High</Priority>
      <Project_percent_complete>10</
Project_percent_complete>
      <Project_status>Kickoff</Project_status>
      <Description>Description for Test Project 2.</
Description>
    </Project>
  </Projects>
</AddProjectsRequest>

```

Successful Response

```

<AddProjectsResponse>
  <Projects>
    <Project request_id="a1b2c3">

```

```
<Project_id>32</Project_id>
<Result>Success</Result>
<AccountNumber>83920</AccountNumber>
<Group_id>19</Group_id>
</Project>
<Project request_id="d4e5f6">
  <Project_id>33</Project_id>
  <Result>Success</Result>
  <AccountNumber>9212</AccountNumber>
  <Group_id>21</Group_id>
</Project>
</Projects>
</AddProjectsResponse>
```

Edit Projects

This function allows the caller to modify one or more Projects already in the database. Search parameters should be specified inside the tag, while parameters to change to would be specified individually. Fields not specified would remain the same.

Input

Specify search criteria within the EditProjectsRequest tag. Search criteria can be:

- project_id
- project_name
- group_id
- group_name
- project_manager_id
- project_category_id
- priority
- request_id (optional)

Each project's search criteria must return a single unique project to modify.

Parameters to change can include:

- Group_id
- Project_name
- Project_start_datetime (yyyy-mm-dd hh:mm format)
- Project_due_datetime (yyyy-mm-dd hh:mm format)
- Project_category_id
- Project_manager_id
- Priority (High, Normal, or Low)
- Project_status
- Project_percent_complete (0 default)
- Waiting_on_id
- Description
- Weekly_email_updates (Y or N)
- Allocated_hours

Output

For each project, success or failure, Project_id, AccountNumber

Example Request 1

```
<EditProjectsRequest>
  <Projects>
    <Project project_id="235 request_id="a1b2c3">
      <Group_id>6</Group_id>
      <Project_name>My Test Project</Project_name>
      <Project_start_datetime>2014-04-25 14:00</
Project_start_datetime>
      <Project_due_datetime>2014-06-25 19:00</
Project_due_datetime>
      <Project_category_id>9</Project_category_id>
      <Project_manager_id>23</Project_manager_id>
      <Priority>Normal</Priority>
    </Project>
    <Project project_name="My Test Project"
request_id="d4e5f6">
```

```
        <Description>New Description for My Test
Project Project 2.</Description>
        <Weekly_email_updates>N</Weekly_email_updates>
        <Allocated_hours>240</Allocated_hours>
    </Project>
</Projects>
</EditProjectsRequest>
```

Example Request 2 (Shared Access)

```
<EditProjectsRequest>
    <Projects>
        <Project project_id="322" account_id="32234">
            <Group_id>32</Group_id>
            <Project_name>Another Test Project</
Project_name>
            <Project_start_datetime>2014-04-29 10:00</
Project_start_datetime>
            <Project_due_datetime>2014-05-30 23:30</
Project_due_datetime>
            <Project_category_id>39</Project_category_id>
            <Project_manager_id>23</Project_manager_id>
            <Priority>Low</Priority>
        </Project>
        <Project project_name="My Test Project 2"
account_id="32344">
            <Description>New Description for My Test
Project Project 3.</Description>
        </Project>
    </Projects>
</EditProjectsRequest>
```

Successful Response

```
<EditProjectsResponse>
    <Projects>
        <Project request_id="a1b2c3">
            <Project_id>322</Project_id>
            <Result>Success</Result>
            <AccountNumber>32234</AccountNumber>
            <Group_id>32</Group_id>
```

```
        </Project>
        <Project request_id="d4e5f6">
            <Project_id>324</Project_id>
            <Result>Success</Result>
            <AccountNumber>32344</AccountNumber>
        </Project>
    </Projects>
</EditProjectsResponse>
```

Delete Projects

This function allows the caller to delete one or more Projects from the database.

Input

Specify search criteria within the each Project tag. Search criteria can be:

- project_id
- project_name
- group_id
- group_name
- project_manager_id
- project_category_id
- priority
- request_id (optional)

Each project's search criteria must return a single unique project to modify.

Output

For each project, success or failure, Project_id.

Example Request 1


```
<DeleteProjectsRequest>
  <Projects>
    <Project project_id="235" request_id="a1b2c3" />
    <Project project_name="My Sample Project"
request_id="d4e5f6" />
  </Projects>
</DeleteProjectsRequest>
```

Example Request 2 (Shared Access)

```
<DeleteProjectsRequest>
  <Projects>
    <Project project_id="323" account_id="39023" />
    <Project project_name="My Other Sample Project"
account_id="93293" />
  </Projects>
</DeleteProjectsRequest>
```

Successful Response

```
<DeleteProjectsResponse>
  <Projects>
    <Project request_id="a1b2c3">
      <Project_id>322</Project_id>
      <Result>Success</Result>
    </Project>
    <Project request_id="d4e5f6">
      <Project_id>324</Project_id>
      <Result>Success</Result>
    </Project>
  </Projects>
</DeleteProjectsResponse>
```

Get Project Updates

This function allows the caller to retrieve project updates from the database. Search parameters should be specified inside the tag. Project updates can be retrieved by ProjectUpdateID, Project ID, Project Name, Contact ID, Contact Firstname, Contact Lastname. Leaving all search

criteria blank would return all of the project updates in the account (for the account owner).

Input

Specify search criteria within the GetProjectUpdatesRequest tag. Search criteria can be project_update_id, project_id, project_name, contact_id, contact_firstname, contact_lastname.

Output

Success or failure. Total number of Project Updates matching search. For each Project Update found: Project_update_id, Project_id, Project_name, Contact_id, Contact_firstname, Contact_lastname, Time_spent, Notes, Media_id, Update_datetime (yyyy-mm-dd hh:mm:ss format).

Example Request 1

```
<GetProjectUpdatesRequest></GetProjectUpdatesRequest>
```

Example Request 2

```
<GetProjectUpdatesRequest project_name="My Test Project"
contact_id="43"></GetProjectUpdatesRequest>
```

Example Request 3 (Shared Access)

```
<GetProjectUpdatesRequest account_id="82038"
project_id="432"></GetProjectUpdatesRequest>
```

Successful Response

```
<GetProjectUpdatesResponse>
  <Result>Success</Result>
  <ProjectUpdates>
    <ProjectUpdate>
      <AccountNumber>143996</AccountNumber>
```

```

        <Project_update_id>32</Project_update_id>
        <Project_id>23</Project_id>
        <Project_name>My test project</Project_name>
        <Contact_id>34</Contact_id>
        <Contact_firstname>Sam</Contact_firstname>
        <Contact_lastname>Adams</Contact_lastname>
        <Time_spent>3.6</Time_spent>
        <Notes>Wrote documentation</Notes>
        <Media_id>32</Media_id>
        <Update_datetime>2014-04-12 10:32:34</
Update_datetime>
    </ProjectUpdate>
    <ProjectUpdate>
        <AccountNumber>23923</AccountNumber>
        <Project_update_id>24</Project_update_id>
        <Project_id>21</Project_id>
        <Project_name>Another test project</
Project_name>
        <Contact_id>32</Contact_id>
        <Contact_firstname>Charlie</Contact_firstname>
        <Contact_lastname>Parker</Contact_lastname>
        <Time_spent>6.7</Time_spent>
        <Notes>Coded the UI</Notes>
        <Media_id></Media_id>
        <Update_datetime>2014-05-01 13:42:55</
Update_datetime>
    </ProjectUpdate>
</ProjectUpdates>
<TotalMatchingProjectUpdates>2</
TotalMatchingProjectUpdates>
</GetProjectUpdatesResponse>

```

Add Project Updates

This function allows the caller to add one or more project updates.

Input

- request_id (optional)

- Project_id (required)
- Contact_id (required)
- Time_spent (0.0 format)
- Notes
- Media_id (optional attachment ID into media library)
- Update_datetime (yyyy-mm-dd hh:mm:ss format)

Output

For each project update, success or failure, Project_update_id if successful, AccountNumber.

Example Request 1

```
<AddProjectUpdatesRequest>
  <ProjectUpdates>
    <ProjectUpdate request_id="a1b2c3">
      <Project_id>93</Project_id>
      <Contact_id>24</Contact_id>
      <Time_spent>3.4</Time_spent>
      <Notes>Worked on coding for new project</Notes>
      <Media_id>92</Media_id>
      <Update_datetime>2014-05-01 18:23:31</
Update_datetime>
    </ProjectUpdate>
    <ProjectUpdate request_id="d4e5f6">
      <Project_id>95</Project_id>
      <Contact_id>22</Contact_id>
      <Time_spent>7.6</Time_spent>
      <Notes>Testing the new product</Notes>
      <Update_datetime>2014-05-05 17:00:00</
Update_datetime>
    </ProjectUpdate>
  </ProjectUpdates>
</AddProjectUpdatesRequest>
```

Example Request 2 - Shared Access

```
<AddProjectUpdatesRequest>
```

```

    <ProjectUpdates>
      <ProjectUpdate account_id="83920">
        <Project_id>29</Project_id>
        <Contact_id>93</Contact_id>
        <Time_spent>6.1</Time_spent>
        <Notes>Contract for new client</Notes>
        <Media_id>93</Media_id>
        <Update_datetime>2014-05-07 17:30:02</
Update_datetime>
      </ProjectUpdate>
      <ProjectUpdate account_id="54231">
        <Project_id>30</Project_id>
        <Contact_id>24</Contact_id>
        <Time_spent>8.7</Time_spent>
        <Notes>Accounting work for month close</Notes>
        <Update_datetime>2014-05-10 16:31:20</
Update_datetime>
      </ProjectUpdate>
    </ProjectUpdates>
  </AddProjectUpdatesRequest>

```

Successful Response

```

<AddProjectUpdatesResponse>
  <ProjectUpdates>
    <ProjectUpdate request_id="a1b2c3">
      <Project_update_id>54</Project_update_id>
      <Result>Success</Result>
      <AccountNumber>92032</AccountNumber>
    </ProjectUpdate>
    <ProjectUpdate request_id="d4e5f6">
      <Project_update_id>55</Project_update_id>
      <Result>Success</Result>
      <AccountNumber>32133</AccountNumber>
    </ProjectUpdate>
  </ProjectUpdates>
</AddProjectUpdatesResponse>

```

Edit Project Updates

This function allows the caller to modify one or more project updates already in the database. Search parameters should be specified inside the tag, while parameters to change to would be specified individually. Fields not specified would remain the same.

Input

Specify search criteria within the EditProjectUpdatesRequest tag. Search criteria can be:

- project_update_id
- project_id
- project_name
- contact_id
- contact_firstname
- contact_lastname
- request_id (optional)

Each project's search criteria must return a single unique project to modify.

Parameters to change can include:

- Project_id
- Contact_id
- Time_spent (0.0 format)
- Notes
- Media_id
- Update_datetime (yyyy-mm-dd hh:mm:ss format).

Output

For each project, success or failure, Project_id, AccountNumber

Example Request 1

```

<EditProjectUpdatesRequest>
  <ProjectUpdates>
    <ProjectUpdate project_update_id="23"
request_id="a1b2c3">
      <Time_spent>4.4</Time_spent>
      <Notes>Helped Jim with sales</Notes>
      <Update_datetime>2014-05-02 11:23:31</
Update_datetime>
    </ProjectUpdate>
    <ProjectUpdate project_update_id="93"
request_id="d4e5f6">
      <Project_id>55</Project_id>
      <Contact_id>12</Contact_id>
      <Time_spent>2.6</Time_spent>
      <Notes>QA meeting</Notes>
      <Update_datetime>2014-04-23 17:00:00</
Update_datetime>
    </ProjectUpdate>
  </ProjectUpdates>
</EditProjectUpdatesRequest>

```

Example Request 2 (Shared Access)

```

<EditProjectUpdatesRequest>
  <ProjectUpdates>
    <ProjectUpdate project_update_id="34"
account_id="32234">
      <Time_spent>2.4</Time_spent>
      <Notes>Close books mid-month</Notes>
      <Update_datetime>2014-05-21 10:23:31</
Update_datetime>
    </ProjectUpdate>
    <ProjectUpdate project_update_id="88"
account_id="32235">
      <Project_id>32</Project_id>
      <Contact_id>12</Contact_id>
      <Time_spent>9.2</Time_spent>
      <Notes>Sales Meeting</Notes>
      <Update_datetime>2014-04-13 16:30:23</
Update_datetime>

```

```
        </ProjectUpdate>
    </ProjectUpdates>
</EditProjectUpdatesRequest>
```

Successful Response

```
<EditProjectUpdatesResponse>
  <ProjectUpdates>
    <ProjectUpdate request_id="a1b2c3">
      <Project_update_id>34</Project_id>
      <Result>Success</Result>
      <AccountNumber>32234</AccountNumber>
    </ProjectUpdate>
    <ProjectUpdate request_id="d4e5f6">
      <Project_id>324</Project_id>
      <Result>Success</Result>
      <AccountNumber>32235</AccountNumber>
    </ProjectUpdate>
  </ProjectUpdates>
</EditProjectUpdatesResponse>
```

Activate Project Players

This function allows the caller to activate players on a given project

Input

Pass the project id and a list of players you would like activated on the project.

Output

Returns a status for each player that was attempted to be activated to the project.

Example Request 1

```
<ActivateProjectPlayersRequest project_id="12345">
```



```
<Player id="1111"></Player>
  <Player id="2222"></Player>
</ActivateProjectPlayersRequest>
```

Successful Response

```
<ActivateProjectPlayersResponse>
  <Player id="1111">
    <Result>Success</Result>
  </Player>
  <Player id="2222">
    <Result>Error</Result>
    <ErrorText>Player not available to add</ErrorText>
  </Player>
</ActivateProjectPlayersResponse>
```

Deactivate Project Players

This function allows the caller to deactivate players from a given project

Input

Pass the project id and a list of players you would like deactivated from the project.

Output

Returns a status for each player that was attempted to be deactivated from the project.

Example Request 1

```
<DeactivateProjectPlayersRequest project_id="12345">
  <Player id="1111"></Player>
  <Player id="2222"></Player>
</DeactivateProjectPlayersRequest>
```

Successful Response

```
<DeactivateProjectPlayersResponse>
  <Player id="1111">
    <Result>Success</Result>
  </Player>
  <Player id="2222">
    <Result>Error</Result>
    <ErrorText>Player not activated in project</
ErrorText>
  </Player>
</DeactivateProjectPlayersResponse>
```

Get Project Tasks

This function allows the caller to retrieve project tasks from the database. Search parameters should be specified inside the tag. Project updates can be retrieved by ProjectTaskID, Project ID, Project Name, Task Description, Task Contact ID, Task Contact Firstname, Task Contact Lastname. Leaving all search criteria blank would return all of the project tasks in the account (for the account owner).

Input

Specify search criteria within the GetProjectTasksRequest tag. Search criteria can be Project_task_id, Project_id, Project_name, Task_description, Task_contact_id, Task_contact_firstname, Task_contact_lastname.

Output

Success or failure. Total number of Project Tasks matching search. For each Project Task found: Project_task_id, Task_description, Project_id, Project_name, Task_contact_id, Task_contact_firstname, Task_contact_lastname, Datetime_start (yyyy-mm-dd hh:mm:ss format), Datetime_due (yyyy-mm-dd hh:mm:ss format), Datetime_completed (yyyy-mm-dd hh:mm:ss format).

Example Request 1

```
<GetProjectTasksRequest></GetProjectTasksRequest>
```

Example Request 2

```
<GetProjectTasksRequest Project_name="My Test Project"
Contact_id="43"></GetProjectTasksRequest>
```

Example Request 3 (Shared Access)

```
<GetProjectTasksRequest account_id="82038"
Project_id="432"></GetProjectTasksRequest>
```

Successful Response

```
<GetProjectTasksRequest>
  <Result>Success</Result>
  <ProjectTasks>
    <ProjectTask>
      <AccountNumber>143996</AccountNumber>
      <Project_task_id>31</Project_update_id>
      <Task_description>Test Task 1</
Task_description>
      <Project_id>23</Project_id>
      <Project_name>My test project</Project_name>
      <Task_contact_id>34</Task_contact_id>
      <Datetime_start>2014-04-12 10:32:34</
Datetime_start>
      <Datetime_due>2014-07-12 13:30:00</
Datetime_due>
      <Datetime_completed>2014-07-01 17:21:34</
Datetime_due>
    </ProjectTask>
    <ProjectTask>
      <AccountNumber>72039</AccountNumber>
      <Project_task_id>25</Project_update_id>
      <Task_description>Another Test Task</
Task_description>
      <Project_id>93</Project_id>
      <Project_name>My test project 2</Project_name>
```

```

        <Task_contact_id>214</Task_contact_id>
        <Datetime_start>2014-05-15 14:32:34</
Datetime_start>
        <Datetime_due>2014-07-23 17:00:00</
Datetime_due>
        <Datetime_completed>2014-07-21 13:21:34</
Datetime_due>
        </ProjectTask>
    </ProjectTasks>
    <TotalMatchingProjectTasks>2</
TotalMatchingProjectTasks>
</GetProjectTasksRequest>

```

Add Project Tasks

This function allows the caller to add one or more project tasks.

Input

Project_id (required), Contact_id (required), Task_description, Datetime_start (yyyy-mm-dd hh:mm:ss format), Datetime_due (yyyy-mm-dd hh:mm:ss format), Datetime_completed (yyyy-mm-dd hh:mm:ss format), Reminder_email_before_hours_due.

Output

For each project task,, success or failure, Project_update_id if successful, AccountNumber.

Example Request 1

```

<AddProjectTasksRequest>
  <ProjectTasks>
    <ProjectTask>
      <Project_id>93</Project_id>
      <Contact_id>24</Contact_id>
    </ProjectTask>
  </ProjectTasks>
</AddProjectTasksRequest>

```

```

        <Task_description>Test Task 1</
Task_description>
        <Datetime_start>2014-07-01 15:23:31</
Datetime_start>
        <Datetime_due>2014-07-31 17:00:00</
Datetime_due>
    </ProjectTask>
    <ProjectTask>
        <Project_id>56</Project_id>
        <Contact_id>12</Contact_id>
        <Task_description>Test Task 2</
Task_description>
        <Datetime_start>2014-08-01 11:38:31</
Datetime_start>
        <Datetime_completed>2014-08-31 13:03:22</
Datetime_start>
        <Datetime_due>2014-09-01 09:00:00</
Datetime_due>
    </ProjectTask>
</ProjectTasks>
</AddProjectTasksRequest>

```

Example Request 2 - Shared Access

```

<AddProjectTasksRequest>
    <ProjectTasks>
        <ProjectTask account_id="83920">
            <Project_id>93</Project_id>
            <Contact_id>24</Contact_id>
            <Task_description>Test Task 1</
Task_description>
            <Datetime_start>2014-07-01 15:23:31</
Datetime_start>
            <Datetime_due>2014-07-31 17:00:00</
Datetime_due>
        </ProjectTask>
        <ProjectTask account_id="54231">
            <Project_id>56</Project_id>
            <Contact_id>12</Contact_id>

```

```

        <Task_description>Test Task 2</
Task_description>
        <Datetime_start>2014-08-01 11:38:31</
Datetime_start>
        <Datetime_completed>2014-08-31 13:03:22</
Datetime_start>
        <Datetime_due>2014-09-01 09:00:00</
Datetime_due>
    </ProjectTask>
</ProjectTasks>
</AddProjectTasksRequest>

```

Successful Response

```

<AddProjectTasksResponse>
  <ProjectTasks>
    <ProjectTask>
      <Project_task_id>42</Project_task_id>
      <Result>Success</Result>
      <AccountNumber>92032</AccountNumber>
    </ProjectTask>
    <ProjectTask>
      <Project_task_id>82</Project_task_id>
      <Result>Success</Result>
      <AccountNumber>32133</AccountNumber>
    </ProjectTask>
  </ProjectTasks>
</AddProjectTasksResponse>

```

Edit Project Tasks

This function allows the caller to modify one or more project tasks already in the database. Search parameters should be specified inside the tag, while parameters to change to would be specified individually. Fields not specified would remain the same.

Input

Specify search criteria within the EditProjectTasksRequest tag. Search criteria can be Project_task_id, Project_id, Project_name, Task_description, Task_contact_id, Task_contact_firstname, Task_contact_lastname. Each project task's search criteria must return a single unique project task to modify. Parameters to change can include: Project_id, Contact_id, Task_description, Datetime_start (yyyy-mm-dd hh:mm:ss format), Datetime_due (yyyy-mm-dd hh:mm:ss format), Datetime_completed (yyyy-mm-dd hh:mm:ss format), Reminder_email_before_hours_due.

Output

For each project task, success or failure, Project_task_id, AccountNumber

Example Request 1

```
<EditProjectTasksRequest>
  <ProjectTasks>
    <ProjectTask Project_task_id="23">
      <Datetime_completed>2014-08-12 11:23:23</
Datetime_completed>
    </ProjectTask>
    <ProjectTask Project_task_id="93">
      <Project_id>21</Project_id>
      <Contact_id>12</Contact_id>
      <Task_description>New task description</
Task_description>
      <Datetime_start>2014-07-23 17:00:00</
Datetime_start>
      <Datetime_completed>2014-08-01 10:26:21</
Datetime_completed>
      <Datetime_due>2014-08-07 16:00:00</
Datetime_completed>
    </ProjectTask>
  </ProjectTasks>
</EditProjectTasksRequest>
```

Example Request 2 (Shared Access)

```
<EditProjectTasksRequest>
  <ProjectTasks>
    <ProjectTask Project_task_id="34"
account_id="32234">
      <Datetime_completed>2014-08-15 10:18:25</
Datetime_completed>
    </ProjectTask>
    <ProjectTask Project_task_id="88"
account_id="32235">
      <Project_id>56</Project_id>
      <Contact_id>8</Contact_id>
      <Task_description>New task description 2</
Task_description>
      <Datetime_start>2014-06-30 17:00:00</
Datetime_start>
      <Datetime_completed>2014-07-11 08:22:31</
Datetime_completed>
      <Datetime_due>2014-07-29 12:00:00</
Datetime_completed>
    </ProjectTask>
  </ProjectTasks>
</EditProjectTasksRequest>
```

Successful Response

```
<EditProjectTasksResponse>
  <ProjectTasks>
    <ProjectTask>
      <Project_task_id>82</Project_task_id>
      <Result>Success</Result>
      <AccountNumber>93203</AccountNumber>
    </ProjectTask>
    <ProjectTask>
      <Project_task_id>14</Project_task_id>
      <Result>Success</Result>
      <AccountNumber>23235</AccountNumber>
    </ProjectTask>
  </ProjectTasks>
```


</EditProjectTasksResponse>

Delete Project Tasks

This function allows the caller to delete one or more project tasks already in the database. Search parameters should be specified inside the tag.

Input

Specify search criteria within the DeleteProjectTasksRequest tag. Search criteria can be Project_task_id, Project_id, Project_name, Task_description, Task_contact_id, Task_contact_firstname, Task_contact_lastname. Each project task's search criteria must return a single unique project task to delete.

Output

For each project task, success or failure, Project_task_id, AccountNumber

Example Request 1

```
<DeleteProjectTasksRequest>
  <ProjectTasks>
    <ProjectTask Project_task_id="23"></ProjectTask>
    <ProjectTask Project_task_id="93"></ProjectTask>
  </ProjectTasks>
</DeleteProjectTasksRequest>
```

Example Request 2 (Shared Access)

```
<DeleteProjectTasksRequest>
  <ProjectTasks>
    <ProjectTask Project_task_id="34"
account_id="32234"></ProjectTask>
```

```
        <ProjectTask Project_task_id="88"
account_id="32235"></ProjectTask>
    </ProjectTasks>
</DeleteProjectTasksRequest>
```

Successful Response

```
<DeleteProjectTasksResponse>
    <ProjectTasks>
        <ProjectTask>
            <Project_task_id>82</Project_task_id>
            <Result>Success</Result>
            <AccountNumber>93203</AccountNumber>
        </ProjectTask>
        <ProjectTask>
            <Project_task_id>14</Project_task_id>
            <Result>Success</Result>
            <AccountNumber>23235</AccountNumber>
        </ProjectTask>
    </ProjectTasks>
</DeleteProjectTasksResponse>
```

Get Projects Power-Users

This function allows the caller to list contacts who are power-users (have the ability to add projects) for a given group.

Input

Pass the group ID. No shared access to this function since it is only available to account owners.

Output

Returns a list of projects power-users for the group

Example Request

```
<GetProjectsPowerUsersRequest group_id="28"></  
GetProjectsPowerUsersRequest>
```

Successful Response

```
<GetProjectsPowerUsersResponse>  
  <Account_id>82343</Account_id>  
  <Group_id>12</Group_id>  
  <ProjectsPowerUsers>  
    <ProjectsPowerUser>  
      <Contact_id>47</Contact_id>  
    </ProjectsPowerUser>  
    <ProjectsPowerUser>  
      <Contact_id>52</Contact_id>  
    </ProjectsPowerUser>  
</GetProjectsPowerUsersResponse>
```

Add Projects Power-Users

This function allows the caller to add contacts who are power-users (have the ability to add projects) to a given group.

Input

Pass the contact ID and the group ID. No shared access to this function since it is only available to account owners.

Output

For each contact passed, success or failure, contact ID, group ID.

Example Request

```
<AddProjectsPowerUsersRequest>  
  <ProjectsPowerUsers>  
    <ProjectsPowerUser group_id="22">  
      <Contact_id>83</Contact_id>  
    </ProjectsPowerUser>
```

```
    <ProjectsPowerUser group_id="51">
      <Contact_id>28</Contact_id>
    </ProjectsPowerUser>
  </ProjectsPowerUsers>
</AddProjectsPowerUsersRequest>
```

Successful Response

```
<AddProjectsPowerUsersResponse>
  <ProjectsPowerUsers>
    <ProjectsPowerUser>
      <Group_id>22</Group_id>
      <Contact_id>83</Contact_id>
    </ProjectsPowerUser>
    <ProjectsPowerUser>
      <Group_id>51</Group_id>
      <Contact_id>28</Contact_id>
    </ProjectsPowerUser>
  </ProjectsPowerUsers>
</AddProjectsPowerUsersResponse>
```

Remove Projects Power-Users

This function allows the caller to remove contacts from the list of power-users (have the ability to add projects) for a given group.

Input

Pass the contact ID and the group ID. No shared access to this function since it is only available to account owners.

Output

For each contact passed, success or failure, contact ID, group ID.

Example Request

```
<RemoveProjectsPowerUsersRequest>
```

```
<ProjectsPowerUsers>
  <ProjectsPowerUser group_id="22">
    <Contact_id>83</Contact_id>
  </ProjectsPowerUser>
  <ProjectsPowerUser group_id="51">
    <Contact_id>28</Contact_id>
  </ProjectsPowerUser>
</ProjectsPowerUsers>
</RemoveProjectsPowerUsersRequest>
```

Successful Response

```
<RemoveProjectsPowerUsersRequest>
  <ProjectsPowerUsers>
    <ProjectsPowerUser>
      <Group_id>22</Group_id>
      <Contact_id>83</Contact_id>
    </ProjectsPowerUser>
    <ProjectsPowerUser>
      <Group_id>51</Group_id>
      <Contact_id>28</Contact_id>
    </ProjectsPowerUser>
  </ProjectsPowerUsers>
</RemoveProjectsPowerUsersRequest>
```

Spec - SMS

Table Of Contents

- Get SMS Campaigns
- Add SMS Campaign
- Edit SMS Campaign
- Delete SMS Campaign
- Get CRM Activities SMSes
- Add SMS Response
- Edit SMS Response
- Delete SMS Response

Get SMS Campaigns

Retrieves the list of SMS campaigns.

Input

- account_id (required for shared access user)
- group_id (required for shared access user)

Output

Success or failure. List of SMS campaigns.

- CampaignID
- CampaignName
- GroupID
- GroupName
- FromPhoneNumber
- SendDatetime

- Message
- MMSimageURL
- NumRecipients

Example Request

```
<GetSMSCampaignsRequest/>
```

Example Request (Shared Access)

```
<GetSMSCampaignsRequest account_id="12345" group_id="1"/>
```

Example Response

```
<GetSMSCampaignsResponse>
  <Result>Success</Result>
  <SMSCampaigns>
    <SMSCampaign>
      <CampaignID>8</CampaignID>
      <CampaignName>Campaign 8</CampaignName>
      <GroupID>11</GroupID>
      <GroupName>Active Subscribers</GroupName>
      <FromPhoneNumber>+13302365946</FromPhoneNumber>
      <SendDatetime>2022-05-03T07:14:59-0700</
SendDatetime>
      <Message>Verifying.</Message>
      <MMSimageURL></MMSimageURL>
      <NumRecipients>1</NumRecipients>
    </SMSCampaign>
    <SMSCampaign>
      <CampaignID>9</CampaignID>
      <CampaignName>Campaign 9</CampaignName>
      <GroupID>11</GroupID>
      <GroupName>Active Subscribers</GroupName>
      <FromPhoneNumber>+13302365946</FromPhoneNumber>
      <SendDatetime>2022-05-05T08:52:42-0700</
SendDatetime>
      <Message>Verify Model::Job 2</Message>
      <MMSimageURL></MMSimageURL>
      <NumRecipients>1</NumRecipients>
    </SMSCampaign>
```

```
</SMSCampaigns>
</GetSMSCampaignsResponse>
```

Add SMS Campaign

Create a new SMS campaign.

Input

- account_id (required for shared access user)
- group_id (required for shared access user)
- CampaignName (required)
- GroupID (required)
- FromPhoneNumber (required, in international format, eg. +12125551234)
- SendDatetime (required, in ISO 8601 format, eg. 2025-01-06T16:41:09-07:00)
- Message (required)
- MMSimageURL (optional)
- RecipientContactIDs (required, list of contact IDs)

Output

Success or failure. New SMS campaign ID.

- CampaignID

Example Request

```
<AddSMSCampaignRequest>
  <CampaignName>Verify Campaign Name</CampaignName>
  <GroupID>4</GroupID>
  <FromPhoneNumber>+61488461116</FromPhoneNumber>
  <SendDatetime>2025-01-03T12:34:56Z</SendDatetime>
  <Message>The quick brown fox jumps over the lazy dog.</
Message>
  <MMSimageURL>https://test.com/test.jpg</MMSimageURL>
  <RecipientContactIDs>
```



```
        <RecipientContactID>123</RecipientContactID>
        <RecipientContactID>623</RecipientContactID>
    </RecipientContactIDs>
</AddSMSCampaignRequest>
```

Example Request (Shared Access)

```
<AddSMSCampaignRequest account_id="12345" group_id="1">
    <CampaignName>Verify Campaign Name</CampaignName>
    <GroupID>4</GroupID>
    <FromPhoneNumber>+61488461116</FromPhoneNumber>
    <SendDatetime>2025-01-03T12:34:56Z</SendDatetime>
    <Message>The quick brown fox jumps over the lazy dog.</
Message>
    <MMSimageURL>https://test.com/test.jpg</MMSimageURL>
    <RecipientContactIDs>
        <RecipientContactID>123</RecipientContactID>
        <RecipientContactID>623</RecipientContactID>
    </RecipientContactIDs>
</AddSMSCampaignRequest>
```

Example Response

```
<AddSMSCampaignResponse>
    <Result>Success</Result>
    <CampaignID>11</CampaignID>
</AddSMSCampaignResponse>
```

Edit SMS Campaign

Update an existing SMS campaign.

Input

- account_id (required for shared access user)
- group_id (required for shared access user)
- campaign_id (required)
- CampaignName (optional)

- FromPhoneNumber (optional, in international format, eg. +12125551234)
- SendDatetime (optional, in ISO 8601 format, eg. 2025-01-06T16:41:09-07:00)
- Message (optional)
- MMSimageURL (optional)

Output

Success or failure. The SMS campaign ID.

- CampaignID

Example Request

```
<EditSMSCampaignRequest campaign_id="11">
  <CampaignName>Edit Verify Name</CampaignName>
  <FromPhoneNumber>+15155551212</FromPhoneNumber>
  <SendDatetime>2025-01-03T12:34:57Z</SendDatetime>
  <Message>the quick brown fox jumps over the lazy dog.</
Message>
  <MMSimageURL>https://edit.com/test.jpg</MMSimageURL>
</EditSMSCampaignRequest>
```

Example Request (Shared Access)

```
<EditSMSCampaignRequest campaign_id="11" account_id="12345"
group_id="1">
  <CampaignName>Edit Verify Name</CampaignName>
  <FromPhoneNumber>+15155551212</FromPhoneNumber>
  <SendDatetime>2025-01-03T12:34:57Z</SendDatetime>
  <Message>the quick brown fox jumps over the lazy dog.</
Message>
  <MMSimageURL>https://edit.com/test.jpg</MMSimageURL>
</EditSMSCampaignRequest>
```

Example Response

```
<EditSMSCampaignResponse>
  <Result>Success</Result>
```

```
<CampaignID>11</CampaignID>
</EditSMSCampaignResponse>
```

Delete SMS Campaign

Remove an existing SMS campaign.

Input

- account_id (required for shared access user)
- group_id (required for shared access user)
- campaign_id (required)

Output

Success or failure. The SMS campaign ID.

- CampaignID

Example Request

```
<DeleteSMSCampaignRequest campaign_id="10"/>
```

Example Request (Shared Access)

```
<DeleteSMSCampaignRequest campaign_id="10"
account_id="12345" group_id="1"/>
```

Example Response

```
<DeleteSMSCampaignResponse>
  <Result>Success</Result>
  <CampaignID>11</CampaignID>
</DeleteSMSCampaignResponse>
```

Get CRM Activities SMSes

Retrieves the list of SMS campaigns and responses for a contact.

Input

- account_id (required for shared access user)
- group_id (required for shared access user)
- contact_id (required)

Output

Success or failure. List of SMS campaigns and responses.

- CampaignID
- CampaignName
- CampaignType
- SendDatetime
- SendDatetimeUTC
- FromPhoneNumber
- Message
- MMSImageURL
- ResponseID
- Reponse
- ResponseDatetime
- ResponseDatetimeUTC

Example Request

```
<GetCRMActivitiesSMSesRequest contact_id="623"/>
```

Example Request (Shared Access)

```
<GetCRMActivitiesSMSesRequest contact_id="623"
account_id="12345" group_id="1"/>
```

Example Response

```
<GetCRMActivitiesSMSesResponse>
  <Result>Success</Result>
  <SMSes>
    <SMS>
      <CampaignID>12</CampaignID>
      <CampaignName>Verify Campaign Name</
CampaignName>
```

```

        <CampaignType>MMS</CampaignType>
        <SendDatetime>20250103043456</SendDatetime>
        <SendDatetimeUTC>2025-01-03T12:34:00Z</
SendDatetimeUTC>
        <FromPhoneNumber>+61488461116</FromPhoneNumber>
        <Message>The quick brown fox jumps over the
lazy dog.</Message>
        <MMSImageURL>https://test.com/test.jpg</
MMSImageURL>
        <Response></Response>
        <ResponseID></ResponseID>
        <ResponseDatetime></ResponseDatetime>
        <ResponseDatetimeUTC></ResponseDatetimeUTC>
</SMS>
<SMS>
    <CampaignID>12</CampaignID>
    <CampaignName>Verify Campaign Name</
CampaignName>
    <CampaignType>SMS</CampaignType>
    <SendDatetime></SendDatetime>
    <SendDatetimeUTC></SendDatetimeUTC>
    <FromPhoneNumber></FromPhoneNumber>
    <Message></Message>
    <MMSImageURL></MMSImageURL>
    <Response>The quickbrown fox jumps over the
lazy dog.</Response>
    <ResponseID>4</ResponseID>
    <ResponseDatetime>20250103043454</
ResponseDatetime>
    <ResponseDatetimeUTC>2025-01-03T12:34:00Z</
ResponseDatetimeUTC>
</SMS>
</SMSes>
</GetCRMActivitiesSMSesResponse>

```

Add SMS Response

Create a new SMS response.

Input

- account_id (required for shared access user)
- group_id (required for shared access user)
- campaign_id (required)
- ContactID (required)
- FromNumber (required, in international format, eg. +12125551234)
- Response (optional)
- ResponseDatetime (required, in ISO 8601 format, eg. 2025-01-06T16:41:09-07:00)

Output

Success or failure. New SMS response ID.

- ResponseID

Example Request

```
<AddSMSResponseRequest campaign_id="12">
  <ContactID>623</ContactID>
  <FromNumber>+15155551214</FromNumber>
  <Response>The quickbrown fox jumps over the lazy dog.</
Response>
  <ResponseDatetime>2025-01-03T12:34:54Z</
ResponseDatetime>
</AddSMSResponseRequest>
```

Example Request (Shared Access)

```
<AddSMSResponseRequest campaign_id="12" account_id="12345"
group_id="1">
  <ContactID>623</ContactID>
  <FromNumber>+15155551214</FromNumber>
  <Response>The quickbrown fox jumps over the lazy dog.</
Response>
  <ResponseDatetime>2025-01-03T12:34:54Z</
ResponseDatetime>
</AddSMSResponseRequest>
```

Example Response

```
<AddSMSResponseResponse>
  <Result>Success</Result>
  <ResponseID>3</ResponseID>
</AddSMSResponseResponse>
```

Edit SMS Response

Update an existing SMS response.

Input

- account_id (required for shared access user)
- group_id (required for shared access user)
- campaign_id (required)
- response_id (required)
- ContactID (optional)
- FromNumber (optional, in international format, eg. +12125551234)
- Response (optional)
- ResponseDatetime (optional, in ISO 8601 format, eg. 2025-01-06T16:41:09-07:00)

Output

Success or failure. The SMS response ID.

- ResponseID

Example Request

```
<EditSMSResponseRequest campaign_id="12" response_id="3">
  <ContactID>623</ContactID>
  <FromNumber>+15155551212</FromNumber>
  <Response>Thequickbrown fox jumps over the lazy dog.</
Response>
  <ResponseDatetime>2025-01-03T12:34:56Z</
ResponseDatetime>
</EditSMSResponseRequest>
```

Example Request (Shared Access)

```
<EditSMSResponseRequest campaign_id="12" response_id="3"
account_id="12345" group_id="1">
  <ContactID>623</ContactID>
  <FromNumber>+15155551212</FromNumber>
  <Response>Thequickbrown fox jumps over the lazy dog.</
Response>
  <ResponseDatetime>2025-01-03T12:34:56Z</
ResponseDatetime>
</EditSMSResponseRequest>
```

Example Response

```
<EditSMSResponseResponse>
  <Result>Success</Result>
  <ResponseID>3</ResponseID>
</EditSMSResponseResponse>
```

Delete SMS Response

Remove an existing SMS response.

Input

- account_id (required for shared access user)
- group_id (required for shared access user)
- campaign_id (required)
- response_id (required)

Output

Success or failure. The SMS response ID.

- ResponseID

Example Request


```
<DeleteSMSResponseRequest campaign_id="12" response_id="3"/>
```

Example Request (Shared Access)

```
<DeleteSMSResponseRequest campaign_id="12" response_id="3"
account_id="12345" group_id="1"/>
```

Example Response

```
<DeleteSMSResponseResponse>
  <Result>Success</Result>
  <ResponseID>3</ResponseID>
</DeleteSMSResponseResponse>
```

Spec - Store

Table Of Contents

- Get Store Item Categories
- Add Store Item Categories
- Edit Store Item Categories
- Get Store Items
- Add Store Items
- Edit Store Items
- Add Store Shopping Cart
- Add Store Purchase

Get Store Item Categories

This function allows the caller to retrieve Store Item Categories from the database. Search parameters should be specified inside the tag. Store Item Categories can be retrieved by category ID, category name, or group (ID or Name). Leaving all search criteria blank would return all of the Store Item Categories in the account.

Input

Specify search criteria within the GetStoreItemCategoriesRequest tag. Search criteria can be category_id, category_name, group_id (return all item categories associated with a group), group_name. If no search criteria, return all Store Item Categories in the account.

Output

Success or failure. For each Store Item Category found: Category_id, Category_name, Group_id, Group_name.

Example Request 1

```
<GetStoreItemCategoriesRequest></  
GetStoreItemCategoriesRequest>
```

Example Request 2

```
<GetStoreItemCategoriesRequest category_id="4"></  
GetStoreItemCategoriesRequest>
```

Example Request 3

```
<GetStoreItemCategoriesRequest group_name="my_group"></  
GetStoreItemCategoriesRequest>
```

Successful Response

```
<GetStoreItemCategoriesResponse>  
  <Result>Success</Result>  
  <StoreItemCategories>  
    <StoreItemCategory>  
      <Category_id>4</Category_id>  
      <Category_name>My Category 4</Category_name>  
      <Group_id>8</Group_id>  
      <Group_name>Test Group</Group_name>  
    </StoreItemCategory>  
    <StoreItemCategory>  
      <Category_id>5</Category_id>  
      <Category_name>My Category 5</Category_name>  
      <Group_id>10</Group_id>  
      <Group_name>Another Test Group</Group_name>  
    </StoreItemCategory>  
  </StoreItemCategories>  
</GetStoreItemCategoriesResponse>
```

Add Store Item Categories

This function allows the caller to add one or more Store Item Categories.

Input

- request_id (optional)
- Category_name (required)
- Group_id (required)

Output

For each Store Item Category, success or failure.

Example Request

```
<AddStoreItemCategoriesRequest>
  <StoreItemCategories>
    <StoreItemCategory request_id="a1b2c3">
      <Category_name>My Item Category 1</
Category_name>
      <Group_id>8</Group_id>
    </StoreItemCategory>
    <StoreItemCategory request_id="d4e5f6">
      <Category_name>My Item Category 2</
Category_name>
      <Group_id>9</Group_id>
    </StoreItemCategory>
  </StoreItemCategories>
</AddStoreItemCategoriesRequest>
```

Successful Response

```
<AddStoreItemCategoriesResponse>
  <StoreItemCategories>
    <StoreItemCategory request_id="a1b2c3">
      <Category_id>41</Category_id>
      <Result>Success</Result>
    </StoreItemCategory>
    <StoreItemCategory request_id="d4e5f6">
      <Category_id>42</Category_id>
      <Result>Success</Result>
    </StoreItemCategory>
  </StoreItemCategories>
</AddStoreItemCategoriesResponse>
```

Edit Store Item Categories

This function allows the caller to edit one or more Store Item Categories.

Input

Search criteria for each Store Item Category to edit. Search criteria can be:

- category_id
- category_name
- group_id (return all item categories associated with a group)
- group_name
- request_id (optional)

A single Store Item Category to edit must be returned by each set of search criteria.

For each Store Item Category to edit:

- Category_name
- Group_id

Output

For each Store Item Category, success or failure.

Example Request

```
<EditStoreItemCategoriesRequest>
  <StoreItemCategories>
    <StoreItemCategory category_id="9"
request_id="a1b2c3">
      <Category_name>My New Item Category 3</
Category_name>
      <Group_id>9</Group_id>
    </StoreItemCategory>
```

```

        <StoreItemCategory category_name="My Item Category
2" request_id="d4e5f6">
            <Category_name>My Item New Category 4</
Category_name>
            <Group_id>11</Group_id>
        </StoreItemCategory>
    </StoreItemCategories>
</EditStoreItemCategoriesRequest>

```

Successful Response

```

<EditStoreItemCategoriesResponse>
    <StoreItemCategories>
        <StoreItemCategory request_id="a1b2c3">
            <Category_id>9</Category_id>
            <Result>Success</Result>
        </StoreItemCategory>
        <StoreItemCategory request_id="d4e5f6">
            <Category_id>21</Category_id>
            <Result>Success</Result>
        </StoreItemCategory>
    </StoreItemCategories>
</EditStoreItemCategoriesResponse>

```

Get Store Items

This function allows the caller to retrieve Store Items from the database. Search parameters should be specified inside the tag. Store Items can be retrieved by item ID, item name, category ID, category name, or group (ID or Name). Leaving all search criteria blank would return all of the Store Items in the account.

Input

Specify search criteria within the GetStoreItemsRequest tag. Search criteria can be item_id, item_name, category_id, category_name, group_id (return all store items associated with a group), group_name. If no search criteria, return all Store Items in the account.

Output

Success or failure. For each Store Item found: Item_id, Item_name, Category_id, Category_name, Group_id, Group_name, Featured_item (Y or N), Item_image_url, Item_description, Item_custom_fieldname1, Item_custom_fielddoptions1, Item_custom_fielddoptionscosts1, Item_custom_inventories1, Item_custom_fieldname2, Item_custom_fielddoptions2, Item_custom_fielddoptionscosts2, Item_custom_fieldname3, Item_custom_fielddoptions3, Item_custom_fielddoptionscosts3, Shipping_options, Shipping_costs, Purchase_conversion_script, Download_url, Num_downloads, Item_price, Item_cost, Current_inventory, Annual_recurring_charge, Monthly_recurring_charge.

Example Request 1

```
<GetStoreItemsRequest></GetStoreItemsRequest>
```

Example Request 2

```
<GetStoreItemsRequest item_id="212"></GetStoreItemsRequest>
```

Example Request 3

```
<GetStoreItemsRequest group_name="my_group"></GetStoreItemsRequest>
```

Successful Response

```
<GetStoreItemsResponse>
  <Result>Success</Result>
  <StoreItems>
    <StoreItem>
      <Item_id>28</Item_id>
      <Item_name>Test Item 1</Item_name>
      <Category_id>14</Category_id>
      <Category_name>My Category 14</Category_name>
      <Group_id>27</Group_id>
```

```

        <Group_name>Test Group 27</Group_name>
        <Featured_item></Featured_item>
        <Item_image_url></Item_image_url>
        <Item_description>This is a description of this
item.</Item_description>
        <Item_custom_fieldname1></
Item_custom_fieldname1>
        <Item_custom_fielddoptions1></
Item_custom_fielddoptions1>
        <Item_custom_fielddoptionscosts1></
Item_custom_fielddoptionscosts1>
        <Item_custom_inventories1></
Item_custom_inventories1>
        <Item_custom_fieldname2></
Item_custom_fieldname2>
        <Item_custom_fielddoptions2></
Item_custom_fielddoptions2>
        <Item_custom_fielddoptionscosts2></
Item_custom_fielddoptionscosts2>
        <Item_custom_fieldname3></
Item_custom_fieldname3>
        <Item_custom_fielddoptions3></
Item_custom_fielddoptions3>
        <Item_custom_fielddoptionscosts3></
Item_custom_fielddoptionscosts3>
        <Shipping_options></Shipping_options>
        <Shipping_costs></Shipping_costs>
        <Purchase_conversion_script></
Purchase_conversion_script>
        <Download_url></Download_url>
        <Num_downloads></Num_downloads>
        <Item_price>199.95</Item_price>
        <Item_cost></Item_cost>
        <Current_inventory></Current_inventory>
        <Annual_recurring_charge>N</
Annual_recurring_charge>
        <Monthly_recurring_charge>N</
Monthly_recurring_charge>
    </StoreItem>
    <StoreItem>

```



```

        <Item_id>31</Item_id>
        <Item_name>Test Item 2</Item_name>
        <Category_id>15</Category_id>
        <Category_name>My Category 15</Category_name>
        <Group_id>28</Group_id>
        <Group_name>Test Group 28</Group_name>
        <Featured_item></Featured_item>
        <Item_image_url></Item_image_url>
        <Item_description>This is a description of
another item.</Item_description>
        <Item_custom_fieldname1></
Item_custom_fieldname1>
        <Item_custom_fieldoptions1></
Item_custom_fieldoptions1>
        <Item_custom_fieldoptionscosts1></
Item_custom_fieldoptionscosts1>
        <Item_custom_inventories1></
Item_custom_inventories1>
        <Item_custom_fieldname2></
Item_custom_fieldname2>
        <Item_custom_fieldoptions2></
Item_custom_fieldoptions2>
        <Item_custom_fieldoptionscosts2></
Item_custom_fieldoptionscosts2>
        <Item_custom_fieldname3></
Item_custom_fieldname3>
        <Item_custom_fieldoptions3></
Item_custom_fieldoptions3>
        <Item_custom_fieldoptionscosts3></
Item_custom_fieldoptionscosts3>
        <Shipping_options></Shipping_options>
        <Shipping_costs></Shipping_costs>
        <Purchase_conversion_script></
Purchase_conversion_script>
        <Download_url></Download_url>
        <Num_downloads></Num_downloads>
        <Item_price>39.95</Item_price>
        <Item_cost></Item_cost>
        <Current_inventory></Current_inventory>

```

```
        <Annual_recurring_charge>N</
Annual_recurring_charge>
        <Monthly_recurring_charge>N</
Monthly_recurring_charge>
    </StoreItem>
</StoreItems>
</GetStoreItemsResponse>
```

Add Store Items

This function allows the caller to add one or more Store Items.

Input

- request_id (optional)
- Item_name (required)
- Category_id
- Group_id (required)
- Featured_item (Y or N)
- Item_image_url
- Item_description
- Item_custom_fieldname1
- Item_custom_fieldoptions1
- Item_custom_fieldoptionscosts1
- Item_custom_inventories1
- Item_custom_fieldname2
- Item_custom_fieldoptions2
- Item_custom_fieldoptionscosts2
- Item_custom_fieldname3
- Item_custom_fieldoptions3
- Item_custom_fieldoptionscosts3
- Shipping_options
- Shipping_costs
- Purchase_conversion_script
- Download_url

- Num_downloads
- Item_price
- Item_cost
- Current_inventory
- Annual_recurring_charge (Y or N)
- Monthly_recurring_charge (Y or N)

Output

For each Store Item, success or failure, Item_id.

Example Request

```
<AddStoreItemsRequest>
  <StoreItems>
    <StoreItem request_id="a1b2c3">
      <Group_id>1</Group_id>
      <Item_name>Test Item 1</Item_name>
      <Item_description>Test Item 1 Description</
Item_description>
      <Category_id>23</Category_id>
    </StoreItem>
    <StoreItem request_id="d4e5f6">
      <Group_id>1</Group_id>
      <Item_name>Test Item 1</Item_name>
      <Item_description>Test Item 1 Description</
Item_description>
      <Category_id>23</Category_id>
    </StoreItem>
  </StoreItems>
</AddStoreItemsRequest>
```

Successful Response

```
<AddStoreItemsResponse>
  <StoreItems>
    <StoreItem request_id="a1b2c3">
      <Item_id>214</Item_id>
      <Result>Success</Result>
```

```
        </StoreItem>
        <StoreItem request_id="d4e5f6">
            <Item_id>215</Item_id>
            <Result>Success</Result>
        </StoreItem>
    </StoreItems>
</AddStoreItemsResponse>
```

Edit Store Items

This function allows the caller to edit one or more Store Items.

Input

Search criteria for each Store Item to edit. Search criteria can be:

- item_id
- item_name
- category_id
- category_name
- group_id
- group_name
- request_id (optional)

A single Store Item to edit must be returned by each set of search criteria.

For each Store Item to edit, the following parameters may be changed:

- Item_name
- Category_id
- Group_id
- Featured_item (Y or N)
- Item_image_url
- Item_description
- Item_custom_fieldname1
- Item_custom_fielddoptions1

- Item_custom_fieldoptionscosts1
- Item_custom_inventories1
- Item_custom_fieldname2
- Item_custom_fieldoptions2
- Item_custom_fieldoptionscosts2
- Item_custom_fieldname3
- Item_custom_fieldoptions3
- Item_custom_fieldoptionscosts3
- Shipping_options
- Shipping_costs
- Purchase_conversion_script
- Download_url
- Num_downloads
- Item_price
- Item_cost
- Current_inventory
- Annual_recurring_charge (Y or N)
- Monthly_recurring_charge (Y or N)

Output

For each Store Item, success or failure, along with the Item ID.

Example Request

```
<EditStoreItemsRequest>
  <StoreItems>
    <StoreItem item_id="39" request_id="a1b2c3">
      <Group_id>21</Group_id>
      <Item_name>Test New Item 10</Item_name>
      <Item_description>Test New Item 10
Description</Item_description>
      <Category_id>27</Category_id>
    </StoreItem>
    <StoreItem item_name="My Item 2"
request_id="d4e5f6">
```

```

        <Group_id>24</Group_id>
        <Item_name>Test New Item 22</Item_name>
        <Item_description>Test New Item 22
Description</Item_description>
        <Category_id>29</Category_id>
    </StoreItem>
</StoreItems>
</EditStoreItemsRequest>

```

Successful Response

```

<EditStoreItemsResponse>
    <StoreItems>
        <StoreItem request_id="a1b2c3">
            <Item_id>39</Category_id>
            <Result>Success</Result>
        </StoreItem>
        <StoreItem request_id="d4e5f6">
            <Item_id>41</Item_id>
            <Result>Success</Result>
        </StoreItem>
    </StoreItems>
</EditStoreItemsResponse>

```

Add Store Shopping Cart

This function allows the caller to a shopping cart, consisting of one or more items..

Input

Group_id (required), CreationDate. For each item in cart, Item_id, Custom_option1, Custom_option2, Custom_option3, Shipping_option, Quantity, SubtotalAmount, Times_downloaded.

Output

Success or failure, Cart_id.

Example Request

```
<AddStoreShoppingCartRequest>
  <Group_id>1</Group_id>
  <CreationDate>2014-01-23 12:23:34</CreationDate>
  <Items>
    <Item>
      <Item_id>1</Item_id>
      <Quantity>2</Quantity>
      <SubtotalAmount>35.00</SubtotalAmount>
    </Item>
    <Item>
      <Item_id>2</Item_id>
      <Quantity>3</Quantity>
      <SubtotalAmount>45.00</SubtotalAmount>
    </Item>
  </Items>
</AddStoreShoppingCartRequest>
```

Successful Response

```
<AddStoreShoppingCartResponse>
  <Cart_id>432</Cart_id>
  <Result>Success</Result>
</AddStoreShoppingCartResponse>
```

Add Store Purchase

This function allows the caller to mark a shopping cart as purchased, with an associated transaction ID..

Input

Cart_id (required), Group_id, PurchaserEmail, PurchaserIP, TransactionDate (required), TransactionAmount (required), Transaction_id (required).

Output

Success or failure.

Example Request

```
<AddStorePurchaseRequest>
  <Group_id>1</Group_id>
  <Cart_id>232</Cart_id>
  <CreationDate>2014-01-23 12:23:34</CreationDate>
  <PurchaserEmail>myemail@myemail.com</PurchaserEmail>
  <PurchaserIP>127.0.0.1</PurchaserIP>
  <TransactionDate>2014-02-05</TransactionDate>
  <TransactionAmount>59.00</TransactionAmount>
  <Transaction_id>3987a89f0908d</Transaction_id>
</AddStorePurchaseRequest>
```

Successful Response

```
<AddStorePurchaseResponse>
  <Result>Success</Result>
</AddStorePurchaseResponse>
```


Spec - Tags

Table Of Contents

- Get Tags
- Add Tags
- Add Tags To Contact
- Delete Tags From Contact

Get Tags

This API retrieves the tags under the user account.

Input

- account_id (required for shared access users)
- group_id (required for shared access users)

Output

Success or failure. List of tags under the user account.

Example Request

```
<GetTagsRequest/>
```

Example Request

```
<GetTagsRequest account_id="12345" group_id="1"/>
```

Example Response

```
<GetTagsResponse>  
  <Result>Success</Result>  
  <Tags>  
    <Tag>
```

```
        <TagID>182745</TagID>
        <TagName>chief executive officer</TagName>
        <Abbreviation>CEO</Abbreviation>
    </Tag>
    <Tag>
        <TagID>182746</TagID>
        <TagName>chief operating officer</TagName>
        <Abbreviation>COO</Abbreviation>
    </Tag>
    <Tag>
        <TagID>192887</TagID>
        <TagName>Facebook User</TagName>
        <Abbreviation>FB</Abbreviation>
    </Tag>
    <Tag>
        <TagID>192890</TagID>
        <TagName>Linkedin User</TagName>
        <Abbreviation>LI</Abbreviation>
    </Tag>
    <Tag>
        <TagID>192889</TagID>
        <TagName>Twitter User</TagName>
        <Abbreviation>TW</Abbreviation>
    </Tag>
</Tags>
</GetTagsResponse>
```

Add Tags

This API call adds new tag(s) to the user account.

Input

- account_id (required for shared access users)
- group_id (required for shared access users)
- request_id (optional)
- TagName (required)
- Abbreviation (required)

Output

Success or failure for each tags with its new TagID.

Example Request

```
<AddTagsRequest>
  <Tags>
    <Tag request_id="a1b2c3">
      <TagName>Chief Executive Officer</TagName>
      <Abbreviation>CEO</Abbreviation>
    </Tag>
    <Tag request_id="d4e5f6">
      <TagName>Chief Operating Officer</TagName>
      <Abbreviation>COO</Abbreviation>
    </Tag>
  </Tags>
</AddTagsRequest>
```

Example Request

```
<AddTagsRequest account_id="12345" group_id="1">
  <Tags>
    <Tag>
      <TagName>Chief Operating Officer</TagName>
      <Abbreviation>COO</Abbreviation>
    </Tag>
  </Tags>
</AddTagsRequest>
```

Example Response

```
<AddTagsResponse>
  <Tags>
    <Tag request_id="a1b2c3">
      <Result>Success</Result>
      <TagID>194498</TagID>
    </Tag>
    <Tag request_id="d4e5f6">
      <Result>Success</Result>
    </Tag>
  </Tags>
</AddTagsResponse>
```

```
        <TagID>194499</TagID>
      </Tag>
    </Tags>
  </AddTagsResponse>
```

Add Tags To Contact

This API call assign tag(s) to a contact.

Input

- account_id (required for shared access users)
- group_id (required for shared access users)
- contact_id (required)
- request_id (optional)
- Tag with tag_id (required)

Output

Success or failure for each tags specified.

Example Request

```
<AddTagsToContactRequest contact_id="123">
  <Tags>
    <Tag tag_id="194498" request_id="a1b2c3"/>
    <Tag tag_id="194499" request_id="d4e5f6"/>
  </Tags>
</AddTagsToContactRequest>
```

Example Request

```
<AddTagsToContactRequest account_id="12345" group_id="1"
contact_id="123">
  <Tags>
    <Tag tag_id="194498"/>
  </Tags>
</AddTagsToContactRequest>
```

Example Response

```
<AddTagsToContactResponse>
  <Tags>
    <Tag request_id="a1b2c3">
      <Result>Success</Result>
      <TagID>194498</TagID>
    </Tag>
    <Tag request_id="d4e5f6">
      <Result>Success</Result>
      <TagID>194499</TagID>
    </Tag>
  </Tags>
</AddTagsToContactResponse>
```

Delete Tags From Contact

This API call removes tag(s) from a contact.

Input

- account_id (required for shared access users)
- group_id (required for shared access users)
- contact_id (required)
- request_id (optional)
- Tag with tag_id (required)

Output

Success or failure for each tags specified.

Example Request

```
<DeleteTagsFromContactRequest contact_id="123">
  <Tags>
    <Tag tag_id="194498" request_id="a1b2c3"/>
    <Tag tag_id="194499" request_id="d4e5f6"/>
  </Tags>
</DeleteTagsFromContactRequest>
```

```
    </Tags>
</DeleteTagsFromContactRequest>
```

Example Request

```
<DeleteTagsFromContactRequest account_id="12345"
group_id="1" contact_id="123">
  <Tags>
    <Tag tag_id="194498"/>
  </Tags>
</DeleteTagsFromContactRequest>
```

Example Response

```
<DeleteTagsFromContactResponse>
  <Tags>
    <Tag request_id="a1b2c3">
      <Result>Success</Result>
      <TagID>194498</TagID>
    </Tag>
    <Tag request_id="d4e5f6">
      <Result>Success</Result>
      <TagID>194499</TagID>
    </Tag>
  </Tags>
</DeleteTagsFromContactResponse>
```

Spec - Tickets

Table Of Contents

- Get Tickets
- Add Ticket
- Edit Ticket
- Get Ticket Updates
- Add Ticket Update
- Get Ticket Categories
- Get Ticket Forms

Get Tickets

This function allows the caller to retrieve a company's list of tickets from the database.

Search parameters should be specified inside the tag.

Shared access users must have contacts permission to the account in order to perform this action.

Input

- account_id (required for shared access users)
- group_id
- company_id
- ticket_id (optional, to fetch a single ticket)
- page (1, 2, 3, etc.)
- include_ticket_updates (true/false)

Output

Success or failure. List of tickets.

Example Request

```
<GetTicketsRequest></GetTicketsRequest>
```

Example Request

```
<GetTicketsRequest group_id="4" company_id="1"></  
GetTicketsRequest>
```

Example Request

```
<GetTicketsRequest group_id="4" company_id="1" page="1"></  
GetTicketsRequest>
```

Example Request

```
<GetTicketsRequest ticket_id="1" page="1"></  
GetTicketsRequest>
```

Example Request (include ticket updates in response)

```
<GetTicketsRequest include_ticket_updates="true"  
page="1"></GetTicketsRequest>
```

Successful Response

```
<GetTicketsResponse>  
  <Result>Success</Result>  
  <Tickets>  
    <Ticket>  
      <TicketID>2</TicketID>  
      <Firstname>Todd</Firstname>  
      <Lastname>Smith</Lastname>  
      <Email>todd@smith.com</Email>  
      <TicketSummary>Test</TicketSummary>  
      <Status>Open (Escalated)</Status>  
      <CreatedDatetime>20141027103646</  
CreatedDatetime>  
      <ClosedDatetime></ClosedDatetime>  
    </Ticket>
```



```

    <Ticket>
      <TicketID>18</TicketID>
      <Firstname>Test</Firstname>
      <Lastname>Wade</Lastname>
      <Email>contact.test@gmail.com</Email>
      <TicketSummary>Test</TicketSummary>
      <Status>Closed</Status>
      <CreatedDatetime>20141113052054</
CreatedDatetime>
      <ClosedDatetime>20141120193949</ClosedDatetime>
    </Ticket>
    <Ticket>
      <TicketID>19</TicketID>
      <Firstname>Test</Firstname>
      <Lastname>Wade</Lastname>
      <Email>contact.test2@gmail.com</Email>
      <TicketSummary>Test</TicketSummary>
      <Status>Open</Status>
      <CreatedDatetime>20141113061011</
CreatedDatetime>
      <ClosedDatetime></ClosedDatetime>
    </Ticket>
    <Ticket>
      <TicketID>20</TicketID>
      <Firstname>Test</Firstname>
      <Lastname>Wade</Lastname>
      <Email>contact.test@gmail.com</Email>
      <TicketSummary>Test</TicketSummary>
      <Status>Open</Status>
      <CreatedDatetime>20141119055612</
CreatedDatetime>
      <ClosedDatetime></ClosedDatetime>
    </Ticket>
  </Tickets>
</GetTicketsResponse>

```

Successful Response (include_ticket_updates="true")

```

<GetTicketsResponse>
  <Result>Success</Result>

```

```

<Tickets>
  <Ticket>
    <TicketID>2</TicketID>
    <Firstname>Todd</Firstname>
    <Lastname>Smith</Lastname>
    <Email>todd@smithco.com</Email>
    <TicketSummary>Test</TicketSummary>
    <Status>Open</Status>
    <CreatedDatetime>20141027103646</
CreatedDatetime>
    <ClosedDatetime></ClosedDatetime>
    <TicketUpdates>
      <TicketUpdate>
        <TicketUpdateID>1</TicketUpdateID>
        <UpdateDatetime>20140724104145</
UpdateDatetime>
        <ContactID>627</ContactID>
        <Firstname>Todd</Firstname>
        <Lastname>Smith</Lastname>
        <Email>toddsmith.test@gmail.com</Email>
        <Content><![CDATA[Test ticket
details<br>]]></Content>
        <ImageURL></ImageURL>
        <ImageSizeKB>0</ImageSizeKB>
        <UpdateIP></UpdateIP>
      </TicketUpdate>
    </TicketUpdates>
  </Ticket>
</Tickets>
</GetTicketsResponse>

```

Add Ticket

Call this API to add a new ticket.

Lookup ContactID or ContactEmail with GetContactsRequest.

Lookup CategoryID with GetTicketCategoriesRequest.

Lookup FormID with GetTicketFormsRequest.

Input

- account_id (required for shared access users)
- group_id (required for shared access users)
- ContactID or ContactEmail (required, contact must exists)
- CategoryID (required)
- FormID (required)
- Summary (required)
- Detail (required, text or escaped-XML entity sets allowed, eg. `£` will not work, use `£` instead. Basic entities like `<`, `>`, `&`, `'`, and `"` will work just fine.)

Output

Success or failure for ticket.

Example Request (ContactID)

```
<AddTicketRequest>
  <Ticket>
    <ContactID>1</ContactID>
    <CategoryID>2</CategoryID>
    <FormID>2</FormID>
    <Summary>One line ticket title or description</
Summary>
    <Detail>&lt;p&gt;Long explanation of ticket&lt;/
p&gt;&lt;p&gt;New line&lt;/p&gt;</Detail>
  </Ticket>
</AddTicketRequest>
```

Example Request (ContactEmail)

```
<AddTicketRequest>
  <Ticket>
    <ContactEmail>john.smith@gmail.com</ContactEmail>
    <CategoryID>2</CategoryID>
```

```
        <FormID>2</FormID>
        <Summary>One line ticket title or description</
Summary>
        <Detail>Long explanation of ticket</Detail>
    </Ticket>
</AddTicketRequest>
```

Example Request (shared access users)

```
<AddTicketRequest account_id="12345" group_id="1">
    <Ticket>
        <ContactID>1</ContactID>
        <CategoryID>2</CategoryID>
        <FormID>2</FormID>
        <Summary>One line ticket title or description</
Summary>
        <Detail>Long explanation of ticket</Detail>
    </Ticket>
</AddTicketRequest>
```

Example Response

```
<AddTicketResponse>
    <Result>Success</Result>
    <Ticket>
        <TicketID>41</TicketID>
        <ContactID>1</ContactID>
        <CategoryID>2</CategoryID>
        <FormID>2</FormID>
        <Summary>One line ticket title or description</
Summary>
        <Detail>Long explanation of ticket</Detail>
    </Ticket>
</AddTicketResponse>
```

Edit Ticket

Call this API to update the ticket status, change the ticket category and/or assign the ticket to a new contact.

Input

- ticket_id (required)
- account_id (required for shared access users)
- group_id (required for shared access users)
- Status ('Open'/'Open (Escalated)'/ 'Closed'/'Closed (Locked)')
- CategoryID
- AssignedToContactID

Output

Success or failure for ticket.

Example Request

```
<EditTicketRequest ticket_id="32">  
  <Ticket>  
    <Status>Open</Status>  
    <CategoryID>3</CategoryID>  
    <AssignedToContactID>623</AssignedToContactID>  
  </Ticket>  
</EditTicketRequest>
```

Example Request (shared access users)

```
<EditTicketRequest ticket_id="32" account_id="12345"  
group_id="1">  
  <Ticket>  
    <Status>Closed</Status>  
    <CategoryID>3</CategoryID>  
    <AssignedToContactID>623</AssignedToContactID>  
  </Ticket>  
</EditTicketRequest>
```

Example Response

```
<EditTicketResponse>  
  <Result>Success</Result>  
  <Ticket>
```

```
<TicketID>41</TicketID>
<Status>Open</Status>
<CategoryID>3</CategoryID>
<AssignedToContactID>623</AssignedToContactID>
</Ticket>
</EditTicketResponse>
```

Get Ticket Updates

This function allows the caller to retrieve the ticket update for a ticket.

Shared access users must have contacts permission to the account in order to perform this action.

Input

- ticket_id (required)
- account_id (required for shared access users)
- group_id (required for shared access users)

Output

Success or failure. List of ticket updates.

Example Request

```
<GetTicketUpdatesRequest ticket_id="1"></
GetTicketUpdatesRequest>
```

Example Request (for shared access users)

```
<GetTicketUpdatesRequest ticket_id="1" account_id="12345"
group_id="1"></GetTicketUpdatesRequest>
```

Successful Response

```
<GetTicketUpdatesResponse>
  <Result>Success</Result>
  <TicketUpdates>
```

```
<TicketUpdate>
  <TicketUpdateID>3</TicketUpdateID>
  <UpdateDatetime>20190916105001</UpdateDatetime>
  <ContactID>1</ContactID>
  <Firstname>John</Firstname>
  <Lastname>Smith</Lastname>
  <Email>john.smith@somedomain.com</Email>
  <Content><![CDATA[<p>The quick brown fox jumps
over the lazy dog.</p>]]></Content>
  <ImageURL></ImageURL>
  <ImageSizeKB>0</ImageSizeKB>
  <UpdateIP>75.179.1.49</UpdateIP>
</TicketUpdate>
<TicketUpdate>
  <TicketUpdateID>2</TicketUpdateID>
  <UpdateDatetime>20180916105001</UpdateDatetime>
  <ContactID>1</ContactID>
  <Firstname>John</Firstname>
  <Lastname>Smith</Lastname>
  <Email>john.smith@somedomain.com</Email>
  <Content><![CDATA[<p>The quick brown fox jumps
over the lazy dog.</p>]]></Content>
  <ImageURL></ImageURL>
  <ImageSizeKB>0</ImageSizeKB>
  <UpdateIP>75.179.1.49</UpdateIP>
</TicketUpdate>
<TicketUpdate>
  <TicketUpdateID>1</TicketUpdateID>
  <UpdateDatetime>20170916105001</UpdateDatetime>
  <ContactID>1</ContactID>
  <Firstname>John</Firstname>
  <Lastname>Smith</Lastname>
  <Email>john.smith@somedomain.com</Email>
  <Content><![CDATA[<p>The quick brown fox jumps
over the lazy dog.</p>]]></Content>
  <ImageURL></ImageURL>
  <ImageSizeKB>0</ImageSizeKB>
  <UpdateIP>75.179.1.49</UpdateIP>
</TicketUpdate>
</TicketUpdates>
```

</GetTicketUpdatesResponse>

Add Ticket Update

Call this API to add a ticket update/reply.

Lookup ContactID or ContactEmail with GetContactsRequest.

Input

- ticket_id (required)
- account_id (required for shared access users)
- group_id (required for shared access users)
- ContactID or ContactEmail (required, contact must exists)
- Detail (required, text or escaped-XML entity sets allowed, eg. £ will not work, use £ instead. Basic entities like <, >, &, ', and " will work just fine.)
- Status (required, 'Open'/'Open (Escalated)'/ 'Closed'/'Closed (Locked)')
- EmailClient (required, Y/N)
- EmailSupportTeam (required, Y/N)

Output

Success or failure for ticket update.

Example Request (ContactID)

```
<AddTicketUpdateRequest ticket_id="32">
  <TicketUpdate>
    <ContactID>1</ContactID>
    <Detail>&lt;p&gt;Long ticket reply&lt;/p&gt;&lt;p&gt;&lt;p&gt;New line&lt;/p&gt;</Detail>
    <Status>Open</Status>
    <EmailClient>Y</EmailClient>
    <EmailSupportTeam>Y</EmailSupportTeam>
```



```
    </TicketUpdate>
</AddTicketUpdateRequest>
```

Example Request (ContactEmail)

```
<AddTicketUpdateRequest ticket_id="32">
  <TicketUpdate>
    <ContactEmail>john.smith@gmail.com</ContactEmail>
    <Detail>Long ticket reply</Detail>
    <Status>Open</Status>
    <EmailClient>Y</EmailClient>
    <EmailSupportTeam>Y</EmailSupportTeam>
  </TicketUpdate>
</AddTicketUpdateRequest>
```

Example Request (shared access users)

```
<AddTicketUpdateRequest ticket_id="32" account_id="12345"
group_id="1">
  <TicketUpdate>
    <ContactID>1</ContactID>
    <Detail>Long ticket reply</Detail>
    <Status>Open</Status>
    <EmailClient>Y</EmailClient>
    <EmailSupportTeam>Y</EmailSupportTeam>
  </TicketUpdate>
</AddTicketUpdateRequest>
```

Example Response

```
<AddTicketUpdateResponse>
  <Result>Success</Result>
  <TicketUpdate>
    <TicketUpdateID>106</TicketUpdateID>
    <TicketID>41</TicketID>
    <ContactID>1</ContactID>
    <Detail>Long ticket reply</Detail>
    <Status>Open</Status>
    <EmailSupportTeam>Y</EmailSupportTeam>
    <EmailClient>Y</EmailClient>
  </TicketUpdate>
```

</AddTicketUpdateResponse>

Get Ticket Categories

Call this API to retrieve the list of available ticket categories.

Input

- account_id (required for shared access users)
- group_id (required for shared access users)
- category_id

Output

Success or failure. List of ticket categories.

Example Request

```
<GetTicketCategoriesRequest/>
```

Example Request (filter by group_id)

```
<GetTicketCategoriesRequest group_id="1"/>
```

Example Request (filter by category_id)

```
<GetTicketCategoriesRequest category_id="2"/>
```

Example Request (shared access users)

```
<GetTicketCategoriesRequest account_id="12345"
group_id="1"/>
```

Example Response

```
<GetTicketCategoriesResponse>
  <Result>Success</Result>
  <TicketCategories>
    <TicketCategory>
      <CategoryID>1</CategoryID>
```

```

        <CategoryName>First Category</CategoryName>
        <GroupID>1</GroupID>
        <AutomaticallyAssignToContactID>623</
AutomaticallyAssignToContactID>
        <CloseTicketWorkflowID>2</
CloseTicketWorkflowID>
        <AlertIfResponseLaterThanHours>0</
AlertIfResponseLaterThanHours>
    </TicketCategory>
    <TicketCategory>
        <CategoryID>2</CategoryID>
        <CategoryName>Second Category</CategoryName>
        <GroupID>1</GroupID>
        <AutomaticallyAssignToContactID>-1</
AutomaticallyAssignToContactID>
        <CloseTicketWorkflowID>0</
CloseTicketWorkflowID>
        <AlertIfResponseLaterThanHours>0</
AlertIfResponseLaterThanHours>
    </TicketCategory>
</TicketCategories>
</GetTicketCategoriesResponse>

```

Get Ticket Forms

Call this API to retrieve the list of available ticket forms.

Input

- account_id (required for shared access users)
- group_id (required for shared access users)
- form_id

Output

Success or failure. List of ticket forms.

Example Request

<GetTicketFormsRequest/>

Example Request (filter by group_id)

<GetTicketFormsRequest group_id="1"/>

Example Request (filter by form_id)

<GetTicketFormsRequest form_id="2"/>

Example Request (shared access users)

<GetTicketFormsRequest account_id="12345" group_id="1"/>

Example Response

<GetTicketFormsResponse>

 <Result>Success</Result>

 <TicketForms>

 <TicketForm>

 <FormID>1</FormID>

 <FormName>Bug Report</FormName>

 <AddNewContactsToGroupIDs>

 <AddNewContactsToGroupID>2</

AddNewContactsToGroupID>

 </AddNewContactsToGroupIDs>

 <ManagedByGroupID>1</ManagedByGroupID>

 <QuickSummaryText>Report bug here</

QuickSummaryText>

 <SendNewTicketToOpener>Y</

SendNewTicketToOpener>

 <AllowImageUpload>Optional</AllowImageUpload>

 <AssignWorkflowID>2</AssignWorkflowID>

 <StartJourneyID>1</StartJourneyID>

 <ReopenLimit></ReopenLimit>

 </TicketForm>

 <TicketForm>

 <FormID>2</FormID>

 <FormName>Feature Request</FormName>

 <AddNewContactsToGroupIDs>

 <AddNewContactsToGroupID>4</

AddNewContactsToGroupID>

```
                <AddNewContactsToGroupID>2</
AddNewContactsToGroupID>
                </AddNewContactsToGroupIDs>
                <ManagedByGroupID>1</ManagedByGroupID>
                <QuickSummaryText>Submit request here</
QuickSummaryText>
                <SendNewTicketToOpener>Y</
SendNewTicketToOpener>
                <AllowImageUpload>Optional</AllowImageUpload>
                <AssignWorkflowID>2</AssignWorkflowID>
                <StartJourneyID>1</StartJourneyID>
                <ReopenLimit></ReopenLimit>
            </TicketForm>
        </TicketForms>
    </GetTicketFormsResponse>
```

Spec - Users

Table Of Contents

- Get Auth Token
- Get User Info
- Get Accounts With Access
- Change Password

Get Auth Token

This function gets an auth token to be used in subsequent XML API calls.

Input

Email and password (from the form variables; not part of the XML). In the XML, DeviceID (optional - pass an ID for the device using to access), AppKey (currently optional - an AppKey assigned by the CRM. Please contact support to obtain one for your app).

Output

Auth token to be passed in subsequent calls.

Example Request 1 (No optional parameters)

```
<GetAuthTokenRequest></GetAuthTokenRequest>
```

Example Request 2 (With optional parameters)

```
<GetAuthTokenRequest>  
  <DeviceID>98940B2C3A11</DeviceID>  
  <AppKey>AB938-34-5769-D23A</AppKey>
```

</GetAuthTokenRequest>

Successful Response

```
<GetAuthTokenResponse>
  <Result>Success</Result>
  <Token>(returned auth token)</Token>
</GetAuthTokenResponse>
```

Get User Info

This function allows the caller to information about the user logged in.

Input

None (user is based on log in information).

Output

Success or failure. On success name, email, address, city, state, zip, country, mobilephone of the user logged in. If the user is the account owner, the timezone of the account will also be included in the <Timezone> tag.

Example Request

<GetUserInfoRequest></GetUserInfoRequest>

Successful Response

```
<GetUserInfoResponse>
  <Result>Success</Result>
  <Name>Joe User</Name>
  <Email>joeuser@exampleco.com</Email>
  <Address>1313 Mockingbird Lane</Address>
  <City>Exampleville</City>
  <State>IL</State>
  <Zipcode>60565</Zipcode>
```

```
<Country>USA</Country>  
<Mobilephone>708-341-8988</Mobilephone>  
</GetUserInfoResponse>
```

Get Accounts With Access

This function allows the caller to discover which accounts in the system the caller has access to. If the caller is an owner of the account, all operations are allowed, and passing an account ID to the other requests is optional (it will always default to the account the caller owns). If the caller is a shared user of an account, a list of groups the caller can access and which functions are available are returned.

Input

None

Output

Success or failure.

On success a list of accounts, with contact ID, group, and permission information for any accounts that the caller is not the owner but a shared user with access.

For accounts that the caller is the owner of or has contacts permissions, number of contacts in the account and maximum contacts for the account.

Example Request 1 (no shared access, owner only)

```
<GetAccountsWithAccessRequest></  
GetAccountsWithAccessRequest>
```

Successful Response 1


```

<GetAccountsWithAccessResponse>
  <Result>Success</Result>
  <Accounts>
    <Account>
      <AccountNumber>1891</AccountNumber>
      <Contact_id>0</Contact_id>
      <IsOwner>Y</IsOwner>
      <Groups>
        <Group>
          <GroupID>1</GroupID>
          <GroupName>My Group</GroupName>
          <GroupType>Private</GroupType>
          <IncludeLoginLink>Yes</
IncludeLoginLink>
        </Group>
        <Group>
          <GroupID>2</GroupID>
          <GroupName>Business Leads</GroupName>
          <GroupType>Private</GroupType>
          <IncludeLoginLink>No</IncludeLoginLink>
        </Group>
      </Groups>
      <NumberOfContacts>2312</NumberOfContacts>
      <MaximumContacts>3000</MaximumContacts>
    </Account>
  </Accounts>
</GetAccountsWithAccessResponse>

```

Example Request 2 (account owner with shared access to another account)

```

<GetAccountsWithAccessRequest></
GetAccountsWithAccessRequest>

```

Successful Response 2

```

<GetAccountsWithAccessResponse>
  <Result>Success</Result>
  <Accounts>
    <Account>
      <AccountNumber>1891</AccountNumber>

```

```

    <Contact_id>0</Contact_id>
    <IsOwner>Y</IsOwner>
    <Groups>
        <Group>
            <GroupID>1</GroupID>
            <GroupName>My Group</GroupName>
            <GroupType>Private</GroupType>
            <IncludeLoginLink>Yes</
IncludeLoginLink>
        </Group>
        <Group>
            <GroupID>2</GroupID>
            <GroupName>Business Leads</GroupName>
            <GroupType>Private</GroupType>
            <IncludeLoginLink>No</IncludeLoginLink>
        </Group>
    </Groups>
    <NumberOfContacts>565</NumberOfContacts>
    <MaximumContacts>4996</MaximumContacts>
</Account>
<Account>
    <AccountNumber>99599</AccountNumber>
    <Contact_id>783</Contact_id>
    <IsOwner>N</IsOwner>
    <Groups>
        <Group>
            <ContactsPermission>Y</
ContactsPermission>
            <GroupsPermission>N</GroupsPermission>
            <EmailPermission>N</EmailPermission>
            <TrackingPermission>N</
TrackingPermission>
            <EventsPermission>N</EventsPermission>
            <MediaPermission>N</MediaPermission>
            <GroupID>20</GroupID>
            <GroupName>Management</GroupName>
            <GroupType>Private</GroupType>
            <IncludeLoginLink>Yes</
IncludeLoginLink>
        </Group>

```

```

        <Group>
            <ContactsPermission>Y</
ContactsPermission>
            <GroupsPermission>N</GroupsPermission>
            <EmailPermission>N</EmailPermission>
            <TrackingPermission>N</
TrackingPermission>
            <EventsPermission>Y</EventsPermission>
            <MediaPermission>N</MediaPermission>
            <GroupID>23</GroupID>
            <GroupName>Team Dev</GroupName>
            <GroupType>Private</GroupType>
            <IncludeLoginLink>Yes</
IncludeLoginLink>
        </Group>
    </Groups>
    <NumberOfContacts>42985</NumberOfContacts>
    <MaximumContacts>49804</MaximumContacts>
</Account>
</Accounts>
</GetAccountsWithAccessResponse>

```

Example Request 3 (all accounts are shared access)

```

<GetAccountsWithAccessRequest></
GetAccountsWithAccessRequest>

```

Successful Response 3

```

<GetAccountsWithAccessResponse>
    <Result>Success</Result>
    <Accounts>
        <Account>
            <AccountNumber>99599</AccountNumber>
            <Contact_id>623</Contact_id>
            <IsOwner>N</IsOwner>
            <Groups>
                <Group>
                    <ContactsPermission>Y</
ContactsPermission>
                    <GroupsPermission>N</GroupsPermission>

```

```

        <EmailPermission>N</EmailPermission>
        <TrackingPermission>N</
TrackingPermission>
        <EventsPermission>Y</EventsPermission>
        <MediaPermission>N</MediaPermission>
        <GroupID>1</GroupID>
        <GroupName>My Group</GroupName>
        <GroupType>Private</GroupType>
        <IncludeLoginLink>Yes</
IncludeLoginLink>
        </Group>
        <Group>
        <ContactsPermission>Y</
ContactsPermission>
        <GroupsPermission>N</GroupsPermission>
        <EmailPermission>N</EmailPermission>
        <TrackingPermission>N</
TrackingPermission>
        <EventsPermission>N</EventsPermission>
        <MediaPermission>N</MediaPermission>
        <GroupID>2</GroupID>
        <GroupName>Management</GroupName>
        <GroupType>Private</GroupType>
        <IncludeLoginLink>No</IncludeLoginLink>
        </Group>
        <Group>
        <ContactsPermission>Y</
ContactsPermission>
        <GroupsPermission>N</GroupsPermission>
        <EmailPermission>N</EmailPermission>
        <TrackingPermission>N</
TrackingPermission>
        <EventsPermission>Y</EventsPermission>
        <MediaPermission>N</MediaPermission>
        <GroupID>4</GroupID>
        <GroupName>Members Group</GroupName>
        <GroupType>Private</GroupType>
        <IncludeLoginLink>Yes</
IncludeLoginLink>
        </Group>

```

```
        </Groups>
        <NumberOfContacts>565</NumberOfContacts>
        <MaximumContacts>4996</MaximumContacts>
    </Account>
</Accounts>
</GetAccountsWithAccessResponse>
```

Change Password

This function allows the caller to change the account password.

Input

- OldPassword
- NewPassword
- ConfirmPassword

Output

Success or failure.

Example Request

```
<ChangePasswordRequest>
  <OldPassword>1234</OldPassword>
  <NewPassword>4321</NewPassword>
  <ConfirmPassword>4321</ConfirmPassword>
</ChangePasswordRequest>
```

Successful Response

```
<ChangePasswordResponse>
  <Result>Success</Result>
</ChangePasswordResponse>
```

Spec - Website Conversions

Table Of Contents

- Get Website Conversions
- Add Website Conversions
- Edit Website Conversions
- Delete Website Conversions

Get Website Conversions

This API retrieves the conversions under the user account.

Input

- account_id (required for shared access users)
- group_id (required for shared access users)
- conversion_id
- contact_id
- start_datetime (YYYYMMDDHHMMSS)
- end_datetime (YYYYMMDDHHMMSS)

Output

Success or failure. List of conversions under the user account.

Example Request

```
<GetWebsiteConversionsRequest/>
```

Example Request (Shared Access)

```
<GetWebsiteConversionsRequest account_id="12345"  
group_id="1"/>
```

Example Request (Filter)

```
<GetWebsiteConversionsRequest  
start_datetime="20160101000000"  
end_datetime="20171231240000" />
```

Example Response

```
<GetWebsiteConversionsResponse>  
  <Result>Success</Result>  
  <WebsiteConversions>  
    <WebsiteConversion>  
      <Value>0.00</Value>  
      <ConversionCode>1234</ConversionCode>  
      <ContactID>767</ContactID>  
      <Stage>0</Stage>  
      <ConversionID>204</ConversionID>  
      <Datetime>20171012075500</Datetime>  
    </WebsiteConversion>  
    <WebsiteConversion>  
      <Value>1234.00</Value>  
      <ConversionCode>1234</ConversionCode>  
      <ContactID>767</ContactID>  
      <Stage>1234</Stage>  
      <ConversionID>206</ConversionID>  
      <Datetime>20171012091203</Datetime>  
    </WebsiteConversion>  
    <WebsiteConversion>  
      <Value></Value>  
      <ConversionCode>1234</ConversionCode>  
      <ContactID>123</ContactID>  
      <Stage></Stage>  
      <ConversionID>209</ConversionID>  
      <Datetime>20171012122125</Datetime>  
    </WebsiteConversion>  
  </WebsiteConversions>  
  <TotalWebsiteConversions>3</TotalWebsiteConversions>  
</GetWebsiteConversionsResponse>
```

Add Website Conversions

This API call adds new conversion(s) to the user account.

Input

- account_id (required for shared access users)
- group_id (required for shared access users)
- request_id (optional)
- ConversionCode (required)
- ContactID
- Datetime (YYYYMMDDHHMMSS)
- Value
- Stage

Output

Success or failure for each conversions with its new ConversionID.

Example Request

```
<AddWebsiteConversionsRequest>
  <WebsiteConversions>
    <WebsiteConversion request_id="a1b2c3">
      <ConversionCode>1234</ConversionCode>
      <ContactID>623</ContactID>
      <Datetime>20171012123400</Datetime>
      <Value>20</Value>
      <Stage>1</Stage>
    </WebsiteConversion>
    <WebsiteConversion request_id="d4e5f6">
      <ConversionCode>4321</ConversionCode>
      <ContactID>623</ContactID>
    </WebsiteConversion>
  </WebsiteConversions>
</AddWebsiteConversionsRequest>
```

Example Request (Shared Access)


```
<AddWebsiteConversionsRequest account_id="12345"
group_id="1">
  <WebsiteConversions>
    <WebsiteConversion>
      <ConversionCode>4321</ConversionCode>
      <ContactID>623</ContactID>
    </WebsiteConversion>
  </WebsiteConversions>
</AddWebsiteConversionsRequest>
```

Example Response

```
<AddWebsiteConversionsResponse>
  <WebsiteConversions>
    <WebsiteConversion request_id="a1b2c3">
      <Result>Success</Result>
      <WebsiteConversionID>224</WebsiteConversionID>
    </WebsiteConversion>
    <WebsiteConversion request_id="d4e5f6">
      <Result>Success</Result>
      <WebsiteConversionID>227</WebsiteConversionID>
    </WebsiteConversion>
  </WebsiteConversions>
</AddWebsiteConversionsResponse>
```

Edit Website Conversions

This API call update existing conversion(s) in the user account.

Input

- account_id (required for shared access users)
- group_id (required for shared access users)
- conversion_id (required)
- request_id (optional)
- ConversionCode
- Datetime (YYYYMMDDHHMMSS)
- Value

- Stage

Output

Success or failure for each conversions with its existing ConversionID.

Example Request

```
<EditWebsiteConversionsRequest>
  <WebsiteConversions>
    <WebsiteConversion conversion_id="230"
request_id="a1b2c3">
      <ConversionCode>1234</ConversionCode>
      <Datetime>20171012123400</Datetime>
      <Value>20</Value>
      <Stage>1</Stage>
    </WebsiteConversion>
    <WebsiteConversion conversion_id="233"
request_id="d4e5f6">
      <ConversionCode>4321</ConversionCode>
      <Value>40</Value>
    </WebsiteConversion>
  </WebsiteConversions>
</EditWebsiteConversionsRequest>
```

Example Request (Shared Access)

```
<EditWebsiteConversionsRequest account_id="12345"
group_id="1">
  <WebsiteConversions>
    <WebsiteConversion conversion_id="230">
      <ConversionCode>1234</ConversionCode>
      <Datetime>20171012123400</Datetime>
      <Value>20</Value>
      <Stage>1</Stage>
    </WebsiteConversion>
    <WebsiteConversion conversion_id="233">
      <ConversionCode>4321</ConversionCode>
      <Value>40</Value>
    </WebsiteConversion>
  </WebsiteConversions>
</EditWebsiteConversionsRequest>
```

```
    </WebsiteConversions>
</EditWebsiteConversionsRequest>
```

Example Response

```
<EditWebsiteConversionsResponse>
  <WebsiteConversions>
    <WebsiteConversion request_id="a1b2c3">
      <Result>Success</Result>
      <WebsiteConversionID>230</WebsiteConversionID>
    </WebsiteConversion>
    <WebsiteConversion request_id="d4e5f6">
      <Result>Success</Result>
      <WebsiteConversionID>233</WebsiteConversionID>
    </WebsiteConversion>
  </WebsiteConversions>
</EditWebsiteConversionsResponse>
```

Delete Website Conversions

This API call removes conversion(s) from the user account.

Input

- account_id (required for shared access users)
- group_id (required for shared access users)
- conversion_id (required)
- request_id (optional)

Output

Success or failure for each conversions with its deleted ConversionID.

Example Request

```
<DeleteWebsiteConversionsRequest>
  <WebsiteConversions>
    <WebsiteConversion conversion_id="224"
request_id="a1b2c3" />
```

```
        <WebsiteConversion conversion_id="227"
request_id="d4e5f6" />
    </WebsiteConversions>
</DeleteWebsiteConversionsRequest>
```

Example Request (Shared Access)

```
<DeleteWebsiteConversionsRequest account_id="12345"
group_id="1">
    <WebsiteConversions>
        <WebsiteConversion conversion_id="224" />
        <WebsiteConversion conversion_id="227" />
    </WebsiteConversions>
</DeleteWebsiteConversionsRequest>
```

Example Response

```
<DeleteWebsiteConversionsResponse>
    <WebsiteConversions>
        <WebsiteConversion request_id="a1b2c3">
            <Result>Success</Result>
            <WebsiteConversionID>224</WebsiteConversionID>
        </WebsiteConversion>
        <WebsiteConversion request_id="d4e5f6">
            <Result>Success</Result>
            <WebsiteConversionID>227</WebsiteConversionID>
        </WebsiteConversion>
    </WebsiteConversions>
</DeleteWebsiteConversionsResponse>
```

Spec - Wiki

Table Of Contents

- Get Wiki Topics
- Get Wiki
- Add Wiki
- Edit Wiki
- Delete Wiki

Get Wiki Topics

This function allows the caller to retrieve a group's wiki topics list from the database.

Search parameters should be specified inside the tag.

Input

- account_id (required for shared access)
- group_id
- search

Output

Success or failure. A list of wiki topics.

Example Request

```
<GetWikiTopicsRequest group_id="4"></GetWikiTopicsRequest>
```

Example Request

```
<GetWikiTopicsRequest group_id="4" search="Test"></  
GetWikiTopicsRequest>
```

Example Request

```
<GetWikiTopicsRequest account_id="38193" group_id="34"></GetWikiTopicsRequest>
```

Successful Response

```
<GetWikiTopicsResponse>
  <Result>Success</Result>
  <WikiTopics>
    <WikiTopic>
      <WikiID>4</WikiID>
      <AllGroupMembersCanWrite>N</AllGroupMembersCanWrite>
      <Title>Test</Title>
      <ParentID>0</ParentID>
      <Public>N</Public>
      <Excerpt>Enter wiki content here</Excerpt>
    </WikiTopic>
    <WikiTopic>
      <WikiID>5</WikiID>
      <AllGroupMembersCanWrite>N</AllGroupMembersCanWrite>
      <Title>Test</Title>
      <ParentID>0</ParentID>
      <Public>N</Public>
      <Excerpt>Enter wiki content here</Excerpt>
      <WikiSubtopics>
        <WikiSubtopic>
          <WikiID>11</WikiID>
          <AllGroupMembersCanWrite>N</AllGroupMembersCanWrite>
          <Title>mobile</Title>
          <ParentID>5</ParentID>
          <Public>Y</Public>
          <Excerpt>test</Excerpt>
        </WikiSubtopic>
      </WikiSubtopics>
    </WikiTopic>
    <WikiTopic>
```

```
        <WikiID>6</WikiID>
        <AllGroupMembersCanWrite>N</
AllGroupMembersCanWrite>
        <Title>Test</Title>
        <ParentID>0</ParentID>
        <Public>N</Public>
        <Excerpt>Enter wiki content here</Excerpt>
    </WikiTopic>
</WikiTopics>
</GetWikiTopicsResponse>
```

Get Wiki

This function allows the caller to retrieve wiki from the database.

Search parameters should be specified inside the tag.

Input

- account_id (required for shared access)
- wiki_id

Output

Success or failure. Wiki data.

Example Request

```
<GetWikiRequest wiki_id="5"></GetWikiRequest>
```

Successful Response

```
<GetWikiResponse>
  <Result>Success</Result>
  <Wiki>
    <WikiID>5</WikiID>
    <AllGroupMembersCanWrite>N</
AllGroupMembersCanWrite>
    <Title>Test</Title>
```

```
        <ParentID>0</ParentID>
        <Public>N</Public>
        <Excerpt>Enter wiki content here</Excerpt>
        <Content>&lt;p&gt;Enter wiki content here&lt;/p&gt;</Content>
    </Wiki>
</GetWikiResponse>
```

Add Wiki

This function allows the caller to add wiki.

Search parameters should be specified inside the tag.

The caller must have wiki edit permissions to an account in order to this action.

Input

- account_id
- group_id
- Title
- Content
- ParentID
- AllGroupMembersCanWrite
- PublicTopic

Output

Success or failure for each wiki. Wiki ID.

Example Request

```
<AddWikiRequest group_id="4">
    <Title>Sample</Title>
    <Content>&lt;p&gt;Sample content.&lt;/p&gt;</Content>
```



```
<ParentID>0</ParentID>
<AllGroupMembersCanWrite>Y</AllGroupMembersCanWrite>
<PublicTopic>Y</PublicTopic>
</AddWikiRequest>
```

Successful Response

```
<AddWikiResponse>
  <Result>Success</Result>
  <WikiID>13</WikiID>
</AddWikiResponse>
```

Edit Wiki

This function allows the caller to modify one or more opportunity products already in the database.

Search parameters should be specified inside the tag, while parameters to change to would be specified individually.

The caller must have wiki edit permissions to an account in order to this action.

Input

- account_id
- group_id
- wiki_id
- Title
- Content
- ParentID
- AllGroupMembersCanWrite
- PublicTopic

Output

Success or failure for each products. List of products.

Example Request

```
<EditWikiRequest group_id="4" wiki_id="1">
  <Title>Sample</Title>
  <Content>&lt;p&gt;Sample content.&lt;#x2F;p&gt;</Content>
  <ParentID>0</ParentID>
  <AllGroupMembersCanWrite>Y</AllGroupMembersCanWrite>
  <PublicTopic>Y</PublicTopic>
</EditWikiRequest>
```

Example Response

```
<EditWikiResponse>
  <Result>Success</Result>
  <WikiID>13</WikiID>
</EditWikiResponse>
```

Delete Wiki

This function allows the caller to delete one or more opportunity products from the database.

Search parameters should be specified inside the tag.

The caller must have wiki edit permissions to an account in order to this action.

Input

- account_id
- group_id
- wiki_id

Output

Success or failure for each products. List of products.

Example Request

```
<DeleteWikiRequest group_id="4" wiki_id="1"/>
```

Example Response

```
<DeleteWikiResponse>  
  <Result>Success</Result>  
  <WikiID>13</WikiID>  
</DeleteWikiResponse>
```

Spec - Workflows

Table Of Contents

- Activate Workflow
- Get Workflows
- Add Workflows
- Edit Workflows
- Delete Workflows
- Get Workflow Activities
- Add Workflow Activities
- Edit Workflow Activities
- Delete Workflow Activities
- Get Activate Workflows

Activate Workflow

This API allows the caller to activate a workflow for a contact.

Input

- account_id (required for shared access users)
- group_id (required for shared access users)
- contact_id (required)
- WorkflowID (required)
- NewWorkflowStartDate (YYYYMMDD)
- AssignedToContactID
- OpportunityID
- GroupID

Output

Success or failure of the activation.

Example Request

```
<ActivateWorkflowRequest group_id="4" contact_id="750">
  <WorkflowID>4</WorkflowID>
  <NewWorkflowStartDate>20151105</NewWorkflowStartDate>
  <AssignedToContactID>0</AssignedToContactID>
  <OpportunityID></OpportunityID>
  <GroupID>1</GroupID>
</ActivateWorkflowRequest>
```

Example Response

```
<ActivateWorkflowResponse>
  <Result>Success</Result>
</ActivateWorkflowResponse>
```

Get Workflows

This API retrieves the workflows of a user account that are defined in Workflow Manager.

Input

- account_id (required for shared access users)
- group_id (required for shared access users)
- workflow_id
- show_options (true, false)

Output

Success or failure. List of workflows from the Workflow Manager.

Example Request

```
<GetWorkflowsRequest show_options="true"/>
```

Example Response

```

<GetWorkflowsResponse>
  <Result>Success</Result>
  <Workflows>
    <Workflow>
      <WorkflowID>5</WorkflowID>
      <WorkflowName>A</WorkflowName>
      <GroupID>0</GroupID>
      <AllowOncePerXDays>5</AllowOncePerXDays>
      <AutoAssignToNewMembers>N</
AutoAssignToNewMembers>
      <AutoAssignToContactID>0</
AutoAssignToContactID>
      <SendEmailMediaID>112</SendEmailMediaID>
      <SendSmsTextFromNumber/>
      <SendSmsText/>
      <AddToGroupID>4</AddToGroupID>
      <RemoveFromGroupID>4</RemoveFromGroupID>

<SendAlertEmailTo>contactemail+activation@gmail.com</
SendAlertEmailTo>
      <HttpRequestToUrl>http://google.com</
HttpRequestToUrl>
      <PrintCampaignID/>
      <AssignValueToField>User8</AssignValueToField>
      <AssignValue>1234</AssignValue>
      <AppendValueToField>User2</AppendValueToField>
      <AppendValue>http://facebook.com</AppendValue>
      <AssignTag>CEO</AssignTag>
      <RemoveTag>COO</RemoveTag>
      <AddCampaignID>test</AddCampaignID>
      <ConversionCode>12345</ConversionCode>
      <ConversionStage>5</ConversionStage>
      <ConversionValue>22.00</ConversionValue>
      <GroupName/>
      <TotalActivities>4</TotalActivities>
    </Workflow>
  </Workflows>
  <Options>
    <AddToGroups>
      <AddToGroup>

```

```

        <GroupID>1</GroupID>
        <GroupName>My Group</GroupName>
    </AddToGroup>
</AddToGroups>
<RemoveFromGroups>
    <RemoveFromGroup>
        <GroupID>1</GroupID>
        <GroupName>My Group</GroupName>
    </RemoveFromGroup>
</RemoveFromGroups>
<SendEmails>
    <SendEmail>
        <MediaID>112</MediaID>
        <MediaDescription>Test email template</
MediaDescription>
        <FileExtension>html</FileExtension>
        <MediaDirectoryID>2</MediaDirectoryID>
        <MediaDirectoryName>Email Templates</
MediaDirectoryName>
    </SendEmail>
</SendEmails>
<PrintOnDemands>
</PrintOnDemands>
<MakeAvailableTos>
    <MakeAvailableTo>
        <GroupID>0</GroupID>
        <GroupName>All Groups</GroupName>
    </MakeAvailableTo>
    <MakeAvailableTo>
        <GroupID>1</GroupID>
        <GroupName>My Group</GroupName>
    </MakeAvailableTo>
</MakeAvailableTos>
<Templates>
    <Template>
        <WorkflowID>4</WorkflowID>
        <WorkflowName>Test</WorkflowName>
    </Template>
</Templates>
<AppTemplates>

```

```

        <AppTemplate>
            <WorkflowID>9</WorkflowID>
            <WorkflowName>Event Planning</WorkflowName>
        </AppTemplate>
        <AppTemplate>
            <WorkflowID>1</WorkflowID>
            <WorkflowName>Meet New Contact</
WorkflowName>
        </AppTemplate>
        <AppTemplate>
            <WorkflowID>7</WorkflowID>
            <WorkflowName>Real Estate, Buyer's Offer
Accepted</WorkflowName>
        </AppTemplate>
    </AppTemplates>
    <SendSmsTextNumbers></SendSmsTextNumbers>
    <SetContactDatas>
        <SetContactData>
            <FieldNum>2</FieldNum>
            <FieldName>Facebook URL</FieldName>
            <AvailableToCompanies>N</
AvailableToCompanies>
        </SetContactData>
        <SetContactData>
            <FieldNum>1</FieldNum>
            <FieldName>Twitter Followers</FieldName>
            <AvailableToCompanies>Y</
AvailableToCompanies>
        </SetContactData>
    </SetContactDatas>
    <AppendContactDatas>
        <AppendContactData>
            <FieldNum>2</FieldNum>
            <FieldName>Facebook URL</FieldName>
            <AvailableToCompanies>N</
AvailableToCompanies>
        </AppendContactData>
        <AppendContactData>
            <FieldNum>1</FieldNum>
            <FieldName>Twitter Followers</FieldName>

```



```

        <AvailableToCompanies>Y</
AvailableToCompanies>
        </AppendContactData>
    </AppendContactDatas>
    <AssignTags>
        <AssignTag>
            <PositionShort>CEO</PositionShort>
            <PositionLong>chief executive officer</
PositionLong>
        </AssignTag>
        <AssignTag>
            <PositionShort>COO</PositionShort>
            <PositionLong>chief operating officer</
PositionLong>
        </AssignTag>
    </AssignTags>
    <RemoveTags>
        <RemoveTag>
            <PositionShort>CEO</PositionShort>
            <PositionLong>chief executive officer</
PositionLong>
        </RemoveTag>
        <RemoveTag>
            <PositionShort>COO</PositionShort>
            <PositionLong>chief operating officer</
PositionLong>
        </RemoveTag>
    </RemoveTags>
    <CampaignFilters>
        <CampaignFilter>
            <CampaignID>test</CampaignID>
            <CampaignLabel>Only contacts from campaign
test</CampaignLabel>
        </CampaignFilter>
    </CampaignFilters>
</Options>
</GetWorkflowsResponse>

```

Add Workflows

This API call adds a new workflow to the user account's Workflow Manager.

Input

- account_id (required for shared access users)
- group_id (required for shared access users)
- request_id (optional)
- WorkflowName (required)
- GroupID (required, 0 for All Groups)
- AddToGroupID
- RemoveFromGroupID
- SendAlertEmailTo
- WorkflowTemplateID
- WorkflowTemplateType (existing, app)

Output

Success or failure for each workflows.

Example Request

```
<AddWorkflowsRequest group_id="4">
  <Workflows>
    <Workflow request_id="a1b2c3">
      <WorkflowName>Spec 2</WorkflowName>
      <GroupID>0</GroupID>
    </Workflow>
  </Workflows>
</AddWorkflowsRequest>
```

Example Request

```
<AddWorkflowsRequest>
  <Workflows>
    <Workflow>
      <WorkflowName>Spec</WorkflowName>
```

```

        <GroupID>0</GroupID>
        <AddToGroupID>4</AddToGroupID>
        <RemoveFromGroupID>4</RemoveFromGroupID>
        <SendAlertEmailTo>contact.test@gmail.com</
SendAlertEmailTo>
        <WorkflowTemplateID>9</WorkflowTemplateID>
        <WorkflowTemplateType>app</
WorkflowTemplateType>
    </Workflow>
</Workflows>
</AddWorkflowsRequest>

```

Example Response

```

<AddWorkflowsResponse>
    <Workflows>
        <Workflow request_id="a1b2c3">
            <Result>Success</Result>
            <WorkflowID>28</WorkflowID>
        </Workflow>
    </Workflows>
</AddWorkflowsResponse>

```

Edit Workflows

This API call allows the user to update and modify existing workflows in the Workflow Manager.

Input

- account_id (required for shared access users)
- group_id (required for shared access users)
- workflow_id (required)
- request_id (optional)
- WorkflowName (required)
- GroupID (required, 0 for All Groups)
- AllowOncePerXDays
- AddToGroupID

- RemoveFromGroupID
- SendAlertEmailTo
- HttpRequestToUrl
- SendEmailMediaID
- AssignValueToField
- AssignValue
- AppendValueToField
- AppendValue
- AssignTag
- RemoveTag
- AddCampaignID
- ConversionCode
- ConversionStage
- ConversionValue
- AutoAssignToNewMembers
- AutoAssignToContactID

Output

Success or failure for each workflows.

Example Request

```
<EditWorkflowsRequest>
  <Workflows>
    <Workflow workflow_id="27" request_id="a1b2c3">
      <WorkflowName>Spec</WorkflowName>
      <AllowOncePerXDays>5</AllowOncePerXDays>
      <GroupID>4</GroupID>
      <AddToGroupID>4</AddToGroupID>
      <RemoveFromGroupID>4</RemoveFromGroupID>
      <SendAlertEmailTo>test.contact@gmail.com</
SendAlertEmailTo>
      <HttpRequestToUrl>www.someservice.com</
HttpRequestToUrl>
      <SendEmailMediaID>112</SendEmailMediaID>
      <AssignValueToField>User2</AssignValueToField>
```

```

        <AssignValue>facebook.com&#x2F;user</
AssignValue>
        <AppendValueToField>User2</AppendValueToField>
        <AppendValue>facebook.com&#x2F;user</
AppendValue>
        <AssignTag>CEO</AssignTag>
        <RemoveTag>COO</RemoveTag>
        <AddCampaignID>test</AddCampaignID>
        <ConversionCode>1234</ConversionCode>
        <ConversionStage>3</ConversionStage>
        <ConversionValue>40.00</ConversionValue>
        <AutoAssignToNewMembers>N</
AutoAssignToNewMembers>
        <AutoAssignToContactID>0</
AutoAssignToContactID>
    </Workflow>
</Workflows>
</EditWorkflowsRequest>

```

Example Response

```

<EditWorkflowsResponse>
    <Workflows>
        <Workflow request_id="a1b2c3">
            <Result>Success</Result>
            <WorkflowID>27</WorkflowID>
        </Workflow>
    </Workflows>
</EditWorkflowsResponse>

```

Delete Workflows

This API call allows the user to delete one or more workflows from the Workflow Manager.

Input

- account_id (required for shared access users)
- group_id (required for shared access users)

- workflow_id (required)
- request_id (optional)

Output

Success or failure for each workflows.

Example Request

```
<DeleteWorkflowsRequest>
  <Workflows>
    <Workflow workflow_id="27" request_id="a1b2c3"/>
  </Workflows>
</DeleteWorkflowsRequest>
```

Example Response

```
<DeleteWorkflowsResponse>
  <Workflows>
    <Workflow request_id="a1b2c3">
      <Result>Success</Result>
      <WorkflowID>28</WorkflowID>
    </Workflow>
  </Workflows>
</DeleteWorkflowsResponse>
```

Get Workflow Activities

This API call retrieves all the workflow activities defined within a workflow.

Input

- account_id (required for shared access users)
- group_id (required for shared access users)
- workflow_id (required)
- workflow_activity_id
- show_options (true, false)

Output

Success or failure. List of workflow activities of a workflow.

Example Request

```
<GetWorkflowActivitiesRequest workflow_id="29"  
show_options="true"/>
```

Example Response

```
<GetWorkflowActivitiesResponse>  
  <Result>Success</Result>  
  <WorkflowActivities>  
    <WorkflowActivity>  
      <WorkflowActivityID>71</WorkflowActivityID>  
      <WorkflowID>29</WorkflowID>  
      <OnlyIfCampaignIDLike/>  
      <Activity>Reserve Room</Activity>  
      <AutoAssignToContactID>0</  
AutoAssignToContactID>  
      <SendReminderHourBeforeDue>N</  
SendReminderHourBeforeDue>  
      <Recurring>Once</Recurring>  
      <Notes/>  
      <MediaID>0</MediaID>  
      <OpportunityPhaseID>1</OpportunityPhaseID>  
      <OpportunitySourceID>1</OpportunitySourceID>  
      <OpportunityValue>0</OpportunityValue>  
      <OpportunityNotes/>  
      <SmsMessage/>  
      <DelayType>Calendar</DelayType>  
      <DelayDays>1</DelayDays>  
      <DelayTime/>  
    </WorkflowActivity>  
  </WorkflowActivities>  
  <Options>  
    <WorkflowActivityTypes>  
      <WorkflowActivityType>
```

```

        <Label>Make Note</Label>
    </WorkflowActivityType>
    <WorkflowActivityType>
        <Label>Video Follow-Up</Label>
    </WorkflowActivityType>
    <WorkflowActivityType>
        <Label>Presentation</Label>
    </WorkflowActivityType>
    <WorkflowActivityType>
        <Label>Send Personal Email</Label>
    </WorkflowActivityType>
    <WorkflowActivityType>
        <Label>Create Opportunity</Label>
    </WorkflowActivityType>
    <WorkflowActivityType>
        <Label>Activate Workflow A</Label>
    </WorkflowActivityType>
</WorkflowActivityTypes>
<CampaignFilters>
    <CampaignFilter>
        <CampaignID>test</CampaignID>
        <CampaignLabel>Only contacts from campaign
test</CampaignLabel>
    </CampaignFilter>
</CampaignFilters>
<Recurrings>
    <Recurring>
        <Label>Once</Label>
    </Recurring>
    <Recurring>
        <Label>Weekly</Label>
    </Recurring>
    <Recurring>
        <Label>Every 2 Weeks</Label>
    </Recurring>
    <Recurring>
        <Label>Every 3 Weeks</Label>
    </Recurring>
    <Recurring>
        <Label>Every 4 Weeks</Label>
    </Recurring>

```



```

    </Recurring>
    <Recurring>
        <Label>Monthly</Label>
    </Recurring>
    <Recurring>
        <Label>Every 6 Weeks</Label>
    </Recurring>
    <Recurring>
        <Label>Every 2 Months</Label>
    </Recurring>
    <Recurring>
        <Label>Every 3 Months</Label>
    </Recurring>
    <Recurring>
        <Label>Every 6 Months</Label>
    </Recurring>
    <Recurring>
        <Label>Every Year</Label>
    </Recurring>
</Recurrings>
<DelayTypes>
    <DelayType>
        <Label>Business</Label>
    </DelayType>
    <DelayType>
        <Label>Calendar</Label>
    </DelayType>
</DelayTypes>
<AutoAssignToContacts>
    <AutoAssignToContact>
        <ContactID>-1</ContactID>
        <Firstname>Default contact assigned to
workflow</Firstname>
        <Lastname/>
        <Email/>
    </AutoAssignToContact>
    <AutoAssignToContact>
        <ContactID>0</ContactID>
        <Firstname>Account</Firstname>
        <Lastname>Owner</Lastname>
    </AutoAssignToContact>

```

```

        <Email/>
    </AutoAssignToContact>
    <AutoAssignToContact>
        <ContactID>2</ContactID>
        <Firstname>Test</Firstname>
        <Lastname>Wade</Lastname>
        <Email>test.contact@gmail.com</Email>
    </AutoAssignToContact>
</AutoAssignToContacts>
<PersonalEmails>
    <PersonalEmail>
        <MediaID>112</MediaID>
        <MediaDescription>Test email template</
MediaDescription>
        <FileExtension>html</FileExtension>
        <MediaDirectoryID>2</MediaDirectoryID>
        <MediaDirectoryName>Email Templates</
MediaDirectoryName>
    </PersonalEmail>
</PersonalEmails>
<OpportunityPhases>
    <OpportunityPhase>
        <PhaseID>1</PhaseID>
        <Phase>New Lead</Phase>
        <PhaseNumber>1</PhaseNumber>
        <WarningDays>5</WarningDays>
    </OpportunityPhase>
    <OpportunityPhase>
        <PhaseID>2</PhaseID>
        <Phase>Qualified Lead</Phase>
        <PhaseNumber>2</PhaseNumber>
        <WarningDays>5</WarningDays>
    </OpportunityPhase>
</OpportunityPhases>
<OpportunitySources>
    <OpportunitySource>
        <SourceID>5</SourceID>
        <Source>Cold Call</Source>
    </OpportunitySource>
    <OpportunitySource>

```

```
        <SourceID>2</SourceID>
        <Source>Internet Search</Source>
    </OpportunitySource>
</OpportunitySources>
</Options>
</GetWorkflowActivitiesResponse>
```

Add Workflow Activities

This API call allows the user to add a new workflow activity of a workflow.

Input

- account_id (required for shared access users)
- group_id (required for shared access users)
- workflow_id (required)
- request_id (optional)
- Activity (required)
- OnlyIfCampaignIDLike
- DelayType (required)
- DelayDays
- DelayTime (HHmm)
- SendReminderHourBeforeDue (required for general Activity, 'Y', 'N')
- Recurring (required for general Activity)
- Notes
- MediaID (required if Activity is 'Send Personal Email')
- SmsMessage (required if Activity is 'Send Personal SMS')
- OpportunityPhaseID (required if Activity is 'Create Opportunity')
- OpportunitySourceID (required if Activity is 'Create Opportunity')
- OpportunityValue
- OpportunityNotes

Output

Success or failure for each workflows activities.

Example Request (Activity)

```
<AddWorkflowActivitiesRequest workflow_id="29">
  <WorkflowActivities>
    <WorkflowActivity request_id="a1b2c3">
      <Activity>Make Note</Activity>
      <OnlyIfCampaignIDLike>test</
OnlyIfCampaignIDLike>
      <DelayType>Business</DelayType>
      <DelayDays>5</DelayDays>
      <DelayTime>0510</DelayTime>
      <SendReminderHourBeforeDue>N</
SendReminderHourBeforeDue>
      <Recurring>Weekly</Recurring>
      <Notes>The quick brown fox jumps over the lazy
dog.</Notes>
    </WorkflowActivity>
  </WorkflowActivities>
</AddWorkflowActivitiesRequest>
```

Example Request (Send Personal Email)

```
<AddWorkflowActivitiesRequest workflow_id="29">
  <WorkflowActivities>
    <WorkflowActivity>
      <Activity>Create Opportunity</Activity>
      <OnlyIfCampaignIDLike></OnlyIfCampaignIDLike>
      <DelayType>Business</DelayType>
      <DelayDays>0</DelayDays>
      <DelayTime>9999</DelayTime>
      <MediaID>1</MediaID>
    </WorkflowActivity>
  </WorkflowActivities>
</AddWorkflowActivitiesRequest>
```

Example Request (Send Personal SMS)

```
<AddWorkflowActivitiesRequest workflow_id="29">
```

```

    <WorkflowActivities>
      <WorkflowActivity>
        <Activity>Create Opportunity</Activity>
        <OnlyIfCampaignIDLike></OnlyIfCampaignIDLike>
        <DelayType>Business</DelayType>
        <DelayDays>0</DelayDays>
        <DelayTime>9999</DelayTime>
        <SmsMessage>SMS text goes here.<SmsMessage>
      </WorkflowActivity>
    </WorkflowActivities>
  </AddWorkflowActivitiesRequest>

```

Example Request (Create Opportunity)

```

<AddWorkflowActivitiesRequest workflow_id="29">
  <WorkflowActivities>
    <WorkflowActivity>
      <Activity>Create Opportunity</Activity>
      <OnlyIfCampaignIDLike></OnlyIfCampaignIDLike>
      <DelayType>Business</DelayType>
      <DelayDays>0</DelayDays>
      <DelayTime>9999</DelayTime>
      <OpportunityPhaseID>1</OpportunityPhaseID>
      <OpportunitySourceID>5</OpportunitySourceID>
      <OpportunityValue>55</OpportunityValue>
      <OpportunityNotes>Opportunity lorem notes.</
OpportunityNotes>
    </WorkflowActivity>
  </WorkflowActivities>
</AddWorkflowActivitiesRequest>

```

Example Response

```

<AddWorkflowActivitiesResponse>
  <WorkflowActivities>
    <WorkflowActivity request_id="a1b2c3">
      <Result>Success</Result>
      <WorkflowActivityID>77</WorkflowActivityID>
    </WorkflowActivity>
  </WorkflowActivities>
</AddWorkflowActivitiesResponse>

```

Edit Workflow Activities

This API call allows the user to update and modify existing workflow activities defined within a workflow.

Input

- account_id (required for shared access users)
- group_id (required for shared access users)
- workflow_id (required)
- workflow_activity_id (required)
- request_id (optional)
- Activity (required)
- OnlyIfCampaignIDLike
- DelayType (required)
- DelayDays
- DelayTime (HHmm)
- SendReminderHourBeforeDue (required for general Activity, 'Y', 'N')
- Recurring (required for general Activity)
- Notes
- MediaID (required if Activity is 'Send Personal Email')
- SmsMessage (required if Activity is 'Send Personal SMS')
- OpportunityPhaseID (required if Activity is 'Create Opportunity')
- OpportunitySourceID (required if Activity is 'Create Opportunity')
- OpportunityValue
- OpportunityNotes

Output

Success or failure for each workflows activities.

Example Request (Activity)

```

<EditWorkflowActivitiesRequest workflow_id="29">
  <WorkflowActivities>
    <WorkflowActivity workflow_activity_id="75"
request_id="alb2c3">
      <Activity>Make Note</Activity>
      <AutoAssignToContactID>0</
AutoAssignToContactID>
      <OnlyIfCampaignIDLike>test</
OnlyIfCampaignIDLike>
      <DelayDays>5</DelayDays>
      <DelayType>Business</DelayType>
      <DelayTime>0510</DelayTime>
      <SendReminderHourBeforeDue>N</
SendReminderHourBeforeDue>
      <Recurring>Weekly</Recurring>
      <Notes>The quick brown fox jumps over the lazy
dog.</Notes>
    </WorkflowActivity>
  </WorkflowActivities>
</EditWorkflowActivitiesRequest>

```

Example Request (Send Personal Email)

```

<EditWorkflowActivitiesRequest workflow_id="29">
  <WorkflowActivities>
    <WorkflowActivity workflow_activity_id="75">
      <Activity>Create Opportunity</Activity>
      <OnlyIfCampaignIDLike></OnlyIfCampaignIDLike>
      <DelayType>Business</DelayType>
      <DelayDays>0</DelayDays>
      <DelayTime>9999</DelayTime>
      <MediaID>1</MediaID>
    </WorkflowActivity>
  </WorkflowActivities>
<EditWorkflowActivitiesRequest>

```

Example Request (Send Personal SMS)

```

<EditWorkflowActivitiesRequest workflow_id="29">
  <WorkflowActivities>
    <WorkflowActivity workflow_activity_id="75">

```

```

        <Activity>Create Opportunity</Activity>
        <OnlyIfCampaignIDLike></OnlyIfCampaignIDLike>
        <DelayType>Business</DelayType>
        <DelayDays>0</DelayDays>
        <DelayTime>9999</DelayTime>
        <SmsMessage>SMS text goes here.<SmsMessage>
    </WorkflowActivity>
</WorkflowActivities>
<EditWorkflowActivitiesRequest>

```

Example Request (Create Opportunity)

```

<EditWorkflowActivitiesRequest workflow_id="29">
    <WorkflowActivities>
        <WorkflowActivity workflow_activity_id="75">
            <Activity>Create Opportunity</Activity>
            <OnlyIfCampaignIDLike></OnlyIfCampaignIDLike>
            <DelayType>Business</DelayType>
            <DelayDays>0</DelayDays>
            <DelayTime>9999</DelayTime>
            <OpportunityPhaseID>1</OpportunityPhaseID>
            <OpportunitySourceID>5</OpportunitySourceID>
            <OpportunityValue>55</OpportunityValue>
            <OpportunityNotes>Opportunity lorem notes.</
OpportunityNotes>
        </WorkflowActivity>
    </WorkflowActivities>
</EditWorkflowActivitiesRequest>

```

Example Response

```

<EditWorkflowActivitiesResponse>
    <WorkflowActivities>
        <WorkflowActivity request_id="a1b2c3">
            <Result>Success</Result>
            <WorkflowActivityID>75</WorkflowActivityID>
        </WorkflowActivity>
    </WorkflowActivities>
</EditWorkflowActivitiesResponse>

```

Delete Workflow Activities

This API call allows the user to delete one or more existing workflow activities defined within a workflow.

Input

- account_id (required for shared access users)
- group_id (required for shared access users)
- workflow_id (required)
- workflow_activity_id (required)
- request_id (optional)

Output

Success or failure for each workflows activities.

Example Request

```
<DeleteWorkflowActivitiesRequest workflow_id="29">
  <WorkflowActivities>
    <WorkflowActivity workflow_activity_id="76"
request_id="alb2c3"/>
  </WorkflowActivities>
</DeleteWorkflowActivitiesRequest>
```

Example Response

```
<DeleteWorkflowActivitiesResponse>
  <WorkflowActivities>
    <WorkflowActivity request_id="alb2c3">
      <Result>Success</Result>
      <WorkflowActivityID>75</WorkflowActivityID>
    </WorkflowActivity>
  </WorkflowActivities>
</DeleteWorkflowActivitiesResponse>
```

Get Activate Workflows

This API call retrieves the selection options for request inputs that are used in 'Activate Workflow' API request.

Input

- account_id (required for shared access users)
- group_id (required for shared access users)
- contact_id

Output

Success or failure. List of selection options values.

Example Request

```
<GetActivateWorkflowsRequest contact_id="750"/>
```

Example Response

```
<GetActivateWorkflowsResponse>
  <Result>Success</Result>
  <Workflows>
    <Workflow>
      <WorkflowID>29</WorkflowID>
      <WorkflowName>Spec</WorkflowName>
      <TotalActivities>4</TotalActivities>
    </Workflow>
    <Workflow>
      <WorkflowID>4</WorkflowID>
      <WorkflowName>Test</WorkflowName>
      <TotalActivities>2</TotalActivities>
    </Workflow>
  </Workflows>
  <AssignedTos>
    <AssignedTo>
      <ContactID>0</ContactID>
      <Firstname>Account</Firstname>
      <Lastname>Owner</Lastname>
      <Email>Todd Wade</Email>
```

```
</AssignedTo>
<AssignedTo>
  <ContactID>623</ContactID>
  <Firstname>Shared</Firstname>
  <Lastname>Test</Lastname>
  <Email>test.contact2@gmail.com</Email>
</AssignedTo>
</AssignedTos>
<ConnectedTos>
  <OpportunityID>1</OpportunityID>
  <OpportunityTitle>Test Opportunity</
OpportunityTitle>
</ConnectedTos>
<AssociatedWiths>
  <AssociatedWith>
    <GroupID>1</GroupID>
    <GroupName>My Group</GroupName>
  </AssociatedWith>
  <AssociatedWith>
    <GroupID>4</GroupID>
    <GroupName>Members Group</GroupName>
  </AssociatedWith>
</AssociatedWiths>
</GetActivateWorkflowsResponse>
```