



Home	Tally Developer	Tally.ERP 9	Tally Presentations	Tally Tips	Download	Tally.ERP 9 Download	
------	-----------------	-------------	---------------------	------------	----------	----------------------	--

List of TDL Functions

An Alphabetical-list of TDL functions (Partial list) is provided herewith for your reference.

Function	Syntax	Return Value	Remarks
\$\$Abs	\$\$Abs : <Expression>	Same as parameter type	Returns the absolute (positive) value for the given expression
\$\$Alias	\$\$Alias	String	\$\$Alias returns alternate value for the current Object. Stock Item and Ledger have Alias name.
\$\$Allow	\$\$Allow : <mode> : <family-report-name>	Logical	Checks whether the current user has permission to access the specified object or report.
\$\$CollectionList	\$\$CollectionList: <Method/Field> : <PositionNumber> : <Collection>	Method/ Field Datatype	\$\$CollectionList function is used to fetch the nth Method/field of a Collection.
\$\$DateFrom	\$\$DateFrom	Date	Returns the Period starting date
\$\$DateTo	\$\$DateTo	Date	Returns the Period ending date
\$\$FullList	\$\$FullList : <Collection> : <FieldList>	Method/ Field Datatype	\$\$FullList function is used to fetch any Method/Field of a Collection. The Method/Field values are separated by commas.
\$\$InPrintMode	\$\$InPrintMode	Logical	Returns true if the selected mode is Print, otherwise false.
\$\$IsContra	\$\$IsContra : <VoucherTypeName>	Logical	Checks whether the specified VoucherType is Contra
\$\$IsCreditNote	\$\$IsCreditNote : <VoucherTypeName>	Logical	Checks whether the specified VoucherType is CreditNote
\$\$IsDebitNote	\$\$IsDebitNote : <VoucherTypeName>	Logical	Checks whether the specified VoucherType is DebitNote
\$\$IsDelNote	\$\$IsDelNote : <VoucherTypeName>	Logical	Checks whether the specified VoucherType is Delivery Note
\$\$IsEmpty	\$\$IsEmpty: <parameter>	Logical	Checks whether the parameter passed is empty or not. Parameter type can be String; Numeric; Date; Logical Example:- \$\$IsEmpty:\$\$Value
\$\$IsFirstObject	\$\$IsFirstObject	Logical	Returns true if the current Object is the 1st object of the Collection.
\$\$IsJournal	\$\$IsJournal : <VoucherTypeName>	Logical	Checks whether the specified VoucherType is Journal
\$\$IsMemo	\$\$IsMemo : <VoucherTypeName>	Logical	Checks whether the specified VoucherType is Memo
\$\$IsPayment	\$\$IsPayment : <VoucherTypeName>	Logical	Checks whether the specified VoucherType is Payment Voucher
\$\$IsPhyStock	\$\$IsPhyStock : <VoucherTypeName>	Logical	Checks whether the specified VoucherType is PhysicalStock Voucher
\$\$IsPurchase	\$\$IsPurchase : <VoucherTypeName>	Logical	Checks whether the specified VoucherType is Purchase Voucher
\$\$IsPurcOrder	\$\$IsPurcOrder : <VoucherTypeName>	Logical	Checks whether the specified VoucherType is Purchase Order Voucher
\$\$IsRcptNote	\$\$IsRcptNote : <VoucherTypeName>	Logical	Checks whether the specified VoucherType is ReceiptNote Voucher
\$\$IsReceipt	\$\$IsReceipt : <VoucherTypeName>	Logical	Checks whether the specified VoucherType is Receipt Voucher



SEARCH

TALLY UPDATES

- Tally.Server 9 Series A Release 4. Now
- Tally.ERP 9 Series A Stat 240 Av
- Tally.ERP 9 Series A Release 4. Now
- Tally awarded as the winner for t "BEST ERP SOFTWARE FOR S VarIndia for the 13th Annual VAF Nite Awards 2014.
- Karnataka VAT event conducted with Mr. Murali Krishna, JCCT, e- Karnataka. Watch highlights!

BLOG ARCHIVE

- ▼ 2011 (26)
 - December (2)
 - November (2)
- ▼ October (7)
 - List of TDL Functions
 - UDF In Ledger Creation
 - Address Book From Tally

\$\$IsRejIn	\$\$IsRejIn : <VoucherTypeName>	Logical	Checks whether the specified VoucherType is RejectionIn Voucher
\$\$IsRejOut	\$\$IsRejOut : <VoucherTypeName>	Logical	Checks whether the specified VoucherType is RejectionOut Voucher
\$\$IsRevJrnl	\$\$IsRevJrnl : <VoucherTypeName>	Logical	Checks whether the specified VoucherType is Reverse Journal Voucher
\$\$IsSales	\$\$IsSales : <VoucherTypeName>	Logical	Checks whether the specified VoucherType is Sales Voucher
\$\$IsSalesOrder	\$\$IsSalesOrder : <VoucherTypeName>	Logical	Checks whether the specified VoucherType is Sales Order Voucher
\$\$IsStockJournal	\$\$IsStockJournal : <VoucherTypeName>	Logical	Checks whether the specified VoucherType is StockJournal Voucher
Function	Syntax	Return Value	Remarks
\$\$LocaleString	\$\$LocaleString: <string>	Unicode string	Accepts a string parameter and returns unicode string. This is to provide multi-lingual support to Tally
\$\$IsVchTypeOfFamily	\$\$IsVchTypeOfFamily : <VoucherTypeName>	Logical	Checks whether the Field value of the <Field> is equal to the <ExpC> Example: \$\$IsVchTypeOfFamily: \$VoucherTypeName : "Payment" Remarks: The function \$\$IsVchTypeOfFamily returns true if the Field-value of \$VoucherTypeName is "Payment"
\$\$MachineDate	\$\$MachineDate	Date	Returns the Date as per your computer system settings Example:- Select \$\$MachineDate from Company
\$\$MachineTime	\$\$MachineTime	String	Returns the Time as per your computer system settings Example:- Select \$\$MachineTime from Company
\$\$Max	\$\$Max : <Expression>	Same as parameter type	Returns the Minimum value. The parameter type can be Numeric, Date or String Example:- \$\$Max:100:15 returns 100
\$\$Min	\$\$Min : <Expression>	Same as parameter type	Returns the Minimum value. The parameter type can be Numeric, Date or String Example:- \$\$Min:100:15 returns 15
\$\$MonthEnd	\$\$MonthEnd: <ExpD>	Date	Returns the ending date of the specified month. Example:- Select \$\$MonthEnd:\$\$MachineDate from Company
\$\$MonthOfDate	\$\$MonthOfDate:<ExpD>	Numeric	Returns the Month (example 12) of the specified date Example:- Select \$\$MonthOfDate:\$\$MachineDate from Company
\$\$MonthStart	\$\$MonthStart: <ExpD>	Date	Returns the starting date of the specified month. Example:- Select \$\$MonthStart:\$\$MachineDate from Company
\$\$Round	\$\$Round : <ExpN> : <RoundLimit>	Numeric	\$\$Round function is used to round-off a value Example:- \$\$Round : 125.72 : 0.10 returns 125.70
\$\$RoundDown	\$\$RoundDown : <ExpN> : <RoundLimit>	Numeric	\$\$Round function is used to round-off a value Example:- \$\$Round : 125.72 : 0.10 returns 125.70
\$\$RoundUp	\$\$RoundUp : <ExpN> : <RoundLimit>	Numeric	\$\$Round function is used to round-off a value Example:- \$\$Round : 125.72 : 0.10 returns 125.80
\$\$SelectedCmps	\$\$SelectedCmps	Numeric	Returns the number of companies currently open in Tally Software.
\$\$SerialNumber	\$\$SerialNumber	String	Returns the Tally Serial Number.
\$\$String	\$\$String: <ExpN>	String	Converts numeric expression into string. Example:- [Field: My Field] Set as : \$\$String:500
\$\$StringLength	\$\$stringLength: <ExpC>	Numeric	Returns the length of the string parameter Example:- [Field: My Field] Set as: \$\$StringLength:"tally Softwares"
\$\$StringPart	\$\$StringPart: <expC>: <StartPos>: <Length>	String	Used to extract a sub-string from another string. Example:- [Field: My Field] Set as: \$\$StringPart:"Tally Softwares":7:9 Remarks:- This will return "Computers".i.e. beginning at the 8th character, it returns the next 9 characters.

How to type Multiple lines In T

Tally Hidden Keys

Change MENU Options in Tal

Tips on Implementaion of Tally Weekly ...

► September (12)

► August (1)

► February (2)

► 2010 (32)

LIVE FEED

			Please note that the 1st character is numbered as 0.
\$\$StringRemWord	\$\$StringRemWord: <Index>: <ExpC>	String	Returns the remaining word from the <ExpC> string after the Index. Example:- \$\$StringRemWord:2:"tally Softwares bangalore" This returns the word "bangalore". i.e. the word after 2 words as specified by the Index
\$\$StringWord	\$\$StringWord: <Index>: <ExpC>	String	Returns the word specified by the Index. Example:- \$\$StringWord:2:"tally Softwares Gandhidham" This returns the word "Computers". i.e. the 2nd word as specified by the Index
\$\$SysName	\$\$SysName: <reserved-string>	String	Specifies the System-name for the reserved string
\$\$SystemPeriodFrom	\$\$SystemPeriodFrom	Date	Returns the value for the System variable SVFRODATE Example:- Select \$\$SystemPeriodFrom from Company or Select ##SVFRODATE from Company
\$\$SystemPeriodTo	\$\$SystemPeriodTo	Date	Returns the value for the System variable SVTODATE Example:- Select \$\$SystemPeriodTo from Company or Select ##SVTODATE from Company
\$\$Upper	\$\$Upper: <ExpC>	String	Converts the string to upper-case
\$\$Value	\$\$Value	Method/Field data type	Returns the value of a field/method. Example:- [Field: My Field] Use: Name Field Validate: NOT \$\$IsEmpty:\$\$Value In the above code, function \$\$Value is used which returns the value of the field 'My Field'.
\$\$YearOfDate	\$\$YearOfDate: <ExpD>	Numeric	Returns the Year for the specified Date. Example:- Select \$\$YearOfDate:\$\$MachineDate from Company The above returns the year (.i.e 2007)
\$\$YearEnd	\$\$YearEnd: <ExprD>	Date	Returns the Year end-date for the Current year (based on the Date passed as parameter) Example:- Select \$\$YearEnd:##SVTODATE from Company The above returns the year-end date (ex. in my system it returns 31-3-2008).
\$\$ZeroFill	\$\$ZeroFill : <ExpC> : <ExpN>	String	\$\$Zero pads the given string with zeros. Example:- \$\$Zero : "525" : 5 returns "00525"

[Newer Post](#)

[Home](#)

[Older Post](#)

IS THIS BLOG HELPED YOU?