



Table Types

Heap




Clustered




• Type	• Description
• Ordinary (heap-organized) table	• Data is stored as an unordered collection (heap).
• Partitioned table	• Data is divided into smaller, more manageable pieces.
• Index-organized table (IOT)	• Data (including non-key values) is sorted and stored in a B-tree index structure.
• Clustered table	• Related data from more than one table are stored together.

Partitioned




IOT



What Is a Partition and Why Use It?

- A partition is:
 - A piece of a “very large” table or index
 - Stored in its own segment
 - Used for improved performance and manageability



RANGE PARTITION

```
CREATE TABLE eladasok ( szla_szam  NUMBER(5),  
                        szla_nev   CHAR(30),  
                        mennyiseg  NUMBER(6),  
                        het        INTEGER )
```

```
PARTITION BY RANGE ( het )
```

```
(PARTITION negyedev1 VALUES LESS THAN ( 13 )  
  TABLESPACE users,
```

```
  PARTITION negyedev2 VALUES LESS THAN ( 26 )  
  TABLESPACE example,
```

```
  PARTITION negyedev3 VALUES LESS THAN ( 39 )  
  TABLESPACE users )
```

DBA_PART_TABLES

DBA_TAB_PARTITIONS

DBA_TAB_SUBPARTITIONS

HASH PARTITION, LIST PARTITION

```
CREATE TABLE eladasok2 (szla_szam  NUMBER(5),  
                        szla_nev   CHAR(30),  
                        mennyiseg  NUMBER(6),  
                        het        INTEGER )
```

```
PARTITION BY HASH ( het )  
  (PARTITION part1 TABLESPACE users,  
   PARTITION part2 TABLESPACE example,  
   PARTITION part3 TABLESPACE users );
```

```
CREATE TABLE eladasok3 (szla_szam  NUMBER(5),  
                        szla_nev   CHAR(30),  
                        mennyiseg  NUMBER(6),  
                        het        INTEGER )
```


```
PARTITION BY LIST ( het )  
  (PARTITION part1 VALUES(1,2,3,4,5)  TABLESPACE users,  
   PARTITION part2 VALUES(6,7,8,9)    TABLESPACE example,  
   PARTITION part3 VALUES(10,11,12,13) TABLESPACE users );
```

SUBPARTITIONS (RANGE-HASH)


```
CREATE TABLE eladasok4 (szla_szam  NUMBER(5),
                        szla_nev   CHAR(30),
                        mennyiseg  NUMBER(6),
                        het        INTEGER )
PARTITION BY RANGE ( het )
SUBPARTITION BY HASH (mennyiseg)
SUBPARTITIONS 3
(PARTITION negyedev1 VALUES LESS THAN ( 13 )
  TABLESPACE users,
PARTITION negyedev2 VALUES LESS THAN ( 26 )
  TABLESPACE example,
PARTITION negyedev3 VALUES LESS THAN ( 39 )
  TABLESPACE users );
```

Index-Organized Tables

- Regular table access



IOT access



Index-Organized Tables and Heap Tables

- Compared to heap tables, IOTs:
 - Have faster key-based access to table data
 - Do not duplicate the storage of primary key values
 - Require less storage
 - Use secondary indexes and logical row IDs
 - Have higher availability because table reorganization does not invalidate secondary indexes

Index-Organized Tables


```
CREATE TABLE cikk_iot  
( ckod integer,  
  cnev varchar2(20),  
  szin varchar2(15),  
  suly float,  
  CONSTRAINT cikk_iot_pk PRIMARY KEY (ckod) )
```

ORGANIZATION INDEX


```
PCTTHRESHOLD 20 INCLUDING cnev  
OVERFLOW TABLESPACE users;
```

```
DBA_INDEXES index_type = 'IOT-TOP' table_name = 'CIKK_IOT'  
DBA_TABLES.IOT_TYPE = 'IOT' or 'IOT_OVERFLOW'  
DBA_TABLES.IOT_NAME = 'CIKK_IOT' for overflow segment
```


Clusters




Unclustered orders and
order_item tables



Clustered orders and
order_item tables

Cluster Types

**Index
cluster**



**Hash
cluster**



Situations Where Clusters Are Useful

Criterion	Index	Hash
Uniform key distribution	X	X
Evenly spread key values		X
Rarely updated key	X	X
Often joined master-detail tables	X	
Predictable number of key values		X
Queries using equality predicate on key		X

INDEX CLUSTER

```
CREATE CLUSTER personnel
```

```
( department_number NUMBER(2) ) SIZE 512;
```

```
CREATE TABLE emp_cl
```

```
( empno NUMBER PRIMARY KEY,ename VARCHAR2(30),  
  job VARCHAR2(27), mgr NUMBER(4), hiredate DATE,  
  sal NUMBER(7,2), comm NUMBER(7,2),  
  deptno NUMBER(2) NOT NULL)
```

```
CLUSTER personnel (deptno);
```

```
CREATE TABLE dept_cl
```

```
( deptno NUMBER(2), dname VARCHAR2(9), loc VARCHAR2(9))
```

```
CLUSTER personnel (deptno);
```

```
CREATE INDEX idx_personnel ON CLUSTER personnel;
```

```
DBA_CLUSTERS
```

```
DBA_CLU_COLUMNS
```

```
DBA_TABLES.CLUSTER_NAME = 'PERSONNEL'
```

HASH CLUSTER

```
CREATE CLUSTER personnel1  
( department_number NUMBER )  
  SIZE 512 HASHKEYS 500  
  STORAGE (INITIAL 100K NEXT 50K);
```

```
CREATE CLUSTER personnel2  
( home_area_code NUMBER, home_prefix NUMBER )  
  HASHKEYS 20  
  HASH IS MOD(home_area_code + home_prefix, 101);
```

```
CREATE CLUSTER personnel3  
(deptno NUMBER)  
  SIZE 512 SINGLE TABLE HASHKEYS 500;
```

```
DBA_CLUSTERS  
DBA_CLU_COLUMNS  
DBA_CLUSTER_HASH_EXPRESSIONS
```