



ORACLE  
NetSuite

# Dataset Builder Plug-in



2025.2

September 3, 2025



Copyright © 2005, 2025, Oracle and/or its affiliates.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software, software documentation, data (as defined in the Federal Acquisition Regulation), or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software," "commercial computer software documentation," or "limited rights data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle®, Java, and MySQL are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

If this document is in public or private pre-General Availability status:

This documentation is in pre-General Availability status and is intended for demonstration and preliminary use only. It may not be specific to the hardware on which you are using the software. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to this documentation and will not be responsible for any loss, costs, or damages incurred due to the use of this documentation.

If this document is in private pre-General Availability status:

The information contained in this document is for informational sharing purposes only and should be considered in your capacity as a customer advisory board member or pursuant to your pre-General Availability trial agreement only. It is not a commitment to deliver any material, code, or functionality, and should not be relied upon in making purchasing decisions. The development, release, timing, and pricing of any features or functionality described in this document may change and remains at the sole discretion of Oracle.

This document in any form, software or printed matter, contains proprietary information that is the exclusive property of Oracle. Your access to and use of this confidential material is subject to the terms and conditions of your Oracle Master Agreement, Oracle License and Services Agreement, Oracle PartnerNetwork Agreement, Oracle distribution agreement, or other license agreement which has been executed by you and Oracle and with which you agree to comply. This document and information contained herein may not be disclosed, copied, reproduced, or distributed to anyone outside Oracle without prior written consent of Oracle. This document is not part of your license agreement nor can it be incorporated into any contractual agreement with Oracle or its subsidiaries or affiliates.

### **Documentation Accessibility**

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <https://www.oracle.com/corporate/accessibility>.

### **Access to Oracle Support**

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

### **Sample Code**

Oracle may provide sample code in SuiteAnswers, the Help Center, User Guides, or elsewhere through help links. All such sample code is provided "as is" and "as available", for use only with an authorized NetSuite Service account, and is made available as a SuiteCloud Technology subject to the SuiteCloud Terms of Service at [www.netsuite.com/tos](http://www.netsuite.com/tos).

Oracle may modify or remove sample code at any time without notice.

### **No Excessive Use of the Service**

As the Service is a multi-tenant service offering on shared databases, Customer may not use the Service in excess of limits or thresholds that Oracle considers commercially reasonable for the Service. If Oracle reasonably concludes that a Customer's use is excessive and/or will cause immediate or ongoing performance issues for one or more of Oracle's other customers, Oracle may slow down or throttle Customer's excess use until such time that Customer's use stays within reasonable limits. If Customer's particular usage pattern requires a higher limit or threshold, then the Customer should procure a subscription to the Service that accommodates a higher limit and/or threshold that more effectively aligns with the Customer's actual usage pattern.

### **Beta Features**

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software" or "commercial computer software documentation" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

This documentation is in pre-General Availability status and is intended for demonstration and preliminary use only. It may not be specific to the hardware on which you are using the software. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to this documentation and will not be responsible for any loss, costs, or damages incurred due to the use of this documentation.

The information contained in this document is for informational sharing purposes only and should be considered in your capacity as a customer advisory board member or pursuant to your pre-General Availability trial agreement only. It is not a commitment to deliver any material, code, or functionality, and should not be relied upon in making purchasing decisions. The development, release, and timing of any features or functionality described in this document remains at the sole discretion of Oracle.

This document in any form, software or printed matter, contains proprietary information that is the exclusive property of Oracle. Your access to and use of this confidential material is subject to the terms and conditions of your Oracle Master Agreement, Oracle License and Services Agreement, Oracle PartnerNetwork Agreement, Oracle distribution agreement, or other license agreement which has been executed by you and Oracle and with which you agree to comply. This document and information contained herein may not be disclosed, copied, reproduced, or distributed to anyone outside Oracle without prior written consent of Oracle. This document is not part of your license agreement nor can it be incorporated into any contractual agreement with Oracle or its subsidiaries or affiliates.

# Table of Contents

|                                                                                    |   |
|------------------------------------------------------------------------------------|---|
| Dataset Builder Plug-in Interface Overview .....                                   | 1 |
| Developing a Dataset Builder Plug-in .....                                         | 1 |
| Enabling Features for a Dataset Builder Plug-in .....                              | 1 |
| Creating a Dataset Builder Plug-in Script File .....                               | 2 |
| Guidelines for Creating a Dataset Builder Plug-in Implementation Script File ..... | 2 |
| Administering a Dataset Builder Plug-in .....                                      | 3 |
| Adding the Plug-in Implementation .....                                            | 3 |
| Dataset Builder Plug-in Interface Definition .....                                 | 5 |
| createDataset(context) .....                                                       | 5 |
| dataset .....                                                                      | 6 |
| description .....                                                                  | 6 |
| name .....                                                                         | 6 |
| owner .....                                                                        | 6 |
| role .....                                                                         | 7 |

# Dataset Builder Plug-in Interface Overview



**Important:** The Dataset Builder Plug-in interface uses SuiteScript 2.0 or 2.1, and your entry point and library scripts need to use SuiteScript 2.0 or 2.1, too. For information, see the help topics [SuiteScript 2.x Script Creation Process](#), [SuiteScript 2.x](#), and [SuiteScript 2.1](#).

Use a Dataset Builder Plug-in to customize the creation of datasets for the Workbook API. For more information about the Workbook API, see the following help topics:

- [Workbook API](#)
- [N/dataset Module](#)
- [N/workbook Module](#)

Dataset Builder Plug-ins let you create custom datasets that fit your business needs. You can override the `createDataset()` function and create a dataset that contains a specific subset of data or uses custom logic. For example, you can create a dataset based on user-specific or role-specific information. The default behavior in the N/dataset module doesn't let you do this. Datasets you make with the N/dataset module are static and can't use dynamic information like the current role, user, and so on.

You can create custom datasets that suit your needs by customizing the core plug-in logic. To accommodate this process, NetSuite provides an interface definition that describes the name, parameters, and return type of each function defined in the plug-in's interface. For details, see [Dataset Builder Plug-in Interface Definition](#).

Dataset Builder Plug-ins are supported by SuiteCloud Development Framework (SDF). SDF enables you to customize your NetSuite account from an integrated development environment (IDE) on your local computer. For details, see .

You can customize a Dataset Builder Plug-in in SDF by defining `datasetbuilderplugin` objects. For details, see the help topic [datasetbuilderplugin](#).

For more information about Dataset Builder Plug-ins, see the following help topics:

| NetSuite Role | Help Topics                                             |
|---------------|---------------------------------------------------------|
| Developer     | <a href="#">Developing a Dataset Builder Plug-in</a>    |
| Administrator | <a href="#">Administering a Dataset Builder Plug-in</a> |

## Developing a Dataset Builder Plug-in

To develop a Dataset Builder Plug-in, complete the following steps:

1. Enable the required features for a Dataset Builder Plug-in. See [Enabling Features for a Dataset Builder Plug-in](#).
2. Create a Dataset Builder Plug-in script file. See [Creating a Dataset Builder Plug-in Script File](#).

## Enabling Features for a Dataset Builder Plug-in

To begin development or administration for a Dataset Builder Plug-in, make sure that the Server SuiteScript and Workbook API features are enabled in the development account.

## To enable features for the plug-in:

1. Go to Setup > Company > Enable Features.
2. Click the **SuiteCloud** subtab.
3. In the **SuiteScript** section, check the **Server SuiteScript** and **Workbook API** boxes.

## Creating a Dataset Builder Plug-in Script File

You must implement each Dataset Builder Plug-in interface function in a JavaScript file (with a .js extension). You can use SuiteCloud IDE, another JavaScript IDE, or a text editor to create the plug-in implementation script file.

The following is a Dataset Builder Plug-in sample:

```

1  /**
2   * @NApiVersion 2.x
3   * @NScriptType datasetbuilderplugin
4   */
5  define(['N/dataset'], function(dataset) {
6      return Object.freeze({
7          createDataset: function(context) {
8              var trandate = dataset.createColumn({
9                  fieldId: 'trandate',
10                 alias: 'date'
11             });
12             var join = dataset.createJoin({
13                 fieldId: 'createdby',
14                 target: 'entity'
15             });
16             var name = dataset.createColumn({
17                 join: join,
18                 fieldId: 'lastname',
19                 alias: 'name'
20             });
21             var tranid = dataset.createColumn({
22                 fieldId: 'tranid',
23                 alias: 'id'
24             });
25             var total = dataset.createColumn({
26                 fieldId: 'foreigntotal',
27                 alias: 'total'
28             });
29             var columns = [tranid, name, trandate, total];
30             context.dataset = dataset.create({
31                 type: 'transaction',
32                 columns: columns,
33                 name: 'Test Dataset',
34                 description: 'My Test Dataset'
35             });
36         },
37     });
38 });

```

## Guidelines for Creating a Dataset Builder Plug-in Implementation Script File

The following guidelines apply when creating a Dataset Builder Plug-in implementation script file:

- If you create an invalid dataset using a Dataset Builder Plug-in, the dataset may produce an unexpected error in the SuiteAnalytics Workbook UI. This error may occur if there are syntax or logic

errors in the code used to create the dataset in the plug-in. The invalid dataset won't show up in the list of available datasets, and you won't be able to use it in any workbooks.

To work around this issue, you should test your dataset creation code in the SuiteScript Debugger before using it in your plug-in implementation script file. To test for syntax errors, copy your dataset creation code into the debugger and run it. The debugger will identify any syntax errors before executing the dataset creation code. To test for logic errors, run the created dataset in the debugger using `Dataset.run()`. If parts of the code are incorrect (such as invalid field names or incorrect joins), the debugger will identify them at runtime. If you do not receive errors in the debugger, your dataset creation code is safe to use in your plug-in implementation script file and will not produce an unexpected error in the SuiteAnalytics Workbook UI. For more information about the SuiteScript Debugger, see the help topic [SuiteScript Debugger](#).

The following general guidelines apply when creating a plug-in implementation script file:

- The plug-in script file can have any name, provided it has a .js extension and contains an implementation of each interface function.
- You can include utility files with helper functions when you create the plug-in implementation.
- Due to limitations with how strings are handled in NetSuite, you cannot use the JavaScript case statement in the plug-in implementation script file.
- The plug-in allows up to 1000 usage units. For more information, see the help topic [SuiteScript Governance and Limits](#).
- If the character limit is exceeded in a field, the value will be truncated.

## Administering a Dataset Builder Plug-in

To install and set up a Dataset Builder Plug-in, complete the following steps:

1. Enable the required features for a Dataset Builder Plug-in. See [Enabling Features for a Dataset Builder Plug-in](#).
2. Add the plug-in implementation. See [Adding the Plug-in Implementation](#).

## Adding the Plug-in Implementation

After you create the plug-in script file, upload the file to NetSuite.

### To add the plug-in implementation:

1. Go to Customization > Plug-ins > Plug-in Implementations > New.  
NetSuite displays the Upload Plug-in Implementation page.
2. Beside the **Script File** field, click the plus icon.
3. Click **Choose File**, then select the script file that contains your plug-in implementation.
4. Click **Save**.
5. Click **Create Plug-in Implementation**.
6. On the **Plug-in Implementation** page, enter the following information:

| Field or Option | Description                                |
|-----------------|--------------------------------------------|
| Name            | User-friendly name for the implementation. |



| Field or Option | Description                                                                                                                                                                                                                                                                                                                                                                                                                              |
|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                 | This name appears in the plug-in implementation list.                                                                                                                                                                                                                                                                                                                                                                                    |
| ID              | Internal ID for the implementation for use in scripting.<br>If you do not provide an ID, NetSuite will provide one for you after you click <b>Save</b> . As a developer, when you write code that uses this implementation, you will reference the implementation using this ID.                                                                                                                                                         |
| Status          | Current status for the implementation.<br>Select <b>Testing</b> to have the implementation accessible to the owner of the implementation. Choose <b>Released</b> to have the implementation accessible in a production environment.                                                                                                                                                                                                      |
| Log Level       | Logging level for the script.<br>Select <b>Debug</b> , <b>Audit</b> , <b>Error</b> , or <b>Emergency</b> . The log information appears on the Execution Log subtab for the implementation after you create it.                                                                                                                                                                                                                           |
| Execute As Role | Role that the script runs as.<br>The Execute As Role field provides role-based granularity in terms of the permissions and restrictions of the executing script. Select <b>Current Role</b> to execute the script with the permissions of the currently logged-in NetSuite user.<br>If you created a custom role, be sure to test using that role. You can then bundle the custom role to distribute it with the plug-in implementation. |
| Description     | Description of the implementation.<br>This field is optional.                                                                                                                                                                                                                                                                                                                                                                            |
| Owner           | User account that owns the implementation.<br>The default value is the current user's account.                                                                                                                                                                                                                                                                                                                                           |
| Inactive        | Indicates whether the plug-in implementation is inactive and does not run in the account.<br>For example, you can make a plug-in implementation inactive to temporarily disable it for testing purposes.                                                                                                                                                                                                                                 |

- On the **Unhandled Errors** subtab, select which individual or individuals are notified if script errors occur. By default, the **Notify Script Owner** box is checked.



**Tip:** To enter multiple email addresses in the **Notify Emails** box, separate email addresses with a semicolon.

- Click **Save**.

# Dataset Builder Plug-in Interface Definition

The Dataset Builder Plug-in interface includes the following interface functions and context object properties:

| Interface Function                  | Context Object Properties                       |
|-------------------------------------|-------------------------------------------------|
| <code>createDataset(context)</code> | dataset<br>description<br>name<br>owner<br>role |

## `createDataset(context)`

|                             |                                                                                                                                                                                                                                                                   |
|-----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Function Declaration</b> | <code>function createDataset(context)</code>                                                                                                                                                                                                                      |
| <b>Type</b>                 | Interface function                                                                                                                                                                                                                                                |
| <b>Description</b>          | Creates a dataset.                                                                                                                                                                                                                                                |
| <b>Returns</b>              | void                                                                                                                                                                                                                                                              |
| <b>Input Parameters</b>     | context – A JavaScript object with the following properties: <ul style="list-style-type: none"> <li>■ <code>dataset</code></li> <li>■ <code>description</code></li> <li>■ <code>name</code></li> <li>■ <code>owner</code></li> <li>■ <code>role</code></li> </ul> |

## Example

```

1 function createDataset(context) {
2   var trandate = dataset.createColumn({
3     fieldId: 'trandate',
4     alias: 'Date'
5   });
6
7   var join = dataset.createJoin({
8     fieldId: 'createdby',
9     target: 'entity'
10  });
11  var name = dataset.createColumn({
12    join: join,
13    fieldId: 'lastname',
14    alias: 'Name'
15  });
16
17  var tranid = dataset.createColumn({
18    fieldId: 'tranid',
19    alias: 'id'
20  });
21  var total = dataset.createColumn({

```

```

22     fieldId: 'foreigntotal',
23     alias: 'total'
24   });
25
26   var columns = [tranid, name, trandate, total];
27   context.dataset = dataset.create({
28     type: 'transaction',
29     columns: columns,
30     name: 'Test Dataset',
31     description: 'My Test Dataset'});
32 }

```

## dataset

**Type** Object property

**Description** A context property for the created dataset.

In your plug-in implementation, use the N/dataset module to create a dataset as a [dataset.Dataset](#) object. After you create this object, assign it to this property. For more information, see the help topic [N/dataset Module](#).

This property is required. If you do not assign a dataset to this property, a NO\_DATASET\_CREATED error is thrown.

This property is write-only and accepts only a [dataset.Dataset](#) object. If you try to assign an object other than a [dataset.Dataset](#) object to this property, a WRONG\_PARAMETER\_TYPE error is thrown.

## description

**Type** Object property

**Description** The description of the plug-in implementation.

This description is the same as the one you specify when you add your plug-in implementation to NetSuite. For more information, see [Adding the Plug-in Implementation](#).

This property is a string.

This property is read-only. If you try to assign a value to this property, a READ\_ONLY error is thrown.

## name

**Type** Object property

**Description** The name of the plug-in implementation.

This name is the same as the one you specify when you add your plug-in implementation to NetSuite. For more information, see [Adding the Plug-in Implementation](#).

This property is a string.

This property is read-only. If you try to assign a value to this property, a READ\_ONLY error is thrown.

## owner

**Type** Object property

|                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b> | <p>The owner of the plug-in implementation.</p> <p>The owner is the user who added the plug-in implementation to NetSuite. For more information, see <a href="#">Adding the Plug-in Implementation</a>.</p> <p>This property is a number, which represents the internal ID of the user who added the plug-in implementation.</p> <p>This property is read-only. If you try to assign a value to this property, a READ_ONLY error is thrown.</p> |
|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

## role

|                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|--------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Type</b>        | Object property                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>Description</b> | <p>The role of the plug-in implementation.</p> <p>The role is the role of the user who added the plug-in implementation to NetSuite. For more information, see <a href="#">Adding the Plug-in Implementation</a>.</p> <p>This property is a number, which represents the internal ID of the role of the user who added the plug-in implementation.</p> <p>This property is read-only. If you try to assign a value to this property, a READ_ONLY error is thrown.</p> |