



ORACLE
NetSuite

NetSuite CPQ Proposal Generator Guide

2025.2

December 17, 2025



Copyright © 2005, 2025, Oracle and/or its affiliates.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software, software documentation, data (as defined in the Federal Acquisition Regulation), or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software," "commercial computer software documentation," or "limited rights data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle®, Java, and MySQL are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

If this document is in public or private pre-General Availability status:

This documentation is in pre-General Availability status and is intended for demonstration and preliminary use only. It may not be specific to the hardware on which you are using the software. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to this documentation and will not be responsible for any loss, costs, or damages incurred due to the use of this documentation.

If this document is in private pre-General Availability status:

The information contained in this document is for informational sharing purposes only and should be considered in your capacity as a customer advisory board member or pursuant to your pre-General Availability trial agreement only. It is not a commitment to deliver any material, code, or functionality, and should not be relied upon in making purchasing decisions. The development, release, timing, and pricing of any features or functionality described in this document may change and remains at the sole discretion of Oracle.

This document in any form, software or printed matter, contains proprietary information that is the exclusive property of Oracle. Your access to and use of this confidential material is subject to the terms and conditions of your Oracle Master Agreement, Oracle License and Services Agreement, Oracle PartnerNetwork Agreement, Oracle distribution agreement, or other license agreement which has been executed by you and Oracle and with which you agree to comply. This document and information contained herein may not be disclosed, copied, reproduced, or distributed to anyone outside Oracle without prior written consent of Oracle. This document is not part of your license agreement nor can it be incorporated into any contractual agreement with Oracle or its subsidiaries or affiliates.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <https://www.oracle.com/corporate/accessibility>.

Access to Oracle Support

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

Sample Code

Oracle may provide sample code in SuiteAnswers, the Help Center, User Guides, or elsewhere through help links. All such sample code is provided "as is" and "as available", for use only with an authorized NetSuite Service account, and is made available as a SuiteCloud Technology subject to the SuiteCloud Terms of Service at www.netsuite.com/tos.

Oracle may modify or remove sample code at any time without notice.

No Excessive Use of the Service

As the Service is a multi-tenant service offering on shared databases, Customer may not use the Service in excess of limits or thresholds that Oracle considers commercially reasonable for the Service. If Oracle reasonably concludes that a Customer's use is excessive and/or will cause immediate or ongoing performance issues for one or more of Oracle's other customers, Oracle may slow down or throttle Customer's excess use until such time that Customer's use stays within reasonable limits. If Customer's particular usage pattern requires a higher limit or threshold, then the Customer should procure a subscription to the Service that accommodates a higher limit and/or threshold that more effectively aligns with the Customer's actual usage pattern.

Beta Features

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software" or "commercial computer software documentation" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

This documentation is in pre-General Availability status and is intended for demonstration and preliminary use only. It may not be specific to the hardware on which you are using the software. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to this documentation and will not be responsible for any loss, costs, or damages incurred due to the use of this documentation.

The information contained in this document is for informational sharing purposes only and should be considered in your capacity as a customer advisory board member or pursuant to your pre-General Availability trial agreement only. It is not a commitment to deliver any material, code, or functionality, and should not be relied upon in making purchasing decisions. The development, release, and timing of any features or functionality described in this document remains at the sole discretion of Oracle.

This document in any form, software or printed matter, contains proprietary information that is the exclusive property of Oracle. Your access to and use of this confidential material is subject to the terms and conditions of your Oracle Master Agreement, Oracle License and Services Agreement, Oracle PartnerNetwork Agreement, Oracle distribution agreement, or other license agreement which has been executed by you and Oracle and with which you agree to comply. This document and information contained herein may not be disclosed, copied, reproduced, or distributed to anyone outside Oracle without prior written consent of Oracle. This document is not part of your license agreement nor can it be incorporated into any contractual agreement with Oracle or its subsidiaries or affiliates.

Table of Contents

- NetSuite CPQ Proposal Generator 1
 - NetSuite CPQ Proposal Generator Setup 1
 - Creating Document Templates 2
 - Dividing Documents into Groups 5
 - Adding Content to Sections 7
 - Including Dynamic Information in Text Sections 10
 - Appending PDF Files to Documents 14
 - Creating Documents from Transactions 15

NetSuite CPQ Proposal Generator

Note: NetSuite CPQ Proposal Generator requires NetSuite CPQ Configurator to create documents from transactions. For more information, see the help topic [Installing NetSuite CPQ SuiteApps](#).

NetSuite CPQ Proposal Generator helps sales teams quickly create customized business documents—such as quotes and proposals—for configured items and transactions. By quickly creating documents, sales teams can close deals for configured items faster.

With NetSuite CPQ Proposal Generator, you can:

- Create PDF files and Microsoft® Word documents (DOCX files).
- Base your documents on information from configured items, transactions, item records, and your account.
- Create document templates and automatically generate documents from those templates.
- Include or exclude information using question and answer combinations from NetSuite CPQ Configurator.
- Organize and structure the document layout.
- Customize and format documents with HTML and CSS code.
- Append existing PDF files to documents.

Note: You can also create documents for transactions that don't contain configured items.

Before creating documents, set up basic and additional options. For more information, see [NetSuite CPQ Proposal Generator Setup](#).

After completing the setup, you can create templates. A template defines the layout and structure for the document to be created. For more information, see [Creating Document Templates](#).

Templates are divided into groups and sections to help you organize information. Groups contain sections. Sections store the document content, such as text, tables, and images. You can nest groups within the template and sections within groups. For more information, see [Dividing Documents into Groups](#) and [Adding Content to Sections](#).

Sections can include dynamic information from configured items, transactions, and your account. For more information, see [Including Dynamic Information in Text Sections](#).

To include or exclude groups and sections in a document, use rules based on question and answer combinations from configurable items. For more information about rules, see the help topic [Activating or Hiding Building Blocks with Rules](#).

If you have information stored in PDF files, you can append those files to the final document. For more information, see [Appending PDF Files to Documents](#).

When templates are ready, users can create documents from transactions. For more information, see [Creating Documents from Transactions](#).

NetSuite CPQ Proposal Generator Setup

Before creating documents, define settings on the options record at CPQ > Proposal Generator > Settings.

Users must be able to view the **Proposal** button on transactions to create documents. To enable the **Proposal** button, check the **Proposal Generator Button** box. For more information about eligible transactions, see the help topic [Selecting Eligible Transactions](#).

If you use custom partner roles that aren't assigned to the Partner Center, check the **Custom Role Centers** box. This option lets users with those roles create documents from transactions. To verify the center assigned to a role, go to Setup > Users/Roles > Manage Roles. On the role record, view the information in the **Center Type** field. For more information about roles, see the help topic [NetSuite Roles Overview](#).

When you're finished with the setup, save the options record.

After the installation, NetSuite CPQ Proposal Generator automatically creates and enables two custom transaction body fields to work with eligible transactions. When customizing these transactions, always maintain these fields enabled to let users create documents.

The following table lists the custom transaction body fields.

Body Field Name	Body Field ID
NS CPQ Auto-generated Proposals	custbody_cpqp_auto_gen_proposals
NS CPQ Proposals JSON	custbody_cpqp_proposals_json

For more information about custom fields in NetSuite, see the help topic [Custom Fields](#).

Users with an administrator or a CPQ PropGen Builder role can create and maintain templates. For more information about NetSuite CPQ custom roles, see the help topic [Assigning NetSuite CPQ Custom Roles](#).

Creating Document Templates

With NetSuite CPQ Proposal Generator, you can create templates to outline the document structure and store the content of your documents.

Before creating a template, you should create a draft to visualize the look and feel of the final document. Drafting the document helps you make decisions about the type, order, and frequency of groups and sections.

Regarding the document layout, you can define the header and footer. Additionally, you can customize the look and feel with CSS code, as well as set up various formatting options—including the page format. To address layout differences between different formats (PDF, DOCX, and browser preview), two predefined CSS class selectors are available for the **Custom Styles** field:

- .html — Defines specific styles for the browser preview.
- .pdf — Defines specific styles for PDF files.

Note: The corresponding html and pdf classes are automatically assigned to the template <body> element; no setup is required.

You can control the styling of DOCX files using general CSS styles, and use the .pdf and .html class selectors for PDF or browser preview styles that will override any general styles. Styles without these class selectors are applied to all document formats.

Documents can also be automatically generated from templates, and you export and import templates. For more information, see:

- [Automatically Creating Documents](#)
- [Exporting Document Templates](#)
- [Importing Document Templates](#)

To create a template:

1. In NetSuite, go to CPQ > Proposal Generator> Templates.
2. Click **New CPQP Template**.
3. Provide a descriptive name for the template.
When users click the **Proposal** button on transactions, this name appears in the template list.
4. (Optional) In the **Description** field, enter a brief explanation of the template.
The description is for internal reference only and isn't displayed to users.
5. To define the page format for the final document, two options are available:
 - In the **Format** field, select a predefined page format, such as A3 or A5. If you leave this field blank, the default format is A4.
 - Check the **Custom Size** box. Then, provide the page height and width in millimeters.
6. In the **Custom Styles** field, enter CSS code to style the final document as you would in an external CSS file.
To identify CSS classes, create the document from the transaction and inspect the browser preview.
7. (Optional) In the **Pages Without Padding** field, specify any pages that shouldn't include margins.
Enter page numbers separated by commas.
8. (Optional) DOCX files include default margins. To remove default top, bottom, left, and right margins in DOCX files, check the **Remove margins in DOCX files** box.
Margins defined on groups will still be applied to the entire page. The first group on a page will determine the margins for the entire page.
9. Provide the content for the header and footer.
You can use the text editor or HTML and CSS code to format the text.



Note: The header and footer aren't included in the browser preview.

10. Provide the header and the footer height in pixels.
If you leave these fields blank, the default values are:
 - **Header** – 150 pixels.
 - **Footer** – 100 pixels.
11. The header and footer are displayed on every page of the final document. To hide them on the cover page, check the **Hide header and footer on the first page** box.
12. To automatically create documents when saving or editing a transaction:
 - Check the **Automatically generate PDF** box to create PDF files.
 - Check the **Automatically generate DOCX** box to create Microsoft® Word documents (DOCX files).

For more information, see [Automatically Creating Documents](#).
13. Click **Save**.

To hide a template from the template list users see on the transaction, check the **Disabled** box on the template record.

Automatically Creating Documents

Documents can be automatically created or updated with the latest transaction data every time users save a transaction. To automatically create documents for eligible transactions, check the following boxes on the template record:

- **Automatically generate PDF** box – Automatically creates PDF files.
- **Automatically generate DOCX** box – Automatically creates Microsoft® Word files.

If you enable these options for multiple templates, you'll obtain multiple documents for the same transaction. Automatically created documents are stored in the **Proposals** folder at File Cabinet > SuiteScripts > CPQ.

After saving and editing the transaction, users can go to the **Custom** subtab to view and download documents from the list of links in the **NS CPQ Auto-Generated Proposals** field.

Exporting Document Templates

After creating templates, you may want to export them for various reasons. You can combine export and import options to move templates from your sandbox to your production account after testing. Through exporting, you can create duplicate templates in your current account and use them as a base for new templates. Exporting is also useful to create backup copies and restore templates if you run into any issues.

In the exported file, you can include additional resources, such as the appended PDF files. If these additional resources aren't available in the target account, make sure you check the **Export resources** box before exporting the template. However, if you export the template for testing purposes and you don't need additional resources, leave the box unchecked.

To export a document template:

1. Go to CPQ > Proposal Generator > Settings.
2. In the **Export Proposal** field, select a template.
3. (Optional) To export additional resources, check the **Export resources** box.
4. Click **Export**.

The template is saved as a ZIP file to your computer.

Importing Document Templates

After exporting a document template, you can import it back into the same account or into a different one. Imported templates may include references to files. These referenced files may need to be retrieved in the target account.

Before importing a document template, choose how to handle references to attached files in the **NS Links Import Options** field:

- **Don't import links** – Leaves all fields that reference a file blank.
Choose this option when importing templates into a sandbox account for testing purposes and you don't need the referenced files.
- **Import links using same IDs** – Assigns file references based on the file's internal ID. This is the default option.
Choose this option when importing templates within the same account to optimize the import process.
- **Import links using search by name** – Finds the file internal ID by looking for the file name and place it in the link field.
Because files with the same name might have different internal IDs, choose this option when importing templates across different accounts.

To import a document template:

1. In NetSuite, go to CPQ > Proposal Generator > Settings.
2. In the **Import Proposal** field, select the ZIP file with the template.
3. In the **NS Links Import Options** field, select how to handle references to files when importing templates.
4. Click **Import**.

Dividing Documents into Groups

A group is a space in a document reserved for a specific type of content, such as the introduction, body, or conclusion. Groups organize documents into smaller parts to help users find information.

Each group has a sequence number that determines its order within the document. Groups with a lower sequence number are placed before those with a higher number.

You can include a group in a document only one time, or repeat it for every line item or configuration on the transaction. The group's frequency determines the section types you can create within that group. Each group can contain multiple sections.

To include or exclude groups in a document, use rules with question and answer combinations from configured items. For more information about rules, see the help topic [Activating or Hiding Building Blocks with Rules](#).

When including a group for every line item, you can make a further selection at the section level to specify the line item type, such as configured or additional item line. For more information about sections, see [Adding Content to Sections](#).

Regarding the look and feel of the group, you can define the page format, orientation, and margins. The group format takes priority over the template's format. If you don't specify the group format, the template format will apply.

On the group record, you can specify a transaction line field to group line items on the document depending on its value. For more information, see [Grouping Line Items](#).

To create a group:

1. In NetSuite, go to CPQ > Proposal Generator > Templates.
2. Edit a template record.
3. Go to the **Groups** subtab.
4. Click **New CPQP Group**.
5. Provide a descriptive name for the group.
6. In the **Repeat** field, select how many times you want to include the group in the final document:
 - **Once** – Includes the group one time only.
For example, you can use this frequency for the document introduction or the terms and conditions.
 - **Every Item** – Includes the group for every line item on the transaction.
The sections in this group can be repeated for every line item. You can also restrict the sections to configured or additional line items only. Define your preferences in the **Run For** field on the section record.
 - **Every Config** – Includes the group for every configuration in the transaction.
This group type is useful when the transaction may include configurations with additional items only.

7. Provide a sequence number to determine the order in which the group is included in the final document.
Enter a negative or positive number, for example, -2 or 5.
8. (Optional) In the **Group Items By** field, enter the transaction line field ID to group line items in the document. For more information, see [Grouping Line Items](#).
9. In the **Page Orientation** field, select how you want to arrange the sections in this group:
 - **Portrait** – Defines a vertical orientation.
This is the default option, and it works well for text sections.
 - **Landscape** – Defines a horizontal orientation.
You can use this option for tables with multiple columns.
10. (Optional) To start the group on a new page, check the **Page Break** box. This option adds a page break before the group.
11. (Optional) To avoid additional margins for the group, check the **No Div Wrap** box. This option prevents wrapping the group into a <div> element.
12. In the **Format** field, select a predefined page format for this group.
13. (Optional) Provide the top, right, bottom, and left margins in pixels.
14. In the **Show Rule** field, provide the condition that determines whether the group is included in the final document.
 - If the condition is based on question and answer combination from a NetSuite CPQ Configurator product, enter question and answer codes separated by a forward slash. For example, A/1. Use operators to combine multiple conditions. For example, A/1&B/2. For more information, see the help topic [Activating or Hiding Building Blocks with Rules](#).
 - Enter */*—the always true operator—in the following cases:
 - To always include a group in the final document.
 - To use the group for transactions without configured items.
 - To include a group that is repeated one time only in the document.
15. Click **Save**.

Grouping Line Items

 **Note:** To group line items, the group must be repeated for every line item.

Documents list line items in the same order as they appear on the transaction. Alternatively, you can organize line items by the values of a transaction line field. Grouping line items can improve the document structure and help users find information quickly.

In the document, you'll obtain a grouping for each value of the transaction line field. If some line items have a blank value for that field, those items will be grouped together. The content of the group will be repeated for every grouping.

To group line items on the document, enter the field ID in the **Group Items By** field on the group record.

You can also add a group header or group footer that repeat one time for each grouping. To do this, select **Item Group Header** or **Item Group Footer** in the **Run For** field on the section record. For more information, see [Adding Content to Sections](#).

If you need to group line items according to business-specific information, you can create a custom transaction line field. For more information, see the help topic [Creating Custom Transaction Line Fields](#).

Adding Content to Sections

Sections are used to store document content and further organize information within groups. For example, a document for a configurable desk may include a group for desk materials. Within that group, there may be:

- A section to introduce the materials.
- A table listing the materials.
- A closing section to explain the manufacturing process.

You can create multiple sections within a group. To sort sections, use the sequence number. Sections with a lower number are placed higher within the parent group.

To include or exclude sections in a document, use rules with question and answer combinations from configured items. For more information about rules, see the help topic [Activating or Hiding Building Blocks with Rules](#).

A section can contain text or a table. You can customize text sections using HTML and CSS code. In text section, you can also include dynamic information using resolve expressions and placeholders. For more information, see [Including Dynamic Information in Text Sections](#).

Table sections may be introduced by text. Some tables can source item data from transaction line fields (**Item List Table** option). The table will include default columns corresponding to the following resources:

- Line number
- Item name/number
- Rate
- Quantity
- Amount

Alternatively, table sections can source data from configured items (**Table** option). Data is sourced from answers or predefined answers that store an array of JSON objects. For example, you may create a table section sourcing content from the predefined answer that stores the list of additional items. Answers that can store arrays are input box text fields and text areas. For more information, see the help topics [Input Box Questions](#) and [Predefined Answers for Configuration Information Storing JSON Objects](#).

 **Note:** Use CSS code to style the tables.

The section type you can choose depends on its purpose, frequency, and the frequency of the parent group. The following table sums up the available section types and the options you can select.

Section Usage	Group Record	Section Record	
	Repeat Field	Type Field	Run For Field
Single text section	Once	HTML	—
Text section repeated for every configured item	Every Item	HTML	Configured Items
Text section repeated for every additional item	Every Item	HTML	Generic items
Text section repeated for every line item	Every Item	HTML	All Items
Introductory text section at the beginning of a grouping by field value	Every Item	HTML	Item Group Header

Section Usage	Group Record	Section Record	
	Repeat Field	Type Field	Run For Field
Closing text section at the end of a grouping by field value	Every Item	HTML	Item Group Footer
Text section repeated for every configuration	Every Config	HTML	—
Single table section with item data from transaction line fields	Once	Item List Table	—
Table section with configured item data repeated for every configured item	Every Item	Table	Configured Items
Table section with configured item data repeated for every configuration	Every Config	Table	—

To create a section:

1. On a saved group record, go to the **Sections** subtab.
2. Click **New CPQP Section**.
3. Provide a descriptive name for the section.
4. Provide a sequence number to sort this section within the group.
Enter a negative or positive number, for example, -2 or 5.
5. Select the section type.
6. If the section type is **HTML**, enter the text in the **HTML Content** field.
You can format the text by changing the paragraph font and size or making the text bold, italic, or underlined. You can also customize the content with HTML code and inline CSS. Click the **Source** button to access the HTML editor.



Note: If the section type is **Table** or **Item List Table**, you can still enter text in the **HTML Content** field. This content will appear before the table.

7. If the section type is **Item List Table** and you want to include transaction fields other than the default ones, specify the transaction line fields that will become the table columns. In the **Table Column Mapping** field, enter the field IDs and assign them labels. This is the syntax:

```

1 | [
2 |   {
3 |     "fieldID1": "label1"
4 |   },
5 |   {
6 |     "fieldID2": "label2"
7 |   },
8 |   {
9 |     "fieldID3": "label3"
10 |  }
11 | ]

```

8. If the section type is **Table**, specify where the array of JSON objects is stored and the JSON properties that will become the table columns.
 1. In the **Table Form QA** field, provide the predefined answer or the answer that stores the array of JSON objects. Enter the question and answer codes separated by a forward slash. For example, SOLE/MATERIALS or Q/A.
 2. In the **Table Column Mapping** field, enter the JSON properties to be used as columns and assign them labels. This is the syntax:

```

1  [
2    {
3      "property1": "label1"
4    },
5    {
6      "property2": "label1"
7    },
8    {
9      "property3": "label1"
10   }
11 ]

```

For example, a configurable desk includes a desk mat, a lamp, and an organizer as additional items. You can create a table using the SOLE/ITEMS predefined answer. This predefined answer stores the list of the additional items as an array of JSON objects.

Let's say you want the table to include the following JSON properties:

- itemname (**Name** field)
- price
- qty

In the **Table Column Mapping** field, you can enter the following code:

```

1  [
2    {
3      "itemname": "Additional Item"
4    },
5    {
6      "price": "Price"
7    },
8    {
9      "qty": "Quantity"
10   }
11 ]

```

Suppose a customer selected all three additional items. If you added basic formatting, the table on the final document would look like this.

Additional Item	Price	Quantity
Desk Mat	50	1
Lamp	30	1
Organizer	20	1

9. If the parent group repeats for every line item, select the line items for which you want to repeat the section in the **Run For** field.

The following options are available:

- **Configured Items** – Repeats the section for every main configured line item on the transaction. Additional items are excluded.
- **Generic Items** – Repeats the section for every additional line item on the transaction.
- **All Items** – Repeats the section for all line items on the transaction: configured, additional, and manually added line items.
- **Item Group Header** and **Item Group Footer** – When items are grouped by field value, these options repeat the section one time at the beginning or at the end of each grouping.

For more information about grouping line items, see [Grouping Line Items](#).

10. In the **Show Rule** field, provide the condition that determines whether the section will be included in the final document.

The condition is based on question and answer combinations from a NetSuite CPQ product. Enter question and answer codes separated by the forward slash character. For example, A/1. Use operators to combine multiple conditions. For example, A/1&B/2. For more information, see the help topic [Activating or Hiding Building Blocks with Rules](#).

11. Click **Save**.

Including Dynamic Information in Text Sections

Text sections can be customized with dynamic information from configured items, transactions, and your account. Dynamic information takes the form of resolve expressions and placeholders, which are added to the **HTML Content** field. You can also include dynamic content when the text section introduces a table.

The type of dynamic information you can add to text sections depends on:

- The parent group frequency.
You can find this information in the **Repeat** field on the group record.
- The line items for which the section is repeated.
You can find this information in the **Run For** field on the section record.

For more information about the available resolve expressions and placeholders, see:

- [Including Dynamic Information from Configured Items](#)
- [Including Dynamic Information from Transactions and Your Account](#)

Including Dynamic Information from Configured Items

In text sections, you can include dynamic information from configured items using resolve expressions and placeholders. Resolve expressions can be used when the parent group is repeated for:

- Every configuration
- Every configured line item
- Every additional line item

The following table sums up the option combinations that admit resolve expressions.

Resolve Expressions	Repeat Field (Group Record)	Run For Field (Section Record)
■ {Q/A} ■ {Q:ALT_NAME} ■ {Q:DESC} ■ {Q:NAME}	Every Item	■ Configured items ■ Generic Items
	Every Config	—

The **Generic Items** option refers to additional items.

You can also use these predefined answers as resolve expressions:

- **{SOLE/QUANTITY}** – The quantity of the configured item.
The value is sourced from the **Quantity** field on the product interface.
- **{SOLE/TOTAL_PRICE}** – The price of the configured item multiplied by the quantity.
The value is sourced from the **Total** field on the product interface.
- **{SOLE/MAT_PRICE}** – The price of a single configured item.

The value is sourced from the **Unit** field on the product interface.

For more information about resolve expressions and predefined answers, see the help topics [Obtaining Answer Data with Resolve Expressions](#) and [Including Additional Conditions in Rules and Actions with Predefined Answers](#).

The following table sums up available placeholders to add dynamic information from configured items.

Placeholder	Description	Repeat Field (Group Record)	Run For Field (Section Record)
{CPI}	Returns the preview image for the configured item.	Every Item	Configured Items
		Every Config	—

Repeating Text Sections Containing Dynamic Information from Configured Items

Note: Dynamic information from configured items can be sourced for sections repeated for every configured item or every configuration.

When working with text sections, you can enter content that will be filled in with data from configured items. Data can be sourced from a qTable question or an input box text field or box storing an array of JSON objects.

The text will repeat:

- For each row in the qTable question
- Or for each object in the array

For more information about qTables and input box questions, see the help topics [QTable Questions](#) and [Input Box Questions](#).

The syntax for the array of JSON objects is:

```

1  [
2    {
3      "property1": "value",
4      "property2": "value",
5      "property3": "value"
6    },
7    {
8      "property1": "value",
9      "property2": "value",
10     "property3": "value"
11   },
12   {
13     "property1": "value",
14     "property2": "value",
15     "property3": "value"
16   }
17 ]

```

You can add as many properties as required to each object.

To repeat a text section with configured item data:

1. Edit the section.
2. In the **Repeat Data Block** field, select whether you want to repeat the content depending on the number of:

- Rows in the qTable question
 - JSON objects in the array
3. If you selected **JSON** in step 2:
 1. In the **JSON Q/A** field, enter the NetSuite CPQ Configurator answer that stores the array of JSON objects.
 2. In the **HTML Content** field, enter the JSON properties preceded by an asterisk and enclosed in curly braces. The syntax is `{*property}`.
 4. If you selected **QTable** in step 2:
 - In the **QTable Question** field, enter the question code from a NetSuite CPQ Configurator qTable.
 - In the **HTML Content** field, enter the qTable answer code in lowercase preceded by an asterisk and enclosed in curly braces. The syntax is `{*answercode}`.
 5. Click **Save**.

Example

Suppose you want the document to list every desk model in the same series the user has selected. This information is already stored in a NetSuite CPQ Configurator answer in JSON format. You want to add that information to the **HTML Content** field to avoid typing in each model.

The array of JSON objects may look like this:

```

1  [
2    {
3      "series": "A1000",
4      "shape": "Rectangle",
5      "topfinish": "Wood"
6    },
7    {
8      "series": "A1000",
9      "shape": "Rectangle",
10     "topfinish": "Laminate"
11   },
12   {
13     "series": "A1000",
14     "shape": "L-shape",
15     "topfinish": "Wood"
16   },
17   {
18     "series": "A1000",
19     "shape": "L-shape",
20     "topfinish": "Laminate"
21   },
22   {
23     "series": "A1000",
24     "shape": "U-shape",
25     "topfinish": "Wood"
26   }
27 ]

```

To work with this array:

- In the **JSON Q/A** field, enter the combination of question and answer codes, for example, DESK_A1000/MODELS.
- In the **HTML Content** field, specify the properties you want to extract from the array. Enter the properties preceded by an asterisk and enclosed in curly braces.

```
Series: {*series} | Shape: {*shape} | Top Finish: {*topfinish}
```

In the final document, the result would be:

```
Series: A1000 | Shape: Rectangle | Top Finish: Wood
Series: A1000 | Shape: Rectangle | Top Finish: Laminate
Series: A1000 | Shape: L-shape | Top Finish: Wood
Series: A1000 | Shape: L-shape | Top Finish: Laminate
Series: A1000 | Shape: U-shape | Top Finish: Wood
```

Including Dynamic Information from Transactions and Your Account

In your documents, you can include information from transactions and your account using placeholders. The following table shows the available placeholders and the data type they represent.

Placeholder	Description
■ {@TransactionBodyFieldID} ■ {#TransactionLineFieldID} ■ {%ItemRecordBodyFieldID}	Represent a transaction body field, a transaction line field, or an item record body field, respectively. Use the field ID. Depending on the field type, they return: ■ The value of text fields. ■ The ID of the option in dropdown lists and multiple-choice fields. If multiple options are selected, they return comma-separated IDs. ■ 'T' (true) or 'F' (false) for checkboxes.  Note: Item body fields for configured items correspond to those of the base item.
{\$storedisplayimage}	Returns the item image from the Item Display Image field. This field is placed under the Web Store subtab on the item record.
{\$GROUPNAME}	Returns the name of the grouping to which the item belongs.  Note: The group name corresponds to the value taken by the field specified in the Group Items By field on the parent group.
{\$GROUPTOTAL}	Returns the total price amount for the items belonging to the same grouping.  Note: The group depends on the value taken by the field specified in the Group Items By field on the parent group.
{\$date}	Returns the current date in DD/MM/YYYY format.
■ {\$page} ■ {\$pages}	Return the page number and the total number of pages, respectively.

The following table describes the options to select in groups and sections when working with each placeholder.

Placeholder	Repeat Field (Group Record)	Run For Field (Section Record)
■ {@TransactionBodyFieldID}	Once	—

Placeholder	Repeat Field (Group Record)	Run For Field (Section Record)
■ {\$date} ■ {\$page} ■ {\$pages}	Every Item	■ Configured Items ■ Generic items ■ All Items ■ Item Group Header ■ Item Group Footer
	Every Config	—
■ {#TransactionLineFieldID} ■ {%ItemRecordBodyFieldID} ■ {\$storedisplayimage}	Every Item	■ Configured Items ■ Generic Items ■ All Items
■ {\$GROUPNAME} ■ {\$GROUPTOTAL}	Every Item	■ Configured Items ■ Generic Items ■ All Items ■ Item Group Header ■ Item Group Footer

Some placeholders can be extended by adding parameters. The following table lists the available parameters for each placeholder.

Placeholder Parameter	Description	Compatible Placeholders
:text	Returns the option or options for dropdown lists and multiple-choice fields instead of the option ID. If users select multiple options, they are returned separated by commas.	■ {@TransactionBodyFieldID} ■ {#TransactionLineItemFieldID} ■ {%ItemRecordBodyFieldID}
\$currency	Formats numbers as currency.  Note: The field must contain numbers.	■ {@TransactionBodyFieldID} ■ {#TransactionLineItemFieldID} ■ {%ItemRecordBodyFieldID} ■ {\$GROUPTOTAL}

Parameters are appended to placeholders. See the following examples:

- {@TransactionBodyFieldID:text}
- {\$GROUPTOTAL\$currency}

Appending PDF Files to Documents

When creating documents, you can append PDF files to the final document to include additional information. Each PDF file has a sequence number to sort it within the final document. PDF files with a lower sequence number are placed before those with a higher number.

You can store the PDF files in the File Cabinet, in fields on the item record, or you can provide the links where they're stored. If the transaction includes configured items, you can append the PDF files based on the answers users select while configuring the item on the product interface.

To append a PDF file to the document:

1. In NetSuite, go to CPQ > Proposal Generator> Templates.
2. Edit a template record.
3. Go to the **PDFs** subtab.
4. Click **New CPQP PDF**.
5. Provide a descriptive name for the PDF file.
6. Provide a sequence number to determine the order in which the PDF file is appended to the document.
Enter a negative or positive number, for example, -2 or 5.
7. In the **Origin to Take From** field, select where to find the PDF file:
 - **File** – Lets you choose a PDF file stored in the File Cabinet.
In the **PDF File** field, select a PDF file.
 - **Item Field** – Lets you use a PDF file stored in an item record field.
In the **Item Field** field, enter the field ID.
 - **URL** – Lets you use a PDF File accessible through a link.
In the **URL field**, enter the link.
8. In the **Show Rule** field, provide the condition that determines whether the file will be appended to the final document.
 - If the condition is based on question and answer combination from a NetSuite CPQ Configurator product, enter question and answer codes separated by a forward slash. For example, A/1. Use operators to combine multiple conditions. For example, A/1&B/2. For more information, see the help topic [Activating or Hiding Building Blocks with Rules](#).
 - If the transaction doesn't include configured items, enter */*—the always true operator—to always append the PDF file to the final document.
9. Click **Save**.

Creating Documents from Transactions

Users can create documents from saved transactions. For more information about eligible transactions, see the help topic [Selecting Eligible Transactions](#).

To create a document:

1. On a saved transaction, click the **Proposal** button on the **Items** subtab.
2. In the template list, select the template to generate the document in the browser.

 **Note:** The document header and footer aren't included in the browser preview.

3. On the document page, click one of the following buttons:
 - **Print** – Prints the document.
 - **PDF** – Downloads the document as a PDF file.
 - **DOC** – Downloads the document as a Microsoft® Word file (DOCX file).