



ORACLE
NetSuite

NetSuite Field Service Management API

2025.2

September 3, 2025



Copyright © 2005, 2025, Oracle and/or its affiliates.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software, software documentation, data (as defined in the Federal Acquisition Regulation), or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software," "commercial computer software documentation," or "limited rights data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle®, Java, and MySQL are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

If this document is in public or private pre-General Availability status:

This documentation is in pre-General Availability status and is intended for demonstration and preliminary use only. It may not be specific to the hardware on which you are using the software. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to this documentation and will not be responsible for any loss, costs, or damages incurred due to the use of this documentation.

If this document is in private pre-General Availability status:

The information contained in this document is for informational sharing purposes only and should be considered in your capacity as a customer advisory board member or pursuant to your pre-General Availability trial agreement only. It is not a commitment to deliver any material, code, or functionality, and should not be relied upon in making purchasing decisions. The development, release, timing, and pricing of any features or functionality described in this document may change and remains at the sole discretion of Oracle.

This document in any form, software or printed matter, contains proprietary information that is the exclusive property of Oracle. Your access to and use of this confidential material is subject to the terms and conditions of your Oracle Master Agreement, Oracle License and Services Agreement, Oracle PartnerNetwork Agreement, Oracle distribution agreement, or other license agreement which has been executed by you and Oracle and with which you agree to comply. This document and information contained herein may not be disclosed, copied, reproduced, or distributed to anyone outside Oracle without prior written consent of Oracle. This document is not part of your license agreement nor can it be incorporated into any contractual agreement with Oracle or its subsidiaries or affiliates.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <https://www.oracle.com/corporate/accessibility>.

Access to Oracle Support

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

Sample Code

Oracle may provide sample code in SuiteAnswers, the Help Center, User Guides, or elsewhere through help links. All such sample code is provided "as is" and "as available", for use only with an authorized NetSuite Service account, and is made available as a SuiteCloud Technology subject to the SuiteCloud Terms of Service at www.netsuite.com/tos.

Oracle may modify or remove sample code at any time without notice.

No Excessive Use of the Service

As the Service is a multi-tenant service offering on shared databases, Customer may not use the Service in excess of limits or thresholds that Oracle considers commercially reasonable for the Service. If Oracle reasonably concludes that a Customer's use is excessive and/or will cause immediate or ongoing performance issues for one or more of Oracle's other customers, Oracle may slow down or throttle Customer's excess use until such time that Customer's use stays within reasonable limits. If Customer's particular usage pattern requires a higher limit or threshold, then the Customer should procure a subscription to the Service that accommodates a higher limit and/or threshold that more effectively aligns with the Customer's actual usage pattern.

Beta Features

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software" or "commercial computer software documentation" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

This documentation is in pre-General Availability status and is intended for demonstration and preliminary use only. It may not be specific to the hardware on which you are using the software. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to this documentation and will not be responsible for any loss, costs, or damages incurred due to the use of this documentation.

The information contained in this document is for informational sharing purposes only and should be considered in your capacity as a customer advisory board member or pursuant to your pre-General Availability trial agreement only. It is not a commitment to deliver any material, code, or functionality, and should not be relied upon in making purchasing decisions. The development, release, and timing of any features or functionality described in this document remains at the sole discretion of Oracle.

This document in any form, software or printed matter, contains proprietary information that is the exclusive property of Oracle. Your access to and use of this confidential material is subject to the terms and conditions of your Oracle Master Agreement, Oracle License and Services Agreement, Oracle PartnerNetwork Agreement, Oracle distribution agreement, or other license agreement which has been executed by you and Oracle and with which you agree to comply. This document and information contained herein may not be disclosed, copied, reproduced, or distributed to anyone outside Oracle without prior written consent of Oracle. This document is not part of your license agreement nor can it be incorporated into any contractual agreement with Oracle or its subsidiaries or affiliates.

Table of Contents

Field Service Management API	1
models/asset	2
models/case	4
models/customer	5
models/task	6
routes/mobile	7
routes/scheduler	49
utilities/collection	66
utilities/config	66
utilities/form	70
utilities/merge	71
utilities/resolve	71
utilities/resource	72
utilities/rule	74
views/asset/address	74
view/asset/addresssearch	75
views/asset/parent	76
views/asset/profitability	76
views/asset/project	77
view/asset/task	79
views/assetcustomer	80
views/case/autoname	82
views/case/invoice	82
views/case/projects	83
views/case/servicereport	86
views/case/tasks	88
views/customer/profitability	92
views/employee/loginas	93
views/employee/mobilelogin	94
views/itemfulfillment/assets	96
views/newnull	98
views/project/autoname	99
views/project/contact	99
views/project/customer	100
views/project/journal	101
views/project/profitability	102
views/project/program	103
view/project/subprojects	105
views/projecttask/servicereport	106
views/schedule	108
views/signature	108
views/task/autoname	109
views/task/servicereport	109
views/task/unassigned	111

Field Service Management API



Important: The code found in the Field Service Management API are samples and may not be applicable to your use case. The sample code described herein is provided on an "as is" basis, without warranty of any kind, to the fullest extent permitted by law.

- [models/asset](#)
- [models/case](#)
- [models/customer](#)
- [models/task](#)
- [routes/mobile](#)
- [routes/scheduler](#)
- [utilities/collection](#)
- [utilities/config](#)
- [utilities/form](#)
- [utilities/merge](#)
- [utilities/resolve](#)
- [utilities/resource](#)
- [utilities/rule](#)
- [views/asset/address](#)
- [view/asset/addresssearch](#)
- [views/asset/parent](#)
- [views/asset/profitability](#)
- [views/asset/project](#)
- [view/asset/task](#)
- [views/assetcustomer](#)
- [views/case/autoname](#)
- [views/case/invoice](#)
- [views/case/projects](#)
- [views/case/servicereport](#)
- [views/case/tasks](#)
- [views/customer/profitability](#)
- [views/employee/loginas](#)
- [views/employee/mobilelogin](#)
- [views/itemfulfillment/assets](#)
- [views/newnull](#)
- [views/project/autoname](#)
- [views/project/contact](#)
- [views/project/customer](#)
- [views/project/journal](#)
- [views/project/profitability](#)
- [views/project/program](#)
- [view/project/subprojects](#)

- views/projecttask/servicereport
- views/schedule
- views/signature
- views/task/autoname
- views/task/servicereport
- views/task/unassigned

models/asset

Parameters

Parameter	Type	Attributes	Description
mode	Number, Boolean	Required	Pass an asset id to load a record, true to create a record, or false to validate a record configuration.
item	Number	Required	Item record the asset was generated from.
serial	String	Required	Unique serial for the asset

Members

uniqueFormula

Type	Description
Array	Formula to check for duplicate assets

Default

```
1 | {}
```

uniqueTemplate

Type	Description
Array	Template to compare objects to search results

Default

```
1 | {}
```

customers

Type	Description
Object	Customers available to be serviced by the current Asset. The current record model and the selected Asset model is in scope.

Default

```

1  {
2    "customers": {
3      "array": true,
4      "customer": {
5        "all": true,
6        "record": "customer",
7        "filters": [
8          "internalid",
9          "anyof",
10         "${ asset.customer || 0 }"
11       ]
12     }
13   }
14 }

```

map

Type	Description
Object	Field map

Properties

Property	Type	Description
name	String	Name of the Asset
autoname	String	Auto generated name for the Asset. When this has a value, the Name is populated from this attribute. Overwrite this to disable autonaming or change the naming formula.
parent	Number	Auto generated name for the Asset. When this has a value, the Name is populated from this attribute. Overwrite this to disable autonaming or change the naming formula.
item	Number	Item the Asset is an instance of.
serial	String	Serial number of the Asset.
customer	Number	Customer owner of the Asset
customers	true, false, *	Customers that are valid to create records against. Overwrite this to refer to Asset fields. When <i>true</i> all customers are available. When <i>false</i> no customers can be selected. When an id or list or ids, these customers are used. Otherwise differ to customers object.
addressbook	String	Customer address book associated with the Asset.
addresstext	String	Address of the asset. This is sourced from <i>addressbook</i> when present.
latitude	String	Latitude of the asset. This is calculated from the <i>addresstext</i> when present.
longitude	String	Longitude of the asset. This is calculated from the <i>addresstext</i> when present.
region	Number	Region the Asset is in.

Default

```

1  {
2    "map": {
3      "name": "name",

```



```

4      "autoname": "formulatext:substr(trim(regexp_replace({custrecord_nx_asset_item}, '^'||{custrecord_nx_asset_item.parent}||' :
      ')||' '||nvl({custrecord_nx_asset_serial}, nvl(regexp_replace({custrecord_nx_asset_address_text},CHR(13)||CHR(10),' ')),
      {custrecord_nx_asset_address}))), 1, 80)",
5      "parent": "parent",
6      "type": "custrecord_nx_asset_type",
7      "item": "custrecord_nx_asset_item",
8      "serial": "custrecord_nx_asset_serial",
9      "customer": "custrecord_nx_asset_customer",
10     "customers": "formulatext:{custrecord_nx_asset_customer.internalid}",
11     "transaction": "custrecord_nx_asset_transaction",
12     "addressbook": "custrecord_nx_asset_address",
13     "addresstext": "custrecord_nx_asset_address_text",
14     "latitude": "custrecord_nx_asset_latitude",
15     "longitude": "custrecord_nx_asset_longitude",
16     "timezone": "custrecord_nx_asset_time_zone",
17     "timezoneid": "custrecord_nx_asset_time_zone.custrecord_nx_time_zone_olson|",
18     "region": "custrecord_nx_asset_region",
19     "locationchanged": "custrecord_nx_asset_location_update",
20     "id": "internalid"
21   }
22 }

```

record

Type	Description
String	Record type

Default

```

1  {
2    "record": "customrecord_nx_asset"
3  }

```

models/case

Members

autoclose

Type	Description
Boolean	Automatically close Project when no open cases

Default

```

1  {
2    "autoclose": true
3  }

```

Methods

invoice()

Generate invoice from existing salesorder

Parameters

Parameter	Type	Attributes	Description
options.verify	Boolean	Required	Optionally check if invoice can be created

Returns

Type	Description
Number, Boolean	Invoice id or Boolean if verify

models/customer

Members

assets

Type	Description
Object	Assets available to be serviced by the selected Customer. The current record model and the selected Customer model is in scope.

Default

```

1  {
2    "assets": {
3      "array": true,
4      "asset": {
5        "all": true,
6        "record": "customrecord_nx_asset",
7        "filters": [
8          "custrecord_nx_asset_customer",
9          "anyof",
10         "${ customer.id }"
11       ]
12     }
13   }
14 }
```

map

Type	Description
Object	Field map

Properties

Property	Type	Description
assets	true, false, *	Assets that are valid to create records against. Overwrite this to refer to Customer fields. When <i>true</i> all Assets are available. When <i>false</i> no Assets can be selected. Otherwise differ to a Customer search.

Default

```

1  {
2    "map": {
3      "contact": "contactprimary.internalid|",
4      "email": "email",
5      "phone": "phone",
6      "currency": false,
7      "assets": "formulatext:''",
8      "id": "internalid"
9    }
10 }

```

models/task

Members

defaults

Type	Description
Object	Field map

Default

```

1  {
2    "defaults": {
3      "name": "To Be Generated",
4      "starttimetz": "09:00",
5      "endtimetz": "17:00"
6    }
7  }

```

map

Type	Description
Object	Field map

Default

```

1  {
2    "map": {
3      "name": "title",
4      "company": "company",
5      "project": "formulatext:nvl2(nullif({company.internalid}, {custevent_nx_customer.internalid}), {company.internalid}, '')|",
6      "status": "status",
7      "priority": "priority",

```

```
8      "message": "message",
9      "type": "custevent_nx_task_type",
10     "customer": "custevent_nx_customer",
11     "asset": "custevent_nx_task_asset",
12     "address": "custevent_nx_address",
13     "latitude": "custevent_nx_latitude",
14     "longitude": "custevent_nx_longitude",
15     "timezone": "custevent_nx_time_zone",
16     "timezoneid": "custevent_nx_timezone_depr",
17     "id": "internalid",
18     "autoname": "formulatext:substr({custevent_nx_task_type}||' '||{custevent_nx_task_number}||' '||{custevent_nx_task_asset}, 1,
19     80)",
20     "number": "custevent_nx_task_number",
21     "start": "starttime",
22     "end": "formulatext:to_char(cast({enddate} as timestamp with local time zone),'fmHH:fmMI am')|endtime",
23     "date": "startdate",
24     "startdate": "custevent_nx_start_date",
25     "starttimetz": "custevent_nx_start_time",
26     "enddate": "custevent_nx_end_date",
27     "endtimetz": "custevent_nx_end_time",
28     "duedate": "duedate",
29     "completed": "custevent_nx_task_end",
30     "booking": "custevent_nx_task_booking_confirmed",
31     "assigned": "assigned",
32     "case": "case.internalid|supportcase",
33     "team": "custevent_nx_task_team[]",
34     "skill": "custevent_nx_task_skill[]",
35     "timedevent": "formulatext:NVL2({starttime}, 'T', 'F')|timedevent",
36     "billing": "custevent_nx_billing_type",
37     "actions": "custevent_nx_actions_taken",
38     "subsidiary": "formulatext:coalesce({case.subsidiary.id}, {job.subsidiary.id}, {company.subsidiary.id}, {assigned.sub
39     sidiary.id}, 1)"
40   }
41 }
```

record

Type	Description
String	Record type

Default

```
1  {
2    "record": "task"
3  }
```

routes/mobile

Mobile web app server

Members

actions

Type	Description
—	Actions

Default

```

1  {
2    "actions": {
3      "label": "Task",
4      "icon": "checked",
5      "element": {
6        "number": {
7          "type": "text",
8          "label": "Number",
9          "class": "col-2",
10         "title": true,
11         "hidden": true,
12         "column": 1
13       },
14       "type": {
15         "type": "select",
16         "label": "Type",
17         "class": "el-12",
18         "required": true,
19         "column": 1,
20         "options": {
21           "sort": "label",
22           "task": {
23             "record": "customrecord_nx_task_type",
24             "map": {
25               "id": "internalid",
26               "label": "name"
27             }
28           }
29         }
30       },
31       "message": {
32         "type": "textarea",
33         "placeholder": "Message...",
34         "class": "el-12"
35       },
36       "assigned": {
37         "type": "select",
38         "label": "Assigned",
39         "placeholder": "Lead...",
40         "class": "el-12",
41         "value": {
42           "id": "${ user.internalid }",
43           "label": "${ user.label }"
44         },
45         "required": true,
46         "options": "resources.options"
47       },
48       "team": {
49         "type": "select",
50         "multiple": true,
51         "placeholder": "Team...",
52         "class": "el-12",
53         "value": "${ event.team }",
54         "options": "resources.options"
55       },
56       "resources": {
57         "type": "datalist",
58         "options": {
59           "sort": "label",
60           "employee": {
61             "record": "employee",
62             "filters": [
63               [
64                 "isinactive",
65                 "is",
66                 "F"
67               ],
68               "and",
69               [
70                 "custentity_nx_region",
71                 "noneof",

```

```

72         "@NONE@"
73     ],
74     ],
75     "map": {
76         "id": "internalid",
77         "label": "formulatext:nvl(trim(trim(trim({firstname}))||' '||{middlename}))||' '||{lastname}), {entityid})"
78     }
79 }
80 }
81 },
82 "date": {
83     "type": "date",
84     "label": "Date",
85     "class": "el-4",
86     "value": "${ event.date }",
87     "column": 2,
88     "required": true
89 },
90 "start": {
91     "type": "timeofday",
92     "label": "Start",
93     "class": "el-4",
94     "value": "09:00",
95     "step": 60
96 },
97 "end": {
98     "type": "timeofday",
99     "label": "End",
100    "class": "el-4",
101    "value": "17:00",
102    "step": 60
103 },
104 "booking": {
105     "type": "checkbox",
106     "label": "Confirmed Booking"
107 }
108 },
109 "article": {
110     "record": "task",
111     "filters": [
112         "custevent_nx_created_from",
113         "anyof",
114         "${ event.internalid }"
115     ],
116     "map": {
117         "number": "custevent_nx_task_number",
118         "start": "formulatext:to_char(nvl({custevent_nx_start_time},{starttime}),'fmHH:fmMI am')|custevent_nx_start_time",
119         "end": "formulatext:to_char(nvl({custevent_nx_end_time}, cast({enddate} as timestamp with local time zone)), 'fmHH:fmMI
am')|custevent_nx_end_time",
120         "date": "formulatext:nvl({custevent_nx_start_date},{startdate})|custevent_nx_start_date",
121         "booking": "custevent_nx_task_booking_confirmed",
122         "message": "message",
123         "assigned": {
124             "id": "=assigned",
125             "label": "#assigned|"
126         },
127         "team": {
128             "id": "=custevent_nx_task_team|",
129             "label": "#custevent_nx_task_team|"
130         },
131         "type": {
132             "id": "=custevent_nx_task_type",
133             "label": "#custevent_nx_task_type|"
134         }
135     },
136     "idempotencyField": "custevent_nx_idempotency_key",
137     "defaults": {
138         "custevent_nx_customer": "${ event.customer }",
139         "company": "${ event.company }",
140         "supportcase": "${ event.supportcase }",
141         "custevent_nx_task_asset": "${ event.asset }",
142         "custevent_nx_created_from": "${ event.internalid }",
143         "timedevent": true

```

```

144 |     }
145 |   }
146 | }
147 | }

```

addable

Type	Description
Boolean	Show the new event button

Default

```

1 | {
2 |   "addable": false
3 | }

```

administrators

Type	Description
Array.<Number>	NetSuite Users in any of these roles are considered Mobile Administrators allowing them to generate mobile invites for other users and to login as another Mobile User. Roles with NextService Mobile check will show here by default.

Default

```

1 | {
2 |   "administrators": [
3 |     3
4 |   ]
5 | }

```

asset

Type	Description
Object	Resource that presents information about the Asset or one of its child assets.

Default

```

1 | {
2 |   "asset": {
3 |     "label": "Asset",
4 |     "hidden": "${ !options.asset && !event.asset }",
5 |     "min": 1,
6 |     "max": 1,
7 |     "element": {
8 |       "image": {
9 |         "type": "image",
10 |        "readonly": true
11 |      },
12 |      "description": {
13 |        "type": "textarea",
14 |        "label": "Description",
15 |        "readonly": true
16 |      }
17 |    },
18 |    "article": {
19 |      "record": "customrecord_nx_asset",

```

```
20     "filters": [
21       [
22         "internalid",
23         "anyof",
24         "${ event.asset || 0 }"
25       ],
26       "or",
27       [
28         [
29           "parent",
30           "noneof",
31           "@NONE@"
32         ],
33         "and",
34         [
35           "parent.internalid",
36           "anyof",
37           "${ event.asset || 0 }"
38         ]
39       ]
40     ],
41     "filterby": {
42       "id": "${ options.asset || event.asset }"
43     },
44     "map": {
45       "image": {
46         "id": "=formulatext:nvl({custrecord_nx_asset_item.storedisplaythumbnail.id}, {custrecord_nx_asset_item.storedisplayimage.id})",
47         "url": "=formulatext:'${ url }file/'||nvl({custrecord_nx_asset_item.storedisplaythumbnail.id}, {custrecord_nx_asset_item.storedisplayimage.id})||'&key=${ user.key }'"
48       },
49       "description": "custrecord_nx_asset_item.description|"
50     }
51   }
52 }
53 }
```

consumables

Type	Description
Object	Resource that allows the user to consume inventory from their warehouse.

Default

```
1 {
2   "consumables": {
3     "label": "Inventory",
4     "icon": "wrench",
5     "element": {
6       "inventory": {
7         "label": "Inventory",
8         "type": "select",
9         "class": "el-9",
10        "search": true,
11        "barcode": true,
12        "options": "consumable.options"
13      },
14      "quantity": {
15        "label": "Quantity",
16        "type": "integer",
17        "class": "el-3",
18        "column": 4,
19        "min": 1,
20        "step": 1,
21        "required": true
22      },
23      "item": {
24        "label": "Item",
```



```

25     "type": "select",
26     "class": "el-12",
27     "column": 1,
28     "readonly": true,
29     "required": true,
30     "value": "inventory.options.filter(o=> { return o.id == inventory.value.id })[0].item"
31   },
32   "location": {
33     "label": "Location",
34     "type": "select",
35     "class": "el-12",
36     "readonly": true,
37     "value": "inventory.options.filter(o=> { return o.id == inventory.value.id })[0].location"
38   },
39   "bin": {
40     "label": "Bin",
41     "type": "select",
42     "class": "el-12",
43     "column": 2,
44     "readonly": true,
45     "value": "inventory.options.filter(o=> { return o.id == inventory.value.id })[0].bin"
46   },
47   "seriallot": {
48     "label": "Serial/Lot",
49     "type": "text",
50     "class": "el-12",
51     "column": 3,
52     "readonly": true,
53     "value": "inventory.options.filter(o=> { return (o.id == inventory.value.id) && (o.serial || o.lot) }).map(o=> { return
o.serial || o.lot })[0].label"
54   },
55   "number": {
56     "label": "Number",
57     "type": "text",
58     "class": "el-12",
59     "hidden": true,
60     "value": "inventory.options.filter(o=> { return (o.id == inventory.value.id) && (o.serial || o.lot) }).map(o=> { return
o.serial || o.lot })[0].id"
61   }
62 },
63 "article": {
64   "record": "customrecord_nx_consumable",
65   "filters": [
66     [
67       "custrecord_nx_constask",
68       "anyof",
69       "${ event.internalid }"
70     ],
71     "and",
72     [
73       "custrecord_nx_consemployee",
74       "anyof",
75       "${ user.internalid }"
76     ]
77   ],
78   "filterby": {
79     "asset": "${ options.asset || event.asset }"
80   },
81   "map": {
82     "readonly": "formulatext:case when {custrecord_nx_constask.status.id} like 'COMPLETE' then 'T' else 'F' end",
83     "quantity": "custrecord_nx_consqty",
84     "asset": "custrecord_nx_consasset",
85     "inventory": {
86       "id": "=formulatext:'item-'||{custrecord_nx_consitem.id}||'-'||{custrecord_nx_conslocation.id}||'-'||{custrecord_nx_con
bin}||'-'||{custrecord_nx_conserial}",
87       "label": "formulatext:{custrecord_nx_consitem}||nv12({custrecord_nx_conbin},' : BIN '||{custrecord_nx_con
bin},' )||nv12({custrecord_nx_conseriallabel},' : I/N '||{custrecord_nx_conseriallabel},' )"
88     },
89     "item": {
90       "id": "custrecord_nx_consitem",
91       "label": "#custrecord_nx_consitem|"
92     },
93     "location": {

```

```

94     "id": "=custrecord_nx_conslocation",
95     "label": "formulatext:regex_replace({custrecord_nx_conslocation}, '.* : ')"
96   },
97   "bin": {
98     "id": "=#custrecord_nx_conbin",
99     "label": "#custrecord_nx_conbin|"
100  },
101  "number": "custrecord_nx_conserial",
102  "seriallot": "custrecord_nx_conseriallabel"
103 },
104 "idempotencyField": "custrecord_nx_consumable_idempotency_key",
105 "defaults": {
106   "custrecord_nx_constask": "${ event.internalid }",
107   "asset": "${ options.asset || event.asset }",
108   "custrecord_nx_consemployee": "${ user.internalid }"
109 }
110 }
111 }
112 }

```

contact

Type	Description
—	Contact

Default

```

1  {
2    "contact": {
3      "label": "Contacts",
4      "icon": "torso",
5      "readonly": true,
6      "element": {
7        "name": {
8          "type": "text",
9          "label": "Name",
10         "title": true,
11         "column": 1,
12         "hidden": true
13       },
14       "image": {
15         "type": "image",
16         "readonly": true
17       },
18       "email": {
19         "type": "email",
20         "label": "Email",
21         "column": 2,
22         "class": "el-12"
23       },
24       "phone": {
25         "type": "phone",
26         "label": "Phone",
27         "column": 3,
28         "class": "el-12"
29       },
30       "mobile": {
31         "type": "phone",
32         "label": "Mobile",
33         "class": "el-12"
34     }
35   },
36   "article": {
37     "contact": {
38       "record": "contact",
39       "filters": [
40         "internalid",
41         "anyof",

```

```

42     "${ event.contact }"
43   ],
44   "map": {
45     "name": "entityid",
46     "email": "email",
47     "phone": "phone",
48     "mobile": "mobilephone",
49     "image": {
50       "id": "=image",
51       "url": "formulatext:'${ url }file/'||{image.id}||'&key=${ user.key }'"
52     }
53   },
54 },
55 "customer": {
56   "record": "customer",
57   "filters": [
58     "formulatext:case when {internalid} = '${ event.customer }' and '${ event.contact }' = '0' then 'T' else 'F' end",
59     "is",
60     "T"
61   ],
62   "map": {
63     "name": "formulatext:nvl(trim({firstname}||' '||{lastname}),{companyname})",
64     "email": "email",
65     "phone": "phone",
66     "mobile": "mobilephone"
67   }
68 }
69 }
70 }
71 }

```

details

Type	Description
Object	Details resource

Default

```

1  {
2    "details": {
3      "label": "Details",
4      "icon": "clipboard",
5      "min": 1,
6      "max": 1,
7      "element": {
8        "actions": {
9          "type": "longtext",
10         "label": "Actions Taken",
11         "placeholder": "Actions taken...",
12         "class": "el-12",
13         "readonly": "${ event.teamuser }",
14         "summary": true
15       },
16       "caseclosed": {
17         "type": "checkbox",
18         "label": "Case Closed",
19         "class": "el-12",
20         "readonly": "${ event.teamuser }",
21         "hidden": "${ event.projecttask }",
22         "summary": true
23       }
24     },
25     "article": {
26       "record": "${ event.record }",
27       "filters": "${ event.internalid }",
28       "map": {
29         "actions": "custevent_nx_actions_taken",
30         "caseclosed": "custevent_nx_case_closed"

```

```

31 |     }
32 |   }
33 | }
34 | }

```

event

Type	Description
Object	Events to load for the current User. This can be configured to source different record types but by default only CRM Tasks are shown.

Properties

Property	Type	Description
event.record	String	Record type
event.filters	Filterexpression	Search filters to apply to the record type
event.map	Object	Field map of search columns and fields. These attributes will be available in definitions for Resources and Articles.
event.map.id	String	Must include an id attribute who's value will be in the pattern of "{modelid}-{internalid}".
event.map.label	String	Label for the event.
event.map.sublabel	String	Sublabel for the event.
event.map.startdate	String	Start date time stamp for the event.
event.map.enddate	String	End date time stamp for the event.
event.map.address	String	Address of the event in Google Api friendly format.
event.map.latitude	Number	Latitude of the event.
event.map.longitude	Number	Longitude of the event.
event.map.timezone	String	Timezone of the event in NetSuite compatible Olsom values. Requests for the Event, it's Resources, and its Articles will be run in this timezone.
event.resources	Array.<object>	Set of rules to lookup which Resources to load for the user. Properties added to the rules will filter the attribute on the user.
event.resources[].resources	Array.<string>	Resource ids to load for the containing rule.

Default

```

1 | {
2 |   "event": {
3 |     "element": {
4 |       "asset": {
5 |         "type": "select",
6 |         "label": "Asset",
7 |         "class": "el-4",
8 |         "required": true,
9 |         "search": true,
10 |        "remote": true,
11 |        "options": {

```

```

12     "record": "customrecord_nx_asset",
13     "filters": [
14         [
15             "isinactive",
16             "is",
17             "F"
18         ],
19         "and",
20         [
21             "formulatext:{name}||' '||nvl(trim({custrecord_nx_asset_customer.firstname})||' '||{custrecord_nx_asset_customer.last
name})),{custrecord_nx_asset_customer.companyname})",
22             "contains",
23             "${ options.search || ' ' }"
24         ]
25     ],
26     "map": {
27         "id": "internalid",
28         "label": "name",
29         "customers": "formulatext:{custrecord_nx_asset_customer.internalid}",
30         "optgroup": "formulatext:nvl(trim({custrecord_nx_asset_customer.firstname})||' '||{custrecord_nx_asset_customer.last
name})),{custrecord_nx_asset_customer.companyname})",
31         "customer": {
32             "id": "custrecord_nx_asset_customer",
33             "label": "formulatext:nvl(trim({custrecord_nx_asset_customer.firstname})||' '||{custrecord_nx_asset_customer.last
name})),{custrecord_nx_asset_customer.companyname})"
34         },
35         "timezone": {
36             "id": "=custrecord_nx_asset_time_zone",
37             "label": "custrecord_nx_asset_time_zone.custrecord_nx_time_zone_abbreviation"
38         }
39     }
40 },
41 },
42 "job": {
43     "type": "select",
44     "label": "Project",
45     "class": "el-4",
46     "required": true,
47     "remote": true,
48     "asset": "asset.value && asset.value.id",
49     "date": "date.value",
50     "options": {
51         "sort": "label",
52         "active": {
53             "record": "job",
54             "filters": [
55                 [
56                     "custentity_nx_asset",
57                     "is",
58                     "${ options.asset || 0 }"
59                 ],
60                 "and",
61                 [
62                     [
63                         "startdate",
64                         "isempty",
65                         ""
66                     ],
67                     "or",
68                     [
69                         "startdate",
70                         "onorbefore",
71                         "${ options.date }"
72                     ]
73                 ],
74                 "and",
75                 [
76                     [
77                         "enddate",
78                         "isempty",
79                         ""
80                     ],
81                     "or",

```

```

82         [
83             "enddate",
84             "onorafter",
85             "${ options.date }"
86         ]
87     ],
88     "and",
89     [
90         "isinactive",
91         "is",
92         "F"
93     ]
94 ],
95 "map": {
96     "id": "internalid",
97     "label": "formulatext:{custentity_nx_project_type}||nv12({startdate},' from '||{startdate},' to '||{enddate},' ')||nv12({custentity_nx_time_zone}, ' ' || {custentity_nx_time_zone.custrecord_nx_time_zone_abbreviation},' ')",
98     "optgroup": "formulatext:nv1(trim({custentity_nx_customer.firstname})||' '||{custentity_nx_customer.lastname}),(custentity_nx_customer.companyname))",
99     "customer": {
100         "id": "custentity_nx_customer",
101         "label": "formulatext:nv1(trim({custentity_nx_customer.firstname})||' '||{custentity_nx_customer.lastname}),(custentity_nx_customer.companyname))"
102     },
103     "timezone": {
104         "id": "=custentity_nx_time_zone",
105         "label": "custentity_nx_time_zone.custrecord_nx_time_zone_abbreviation"
106     }
107 },
108 },
109 "types": {
110     "record": "customrecord_nx_project_type",
111     "filters": [
112         [
113             "isinactive",
114             "is",
115             "F"
116         ],
117         "and",
118         [
119             "internalid",
120             "noneof",
121             [
122                 0
123             ]
124         ]
125     ],
126     "map": {
127         "id": "formulatext:'type-'||{internalid}",
128         "label": "name",
129         "optgroup": "formulatext:'- New -'"
130     }
131 }
132 },
133 },
134 "date": {
135     "type": "date",
136     "label": "Date",
137     "class": "el-4",
138     "column": 2,
139     "required": true
140 },
141 "customer": {
142     "type": "select",
143     "label": "Customer",
144     "class": "el-6",
145     "required": true,
146     "remote": true,
147     "search": "(asset.value && asset.options.filter(o=>{ return o.id == asset.value.id }))[0].customers === true) ? 'remote' : 'local'",
148     "asset": "asset.value && asset.value.id",
149     "value": "(job.value && job.options.filter(o=>{ return o.id == job.value.id }))[0].customer) || (asset.value && asset.options.filter(o=>{ return o.id == asset.value.id }))[0].customer)",

```

```

150     "disabled": "job.value && !job.value.id.match(/^type-/)",
151     "options": {
152       "record": "customer",
153       "filters": [
154         [
155           "formulatext:nvl(trim({firstname}||' '||{lastname}},{companyname})",
156           "contains",
157           "${ options.search || ' ' }"
158         ],
159         "and",
160         "${ var customers = typeof asset != 'undefined' && asset && new Asset(asset).customers; return customers && ((customers
instanceof Array) ? ['internalid', 'anyof', customers] : ['internalid', 'noneof', '@NONE@']) }"
161       ],
162       "map": {
163         "id": "internalid",
164         "label": "formulatext:nvl(nvl(trim({firstname}||' '||{lastname}},{companyname}), {entityid})"
165       }
166     },
167   },
168   "contact": {
169     "type": "select",
170     "label": "Contact",
171     "class": "el-6",
172     "remote": true,
173     "required": "!(contact.options && contact.options.length)",
174     "disabled": "!(contact.options && contact.options.length)",
175     "entity": "(job.value && !job.value.id.match(/^type-/)) && job.value.id || (customer.value && customer.value.id)",
176     "options": {
177       "record": "contact",
178       "filters": [
179         [
180           "customer.internalid",
181           "anyof",
182           "${ options.entity || 0 }"
183         ],
184         "or",
185         [
186           "job.internalid",
187           "anyof",
188           "${ options.entity || 0 }"
189         ]
190       ],
191       "map": {
192         "id": "internalid",
193         "label": "<entityid", "selected": "formulatext:case when {role.id} = -10 then 'T' else 'I'
end } } }", "case": { "type": "select", "label": "Case", "class": "el-12", "placeholder": "Type...", "required": true, "column": 1, "options": { "sort": "label", "task": { "record": "customrecord_nx_case_type", "map": { "id": "internalid", "label": "name" } } } }, "details": { "type": "textarea", "placeholder": "Details...", "class": "el-12", "required": true }, "type": { "type": "select", "label": "Task", "class": "el-12", "placeholder": "Type...", "required": true, "column": 1, "options": { "sort": "label", "task": { "record": "customrecord_nx_task_type", "map": { "id": "internalid", "label": "name" } } } }, "message": { "type": "textarea", "placeholder": "Message...", "class": "el-12", "required": true }, "start": { "type": "timeofday", "label": "Start", "class": "el-4", "value": "09:00", "step": 60, "required": true }, "end": { "type": "timeofday", "label": "End", "class": "el-4", "value": "17:00", "step": 60, "required": true }, "timezone": { "type": "select", "label": "Time Zone", "class": "el-4", "disabled": true, "value": "(job.value && job.options.filter(o => o.id == job.value.id)[0].timezone) || (job.value && asset.options.filter(o => o.id == asset.value.id)[0].timezone)"
194       },
195       "booking": {
196         "type": "checkbox",
197         "label": "Confirmed Booking"
198       }
199     },
200   "article": {
201     "task": {
202       "record": "task",
203       "filters": [
204         [
205           "assigned",
206           "anyof",
207           "${ user.internalid }"
208         ],
209         "or",
210

```

[illegible]


```
265     "case": "case.custevent_nx_case_type|",
266     "task": "custevent_nx_task_type|",
267     "assettype": "custevent_nx_task_asset.custrecord_nx_asset_type|",
268     "crtask": "internalid",
269     "customer": "custevent_nx_customer",
270     "company": "company",
271     "subsidiary": "formulatext:coalesce({case.subsidiary.id}, {job.subsidiary.id}, {company.subsidiary.id})",
272     "team": {
273       "id": "=custevent_nx_task_team|",
274       "label": "#custevent_nx_task_team|"
275     },
276     "teamuser": "formulatext:case when instr(''||{custevent_nx_task_team.id}||',' , '||'{$ user.internalid }'||',' ) = 0
then 'F' else 'T' end",
277     "assigneduser": "formulatext:case when '{$ user.internalid }' = {Assigned.id} then 'T' else 'F' end",
278     "contact": "formulatext:COALESCE(TO_NUMBER({contact.id}), TO_NUMBER({case.contact.id}), TO_NUMBER({job.contac
t.id}), TO_NUMBER({custevent_nx_customer.contact.id}), 0)",
279     "email": "case.email|"
280   },
281   "idempotencyField": "custevent_nx_idempotency_key",
282   "resources": [],
283   "defaults": {
284     "name": "To Be Generated",
285     "starttimetz": "09:00",
286     "endtimetz": "17:00"
287   }
288 },
289 "projecttask": false
290 }
291 }
292 }
```

expenses

Type	Description
—	Expenses

Default

```
1 {
2   "expenses": {
3     "label": "Expenses",
4     "icon": "creditcard",
5     "max": 1,
6     "element": {
7       "expenses": {
8         "type": "table",
9         "label": "Expenses",
10        "required": true
11      },
12      "entity": {
13        "type": "hidden",
14        "value": "{$ event.company }",
15        "parent": "expenses"
16      },
17      "asset": {
18        "type": "hidden",
19        "value": "{$ event.asset }",
20        "parent": "expenses"
21      },
22      "crtask": {
23        "type": "hidden",
24        "value": "{$ event.crtask }",
25        "parent": "expenses"
26      },
27      "category": {
28        "type": "select",
29        "label": "Category",
30        "class": "col-xs-0 col-sm-0 el-9",
```

```

31     "required": true,
32     "parent": "expenses",
33     "column": 2,
34     "options": {
35       "sort": "label",
36       "categories": {
37         "record": "expensecategory",
38         "filters": [
39           "custrecord_nx_expensecat_show_on_mobile",
40           "is",
41           "T"
42         ],
43         "map": {
44           "id": "internalid",
45           "label": "name"
46         }
47       }
48     },
49   },
50   "amount": {
51     "type": "currency",
52     "label": "Amount",
53     "class": "el-3",
54     "min": 0.01,
55     "step": 0.01,
56     "required": true,
57     "parent": "expenses",
58     "column": 4
59   },
60   "date": {
61     "type": "date",
62     "label": "Date",
63     "class": "col-xs-0",
64     "hidden": "${ event.crmtask }",
65     "parent": "expenses",
66     "column": 3
67   },
68   "memo": {
69     "type": "textarea",
70     "label": "Description",
71     "required": true,
72     "parent": "expenses",
73     "column": 1
74   },
75   "receipt": {
76     "type": "image",
77     "label": "Receipt",
78     "parent": "expenses"
79   },
80   "total": {
81     "type": "currency",
82     "label": "Total",
83     "class": "el-12",
84     "readonly": true,
85     "column": 3
86   },
87   "status": {
88     "type": "text",
89     "label": "Status",
90     "class": "el-12",
91     "readonly": true,
92     "column": 2
93   },
94   "transid": {
95     "type": "text",
96     "label": "Transaction",
97     "hidden": true,
98     "title": true,
99     "column": 1
100  },
101 },
102 "article": {
103   "extend": "models/transaction",

```

```

104     "record": "expensereport",
105     "filters": [
106       [
107         [
108           "custbody_nx_task",
109           "anyof",
110           "${ event.internalid }"
111         ],
112         "or",
113         [
114           "custbody_nx_projecttask",
115           "anyof",
116           "${ event.internalid }"
117         ]
118       ],
119       "and",
120       [
121         "employee.internalid",
122         "anyof",
123         "${ user.internalid }"
124       ]
125     ],
126     "map": {
127       "id": "**formulanumeric:case when {taxline} = 'F' and {line} > 0 then {internalid} end|internalid",
128       "tranid": "tranid|",
129       "status": "status#|",
130       "total": "total|",
131       "expenses": [
132         {
133           "line": "line|expense.line",
134           "entity": "customer.internalid|expense.customer",
135           "memo": "formulatext:REPLACE({memo}, {expensecategory}||': ')|expense.memo",
136           "amount": "amount|expense.amount",
137           "category": {
138             "id": "=expensecategory|expense.category",
139             "label": "#expensecategory|"
140           },
141           "receipt": {
142             "id": "=lineFile.internalid|expense.expmidiaitem",
143             "url": "formulatext:nv12({lineFile.internalid},'${ url }file/'||{lineFile.internalid.id}||'&key=${ user.key }', '')"
144           },
145           "date": "expensedate|expense.expensedate",
146           "asset": "custcol_nx_asset|expense.custcol_nx_asset",
147           "crmtask": "custcol_nx_task|expense.custcol_nx_task"
148         }
149       ]
150     },
151     "defaults": {
152       "custbody_nx_customer": "${ event.customer }",
153       "custbody_nx_task": "${ event.crmtask }",
154       "custbody_nx_projecttask": "${ event.projecttask }",
155       "custbody_nx_case": "${ event.supportcase }",
156       "custbody_nx_asset": "${ event.asset }",
157       "entity": "${ user.internalid }",
158       "trandate": "${ event.date }",
159       "use multicurrency": false
160     }
161   }
162 }
163 }

```

files

Type	Description
Object	Resource that allows the user to upload and attach files to the current task.

Default

```

1 {
2   "files": {
3     "label": "Files",
4     "icon": "paperclip",
5     "element": {
6       "name": {
7         "label": "Name",
8         "type": "text",
9         "column": 1,
10        "title": true,
11        "hidden": true
12      },
13      "document": {
14        "label": "size.value ? 'Download' : 'Upload'",
15        "type": "file",
16        "required": true,
17        "readonly": "!!size.value"
18      },
19      "size": {
20        "label": "Size",
21        "type": "number",
22        "unit": "byte",
23        "class": "el-12",
24        "column": 3,
25        "readonly": true,
26        "hidden": "!!size.value"
27      },
28      "description": {
29        "label": "Description",
30        "type": "textarea",
31        "required": true,
32        "column": 2
33      }
34    },
35    "article": {
36      "record": "file",
37      "filters": [
38        [
39          "formulatext:case when {folder} like '${ event.id }-%${ user.internalid }' then 'T' else 'F' end",
40          "is",
41          "T"
42        ],
43        "or",
44        [
45          "internalid",
46          "anyof",
47          {
48            "array": true,
49            "default": "@NONE@",
50            "event": {
51              "record": "${ event.record }",
52              "filters": [
53                "internalid",
54                "anyof",
55                "${ event.internalid }"
56              ],
57              "map": "formulatext:{file.internalid}"
58            }
59          ]
60        ],
61        "filterby": {
62          "asset": "${ options.asset || event.asset }"
63        },
64        "map": {
65          "name": "name",
66          "document": {
67            "id": "internalid",
68            "url": "formulatext:'${ url }file/'||{internalid}||'&key=${ user.key }'"
69          },
70          "description": "formulatext:regexp_replace({description}, ['\r\n']*{^})*$", ''",
71          "size": "formulanumeric:{documentsize}*1024|",

```

```

73     "asset": "formulatext:case when {folder} like '${ event.id }-%${ user.internalid }' then regexp_replace({folder},
74     '${ event.id }-(.*)-${ user.internalid }', '\\1') else '${ event.asset }' end"
75   },
76   "defaults": {
77     "record": "${ event.record }",
78     "recordid": "${ event.internalid }"
79   }
80 }
81 }

```

history

Type	Description
Object	Resource that shows the service history for the event Asset or one of its child assets.

Default

```

1  {
2    "history": {
3      "label": "History",
4      "icon": "bookmark",
5      "hidden": "${ !options.asset && !event.asset }",
6      "search": true,
7      "remote": true,
8      "readonly": true,
9      "element": {
10       "number": {
11         "type": "text",
12         "label": "Number",
13         "title": true,
14         "hidden": true
15       },
16       "date": {
17         "type": "date",
18         "label": "Date",
19         "class": "el-12 col-right",
20         "column": 2
21       },
22       "assigned": {
23         "type": "text",
24         "label": "Assigned",
25         "class": "el-12"
26       },
27       "phone": {
28         "type": "phone",
29         "label": "Phone",
30         "class": "el-12"
31       },
32       "details": {
33         "type": "html",
34         "label": "Details",
35         "column": 1
36       },
37       "actions": {
38         "type": "textarea",
39         "label": "Actions"
40       },
41       "inventory": {
42         "type": "table",
43         "label": "Inventory"
44       },
45       "item": {
46         "type": "text",
47         "label": "Item",
48         "class": "col-9 el-9",
49         "parent": "inventory",
50         "column": 1

```

[illegible]

```
120     "inventory": {
121       "all": true,
122       "record": "salesorder",
123       "filters": [
124         "custcol_nx_asset",
125         "anyof",
126         "${ options.asset || event.asset }"
127       ],
128       "map": {
129         "id": "*formulatext:nvl2({custcol_nx_task}, 'task-'||{custcol_nx_task.id}, 'projecttask-'||{custcol_nx_projecttask.id})",
130         "inventory": [
131           {
132             "item": "item#",
133             "quantity": "quantity"
134           }
135         ]
136       }
137     },
138     "files": {
139       "all": true,
140       "record": "file",
141       "filters": [
142         "formulatext:case when {folder} like '%task-%${ options.asset || event.asset }-%' then 'T' else 'F' end",
143         "is",
144         "T"
145       ],
146       "map": {
147         "id": "*formulatext:regexp_replace({folder}, '^([[:alpha:]]*-[[:digit:]]+).*', '\\1')",
148         "files": [
149           {
150             "name": "name",
151             "document": {
152               "id": "=internalid",
153               "url": "formulatext:'${ url }file/'||{internalid}||'&key=${ user.key }'"
154             },
155             "description": "description",
156             "size": "documentsize"
157           }
158         ]
159       }
160     }
161   }
162 }
163 }
```

imagesize

Type	Description
Number	Default maximum dimensions of images uploaded from file inputs

Default

```
1 {
2   "imagesize": 1080
3 }
```

import

Type	Description
Object	JavaScript, JSON, and CSS file paths to append to the head of the document. These files are cached for offline usage and will trigger an update and redownload all files when any import id changes. JSON files are loaded as a JavaScript global named after the import id.

Default

```

1 | {
2 |   "import": {}
3 | }

```

inject

Type	Description
String	Optional HTML to append to the head of the document. Useful for adding styles and scripts for customization.

Default

```

1 | {
2 |   "inject": "<!-- Inject -->"
3 | }

```

inventory

Type	Description
Object	Inventory Resource to load datalists of items that can be used on Task Resources. The configured but unprocessed JSON for these Resources can be accessed in the Mobile Suitelet by navigating the Mobile to the url mobile/task.

Properties

Property	Type	Description
consumable	Object	Datalist element of consumable items available in the Users location.
consumable.options	Object	Object to resolve into array of options. Sorts on the label property.
consumable.options.group	Object	Item Groups.
consumable.options.location	Object	Non Serialized, Non Bin, Non Lot Numbered inventory when Inventory Locations is disabled.
consumable.options.inventorylocation	Object	Non Serialized, Non Bin, Non Lot inventory when Inventory Locations is enabled.
consumable.options.inventorynumber	Object	Serialized or Lot Numbered inventory.
consumable.options.inventorynumberbinonhand	Object	Bin Numbered, Serialized, or Lot Numbered inventory when Advanced Inventory enabled.
consumable.options.binnumber	Object	Bin Numbered, Non Serialized, Non Lot Numbered inventory when Advanced Inventory disabled.
consumable.options.binonhand	Object	Bin Numbered, Non Serialized, Non Lot Numbered inventory when Advanced Inventory enabled.
orderable	Object	Datalist element of orderable and quotable items.

Property	Type	Description
orderable.options	Object	Object to resolve into array of options. Sorts on the label property.
orderable.options.location	Object	Quotable and Orderable items

Default

```

1  {
2    "inventory": {
3      "label": "Inventory",
4      "element": {
5        "consumable": {
6          "uri": "consumable",
7          "type": "datalist",
8          "options": {
9            "sort": "label",
10         "group": {
11           "all": true,
12           "record": "item",
13           "filters": [
14             [
15               "isinactive",
16               "is",
17               "F"
18             ],
19             "and",
20             [
21               "type",
22               "anyof",
23               [
24                 "Group"
25               ]
26             ],
27             "and",
28             [
29               "custitem_nx_show_on_mobile",
30               "is",
31               "T"
32             ]
33           ],
34         "map": {
35           "id": "formulatext:item-||{internalid}",
36           "label": "formulatext:nvl({displayname}, {name})",
37           "item": {
38             "id": "internalid",
39             "label": "formulatext:nvl({displayname}, {name})"
40           }
41         }
42       },
43       "location": false,
44       "inventorylocation": {
45         "all": true,
46         "record": "item",
47         "filters": [
48           [
49             "isinactive",
50             "is",
51             "F"
52           ],
53           "and",
54           [
55             "type",
56             "anyof",
57             [
58               "InvPart",
59               "Assembly"
60             ]
61           ],
62           "and",

```

```

63     [
64         "custitem_nx_show_on_mobile",
65         "is",
66         "T"
67     ],
68     "and",
69     [
70         "inventorylocation",
71         "anyof",
72         "${ options.location || user.location }"
73     ],
74     "and",
75     [
76         "locationquantityavailable",
77         "greaterthan",
78         0
79     ],
80     "and",
81     [
82         "internalid",
83         "noneof",
84         "@NONE@"
85     ],
86     "and",
87     [
88         "internalid",
89         "noneof",
90         "@NONE@"
91     ],
92     "and",
93     [
94         "internalid",
95         "noneof",
96         "@NONE@"
97     ]
98 ],
99 "map": {
100     "id": "formulatext:item-'||{internalid}||'-'||{inventorylocation.internalid}||'--'",
101     "label": "formulatext:nvl({displayname}, {name})",
102     "item": {
103         "id": "internalid",
104         "label": "formulatext:nvl({displayname}, {name})"
105     },
106     "location": {
107         "id": "inventorylocation",
108         "label": "inventorylocation#"
109     },
110     "available": "locationquantityavailable"
111 }
112 },
113 "inventorynumber": false,
114 "inventorynumberbinonhand": false,
115 "binnumber": false,
116 "binonhand": false
117 }
118 },
119 "kit": {
120     "uri": "kit",
121     "type": "datalist",
122     "options": {
123         "all": true,
124         "record": "item",
125         "filters": [
126             [
127                 "isinactive",
128                 "is",
129                 "F"
130             ],
131             "and",
132             [
133                 "type",
134                 "anyof",
135                 [

```

```

136         "Kit"
137     ],
138     "and",
139     [
140         "custitem_nx_show_on_mobile",
141         "is",
142         "T"
143     ]
144 ],
145 ],
146 "map": {
147     "id": "**formulatext:item-'||'{internalid}",
148     "item": {
149         "id": "internalid",
150         "label": "formulatext:nvl({displayname}, {name})"
151     },
152     "components": [
153         {
154             "id": "formulatext:item-'||'{memberitem.internalid}",
155             "item": {
156                 "id": "memberitem",
157                 "label": "formulatext:nvl({memberitem.displayname}, {memberitem.name})"
158             },
159             "quantity": "memberquantity",
160             "type": "memberitem.type"
161         }
162     ]
163 }
164 },
165 },
166 "orderable": {
167     "uri": "orderable",
168     "type": "datalist",
169     "options": {
170         "sort": "label",
171         "subtotal": {
172             "id": "-2",
173             "label": "Subtotal",
174             "description": "",
175             "min": 0
176         },
177         "location": {
178             "record": "item",
179             "filters": [
180                 [
181                     "isinactive",
182                     "is",
183                     "F"
184                 ],
185                 "and",
186                 [
187                     [
188                         "type",
189                         "is",
190                         "Discount"
191                     ],
192                     "or",
193                     [
194                         "custitem_nx_show_on_mobile",
195                         "is",
196                         "T"
197                     ]
198                 ]
199             ],
200             "map": {
201                 "id": "internalid",
202                 "label": "formulatext:nvl({displayname}, {name})",
203                 "description": "salesdescription",
204                 "min": "formulatext:nvl({minimumquantity}, 1)"
205             }
206         }
207     }
208 },

```

```

209 "receivable": {
210   "uri": "receivable",
211   "type": "datalist",
212   "options": {
213     "sort": "id",
214     "transferpricecostingfalse": {
215       "record": "transferorder",
216       "filters": [
217         [
218           "transferlocation",
219           "is",
220           "${ options.location || user.location }"
221         ],
222         "and",
223         [
224           "status",
225           "anyof",
226           [
227             "TrnfrOrd:F",
228             "TrnfrOrd:E"
229           ]
230         ],
231         "and",
232         [
233           "formulanumeric:nvl({transferorderquantityshipped},0)",
234           "greaterthan",
235           "0"
236         ],
237         "and",
238         [
239           "mainline",
240           "is",
241           "F"
242         ],
243         "and",
244         [
245           "istransferpricecosting",
246           "is",
247           "F"
248         ]
249       ],
250     },
251     "map": {
252       "id": "internalid",
253       "label": "formulatext:'Transfer Order #'||{trandid}",
254       "item": {
255         "id": "item",
256         "label": "#item"
257       },
258       "quantity": "transferorderquantityshipped",
259       "transferorder": "internalid"
260     },
261     "transferpricecostingtrue": {
262       "record": "itemfulfillment",
263       "filters": [
264         [
265           "createdfrom.transferlocation",
266           "is",
267           "${ options.location || user.location }"
268         ],
269         "and",
270         [
271           "createdfrom.status",
272           "anyof",
273           [
274             "TrnfrOrd:F",
275             "TrnfrOrd:E"
276           ]
277         ],
278         "and",
279         [
280           "formulatext:case when {account} is null and lower({item.type.id}) not in ('taxitem', 'taxgroup', 'shipitem') then
'T' else 'F' end",

```

```

281         "is",
282         "T"
283     ],
284     "and",
285     [
286         "createdfrom.istransferpricecosting",
287         "is",
288         "T"
289     ],
290     "and",
291     [
292         "createdfrom.recordtype",
293         "is",
294         "transferorder"
295     ],
296     "and",
297     [
298         "internalid",
299         "noneof",
300         {
301             "array": true,
302             "default": "@NONE@",
303             "received": {
304                 "record": "itemreceipt",
305                 "filters": [
306                     [
307                         "createdfrom.transferlocation",
308                         "is",
309                         "${ options.location || user.location }"
310                     ],
311                     "and",
312                     [
313                         "createdfrom.status",
314                         "anyof",
315                         [
316                             "TrnfrOrd:F",
317                             "TrnfrOrd:E"
318                         ]
319                     ],
320                     "and",
321                     [
322                         "createdfrom.recordtype",
323                         "is",
324                         "transferorder"
325                     ],
326                     "and",
327                     [
328                         "appliedtotransaction.recordtype",
329                         "is",
330                         "itemfulfillment"
331                     ]
332                 ],
333                 "map": "appliedtotransaction"
334             }
335         }
336     ],
337 ],
338 "map": {
339     "id": "formulatext:{createdfrom.id}||'-'||{internalid}",
340     "label": "formulatext:'Transfer Order #'||{createdfrom.tranid}||' - Item Fulfillment #'||{tranid}",
341     "item": {
342         "id": "item",
343         "label": "#item"
344     },
345     "quantity": "quantity",
346     "transferorder": "createdfrom",
347     "itemfulfillment": "internalid"
348 }
349 }
350 }
351 }
352 }
353 }

```

354 | }

notes

Type	Description
Object	Resource that allows the user to create notes against the current event.

Default

```

1  {
2    "notes": {
3      "label": "Notes",
4      "icon": "comment",
5      "element": {
6        "title": {
7          "type": "text",
8          "label": "Title",
9          "class": "el-12",
10         "required": true,
11         "column": 1
12       },
13       "body": {
14         "type": "richtext",
15         "label": "Message",
16         "class": "el-12",
17         "required": true
18       },
19       "date": {
20         "type": "date",
21         "label": "Date",
22         "value": "${ event.date }",
23         "title": true,
24         "column": 2,
25         "hidden": true
26       }
27     },
28     "article": {
29       "record": "note",
30       "filters": [
31         "internalid",
32         "anyof",
33         {
34           "array": true,
35           "default": "@NONE@",
36           "event": {
37             "record": "${ event.record }",
38             "filters": [
39               [
40                 "internalid",
41                 "anyof",
42                 "${ event.internalid }"
43               ],
44               "and",
45               [
46                 "usernotes.author",
47                 "anyof",
48                 "${ user.internalid }"
49               ]
50             ],
51             "map": "usernotes.internalid"
52           }
53         }
54       ],
55       "filterby": {
56         "asset": "${ options.asset || event.asset }"
57       },
58       "map": {
59         "date": "notedate|",

```

```
60     "author": "author",
61     "title": "title",
62     "body": "note",
63     "asset": "custrecord_nx_asset"
64   },
65   "idempotencyField": "custrecord_nx_note_idempotency_key",
66   "defaults": {
67     "author": "${ user.internalid }",
68     "activity": "${ event.internalid }",
69     "asset": "${ options.asset || event.asset }"
70   }
71 }
72 }
73 }
```

onsite

Type	Description
Number	Distance in kilometers that a Resource is considered on site for an Event.

Default

```
1 {
2   "onsite": 0.5
3 }
```

order

Type	Description
—	Order disabled when the order is pending receipt

Default

```
1 {
2   "order": {
3     "label": "Order",
4     "hidden": false,
5     "icon": "shoppingcart",
6     "element": {
7       "trandid": {
8         "type": "text",
9         "label": "Transaction",
10        "hidden": true,
11        "title": true,
12        "column": 1
13      },
14      "location": {
15        "type": "select",
16        "label": "From",
17        "class": "el-9",
18        "required": true,
19        "column": 2,
20        "options": {
21          "record": "location",
22          "filters": [
23            [
24              "internalid",
25              "noneof",
26              "${ user.location }"
27            ],
28            "and",
29            [
30              "subsidiary",
```

```

31         "anyof",
32         "${ user.subsidiary }"
33     ]
34 },
35     "map": {
36         "id": "internalid",
37         "label": "name",
38         "selected": "formulatext:case when {internalid} = '${ user.warehouse }' then 'A' end"
39     }
40 },
41 },
42 "items": {
43     "type": "table",
44     "label": "Items",
45     "required": true
46 },
47 "item": {
48     "type": "select",
49     "label": "Item",
50     "class": "el-9",
51     "search": true,
52     "required": true,
53     "column": 1,
54     "options": "orderable.options",
55     "parent": "items"
56 },
57 "quantity": {
58     "type": "integer",
59     "label": "Quantity",
60     "class": "el-3",
61     "min": 1,
62     "step": 1,
63     "required": true,
64     "column": 2,
65     "parent": "items"
66 },
67 "status": {
68     "type": "text",
69     "label": "Status",
70     "class": "el-12",
71     "readonly": true,
72     "column": 2,
73     "value": "Open"
74 }
75 },
76 "article": {
77     "extend": "models/transaction",
78     "record": "transferorder",
79     "filters": [
80         [
81             [
82                 "custbody_nx_task",
83                 "anyof",
84                 "${ event.internalid }"
85             ],
86             "or",
87             [
88                 "custbody_nx_projecttask",
89                 "anyof",
90                 "${ event.internalid }"
91             ]
92         ],
93         "and",
94         [
95             "requestor.internalid",
96             "is",
97             "${ user.internalid }"
98         ],
99         "and",
100         [
101             "transferlocation",
102             "is",
103             "${ user.location }"

```



```
104     ]
105   },
106   "map": {
107     "id": "**formulatext:case when {line} > 0 and {transferorderitemline} is null then {internalid} end|internalid",
108     "tranid": "tranid|",
109     "status": "status#|",
110     "location": {
111       "id": "=location",
112       "label": "#location|"
113     },
114     "readonly": "formulatext:case when {status.id} like 'pendingReceipt%' then 'T' else 'F' end",
115     "items": [
116       {
117         "line": "line|item.line",
118         "item": {
119           "id": "=item|item.item",
120           "label": "#item|"
121         },
122         "quantity": "formulanumeric:abs({quantity})|item.quantity"
123       }
124     ]
125   },
126   "defaults": {
127     "subsidiary": "${ user.subsidiary }",
128     "employee": "${ user.internalid }",
129     "transferlocation": "${ user.location }",
130     "trandate": "${ event.date }",
131     "custbody_nx_customer": "${ event.customer }",
132     "custbody_nx_task": "${ event.crmtask }",
133     "custbody_nx_projecttask": "${ event.projecttask }",
134     "custbody_nx_case": "${ event.supportcase }"
135   }
136 }
137 }
138 }
```

quote

Type	Description
—	Quotes

Default

```
1 {
2   "quote": {
3     "label": "Quote",
4     "icon": "quote",
5     "element": {
6       "items": {
7         "type": "table",
8         "label": "Items",
9         "required": true
10      },
11      "item": {
12        "type": "select",
13        "label": "Item",
14        "class": "col-0 col-sm el-9",
15        "required": true,
16        "search": true,
17        "parent": "items",
18        "column": 1,
19        "options": "orderable.options"
20      },
21      "quantity": {
22        "type": "integer",
23        "label": "Qty",
24        "class": "el-3",
25        "min": "item.value ? orderable.options.filter(o=>{ return o.id == item.value.id })[0].min : undefined",
```

```

26     "value": 1,
27     "required": true,
28     "parent": "items",
29     "column": 3
30 },
31 "description": {
32     "type": "text",
33     "label": "Description",
34     "parent": "items",
35     "column": 2,
36     "value": "item.value ? orderable.options.filter(o=>{ return o.id == item.value.id })[0].description : ''"
37 },
38 "amount": {
39     "type": "currency",
40     "label": "Amount",
41     "hidden": true,
42     "parent": "items",
43     "column": 4
44 },
45 "taskcol": {
46     "type": "hidden",
47     "value": "${ event.crmtask }",
48     "parent": "items"
49 },
50 "projecttaskcol": {
51     "type": "hidden",
52     "value": "${ event.projecttask }",
53     "parent": "items"
54 },
55 "assetcol": {
56     "type": "hidden",
57     "value": "${ event.asset }",
58     "parent": "items"
59 },
60 "total": {
61     "type": "currency",
62     "label": "Total",
63     "class": "el-12",
64     "readonly": true,
65     "column": 4
66 },
67 "purchaseorder": {
68     "type": "text",
69     "label": "PO#",
70     "class": "el-12",
71     "maxlength": 45
72 },
73 "status": {
74     "type": "text",
75     "label": "Status",
76     "class": "el-12",
77     "readonly": true,
78     "column": 2,
79     "value": "Open"
80 },
81 "tranid": {
82     "type": "text",
83     "label": "Transaction",
84     "hidden": true,
85     "title": true,
86     "column": 1
87 },
88 "task": {
89     "type": "text",
90     "value": "${ event.internalid }",
91     "hidden": true
92 },
93 "sendemail": {
94     "type": "checkbox",
95     "label": "Send Email",
96     "class": "el-12"
97 },
98 "emailto": {

```

```

99     "type": "text",
100     "label": "Emails",
101     "class": "el-12",
102     "required": true,
103     "value": "${ event.email }",
104     "pattern": "((^|;)[a-zA-Z0-9._%+-]+@[a-zA-Z0-9.-]+.[a-zA-Z]{2,3})+$"
105   },
106   "apply": {
107     "type": "checkbox",
108     "label": "Apply to current job",
109     "class": "el-12",
110     "column": 3
111   },
112   "signature": {
113     "type": "signature",
114     "label": "Sign to create Sales Order"
115   }
116 },
117 "article": {
118   "extend": "models/transaction",
119   "record": "estimate",
120   "filters": [
121     [
122       "recordtype",
123       "is",
124       "estimate"
125     ],
126     "and",
127     [
128       [
129         "custbody_nx_task",
130         "is",
131         "${ event.internalid }"
132       ],
133       "or",
134       [
135         "custbody_nx_projecttask",
136         "is",
137         "${ event.internalid }"
138       ],
139       "or",
140       [
141         "formulatext:case when ({job.internalid} = '${ event.job }') and {custbody_nx_case.internalid} = '${ event.support
case }' then 'T' else 'F' end",
142         "is",
143         "T"
144       ]
145     ]
146   ],
147   "map": {
148     "id": "*formulatext:case when lower({item.type.id}) not in ('taxitem', 'taxgroup', 'shipitem') then {internalid} end|inter
nalid",
149     "readonly": "formulatext:case when {status.id} like 'processed' then 'T' else 'F' end",
150     "tranid": "tranid|",
151     "status": "status|",
152     "purchaseorder": "otherrefnum",
153     "total": "total|",
154     "apply": "formulatext:case when {job.internalid} = '${ event.job }' then 'T' else 'F' end",
155     "signature": "custbody_nx_customer_signature",
156     "sendemail": "tobeemailed",
157     "emailto": "email",
158     "items": [
159       {
160         "line": "line|item.line",
161         "description": "memo|item.description",
162         "item": {
163           "id": "=item|item.item",
164           "label": "#item|"
165         },
166         "quantity": "formulatext:nvl({quantity},1)|item.quantity",
167         "amount": "amount|",
168         "readonly": "formulatext:case when ({custcol_nx_task.internalid} = '${ event.internalid }' or {custcol_nx_project
task.internalid} = '${ event.internalid }') then 'F' else 'T' end",

```

```

169         "taskcol": "custcol_nx_task|item.custcol_nx_task",
170         "projecttaskcol": "custcol_nx_projecttask|item.custcol_nx_projecttask",
171         "assetcol": "custcol_nx_asset|item.custcol_nx_asset"
172     }
173 }
174 },
175 "defaults": {
176     "customer": "${ event.customer }",
177     "trandate": "${ event.date }",
178     "custbody_nx_customer": "${ event.customer }",
179     "custbody_nx_task": "${ event.crmtask }",
180     "custbody_nx_projecttask": "${ event.projecttask }"
181 },
182 "initialize": {
183     "copy": "copy",
184     "createdfrom": "transform",
185     "createdfromtype": "transformtype",
186     "recordmode": "recordmode",
187     "customform": "customform",
188     "subsidiary": "subsidiary"
189 },
190 "syncentity": true
191 }
192 }
193 }

```

receive

Type	Description
—	Receive No bin selection

Default

```

1  {
2  "receive": {
3      "label": "Receive",
4      "hidden": false,
5      "icon": "inbox",
6      "element": {
7          "trandid": {
8              "type": "text",
9              "label": "Transaction",
10             "hidden": true,
11             "title": true,
12             "column": 1
13         },
14         "createdfrom": {
15             "label": "Order",
16             "type": "select",
17             "required": true,
18             "search": true,
19             "column": 2,
20             "readonly": "!!trandid.value",
21             "options": "_.uniq(receivable.options, o=>{return o.id})",
22             "autoselect": false
23         },
24         "transferorder": {
25             "type": "text",
26             "label": "Transfer Order Id",
27             "hidden": true,
28             "value": "createdfrom.value ? (receivable.options.filter(o => { return o.id == createdfrom.value.id })[0] || {}).transfer
order : null"
29         },
30         "itemfulfillment": {
31             "type": "text",
32             "label": "Item Fulfillment Id",
33             "hidden": true,

```

```

34      "value": "createdfrom.value ? (receivable.options.filter(o => { return o.id == createdfrom.value.id }))[0] || {}").itemful
fillment : null"
35    },
36    "items": {
37      "type": "table",
38      "label": "Items",
39      "readonly": true,
40      "value": "createdfrom.value ? receivable.options.filter(o => { return o.id == createdfrom.value.id }).map(o => ({ item:
o.item, quantity: o.quantity })) : []"
41    },
42    "item": {
43      "type": "select",
44      "label": "Item",
45      "class": "el-9",
46      "column": 1,
47      "parent": "items"
48    },
49    "quantity": {
50      "type": "integer",
51      "label": "Quantity",
52      "class": "el-3",
53      "step": 1,
54      "column": 2,
55      "parent": "items"
56    }
57  },
58  "article": {
59    "extend": "models/transaction",
60    "record": "itemreceipt",
61    "filters": [
62      [
63        [
64          "custbody_nx_task",
65          "anyof",
66          "${ event.internalid }"
67        ],
68        "or",
69        [
70          "custbody_nx_projecttask",
71          "anyof",
72          "${ event.internalid }"
73        ]
74      ],
75      "and",
76      [
77        "location",
78        "is",
79        "${ user.location }"
80      ]
81    ],
82    "map": {
83      "id": "**formulatext:case when ({line} > 0 and {quantity} > 0) then {internalid} end|internalid",
84      "tranid": "tranid|",
85      "status": "status#|",
86      "createdfrom": {
87        "id": "=createdfrom|",
88        "label": "#createdfrom|"
89      },
90      "items": [
91        {
92          "quantity": "quantity|item.quantity",
93          "item": {
94            "id": "=item|item.item",
95            "label": "#item|"
96          }
97        }
98      ]
99    }
100  }
101 }
102 }

```

return

Type	Description
—	Return Transfer orders transferring from the user location

Default

```

1  {
2    "return": {
3      "label": "Return",
4      "hidden": false,
5      "icon": "outbox",
6      "element": {
7        "tranid": {
8          "type": "text",
9          "label": "Transaction",
10         "hidden": true,
11         "title": true,
12         "column": 1
13       },
14       "transferlocation": {
15         "type": "select",
16         "label": "To",
17         "required": true,
18         "options": {
19           "record": "location",
20           "filters": [
21             [
22               "internalid",
23               "noneof",
24               "${ user.location }"
25             ],
26             "and",
27             [
28               "subsidiary",
29               "anyof",
30               "${ user.subsidiary }"
31             ]
32           ],
33           "map": {
34             "id": "internalid",
35             "label": "name",
36             "selected": "formulatext:case when {internalid} = '${ user.warehouse }' then 'A' end"
37           }
38         },
39       },
40       "items": {
41         "type": "table",
42         "label": "Items",
43         "required": true
44       },
45       "item": {
46         "label": "Item",
47         "parent": "items",
48         "type": "select",
49         "class": "col-sm el-9",
50         "required": true,
51         "search": true,
52         "barcode": true,
53         "column": 1,
54         "options": "_.uniq(consumable.options.filter(o=>{return o.location && (o.location.id == item.location)}).map(o=>{return o.item}), o=>{return o.id})",
55         "location": "${ user.location }"
56       },
57       "quantity": {
58         "type": "integer",
59         "label": "Qty",
60         "class": "el-3",
61         "min": 1,

```

```

62     "step": 1,
63     "value": 1,
64     "required": true,
65     "parent": "items",
66     "column": 5
67   },
68   "bin": {
69     "type": "select",
70     "label": "Bin",
71     "class": "col-xs-0 col-sm-0 col-md-0",
72     "parent": "items",
73     "hidden": "!(bin.value || bin.options.length)",
74     "options": "item.value ? _.uniq(consumable.options.filter(o=>{ return (o.item.id == item.value.id) && o.bin && o.location
&& (o.location.id == item.location) })).map(o=>{return o.bin}), o=>{return o.id}) : []"
75   },
76   "lot": {
77     "type": "select",
78     "label": "Lot",
79     "class": "col-xs-0 col-sm-0 col-md-0",
80     "parent": "items",
81     "hidden": "!(lot.value || lot.options.length)",
82     "options": "item.value ? _.uniq(consumable.options.filter(o=>{ return (o.item.id == item.value.id) && o.lot && o.location
&& (o.location.id == item.location) && ((o.bin && o.bin.id) == (bin.value && bin.value.id)) })).map(o=>{return o.lot}), o=>{return
o.id}) : []"
83   },
84   "serial": {
85     "type": "select",
86     "multiple": true,
87     "search": true,
88     "barcode": true,
89     "label": "Serial",
90     "parent": "items",
91     "class": "col-xs-0",
92     "column": 3,
93     "hidden": "!(serial.value.length || serial.options.length)",
94     "options": "item.value ? _.uniq(consumable.options.filter(o=>{ return (o.item.id == item.value.id) && o.serial && o.loca
tion && (o.location.id == item.location) && ((o.bin && o.bin.id) == (bin.value && bin.value.id)) })).map(o=>{return o.serial}),
o=>{return o.id}) : []"
95   },
96   "status": {
97     "type": "text",
98     "label": "Status",
99     "class": "el-12",
100    "readonly": true,
101    "column": 2,
102    "value": "Open"
103  },
104 },
105 "article": {
106   "extend": "models/transaction",
107   "record": "transferorder",
108   "filters": [
109     [
110       [
111         "custbody_nx_task",
112         "anyof",
113         "${ event.internalid }"
114       ],
115       "or",
116       [
117         "custbody_nx_projecttask",
118         "anyof",
119         "${ event.internalid }"
120       ]
121     ],
122     "and",
123     [
124       "requestor.internalid",
125       "is",
126       "${ user.internalid }"
127     ],
128     "and",
129     [

```

```

130     "location",
131     "anyof",
132     "${ user.location }"
133   ]
134 },
135   "map": {
136     "id": "**formulatext:case when {line} > 0 and {transferorderitemline} is null then {internalid} end|internalid",
137     "tranid": "tranid|",
138     "status": "status#|",
139     "transferlocation": {
140       "id": "=transferlocation",
141       "label": "#transferlocation|"
142     },
143     "items": [
144       {
145         "line": "line|item.line",
146         "item": {
147           "id": "=item|item.item",
148           "label": "#item|"
149         },
150         "quantity": "formulanumeric:abs({quantity})|item.quantity"
151       }
152     ]
153   },
154   "defaults": {
155     "orderstatus": "B",
156     "subsidiary": "${ user.subsidiary }",
157     "employee": "${ user.internalid }",
158     "location": "${ user.location }",
159     "trandate": "${ event.date }",
160     "custbody_nx_customer": "${ event.customer }",
161     "custbody_nx_task": "${ event.crmtask }",
162     "custbody_nx_projecttask": "${ event.projecttask }",
163     "custbody_nx_case": "${ event.supportcase }"
164   },
165   "fulfill": true,
166   "inventory": "items"
167 }
168 }
169 }

```

salesorder

Sales Order resource allows users to view or edit Sales Orders in the field. Default configuration shows the first Sales Order found on the current project. Item group header and footer lines and those not created from this task on the mobile are readonly. Lines that are added or edited from the current task that are fulfillable will automatically be fulfilled on save.

Known Issues

- Deleting sales order lines in or above item groups will cause a syncing error.
- Multiple users concurrently editing the Sales Order could overwrite changes.
- Accounts with basic inventory will fulfill Bin items but not show on the Sales Order line.
- Maximum quantity not enforced based on item availability at selected location. This could put the item in backorder or cause a syncing error with inventory detail.
- Does not show tax or shipping line.
- Does not apply billing rule logic.

Default

```

1 {
2   "salesorder": {
3     "label": "Sales Order",
4     "icon": "wrench",
5     "max": 1,
6     "element": {

```



```

7      "items": {
8        "type": "table",
9        "label": "Items",
10       "required": true
11     },
12     "item": {
13       "label": "Item",
14       "parent": "items",
15       "type": "select",
16       "class": "col-sm el-9",
17       "required": true,
18       "search": true,
19       "barcode": true,
20       "column": 1,
21       "options": "_.uniq(consumable.options.concat(kit.options).map(o=>{return {...o.item, barcode: o.barcode}}), o=>{return
o.id})",
22       "component": "var kititem = item.value && kit.options.filter(o=>{return o.item.id == item.value.id })[0]; return kititem ?
kititem.components : []",
23       "stocked": "item.value ? (item.component.length ? item.component.filter(o=>{ return ~['InvPart','Assembly'].index
Of(o.type) }) .map(o=>{ return o.item.id }) : [item.value.id]) : []",
24       "assignment": "consumable.options.filter(o=>{ return o.location && ~item.stocked.indexOf(o.item.id)})",
25       "location": "var locations = {}; item.assignment.map(o=>{ var id = o.location.id; if (!locations[id]) locations[id] =
{ location: o.location, stock: [] }; if (!~locations[id].stock.indexOf(o.item.id)) locations[id].stock.push(o.item.id); return
o }); return locations"
26     },
27     "quantity": {
28       "type": "integer",
29       "label": "Qty",
30       "class": "el-3",
31       "min": 1,
32       "step": 1,
33       "value": 1,
34       "required": true,
35       "parent": "items",
36       "column": 5
37     },
38     "location": {
39       "type": "select",
40       "label": "Location",
41       "parent": "items",
42       "class": "col-xs-0 col-sm-0",
43       "column": 2,
44       "hidden": "!(location.value || location.options.length)",
45       "options": "Object.keys(item.location).filter(id=>{ return item.location[id].stock.length == item.s
tocked.length }).map(id=>{ return item.location[id].location })"
46     },
47     "bin": {
48       "type": "select",
49       "label": "Bin",
50       "class": "col-xs-0 col-sm-0 col-md-0",
51       "parent": "items",
52       "hidden": "!(bin.value || bin.options.length)",
53       "options": "(item.value && location.value) ? _.uniq(consumable.options.filter(o=>{ return (o.item.id == item.value.id) &&
o.bin && o.location && (o.location.id == location.value.id) }).map(o=>{return o.bin}), o=>{return o.id}) : []"
54     },
55     "lot": {
56       "type": "select",
57       "label": "Lot",
58       "class": "col-xs-0 col-sm-0 col-md-0",
59       "parent": "items",
60       "hidden": "!(lot.value || lot.options.length)",
61       "options": "(item.value && location.value) ? _.uniq(consumable.options.filter(o=>{ return (o.item.id == item.value.id) &&
o.lot && o.location && (o.location.id == location.value.id) && (o.bin && o.bin.id == (bin.value && bin.value.id) }) .map(o=>{re
turn o.lot}), o=>{return o.id}) : []"
62     },
63     "serial": {
64       "type": "select",
65       "multiple": true,
66       "search": true,
67       "barcode": true,
68       "label": "Serial",
69       "parent": "items",
70       "class": "col-xs-0",

```

```

71     "column": 3,
72     "hidden": "!(serial.value.length || serial.options.length)",
73     "options": "(item.value && location.value) ? _.uniq(consumable.options.filter(o=>{ return (o.item.id == item.val
ue.id) && o.serial && o.location && (o.location.id == location.value.id) && ((o.bin && o.bin.id) == (bin.value && bin.val
ue.id)) }).map(o=>{return o.serial}), o=>{return o.id}) : []"
74   },
75   "amount": {
76     "type": "currency",
77     "label": "Amount",
78     "class": "col-right",
79     "hidden": true,
80     "parent": "items",
81     "column": 6
82   },
83   "task": {
84     "type": "hidden",
85     "value": "${ event.crmtask }",
86     "parent": "items"
87   },
88   "projecttask": {
89     "type": "hidden",
90     "value": "${ event.projecttask }",
91     "parent": "items"
92   },
93   "asset": {
94     "type": "hidden",
95     "value": "${ event.asset }",
96     "parent": "items"
97   },
98   "total": {
99     "type": "currency",
100    "label": "Total",
101    "class": "el-12",
102    "readonly": true,
103    "column": 4
104  },
105  "status": {
106    "type": "text",
107    "label": "Status",
108    "class": "el-12",
109    "readonly": true,
110    "column": 2,
111    "value": "Pending Fulfillment"
112  },
113  "trandid": {
114    "type": "text",
115    "label": "Transaction",
116    "hidden": true,
117    "title": true
118  }
119 },
120 "article": {
121   "extend": "models/transaction",
122   "record": "salesorder",
123   "filters": "${ event.company && event.company != event.customer ? ['job.internalid', 'anyof', event.company] :
['custbody_nx_task', 'anyof', event.crmtask || 0] }",
124   "map": {
125     "id": "**formulatext:case when lower({item.type.id}) not in ('taxitem', 'taxgroup', 'shipitem') then {internalid} end|inter
nvalid",
126     "project": "job.internalid|entity",
127     "customer": "custbody_nx_customer",
128     "trandid": "trandid|",
129     "status": "status#|",
130     "total": "total|",
131     "items": [
132       {
133         "line": "line|item.line",
134         "task": "custcol_nx_task|item.custcol_nx_task",
135         "asset": "custcol_nx_asset|item.custcol_nx_asset",
136         "readonly": "formulatext:case when {item.type.id} like '%Group%' then 'T' when ({custcol_nx_task.id} = '${ event.inter
nvalid }' or {custcol_nx_projecttask.id} = '${ event.internalid }') then 'F' else 'T' end",
137         "item": {
138           "id": "=item|item.item",

```

```

139         "label": "item#"
140     },
141     "location": {
142         "id": "=location|item.location",
143         "label": "formulatext:regexp_replace({location}, '.* : ')"
144     },
145     "quantity": "quantity|item.quantity",
146     "amount": "amount|"
147 }
148 ]
149 },
150 "defaults": {
151     "customer": "${ event.customer }",
152     "project": "${ event.company == event.customer ? null : event.company }",
153     "trandate": "${ event.date }",
154     "custbody_nx_task": "${ event.crmtask }",
155     "custbody_nx_projecttask": "${ event.projecttask }",
156     "custbody_nx_case": "${ event.supportcase }",
157     "custbody_nx_asset": "${ event.asset }",
158     "orderstatus": "B",
159     "iscrosssubtransaction": true
160 },
161 "initialize": {
162     "copy": "copy",
163     "createdfrom": "transform",
164     "createdfromtype": "transformtype",
165     "recordmode": "recordmode",
166     "customform": "customform",
167     "subsidiary": "subsidiary"
168 },
169 "syncentity": true,
170 "fulfill": true,
171 "inventory": "items"
172 }
173 }
174 }

```

times

Type	Description
Object	Resource that allows the user to log time.

Default

```

1 {
2   "times": {
3     "label": "Time",
4     "icon": "clock",
5     "element": {
6       "item": {
7         "type": "select",
8         "label": "Item",
9         "class": "el-6",
10        "search": true,
11        "required": true,
12        "column": 1,
13        "options": {
14          "sort": "label",
15          "serviceitems": {
16            "record": "item",
17            "filters": [
18              [
19                "isinactive",
20                "is",
21                "F"
22              ],
23              "and",
24              [

```

```

25         "type",
26         "anyof",
27         "Service"
28     ],
29     "and",
30     [
31         "custitem_nx_show_on_mobile",
32         "is",
33         "T"
34     ]
35 ],
36 "map": {
37     "id": "internalid",
38     "label": "name"
39 }
40 }
41 }
42 },
43 "date": {
44     "type": "date",
45     "label": "Date",
46     "class": "el-3",
47     "hidden": "${ event.crmtask }",
48     "column": 2,
49     "value": "${ event.date }"
50 },
51 "duration": {
52     "type": "float",
53     "label": "Hours",
54     "class": "el-3",
55     "min": 0.1,
56     "max": 24,
57     "step": 0.1,
58     "column": 3,
59     "required": true
60 }
61 },
62 "article": {
63     "record": "timebill",
64     "filters": [
65         [
66             "${ event.record }.internalid",
67             "anyof",
68             "${ event.internalid }"
69         ],
70         "and",
71         [
72             "employee",
73             "anyof",
74             "${ user.internalid }"
75         ]
76     ],
77     "filterby": {
78         "asset": "${ options.asset || event.asset }"
79     },
80     "map": {
81         "duration": "durationdecimal|hours",
82         "item": {
83             "id": "=item.internalid|item",
84             "label": "item.name|"
85         },
86         "date": "date|trandate",
87         "asset": "custcol_nx_asset"
88     },
89     "idempotencyField": "custcol_nx_idempotency_key",
90     "defaults": {
91         "casetaskevent": "${ event.internalid }",
92         "custcol_nx_task": "${ event.crmtask }",
93         "custcol_nx_projecttask": "${ event.projecttask }",
94         "asset": "${ options.asset || event.asset }",
95         "customer": "${ event.company }",
96         "employee": "${ user.internalid }"
97     }

```

```

98 |   }
99 |   }
100 | }

```

user

Type	Description
Object	Records in NetSuite that are considered Mobile Users. This is a hash of Model definitions that relate a user to a record. Any model properties or functions can be defined including the sync function.

Properties

Property	Type	Description
record	String	Record type
filters	Filterexpression	Search filters to apply to the record type
map	Object	Field map of search columns and fields. These attributes will be available in definitions for resources using the template tag {user.*}. They are also used to match on resource rule lookups.
map.id	String	Must be in the pattern of "{recordtype}-{internalid}".
map.label	String	Name to show for the User
map.email	String	Email address to identify the User for Authentication
map.password	String	Encrypted password to use for Authentication when the User does not have NetSuite access.
map.latitude	Number	Latitude of the user.
map.longitude	Number	Longitude of the user.
map.language	String	Language preference for the User in NetSuite format language values. Requests for the User, Event, it's Resources, and its Articles will be run in this timezone.
map.*	*	Optional additional attributes can be added to make available for resource lookups and variables.
resources	Array.<object>	Set of rules to lookup which Resources to load for the user. Properties added to the rules will filter the attribute on the user.
resources[].resources	Array.<string>	Resource ids to load for the containing rule.

Default

```

1 | {
2 |   "user": {
3 |     "employee": {
4 |       "record": "employee",
5 |       "filters": [
6 |         [
7 |           "isinactive",
8 |           "is",
9 |           "F"
10 |         ],

```

```
11     "and",
12     [
13       [
14         "custentity_nx_mobile_user",
15         "is",
16         "T"
17       ],
18       "or",
19       [
20         "formulatext:case when regexp_like(email), '${ license.administrator }', 'i') then 'T' else 'F' end",
21         "is",
22         "T"
23       ]
24     ],
25   ],
26   "map": {
27     "label": "formulatext:nvl(trim(trim(trim({firstname}))||' '||{middlename}))||' '||{lastname}), {entityid})",
28     "email": "email|",
29     "password": "custentity_nx_password|",
30     "giveaccess": "giveaccess|",
31     "latitude": "custentity_nx_latitude",
32     "longitude": "custentity_nx_longitude",
33     "language": "formulatext:''",
34     "image": "formulatext:nvl2({image}, '${ url }file/'||{image.id}, '')",
35     "location": "formulatext:nvl({custentity_nx_location.id}, 0)",
36     "warehouse": "formulatext:nvl({custentity_nx_warehouse.id}, 0)",
37     "subsidiary": "subsidiary|",
38     "createevent": "${ server.addable }"
39   },
40   "resources": [
41     {
42       "resources": [
43         "inventory"
44       ]
45     }
46   ]
47 }
48 }
49 }
```

routes/scheduler

Scheduler web app server

Members

administrators

Type	Description
Array.<Number>	Roles of editors

Default

```
1 {
2   "administrators": [
3     3
4   ]
5 }
```

assignedpanel

Type	Description
Array.<Object>	Assigned events filtering and sorting options.

Default

```

1  {
2    "assignedpanel": {
3      "filter": {
4        "region": {
5          "label": "Region",
6          "column": "region",
7          "options": {
8            "record": "customlist_nx_region",
9            "map": {
10             "id": "internalid",
11             "label": "name"
12           }
13         }
14       },
15       "type": {
16         "label": "Type",
17         "column": "type",
18         "options": {
19           "record": "customrecord_nx_task_type",
20           "map": {
21             "id": "internalid",
22             "label": "name"
23           }
24         }
25       },
26       "skill": {
27         "label": "Skill",
28         "column": "skill",
29         "options": {
30           "record": "customrecord_nx_skill",
31           "map": {
32             "id": "internalid",
33             "label": "name"
34           }
35         }
36       },
37       "allany": true
38     },
39     "priority": {
40       "label": "Priority",
41       "column": "priority",
42       "options": [
43         {
44           "id": "3",
45           "label": "Low"
46         },
47         {
48           "id": "2",
49           "label": "Medium"
50         },
51         {
52           "id": "1",
53           "label": "High"
54         }
55       ]
56     },
57     "status": {
58       "label": "Status",
59       "column": "status",
60       "options": [
61         {
62           "id": "completed",
63           "label": "Completed"
64         }
65       ]
66     }
67   }

```

```

63     },
64     {
65         "id": "inprogress",
66         "label": "In Progress"
67     },
68     {
69         "id": "notstarted",
70         "label": "Not Started"
71     }
72 ]
73 },
74 "booking": {
75     "label": "Booking",
76     "column": "booking",
77     "options": [
78         {
79             "id": "tentative",
80             "label": "Tentative"
81         },
82         {
83             "id": "confirmed",
84             "label": "Confirmed"
85         }
86     ]
87 }
88 },
89 "sort": {
90     "prioritydesc": {
91         "label": "High Priority",
92         "column": "priority",
93         "direction": "asc"
94     },
95     "priorityasc": {
96         "label": "Low Priority",
97         "column": "priority",
98         "direction": "desc"
99     },
100     "startasc": {
101         "label": "Oldest",
102         "column": "startdate",
103         "direction": "asc"
104     },
105     "startdesc": {
106         "label": "Newest",
107         "column": "startdate",
108         "direction": "desc"
109     },
110     "labelasc": {
111         "label": "A-Z",
112         "column": "label",
113         "direction": "asc"
114     },
115     "labeldesc": {
116         "label": "Z-A",
117         "column": "label",
118         "direction": "desc"
119     }
120 }
121 }
122 }

```

calendar

Type	Description
Array.<Object>	Resolvable collection of Resource Calendars. Run time json is viewable here .

Properties

Property	Type	Description
nxworkcalendar	Object	NextService Work Calendar
workcalendar	Object	Advanced Projects Work Calendar

Default

```

1  {
2    "calendar": {
3      "array": true,
4      "nxworkcalendar": {
5        "record": "customrecord_nx_work_calendar",
6        "map": {
7          "id": "**formulatext:'nxworkcalendar-'||{internalid}",
8          "start": "custrecord_nx_work_calendar_start",
9          "hours": "custrecord_nx_work_calendar_hours",
10         "sunday": "custrecord_nx_work_calendar_sunday",
11         "monday": "custrecord_nx_work_calendar_monday",
12         "tuesday": "custrecord_nx_work_calendar_tuesday",
13         "wednesday": "custrecord_nx_work_calendar_wednesday",
14         "thursday": "custrecord_nx_work_calendar_thursday",
15         "friday": "custrecord_nx_work_calendar_friday",
16         "saturday": "custrecord_nx_work_calendar_saturday",
17         "dates": {
18           "date": "=custrecord_nx_work_calendar.custrecord_nx_work_calendar_date[]",
19           "label": "custrecord_nx_work_calendar.name",
20           "icon": "formulatext:'nonworkingday'"
21         }
22       }
23     },
24     "workcalendar": false
25   }
26 }

```

colour

Type	Description
Object	The color options and palette defaults

Default

```

1  {
2    "colour": {
3      "enabled": true,
4      "readonly": false,
5      "default": "priority",
6      "group": {
7        "priority": {
8          "label": "Priority",
9          "column": "priority",
10         "palette": "rainbow",
11         "items": [
12           {
13             "id": "1",
14             "label": "High",
15             "cluster": "1"
16           },
17           {
18             "id": "2",
19             "label": "Medium",
20             "cluster": "2"
21           },
22           {
23             "id": "3",
24             "label": "Low",

```

```

25     "cluster": "3"
26   }
27 ],
28 "eventswatch": true
29 },
30 "status": {
31   "label": "Status",
32   "column": "status",
33   "palette": "cool",
34   "items": [
35     {
36       "id": "notstarted",
37       "label": "Not Started",
38       "swatch": "cornflowerblue",
39       "cluster": "4"
40     },
41     {
42       "id": "travelling",
43       "label": "Travelling",
44       "swatch": "cyanprocess",
45       "cluster": "3"
46     },
47     {
48       "id": "inprogress",
49       "label": "In Progress",
50       "swatch": "inchworm",
51       "cluster": "2"
52     },
53     {
54       "id": "overdue",
55       "label": "Overdue",
56       "swatch": "electricpurple",
57       "cluster": "1"
58     }
59   ],
60   "eventswatch": true
61 },
62 "type": {
63   "label": "Task Type",
64   "column": "type",
65   "palette": "warm",
66   "items": {
67     "record": "customrecord_nx_task_type",
68     "map": {
69       "id": "internalid",
70       "label": "name"
71     }
72   },
73   "eventswatch": true
74 },
75 "casetype": {
76   "label": "Case Type",
77   "column": "casetype",
78   "palette": "contrast",
79   "items": {
80     "record": "customrecord_nx_case_type",
81     "map": {
82       "id": "internalid",
83       "label": "name"
84     }
85   },
86   "eventswatch": true
87 }
88 },
89 "palette": {
90   "rainbow": {
91     "label": "Rainbow",
92     "swatches": [
93       "redpigment",
94       "sizzlingsunrise",
95       "skybluecrayola",
96       "darkorange",
97       "bitterlime",

```

```

98     "shockingpink",
99     "electricviolet",
100    "battleshipgrey"
101  ],
102  },
103  "cool": {
104    "label": "Cool",
105    "swatches": [
106      "cornflowerblue",
107      "viridiangreen",
108      "cyanprocess",
109      "mediumaquamarine",
110      "inchworm",
111      "electricpurple",
112      "electricindigo",
113      "battleshipgrey"
114    ]
115  },
116  "warm": {
117    "label": "Warm",
118    "swatches": [
119      "redpigment",
120      "sizzlingsunrise",
121      "laserlemon",
122      "darkorange",
123      "bitterlime",
124      "shockingpink",
125      "electricviolet",
126      "battleshipgrey"
127    ]
128  },
129  "contrast": {
130    "label": "Contrast",
131    "swatches": [
132      "ultramarine",
133      "celadongreen",
134      "metallicseaweed",
135      "navyblue",
136      "greenryb",
137      "bluevioletcolorwheel",
138      "trypanblue",
139      "onyx"
140    ]
141  }
142 }
143 }
144 }
```

end

Type	Description
Number	The end of service time in hours = 5:00 pm.

Default

```

1  {
2    "end": 17
3  }
```

event

Type	Description
Array.<Object>	Resolvable collection of Events. Run time json is viewable here .

Properties

Property	Type	Description
nonworkingday	Object	NextService Employee Non Working Days
task	Object	CRM tasks
projecttask	Object	Project tasks
resourceallocation	Object	Resource allocations

Default

```

1  {
2    "event": {
3      "array": true,
4      "nonworkingday": {
5        "record": "customrecord_nx_employee_non_working_day",
6        "filters": [
7          [
8            "custrecord_nx_emp_avail_emp.internalid",
9            "anyof",
10           "${ request.parameters.resource }"
11          ],
12          "and",
13          [
14            "custrecord_nx_emp_avail_enddate",
15            "onorafter",
16            "${ request.parameters.start }"
17          ],
18          "and",
19          [
20            "custrecord_nx_emp_avail_startdate",
21            "onorbefore",
22            "${ request.parameters.end }"
23          ]
24        ],
25        "map": {
26          "id": "formulatext:'nonworkingday-|'|{internalid}",
27          "resource": "custrecord_nx_emp_avail_emp",
28          "startdate": "formulatext:to_char({custrecord_nx_emp_avail_startdate},'YYYY-MM-DD')||'T00:00:00'",
29          "enddate": "formulatext:to_char({custrecord_nx_emp_avail_enddate},'YYYY-MM-DD')||'T23:59:59'",
30          "class": "",
31          "swatch": "formulatext:'unavailable'",
32          "label": "name",
33          "title": "name",
34          "region": "custrecord_nx_emp_avail_emp.custentity_nx_region",
35          "editable": false
36        }
37      },
38      "task": {
39        "all": true,
40        "record": "task",
41        "filters": [
42          [
43            [
44              [
45                "assigned",
46                "anyof",
47                "${ request.parameters.resource }"
48              ],
49              "or",
50              [
51                [
52                  "formulatext:{custevent_nx_task_team.id}",
53                  "isnot",
54                  ""
55                ],
56                "and",
57                [

```

```

58         "custevent_nx_task_team",
59         "anyof",
60         "${ request.parameters.resource }"
61     ]
62 ]
63 ],
64 "and",
65 [
66     "startdate",
67     "onorafter",
68     "${ request.parameters.start }"
69 ],
70 "and",
71 [
72     "startdate",
73     "onorbefore",
74     "${ request.parameters.end }"
75 ],
76 "and",
77 [
78     "formulatext:case when '${ user.view }' = '0' or coalesce({case.subsidiary.id}, {job.subsidiary.id}, {company.sub
subsidiary.id}, 0) in (0,${ user.view }) then 'T' else 'F' end",
79     "is",
80     "T"
81 ]
82 ],
83 "or",
84 [
85     "case.internalid",
86     "anyof",
87     {
88         "array": true,
89         "default": "0",
90         "cases": {
91             "all": true,
92             "record": "task",
93             "filters": [
94                 [
95                     [
96                         "assigned",
97                         "anyof",
98                         "${ request.parameters.resource }"
99                     ],
100                     "or",
101                     [
102                         [
103                             "formulatext:{custevent_nx_task_team.id}",
104                             "isnot",
105                             ""
106                         ],
107                         "and",
108                         [
109                             "custevent_nx_task_team",
110                             "anyof",
111                             "${ request.parameters.resource }"
112                         ]
113                     ]
114                 ],
115                 "and",
116                 [
117                     "startdate",
118                     "onorafter",
119                     "${ request.parameters.start }"
120                 ],
121                 "and",
122                 [
123                     "startdate",
124                     "onorbefore",
125                     "${ request.parameters.end }"
126                 ],
127                 "and",
128                 [

```

```
129 "formulatext:case when ({ user.view } = '0' or coalesce({case.subsidiary.id}, {job.subsidiary.id}, {company.subsidiary.id}, 0) in (0,{ user.view })) then 'T' else 'F' end",  
    "is",  
    "T"  
  ],  
  "map": "<^case.internalid"  
}  
  
],  
"map": {  
  "id": "formattext:'task-'||internalid)",  
  "resource": "assigned",  
  "resources": "custevent_nx_task_team()",  
  "startdate": "formattext:to_char((case when ((custevent_nx_time_zone) is not null and {custevent_nx_start_date} is  
not null and {custevent_nx_end_time} is not null) then to_timestamp_tz(to_char({custevent_nx_start_date}, 'YYYY-MM-DD') ||  
to_char({custevent_nx_start_time}, 'HH24:MI:SS')) || (case when {custevent_nx_time_zone.custrecord_nx_time_zone_olson} like '%/%'  
then {custevent_nx_time_zone.custrecord_nx_time_zone_olson} else 'Australia/Sydney' end), 'YYYY-MM-DDHH24:MI:SSTZR') else cast(({startdate)  
as timestamp with time zone) end at time zone 'UTC','YYYY-MM-DD\\\"HH24:MI:SS\\\"Z\\\")|startdate",  
  "enddate": "formattext:to_char((case when ((custevent_nx_time_zone) is not null and {custevent_nx_end_date} is not null  
and {custevent_nx_end_time} is not null) then to_timestamp_tz(to_char({custevent_nx_end_date}, 'YYYY-MM-DD') || to_char({custen  
t_nx_end_time}, 'HH24:MI:SS')) || (case when {custevent_nx_time_zone.custrecord_nx_time_zone_olson} like '%/%' then {custen  
t_nx_time_zone.custrecord_nx_time_zone_olson} else 'Australia/Sydney' end), 'YYYY-MM-DDHH24:MI:SSTZR') else cast(({enddate) -  
trunc(cast(enddate as date) - cast(startdate as date))) as timestamp with time zone) end at time zone 'UTC','YYYY-MM-DD\\\"T  
\\\"HH24:MI:SS\\\"Z\\\")|enddate",  
  "timezone": "custevent_nx_timezone_depr",  
  "address": "custevent_nx_address",  
  "latitude": "custevent_nx_latitude",  
  "longitude": "custevent_nx_longitude",  
  "link": "formattext:{case.case_number}",  
  "booking": "formattext:case when {custevent_nx_booking_confirmed} = 'T' then 'confirmed' else 'tentative' end",  
  "editable": "formattext:case when {status.id} like 'NOTSTART' and ({ $ { user.edit } } = '0' or coalesce({case.sub  
sidiary.id}, {job.subsidiary.id}, {company.subsidiary.id}, 0) in (0,$ { user.edit } )) then 'T' else 'F' end",  
  "region": "custevent_nx_asset.custrecord_nx_asset_region",  
  "skill": "custevent_nx_skill[]",  
  "type": "custevent_nx_type",  
  "status": "formattext:case when {status.id} like 'COMPLETE' then 'completed' when {status.id} like 'NOTSTART' then  
'notstarted' when {status.id} like 'PROGRESS' then 'inprogress' else '' end",  
  "priority": "formattext:case when {priority.id} like 'LOW' then '3' when {priority.id} like 'MEDIUM' then '2' when {priorit  
ty.id} like 'HIGH' then '1' end",  
  "class": "",  
  "swatch": "formattext:case when {status.id} like 'COMPLETE' then 'ashgray' when {status.id} not like 'COMPLETE' and  
{case.stage} like 'CLOSED' then 'inactive' end",  
  "casetype": "case.custevent_nx_case_type",  
  "icon": "",  
  "label": "formattext:coalesce(custevent_nx_customer.companyname),trim({custevent_nx_customer.firstname})|'|{|{custen  
t_nx_customer.lastname}), {title})",  
  "secondarylabel": "formattext:{custevent_nx_task_type}|'|{|internalid}|'| - '|regex_replace(regex_replace({custeven  
t_nx_address}, '(.)+|[CHR(13)|CHR(10)])(.+)', '\\2'), '[|]|CHR(13)|CHR(10)||'] , ' )'",  
  "tertiarylabe": "custevent_nx_task_asset_name",  
  "title": "formattext:nvl2(custevent_nx_customer,'<a href='\"$ { url.customer } ?id= \"||{custevent_nx_customer.inter  
nalid}\"'||\" target=\"_blank\">\"|nvl({custevent_nx_customer.companyname},{custevent_nx_customer.firstname})|'|{|{custevent_nx cus  
tomer.lastname})|'|</a>', '<a href='\"$ { url.task } ?id= \"||{internalid}|'|\" target=_\"_blank\">\"|{|title}|'|</a>'")",  
  "details": "formattext:\\t\\t\\t\\t\\t\\t\\t<p><a href='\"$ { url.task } ?id= \"||{internalid}|'|\" title='Task |'{custeven  
t_nx_task_number}\\t\\t\\t\\t\\t\\t\\t<p>|'|Priority<p>|'|\\t\\t\\t\\t\\t\\t\\t\\tnvl2({custevent_nx_task_asset}, '<p><a href='\"$ { url.as  
set } &id= \"||{custevent_nx_task_asset.internalid}|'|\" title='Asset |'{custevent_nx_task_asset.custrecord_nx_asset_seri  
al}\\t\\t\\t\\t\\t\\t\\t\\tnvl2({case.internalid}, '<p><a href='\"$ { url.case } ?id= \"||{case.internalid}|'|\" title='Case |'{case.caseenum  
ber}\\t\\t\\t\\t\\t\\t\\t\\tnvl2(case,custevent_nx_case_type),'Case')|'|{|case.case_number}|'|</a><p>, ')|\\t\\t\\t\\t\\t\\t\\t  
\\t\\tnvl2(job,custevent_nx_project_type,'Project')|'|{|job.entitytid}|'|</a><p>, ')|\\t\\t\\t\\t\\t\\t\\t\\t  
\\t\\tnvl2(case,custevent_nx_details),'<p class='ellipsis'><b>Details:</b><br>|substr(case,custevent_nx_detail s,1,200)|'|<p>, ')|\\t\\t\\t\\t\\t\\t\\t\\t\\tnvl2(message),'<p class='ellipsis'><b>Message:</b><br>|substr(message,1,200)|'|<  
p>, ')|\\t\\t\\t\\t\\t\\t\\t\\t\\tnvl2(custevent_nx_task_skill),'<p><b>Skills:</b><br>|replace(custevent_nx_task_skill,', ',' '), '  
, ')|\\t\\t\\t\\t\\t\\t\\t\\t\\tnvl2(custevent_nx_actions_taken),'<p class='ellipsis'><b>Actions Taken:</b><br>|substr({custeven  
t_nx_actions_taken},1,200)|'|<p>, ')",  
  "add": "formattext:$ { url.task }?supportcase= \"||{case.internalid}|'|&company= \"||{job.internalid}\",  
  "copy": "formattext:$ { url.task } ?id= \"||{internalid}|'|&t=T&c=T\"",  
  "download": "formattext:$ { url.api } /models/task/'||{internalid}' /service report&template= service report&pdf=true "  
},  
  "sendemail": true
```

```

171     },
172     "projecttask": false,
173     "resourceallocation": false
174   }
175 }

```

eventstatus

Type	Description
Object	Event status text and icons.

Default

```

1  {
2    "eventstatus": {
3      "notstarted": {
4        "label": "Not Started",
5        "icon": "notstarted"
6      },
7      "inprogress": {
8        "label": "In Progress",
9        "icon": "inprogress"
10     },
11     "completed": {
12       "label": "Completed",
13       "icon": "completed"
14     },
15     "tentative": {
16       "label": "Tentative",
17       "icon": "tentative"
18     },
19     "confirmed": {
20       "label": "Confirmed",
21       "icon": "confirmed"
22     },
23     "overdue": {
24       "label": "Overdue",
25       "icon": "overdue"
26     }
27   }
28 }

```

feedback

Type	Description
Object	Feedback types and default option.

Default

```

1  {
2    "feedback": {
3      "enabled": true,
4      "default": "feedback",
5      "type": {
6        "feedback": {
7          "label": "Feedback",
8          "placeholder": "Tell us what you think",
9          "submittitle": "Submitting your feedback...",
10         "submitbody": "A case will be created and our customer success team will follow up.<br/><br/>You will receive a confirmation email.",

```

```

11     "successtitle": "Thanks for your feedback!",
12     "errorbody": "We couldn't submit your feedback. Please try again later.<br/>If the error persists, please contact your
    administrator."
13 },
14     "help": {
15         "label": "Help",
16         "placeholder": "How can we help you?",
17         "submittitle": "Submitting your request...",
18         "submitbody": "We'll get back to you soon.<br/><br/>A case will be created and you will receive a confirmation email.",
19         "successtitle": "Help is on its way!",
20         "errorbody": "We couldn't submit your request. Please try again later.<br/>If the error persists, please contact your admin
    istrator."
21     },
22     "suggestion": {
23         "label": "Suggestions",
24         "placeholder": "How can we improve your experience?",
25         "submittitle": "Submitting your suggestions...",
26         "submitbody": "A case will be created and our customer success team will follow up.<br/><br/>You will receive a confirma
    tion email.",
27         "successtitle": "Thanks for your suggestions!",
28         "errorbody": "We couldn't submit your suggestions. Please try again later.<br/>If the error persists, please contact your
    administrator."
29     },
30     "question": {
31         "label": "Questions",
32         "placeholder": "What would you like to know?",
33         "submittitle": "Submitting your questions...",
34         "submitbody": "Our customer success team will get back to you soon.<br/><br/>A case will be created and you will receive a
    confirmation email.",
35         "successtitle": "Thanks for your enquiry!",
36         "errorbody": "We couldn't submit your enquiry. Please try again later.<br/>If the error persists, please contact your admin
    istrator."
37     }
38 }
39 }
40 }

```

groups

Type	Description
Array.<String>	Resource attribute names to group by.

Default

```

1 {
2   "groups": [
3     "regiontext"
4   ]
5 }

```

inject

Type	Description
String	Html to append to the head of the document to load custom content such as styles and scripts.

Default

```

1 {
2   "inject": "<!-- Inject -->"

```



```
3 | }
```

netpromoterscore

Type	Description
Object	Net Promoter Score delay settings and scores.

Default

```

1 | {
2 |   "netpromoterscore": {
3 |     "enabled": true,
4 |     "start": "",
5 |     "popupfrequency": 90,
6 |     "feedbackfrequency": 30,
7 |     "ignoredelay": 30,
8 |     "score": {
9 |       "veryunlikely": {
10 |         "label": "Very unlikely",
11 |         "value": 1,
12 |         "icon": "nps_veryunlikely_static",
13 |         "iconanimated": "nps_veryunlikely"
14 |       },
15 |       "unlikely": {
16 |         "label": "Unlikely",
17 |         "value": 2,
18 |         "icon": "nps_unlikely_static",
19 |         "iconanimated": "nps_unlikely"
20 |       },
21 |       "maybe": {
22 |         "label": "Maybe",
23 |         "value": 3,
24 |         "icon": "nps_maybe_static",
25 |         "iconanimated": "nps_maybe"
26 |       },
27 |       "likely": {
28 |         "label": "Likely",
29 |         "value": 4,
30 |         "icon": "nps_likely_static",
31 |         "iconanimated": "nps_likely"
32 |       },
33 |       "verylikely": {
34 |         "label": "Very likely",
35 |         "value": 5,
36 |         "icon": "nps_verylikely_static",
37 |         "iconanimated": "nps_verylikely"
38 |       }
39 |     }
40 |   }
41 | }
```

onsite

Type	Description
Number	Distance in kilometers that a Resource is considered on site for an Event.

Default

```
1 | {
```

```

2 | "onsite": 0.5
3 | }

```

refresh

Type	Description
Number	Frequency of refreshes of Resource and Events in milliseconds. 60000 = 1 minute.

Default

```

1 | {
2 |   "refresh": 60000
3 | }

```

resource

Type	Description
Array.<Object>	Resolvable collection of Resources. Run time json is viewable here .

Properties

Properties	Type	Description
employee	Object	Employees

Default

```

1 | {
2 |   "resource": {
3 |     "sort": "label",
4 |     "employee": {
5 |       "record": "employee",
6 |       "filters": [
7 |         [
8 |           "isinactive",
9 |           "is",
10 |          "F"
11 |        ],
12 |        "and",
13 |        [
14 |          "custentity_nx_region",
15 |          "noneof",
16 |          "@NONE@"
17 |        ],
18 |        "and",
19 |        [
20 |          "formulatext:case when '${ user.view }' = '0' or {subsidiary.id} in (${ user.view }) then 'T' else 'F' end",
21 |          "is",
22 |          "T"
23 |        ]
24 |      ],
25 |     "map": {
26 |       "id": "internalid",
27 |       "latitude": "custentity_nx_latitude",
28 |       "longitude": "custentity_nx_longitude",

```

```

29     "calendar": "formulatext:nvl2({custentity_nx_work_calendar}, 'nxworkcalendar-'||{custentity_nx_work_calendar.id}, '')",
30     "class": "formulatext:''",
31     "initials": "formulatext:substr({firstname}, 1, 1)||substr({lastname}, 1, 1)",
32     "label": "formulatext:nvl(trim(trim(trim({firstname}))||' '||{middlename}))||' '||{lastname}), {entityid})",
33     "title": "formulatext:'<a href=\"${ url.employee }?id='||{internalid}||\" target=\"_blank\">'||nvl(trim(trim(trim({first
name}))||' '||{middlename}))||' '||{lastname}), {entityid})||'</a>'",
34     "jobtitle": "title|",
35     "subtitle": "formulatext:{subsidiary.nameno hierarchy}",
36     "project": false,
37     "editable": "formulatext:case when '${ user.edit }' = '0' or {subsidiary.id} in (${ user.edit }) then 'T' else 'F' end",
38     "details": "formulatext:\\t\\t\\t\\t\\t\\t\\t\\tnvl2({comments}, '<p>'||{comments}||'</p>', '')||\\t\\t\\t\\t\\t\\t\\t\\tnvl2({custenti
ty_nx_skill}, replace({custentity_nx_skill}, ',', '<br>', '')),
39     "skill": "custentity_nx_skill[]",
40     "skilltext": "formulatext:nvl2({custentity_nx_skill}, replace({custentity_nx_skill}, ',', '<br>', '')),
41     "region": "custentity_nx_region",
42     "regiontext": "custentity_nx_region#",
43     "image": "formulatext:nvl2(image, '${ server }file/'||{image.id}, '')",
44     "phone": "mobilephone",
45     "mobile": "formulatext:case when ({custentity_nx_mobile_user} = 'T' or regexp_like(email), '${ license.administrator }',
'i')) and ({internalid} = ${ user.internalid } or '${ user.mobile }' = 'true') then '${ url.mobile }&user='||{email} end",
46     "online": "formulatext:to_char(cast({lastmodifieddate} as timestamp with time zone) at time zone 'UTC', 'YYYY-MM-DD\\T
\\HH24:MI:SS\\Z\\')",
47     "email": "email|"
48   }
49 }
50 }
51 }

```

resourcepanel

Type	Description
Array.<Object>	Resource panel filtering and sorting options.

Default

```

1  {
2    "resourcepanel": {
3      "filter": {
4        "region": {
5          "label": "Region",
6          "column": "region",
7          "options": {
8            "record": "customlist_nx_region",
9            "map": {
10             "id": "internalid",
11             "label": "name"
12           }
13         }
14       },
15       "skill": {
16         "label": "Skill",
17         "column": "skill",
18         "options": {
19           "record": "customrecord_nx_skill",
20           "map": {
21             "id": "internalid",
22             "label": "name"
23           }
24         },
25       "allany": true
26     },
27     "id": {
28       "label": "Name",
29       "column": "id",
30       "options": {
31         "sort": "label",

```

```
32     "employee": {
33       "record": "employee",
34       "filters": [
35         [
36           "isinactive",
37           "is",
38           "F"
39         ],
40         "and",
41         [
42           "custentity_nx_region",
43           "noneof",
44           "@NONE@"
45         ],
46         "and",
47         [
48           "formulatext:case when '${ user.view }' = '0' or {subsidiary.id} in (${ user.view }) then 'T' else 'F' end",
49           "is",
50           "T"
51         ]
52       ],
53       "map": {
54         "id": "internalid",
55         "label": "formulatext:nvl(trim(trim(trim({firstname}))||' '||{middlename}))||' '||{lastname}), {entityid}"
56       }
57     }
58   }
59 }
60 },
61 "sort": {
62   "labelasc": {
63     "label": "A-Z",
64     "column": "label",
65     "direction": "asc"
66   },
67   "labeldesc": {
68     "label": "Z-A",
69     "column": "label",
70     "direction": "desc"
71   }
72 }
73 }
74 }
```

start

Type	Description
Number	The start of service time in hours = 9:00 am.

Default

```
1 {
2   "start": 9
3 }
```

unassignedpanel

Type	Description
Array.<Object>	Unassigned events filtering and sorting options.

Default

```

1  {
2    "unassignedpanel": {
3      "filter": {
4        "region": {
5          "label": "Region",
6          "column": "region",
7          "options": {
8            "record": "customlist_nx_region",
9            "map": {
10             "id": "internalid",
11             "label": "name"
12           }
13         }
14       },
15       "type": {
16         "label": "Type",
17         "column": "type",
18         "options": {
19           "record": "customrecord_nx_task_type",
20           "map": {
21             "id": "internalid",
22             "label": "name"
23           }
24         }
25       },
26       "skill": {
27         "label": "Skill",
28         "column": "skill",
29         "options": {
30           "record": "customrecord_nx_skill",
31           "map": {
32             "id": "internalid",
33             "label": "name"
34           }
35         },
36       "allany": true
37     },
38     "priority": {
39       "label": "Priority",
40       "column": "priority",
41       "options": [
42         {
43           "id": "3",
44           "label": "Low"
45         },
46         {
47           "id": "2",
48           "label": "Medium"
49         },
50         {
51           "id": "1",
52           "label": "High"
53         }
54       ]
55     },
56     "booking": {
57       "label": "Booking",
58       "column": "booking",
59       "options": [
60         {
61           "id": "tentative",
62           "label": "Tentative"
63         },
64         {
65           "id": "confirmed",
66           "label": "Confirmed"
67         }
68       ]
69     },
70   },
71   "sort": {

```

```

72     "prioritydesc": {
73       "label": "High Priority",
74       "column": "priority",
75       "direction": "asc"
76     },
77     "priorityasc": {
78       "label": "Low Priority",
79       "column": "priority",
80       "direction": "desc"
81     },
82     "startasc": {
83       "label": "Oldest",
84       "column": "startdate",
85       "direction": "asc"
86     },
87     "startdesc": {
88       "label": "Newest",
89       "column": "startdate",
90       "direction": "desc"
91     },
92     "labelasc": {
93       "label": "A-Z",
94       "column": "label",
95       "direction": "asc"
96     },
97     "labeldesc": {
98       "label": "Z-A",
99       "column": "label",
100      "direction": "desc"
101    }
102  }
103 }
104 }

```

unit

Type	Description
Number	The minimum duration and rounding unit for editable Events start and end times in milliseconds. 900000 = 15 minutes.

Default

```

1  {
2    "unit": 900000
3  }

```

views

Type	Description
Object	The tabs available for browsing.

Default

```

1  {
2    "views": {
3      "day": {
4        "label": "1 Day",

```

```

5      "unit": "days",
6      "start": 0,
7      "end": 0
8    },
9    "three": {
10     "label": "3 Days",
11     "unit": "days",
12     "start": -1,
13     "end": 1
14   },
15   "seven": {
16     "label": "7 Days",
17     "unit": "days",
18     "start": -3,
19     "end": 3,
20     "default": true
21   },
22   "fifteen": {
23     "label": "15 Days",
24     "unit": "days",
25     "start": -7,
26     "end": 7
27   },
28   "thirtyone": {
29     "label": "31 Days",
30     "unit": "days",
31     "start": -15,
32     "end": 15
33   }
34 }
35 }

```

utilities/collection

Utility to convert hash of objects to sorted array of objects with id

Parameters

Parameter	Type	Attributes	Description
data	Object	Required	Hash of objects to convert.
data.*.index	Number	Optional	Zero based index for the item in the collection.

returns

Type	Description
Array.<Object>	Ordered collection of objects

utilities/config

Reads an attribute from config and templates object attributes into a string or object containing strings. This is not a configurable module.

Members

accounting

Type	Description
—	Accounts internalid ids

Properties

Property	Type	Description
debit_account	Number	Account internal id to debit labor recovery journey lines.
credit_account	Number	Account internal id to credit labor recovery journey lines.
asset_profitability_report	Number	NextService Asset Profitability Report internal id unique to the account.
entity_profitability_report	Number	NextService Entity Profitability Report internal id unique to the account.

Default

```

1  {
2    "accounting": {
3      "debit_account": 0,
4      "credit_account": 0,
5      "asset_profitability_report": 0,
6      "entity_profitability_report": 0
7    }
8  }
```

billing

Type	Description
—	Billing rules

Properties

Property	Type	Description
task	Array.<Object>	Set of task type rules to apply a default billing type.
task[].project	Array.<Number>	Project types to match on.
task[].case	Array.<Number>	Case types to match on.
task[].task	Array.<Number>	Task types to match on.
task[].billing	Array.<Number>	Default Billing Type to set on task.
time	Boolean	Resolves to true if the time and task context should be billable.
expense	Boolean	Resolves to true if the expense category and task context should be billable.
consumable	Boolean	Resolves to true if the consumable and task context should be billable.

Default

```
1 {
2   "billing": {
3     "task": [],
4     "time": {
5       "join": true,
6       "item": {
7         "record": "item",
8         "filters": "${ time.item }",
9         "map": "formulatext:case when ${ task.billing } in (3,4,7,8) then 'F' else 'T' end"
10      }
11    },
12    "expense": {
13      "boolean": true,
14      "category": {
15        "record": "expensecategory",
16        "filters": "${ expense.category }",
17        "map": "formulatext:case when ${ task.billing } in (2,4,6,8) then 'F' else 'T' end"
18      }
19    },
20    "consumable": {
21      "join": true,
22      "item": {
23        "record": "item",
24        "filters": "${ consumable.item }",
25        "map": "formulatext:case when ${ task.billing } in (5,6,7,8) then 'F' else 'T' end"
26      }
27    }
28  }
29 }
```

icons

Type	Description
—	SVG Definitions with a 100 x 100 view box.

Properties

Property	Type	Description
defs	Object	Namespace for icon paths.
defs.default	String	Flag icon path.

Default

```
1 {
2   "icons": {
3     "defs": {
4       "flag": "<path d=\"M80.9,30c-0.2,0-0.3,0-0.5,0.1v0c-2.7,1.4-5.8,2.2-9.1,2.2c-6,0-11.5-2.7-15.1-7c-3.3-3.1-7.6-5-12.5-5c-4.7,0-8.9,1.7-12.1,4.6c-0.7-1.4-2.1-2.4-3.8-2.4c-2.3,0-4.2,1.9-4.2,4.2v50.6c0,2.3,1.9,4.2,4.2,4.2s4.2-1.9,4.2-4.2V54.6c2.7-1.3,5.7-2.1,8.8-2.1c6.1,0,11.5,2.7,15.1,7.1c3.3,3.1,7.6,4.9,12.5,4.9c5.2,0,9.9-2.2,13.2-5.7c0.2-0.2,0.4-0.6,0.4-0.9V31.3C82.1,30.6,81.5,30.8,9.30z\"/>",
5       "torsos": "<path d=\"M40.348,49.813c0.919-0.584,1.763-1.303,2.527-2.121c-2.683-4.036-4.239-8.966-4.239-14.191c0-3.492,0.689-6.798,1.896-9.787c-1.879-1.25-4.026-2.022-6.349-2.022c-7.114,0-12.872,6.702-12.872,14.978c0,5.79,2.83,10.801,6.962,13.295l-17.448,8.121c-1.087,0.511-1.804,1.739-1.804,3.111v13.771c0,1.846,1.289,3.341,2.874,3.341h11.532v-14.45c0-3.739,2.068-7.121,5.275-8.623L40.348,49.813z\"/>
6       ">path d=\"M88.772,60.017l-15.023-7.167l-6.353-3.03c2.775-1.748,5.028-4.445,6.503-7.695c1.169-2.581,1.866-5.502,1.866-8.625c0-1.753-0.278-3.416-0.666-5.023c-1.89-7.782-7.968-13.515-15.263-13.515c-7.158,0-13.144,5.529-15.15,13.09c-0.463,1.734-0.782,3.538-0.782,5.448c0,3.319,0.775,6.412,2.092,9.103c1.523,3.121,3.78,5.696,6.527,7.351-6.085,2.834L30.93,60.01c-1.348,0.631-2.233,2.151-2.233,3.849v14.45v2.593c0,2.284,1.591,4.136,3.557,4.136H87.42c1.965,0,3.557-1.852,3.557-4.136v-2.593v-14.45c90.977,62.168,90.106,60.662,88.772,60.017z\"/>"
7     }
8   }
9 }
```

```

6 |   }
7 | }
8 | }

```

program

Type	Description
—	Program definitions for projects and cases

Properties

Property	Type	Description
project	Array.<Object>	Set of rules to generate a Program of Work for a Project.

Default

```

1 | {
2 |   "program": {
3 |     "project": [],
4 |     "case": []
5 |   }
6 | }

```

tab

Type	Description
—	Tab internal ids. These properties are configured automatically on install.

Properties

Property	Type	Description
tab.transaction	String	Label or internalid of the tab to attach form elements to..
tab.entity	String	Label or internalid of the tab to attach form elements to..
tab.item	String	Label or internalid of the tab to attach form elements to..
tab.crm	String	Label or internalid of the tab to attach form elements to..
tab.asset	String	Label or internalid of the tab to attach form elements to..

Default

```

1 | {
2 |   "tab": {
3 |     "transaction": "custom6",
4 |     "entity": "custom8",
5 |     "item": "custom7",
6 |     "crm": "custom9",
7 |     "asset": "custom4"
8 |   }
9 | }

```

warranty

Type	Description
Object	Warranty projects to create when an asset is created.

Default

```
1 {
2   "warranty": {
3     "asset": {
4       "array": true,
5       "item": {
6         "record": "item",
7         "filters": [
8           [
9             "custitem_nx_project_type",
10            "noneof",
11            "@NONE@"
12          ],
13          "and",
14          [
15            "formulatext:case when {internalid} in ('${ asset.item }') then 'T' else 'F' end",
16            "is",
17            "T"
18          ]
19        ],
20        "map": {
21          "type": "custitem_nx_project_type",
22          "start": "formuladate:CURRENT_TIMESTAMP at time zone ${ asset.timezoneid ? '\\\\' + asset.timezoneid + '\\\\' : 'SESSION
23          TIMEZONE' }",
24          "end": "formuladate:ADD_MONTHS(CURRENT_TIMESTAMP at time zone ${ asset.timezoneid ? '\\\\' + asset.timezoneid + '\\\\' :
25          'SESSIONTIMEZONE' }, {custitem_nx_project_duration}) - 1"
26        }
27      }
28    }
29  }
```

utilities/form

Utility to generate a record form as json

Parameters

Parameter	Type	Attributes	Description
options.record	String	Required	Record type
options.order	Boolean	Optional	Apply user event before load field ordering.
options.options	Boolean	Optional	Load select options
options.hidden	Boolean	Optional	Include hidden fields
options.inline	Boolean	Optional	Include inline fields
options.include	Array.<String>	Optional	Only return these fields
options.exclude	Array.<String>	Optional	Return all fields excep these
options.cache	Boolean	Optional	Store or retrieve cached form matching the defined options

returns

Type	Description
Object	Form

utilities/merge

Utility to deep merge objects

Parameters

Parameter	Type	Attributes	Description
target	Object	Required	Object to merge onto
values	Object	Required	Object to import.
options.regexp	Boolean	Optional	If the value key is a pattern, merge into all matching target keys. The value will be templated with capture groups for each matched key.
options.delete	Boolean	Optional	Delete keys when merging in null value.
options.foldcase	Boolean	Optional	Merges keys with case-insensitive match. New keys are added as is.

returns

Type	Description
*	Transformed object

utilities/resolve

Utility to transform an object recursively for searches subqueries, templating, email creation, file loading/creation, array merging/sorting/ordering, object flattening.

Parameters

Parameter	Type	Attributes	Description
data	*	Required	Data to recurse and transform
data.template	String	Optional	Freemarker template to render with the data found on all sibling properties. Use the property name to access the data in the template. The rendered string is returned.
data.boolean	Boolean	Optional	Returns true if all sibling properties are truthy. Array values must all be truthy to pass. Setting to false passes when all values are falsey.

Parameter	Type	Attributes	Description
data.parse	String	Optional	JSON string to parse and return.
data.array	Boolean, String	Optional	Concatenates and all property arrays as a single array. If array is a string, the concatenated array is sorted by that property.
data.sort	String	Optional	Sort the concatenated array by this property before returning.
data.join	Boolean, String	Optional	Join the concatenated array before returning as a string. If join is a string, that value is used as the separator.
data.file	String, Number	Optional	Loads and returns a file when this is a path string or internalid number. If file is a file extension, a file is created from the content property and is returned.
data.contents	String	Optional	Content of the file to create. If the file option is 'pdf', the content is converted from xml to pdf before creating.
data.name	String	Optional	Name of the file to create. If no name is defined, name is set to the title xml tag found in the content property.
data.record	String	Optional	Returns either a record search or loaded record of this record type.
data.id	Number	Optional	Loads and the record with this internalid.
data.filters	*	Optional	Searches the record using these filters.
data.map	*	Optional	Searches the record using this field map.
data.form	*	Optional	Extends the map property with all fields found on a form.
data.body	String	Optional	When body and recipients properties are present, consider this an email definition.
data.recipients	Array.<String>	Optional	When body and recipients properties are present, consider this an email definition.
data.subject	String	Optional	When no email subject is defined, subject is set to the title tag found in the body property.
data.options	Array.<Object>	Optional	The option in the array with the lowest value for the selected property has selected set to true. All other options have selected removed.

Returns

Type	Description
*	Transformed object

utilities/resource

Utility to render a resource

Parameters

Parameter	Type	Attributes	Description
original	Object	Required	Resource template
options.id	String	Required	Unique ID to assign to resource.
options.parentid	Number	Optional	Parent record id.
options.where	Object	Optional	Filters to apply to article fetch.
options.upload	String	Required	Upload path.
options.download	String	Required	Download path.
options.imagesize	Number	Required	Maximum image size.
options.icon	Boolean	Optional	—
options.label	String	Optional	—
options.parent	String	Optional	ID of the parent resource to add this resource as a sub menu option of.
options.article	Boolean	Optional	Return the Article model constructor.
options.article.extend	Boolean	Optional	—
options.article.parent	Boolean	Optional	—
options.articleonly	Boolean	Optional	Return the Article model constructor.
options.element	String	Optional	Element definitions.
options.elementonly	String	Optional	Return the element definition.
options.form	true, Number, Object	Optional	Loads a form for the Article model and extends the resource element property and article map with fields loaded from the form. Refer to Record.form for valid parameters.
options.hidden	Boolean	Optional	The resource is hidden.
options.search	Boolean	Optional	—
options.remote	Boolean	Optional	—
options.readonly	Boolean	Optional	—
options.min	Boolean	Optional	—
options.max	Boolean	Optional	—
options.enable	Boolean	Optional	—
options.disable	Boolean	Optional	—
options.*	Object	Optional	All other option values are added to the templating scope under <i>options</i> .

utilities/rule

Utility to finds the matching rules in a rule set

Parameters

Parameter	Type	Attributes	Description
rules	Array.<Object>	Required	Rules to test against
ignore	Array	Required	Rule attributes to ignore
attributes	Object	Required	Attributes to match on

Returns

Type	Description
Object	The matching rule
Null	If no matching rule found

views/asset/address

Asset Address Component Replaces the [Asset] address book field with a select of [Customer] addresses.

Members

available

Type	Description
String	Template for the label of the custom page Select field.

Default

```
1 | {  
2 |   "available": "Select from ${ total } available..."  
3 | }
```

hidden

Type	Description
Boolean	This view is to be shown or hidden.

Default

```

1 | {
2 |   "hidden": false
3 | }

```

name

Type	Description
String	Unique name of the custom page Select field.

Default

```

1 | {
2 |   "name": "custpage_nx_address"
3 | }

```

view/asset/addresssearch

Asset Address Search Component Add a google address search input to the form

Members

hidden

Type	Description
Boolean	This view is to be shown or hidden.

Default

```

1 | {
2 |   "hidden": false
3 | }

```

label

Type	Description
String	Field label

Default

```

1 | {

```



```

2 | "label": "Address Search"
3 | }

```

name

Type	Description
String	Unique name of the custom page Select field.

Default

```

1 | {
2 |   "name": "custpage_nx_address_autocomplete"
3 | }

```

views/asset/parent

Asset Parent Component Enable and disable fields

views/asset/profitability

Asset Profitability Report Component Adds a button to view mode of Assets to view the Profitability Report.

Members

hidden

Type	Description
Boolean	This view is to be shown or hidden

Default

```

1 | {
2 |   "hidden": false
3 | }

```

label

Type	Description
String	Button label

Default

```

1 | {
2 |   "label": "Profitability Report"
3 | }

```

name

Type	Description
String	Button name

Default

```

1 | {
2 |   "name": "custpage_nx_profitability"
3 | }

```

report

Type	Description
Number	Asset Profitability report internal id

Default

```

1 | {
2 |   "report": 307
3 | }

```

url

Type	Description
String	Url template to the report

Default

```

1 | {
2 |   "url": "/app/reporting/reportrunner.nl?cr=${ report }&crit_2=${ name }"
3 | }

```

views/asset/project

Asset Project Component Adds a button to edit and view mode of Assets to create a new project

Members

hidden

Type	Description
Boolean	This view is to be shown or hidden

Default

```
1 | {  
2 |   "hidden": false  
3 | }
```

label

Type	Description
String	Button label

Default

```
1 | {  
2 |   "label": "New Project"  
3 | }
```

name

Type	Description
String	Button name

Default

```
1 | {  
2 |   "name": "custpage_nx_project"  
3 | }
```

url

Type	Description
String	Url template to the report

Default

```

1 | {
2 |   "url": "/app/accounting/project/project.nl?compid=9607429&pf=CUSTENTITY_NX_ASSET&pi=${ id }&pr=${ record }"
3 | }

```

view/asset/task

Asset Task Component Adds a button to edit and view mode of Assets to create a new task

Members

hidden

Type	Description
Boolean	This view is to be shown or hidden

Default

```

1 | {
2 |   "hidden": false
3 | }

```

label

Type	Description
String	Button label

Default

```

1 | {
2 |   "label": "New Task"
3 | }

```

name

Type	Description
String	Button name

Default

```

1 | {

```

```

2 | "name": "custpage_nx_task"
3 | }

```

url

Type	Description
String	Url template to the report

Default

```

1 | {
2 |   "url": "/app/crm/calendar/task.nl?compid=9607429&pf=CUSTEVENT_NX_TASK_ASSET&pi=${ id }&pr=${ record }"
3 | }

```

views/assetcustomer

Asset Customer Fields Component

Manages the selectable options for the Customer and Asset fields on Transactions, Project, Case, and Task forms. When an Asset or Customer is selected, the other field will filter to options that are valid for that value. The first field the user selects will initiate filtering of the other field. To remove filtering of the second field, the user must clear the first field.

Over time, an Asset and Customer relationship may change and an old record may have values that are no longer valid. When these records are edited, the form will not clear the invalid values unless the Asset or Customer is changed.

The options that are available to select are firstly defined by the `models/asset.map.customers` property and the `models/customer.map.assets` property. When *true*, all options are available and no filtering is applied. When *false*, no options can be selected and filtering will be applied with no options. When any other value, filtering will be applied with the options defined by `models/asset.customers` and `models/customer.assets`.

Members

assetFilter

Type	Description
String	Name of the filtered Asset select field that is shown when filtering is applied.

Default

```

1 | {
2 |   "assetFilter": "custpage_nx_asset"
3 | }

```

assetOption

Type	Description
Object	Asset option map.

Default

```

1 | {
2 |   "assetOption": {
3 |     "id": "internalid",
4 |     "label": "name"
5 |   }
6 | }
```

customerFilter

Type	Description
String	Name of the filtered Customer select field that is shown when filtering is applied.

Default

```

1 | {
2 |   "customerFilter": "custpage_nx_customer"
3 | }
```

customerOption

Type	Description
Object	Customers option map.

Default

```

1 | {
2 |   "customerOption": {
3 |     "id": "internalid",
4 |     "label": "formulatext:nvl(nvl(trim({firstname}||' '||{lastname}),{companyname}), {entityid})"
5 |   }
6 | }
```

hidden

Type	Description
Boolean	This view will be active when the form is in create/edit/copy mode and the Asset and Customer fields are visible.

Default

```

1 | {
```

```

2 | "hidden": false
3 | }

```

views/case/autoname

Case Autoname Component Enable and disable name field when autonaming as you can't from forms.

Members

hidden

Type	Description
Boolean	This view is to be shown or hidden

Default

```

1 | {
2 |   "hidden": false
3 | }

```

views/case/invoice

Case Invoice Component Adds a button to view mode of Cases with unbilled time, expenses, or sales to create an Invoice.

Members

confirm

Type	Description
String	Confirm text before creating the invoice.

Default

```

1 | {
2 |   "confirm": "Are you sure you want to generate the Invoice?"
3 | }

```

hidden

Type	Description
Boolean	This view is to be shown or hidden

Default

```

1 | {
2 |   "hidden": false
3 | }

```

label

Type	Description
String	Button label

Default

```

1 | {
2 |   "label": "Generate Invoice"
3 | }

```

name

Type	Description
String	Button name

Default

```

1 | {
2 |   "name": "custpage_nx_invoice"
3 | }

```

success

Type	Description
String	Alert text when the invoice is successfully created.

Default

```

1 | {
2 |   "success": "Invoice successfully created."
3 | }

```

views/case/projects

Case Projects Component Adds a select to edit mode of Cases to select active projects for the Asset.

Members

hidden

Type	Description
Boolean	This view is to be shown or hidden

Default

```
1 {
2   "hidden": false
3 }
```

label

Type	Description
String	Select label

Default

```
1 {
2   "label": "Project"
3 }
```

name

Type	Description
String	Select name

Default

```
1 {
2   "name": "custpage_nx_active_projects"
3 }
```

options

Resolvable template for the select options for the current case.

Properties

Property	Type	Description
id	String	Project id
label	String	Label to use for the project

Property	Type	Description
selected	String	Options with a truthy selected value are automatically selected in ascending order.

Default

```

1  {
2    "options": {
3      "array": true,
4      "active": {
5        "record": "job",
6        "filters": [
7          [
8            "custentity_nx_asset",
9            "anyof",
10           "${ supportcase.asset }"
11          ],
12          "and",
13          [
14            [
15              "startdate",
16              "isempty",
17              ""
18            ],
19            "or",
20            [
21              "formulatext:case when from_tz(cast({startdate} as timestamp), case when {custentity_nx_time_zone.cus
trecord_nx_time_zone_olson} like '%/%' then {custentity_nx_time_zone.custrecord_nx_time_zone_olson} else SESSIONTIMEZONE
end) <= timestamp '${ supportcase.starttimestamp }' then 'T' else 'F' end", "is", "T" ] ], "and", [ [ "enddate", "isempty",
"" ], "or", [ "formulatext:case when from_tz(cast(({enddate} + 1) as timestamp), case when {custentity_nx_time_zone.cus
trecord_nx_time_zone_olson} like '%/%' then {custentity_nx_time_zone.custrecord_nx_time_zone_olson} else SESSIONTIMEZONE end) >
timestamp '${ supportcase.starttimestamp }' then 'T' else 'F' end",
22              "is",
23              "T"
24            ]
25          ],
26          "and",
27          [
28            "isinactive",
29            "is",
30            "F"
31          ]
32        ],
33        "map": {
34          "id": "internalid",
35          "label": "formulatext:{custentity_nx_customer}||' : '||{custentity_nx_project_type}||nv12({startdate}, ' from '||
{startdate}, ')||nv12({enddate}, ' to '||{enddate}, ')||nv12({custentity_nx_time_zone}, ' ' || {custentity_nx_time_zone.cus
trecord_nx_time_zone_abbreviation}, ')",
36          "selected": "formulatext:''"
37        }
38      },
39      "types": {
40        "record": "customrecord_nx_project_type",
41        "filters": [
42          [
43            "isinactive",
44            "is",
45            "F"
46          ],
47          "and",
48          [
49            "internalid",
50            "noneof",
51            [
52              0
53            ]
54          ]
55        ],
56        "map": {
57          "id": "formulatext:'type-'||{Internalid}",
58          "label": "formulatext:'- New '||{Name}||' - '",

```

```

59     "selected": "formulatext:''"
60   }
61 }
62 }
63 }

```

refreshFields

Type	Description
Array.<String>	Fields that trigger refresh

Default

```

1 {
2   "refreshFields": [
3     "custevent_nx_case_asset",
4     "startdate",
5     "starttime"
6   ]
7 }

```

showFields

Type	Description
Array.<String>	Fields required to show active projects field

Default

```

1 {
2   "showFields": [
3     "custevent_nx_case_asset"
4   ]
5 }

```

views/case/servicereport

Case Service Report Component Adds a button to view mode of Closed Cases to preview the Service Report pdf and email to the customer.

Members

delay

Type	Description
Number	Delay in milliseconds before confirming with the user to send the email.

Default

```
1 | {
2 |   "delay": 1000
3 | }
```

hidden

Type	Description
Boolean	This view is to be shown or hidden

Default

```
1 | {
2 |   "hidden": false
3 | }
```

label

Type	Description
String	Button label

Default

```
1 | {
2 |   "name": "custpage_nx_servicereport"
3 | }
```

send

Type	Description
String	Confirm text before sending the email. Clear this value to only preview the pdf.

Default

```
1 | {
2 |   "send": "Are you sure you want to send this Service Report?"
3 | }
```

success

Type	Description
String	Alert text when the email is successfully sent.

Default

```
1 | {
2 |   "success": "Service Report successfully queued to be sent."
3 | }
```

views/case/tasks

Case Tasks Component Builds and manages sublist on the case to add tasks

Members

assignees

Type	Description
—	Options for the assigned fields

Default

```

1 {
2   "assignees": {
3     "array": true,
4     "default": {},
5     "employee": {
6       "record": "employee",
7       "filters": [
8         [
9           "isinactive",
10          "is",
11          "F"
12        ],
13        "and",
14        [
15          "custentity_nx_region",
16          "noneof",
17          "@NONE@"
18        ],
19        "and",
20        [
21          "formulatext:case when '${ user.view }' = '0' or {subsidiary.id} in (${ user.view }) then 'T' else 'F' end",
22          "is",
23          "T"
24        ]
25      ],
26      "map": {
27        "id": "internalid",
28        "label": "<formulatext:nvl(trim(trim(trim({firstname}))||' '||{middlename}))||' '||{lastname}), {entityid})",
29        "skill": "custentity_nx_skill[]"
30      }
31    }
32  }
33 }
```

available

Type	Description
String	Label for available assignees

Default

```

1 {
2   "available": "${ total } available..."
3 }
```

el

Type	Description
—	Form elements

Default

```

1 {
2   "el": {
3     "tab": {
4       "type": "subtab",
5       "label": "Add Tasks",
6       "parent": "custom9",
7       "name": "custpage_nx_tasks"
8     },
9     "list": {
10      "type": "inlineeditor",
11      "label": "Tasks",
12      "parent": "tab"
13    },
14    "assignees": {
15      "type": "longtext",
16      "display": "hidden",
17      "parent": "tab"
18    },
19    "addtype": {
20      "type": "select",
21      "label": "Type",
22      "parent": "tab",
23      "layout": "midrow",
24      "width": 180
25    },
26    "addassigned": {
27      "type": "select",
28      "label": "Assigned",
29      "parent": "tab",
30      "layout": "midrow",
31      "width": 180
32    },
33    "adddate": {
34      "type": "date",
35      "label": "Start Date",
36      "parent": "tab",
37      "layout": "midrow"
38    },
39    "adddue": {
40      "type": "date",
41      "label": "End Date",
42      "parent": "tab",
43      "layout": "midrow"
44    },
45    "addstart": {
46      "type": "timeofday",
47      "label": "Start",
48      "parent": "tab",
49      "value": "09:00",
50      "layout": "midrow",
51      "width": 7
52    },
53    "addend": {
54      "type": "timeofday",
55      "label": "End",
56      "parent": "tab",
57      "value": "17:00",
58      "layout": "midrow",
59      "width": 7
60    },
61    "addbooking": {
62      "type": "checkbox",

```

```

63     "label": "Confirmed Booking",
64     "parent": "tab",
65     "layout": "midrow"
66   },
67   "addskill": {
68     "type": "multiselect",
69     "label": "Skills",
70     "parent": "tab",
71     "map": "[]",
72     "layout": "startrow",
73     "break": "startrow",
74     "width": 370,
75     "height": 3
76   },
77   "addmessage": {
78     "type": "textarea",
79     "label": "Message",
80     "parent": "tab",
81     "layout": "midrow",
82     "width": 50,
83     "height": 6
84   },
85   "add": {
86     "type": "button",
87     "label": "Add",
88     "parent": "list"
89   },
90   "reset": {
91     "type": "button",
92     "label": "Remove All",
93     "parent": "list"
94   },
95   "type": {
96     "type": "select",
97     "label": "Type",
98     "parent": "list",
99     "required": true
100  },
101  "assigned": {
102    "type": "select",
103    "label": "Assigned",
104    "parent": "list",
105    "required": false
106  },
107  "date": {
108    "type": "date",
109    "label": "Date",
110    "parent": "list",
111    "required": true
112  },
113  "start": {
114    "type": "timeofday",
115    "label": "Start",
116    "parent": "list",
117    "required": true
118  },
119  "end": {
120    "type": "timeofday",
121    "label": "End",
122    "parent": "list",
123    "required": true
124  },
125  "booking": {
126    "type": "checkbox",
127    "label": "Confirmed Booking",
128    "parent": "list"
129  },
130  "message": {
131    "type": "text",
132    "label": "Message",
133    "parent": "list"
134  },
135  "skill": {

```

```

136     "type": "text",
137     "label": "Skill",
138     "parent": "list",
139     "map": "[]",
140     "display": "hidden"
141   }
142 }
143 }

```

hidden

Type	Description
Boolean	This view is to be shown or hidden

Default

```

1 {
2   "hidden": false
3 }

```

skills

Type	Description
—	Options for the skills field

Default

```

1 {
2   "skills": {
3     "array": true,
4     "default": {
5       "label": "None"
6     },
7     "task": {
8       "record": "customrecord_nx_skill",
9       "filters": [
10        "isinactive",
11        "is",
12        "F"
13      ],
14       "map": {
15         "id": "internalid",
16         "label": "name"
17       }
18     }
19   }
20 }

```

types

Type	Description
—	Options for the type field

Default

```

1 | {
2 |   "types": {
3 |     "array": true,
4 |     "default": {},
5 |     "task": {
6 |       "record": "customrecord_nx_task_type",
7 |       "filters": [
8 |         "isinactive",
9 |         "is",
10 |        "F"
11 |      ],
12 |       "map": {
13 |         "id": "internalid",
14 |         "label": "name"
15 |       }
16 |     }
17 |   }
18 | }

```

views/customer/profitability

Customer Profitability Report Component Adds a button to view mode of Customer to view the Profitability Report.

Members

hidden

Type	Description
Boolean	This view is to be shown or hidden

Default

```

1 | {
2 |   "hidden": false
3 | }

```

label

Type	Description
String	Button label

Default

```

1 | {
2 |   "label": "Profitability Report"
3 | }

```

name

Type	Description
String	Button name

Default

```
1 {
2   "name": "custpage_nx_profitability"
3 }
```

report

Type	Description
Number	Asset Profitability report internal id

Default

```
1 {
2   "report": 306
3 }
```

url

Type	Description
String	Url template to the report

Default

```
1 {
2   "url": "/app/reporting/reportrunner.nl?cr=${ report }&crit_1_mod=${ date }&crit_1_from=${ start }&crit_1_to=${ end }&crit_2=
3   ${ entity }&crit_3=${ name }"
```

views/employee/loginas

Employee Login As Button Component Adds a button to view mode of Mobile Employees to login as them in the browser.

Members

hidden

Type	Description
Boolean	This view is to be shown or hidden

Default

```

1 | {
2 |   "hidden": false
3 | }

```

label

Type	Description
String	Button label

Default

```

1 | {
2 |   "label": "Mobile Login"
3 | }

```

name

Type	Description
String	Button name

Default

```

1 | {
2 |   "name": "custpage_nx_loginas"
3 | }

```

views/employee/mobilelogin

Employee Mobile Login Button Component Adds a button to view mode of Mobile Employees to email them a link to the Mobile app.

Members

confirm

Type	Description
String	Confirm text before creating the invoice.

Default

```

1 | {
2 |   "confirm": "Are you sure you want to send this email?"

```

```
3 | }
```

hidden

Type	Description
Boolean	This view is to be shown or hidden

Default

```
1 | {
2 |   "hidden": false
3 | }
```

label

Type	Description
String	Button label

Default

```
1 | {
2 |   "label": "Email Mobile Login"
3 | }
```

name

Type	Description
String	Button name

Default

```
1 | {
2 |   "name": "custpage_nx_mobilelogin"
3 | }
```

success

Type	Description
String	Alert text when the email is successfully sent.

Default

```
1 | {
2 |   "success": "Email successfully queued to be sent."
```

3 | }

views/itemfulfillment/assets

Item Fulfillment Assets Component Adds a sublist to Itemfulfillment that creates or updates Assets records from fulfilled Asset Items

Members

element

Type	Description
Object	Form element definitions.

Properties

Property	Type	Description
element.list	Object	Asset sublist.
element.item	Object	Source the item from the transaction line. This is populated with script from the fulfilled line.
element.serial	Object	Source the serial number from the transaction line. This is populated with script from the fulfilled line inventory detail.
element.id	Object	Link to existing Asset record. This is populated with script when a matching Asset record is found.
element.customer	Object	Sources the customer from the transaction body field.
element.parent	Object	Sources the parent from the transaction body field.
element.addressbook	Object	Source the address id from the transaction ship address.
element.addresstext	Object	Source the address text from the transaction ship address text. When present, this is populated with script to format the address and remove the Attention and Addressee.

Default

```

1  {
2    "element": {
3      "list": {
4        "label": "Create/Update Assets",
5        "name": "custpage_nx_assets",
6        "type": "inlineeditor",
7        "parent": "custom6"
8      },
9      "item": {
10       "label": "Item",
11       "type": "select",
12       "parent": "list",
13       "display": "disabled",
14       "required": true
15     },

```

```
16   "serial": {
17     "label": "Serial Number",
18     "type": "text",
19     "parent": "list",
20     "required": true
21   },
22   "id": {
23     "label": "Asset",
24     "type": "select",
25     "parent": "list",
26     "display": "disabled"
27   },
28   "customer": {
29     "label": "Customer",
30     "type": "select",
31     "parent": "list",
32     "display": "hidden",
33     "source": "customer",
34     "sourcefrom": "custbody_nx_customer"
35   },
36   "parent": {
37     "label": "Parent",
38     "type": "select",
39     "parent": "list",
40     "display": "hidden",
41     "source": "customrecord_nx_asset",
42     "sourcefrom": "custbody_nx_asset"
43   },
44   "addressbook": {
45     "label": "Address Book",
46     "type": "integer",
47     "parent": "list",
48     "display": "hidden",
49     "sourcefrom": "shipaddresslist"
50   },
51   "addresstext": {
52     "label": "Address",
53     "type": "textarea",
54     "parent": "list",
55     "display": "disabled",
56     "sourcefrom": "shipaddress"
57   }
58 }
59 }
```

error

Type	Description
Object	User error messages.

Properties

Property	Type	Description
error.required	String	Alert text when an Asset does not have the require fields completed. The scope of this template is a hash of the missing required element name and labels.
error.duplicate	String	Alert text when the Asset line is not unique. The scope of this template is the duplicate line data.

Default

```
1  {
2    "error": {
```

```
3      "required": "Please enter value(s) for: ${ Array.prototype.join.apply(arguments, [' ', '']) }",
4      "duplicate": "Duplicate Asset already exists at line ${ line }."
5    }
6  }
```

hidden

Type	Description
Boolean	This view is to be shown or hidden

Default

```
1  {
2    "hidden": false
3  }
```

views/newnull

New Null Component On Parent records, the Child Records sublist and Create New menu show 'null' instead of the record name. This replaces 'null' in the button and options' labels with the record name from the form.

Members

hidden

Type	Description
Boolean	This view is to be shown or hidden

Default

```
1  {
2    "hidden": false
3  }
```

name

Type	Description
String	Unique name of the html page field.

Default

```
1  {
2    "name": "custpage_nx_newnull"
3  }
```

views/project/autoname

Project Autoname Component Enable and disable name field when autonaming as you can't from forms

Members

hidden

Type	Description
Boolean	This view is to be shown or hidden

Default

```
1 | {  
2 |   "hidden": false  
3 | }
```

views/project/contact

Project Contact Component Add a contact field to the project on create to set the Primary Contact.

Members

hidden

Type	Description
Boolean	This view is to be shown or hidden

Default

```
1 | {  
2 |   "hidden": false  
3 | }
```

label

Type	Description
String	Select label

Default

```
1 | {  
2 |   "label": "Contact"  
3 | }
```


name

Type	Description
String	Unique name of the custom page Select field.

Default

```

1 {
2   "name": "custpage_nx_contact"
3 }
```

options

Type	Description
—	Resolvable template for the select options for the current project.

Default

```

1 {
2   "options": {
3     "array": true,
4     "contacts": {
5       "record": "customer",
6       "filters": [
7         "internalid",
8         "is",
9         "${ project.customer }"
10      ],
11      "map": {
12        "id": "contact.internalid",
13        "label": "<contact.entityid",
14        "selected": "formulatext:case when {contact.role} = -10 then 'T' else '' end"
15      }
16    }
17  }
18 }
```

views/project/customer

Project Parent Component NetSuite prevents users from changing the Parent field on a Project after it has been created. As the Customer and Parent fields are linked, the Customer field must also be readily when editing a Project.

Members

hidden

Type	Description
Boolean	This view is to be shown or hidden

Default

```
1 | {  
2 |   "hidden": false  
3 | }
```

views/project/journal

Project Journal Component Adds a button to view mode of Projects with unrecoverd Time to create a Labour Recovery Journal.

Members

hidden

Type	Description
Boolean	This view is to be shown or hidden

Default

```
1 | {  
2 |   "hidden": false  
3 | }
```

label

Type	Description
String	Button label

Default

```
1 | {  
2 |   "label": "Create Time Journal"  
3 | }
```

name

Type	Description
String	Button name

Default

```
1 | {  
2 |   "name": "custpage_nx_journal"  
3 | }
```

success

Type	Description
String	Alert text when the Journal is successfully created.

Default

```
1 {
2   "success": "Journal successfully created."
3 }
```

views/project/profitability

Project Profitability Report Component Adds a button to view mode of Customer to view the Profitability Report.

Members

hidden

Type	Description
Boolean	This view is to be shown or hidden

Default

```
1 {
2   "hidden": false
3 }
```

label

Type	Description
String	Button label

Default

```
1 {
2   "label": "Profitability Report"
3 }
```

name

Type	Description
String	Button name

Default

```
1 | {
2 |   "name": "custpage_nx_profitability"
3 | }
```

report

Type	Description
Number	Asset Profitability report internal id

Default

```
1 | {
2 |   "report": 306
3 | }
```

url

Type	Description
String	Url template to the report

Default

```
1 | {
2 |   "url": "/app/reporting/reportrunner.nl?cr=${ report }&crit_1_mod=${ date }&crit_1_from=${ start }&crit_1_to=${ end }&crit_2=${ entity }&crit_3=${ name }"
3 | }
```

views/project/program

Project Program Component Builds and manages sublist on the project to show programmed cases

Members

el

Type	Description
—	Form elements

Default

```
1 | {
2 |   "el": {
```

```

3      "list": {
4          "type": "inlineeditor",
5          "label": "Program",
6          "parent": "custom8",
7          "name": "custpage_nx_program",
8          "readonly": true
9      },
10     "type": {
11         "type": "select",
12         "label": "Type",
13         "parent": "list",
14         "display": "readonly",
15         "source": "customrecord_nx_case_type"
16     },
17     "date": {
18         "type": "date",
19         "label": "Program Date",
20         "parent": "list",
21         "display": "readonly"
22     },
23     "case": {
24         "type": "select",
25         "label": "Case",
26         "parent": "list",
27         "display": "readonly",
28         "source": "supportcase"
29     },
30     "start": {
31         "type": "date",
32         "label": "Start Date",
33         "parent": "list",
34         "display": "readonly"
35     },
36     "end": {
37         "type": "date",
38         "label": "End Date",
39         "parent": "list",
40         "display": "readonly"
41     },
42     "status": {
43         "type": "select",
44         "label": "Status",
45         "parent": "list",
46         "display": "readonly",
47         "source": "supportcasestatus"
48     },
49     "assigned": {
50         "type": "select",
51         "label": "Assigned To",
52         "parent": "list",
53         "display": "readonly",
54         "source": "employee"
55     }
56 }
57 }

```

hidden

Type	Description
Boolean	This view is to be shown or hidden

Default

```

1 {
2   "hidden": false
3 }

```

view/project/subprojects

Project Subprojects Component Builds and manages sublist on the project to add equipment to pm

Members

assetOption

Type	Description
Object	Asset option map.

Default

```
1 {
2   "assetOption": {
3     "id": "internalid",
4     "label": "name"
5   }
6 }
```

el

Type	Description
—	Form elements

Default

```
1 {
2   "el": {
3     "list": {
4       "type": "inlineeditor",
5       "label": "Add Subprojects",
6       "parent": "custom8",
7       "name": "custpage_nx_subprojects"
8     },
9     "asset": {
10      "type": "select",
11      "label": "Asset",
12      "parent": "list",
13      "required": true,
14      "source": "customrecord_nx_asset"
15    },
16    "assetfiltered": {
17      "type": "select",
18      "label": "Asset",
19      "parent": "list",
20      "required": true
21    },
22    "type": {
23      "type": "select",
24      "label": "Type",
25      "parent": "list",
26      "required": true
27    }
28  }
```

```
28 |     "start": {
29 |       "type": "date",
30 |       "label": "Start",
31 |       "parent": "list",
32 |       "required": true
33 |     },
34 |     "end": {
35 |       "type": "date",
36 |       "label": "End",
37 |       "parent": "list",
38 |       "required": true
39 |     },
40 |     "programstart": {
41 |       "type": "date",
42 |       "label": "Program Start",
43 |       "parent": "list"
44 |     },
45 |     "programuntil": {
46 |       "type": "integer",
47 |       "label": "Program Create Until",
48 |       "parent": "list"
49 |     }
50 |   }
51 | }
```

hidden

Type	Description
Boolean	This view is to be shown or hidden

Default

```
1 | {
2 |   "hidden": false
3 | }
```

views/projecttask/servicereport

Project Task Service Report Component Adds a button to view mode of Completed Tasks to preview the Service Report pdf and email to the customer.

Members

delay

Type	Description
Number	Delay in milliseconds before confirming with the user to send the email.

Default

```
1 | {}
```

hidden

Type	Description
Boolean	This view is to be shown or hidden

Default

¹ | {}

label

Type	Description
String	Button label

Default

¹ | {}

name

Type	Description
String	Button name

Default

¹ | {}

send

Type	Description
String	Confirm text before sending the email. Clear this value to only preview the pdf.

Default

¹ | {}

success

Type	Description
String	Alert text when the email is successfully sent.

Default


```
1 | {}
```

views/schedule

Scheduled Script Banner Component Adds schedule script status banners to forms in view mode.

Members

hidden

Type	Description
Boolean	This view is to be shown or hidden.

Default

```
1 | {
2 |   "hidden": false
3 | }
```

name

Type	Description
String	Unique name of the custom page inline html field.

Default

```
1 | {
2 |   "name": "custpage_nx_schedule"
3 | }
```

views/signature

Signature Pad Component Adds signature pads to forms

Members

hidden

Type	Description
Boolean	This view is to be shown or hidden.

Default

```
1 {  
2   "hidden": false  
3 }
```

pattern

Type	Description
String	Naming convention to identify rich text fields to be displayed as signature pads

Default

```
1 {  
2   "pattern": "^cust[a-z_0-9]+_nx[a-z_0-9]+signature[a-z_0-9]*$"   
3 }
```

views/task/autoname

Task Autoname Component Enable and disable name field when autonaming as you can't from forms

Members

hidden

Type	Description
Boolean	This view is to be shown or hidden.

Default

```
1 {  
2   "hidden": false  
3 }
```

views/task/servicereport

Task Service Report Component Adds a button to view mode of Completed Tasks to preview the Service Report pdf and email to the customer.

Members

delay

Type	Description
Number	Delay in milliseconds before confirming with the user to send the email.

Default

```

1 | {
2 |   "delay": 1000
3 | }

```

hidden

Type	Description
Boolean	This view is to be shown or hidden

Default

```

1 | {
2 |   "hidden": false
3 | }

```

label

Type	Description
String	Button label

Default

```

1 | {
2 |   "label": "Service Report"
3 | }

```

name

Type	Description
String	Button name

Default

```

1 | {
2 |   "name": "custpage_nx_servicereport"
3 | }

```

send

Type	Description
String	Confirm text before sending the email. Clear this value to only preview the pdf.

Default

```

1 | {
2 |   "send": "Are you sure you want to send this Service Report?"
3 | }

```

success

Type	Description
String	Alert text when the email is successfully sent.

Default

```

1 | {
2 |   "success": "Service Report successfully queued to be sent."
3 | }

```

views/task/unassigned

Task Unassigned Component Allow unassigned tasks for new scheduler panel

Members

hidden

Type	Description
Boolean	This view is to be shown or hidden

Default

```

1 | {
2 |   "hidden": false
3 | }

```