



ORACLE
NetSuite

SuiteCloud CLI for Java

2025.2

December 17, 2025



Copyright © 2005, 2025, Oracle and/or its affiliates.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software, software documentation, data (as defined in the Federal Acquisition Regulation), or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software," "commercial computer software documentation," or "limited rights data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle®, Java, and MySQL are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

If this document is in public or private pre-General Availability status:

This documentation is in pre-General Availability status and is intended for demonstration and preliminary use only. It may not be specific to the hardware on which you are using the software. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to this documentation and will not be responsible for any loss, costs, or damages incurred due to the use of this documentation.

If this document is in private pre-General Availability status:

The information contained in this document is for informational sharing purposes only and should be considered in your capacity as a customer advisory board member or pursuant to your pre-General Availability trial agreement only. It is not a commitment to deliver any material, code, or functionality, and should not be relied upon in making purchasing decisions. The development, release, timing, and pricing of any features or functionality described in this document may change and remains at the sole discretion of Oracle.

This document in any form, software or printed matter, contains proprietary information that is the exclusive property of Oracle. Your access to and use of this confidential material is subject to the terms and conditions of your Oracle Master Agreement, Oracle License and Services Agreement, Oracle PartnerNetwork Agreement, Oracle distribution agreement, or other license agreement which has been executed by you and Oracle and with which you agree to comply. This document and information contained herein may not be disclosed, copied, reproduced, or distributed to anyone outside Oracle without prior written consent of Oracle. This document is not part of your license agreement nor can it be incorporated into any contractual agreement with Oracle or its subsidiaries or affiliates.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <https://www.oracle.com/corporate/accessibility>.

Access to Oracle Support

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

Sample Code

Oracle may provide sample code in SuiteAnswers, the Help Center, User Guides, or elsewhere through help links. All such sample code is provided "as is" and "as available", for use only with an authorized NetSuite Service account, and is made available as a SuiteCloud Technology subject to the SuiteCloud Terms of Service at www.netsuite.com/tos.

Oracle may modify or remove sample code at any time without notice.

No Excessive Use of the Service

As the Service is a multi-tenant service offering on shared databases, Customer may not use the Service in excess of limits or thresholds that Oracle considers commercially reasonable for the Service. If Oracle reasonably concludes that a Customer's use is excessive and/or will cause immediate or ongoing performance issues for one or more of Oracle's other customers, Oracle may slow down or throttle Customer's excess use until such time that Customer's use stays within reasonable limits. If Customer's particular usage pattern requires a higher limit or threshold, then the Customer should procure a subscription to the Service that accommodates a higher limit and/or threshold that more effectively aligns with the Customer's actual usage pattern.

Beta Features

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software" or "commercial computer software documentation" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

This documentation is in pre-General Availability status and is intended for demonstration and preliminary use only. It may not be specific to the hardware on which you are using the software. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to this documentation and will not be responsible for any loss, costs, or damages incurred due to the use of this documentation.

The information contained in this document is for informational sharing purposes only and should be considered in your capacity as a customer advisory board member or pursuant to your pre-General Availability trial agreement only. It is not a commitment to deliver any material, code, or functionality, and should not be relied upon in making purchasing decisions. The development, release, and timing of any features or functionality described in this document remains at the sole discretion of Oracle.

This document in any form, software or printed matter, contains proprietary information that is the exclusive property of Oracle. Your access to and use of this confidential material is subject to the terms and conditions of your Oracle Master Agreement, Oracle License and Services Agreement, Oracle PartnerNetwork Agreement, Oracle distribution agreement, or other license agreement which has been executed by you and Oracle and with which you agree to comply. This document and information contained herein may not be disclosed, copied, reproduced, or distributed to anyone outside Oracle without prior written consent of Oracle. This document is not part of your license agreement nor can it be incorporated into any contractual agreement with Oracle or its subsidiaries or affiliates.

Table of Contents

SuiteCloud CLI for Java Guide	1
SuiteCloud CLI for Java Installation Prerequisites	1
Installing SuiteCloud CLI for Java	2
SuiteCloud CLI for Java Reference	5
SuiteCloud CLI for Java Commands	5
adddependencies	7
authenticate	8
authenticateci	9
createfile	10
createproject	11
deploy	12
importbundle	14
importconfiguration	15
importfiles	16
importobjects	17
listbundles	18
listconfiguration	19
listfiles	20
listmissingdependencies	20
listobjects	21
manageauth	23
package	23
preview	24
project	25
update	26
updatecustomrecordwithinstances	27
uploadfiles	27
uploadfolders	28
validate	29

SuiteCloud CLI for Java Guide

Important: Starting February 2025, SuiteCloud CLI for Java version 2024.1, which supports Token-Based Authentication (TBA) and OAuth 1.0, will no longer be available for new installations. If you are still using an older version of the tool, you should upgrade to the latest version as soon as possible. The latest version of SuiteCloud CLI for Java is version 2025.1, and this version uses the OAuth 2.0 protocol for authorization.

SuiteCloud Command Line Interface for Java (SuiteCloud CLI for Java) is a tool you can use with your integrated development environment (IDE) to develop SuiteCloud projects. You can also create batch and shell scripts that use CLI commands to automate SuiteCloud project validation and deployment processes. SuiteCloud CLI for Java is part of the SuiteCloud Software Development Kit (SuiteCloud SDK).

Note: SuiteCloud CLI for Java is intended for experienced SDF users and users who are already familiar with SuiteCloud IDE plug-ins and extensions. You should use SuiteCloud IDE plug-ins and extensions to develop your first project and to learn more about SDF before trying SuiteCloud CLI for Java. For more information, see the help topics [Getting Started with SuiteCloud Development Framework](#) and [SuiteCloud Development Framework Tutorial](#).

The following topics provide instructions to install and use SuiteCloud CLI for Java:

- [SuiteCloud CLI for Java Installation Prerequisites](#)
- [Installing SuiteCloud CLI for Java](#)

SuiteCloud CLI for Java Installation Prerequisites

Verify the following prerequisites before you install SuiteCloud CLI for Java:

- **Java SE Development Kit** – SuiteCloud CLI for Java requires [Oracle JDK version 17](#) or [Oracle JDK version 21](#).
- **SuiteCloud Development Framework (SDF) enabled** – Ensure SDF is enabled in your NetSuite account. Go to Setup > Company > Enable Features, click the SuiteCloud subtab, and check the SuiteCloud Development Framework box.
- **NetSuite account features** – An account administrator must enable the features in your account that SDF depends on. For more information, see the help topic [Enabling SuiteCloud Development Framework in the Target NetSuite Account \(Administrator Only\)](#).
- **NetSuite permissions** – A user with the Administrator role must create and assign the SDF Developer role to your account.

For more information, see the help topic [Assigning the Developer Role \(Administrator Only\)](#).

- **Operating system** – SuiteCloud CLI for Java officially supports these operating systems:
 - Windows
 - Linux
 - macOS

Specifically, it's been tested with these operating systems and browser combinations:

- Windows 11 – Firefox and Chrome
- Linux Fedora – Firefox, Chrome
- macOS Sequoia – Firefox, Safari, and Chrome

- **OAuth 2.0 enabled** – Ensure OAuth 2.0 is enabled in your NetSuite account. To enable it, go to Setup > Company > Enable Features, click the **SuiteCloud** subtab, and check the **OAuth 2.0** box in the **Manage Authentication** section. For more information, see the help topic [Enable the OAuth 2.0 Feature](#).

Installing SuiteCloud CLI for Java



Important: Before downloading SuiteCloud CLI for Java, read the **Oracle Free Use Terms and Conditions** license below.

■ Definitions

"Oracle" refers to Oracle America, Inc. "You" and "Your" refers to (a) a company or organization (each an "Entity") accessing the Programs, if use of the Programs will be on behalf of such Entity; or (b) an individual accessing the Programs, if use of the Programs will not be on behalf of an Entity. "Program(s)" refers to Oracle software provided by Oracle pursuant to the following terms and any updates, error corrections, and/or Program Documentation provided by Oracle. "Program Documentation" refers to Program user manuals and Program installation manuals, if any. If available, Program Documentation may be delivered with the Programs and/or may be accessed from www.oracle.com/documentation. "Separate Terms" refers to separate license terms that are specified in the Program Documentation, readmes or notice files and that apply to Separately Licensed Technology. "Separately Licensed Technology" refers to Oracle or third party technology that is licensed under Separate Terms and not under the terms of this license.

■ Separately Licensed Technology

Oracle may provide certain notices to You in Program Documentation, readmes or notice files in connection with Oracle or third party technology provided as or with the Programs. If specified in the Program Documentation, readmes or notice files, such technology will be licensed to You under Separate Terms. Your rights to use Separately Licensed Technology under Separate Terms are not restricted in any way by the terms herein. For clarity, notwithstanding the existence of a notice, third party technology that is not Separately Licensed Technology shall be deemed part of the Programs licensed to You under the terms of this license.

■ Source Code for Open Source Software

For software that You receive from Oracle in binary form that is licensed under an open source license that gives You the right to receive the source code for that binary, You can obtain a copy of the applicable source code from <https://oss.oracle.com/sources/> or <http://www.oracle.com/goto/opensourcecode>. If the source code for such software was not provided to You with the binary, You can also receive a copy of the source code on physical media by submitting a written request pursuant to the instructions in the "Written Offer for Source Code" section of the latter website.

The following license terms apply to those Programs that are not provided to You under Separate Terms.

■ License Rights and Restrictions

Oracle grants to You, as a recipient of this Program, a nonexclusive, nontransferable, limited license to, subject to the conditions stated herein, (a) internally use the unmodified Programs for the purposes of developing, testing, prototyping and demonstrating your applications, and running the Programs for your own internal business operations; and (b) redistribute unmodified Programs and Programs Documentation, under the terms of this License, provided that You do not charge Your end users any additional fees for the use of the Programs. You may make copies of the Programs to the extent reasonably necessary for exercising the license rights granted herein and for backup purposes. You are granted the right to use the Programs to provide third party training in the use of the Programs and associated Separately Licensed Technology only if there is express authorization of such use by Oracle on the Program's download page or in the Program Documentation.

Your license is contingent on Your compliance with the following conditions:

- You include a copy of this license with any distribution by You of the Programs;
- You do not remove markings or notices of either Oracle's or a licensor's proprietary rights from the Programs or Program Documentation;
- You comply with all U.S. and applicable export control and economic sanctions laws and regulations that govern Your use of the Programs (including technical data);
- You do not cause or permit reverse engineering, disassembly or decompilation of the Programs (except as allowed by law) by You nor allow an associated party to do so.

For clarity, any source code that may be included in the distribution with the Programs is provided solely for reference purposes and may not be modified, unless such source code is under Separate Terms permitting modification.

■ **Ownership**

Oracle or its licensors retain all ownership and intellectual property rights to the Programs.

■ **Information Collection**

The Programs' installation and/or auto-update processes, if any, may transmit a limited amount of data to Oracle or its service provider about those processes to help Oracle understand and optimize them. Oracle does not associate the data with personally identifiable information. Refer to Oracle's Privacy Policy at www.oracle.com/privacy.

■ **Disclaimer of Warranties; Limitation of Liability**

THE PROGRAMS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND. ORACLE FURTHER DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NONINFRINGEMENT.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW WILL ORACLE BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

To install SuiteCloud CLI for Java, extract the installation package so you can then run CLI using Java.



Important: The instance of SuiteCloud CLI for Java installed in your machine doesn't get updated automatically. Every time a new version of the CLI is released, you must update your SuiteCloud CLI for Java instance manually. You can download the latest version of the installation package from the link provided in the steps below.

To install SuiteCloud CLI for Java:

1. Create a folder where you want to install SuiteCloud CLI for Java, like C:\javacli\ for Windows or /javacli/ for Linux and macOS.
2. Adjust your PATH system environment variable to include the SuiteCloud CLI for Java directory. This lets you use SuiteCloud CLI for Java from any folder on your machine.
 - Select **Control Panel > System > Advanced system settings**.
 - Click **Environment Variables...**
 - Under **System variable**, select the PATH variable, and click **Edit...**
 - Click **New**, enter the SuiteCloud CLI for Java directory path, and click **OK**.
 - In the **Environment Variables** window, click **OK**. Then, in the **System Properties** window, click **Apply**, and then **OK**.

Note: To set up a proxy server, create the SUITECLOUD_PROXY environment variable. The value must include an http or https protocol, a hostname, and a port number, for example: `http://proxyurl:proxyport`. After creating the variable, restart your console.

3. Download the SuiteCloud CLI for Java and extract the contents to your SuiteCloud CLI for Java directory:

The latest version of SuiteCloud CLI for Java is version 2025.2 and it's compatible with NetSuite 2025.2. To get it, use one of the following links:

- Windows: <https://system.netsuite.com/download/suitecloud-sdk/cli/java/25.2/sdf-cli.zip>
- Linux and macOS: <https://system.netsuite.com/download/suitecloud-sdk/cli/java/25.2/sdf-cli.tar.gz>

If you want to get the latest updates automatically, use one of the following links:

- Windows: <https://system.netsuite.com/download/suitecloud-sdk/cli/java/latest/sdf-cli.zip>
- Linux and macOS: <https://system.netsuite.com/download/suitecloud-sdk/cli/java/latest/sdf-cli.tar.gz>

If you want to use the previous version of the CLI, use one of the following links:

- Windows: <https://system.netsuite.com/download/suitecloud-sdk/cli/java/25.1/sdf-cli.zip>
- Linux and macOS: <https://system.netsuite.com/download/suitecloud-sdk/cli/java/25.1/sdf-cli.tar.gz>

Note: The packages include the JAR file and either the SuiteCloud CLI for Java bash or batch script, depending on your operating system.

Now you can use SuiteCloud CLI for Java by running the `sdfcli` command.

Important: Starting February 2025, SuiteCloud CLI for Java version 2024.1, which supports Token-Based Authentication (TBA) and OAuth 1.0, won't be available for new installations. If you're still using an older version of the tool, you should upgrade to the latest version as soon as possible. For more information, see [Removal of OAuth 1.0 Token-Based Authentication Support in SuiteCloud SDK](#) (SuiteAnswer ID 1019514).

4. For Linux and macOS, make the `sdfcli` bash file executable by running this command from the SuiteCloud CLI for Java directory:

```
chmod +x sdfcli
```

Now you can use SuiteCloud CLI for Java by running the `sdfcli` command.

Note: You need read, write, and execute access on any folder where you want to run SuiteCloud CLI for Java.

SuiteCloud CLI for Java Reference

SuiteCloud CLI for Java Commands

SuiteCloud CLI for Java Commands

You can use SuiteCloud CLI for Java to manage SuiteCloud project components, and to validate and deploy projects to your NetSuite account.

Note: SuiteCloud CLI for Java is intended for experienced SDF users and users who are already familiar with SuiteCloud IDE plug-ins and extensions. Use a SuiteCloud IDE plug-in or extension to develop your first project and to learn more about SDF before trying SuiteCloud CLI for Java. For more information, see the help topics [Getting Started with SuiteCloud Development Framework](#) and [SuiteCloud Development Framework Tutorial](#).

SuiteCloud CLI for Java Syntax

```
sdfcli <command> <option> <argument>
```

Note: If an argument is in angle brackets (<argument>), it's required. If it's in brackets ([argument]), it's optional.

SuiteCloud CLI for Java Command Reference

Command	Description
adddependencies	Adds any missing dependencies to the manifest file.
authenticate	Grants authorization for SuiteCloud SDK to access NetSuite with an account-role combination. It requires browser-based login to NetSuite.
authenticateci	Grants authorization for SuiteCloud SDK to access NetSuite with an account-role combination. It doesn't require browser-based login to NetSuite. This command is helpful for automated environments such as CI.
createfile	Creates a SuiteScript file.
createproject	Creates a SuiteCloud project.
deploy	Deploys the folder or ZIP file with your SuiteCloud project.
importbundle	Imports a customization bundle from your NetSuite account and turns it into an account customization project.

	Note: SuiteBundler is still supported, but it won't get any new features. To take advantage of new features for packaging and distributing customizations, you can use the Copy to Account and SuiteCloud Development (SDF) features instead of SuiteBundler. Copy to Account is an administrator tool that you can use to copy objects between your accounts. The tool can copy one object at a time, including dependencies and data. For more information, see the help topic Copy to Account. SuiteCloud Development Framework is a development framework that you can use to create SuiteApps from an integrated development environment (IDE) on your local computer. For more information, see the help topic SuiteCloud Development Framework.
importconfiguration	Imports the feature configuration from your NetSuite account to the account customization project, so you can enable or disable features in the project.
importfiles	Imports files from your NetSuite account to the account customization project.
importobjects	Imports SDF custom objects from your NetSuite account your SuiteCloud project.
listbundles	Lists the customization bundles created in your NetSuite account.
listconfiguration	Lists the configuration types available in your NetSuite account.
listfiles	Lists the files in your NetSuite account's File Cabinet .
listmissingdependencies	Lists the missing dependencies in your SuiteCloud project.
listobjects	Lists the SDF custom objects in your NetSuite account.
manageauth	Manages authentication IDs for all your projects.
package	Generates a ZIP file from your project.
preview	Previews the deployment steps of a folder or ZIP file with your SuiteCloud project.
project	Sets the default project folder or ZIP file for SuiteCloud CLI for Java.
update	Updates the SDF custom objects in your SuiteCloud project folder with the matching ones from your NetSuite account.
updatecustomrecordwithinstances	Updates the SDF custom objects and their instances in your SuiteCloud project.
uploadfiles	Uploads one or more files from a SuiteCloud project to your account's File Cabinet.
uploadfolders	Uploads all the files in one or more folders from a SuiteCloud project to your account's File Cabinet.

<code>validate</code>	Validates the folder or ZIP file with your SuiteCloud project.
-----------------------	--

adddependencies

Adds any missing dependencies to the manifest file.

Syntax

```

1 sdfcli adddependencies <-authid AuthId>
2   <-p FolderOrZipFile>
3   [-all]
4   [-feature FeatureName1:{optional|required} [FeatureName2:{optional|required}] [...]]
5   [-file File1 [File2] [...]]
6   [-object "appid=<appid>,scriptid=<scriptid1>" "scriptid=<scriptid2>" "[Script3]" [...]]

```

Options

Option	Required / Optional	Description
<code>-authid</code>	Required	References the custom alias you give to a specific account-role combination.
<code>-p</code>	Required when a default project has not been specified by the project command or when you want to specify a project other than the default. For more information, see project .	References the folder or ZIP file that contains your SuiteCloud project.
<code>-all</code>	Optional	Adds all missing dependencies to your SuiteCloud project. When specified, ensure that you don't use the -feature, -file, and -object options.
<code>-feature</code>	Optional	Specifies the feature dependency references to add to your SuiteCloud project. Each reference is a name:value pair separated by a space. For example: <pre>1 CUSTOMRECORD:required ACCOUNTING:optional</pre> When specified, ensure that you don't use the -all option.
<code>-file</code>	Optional	Specifies the files to add to your SuiteCloud project. When specified, ensure that you don't use the -all option.
<code>-object</code>	Optional	Specifies the SDF custom objects to add to your SuiteCloud project. When specified, ensure that you don't use the -all option. You can use two formats for object references. The preferred format uses attribute=value pairs. For example, here's a reference to an SDF custom object with a script ID of <code>custobject_sample</code>:

		<pre>1 "scriptid=custobject_sample"</pre> For SuiteApp projects, you have to use the attribute=value pair format, and include both the script ID and application ID, separated by a comma. For example: <pre>1 "appid=com.netsuite.test01,scriptid=customrecordcrt01" "scriptid=customrecordcrt02"</pre>
-h or -help	Optional	Prints the help for this command.

Example

Here's a command that updates the manifest file of a SuiteCloud project. It adds dependencies on the CUSTOMRECORD feature, a file, and an SDF custom object.

```
1 | sdfcli adddependencies
2 |   -authid AuthId -p c:/project/
3 |   -feature CUSTOMRECORD:required -file /js/test.js
4 |   -object "scriptid=custobject_sample"
```

When you run the command, it prompts you to update the manifest file and produces output that is similar to the following:

```
1 | SuiteCloud Development Framework CLI (com.netsuite.ide.core_2021.1.0)
2 | Manifest file will be updated to add the dependencies, do you want to continue?
3 | Type YES to update the manifest file.
4 | YES
5 | Done.
```

authenticate



Important: Browser-based authentication is not compatible with Windows Subsystem for Linux.

Grants authorization for SuiteCloud SDK to access NetSuite with an account-role combination. It requires browser-based login to NetSuite.



Important: For this command to work, at least one of the following ports needs to be accessible locally from your machine: **52300 – 52315**.

Syntax

```
1 | sdfcli authenticate <-authid AuthId>
2 |   [-url NetSuiteDomainURL]
```

Options

Option	Required / Optional	Description
-authid	Required	References the custom alias you give to a specific account-role combination (also called authentication ID or auth ID in the documentation).

-url	Optional Not required when authenticating against system.netsuite.com.	References the NetSuite domain of the account you want to use. It only needs to be specified if you want to use a customized NetSuite domain.
-h or -help	Optional	Prints the help for this command.

Example

Here's a command that authenticates an account by prompting the browser:

```
1 | sdfcli authenticate <--authid AuthId>
```

Output example

After the browser closes and the account-role combination is authenticated, the command produces output that is similar to the following:

The authentication was successful with the following account and role: Account ID [Role]. This project will use the authentication ID "AuthId" as default.

authenticateci

Grants authorization for SuiteCloud SDK to access NetSuite with an account-role combination. It doesn't require browser-based login to NetSuite. This command is helpful for automated environments such as CI.

For more information, see the help topic [OAuth 2.0 Authentication for SuiteCloud SDK](#).

Syntax

```
1 | sdfcli authenticateci <--account AccountId>
2 |   <--authid AuthId>
3 |   <--certificateid CertificateId>
4 |   <--privatekeypath PrivateKeyPath>
5 |   [-url NetSuiteDomainURL]
```

Options

Option	Required / Optional	Description
-account	Required	References the NetSuite account ID.
-authid	Required	References the custom alias you give to a specific account-role combination (also called authentication ID or auth ID in the documentation).
-certificateid	Required	References the certificate ID you get from NetSuite after uploading the public key file.
-url	Optional	References the NetSuite domain of the account you want to use. It only needs to be specified if you want to use a customized NetSuite domain.
-privatekeypath	Required	References the local path to the private key file that matches the certificate in NetSuite. For example: d:/path/private-key.pem.
-h or -help	Optional	Prints the help for this command.



Important: To get the **certificate ID**, you need to generate an **RSA certificate**. The RSA certificate has two parts: the **public key** and the **private key**.

Upload the public key in the OAuth 2.0 Client Credentials Setup by choosing **SuiteCloud Development Integration** in the **Application** field and selecting the entity and role to map. This will generate a new row with the certificate ID value.

The private key path value is the location where the private key is saved.

For more information about how to generate the **RSA certificate**, see the help topic [Certificate Conditions](#).

For more information about how to upload the public key, follow the steps in [OAuth 2.0 Client Credentials Setup](#).

Example

Here's a command that sets up the account for your current SuiteCloud project:

```
1 sdfcli authenticatoci <-authid AuthId>
2   <-certificateid CertificateId>
3   <-privatekeypath PrivateKeyPath>
4   <-account AccountId>
```

Output example

When you run the command, it produces an output that is similar to the following example:

The authentication was successful with the following account and role: Account ID [Role]. This project will use the authentication ID "AuthId" as default.

createfile

Creates a SuiteScript file of the script type you specify in a SuiteCloud project, which can be either an account customization project or a SuiteApp project.

Syntax

```
1 sdfcli createfile [-type]
2   [-module]
3   <-path>
4   <-project>
```

Options

Option	Required / Optional	Description
--------	---------------------	-------------

-type	Optional	Specifies the script type for the SuiteScript file that you want to create. For example, you can specify the map/reduce script type the following way: -type 'mapReduce'. For a list of available SuiteScript script types, see the help topic SuiteScript 2.x Script Types .
-module	Optional	Specifies the SuiteScript modules that you want to add to the SuiteScript file. For example, you can specify N/currency and N/email modules the following way: -module 'n/currency n/email'. For a list of available SuiteScript modules, see the help topic SuiteScript 2.x Modules .
-path	Required	Specifies the path and file name for the SuiteScript file you are creating. For example, you can specify to create a script in the File Cabinet of your SuiteApp project the following way: -path 'FileCabinet/SuiteApps/com.example.currency/currency.js'. For information about where SuiteScript files can be stored in SuiteCloud projects, see the help topic SuiteCloud Project Structure and File Components .
-project	Required	Specifies the path to the folder with your SuiteCloud project. For example, -project 'c:projects/com.example.currency'.

Example

Here's a command that creates a file:

```

1 sdfcli createfile -type 'mapReduce'
2 -module 'n/currency n/email'
3 -path 'FileCabinet/SuiteApps/com.example.currency/currency.js'
4 -project 'c:projects/com.example.currency'

```

createproject

Creates a SuiteCloud project, either an account customization project (ACP) or a SuiteApp project.

Syntax

```

1 sdfcli createproject [-overwrite]
2 <-type AccountType>
3 <-parentdirectory FolderPath>
4 <-projectname ProjectName>
5 [-projectid ProjectID]
6 [-publisherid PublisherID]
7 [-projectversion ProjectVersion]

```

Options

Option	Required / Optional	Description
-type	Required	The project type. Valid values are ACCOUNTCUSTOMIZATION or SUITEAPP.
-overwrite	Optional	Indicates that an existing project with an identical project name can be overwritten.
-parentdirectory	Required	Sets the parent directory for the project you're creating. For example:

		<pre>1 c:/Users/myUserName/Desktop/NetSuiteCustomizations</pre>  Note: You need read, write, and execute access on any directory where you want to run SuiteCloud CLI.
-projectname	Required	A name for your project.
-projectid	Required when type is specified as SUITEAPP	A unique ID for your project. This value must be a word with lowercase alphanumeric characters. It must be less than 40 characters.
-publisherid	Required when type is specified as SUITEAPP	The publisher ID of your SuiteApp project.
-projectversion	Required when type is specified as SUITEAPP	The version for your project, using semantic versioning. For example, if your SDF SuiteApp is version 1.02, minor revision #01242016, you'd use: <pre>1 1.02.01242016</pre>
-h or -help	Optional	Prints the help for this command.

Example

Here's a command that creates an account customization project:

```
sdfcli createproject [-overwrite] -type ACCOUNTCUSTOMIZATION -parentdirectory d:/myprojects/customizations -projectname MySDFProject
```

Here's a command that creates a SuiteApp project:

```
sdfcli createproject [-overwrite] -type SUITEAPP -parentdirectory d:/sdfprojects/mysuiteapps -projectid mysuiteapp123 -projectname MySDFProject2 -publisherid com.netsuite -projectversion 1.0.0
```

deploy

Deploys the folder or ZIP file with your SuiteCloud project.

The SuiteCloud project folder gets zipped before deployment. Only the files and folders listed in the `deploy.xml` file are included in the ZIP file.



Important: For installation script, installation preference, and translation collection objects, files referenced in their xml structure are also deployed, even if these files are not part of the `deploy.xml` file.

Syntax

```
1 | sdfcli deploy <-authid AuthId>
2 |   [-p FolderOrZipFile]
3 |   [-applyinstallprefs]
4 |   [-l LogPathOrFile]
5 |   [-np]
6 |   [-v]
```

```
7 | [-sw]
8 | [-accountsspecificvalues (WARNING|ERROR)]
```

Options

Option	Required / Optional	Description
-authid	Required	References the custom alias you give to a specific account-role combination.
-p	Required when a default project has not been specified by the project command or when you want to specify a project other than the default. For more information, see project .	References the folder or ZIP file with your SuiteCloud project.
-applyinstallprefs	Required when locking.xml, hiding.xml, and overwriting.xml exist in the InstallationPreferences folder of a SuiteApp project.	Indicates whether installation preferences should be applied. For more information, see the help topic Installation Preferences in the SuiteApp of SuiteCloud Project .
-accountsspecificvalues	Optional	Indicates how to handle account-specific values in an account customization project. If you set this to WARNING and there are account-specific values in the project, you get a warning but deployment continues. If you set this to ERROR and there are account-specific values in the project, you get an error message and deployment stops. For more information, see the help topic Account-Specific Values Validation in SuiteCloud Projects .  Important: If you don't specify the accountsspecificvalues option, it acts the same as if you passed ERROR.
-l	Optional	Specifies the deployment log file location as a directory path or a file name. If you specify a directory, the log file is created there by default. Deployment log details are added to the end of the file.
-np	Optional	Skips the preview step.
-v	Optional	Starts client-side project validation. Deployment stops if any errors occur during this process.
-sw	Optional	Removes the warning you get before deploying to a production account.

-h or -help	Optional	Prints the help for this command.
-------------	----------	-----------------------------------

Example

Here's a command that deploys a SuiteCloud project to an account and creates a deployment log:

```
sdfcli deploy -authid AuthId -p c:/project/ -l d:/path/test.log -np -v
```

When you run the command, it produces an output that is similar to the following:

```

1 SuiteCloud Development Framework CLI (com.netsuite.ide.core_2021.1.0)
2 Enter password:
3 Deploy "c:\project".
4 2021-04-02 11:08:23 (PST) Installation started
5 Info -- Account [(PRODUCTION) Wolfe Electronics]
6 Info -- Account Customization Project [Project]
7 Info -- Framework Version [1.0]
8 Validate manifest -- Success
9 Validate deploy file -- Success
10 Validate configuration -- Success
11 Validate script file -- Success
12 Validate objects -- Success
13 Validate resource files -- Success
14 Validate account settings -- Success
15 Begin deployment
16 2021-04-02 11:08:23 (PST) Installation COMPLETE (0 minutes 1 second)
17
18 Writing to log file d:\path\test.log.
```

importbundle



Note: SuiteBundler is still supported, but it won't be updated with any new features.

To take advantage of new features for packaging and distributing customizations, you can use the Copy to Account and SuiteCloud Development (SDF) features instead of SuiteBundler.

Copy to Account is an administrator tool that you can use to copy objects between your accounts. The tool can copy one object at a time, including dependencies and data. For more information, see the help topic [Copy to Account](#).

SuiteCloud Development Framework is a development framework that you can use to create SuiteApps from an integrated development environment (IDE) on your local computer. For more information, see the help topic [SuiteCloud Development Framework](#).

Imports a customization bundle from your NetSuite account and turns it into an account customization project. For more information, see the help topic [Conversion of a Bundle to an Account Customization Project for SDF](#).

Syntax

```

1 sdfcli importbundle <-bundleid BundleID>
2   <-authid AuthId>
3   [-p FolderOrZipFile]
```

Options

Option	Required / Optional	Description
-bundleid	Required	Specifies the ID of the bundle to import.
-authid	Required	References the custom alias you give to a specific account-role combination.
-p	Required when a default project has not been specified by the project command or when you want to specify a project other than the default. For more information, see project .	References the folder or ZIP file with your SuiteCloud project.
-h or -help	Optional	Prints the help for this command.

Example

Here's a command that imports a bundle and creates an account customization project:

```
sdfcli importbundle -bundleid 123 -authid AuthId -p c:/SDFproject
```

When you run the command, it produces an output that is similar to the following:

```

1 SuiteCloud Development Framework CLI (com.netsuite.ide.core_2021.1.0)
2 Existing files will be overwritten, do you want to continue? Type YES to continue.
3 YES
4 Importing bundle with id 123 to path: "C:\SDFproject".
5 The following bundle component(s) were imported.
6 Objects\customlist_sample_cust_list_1.xml
```

importconfiguration

Imports the feature configuration from your NetSuite account to the account customization project, so you can enable or disable features in the project.

Syntax

```

1 sdfcli importconfiguration <-configurationid ConfigID>
2   <-authid AuthId>
3   [-p FolderOrZipFile]
```

Options

Option	Required / Optional	Description
-configurationid	Required	Specifies the configuration to import. This value should be set to FEATURES:ALL_FEATURES. You can only import the configuration for all features.
-authid	Required	References the custom alias you give to a specific account-role combination.
-p	Required when a default project has not been specified by the project command or	References the folder or ZIP file with your SuiteCloud project.

	when you want to specify a project other than the default. For more information, see project .	
-h or -help	Optional	Prints the help for this command.

Example

Here's a command that imports the feature configuration from your NetSuite account to an account customization project:

```
sdfcli importconfiguration -configurationid FEATURES:ALL_FEATURES -authid AuthId -p c:/SDFproject
```

When you run the command, it produces an output that is similar to the following:

```
1 | SuiteCloud Development Framework CLI (com.netsuite.ide.core_2021.1.0)
2 | The following objects were imported successfully:
3 | FEATURES:ALL_FEATURES
```

importfiles

Imports files from your NetSuite account to the account customization project.

Syntax

```
1 | sdfcli importfiles <-paths FileCabinetPath1 [FilePathCabinet2] [...]>
2 | <-authid AuthId>
3 | [-p FolderOrZipFile]
4 | [-excludeproperties]
```

Options

Option	Required / Optional	Description
-paths	Required	Specifies the File Cabinet path or paths that have the files you want to import.  Important: Wildcards are not supported.
-authid	Required	References the custom alias you give to a specific account-role combination.
-p	Required when a default project has not been specified by the project command or when you want to specify a project other than the default. For more information, see project .	References the folder or ZIP file with your SuiteCloud project.
-excludeproperties	Optional	Excludes the file and folder properties specified in your NetSuite account. If you specify this option, the .attributes folder is not created.
-h or -help	Optional	Prints the help for this command.

Example

Here's a command that imports a file from a NetSuite account into a specified SuiteCloud project:

```
sdfcli importfiles -paths "/SuiteScripts/test.js" -authid AuthId -p c:/project/
```

When you run the command, it prompts you to overwrite any existing files in your SuiteCloud project and produces output that is similar to the following:

```
1 SuiteCloud Development Framework CLI (com.netsuite.ide.core_2021.1.0)
2 Existing files will be overwritten, do you want to continue? Type YES to continue.
3 YES
4 Done
```

importobjects

Imports SDF custom objects from your NetSuite account to your SuiteCloud project. By default in account customization projects (ACP), if SuiteScript files are referenced in the SDF custom objects you import, those files get imported too.

Syntax

```
1 sdfcli importobjects <-destinationfolder DestinationPath>
2   <-scriptid ScriptID1 [ScriptID2] [...]>
3   <-type CustomObjectType>
4   <-authid AuthId>
5   [-p FolderOrZipFile]
6   [-appid QualifiedAppID]
```

Options

Option	Required / Optional	Description
-destinationfolder	Required	Indicates where SDF custom objects are saved. Use a folder path that's relative to your SuiteCloud project. It has to start with /objects.
-scriptid	Required	Imports the SDF custom objects that are associated with the specified scripts IDs.
-type	Required	Imports the SDF custom objects that are associated with the specified custom script types. Use ALL to import SDF custom objects of all custom script types.
-authid	Required	References the custom alias you give to a specific account-role combination.
-p	Required when a default project has not been specified by the project command or when you want to specify a project other than the default. For more information, see project .	References the folder or ZIP file with your SuiteCloud project.
-appid	Optional	References the application ID of the SDF SuiteApp. The application ID is a fully qualified name like <publisherid>.<projectid>. For example,

		com.netsuite.mysuiteapp or org.mycompany.helloworld are valid app IDs. If you specify an application ID, only SDF custom objects linked to that app ID are imported. Otherwise, only SDF custom objects not linked to an app ID are imported. For information about the SuiteApp application ID, see the help topic SuiteApp Application ID.
-excludefiles	Optional	Indicates that the SuiteScript files referenced in the SDF custom objects are not imported. This option can only be used in account customization projects (ACP). If this option is not specified, the SuiteScript files referenced in the imported SDF custom objects are get imported too.
-h or -help	Optional	Prints the help for this command.

Example

Here's a command that imports two SDF custom objects, customlist2 and customrole1009, into a project.

```
sdfcli importobjects -destinationfolder "/Objects/subfolder" -scriptid customlist2
customrole1009 -type ALL -account 0000001 -p c:/project/ -authid AuthId -appid
org.mycompany.helloworldapp
```

When you run the command, it prompts you to overwrite any existing SDF custom objects in your SuiteCloud project and produces output that is similar to the following:

```
1 | SuiteCloud Development Framework CLI (com.netsuite.ide.core_2021.1.0)
2 | Existing objects will be overwritten, do you want to continue? Type YES to continue.
3 | YES
4 | The following objects were imported successfully:
5 | customlist:customlist2
6 | role:customrole1009
```

listbundles



Note: SuiteBundler is still supported, but it won't be updated with any new features.

To take advantage of new features for packaging and distributing customizations, you can use the Copy to Account and SuiteCloud Development (SDF) features instead of SuiteBundler.

Copy to Account is an administrator tool that you can use to copy objects between your accounts. The tool can copy one object at a time, including dependencies and data. For more information, see the help topic [Copy to Account](#).

SuiteCloud Development Framework is a development framework that you can use to create SuiteApps from an integrated development environment (IDE) on your local computer. For more information, see the help topic [SuiteCloud Development Framework](#).

Lists the customization bundles created in your NetSuite account. For more information, see the help topic [Conversion of a Bundle to an Account Customization Project for SDF](#).

Syntax

```
1 | sdfcli listbundles <-authid AuthId>
```

Options

Option	Required / Optional	Description
-authid	Required	References the custom alias you give to a specific account-role combination.
-h or -help	Optional	Prints the help for this command.

Example

Here's a command that lists all the bundles in a NetSuite account:

```
sdfcli listbundles -authid AuthId
```

When you run the command, it produces an output that is similar to the following:

```
1 | SuiteCloud Development Framework CLI (com.netsuite.ide.core_2021.1.0)
2 | 123455:My Test Bundle
3 | 123456:Managed Bundle to Production
```

listconfiguration

Lists the configuration types you can import from your NetSuite account.

Syntax

```
1 | sdfcli listconfiguration <-authid AuthId>
```

Options

Option	Required / Optional	Description
-authid	Required	References the custom alias you give to a specific account-role combination.
-h or -help	Optional	Prints the help for this command.

Example

Here's a command that lists the configuration types that you can import from your account:

```
sdfcli listconfiguration -authid AuthId
```

When you run the command, it produces an output that is similar to the following:

```

1 | SuiteCloud Development Framework CLI (com.netsuite.ide.core_2021.1.0)
2 | FEATURES:ALL_FEATURES:Enable Features

```

listfiles

Lists the files in the File Cabinet of your NetSuite account.

Syntax

```

1 | sdfcli listfiles <-authid AuthId>
2 |   <-folder FileCabinetPath1 [FileCabinetPath2] [...]>

```

Options

Option	Required / Optional	Description
-folder	Required	Specifies the File Cabinet folder that contains the files to list. It also lists files in any subfolders.
-authid	Required	References the custom alias you give to a specific account-role combination.
-h or -help	Optional	Prints the help for this command.

Example

Here's a command that lists the files in your NetSuite's account File Cabinet:

```
sdfcli listfiles -folder "/SuiteScripts" -authid AuthId
```

When you run the command, it produces an output that is similar to the following:

```

1 | SuiteCloud Development Framework CLI (com.netsuite.ide.core_2021.1.0)
2 | /SuiteScripts/file1.js
3 | /SuiteScripts/file2.js
4 | /SuiteScripts/file3.js
5 | /SuiteScripts/file4.js
6 | /SuiteScripts/RunTimeFiles/document.pdf
7 | /SuiteScripts/RunTimeFiles/data.csv
8 | /SuiteScripts/RunTimeFiles/log.txt
9 | /SuiteScripts/RunTimeFiles/sample.txt
10 | /SuiteScripts/RunTimeFiles/test.xml

```

listmissingdependencies

Lists any missing dependencies in your SuiteCloud project.

Syntax

```

1 | sdfcli listmissingdependencies <-authid AuthId>
2 |   [-l DependencyListFileName]

```

3 | [-p FolderOrZipFile]

Options

Option	Required / Optional	Description
-authid	Required	References the custom alias you give to a specific account-role combination.
-l	Optional	Specifies the missing dependency log file location as a directory path or a file name. If you specify a directory, the log file is created there by default. Missing dependency log details are added to the end of the file.
-p	Required when a default project has not been specified by the project command or when you want to specify a project other than the default. For more information, see project .	References the folder or ZIP file with your SuiteCloud project.
-h or -help	Optional	Prints the help for this command.

Example

Here's a command that lists the missing dependencies in a SuiteCloud project:

```
sdfcli listmissingdependencies -p c:/project/ -l test.log
```

The command outputs a list of missing dependencies for the project located in `c:/project`, and writes the list to `test.log`.

When you run the command, it produces an output that is similar to the following:

```
1 | SuiteCloud Development Framework CLI (com.netsuite.ide.core_2021.1.0)
2 | Unresolved dependencies:
3 | Feature - CUSTOMRECORDS:required
4 | Object - customsearch51
5 | Writing to log file C:\sdfprojects\myproject\test.log.
```

The output says the feature CUSTOMRECORDS is required, so you need to enable that feature in the manifest. The object customsearch51 is a missing dependency. To fix it, add customsearch51 to the project or reference it in the manifest. The command writes the list to `test.log` in the SDF CLI installation directory.

listobjects

Lists the SDF custom objects in your NetSuite account.

Syntax

```
1 | sdfcli listobjects <-authid AuthId>
2 |   [-p FolderOrZipFile]
3 |   [-appid QualifiedAppID]
4 |   [-scriptid ScriptID]
5 |   [-type CustomObjectType1 [CustomObjectType2] [...]]
```

Options

Option	Required / Optional	Description
-authid	Required	References the custom alias you give to a specific account-role combination.
-p	Required when a default project has not been specified by the project command or when you want to specify a project other than the default. For more information, see project .	References the folder or ZIP file with your SuiteCloud project.
-appid	Optional	References the application ID of the SDF SuiteApp. The application ID is a fully qualified name like <publisherid>.<projectid>. For example, com.netsuite.mysuiteapp or org.mycompany.helloworld are valid app IDs. If you specify an application ID, only SDF custom objects linked to that app ID are listed. Otherwise, only SDF custom objects not linked to an app ID are listed. For information about the SuiteApp application ID, see the help topic SuiteApp Application ID.
-scriptid	Optional	Lists the SDF custom objects with script IDs that match or contain the string you specify. If you use this with the -type option, the list is also filtered by the -type criteria. If you don't use -scriptid or -type, all SDF custom objects are listed.
-type	Optional	Lists the SDF custom objects that are associated with the specified custom NetSuite types. If you use this with the -scriptid option, the list is also filtered by the -scriptid criteria. If you don't use -scriptid or -type, all SDF custom objects are listed.
-h or -help	Optional	Prints the help for this command.

Example

Here's a command that lists the SDF custom objects in your NetSuite account:

```
sdfcli listobjects -authid AuthId -p c:/project/ -appid org.mycompany.helloworldapp -scriptid 9
-type customlist role savedsearch
```

When you run the command, it produces an output that is similar to the following:

```
1 SuiteCloud Development Framework CLI (com.netsuite.ide.core_2021.1.0)
2 customlist:customlist19
3 customlist:customlist9
4 role:customrole1009
5 savedsearch:customsearch39
6 savedsearch:customsearch49
7 savedsearch:customsearch9
```

manageauth

Manages authentication IDs for all your projects. An authentication ID is a custom alias you give to a specific account-role combination.

Syntax

```
1 sdfcli manageauth
2   [-info AuthId]
3   [-list]
4   [-rename AuthId -renameto NewAuthId]
5   [-remove AuthId]
```

Options

Option	Required / Optional	Description
-info	Optional	Prints the following information for the specified authentication ID: account ID, role ID, and url. Usage: sdfcli manageauth -info.
-list	Optional	Prints a list of all the configured authentication IDs. Usage: sdfcli manageauth -list.
-remove	Optional	Removes an authentication ID. This option only removes the credentials locally and doesn't revoke the token from the account. Usage: sdfcli manageauth -remove {authId}.
-rename	Optional	Renames an authentication ID. Use it with the renameto option. Usage: sdfcli manageauth -rename {authId}.
-renameto	Required when the -rename option is specified.	Specifies the new ID for an authentication ID. Use it with the -rename option. Usage: sdfcli manageauth -rename {authId} -renameto {newAuthId}.
-h or -help	Optional	Prints the help for this command.

Example

When you run `sdfcli manageauth -list`, the command produces output that is similar to the following:

The following authentication IDs are available for your account: - AuthId | My Account - 123456 [Administrator] - AuthId | My Developer Account - 110010100 [Developer]

package

Generates a ZIP file from your project, following the structure specified in the `deploy.xml` file. You can use this command for both account customization and SuiteApp projects.

Syntax

```
1 | sdfcli package <-destination destinationFolder>
2 |     <-project projectFolder>
```

Options

Option	Required / Optional	Description
-d or -destination	Required	Specifies a path to store the ZIP file containing your project.
-p or -project	Required	Specifies the preview log file location as a directory path or a file name. If you specify a directory, the log file is created there by default. Preview log details are added to the end of the file.
-h or -help	Optional	Prints the help for this command.

Example

Here's a command that creates a ZIP file with a SuiteCloud project and stores it in a specific folder:

```
sdfcli package -d C:\sdfProjects -p C:\sdfProjects\projectACP
```

When you run the command, it produces an output that is similar to the following:

```
1 | The projectACP-2020-08-17_14-50-23.zip file has been successfully created.
```

preview

Previews the deployment steps of a folder or ZIP file with your SuiteCloud project.

The SuiteCloud project gets zipped before previewing.

Syntax

```
1 | sdfcli preview <-authid AuthId>
2 | [-p FolderOrZipFile]
3 | [-applyinstallprefs]
4 | [-l LogPathOrFile]
```

Options

Option	Required / Optional	Description
-authid	Required	References the custom alias you give to a specific account-role combination.
-p	Required when a default project has not been specified by the project command or when you want to specify a project other than the default. For more information, see project .	References the folder or ZIP file with your SuiteCloud project.

-applyinstallprefs	Required when locking.xml, hiding.xml, and overwriting.xml exist in the InstallationPreferences folder of a SuiteApp project.	Indicates whether installation preferences should be applied. For more information, see the help topic Installation Preferences in the SuiteApp of SuiteCloud Project .
-l	Optional	Specifies the preview log file location as a directory path or a file name. If you specify a directory, the log file is created there by default. Previews log details are added to the end of the file.
-h or -help	Optional	Prints the help for this command.

Example

Here's a command that previews deployment steps for your SuiteCloud project and stores them in a log file:

```
sdfcli preview -authid AuthId -p c:/project/ -l d:/path/test.log
```

When you run the command, it produces an output that is similar to the following:

```

1 | SuiteCloud Development Framework CLI (com.netsuite.ide.core_2021.1.0)
2 | Preview "c:\project".
3 | Validate manifest -- Success
4 | Validate deploy file -- Success
5 | Validate configuration -- Success
6 | Validate script file -- Success
7 | Validate objects -- Success
8 | Validate resource files -- Success
9 | Validate account settings -- Success
10 | Deployment preview
11 | Upload file -- ~/FileCabinet/SuiteScripts/UserEventScript.js

```

project

Sets the default project folder or ZIP file for SuiteCloud CLI.

If you run this command without the -p option, it shows the current default project or ZIP file.

If you've set a default project, you don't need to specify a project when using CLI commands.

Syntax

```
1 | sdfcli project [-p FolderOrZipFile]
```

Options

Option	Required / Optional	Description
--------	---------------------	-------------

-p	Required when specifying a default project.	Sets the default folder or ZIP file for your SuiteCloud project. When specified, you don't need to specify the -p option in most other CLI commands unless you want to reference a different project folder or ZIP file.
-h or -help	Optional	Prints the help for this command.

Example

Here's a command that sets a default project based on a specific path:

```
sdfcli project -p c:/project/
```

When you run the command, it produces an output that is similar to the following:

```
1 | SuiteCloud Development Framework CLI (com.netsuite.ide.core_2020.1.0)
2 | Default project folder set to c:\project.
```

update

Updates the SDF custom objects in your SuiteCloud project folder with the matching ones from your NetSuite account.

Syntax

```
1 | sdfcli update <-scriptid scriptID1 [scriptID2] [...]>
2 |   <-authid AuthId>
3 |   [-p FolderOrZipFile]
```

Options

Option	Required / Optional	Description
-scriptid	Required	Lists the script IDs of the SDF custom objects to update.
-authid	Required	References the custom alias you give to a specific account-role combination.
-p	Required when a default project has not been specified by the project command or when you want to specify a project other than the default. For more information, see project .	References the folder or ZIP file with your SuiteCloud project.
-h or -help	Optional	Prints the help for this command.

Example

Here's a command that checks for updates to an object in a NetSuite account (if it exists) and updates the SDF custom object in your SuiteCloud project:

```
sdfcli update -scriptid customrecord_test1 customrecord_test2 -authid AuthId -p c:/project/
```

When you run the command, it produces an output that is similar to the following:

```

1 | SuiteCloud Development Framework CLI (com.netsuite.ide.core_2021.1.0)
2 | customrecord_test1 updated.
3 | customrecord_test2 updated.

```

updatecustomrecordwithinstances

Updates the SDF custom object and its instances.

Only the first 100 instances are updated, based on their order of creation.

Syntax

```

1 | sdfcli updatecustomrecordwithinstances <-authid AuthId>
2 |   [-p FolderOrZipFile]
3 |   <-scriptid ScriptID>

```

Options

Option	Required / Optional	Description
-scriptid	Required	The script ID of the SDF custom object. The script ID has to start with customrecord.
-authid	Required	References the custom alias you give to a specific account-role combination.
-p	Required when a default project has not been specified by the project command or when you want to specify a project other than the default. For more information, see project .	References the folder or ZIP file with your SuiteCloud project.
-h or -help	Optional	Prints the help for this command.

Example

Here's a command that updates the SDF custom object and all its instances, if they exist:

```
sdfcli updatecustomrecordwithinstances -scriptid customrecord10 -authid AuthId -p c:/project
```

When you run the command, it prompts you to overwrite any existing SDF custom objects in your SuiteCloud project and produces output that is similar to the following:

```

1 | SuiteCloud Development Framework CLI (com.netsuite.ide.core_2021.1.0)
2 | Existing Custom Record will be overwritten, do you want to continue? Type YES to continue.
3 | YES
4 | Custom record "customrecord10" has been updated with custom record instances included.

```

uploadfiles

Uploads one or more files from a SuiteCloud project to your account's File Cabinet. If the folder with the files doesn't already exist in the File Cabinet, it gets added to your account.

Syntax

```
1 sdfcli uploadfile <-authid AuthId>
2   [-project FolderOrZipFile]
3   <-paths FilePath1 [FilePathCabinet2] [...]>
```

Options

Option	Required / Optional	Description
-paths	Required	Specifies the file path or paths for the files you want to upload. To upload multiple files, put a space between each path and wrap the whole argument in double quotes. For example: <code>"/SuiteScripts/myscripts/sample.js"</code>.  Note: The path has to start with a forward slash (/).
-authid	Required	References the custom alias you give to a specific account-role combination.
-project	Required when a default project has not been specified by the project command or when you want to specify a project other than the default. For more information, see project .	References the folder or ZIP file with your SuiteCloud project.
-h or -help	Optional	Prints the help for this command.

Example

Here's a command that uploads a file from a SuiteCloud project into an account:

```
sdfcli uploadfiles -paths "/SuiteScripts/test.js" -authid AuthId -project c:/project/
```

uploadfolders

Uploads all the files in one or more folders from a SuiteCloud project to your account's File Cabinet. If the folder doesn't already exist in the File Cabinet, it gets added to your account.

All files in the specified folder, including subfolders, are uploaded recursively.

Syntax

```
1 sdfcli uploadfolders <-authid AuthId>
2   [-project FolderOrZipFile]
3   <-paths FolderPath1 [FolderPathCabinet2] [...]>
```

Options

Option	Required / Optional	Description
--------	---------------------	-------------

-paths	Required	Sets the path or paths for the folders you want to upload. To upload multiple folders, put a space between each path and wrap the whole argument in double quotes. For example: <code>"/SuiteScripts" "/SuiteScripts/Test"</code>.  Note: The path has to start with a forward slash (/).
-authid	Required	References the custom alias you give to a specific account-role combination.
-project	Required when a default project has not been specified by the project command or when you want to specify a project other than the default. For more information, see project .	References the folder or ZIP file with your SuiteCloud project.
-h or -help	Optional	Prints the help for this command.

Example

Here's a command that uploads a folder from a SuiteCloud project into an account:

```
sdfcli uploadfolder -paths "/SuiteScripts" -authid AuthId -project c:/project/
```

validate

Validates the folder or ZIP file with your SuiteCloud project.

Syntax

```

1  sdfcli validate <-authid AuthId>
2  [-p FolderOrZipFile]
3  [-applyinstallprefs]
4  [-l LogFile]
5  [-server]
6  [-accountspecificvalues (WARNING|ERROR)]

```

Options

Option	Required / Optional	Description
-authid	Required	References the custom alias you give to a specific account-role combination.
-p	Required when a default project has not been specified by the project command or when you want to specify a project other than the default. For more information, see project .	References the folder or ZIP file with your SuiteCloud project.
-applyinstallprefs	Required when <code>locking.xml</code> , <code>hiding.xml</code> , and <code>overwriting.xml</code> exist in the	Indicates whether installation preferences should be applied.

	InstallationPreferences folder of a SuiteApp project.	For more information, see the help topic Installation Preferences in the SuiteApp of SuiteCloud Project .
-accountspecificvalues	Optional	Indicates how to handle account-specific values in an account customization project. The default value is ERROR. If the argument value is WARNING and there are account-specific values in the project, you'll get a warning. If the argument value is ERROR and there are account-specific values in the project, you'll get an error. For more information, see the help topic Account-Specific Values Validation in SuiteCloud Projects.
-l	Optional	Specifies the validation log file location as a directory path or a file name. If you specify a directory, the log file is created there by default. Validation log details are added to the end of the file.
-server	Optional	Indicates that validation should be performed on the server. You have to be authenticated to do this. If you don't use this option, client-side validation is performed.
-h or -help	Optional	Prints the help for this command.

Example One

Here's a command that performs a server-side validation on a project folder:

```
sdfcli validate -authid AuthId -p c:/project/ -l d:/path/test.log -server
```

When you run the command, it produces an output that is similar to the following:

```

1 SuiteCloud Development Framework CLI (com.netsuite.ide.core_2021.1.0)
2 Validating using account (0000001).
3 Validate manifest -- Success
4 Validate deploy file -- Success
5 Validate configuration -- Success
6 Validate script file -- Success
7 Validate objects -- Success
8 Validate resource files -- Success
9 Validate account settings -- Failed
10 *** ERROR ***
11
12 Validation of account settings failed.
13
14 An error occurred during account settings validation.
15 Details: The manifest contains a dependency on customrecord_tutorial object, but it is not in the account.
16
```

```

17 | No errors found.
18 | Writing to log file C:\path\test.log.

```

Example Two

Here's a command that performs a client-side validation on a project folder:

```
sdfcli validate -authid AuthId -p c:/project/ -l d:/path/test.log
```

When you run the command, it produces an output that is similar to the following:

```

1 | SuiteCloud Development Framework CLI (com.netsuite.ide.core_2021.1.0)
2 | Validating using client-side SDF metadata.
3 | Updating SDF metadata.
4 | SDF metadata updated.
5 | Warnings for file c:\sdfprojects\SDFTutorialFromHelp\Objects\customrecord_tutorial.xml.
6 |   - Line No. 13 - Error Message: The "enabledle" field depends on the "EXTREMELIST" feature.
7 |     The manifest must define the "EXTREMELIST" feature as required or Optional
8 |   - Line No. 15 - Error Message: The "enablemailmerge" field depends on the "MAILMERGE" feature.
9 |     The manifest must define the "MAILMERGE" feature asrequired or Optional
10 | Writing to log file C:\path\test.log.

```