



ORACLE
NetSuite

Workbook Builder Plug-in



2025.2

September 3, 2025



Copyright © 2005, 2025, Oracle and/or its affiliates.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software, software documentation, data (as defined in the Federal Acquisition Regulation), or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software," "commercial computer software documentation," or "limited rights data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle®, Java, and MySQL are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

If this document is in public or private pre-General Availability status:

This documentation is in pre-General Availability status and is intended for demonstration and preliminary use only. It may not be specific to the hardware on which you are using the software. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to this documentation and will not be responsible for any loss, costs, or damages incurred due to the use of this documentation.

If this document is in private pre-General Availability status:

The information contained in this document is for informational sharing purposes only and should be considered in your capacity as a customer advisory board member or pursuant to your pre-General Availability trial agreement only. It is not a commitment to deliver any material, code, or functionality, and should not be relied upon in making purchasing decisions. The development, release, timing, and pricing of any features or functionality described in this document may change and remains at the sole discretion of Oracle.

This document in any form, software or printed matter, contains proprietary information that is the exclusive property of Oracle. Your access to and use of this confidential material is subject to the terms and conditions of your Oracle Master Agreement, Oracle License and Services Agreement, Oracle PartnerNetwork Agreement, Oracle distribution agreement, or other license agreement which has been executed by you and Oracle and with which you agree to comply. This document and information contained herein may not be disclosed, copied, reproduced, or distributed to anyone outside Oracle without prior written consent of Oracle. This document is not part of your license agreement nor can it be incorporated into any contractual agreement with Oracle or its subsidiaries or affiliates.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <https://www.oracle.com/corporate/accessibility>.

Access to Oracle Support

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

Sample Code

Oracle may provide sample code in SuiteAnswers, the Help Center, User Guides, or elsewhere through help links. All such sample code is provided "as is" and "as available", for use only with an authorized NetSuite Service account, and is made available as a SuiteCloud Technology subject to the SuiteCloud Terms of Service at www.netsuite.com/tos.

Oracle may modify or remove sample code at any time without notice.

No Excessive Use of the Service

As the Service is a multi-tenant service offering on shared databases, Customer may not use the Service in excess of limits or thresholds that Oracle considers commercially reasonable for the Service. If Oracle reasonably concludes that a Customer's use is excessive and/or will cause immediate or ongoing performance issues for one or more of Oracle's other customers, Oracle may slow down or throttle Customer's excess use until such time that Customer's use stays within reasonable limits. If Customer's particular usage pattern requires a higher limit or threshold, then the Customer should procure a subscription to the Service that accommodates a higher limit and/or threshold that more effectively aligns with the Customer's actual usage pattern.

Beta Features

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software" or "commercial computer software documentation" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

This documentation is in pre-General Availability status and is intended for demonstration and preliminary use only. It may not be specific to the hardware on which you are using the software. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to this documentation and will not be responsible for any loss, costs, or damages incurred due to the use of this documentation.

The information contained in this document is for informational sharing purposes only and should be considered in your capacity as a customer advisory board member or pursuant to your pre-General Availability trial agreement only. It is not a commitment to deliver any material, code, or functionality, and should not be relied upon in making purchasing decisions. The development, release, and timing of any features or functionality described in this document remains at the sole discretion of Oracle.

This document in any form, software or printed matter, contains proprietary information that is the exclusive property of Oracle. Your access to and use of this confidential material is subject to the terms and conditions of your Oracle Master Agreement, Oracle License and Services Agreement, Oracle PartnerNetwork Agreement, Oracle distribution agreement, or other license agreement which has been executed by you and Oracle and with which you agree to comply. This document and information contained herein may not be disclosed, copied, reproduced, or distributed to anyone outside Oracle without prior written consent of Oracle. This document is not part of your license agreement nor can it be incorporated into any contractual agreement with Oracle or its subsidiaries or affiliates.

Table of Contents

Workbook Builder Plug-in Interface Overview	1
Developing a Workbook Builder Plug-in	1
Enabling Features for a Workbook Builder Plug-in	1
Creating a Workbook Builder Plug-in Script File	2
Guidelines for Creating a Workbook Builder Plug-in Implementation Script File	4
Administering a Workbook Builder Plug-in	5
Adding the Plug-in Implementation	5
Workbook Builder Plug-in Interface Definition	7
createWorkbook(context)	7
description	11
name	11
owner	11
role	11
workbook	12

Workbook Builder Plug-in Interface Overview



Important: The Workbook Builder Plug-in interface uses SuiteScript 2.0 or SuiteScript 2.1. Your entry point scripts and supporting library scripts must also use SuiteScript 2.0 or SuiteScript 2.1. For information, see the help topics [SuiteScript 2.x Script Creation Process](#), [SuiteScript 2.x](#), and [SuiteScript 2.1](#).

Use a Workbook Builder Plug-in to customize the creation of workbooks for the Workbook API. For more information about the Workbook API, see the following help topics:

- [Workbook API](#)
- [N/dataset Module](#)
- [N/workbook Module](#)

Workbook Builder Plug-ins let you create custom workbooks that fit your business needs. You can override the `createWorkbook()` function and create a workbook that contains a specific subset of data or uses custom logic. For example, you can create a workbook based on user-specific or role-specific information. The default behavior in the N/workbook module does not permit you to do this. Workbooks you create using the N/workbook module are static and cannot use dynamic information such as the current role, current user, and so on.

You can create custom workbooks that suit your needs by customizing the core plug-in logic. To accommodate this process, NetSuite provides an interface definition that describes the name, parameters, and return type of each function defined in the plug-in's interface. For details, see [Workbook Builder Plug-in Interface Definition](#).

Workbook Builder Plug-ins are supported by SuiteCloud Development Framework (SDF). SDF enables you to customize your NetSuite account from an integrated development environment (IDE) on your local computer. For details, see .

You can customize a Workbook Builder Plug-in in SDF by defining `workbookbuilderplugin` objects. For details, see the help topic [workbookbuilderplugin](#).

For more information about Workbook Builder Plug-ins, see the following help topics:

NetSuite Role	Help Topics
Developer	Developing a Workbook Builder Plug-in
Administrator	Administering a Workbook Builder Plug-in

Developing a Workbook Builder Plug-in

To develop a Workbook Builder Plug-in, complete the following steps:

1. Enable the required features for a Workbook Builder Plug-in. See [Enabling Features for a Workbook Builder Plug-in](#).
2. Create a Workbook Builder Plug-in script file. See [Creating a Workbook Builder Plug-in Script File](#).

Enabling Features for a Workbook Builder Plug-in

To begin development or administration for a Workbook Builder Plug-in, make sure that the Server SuiteScript and Workbook API features are enabled in the development account.

To enable features for the plug-in:

1. Go to Setup > Company > Enable Features.
2. Click the **SuiteCloud** subtab.
3. In the **SuiteScript** section, check the **Server SuiteScript** and **Workbook API** boxes.

Creating a Workbook Builder Plug-in Script File

You must implement each Workbook Builder Plug-in interface function in a JavaScript file (with a .js extension). You can use SuiteCloud IDE, another JavaScript IDE, or a text editor to create the plug-in implementation script file.

The following is a Workbook Builder Plug-in sample:

```

1  /**
2   * @NApiVersion 2.x
3   * @NScriptType workbookbuilderplugin
4   */
5  define(['N/workbook', 'N/dataset'], function(wb, ds) {
6      return Object.freeze({
7          createWorkbook: function(context) {
8              var dataset = ds.load({
9                  id: 'customscript_dataset'
10             });
11             var idExpr = dataset.getExpressionFromColumn({
12                 alias: 'id'
13             });
14             var sort = wb.createSort({
15                 ascending: false
16             });
17             var col1 = wb.createTableColumn({
18                 datasetColumnAlias: 'id'
19             });
20             var col2 = wb.createTableColumn({
21                 datasetColumnAlias: 'name'
22             });
23             var col3 = wb.createTableColumn({
24                 datasetColumnAlias: 'date'
25             });
26             var col4 = wb.createTableColumn({
27                 datasetColumnAlias: 'total'
28             });
29             var tableview = wb.createTable({
30                 id: 'view',
31                 name: 'View',
32                 dataset: dataset,
33                 columns: [col1, col2, col3, col4]
34             });
35             var rowItem = wb.createDataDimensionItem({
36                 label: 'A',
37                 expression: dataset.getExpressionFromColumn({
38                     alias: 'date'
39                 })
40             });
41             var rowDataDimension = wb.createDataDimension({
42                 items: [rowItem]
43             });
44             var rowSection = wb.createSection({
45                 children: [rowDataDimension]
46             });
47             var columnItem = wb.createDataDimensionItem({
48                 label: 'B',
49                 expression: dataset.getExpressionFromColumn({
50                     alias: 'total'
51                 })
52             });
53             var columnDataDimension = wb.createDataDimension({
54                 items: [columnItem]

```

```

55     });
56     var columnMeasure = wb.createDataMeasure({
57         label: 'M',
58         expression: idExpr,
59         aggregation: wb.Aggregation.MAX
60     });
61     var columnSection = wb.createSection({
62         children: [columnDataDimension, columnMeasure]
63     });
64     var constExpr = wb.createConstant(1);
65     var anyOfExpr = wb.createExpression({
66         functionId: wb.ExpressionType.ANY_OF,
67         parameters: {
68             expression: idExpr,
69             set: [constExpr]
70         }
71     });
72     var notExpr = wb.createExpression({
73         functionId: wb.ExpressionType.NOT,
74         parameters: {
75             expression: anyOfExpr
76         }
77     });
78     var allSubNodesSelector = wb.DescendantOrSelfNodesSelector;
79     var rowItemSelector = wb.createDimensionSelector({
80         dimension: rowDataDimension
81     });
82     var columnItemSelector = wb.createDimensionSelector({
83         dimension: columnDataDimension
84     });
85     var rowSelector = wb.createPathSelector({
86         elements: [allSubNodesSelector, rowItemSelector]
87     });
88     var columnSelector = wb.createPathSelector({
89         elements: [allSubNodesSelector, columnItemSelector]
90     });
91     var rowSort = wb.createSortByDataDimensionItem({
92         item: rowItem,
93         sort: sort
94     });
95     var columnSort = wb.createSortByMeasure({
96         measure: columnMeasure,
97         sort: sort,
98         otherAxisSelector: allSubNodesSelector
99     });
100    var rowSortDefinition = wb.createSortDefinition({
101        sortBy: [rowSort],
102        selector: rowSelector
103    });
104    var columnSortDefinition = wb.createSortDefinition({
105        sortBy: [columnSort],
106        selector: columnSelector
107    });
108    var rowAxis = wb.createPivotAxis({
109        root: rowSection,
110        sortDefinitions: [rowSortDefinition]
111    });
112    var columnAxis = wb.createPivotAxis({
113        root: columnSection,
114        sortDefinitions: [columnSortDefinition]
115    });
116    var limitingFilter = wb.createLimitingFilter({
117        row: true,
118        filteredNodesSelector: rowSelector,
119        limit: 1,
120        sortBy: [rowSort]
121    });
122    var conditionalFilter = wb.createConditionalFilter({
123        row: false,
124        rowSelector: rowSelector,
125        columnSelector: columnSelector,
126        measure: columnMeasure,
127        predicate: notExpr

```



```

128     });
129     var pivot = wb.createPivot({
130         id: 'pivot',
131         name: 'Pivot',
132         dataset: dataset,
133         rowAxis: rowAxis,
134         columnAxis: columnAxis,
135         filterExpressions: [notExpr],
136         aggregationFilters: [limitingFilter, conditionalFilter]
137     });
138     var firstAxis = wb.createChartAxis({
139         title: 'First axis'
140     });
141     var secondAxis = wb.createChartAxis({
142         title: 'Second axis'
143     });
144     var category = wb.createCategory({
145         axis: firstAxis,
146         root: rowSection
147     });
148     var legend = wb.createLegend({
149         axes: [secondAxis],
150         root: columnSection
151     });
152     var aspect = wb.createAspect({
153         measure: columnMeasure
154     });
155     var series = wb.createSeries({
156         aspects: [aspect]
157     });
158     var chart = wb.createChart({
159         id: 'chart',
160         name: 'Chart',
161         dataset: dataset,
162         category: category,
163         legend: legend,
164         series: [series]
165     });
166     var workbook = wb.create({
167         description: 'My Test Workbook',
168         name: 'Test Workbook',
169         tables: [tableview],
170         pivots: [pivot],
171         charts: [chart]
172     });
173     context.workbook = workbook;
174 }
175 });
176 });

```

Guidelines for Creating a Workbook Builder Plug-in Implementation Script File

The following guidelines apply when creating a Workbook Builder Plug-in implementation script file:

- If you create an invalid workbook using a Workbook Builder Plug-in, the workbook may produce an unexpected error in the SuiteAnalytics Workbook UI, or you may receive a "Workbook does not exist" or "Workbook is no longer available" error. These errors may occur if there are syntax or logic errors in the code used to create the workbook in the plug-in. The invalid workbook will appear in the list of available workbooks, but you will not be able to load it or work with any of its elements (such as table views and pivots).

To work around this issue, you should test your workbook creation code in the SuiteScript Debugger before using it in your plug-in implementation script file. When the workbook creation code is syntactically correct, the workbook will appear in the SuiteAnalytics Workbook UI. However, if the code includes logic errors, some elements (such as pivots or charts) may not be displayed correctly.

To test for syntax errors, copy your workbook creation code into the debugger and run it. The debugger will identify any syntax errors before executing the workbook creation code. To test for logic errors, run the workbook visualizations in the debugger using methods that are available for workbook visualization types. For example, you can use [Workbook.runPivot\(options\)](#) to test the creation of pivots in your workbook. If you do not receive errors in the debugger, your workbook creation code is safe to use in your plug-in implementation script file and will not produce errors in the SuiteAnalytics Workbook UI. For more information about the SuiteScript Debugger, see the help topic [SuiteScript Debugger](#).

- When you create a workbook using a Workbook Builder Plug-in, the workbook name in the SuiteAnalytics Workbook UI appears as the name of the plug-in deployment script record instead of the workbook name that is specified in the plug-in. The dataset name will appear as the dataset name that is specified in the plug-in.

The following general guidelines apply when creating a plug-in implementation script file:

- The plug-in script file can have any name, provided it has a .js extension and contains an implementation of each interface function.
- You can include utility files with helper functions when you create the plug-in implementation.
- Due to limitations with how strings are handled in NetSuite, you cannot use the JavaScript case statement in the plug-in implementation script file.
- The plug-in allows up to 1000 usage units. For more information, see the help topic [SuiteScript Governance and Limits](#).
- If the character limit is exceeded in a field, the value will be truncated.

Administering a Workbook Builder Plug-in

To install and set up a Workbook Builder Plug-in, complete the following steps:

1. Enable the required features for a Workbook Builder Plug-in. See [Enabling Features for a Workbook Builder Plug-in](#).
2. Add the plug-in implementation. See [Adding the Plug-in Implementation](#).

Adding the Plug-in Implementation

After you create the plug-in script file, upload the file to NetSuite.

To add the plug-in implementation:

1. Go to Customization > Plug-ins > Plug-in Implementations > New.
NetSuite displays the Upload Plug-in Implementation page.
2. Beside the **Script File** field, click the plus icon.
3. Click **Choose File**, then select the script file that contains your plug-in implementation.
4. Click **Save**.
5. Click **Create Plug-in Implementation**.
6. On the **Plug-in Implementation** page, enter the following information:

Field or Option	Description
Name	User-friendly name for the implementation.

Field or Option	Description
	This name appears in the plug-in implementation list.
ID	Internal ID for the implementation for use in scripting. If you do not provide an ID, NetSuite will provide one for you after you click Save . As a developer, when you write code that uses this implementation, you will reference the implementation using this ID.
Status	Current status for the implementation. Select Testing to have the implementation accessible to the owner of the implementation. Choose Released to have the implementation accessible in a production environment.
Log Level	Logging level for the script. Select Debug , Audit , Error , or Emergency . The log information appears on the Execution Log subtab for the implementation after you create it.
Execute As Role	Role that the script runs as. The Execute As Role field provides role-based granularity in terms of the permissions and restrictions of the executing script. Select Current Role to execute the script with the permissions of the currently logged-in NetSuite user. If you created a custom role, be sure to test using that role. You can then bundle the custom role to distribute it with the plug-in implementation.
Description	Description of the implementation. This field is optional.
Owner	User account that owns the implementation. The default value is the current user's account.
Inactive	Indicates whether the plug-in implementation is inactive and does not run in the account. For example, you can make a plug-in implementation inactive to temporarily disable it for testing purposes.

7. On the **Unhandled Errors** subtab, select which individual or individuals are notified if script errors occur. By default, the **Notify Script Owner** box is checked.



Tip: To enter multiple email addresses in the **Notify Emails** box, separate email addresses with a semicolon.

8. Click **Save**.

Workbook Builder Plug-in Interface Definition

The Workbook Builder Plug-in interface includes the following interface functions and context object properties:

Interface Function	Context Object Properties
<code>createWorkbook(context)</code>	description name owner role workbook

createWorkbook(context)

Function Declaration	<code>function createWorkbook(context)</code>
Type	Interface function
Description	Creates a workbook.
Returns	void
Input Parameters	context – A JavaScript object with the following properties: ■ <code>description</code> ■ <code>name</code> ■ <code>owner</code> ■ <code>role</code> ■ <code>workbook</code>

Example

```

1  /**
2   * @NApiVersion 2.x
3   * @NScriptType workbookbuilderplugin
4   */
5  define(['N/workbook', 'N/dataset', 'N/query'], function(wb, ds, query) {
6      return Object.freeze({
7          createWorkbook: function(context) {
8              var dataset = ds.load({
9                  id: "%s"
10             });
11
12             var idExpr = dataset.getExpressionFromColumn({
13                 alias: 'id'
14             });
15
16             var totalExpr = dataset.getExpressionFromColumn({
17                 alias: 'total'
18             });
19
20             var constExpr = wb.createConstant({

```

```

21         constant: 1,
22         type: wb.ConstantType.DECIMAL
23     });
24
25     var anyOfExpr = wb.createExpression({
26         functionId: wb.ExpressionType.ANY_OF,
27         parameters: {
28             expression: idExpr,
29             set: [constExpr]
30         }
31     });
32
33     var notExpr = wb.createExpression({
34         functionId: wb.ExpressionType.NOT,
35         parameters: {
36             operand1: anyOfExpr
37         }
38     });
39
40     var sort = wb.createSort({
41         ascending: false,
42         locale: query.SortLocale.EN_AU,
43         nullsLast: false,
44         caseSensitive: true
45     });
46
47     var tableViewFilter = wb.createTableColumnFilter({
48         operator: query.Operator.START_WITH_NOT,
49         values: ["test"]
50     });
51
52     var fieldContext = wb.createFieldContext({
53         name: 'RAW'
54     });
55
56     var fieldContext1 = wb.createFieldContext({
57         name: 'HIERARCHY'
58     });
59
60     var col1 = wb.createTableColumn({
61         datasetColumnAlias: 'id',
62         fieldContext: fieldContext
63     });
64
65     var col2 = wb.createTableColumn({
66         condition: wb.createTableColumnCondition({operator: "AND", filters: [tableViewFilter]}),
67         width: 10,
68         datasetColumnAlias: 'name',
69         label: "Name",
70         sort: sort
71     });
72
73     var col3 = wb.createTableColumn({
74         datasetColumnAlias: 'date'
75     });
76
77     var col4 = wb.createTableColumn({
78         datasetColumnAlias: 'total'
79     });
80
81     var col5 = wb.createTableColumn({
82         datasetColumnAlias: 'subsidiary',
83         fieldContext: fieldContext1
84     });
85
86     var tableview = wb.createTable({
87         name: "View",
88         id: "view",
89         dataset: dataset,
90         columns: [col1, col2, col3, col4, col5]
91     });
92
93     var rowItem = wb.createDataDimensionItem({
94         label: "A",
95         expression: dataset.getExpressionFromColumn({
96             alias: "date"
97         })
98     });

```

```

94     });
95
96     var rowDataDimension = wb.createDataDimension({
97         items: [rowItem]
98     });
99
100    var rowSection = wb.createSection({
101        totalline: wb.TotalLine.FIRST_LINE,
102        children: [rowDataDimension]
103    });
104
105
106    var columnItem = wb.createDataDimensionItem({
107        label: "B",
108        expression: dataset.getExpressionFromColumn({
109            alias: "total"
110        })
111    });
112
113    // var colDataDimensionChild = wb.createDataDimension({
114    //     items: [columnItem]
115    // });
116
117    var columnDataDimension = wb.createDataDimension({
118        totalline: wb.TotalLine.HIDDEN,
119        items: [columnItem],
120        // children: [colDataDimensionChild]
121    });
122
123    var columnMeasure = wb.createDataMeasure({
124        label: "M",
125        expressions: [idExpr, totalExpr],
126        aggregation: wb.Aggregation.COUNT_DISTINCT
127    });
128
129    var columnSection = wb.createSection({
130        children: [columnDataDimension, columnMeasure]
131    });
132
133    var allSubNodesSelector = wb.DescendantOrSelfNodesSelector;
134
135    var rowItemSelector = wb.createDimensionSelector({
136        dimension: rowDataDimension
137    });
138    var columnItemSelector = wb.createDimensionSelector({
139        dimension: columnDataDimension
140    });
141
142    var pathSelector = wb.createPathSelector({
143        elements: [allSubNodesSelector, columnItemSelector]
144    });
145
146    var rowSelector = wb.createPathSelector({
147        elements: [allSubNodesSelector, rowItemSelector]
148    });
149    var columnSelector = wb.createPathSelector({
150        elements: [allSubNodesSelector, columnItemSelector]
151    });
152
153    var rowSort = wb.createSortByDataDimensionItem({
154        item: rowItem,
155        sort: sort
156    });
157
158    var columnSort = wb.createSortByMeasure({
159        measure: columnMeasure,
160        sort: sort,
161        otherAxisSelector: allSubNodesSelector
162    });
163
164    var rowSortDefinition = wb.createSortDefinition({
165        row: false,
166        sortBy: [rowSort],

```

```

167         selector: rowSelector
168     });
169
170     var columnSortDefinition = wb.createSortDefinition({
171         sortBy: [columnSort],
172         selector: columnSelector
173     });
174
175     var rowAxis = wb.createPivotAxis({
176         root: rowSection,
177         sortDefinitions: [rowSortDefinition]
178     });
179
180     var columnAxis = wb.createPivotAxis({
181         root: columnSection,
182         sortDefinitions: [columnSortDefinition]
183     });
184
185
186     var pivot = wb.createPivot({
187         name: "Pivot",
188         id: "pivot",
189         rowAxis: rowAxis,
190         columnAxis: columnAxis,
191         dataset: dataset
192     });
193
194     var firstAxis = wb.createChartAxis({
195         title: "First axis"
196     });
197     var secondAxis = wb.createChartAxis({
198         title: "Second axis"
199     });
200
201     var category = wb.createCategory({
202         axis: firstAxis,
203         root: rowSection,
204         sortDefinitions: [rowSortDefinition]
205     });
206     var legend = wb.createLegend({
207         axes: [secondAxis],
208         root: columnSection,
209         sortDefinitions: [columnSortDefinition]
210     });
211     var aspect = wb.createAspect({
212         type: wb.AspectType.VALUE,
213         measure: columnMeasure
214     });
215     var series = wb.createSeries({
216         aspects: [aspect]
217     });
218
219     var chart = wb.createChart({
220         name: "Chart",
221         title: "First Chart",
222         subTitle: "sub first chart",
223         id: "chart",
224         type: wb.ChartType.BAR,
225         stacking: wb.Stacking.NORMAL,
226         category: category,
227         legend: legend,
228         dataset: dataset,
229         series: [series]
230     });
231
232     var workbook = wb.create({
233         name: "Name Workbook",
234         description: "Description Workbook",
235         tables: [tableview],
236         pivots: [pivot],
237         charts: [chart],
238         id: "custworkbook_workbook"
239     });

```

```

240 | context.workbook = workbook;
241 |     }
242 | });
243 | });

```

description

Type	Object property
Description	The description of the plug-in implementation. This description is the same as the one you specify when you add your plug-in implementation to NetSuite. For more information, see Adding the Plug-in Implementation. This property is a string. This property is read-only. If you try to assign a value to this property, a READ_ONLY error is thrown.

name

Type	Object property
Description	The name of the plug-in implementation. This name is the same as the one you specify when you add your plug-in implementation to NetSuite. For more information, see Adding the Plug-in Implementation. This property is a string. This property is read-only. If you try to assign a value to this property, a READ_ONLY error is thrown.

owner

Type	Object property
Description	The owner of the plug-in implementation. The owner is the user who added the plug-in implementation to NetSuite. For more information, see Adding the Plug-in Implementation. This property is a number, which represents the internal ID of the user who added the plug-in implementation. This property is read-only. If you try to assign a value to this property, a READ_ONLY error is thrown.

role

Type	Object property
Description	The role of the plug-in implementation. The role is the role of the user who added the plug-in implementation to NetSuite. For more information, see Adding the Plug-in Implementation. This property is a number, which represents the internal ID of the role of the user who added the plug-in implementation.

This property is read-only. If you try to assign a value to this property, a `READ_ONLY` error is thrown.

workbook

Type Object property

Description A context property for the created workbook.

In your plug-in implementation, use the `N/workbook` module to create a workbook as a [workbook.Workbook](#) object. After you create this object, assign it to this property. For more information, see the help topic [N/workbook Module](#).

This property is required. If you do not assign a workbook to this property, a `NO_WORKBOOK_CREATED` error is thrown.

This property is write-only and accepts only a [workbook.Workbook](#) object. If you try to assign an object other than a [workbook.Workbook](#) object to this property, a `WRONG_PARAMETER_TYPE` error is thrown.

You can reference only datasets that have been saved using the SuiteAnalytics Workbook UI or a Dataset Builder Plug-in. If you try to reference a dataset that has not been saved, a `CAN_REFERENCE_ONLY_PERSISTED_DATASET` error is thrown.