Virtual Memory

Operating Systems (CS-220)
Spring 2021, FAST NUCES


Virtual Memory

- □ Virtual memory is a memory management capability of an OS, uses hardware and software to allow a computer to compensate for physical memory shortages by temporarily transferring data from random access memory (RAM) to disk storage.
- □ Virtual memory is not RAM (Random access memory) on memory chips.
- Virtual memory is an area of hard drive or other storage space, which
 OS uses as swap space (overflow) for the physical RAM.
- When the demands of the software and data exceed the physical RAM size, the operating system copies to hard disk blocks of data from RAM that have been seldom used and releases that RAM for use by the current process.
- When the block (or Page) is required again, the OS makes room in RAM by copying another block to hard drive and copying in the data from the first block.

Background


- Virtual memory separation of user logical memory from physical memory
 - Only part of the program needs to be in memory for execution
 - Logical address space can therefore be much larger than physical address space
 - Allows address spaces to be shared by several processes
 - Allows for more efficient process creation
 - More programs running concurrently
 - Less I/O needed to load or swap processes.
- Virtual memory can be implemented via:
 - Demand paging
 - Demand segmentation

Virtual Memory That is Larger Than Physical Memory




Virtual-address Space

- Virtual address spaces that include holes are known as sparse address spaces.
- System libraries shared via mapping into virtual address space
- Shared memory by mapping pages readwrite into virtual address space
- Pages can be shared during fork(), speeding process creation




Shared Library Using Virtual Memory




Demand Paging

- Could bring entire process into memory at load time
- Or bring a page into memory only when it is needed
 - Less I/O needed, no unnecessary I/O
 - Less memory needed
 - Faster response
 - More users
- □ Page is needed ⇒ reference to it
 - □ invalid reference ⇒ abort
 - not-in-memory ⇒ bring to memory
- Lazy swapper never swaps a page into memory unless page will be needed
 - Swapper that deals with pages is a pager




Valid-Invalid Bit


- With each page table entry, a valid–invalid bit is associated
 (v ⇒ in-memory memory resident, i ⇒ not-in-memory)
- Initially valid—invalid bit is set to i on all entries
- Example of a page table snapshot:





During MMU address translation, if valid-invalid bit in page table entry is i ⇒ page fault

Page Table
When Some
Pages Are
Not in Main
Memory









physical memory


Page Fault

If there is a reference to a page, first reference to that page will trap to operating system:

page fault

- 1. Operating system looks at another table to decide:
 - □ Invalid reference ⇒ abort
 - Just not in memory
- 2. Find free frame
- 3. Swap page into frame via scheduled disk operation
- Reset tables to indicate page now in memory Set validation bit = v
- 5. Restart the instruction that caused the page fault

Steps in Handling a Page Fault



Aspects of Demand Paging

- Extreme case start process with no pages in memory
 - OS sets instruction pointer to first instruction of process, nonmemory-resident -> page fault
 - And for every other process pages on first access
 - Pure demand paging
- A given instruction could access multiple pages -> multiple page faults
 - Pain decreased because of locality of reference
- Hardware support needed for demand paging
 - Page table with valid / invalid bit
 - Secondary memory (swap device with swap space)
 - Instruction restart

Performance of Demand Paging

- □ Page Fault Rate $0 \le p \le 1$
 - \Box if p = 0 no page faults
 - \square if p = 1, every reference is a fault
- □ Effective Access Time (EAT) =

```
EAT = (1 - p) \times ma + p  (page fault time)
```

page fault time = fault overhead+ swap page out+ swap page in

Page fault (EAT calculation)

- Memory access time = ma = 200 nanoseconds
- Average page-fault service time = page fault time = 8 milliseconds
- ☐ If one access out of 1,000 causes a page fault, then p = 1/1000 = 0.001
- \Box EAT = (1 p) x ma + p (page fault time)
- \square EAT = $(1 0.001) \times 200 + 0.001 \times (8e 6)$
- ☐ EAT = 8199.8 nanoseconds
- ☐ EAT = 8.199 microseconds

Millisecond = 10 e-3

Microsecond = 10e-6

Nanoseconds = 10e-9


Demand Paging Optimizations

- Copy entire process image to swap space at process load time
 - Then page in and out of swap space
 - 2. Used in older BSD Unix
- Demand page in from program binary on disk, Demand pages for such files are brought directly from the file system.
 - 1. Used in Solaris and current BSD


Copy-on-Write

- Copy-on-Write (COW) technique allows both parent and child processes to initially share the same pages in memory
 - If either process modifies a shared page, only then is the page copied.
- COW allows more efficient process creation as only modified pages are copied.
- In general, free pages are allocated from a pool of zero-fill-on-demand pages
- vfork() (for virtual memory fork) variation on fork() system call has parent suspend and child using copy-on-write address space of parent
 - Designed to have child call exec()
 - Very efficient

Before Process 1 Modifies Page C




After Process 1 Modifies Page C





What Happens if There is no Free Frame?


- Page replacement find some page in memory, but not really in use, page it out
 - Algorithm terminate? swap out? replace the page?
 - Performance want an algorithm which will result in minimum number of page faults
- Same page may be brought into memory several times.

Need For Page Replacement










Basic Page Replacement Steps

- 1. Find the location of the desired page on disk
- 2. Find a free frame:
 - If there is a free frame, use it
 - If there is no free frame, use a page replacement algorithm to select a victim frame
 - Write victim frame to disk if dirty
- 3. Bring the desired page into the (newly) free frame; update the page and frame tables
- 4. Continue the process by restarting the instruction that caused the trap

Note now potentially 2-page transfers for page fault – increasing EAT


Page Replacement



Page Replacement

- Page Replacement carried out by:
- 1. Page-replacement algorithm
- 2. Frame-allocation algorithm
- □ Frame-allocation algorithm determines
 - How many frames to give each process
 - Which frames to replace
- Page-replacement algorithm
 - Want lowest page-fault rate on both first access and re-access

Graph of Page Faults Versus The Number of Frames



Page Replacement Algorithms

- Basic page replacement algorithms are:
- 1. FIFO
- 2. Optimal Solution
- 3. LRU Algorithm
- 4. LRU –Approximation
- Evaluate algorithm by running it on a particular string of memory references (reference string) and computing the number of page faults on that string
 - String is just page numbers, not full addresses
 - Repeated access to the same page does not cause a page fault
 - Results depend on number of frames available
- In all our examples, the reference string of referenced page numbers is

First-In-First-Out (FIFO) Algorithm

☐ The simplest page-replacement algorithm is a first-in, first-out (FIFO) algorithm. A FIFO replacement algorithm associates with each page the time when that page was brought into memory. When a page must be replaced, the oldest page is chosen.

Covered in Class

6,0,1,2,0,3,0,5,2,3,0,3,0,3,2,1,2,0,1,6,0,1

ratio	6	0	1	2	0	3	0	5	2	3	0	3	0	3	2	1	2	0	1	6	0	1
f1																						
f2																						
f3																						

Optimal Page Replacement Algorithm

- ☐ To Overcome Belady's anomaly, **optimal page-replacement algorithm introduced**—the algorithm that has the lowest page-fault rate of all algorithms and will never suffer from Belady's anomaly.
- Such an algorithm does exist and has been called OPT or MIN. It is simply this:
- Replace the page that will not be used for the longest period of time.
- □ Use of this page-replacement algorithm guarantees the lowest possible page- fault rate for a fixed number of frames.

Covered in Class

7,0,1,2,0,3,0,4,2,3,0,3,0,3,2,1,2,0,1,7,0,1

ratio	7	0	1	2	0	3	0	4	2	3	0	3	0	3	2	1	2	0	1	7	0	1
f1																						
f2																						
f3																						

Least Recently Used (LRU) Algorithm

- LRU replacement associates with each page the time of that page's last use.
- When a page must be replaced, LRU chooses the page that has not been used for the longest period.
- LRU strategy as the optimal page-replacement algorithm looking backward in time, rather than forward.

Covered in Class

7,0,1,2,0,3,0,4,2,3,0,3,0,3,2,1,2,0,1,7,0,1

ratio	7	0	1	2	0	3	0	4	2	3	0	3	0	3	2	1	2	0	1	7	0	1
f1																						
f2																						
f3																						

LRU Algorithm (Cont.)

- Counter implementation
 - Every page entry has a counter; every time page is referenced through this entry, copy the clock into the counter
 - When a page needs to be changed, look at the counters to find smallest value
 - Search through table needed
- Stack implementation
 - Keep a stack of page numbers in a double link form:
 - Page referenced:
 - move it to the top
 - requires 6 pointers to be changed
 - But each update more expensive
 - No search for replacement

LRU Approximation Algorithms

LRU needs special hardware and still slow. There are three LRU Approximation Algorithms:

- 1. Additional reference bit Algorithm
- 2. Second Chance Algorithm
- 3. Enhanced Second Chance Algorithm

LRU Approximation Algorithms

- □ Reference bit Algorithm
 - □ With each page associate a bit, initially = 0
 - When page is referenced, bit set to 1
 - Replace any with reference bit = 0 (if one exists)
 - We do not know the order, however
- Second-chance algorithm
 - Generally, FIFO, plus hardware-provided reference bit
 - Clock replacement
 - If page to be replaced has
 - ▶ Reference bit = 0 -> replace it
 - reference bit = 1 then:
 - set reference bit 0, leave page in memory
 - replace next page, subject to same rules

Second Chance Algorithm

Covered in Class

Thank You!