Technische Universität München





Department of Civil, Geo and Environmental Engineering Chair of Geodesy Geodetic Laboratory

Dr.-Ing.
Peter Wasmeier

Arcisstraße 21 80333 München Germany

Tel +49.89.289.22847 Fax +49.89.289.23967

p.wasmeier@tum.de www.geo.bgu.tum.de

Correspondent bank: Bayerische Landesbank München

SWIFT-Code: bylademm

IBAN-No.: DE 10700500000000024866

VAT.-ID-No.: DE811193231

Technische Universität München Chair of Geodesy – Geodetic Laboratory 80290 München Germany

C.R. Kennedy Survey Solutions 17 – 19 Oxford Close West Leederville WA 6007 Australia

Munich, January 20th, 2015

Remarks on the Invar rod calibration contract 14-72-07

Rod no: 26296, 26909, 27690

At the Geodetic Laboratory of the Technische Universität München invar levelling rods are calibrated according to the normative regulations of DIN 18717 which is identical to ISO 12858-1.

The stated requirements are:

- Thermal expansion coefficient ≤ 1 ppm/K
 This is achieved by all three rods.
- Rod scale factor ≤ 26.6 ppm for 3m rods
 This is achieved by all three rods.
- Index correction ≤ 0.05 mm
 This is achieved by all three rods.
- Deviation from rectangularity between the tape axis of the rod and the setup plate ≤ 5' = 0.0833°
 This is not achieved by all three rods.

This does not mean that the setup plate itself is not planar, but that the whole plane is tilted.

As a result of the misalignment between the rod tape axis and the setup plate, different setup positions of the rod will lead to different index errors which at the far ends of the setup plate will exceed 0.05 mm.

For practical use, it should be considered to set up the rod close to its reference point and avoid setups at the setup plate boundaries.

The detected rod tape straightness variations are harmless until it is guaranteed that the rod tape is free to move within its slide.

Dr.-Ing. Peter Wasmeier (Call

Seite 1

Calibration Report

Invar rod (Type, No):

GPCL3 26909


Contract:

14-72-07


Date of calibration:

20.01.2015

Rod tape straightness



Setup plate planarity



Deviation from rectangularity between rod tape regression and setup plate: 0.0974°

Calibration: Dr.-Ing. Peter Wasmeier



Geodätisches Prüflabor am Lehrstuhl für Geodäsie der TU München Arcisstraße 21, 80290 München, Tel.: 089/289-22850, Fax: 089/289-23967

Calibration Report

Invar rod (Type, No):

GPCL3 27690


Contract:

14-72-07


Date of calibration:

20.01.2015

Rod tape straightness




Setup plate planarity



Deviation from rectangularity between rod tape regression and setup plate: 0.1439°

Calibration: Dr.-Ing. Peter Wasmeier





Calibration Report

Invar rod (Type, No):

GPCL3 26296


Contract:

14-72-07


Date of calibration:

20.01.2015

Rod tape straightness



Setup plate planarity



Deviation from rectangularity between rod tape regression and setup plate: 0.1624°

Calibration: Dr.-Ing. Peter Wasmeier



Geodätisches Prüflabor am Lehrstuhl für Geodäsie der TU München Arcisstraße 21, 80290 München, Tel.: 089/289-22850, Fax: 089/289-23967