

CP2K-UK: Supporting Advances in Atomistic Simulation Capability

Iain Bethune^{*1}, Jeremy Nowell¹, Fiona Reid¹, Lev Kantorovich², Lianheng Tong², Matt Watkins³, and Ben Slater³

^{*}ibethune@epcc.ed.ac.uk

¹EPCC, The University of Edinburgh

²King's College London

³University College London

Project Overview

CP2K [1] is a freely available (www.cp2k.org) open-source program for atomistic simulation, best known for its implementation of the Quickstep Gaussian and Plane Waves (GPW) linear-scaling Density Functional Theory (DFT) method [2]. However, CP2K provides a much wider range of capabilities, including classical potentials, QM/MM, semi-empirical models, hybrid DFT functionals, and most recently Møller-Plesset 2nd order perturbation theory (MP2)[3] and the Random Phase Approximation (RPA)[4]. Built on top of these models are an extensive set of simulation tools including molecular dynamics, Monte Carlo, nudged elastic band, path integrals and free energy methods. Thus CP2K appeals to a wide range of users including Computational Chemists, Materials Scientists, Solid State Physicists and Biochemists. Usage of CP2K is growing, to the point where it is now the second most heavily used code on ARCHER, the UK national HPC service.




Figure 1: Computed unit cell of a sigma-alkane complex.
Image courtesy Prof. Stuart Macgregor.

The CP2K-UK project, part of EPSRC's Software For the Future strategy, is supporting the growing user community to make best use of the capabilities CP2K has to offer. We have identified key barriers to usability, and are offering training and direct support to users to overcome these. In addition, we are building the capability of the user community to become developers of CP2K – adding functionality as required for their particular research goals.

CP2K-UK will run from 2013 to 2018, and we present here some of the recent achievements of the project.

Support for Users

Networking: There is already a great deal of experience in using CP2K embedded within research groups around the UK, and part of the role of CP2K-UK is to offer opportunities for new users to make contact with existing users. We have started a series of annual user group meetings, which have proved to be very popular. These include a mixture of talks from key CP2K developers, shorter talks focused on how to use particular functionality in the code, and three minute lightning talks, highlighting the breadth of research supported by CP2K. Slides from this year's meeting are at www.epcc.ed.ac.uk/content/cp2k-uk-workshop-2015.

Training: The CP2K-UK project offers training in the usage of CP2K, both through classroom-based training events, and bespoke training days with individual research groups. One of the groups we visited during 2014 subsequently applied for an ARCHER 'Instant Access' grant to test out CP2K at scale, and recently received a substantial award of CPU time through the ARCHER Resource Allocation Panel (RAP) call to carry out their calculations.

Performance: CP2K offers excellent performance and scalability, but choosing the optimal set of parameters for parallelisation is not always straightforward. To help address this, we carried out systematic benchmarking using a range of different calculation types on different HPC machines, and published a paper on CP2K performance [5]. These results have been extended and made available on the CP2K website along with scripts for plotting performance graphs (www.cp2k.org/performance), and we encourage users to contribute benchmark results from their own machines .




Figure 2: Scaling of water benchmarks from 32 to 2048 molecules on ARCHER (and a Cray XT3 from 2005).

Support for Developers

During the last year, we have worked on improving CP2K code quality, to make it easier for new developers to understand and contribute to the project. The entire CP2K code-base now contains automatically-generated 'doxygen' documentation, which can be browsed online at doxygen.cp2k.org. In addition, we have extended the CP2K automated regression test environment to cover use of the Intel Fortran compiler and MKL library, and now have reliable results on this platform.

We have also implemented two new methods in CP2K which we believe will be of wide benefit to the community:

- Langevin Dynamics with arbitrary thermal regions, following the method in [6]. This functionality is available in CP2K version 2.6.

- Filter matrix diagonalisation [7], a scheme where a minimal basis set is constructed dynamically during the SCF procedure which spans a new subspace, guaranteed to contain the minimum energy configuration. The algorithm works by constructing many 'atomic' Hamiltonian matrices, localised in a region around each atom. Each of these can then be diagonalised and a minimal 'filtered' basis set constructed.

The minimal basis sets are then combined and a reduced-size global Hamiltonian matrix constructed, which may be diagonalised much more cheaply than the full Hamiltonian in the original basis. The filtered basis method is currently available in the CP2K SVN trunk, and is still under active development.




Figure 3: Schematic showing the key operations of the filter matrix diagonalisation method as implemented in CP2K.

Get Involved!

CP2K-UK's primary purpose is to benefit the CP2K community – so if you are already using CP2K, have specific features or methods you want to find out more about, or are just starting to investigate CP2K, then we would like to hear from you. Here are some ways you can get involved:

- CP2K Tutorial (Aug 31 – Sep 4, 2015) – A week-long CECAM-sponsored workshop in Zurich. Ideal for users with a little CP2K experience who want in-depth training. Register at www.cecam.org/workshop-1122.html.
- Want to get started with CP2K? Contact us to arrange a hands-on introduction to CP2K at your institution, with specific focus on your application areas.
- The CP2K website (www.cp2k.org) is now a wiki and anyone can contribute. Please make improvements, contribute tutorials based on your own experience, or ask if your think information is missing.
- Have an idea for a new feature or tool that you'd like to see implemented in CP2K? Talk to us about software development funding opportunities and training.
- If you are applying for a research grant involving CP2K, or wish to use CP2K on ARCHER, contact us to see how we can support your application
- To stay in the loop about upcoming CP2K events, we maintain a notification-only email list. Contact us to subscribe.

For any of the above, or if you have other questions about the CP2K-UK project, please email ibethune@epcc.ed.ac.uk

[1] Hutter et al, WIREs Computational Molecular Science 4(1):15-25 (2013)

[2] VandeVondele et al, Computer Physics Communications 167, 103 (2005)

[3] Del Ben et al, Journal of Chemical Theory and Computation 8(11) (2012)

[4] Del Ben et al, Computer Physics Communications 187, 120-129 (2014)

[5] Bethune et al, Proceedings of the Cray User Group (2014)

[6] L. Kantorovich, Physical Review B, 78 (9) (2008)

[7] Rayson and Briddon, Physical Review B, 80 (20) (2009)

CP2K-UK is supported by the Engineering and Physical Sciences Research Council [grant number EP/K038583/1].

This work used the ARCHER UK National Supercomputer Service (<http://www.archer.ac.uk>).

EPSRC

Engineering and Physical Sciences
Research Council

KING'S
College
LONDON

epcc

UCL