

Lab 1: Install IBM Event Streams on IBM Cloud Private

Duration: 1 hour

In this exercise, you install IBM Event Streams on IBM Cloud Private. If you have not already done so, start with Step 1. Access the remote lab environment. Otherwise, review **Tips for using the remote environment**, and start with Step 2.

Step 1. Access the remote lab environment.

This lab exercise is intended to run in a remote environment where IBM Cloud Private is already installed and configured. For instructor-led deliveries, the instructor provides the URL to access this environment. For self-paced virtual courses (SPVC), the URL is provided through the Digital Learning Platform (DLP).

1. In a browser, go to the lab environment URL, and click **Run** to start the virtual machines.

IBM

Feedback Videos Help/Support

IBM Event Streams 3.1 pre-Installation on ICP 3.1.1_2858

Region: US-Central

VMs: 5

Sort by name

VM Name	Status	Endpoints	SVMS	RAM	CPUS	STORAGE
ICP Master	Powered off	1 (master - 10.0.0.1)	32	32 GB	24	350 GB
Proxy	Powered off	1 (host-1 - 10.0.0.5)	8	8 GB	8	200 GB
Worker1	Powered off	1 (worker1 - 10.0.0.2)	16	16 GB	16	200 GB
Worker2	Powered off	1 (worker2 - 10.0.0.3)	16	16 GB	16	200 GB
Worker3	Powered off	1 (worker3 - 10.0.0.4)	16	16 GB	16	200 GB

It might take a few minutes for the machines to start up.

1. After the status changes to Running, click the image for the **ICP Master** to open the desktop.



IBM Event Streams 3.1 pre-Installation on ICP 3.1.1_2858

Region: US-Central



VMs: 5

☒ Sort by name

Running

☒ **ICP Master**
Endpoints: 1 (master - 10.0.0.1)

SVMS	RAM	CPU	STORAGE
32	32 GB	24	350 GB

2

Running

☒ **Proxy**
Endpoints: 1 (host-1 - 10.0.0.5)

SVMS	RAM	CPU	STORAGE
8	8 GB	8	200 GB

2

Running

☒ **Worker1**
Endpoints: 1 (worker1 - 10.0.0.2)

SVMS	RAM	CPU	STORAGE
16	16 GB	16	200 GB

2

Running

☒ **Worker2**
Endpoints: 1 (worker2 - 10.0.0.3)

SVMS	RAM	CPU	STORAGE
16	16 GB	16	200 GB

2

Running

☒ **Worker3**
Endpoints: 1 (worker3 - 10.0.0.4)

SVMS	RAM	CPU	STORAGE
16	16 GB	16	200 GB

2


1. Log in to the Linux desktop with user ID **student**, and password **Passw0rd!**.

If you see any pop-ups about system problems being detected, or software updates, click **Cancel** to dismiss them.


Tips for using the remote environment

After a period of inactivity, your session is automatically suspended. You can resume your session by clicking **Run** to start the virtual machines again. It can take several minutes for all of the processes to resume, even after the status changes to Running, so if the desktop is unresponsive, wait a bit longer and try again.

To copy and paste from your local desktop to the remote one, use the Clipboard icon in the toolbar of the remote desktop.



You can copy and paste text here to use it on the remote desktop.



Be careful when copying and pasting text directly from certain applications. Formatting, spacing, and special characters might not be interpreted correctly.

You can also cut and paste commands from a text file that is provided on the remote desktop.

Step 2. Download and install IBM Event Streams

NOTE: It can still take up to 20 minutes for all of the processes on the virtual machine to start up, so wait a few minutes before proceeding with the following steps.


A. Create a namespace for Event Streams

1. Open the IBM Cloud Private console. Click the Firefox icon on the desktop to open the browser, and click the **IBM Cloud Private** bookmark on the Bookmarks toolbar.


NOTE: If you see a warning about using an insecure connection, click **Advanced > Accept the risk and continue**.

If you see a 502 error, wait a few minutes and try again. All the required components might need more time to start up.

2. On the IBM Cloud Private login page, log in with the user ID **admin** and password **admin**.



3. Click the "hamburger" icon in the upper left corner to access the menu.



4. Select **Manage > Namespaces**.

To prepare for installation of IBM Event Streams, you create a namespace for it in IBM Cloud Private.

5. Click **Create Namespace**, and complete the form as follows:

- Name: **es**
- Pod Security Policy: **ibm-restricted-psp**

6. Click **Create**. The new namespace is displayed in the list of namespaces.



Namespaces

Create Namespace +

Name	Status	Pod Security Policy
cert-manager	Active	ibm-anyuid-hostpath-psp
default	Active	default, ibm-anyuid-hostaccess-psp, ibm-anyuid-hostpath-psp, ibm-anyuid-psp, ibm-privileged-psp, ibm-restricted-psp, privileged
es	Active	ibm-anyuid-hostpath-psp, ibm-restricted-psp
ibmcom	Active	ibm-anyuid-hostpath-psp
istio-system	Active	ibm-anyuid-hostpath-psp, ibm-privileged-psp

B. Start the installation

The IBM Event Streams compressed installation file is already downloaded to the lab environment.

1. Click the command terminal icon on the desktop to open a command terminal window.
2. Log in to the IBM Cloud Private cluster by entering the following command:

```
sudo cloudctl login -a https://10.0.0.1:8443 --skip-ssl-validation
```

In this case, the address of the master node is `10.0.0.1`, and the default port is `8443`. Most IBM Cloud Private commands must be run with root access, so that is why you must use `sudo`.

3. Enter the password `Passw0rd!` when prompted.
4. You are prompted again for the IBM Cloud Private user ID and password. Enter `admin`, and `admin`.
5. If you are prompted to select an account, accept the default.
6. When prompted to select a namespace, enter the number for the `es` namespace. In this case it is `3`.

```
student@master:~$ sudo cloudctl login -a https://10.0.0.1:8443 --skip-ssl-validation
[sudo] password for student:
Username> admin
Password>
Authenticating...
OK
Targeted account mycluster Account (id-mycluster-account)
Select a namespace:
1. cert-manager
2. default
3. es
4. ibmcom
5. istio-system
6. kube-public
7. kube-system
8. platform
9. services
Enter a number> 3
```

```

Targeted namespace es

Configuring kubectl ...
Property "clusters.mycluster" unset.
Property "users.mycluster-user" unset.
Property "contexts.mycluster-context" unset.
Cluster "mycluster" set.
User "mycluster-user" set.
Context "mycluster-context" created.
Switched to context "mycluster-context".
OK

Configuring helm: /home/student/.helm
OK

```

7. Enter the following command to log in to Docker:

```
sudo docker login mycluster.icp:8500
```

In this example, `mycluster.icp:8500` is the address and port for Docker on the IBM Cloud Private cluster.

8. You are prompted again for the IBM Cloud Private user ID and password. Enter `admin` , and `admin` .
9. Change to `/home/student/Downloads` and display the contents:

```
cd Downloads
ls
```

```

student@master:~$ cd Downloads
student@master:~/Downloads$ ls
cloudctl-linux-amd64-3.1.1-973      helm-linux-amd64-v2.9.1.tar.gz
eventstreams.2018.3.0.x86.pak.tar.gz  icp-docker-18.03.1_x86_64.bin
eventstreams.2018.3.1.z_x86.pak.tar.gz  kubectl-linux-amd64-v1.11.1
google-chrome-stable_current_amd64.deb

```

The IBM Event Streams compressed installation file is `eventstreams.2018.3.1.z_x86.pak.tar.gz` .

10. Load the Event Streams Helm chart in to the IBM Cloud Private Catalog by entering the following command:


```
sudo cloudctl catalog load-archive --archive eventstreams.2018.3.1.z_x86.pak.tar.gz
```

NOTE: If you are prompted for a password, enter `Passw0rd!` . The process might take several minutes to complete.

After the installation completes, the catalog is updated with the IBM Event Streams local chart, and the internal Docker repository is populated with the Docker images that IBM Event Streams uses.

Step 3. Verify the installation

1. Return to the IBM Cloud Private Console and click Catalog in the upper right corner.



2. In the search bar, enter **eventstreams**.
3. Verify that **ibm-eventstreams-prod** is now listed in the catalog. Note that **ibm-eventstreams-dev** comes with IBM Cloud Private, and is already included in the catalog. If you see **ibm-eventstreams-prod**, the installation was successful.

Catalog

All Categories >

Blockchain

Business Automation

Data

Data Science & Analytics

DevOps

Integration

IoT

eventstreams

**ibm-eventstreams-dev**

IBM Event Streams based on Apache Kafka.

ibm-charts

**ibm-eventstreams-prod**

IBM Event Streams based on Apache Kafka.

local-charts

Step 4. Verify Event Streams prerequisites

1. Create an image pull secret for the `es` namespace by entering the following command (use your own email address in place of the one used in this command):

```
sudo kubectl create secret docker-registry regcred --docker-server=mycluster.icp:8500 --docker-username=admin --docker-password=admin --docker-email=mirv@us.ibm.com -n es
```

```
student@master:~/Downloads$ sudo kubectl create secret docker-registry regcred -
--docker-server=mycluster.icp:8500 --docker-username=admin --docker-password=admi
n --docker-email=mirv@us.ibm.com -n es
secret/regcred created
```

This secret provides access to the IBM Cloud Private internal docker repository. In this example, `regcred` is the name of the secret.

2. Create an image policy for the internal Docker repository. Enter the following command to create a YAML file to contain this policy:

```
gedit /home/student/Downloads/imgpol.yaml
```

In this example, the file is named `imgpol.yaml`.

3. In the editor, enter the following contents for the file:

```
apiVersion: securityenforcement.admission.cloud.ibm.com/v1beta1
kind: ImagePolicy
metadata:
  name: image-policy
  namespace: es
spec:
  repositories:
    - name: docker.io/*
      policy: null
    - name: mycluster.icp:8500/*
      policy: null
```

NOTE: The spacing is very important here. Make sure that `apiVersion`, `kind`, `metadata`, and `spec` are aligned left, the first level of indented lines are preceded by two spaces, and the second level of indented lines are preceded by four spaces.

4. Save the file and close the editor.
5. Apply the image policy that you just created by entering the following command:

```
sudo kubectl apply -f imgpol.yaml
```

If you are prompted for a password, enter `Passw0rd!`.

End of exercise

Notices

This information was developed for products and services offered in the US. IBM may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service. IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not grant you any license to these patents. You can send license inquiries, in writing, to: IBM Director of Licensing IBM Corporation North Castle Drive, MD-NC119 Armonk, NY 10504-1785 United States of America INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you. This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice. Any references in this information to non-IBM websites are provided for convenience only and do not in any manner serve as an endorsement of those websites. The materials at those websites are not part of the materials for this IBM product and use of those websites is at your own risk. IBM may use or distribute any of the information you provide in any way it believes appropriate without incurring any obligation to you. Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements or other publicly available sources. IBM has not tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products. This information contains examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to actual people or business enterprises is entirely coincidental. **Trademarks** IBM, the IBM logo, and ibm.com are trademarks or registered trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the web at "Copyright and trademark information" at www.ibm.com/legal/copytrade.shtml. © **Copyright International Business Machines Corporation 2019. This document may not be reproduced in whole or in part without the prior written permission of IBM.** US Government Users Restricted Rights - Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

Trademarks

The reader should recognize that the following terms, which appear in the content of this training document, are official trademarks of IBM or other companies: IBM, the IBM logo, and ibm.com are trademarks or registered trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. The following are trademarks of International Business Machines Corporation, registered in many jurisdictions worldwide: IBM Cloud™ z/OS® Java™ and all Java-based trademarks and logos are trademarks or registered trademarks of Oracle and/or its affiliates. VMware is a registered trademark or trademark of VMware, Inc. or its subsidiaries in the United States and/or other jurisdictions. Other product and service names might be trademarks of IBM or other companies.