

## Lab 5: Use Kafka Connect sink connector for IBM MQ

**Duration:** 1 hour

In this exercise, you connect IBM Event Streams to IBM MQ by using the Kafka Connect sink connector for IBM MQ. You can use this connector to transfer messages from an Event Streams or Kafka Topic to an MQ queue.

In the previous lab exercise, you installed MQ and configured the Kafka Connect source connector, which takes messages from an MQ queue and transfers them to a Topic in Event Streams. In this exercise, you use the same MQ queue manager that you configured previously, and test the sink connector by using the eslabtester application that you used before.


You must complete Labs 1-4 before proceeding with this lab.

### Step 1. Install the connector


1. Open the Event Streams console.

HINT: To access the Event Streams admin console, in the IBM Cloud Private console, select **Workloads > Helm Releases** from the console menu, click **eslab**, and then click **Launch** in the upper right corner, and select **admin-ui-https**.

2. Click **Toolbox** and scroll down to **Connectors**.
3. Under **Kafka Connect sink connector for IBM MQ**, click **Find out more**.



4. Click the links to download the **Connector JAR** and **Sample connector properties** file, and click **Save file**.



NOTE: You can also obtain the connector from [GitHub](#) if you want to build it yourself.

5. Copy the files into `/home/student`.

### Step 2. Configure the connector

REMINDER: There are two configuration files: the worker configuration file contains the properties that are required to connect to Kafka, and the connector configuration file contains the properties that are used by the connector, so that is where the MQ configuration goes.

As you did in a previous exercise, you must create a new API key for the consumer application.

## A. Update sink connector properties

1. In a command terminal window, change to `/home/student` and open the `mq-sink.properties` file in an editor:

```
cd /home/student
gedit mq-sink.properties
```

2. Update the properties as follows:

- `topic=eslab`
- `mq.queue.manager=QM1`
- `mq.connection.name.list=10.0.0.1(port)`
- `mq.channel.name=DEV.APP.SVRCONN`
- `mq.queue=DEV.QUEUE.2`

In this case, the target queue is DEV.QUEUE.2.

NOTE: For the `port`, use your MQ listener port, which is displayed in the IBM Cloud Private console under **Network Access > Services > mymq-ibm-mq**.

<b>Node port</b>	<a href="#">console-https 30753/TCP</a> <a href="#">qmg 32053/CP</a>
------------------	---

The number might be different than the one shown here.

```
# The list of source Kafka topics
topics=eslab

# The name of the MQ queue manager - required
mq.queue.manager=QM1

# The connection mode to connect to MQ - client (default) or bindings - optional
# mq.connection.mode=client
# mq.connection.mode=bindings

# A list of one or more host(port) entries for connecting to the queue manager. Entries are
separated with a comma - required (unless using bindings or CCDT)
mq.connection.name.list=10.0.0.1(32053)


# The name of the server connection channel - required (unless using bindings or CCDT)
mq.channel.name=DEV.APP.SVRCONN

# The name of the target MQ queue - required
mq.queue=DEV.QUEUE.2
```

3. Save and close the file.

## B. Create an API key for the consumer application

1. In the Event Streams console, select **Topics > eslab > Connect to this topic**.



2. Under **API key**, enter a name in **Name your application**, for example, **eslabsink**, and click **Consume only**.

Connect a client
Sample code
Geo-replication

To connect an application or tool to this cluster, you will need the address of a bootstrap server, a certificate and an API key.

### Bootstrap server

Your application or tool will make its initial connection to the cluster using the bootstrap server.

10.0.0.5:32307

### Certificates

A certificate is required by your Kafka clients to connect securely to this cluster.

Java truststore

Use this for a Java client

Truststore password: password

PEM certificate

Screenshot

### API key

To connect securely to Event Streams, your application or tool needs an API key with permission to access the cluster and resources such as topics.

Name your application

eslabsink

What do you want it to do?

Produce only →

Consume only →

Produce and consume →

Produce, consume and create topics →

3. Enter **eslab** for **Which topic?**, and click **Next**.

### API key

To connect securely to Event Streams, your application or tool needs an API key with permission to access the cluster and resources such as topics.

Start again ↺

Which topic?

All topics ☐

eslab

Next >


Connecting your tool or application will generate a service ID using your application name, a service policy and an API key in IBM Cloud Private. Additional API keys can be generated in the IBM Cloud Private Cluster Management Console or CLI.

[IBM Cloud Private Cluster Management Console](#)

4. Enter **eslabsink** for the **Which consumer group?**, and click **Generate API key**.

## API key


To connect securely to Event Streams, your application or tool needs an API key with permission to access the cluster and resources such as topics.



Connecting your tool or application will generate a service ID using your application name, a service policy and an API key in IBM Cloud Private. Additional API keys can be generated in the IBM Cloud Private Cluster Management Console or CLI.

[IBM Cloud Private Cluster Management Console](#)

5. Click the button to either copy the key to the clipboard, or save it to a file.



## C. Update worker properties

1. In the Kafka root `config` directory, make a copy of the `mqmlab.properties` file, and name it `connect-standalone-sink.properties`.

```
cd /home/student/Downloads/kafka_2.12-2.2.0/config
gedit connect-standalone-sink.properties
```

2. In the text editor menu, select **File > Save As**, edit the name of the file, and click **Save**.
3. Replace the consumer API keys with the one you just generated.
4. Add the following line after the `security` and `consumer` code stanzas:

```
consumer.group.id=eslabsink
```

NOTE: The file should still contain your bootstrap server address and port, from the previous lab exercise.

```
# These are defaults. This file just demonstrates how to override some settings.
bootstrap.servers=10.0.0.5:32307

security.protocol=SASL_SSL
ssl.protocol=TLSv1.2
ssl.endpoint.identification.algorithm=
ssl.truststore.location=/home/student/Downloads/es-cert.jks
ssl.truststore.password=password
sasl.mechanism=PLAIN
sasl.jaas.config=org.apache.kafka.common.security.plain.PlainLoginModule required username="token"
password="UmQ...AQJ"

consumer.security.protocol=SASL_SSL
consumer.ssl.protocol=TLSv1.2
consumer.ssl.endpoint.identification.algorithm=
consumer.ssl.truststore.location=/home/student/Downloads/es-cert.jks
consumer.ssl.truststore.password=password
consumer.sasl.mechanism=PLAIN
consumer.sasl.jaas.config=org.apache.kafka.common.security.plain.PlainLoginModule required
username="token" password="UmQ...AQJ"

consumer.group.id=eslabsink

# The converters specify the format of data in Kafka and how to translate it into Connect data.
Every Connect user will
```

Bootstrap server address and port

Sink consumer API key

5. Save and close the file.

### Step 3. Test the sink connector

1. In a command terminal window, change to the Kafka root directory, and run the following command to start the connector:

```
CLASSPATH=/home/student/kafka-connect-mq-sink-1.0.1-jar-with-dependencies.jar bin/connect-standalone.sh config/connect-standalone-sink.p
```

The connector starts, establishes a connection to the MQ queue manager, and starts listening for messages on topic eslab. Look for the message "Connection to MQ established," in the output.

2. Run the eslabtester starter application again. If it is not already open, in a new browser tab, enter the following URL:


```
http://localhost:9080/elabtester
```

HINT: If you need to run the starter application again, in a command terminal, change to the `/home/student/Downloads` directory and enter the following commands:

```
cd /home/student/Downloads
export _JAVA_OPTIONS=-Djdk.net.URLClassPath.disableClassPathURLCheck=true
mvn install liberty:run-server
```

Wait until you see the message, "The server defaultServer is ready to run a smarter planet" before you proceed to the next step.

3. In the eslabtester application, click the arrow to start producing messages.



- After the number of messages begins to increase, check the MQ console. Click the refresh icon for **Queues on QM1**.



The **Queue depth** for **DEV.QUEUE.2** increases as the number of messages increases.

Name	Queue type	Queue depth
AMQ.5CE45AB422385	Local	13
DEV.DEAD.LETTER.QU	Local	0
DEV.QUEUE.1	Local	0
DEV.QUEUE.2	Local	12
DEV.QUEUE.3	Local	0
Total: 5		Last updated: 5:46:58 PM

- In the eslabtester application, click the run button again to stop producing messages.
- Check the MQ console again to verify that the messages were received.
- Stop the connector and eslabtester application by pressing Ctrl-C in each terminal window.

## End of exercise

## Notices

This information was developed for products and services offered in the US. IBM may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service. IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not grant you any license to these patents. You can send license inquiries, in writing, to: IBM Director of Licensing IBM Corporation North Castle Drive, MD-NC119 Armonk, NY 10504-1785 United States of America INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you. This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice. Any references in this information to non-IBM websites are provided for convenience only and do not in any manner serve as an endorsement of those websites. The materials at those websites are not part of the materials for this IBM product and use of those websites is at your own risk. IBM may use or distribute any of the information you provide in any way it believes appropriate without incurring any obligation to you. Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements or other publicly available sources. IBM has not tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products. This information contains examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to actual people or business enterprises is entirely coincidental. **Trademarks** IBM, the IBM logo, and ibm.com are trademarks or registered trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the web at "Copyright and trademark information" at [www.ibm.com/legal/copytrade.shtml](http://www.ibm.com/legal/copytrade.shtml). © **Copyright International Business Machines Corporation 2019. This document may not be reproduced in whole or in part without the prior written permission of IBM.** US Government Users Restricted Rights - Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

## Trademarks

The reader should recognize that the following terms, which appear in the content of this training document, are official trademarks of IBM or other companies: IBM, the IBM logo, and ibm.com are trademarks or registered trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. The following are trademarks of International Business Machines Corporation, registered in many jurisdictions worldwide: IBM Cloud™ z/OS® Java™ and all Java-based trademarks and logos are trademarks or registered trademarks of Oracle and/or its affiliates. VMware is a registered trademark or trademark of VMware, Inc. or its subsidiaries in the United States and/or other jurisdictions. Other product and service names might be trademarks of IBM or other companies.-->