

Notices

This information was developed for products and services offered in the US.

IBM may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service.

IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not grant you any license to these patents. You can send license inquiries, in writing, to:

IBM Director of Licensing IBM Corporation

North Castle Drive, MD-NC119 Armonk, NY 10504-1785

United States of America

INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF

NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

Any references in this information to non-IBM websites are provided for convenience only and do not in any manner serve as an endorsement of those websites. The materials at those websites are not part of the materials for this IBM product and use of those websites is at your own risk.

IBM may use or distribute any of the information you provide in any way it believes appropriate without incurring any obligation to you.

Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements or other publicly available sources. IBM has not tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

This information contains examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to actual people or business enterprises is entirely coincidental.

Trademarks

IBM, the IBM logo, and ibm.com are trademarks or registered trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the web at "Copyright and trademark information" at www.ibm.com/legal/copytrade.shtml.

© Copyright International Business Machines Corporation 2019.

This document may not be reproduced in whole or in part without the prior written permission of IBM.

US Government Users Restricted Rights - Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

Trademarks

The reader should recognize that the following terms, which appear in the content of this training document, are official trademarks of IBM or other companies:

IBM, the IBM logo, and ibm.com are trademarks or registered trademarks of International Business Machines Corp., registered in many jurisdictions worldwide.

The following are trademarks of International Business Machines Corporation, registered in many jurisdictions worldwide:

IBM Cloud™

z/OS®

Java™ and all Java-based trademarks and logos are trademarks or registered trademarks of Oracle and/or its affiliates.

VMware is a registered trademark or trademark of VMware, Inc. or its subsidiaries in the United States and/or other jurisdictions.

Other product and service names might be trademarks of IBM or other companies.

Getting started with IBM Event Streams

- Install and configure Event Streams
- Exploring the Event Streams console
- Work with a sample application

Installing IBM Event Streams

Installing Event Streams on IBM Cloud Private

Ensure you have set up your environment [according to the prerequisites](#)

The Event Streams installation process creates and runs jobs in the target namespace, and in the kube-system namespace

Plan for installation: create required persistent volumes, and ConfigMap for Kafka static configuration

You will need:

- Master host and port of your IBM Cloud Private cluster
- SSH password

Make sure that your proxy address uses lowercase characters (otherwise, you must make the appropriate changes to your configuration)


Make sure that the IBM Cloud Private monitoring service is installed.


Installation overview

1. Create a target namespace for Event Streams
2. Download the IBM Event Streams installation image file, and make it available in your catalog
3. Create an image pull secret for the Event Streams namespace
4. Create an image policy for the internal Docker repository
5. Install the Event Streams chart
6. Verify installation





Creating a namespace

 IBM Cloud Private

Create resourceCatalogDocsSupport

Namespaces

 Search

Create Namespace 

Name	Status	Pod Security Policy
cert-manager	Active	ibm-anyuid-hostpath-ppsp
default	Active	default, ibm-anyuid-hostaccess-ppsp, ibm-anyuid-hostpath-ppsp, ibm-anyuid-ppsp, ibm-privileged-ppsp, ibm-restricted-ppsp, privileged
es	Active	ibm-anyuid-hostpath-ppsp, ibm-restricted-ppsp
ibmcom	Active	ibm-anyuid-hostpath-ppsp
istio-system	Active	ibm-anyuid-hostpath-ppsp, ibm-privileged-ppsp

Using the IBM Cloud Private Catalog

1. Download the Event Streams archive
2. Log in to IBM Cloud Private (`cloudctl login`), and Docker (`docker login`)
3. Load the Event Streams Helm chart in to the IBM Cloud Private Catalog (`cloudctl catalog`)




Image pull secret and image policy

Creating an image pull secret (kubectl create secret)

```
student@master:~/Downloads$ sudo kubectl create secret docker-registry regcred -  
-docker-server=mycluster.icp:8500 --docker-username=admin --docker-password=admi  
n --docker-email=mrv@us.ibm.com -n es  
secret/regcred created
```

Creating an image policy

```
apiVersion: securityenforcement.admission.cloud.ibm.com/v1beta1  
kind: ImagePolicy  
metadata:  
  name: image-policy  
  namespace: es  
spec:  
  repositories:  
    - name: docker.io/*  
      policy: null  
    - name: mycluster.icp:8500/*  
      policy: null
```

Installing the Helm chart

1. Sync repositories
2. Select the chart from the Catalog and click Configure
3. Enter a name and target namespace, and any other relevant information (for example, the image pull secret)
4. Click Install

The screenshot shows the 'Configuration' page for the 'IBM Event Streams' Helm chart in the IBM Cloud Private console. At the top, there is a 'Pod Security Warning' indicating that the cluster is running all namespaces unrestricted by default. The configuration section includes three main fields: 'Helm release name' with the value 'eslab', 'Target namespace' with the value 'es', and a 'License' checkbox that is checked. Below these, the 'Pod Security' section explains that a restricted pod security policy is required for deployment. At the bottom, there is a 'Parameters' section with a link to view all parameters. The 'Install' button is highlighted in blue.

IBM Cloud Private

Create resource Catalog Docs Support

Pod Security Warning Your ICP cluster is running all namespaces Unrestricted (ibm-anyuid-hostpath-psp) by default. This could pose a security risk.

Configuration
IBM Event Streams based on Apache Kafka. Edit these parameters for configuration.

Helm release name * eslab

Target namespace * es

License * ☒ I have read and agreed to the License agreement

Pod Security
To deploy correctly this chart requires a Namespace with an **ibm-restricted-psp** pod security policy.
Target namespace policies
ibm-anyuid-hostpath-psp, ibm-restricted-psp


Parameters
To install this chart, some additional configuration is recommended in Quick Start. If further customization is desired, view All parameters.

Cancel Install

Verifying the installation

In the IBM Cloud Private console, select **Workload** > **Helm Releases**

Click the release name to see more details




NAME ^	NAMESPACE	STATUS	CHART NAME	CURRENT VERSION	AVAILABLE VERSION	UPDATED	ACTION
audit-logging	kube-system	Deployed	audit-logging	3.1.1	Up To Date	December 18, 2018 03:56pm	⋮
auth-apikeys	kube-system	Deployed	auth-apikeys	3.1.1	Up To Date	December 18, 2018 03:51pm	Launch ⋮
auth-idp	kube-system	Deployed	auth-idp	3.1.1	Up To Date	December 18, 2018 03:51pm	Launch ⋮
auth-pap	kube-system	Deployed	auth-pap	3.1.1	Up To Date	December 18, 2018 03:51pm	Launch ⋮
auth-pdp	kube-system	Deployed	auth-pdp	3.1.1	Up To Date	December 18, 2018 03:51pm	Launch ⋮
calico	kube-system	Deployed	calico	3.1.1	Up To Date	December 18, 2018 03:47pm	⋮
catalog-ui	kube-system	Deployed	icp-catalog-chart	3.1.1	Up To Date	December 18, 2018 03:55pm	⋮
cert-manager	kube-system	Deployed	ibm-cert-manager	3.1.1	Up To Date	December 18, 2018 03:49pm	⋮
custom-metrics-adapter	kube-system	Deployed	ibm-custom-metrics-adapter	3.1.1	Up To Date	December 18, 2018 03:55pm	Launch ⋮
eslab	es	Deployed	ibm-eventstreams-prod	1.1.0	Up To Date	May 8, 2019 10:47am	Launch ⋮
heapster	kube-system	Deployed	heapster	3.1.1	Up To Date	December 18, 2018 03:55pm	⋮

Exploring the Event Streams console

Accessing the Event Streams console

To access the Event Streams admin console, click **Launch** in the upper right corner of the release page, and then select **admin-ui-https**.



IBM Cloud Private

Create resource Catalog Docs Support

← View All

eslab ● Deployed
UPDATED: May 8, 2019 at 10:47 AM

Launch

brk2-external
admin-rest-https
admin-ui-https

Details and Upgrades

CHART NAME	CURRENT VERSION	AVAILABLE VERSION	
eslab	1.1.0	1.1.0	
NAMESPACE	es		

Installed: May 8, 2019
→ [Release Notes](#)

Released: May 7, 2019
→ [Release Notes](#)

Upgrade

Rollback


ConfigMap

NAME	DATA	AGE
eslab-ibm-es-replicator-cm	1	30m
eslab-license-accept	1	30m
eslab-ibm-es-metrics-cm	1	30m

Welcome page


Event Streams status
is displayed in the
lower right corner

Click to expand the
status bar




Create a simulated topic

In the Event Streams console, click **Use a simulated topic**



Viewing topics

Select the Topics tab



The screenshot shows the IBM Event Streams console interface. At the top, the header bar displays "IBM Event Streams" on the left, and user information "admin" and a profile icon on the right. Below the header, the "eslab" logo is on the left, and a navigation bar contains the following tabs: "Getting started", "Topics" (which is highlighted with a yellow box and a yellow arrow points to it), "Consumer groups", "Monitor", and "Toolbox". To the right of the navigation bar is a link "Connect to this cluster" with a small icon. Below the navigation bar, the main content area is titled "Topics". It features a search bar with the placeholder text "Type to search topics", a "Geo-replication" button, and a "Create topic" button with a plus icon. Below these elements is a table with the following structure:

Name	Replicas	Partitions
IBM_Simulated_Topic	3	2

The "IBM_Simulated_Topic" row is highlighted with a yellow box. To the right of the table, there is a vertical ellipsis icon. Below the table, there is a text block that reads "Topic management illustration" and a pink callout box that says "You have a simulated topic. The simulated topic will allow you to explore the IBM".

Topic details

On the Topics page, click a topic to view more details about it

The screenshot shows the 'IBM Event Streams' interface. At the top, the header 'IBM Event Streams' is visible along with a user profile 'admin'. Below the header, a blue banner states 'This is a simulated topic with generated data'. The main heading is 'Topics', followed by the specific topic name 'IBM_Simulated_Topic'. There are tabs for 'Messages' (selected) and 'Consumer groups'. A 'Connect to this topic' link is on the right. Below the tabs, a dropdown menu shows 'All partitions' and a status 'Showing 17 message(s) across all partitions'. A 'Find message' link is on the right. A notification box at the top of the message list says 'This is a simulated topic'. Below this, a 'Show messages from date:' section includes a calendar for May 2019 with the 8th selected. To the right is a table with columns 'Kafka timestamp', 'Partition', and 'Offset'. The table contains four rows of simulated data. At the bottom right, a green checkmark icon is next to the text 'System is healthy'.

IBM Event Streams

admin

This is a simulated topic with generated data

Topics

IBM_Simulated_Topic

Messages Consumer groups

Connect to this topic

All partitions Showing 17 message(s) across all partitions Find message

This is a simulated topic

Show messages from date:

5/8/2019

MAY 2019

Kafka timestamp	Partition	Offset
5/8/2019, 2:11:09 PM	0	0
5/8/2019, 2:11:09 PM	1	0
5/8/2019, 2:11:11 PM	0	1
5/8/2019, 2:11:13 PM	0	

System is healthy

Creating a topic

On the Topics page,
click **Create Topic**

Click **Advanced** to
expand and review the
configuration
parameters that are
available

Click **Next** to proceed
through the remaining
options, and then
click **Create Topic**

The screenshot shows the 'Create topic' configuration page in the IBM Event Streams console. The page has a dark blue header with 'IBM Event Streams' and a light gray sub-header with a back arrow and 'Topics'. The main title is 'Create topic'. Below it is a progress indicator with four steps: 'Advanced' (selected), 'Name', 'Partitions', and 'Replicas'. The 'Advanced' section is expanded, showing a toggle switch for 'Advanced' (currently off) and a 'Replicas' section. The 'Replicas' section has three radio button options: 'Replication factor: 1, Minimum in-sync replicas: 1', 'Replication factor: 3, Minimum in-sync replicas: 2' (selected), and 'Replication factor: 3, Minimum in-sync replicas: 2'. Below these are two dropdown menus for 'Replication factor' (set to 3) and 'Minimum in-sync replicas' (set to 2). A yellow callout box points to the 'Replicas' section with the text: 'This is how many copies of a topic will be made for high availability. The partitions of each topic can be replicated across a configurable number of brokers.' At the bottom right, there are two buttons: 'Back' and 'Create topic'. The 'Create topic' button is highlighted with a yellow border and a yellow arrow points to it from the callout box.

IBM Event Streams

← Topics

Create topic

Advanced ☐

Replicas

☐ Replication factor: 1
Minimum in-sync replicas: 1

☒ Replication factor: 3
Minimum in-sync replicas: 2

Replication factor

3

Minimum in-sync replicas

2

This is how many copies of a topic will be made for high availability.
The partitions of each topic can be replicated across a configurable number of brokers.

Back Create topic

Connecting to a topic

On the topic page,
click Connect to this
topic

The address and port
of the bootstrap server
is displayed


The screenshot shows the IBM Event Streams console interface. At the top, the header reads 'IBM Event Streams' with a user profile 'admin' and a settings icon. Below the header, the breadcrumb 'Topics' is visible. The main content area displays the topic name 'eslab'. There are tabs for 'Messages' and 'Consumer groups'. A dropdown menu shows 'All partitions'. On the right side, there is a button 'Connect to this topic' with a magnifying glass icon, which is highlighted by a yellow box and a yellow arrow. Below this button is a 'Find message' link. A modal window titled 'Topic connection' is open in the foreground. It has three tabs: 'Connect a client' (active), 'Sample code', and 'Geo-replication'. The modal contains the text: 'To connect an application or tool to this cluster, you will need address of a bootstrap server, a certificate and an API key.' Below this, under the heading 'Bootstrap server', it says 'Your application or tool will make its initial connection to the cluster using the bootstrap server.' At the bottom of the modal, the bootstrap server address '10.0.0.5:32643' is displayed in a light blue box and is circled with a yellow oval. A copy icon is to the right of the address.

Working with the sample applications

Using the starter application

Click the **Toolbox** tab

Click **Generate application**



The screenshot shows the 'eslab' web interface. At the top, there is a navigation bar with tabs: 'Getting started', 'Topics', 'Consumer groups', 'Monitor', and 'Toolbox' (which is selected). To the right of the tabs is a link 'Connect to this cluster' with a small icon. Below the navigation bar, the main content area is titled 'Applications'. On the left, there is a sidebar with a search bar and a list of application categories. The main content area displays two application cards. The first card is titled 'Starter application' and contains the text: 'Download and install this application which you can connect to a topic. This application is a full project containing a Kafka producer and consumer for you to try out.' Below this text is a purple button labeled 'Generate application', which is highlighted with a yellow rectangular border. A yellow arrow points from the left towards this button. To the right of the 'Generate application' button is a link 'Just looking for the instructions?'. The second card is titled 'Workload generation application' and contains the text: 'Want to quickly validate your IBM Event Streams instance? Download and run a pre-built tool to generate messages at a configurable rate, or download and modify the source to simulate your own workload.' Below this text is a purple button labeled 'View in GitHub'.

Configuring the starter application

Enter an application name, and select a topic

Select the options to produce or consume message


Click **Generate**

The screenshot shows the 'Toolbox' configuration window for a starter application. The 'Application name' field is set to 'eslabtester' and is highlighted with a yellow box. Below it, the question 'What do you want this application to be able to do?' has two checked options: 'Produce messages' and 'Consume messages'. The next section, 'Which topic shall we connect with?', offers two choices: 'Create topic' (unselected) and 'Choose existing topic' (selected). The 'Choose existing topic' dropdown menu is set to 'eslab' and is also highlighted with a yellow box. At the bottom right, the 'Generate' button is highlighted with a yellow box and pointed to by a yellow arrow. Other visible elements include a 'Cancel' button, a link 'Just looking for the instructions?', and a status indicator 'System is healthy' with a green checkmark.

Downloading the application

After the starter application is generated, click **Download** and save the archive file

Extract and run the application (`mvn install`)



← Toolbox

Starter application

✓ The starter application has been generated

- 1. Download the starter application**
Download the compressed file and extract the contents to your preferred location.
Download
- 2. Navigate to the extracted file and run this command to build and deploy the application**
Java version 8 and Maven are prerequisites to building and running the starter application
[Maven download repository](#)

```
mvn install liberty:run-server
```

Running the application

In a browser tab, enter the following URL:

http://localhost:9080/<application_name>

Click the arrow to start producing messages

The screenshot shows the IBM Event Streams Starter Application interface. It is divided into two main panels. The left panel, titled 'Starter Application', contains a 'How does this work?' section, a large '00' counter for 'messages have been produced', a text input field for 'Custom payload string (optional)' with a placeholder 'Add custom payload (Hello World)', and a 'Most recent messages' section. A blue callout box with the text 'Click to start producing messages' and a downward arrow points to a blue play button icon next to the payload input field. The right panel shows a large '00' counter for 'messages have been consumed', a 'Most recent messages' section, and a table with headers 'Partition' and 'Offset'. A blue callout box with the text 'Consumer is listening for messages' and a downward arrow points to a yellow-bordered box containing a 'Stop listening for messages' button and a small blue square icon.

Running the application (cont.)

The producer begins producing messages, which are sent to the Topic

On the consumer side, the number of messages increments, while the message list becomes populated

The screenshot displays the 'IBM Event Streams Starter Application' interface. It is divided into two main panels. The left panel, titled 'How does this work?', explains the application's purpose and shows a large '10' indicating 'messages have been produced' for the 'topic: eslab'. It includes a 'Custom payload string (optional)' field with the value 'Hello World!' and a 'Show 5 most recent message(s)' button. The right panel shows a large '10' indicating 'messages have been consumed' for the 'topic: eslab'. It features a 'Stop listening for messages' button and a table of the 10 most recent messages.


Showing 10 most recent message(s)	Partition	Offset
Message 10	0	9 Consumed at 4:50:25 PM
Message 9	0	8 Consumed at 4:50:23 PM
Message 8	0	7 Consumed at 4:50:21 PM

Using the workload generator

There is another sample application that you can use to generate workloads of a specific size


You can use one of the predefined load sizes, or you can specify your own settings to test throughput

You download the application from GitHub



Running an application with load

When you run the workload generator application, you can see some metrics for the load on the Monitor tab



More resources

Installing IBM Event Streams

<https://ibm.github.io/event-streams/installing/installing/>

Generating a starter application

<https://ibm.github.io/event-streams/getting-started/generating-starter-app/>

Creating and testing message loads

<https://ibm.github.io/event-streams/getting-started/testing-loads/>



