

Release Note

The original "User Guide" provided with MS15 has been converted to Latex from IBM's BookManager format and follows.

The code, mnglogs.exec, was most recently updated in 2014 to handle the 8 byte "wide" RBA capability provided in IBM MQ Version 8.0

MS15: MQSeries for MVS/ESA
Archive log housekeeping
Version 1.2
User Guide

Pete Siddall
IBM Hursley Development Lab
pete_siddall@uk.ibm.com

20th December, 1999

Take Note!
Before using this User's Guide and the product it supports, be sure to read the general information under "Notices".

Fourth Edition, April 2005 This edition solves some issues with deleting archives. If the delete of an archive log or bsds copy fails for a reason other than entry not found, the TSO error messages are shown.

A new option, DELPURGE, allows the PURGE operand of the DELETE command to be used, overriding any expiration processing.

Third Edition, September 2002 This edition features changes made to packaging as a result of re-issuing the software to accomodate changes required to support WebSphere MQ for z/OS Version 5 Release 3.

Second Edition, December 1999 This edition applies to Version 1.1 of MQSeries for MVS/ESA Archive log housekeeping and to all subsequent releases and modifications until otherwise indicated in new editions.

A form for reader's comments is provided at the back of this publication. If the form has been removed, address your comments to:

IBM United Kingdom Laboratories
Transaction Systems Marketing Support (MP102)
Hursley Park
Hursley
Hampshire, S021 2JN, England

When you send information to IBM, you grant IBM a non-exclusive right to use or distribute the information in any way it believes appropriate without incurring any obligation to you. You may continue to use the information that you supply.

Copyright

Copyright ©1999, 2016 IBM Corporation and other Contributors.

All rights reserved. This program and the accompanying materials are made available under the terms of the Eclipse Public License v1.0 which accompanies this distribution, and is available at <http://www.eclipse.org/legal/epl-v10.html>

Notices

The following paragraph does not apply in any country where such provisions are inconsistent with local law.

INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Some states do not allow disclaimer of express or implied warranties in certain transactions, therefore this statement may not apply to you.

References in this publication to IBM products, programs, or services do not imply that IBM intends to make these available in all countries in which IBM operates.

Any reference to an IBM licensed program or other IBM product in this publication is not intended to state or imply that only IBM's program or other product may be used. Any functionally equivalent program that does not infringe any of the intellectual property rights may be used instead of the IBM product. Evaluation and verification of operation in conjunction with other products, except those expressly designated by IBM, is the user's responsibility.

IBM may have patents or pending patent applications covering subject matter in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to the IBM Director of Licensing, IBM Corporation, 500 Columbus Avenue, Thornwood, New York 10594, USA.

The information contained in this document has not been submitted to any formal IBM test and is distributed AS IS. The use of the information or the implementation of any of these techniques is a customer responsibility and depends on the customer's ability to evaluate and integrate them into the customer's operational environment. While each item has been reviewed by IBM for accuracy in a specific situation, there is no guarantee that the same

or similar results will be obtained elsewhere. Customers attempting to adapt these techniques to their own environments do so at their own risk.

The following terms are trademarks of the International Business Machines Corporation in the United States and/or other countries:

- MQSeries
- IBM
- MVS
- ESA
- MQM

Date	Changes
April 2005	Description of the new DELPURGE option.
September 2002	The SLEEP module originally supplied as part of this package is now no longer required as it is available in base OS/390 and z/OS function.
20th December 1999	Added function to enable this tool to be tied into backup procedures to ensure that archive logs are only deleted once suitable backups have been taken.
20th October 1999	Initial release

Introduction

This document describes an exec designed to housekeep archive logs stored on disk by MQSeries for MVS/ESA, i.e. it will delete redundant archive logs in order to save disk space. The archive logs are regarded as redundant from the MQSeries for MVS/ESA recovery perspective, i.e. they are not required by the product to recover from a failure. If you need to keep archive logs for reasons other than recovery then you should not use this exec.

You must keep in mind that there are certain recovery scenarios, where you might need the archive logs, even though they are eligible to be deleted by the exec, for instance if you need to restart using a backup of a pageset that has been damaged, you will need the active and archive log backups that go with the pageset backup in order to recover your queue manager. For this reason, it is essential that you consider use of this exec in association with your backup procedures.

Note: This Supportpac requires SupportPac MA19 in order to submit commands to the queue manager from a REXX exec.

Installation

Take the following actions to install the SupportPac from the MS15.ZIP file:

1. Use **INFOZIP's** UNZIP to unpack the **MS15.ZIP** file.

This produces

ms15.src Source library

ms15.loa Load library

license2.txt License file

2. The library files need to be transferred to the destination TSO system as sequential binary filed with a record format of FB 80. Use one of the following methods to accomplish this:

- To send them via ftp ensure the BINARY option is set then use the following commands:

```
site fixrecfm 80
put ms15.src ms15.srcseq
put ms15.loa ms15.loadseq
```

- With Personal Communications, use the "Send Files to Host" option under the Transfer menu item to transmit to TSO

```
PC File          ms15.src etc
Host File        ms15.srcseq etc
Transfer Type    loadlib
```

The Transfer type of **loadlib** may need to be correctly setup. To do this, use the "Setup.Define Transfer Types" option under the Transfer menu item and create the **loadlib** type with the Ascii, CRLF and Append checkboxes all unselected, the **Fixed** radio button selected and the **LRECL** set to **80**.

3. On TSO, issue the following commands to unload these sequential files into TSO partitioned datasets:

- `receive indsnam(ms15.srcseq)`
when prompted for a filename, reply
`dsn(ms15.source)`
- `receive indsnam(ms15.loadseq)`
when prompted for a filename, reply
`dsn(ms15.load)`

4. Confirm that the datasets have been unloaded correctly by browsing the PDS and ensuring the appropriate members exist as shown in the following table:

DATASET	MS15 LOAD	MS15 SOURCE
MEMBERS	SLEEP	MNGLOGS MNGLOGSJ SLEEP SLEEPJ

Enabling the exec

To run the exec you should tailor the MNGLOGSJ job to your requirements, it looks like this:

```
//<jobcard>
// SET MA19LOAD=<MA19.LOADLIB>
// SET MS15=<MS15 HIGH LEVEL QUALIFIERS>
// SET MQHLQS=<MQSERIES HIGH LEVEL QUALIFIERS>
//RMNGLOGS EXEC PGM=IKJEFT01,REGION=2M,DYNAMNBR=99
//SYSEXEC DD DSN=&MS15..SOURCE,DISP=SHR
//SYSTSPRT DD SYSOUT=*
//SYSPRINT DD SYSOUT=*
//STEPLIB DD DSN=&MA19LOAD.,DISP=SHR /* MA19 SUPPORTPAC */
// DD DSN=&MQHLQS..SCSQANLE,DISP=SHR
// DD DSN=&MQHLQS..SCSQAUTH,DISP=SHR
//SYSTSIN DD *
%MNGLOGS QMGR(<QUEUE MANAGER NAME E.G. VCMA>) -
  HLQS(<MQSERIES HIGH LEVEL QUALIFIERS E.G. MQ.V210>) -
  BS1(<BOOTSTRAP DATA SET NO.1 NAME E.G. MQ.VCMA.BSDS01>) -
  BS2(<BOOTSTRAP DATA SET NO.2 NAME E.G. MQ.VCMA.BSDS02>) -
  BSDS(<DUAL BOOTSTRAPS? Y OR N>) -
  SLEEP(<SLEEP PERIOD BETWEEN CHECKS IN SECONDS>)
  BACKUP(<TAKE BACKUPS? Y OR N>) -
  RUNTYPE(<O - ONCE, C - CONTINUOUS>) -
  RESTARTRBA(<RESTART RELATIVE BYTE ADDRESS>) -
  DELPURGE(<USE DELETE PURGE? Y or N>)
/*
```

You will need one copy of this job for each queue manager you wish to run it against.

1. Replace <jobcard> with valid job details for your system
2. Replace <MA19.LOADLIB> with the fully qualified name of the MA19 SupportPac load library.
3. Replace <MS15 HIGH LEVEL QUALIFIERS> with the high level qualifiers of the MS15 SupportPac data sets.
4. Replace <MQSERIES HIGH LEVEL QUALIFIERS> with the high level qualifiers of the MQSeries for MVS/ESA data sets.

5. Replace <QUEUE MANAGER NAME E.G. VCMA> with the name of the queue manager whose archive logs the exec will be monitoring.
6. Replace <MQSERIES HIGH LEVEL QUALIFIERS E.G. MQ.V210> with the high level qualifiers of the MQSeries for MVS/ESA data sets.
7. Replace <BOOTSTRAP DATA SET NO.1 NAME E.G. MQ.VCMA.BSDS01> with the name of your 1st bootstrap data set.
8. If you have a 2nd bootstrap data set, then replace <BOOTSTRAP DATA SET NO.2 NAME E.G. MQ.VCMA.BSDS02> with the name of your 2nd bootstrap data set, otherwise delete this particular record from the job.
9. If you are using dual bootstrap data sets for this queue manager, then replace <DUAL BOOTSTRAPS? Y OR N> with Y, otherwise replace it with N. It is essential that this parameter is set correctly otherwise it could result in dual bootstrap data sets becoming inconsistent.
10. Replace <SLEEP PERIOD BETWEEN CHECKS IN SECONDS> with the time in seconds that you want the exec to sleep between checking the status of the archive logs, for example, 300 will cause it to sleep for 5 minutes.
11. If you want the exec to start your backup procedures, you need to do the following:
 - (a) Edit MNGLOGS EXEC, and change the perform_backups routine at the very bottom of the exec to run your backup procedures. The backups should include:
 - Pagesets
 - Bootstrap datasets
 - Active logs
 - Archive logs
 - Object definitions if you need to keep them independently.

To drive the backups, the exec uses two variables to hold the restart relative byte address:

Variable	Content
restart__rba	The restart RBA in hexadecimal.
decimal__restart__rba	The restart RBA in decimal.
 - (b) In MNGLOGSJ replace <TAKE BACKUPS? Y OR N> with Y.

12. If you do not want MNGLOGS to start your backup procedures, replace <TAKE BACKUPS? Y OR N> with N.
13. If you want the exec to check the archive logs once only i.e. check and delete any redundant archive logs, and then terminate, replace <O - ONCE, C - CONTINUOUS> with O. If however you want the exec to run continuously in parallel with the queue manager then replace <O - ONCE, C - CONTINUOUS>with C.
14. If you want to specify to MNGLOGS the restart RBA you want it to start with then replace <RESTART RELATIVE BYTE ADDRESS> with the restart RBA you want it to use in hexadecimal notation, for example: 6DF37FFFF. This is an alternative way for you to tie the exec into your backup procedures. If you do not want to use this parameter, remove it from the JCL, and remove the continuation mark '-' from the end of the previous line.
15. If you want to delete archives, regardless of the retention period specified for the dataset (ARCRETN in CSQ6ARVP for ZPARMS). Use the operand DELPURGE(Y), so that a DELETE dsn PURGE command is used.

SLEEP function

The USS services sleep() function is now used instead of the SLEEP module described in the following paragraph.

A TSO sleep function is provided with this SupportPac, which enables the exec to sleep (i.e. Not use any system resources) for a specified period. The source for this function (SLEEP) and sample JCL to build it (SLEEPJ) can be found in the MS15.SOURCE data set.

What it does

The exec is intended to manage archive logs on disk so that you only keep the ones MQSeries needs to be able to recover from a failure or backout incomplete work, however there are certain disaster scenarios, for instance pageset damage, which might require you to recover from archive logs which are no longer necessary to recover a clean system. It is therefore vital that you consider backing up your archive logs along with your pagesets, bootstrap data sets, and active logs, before deleting them from your main storage, to this end the exec has been written to allow you to tie it in with your backup procedures.

The exec can be run in one of two modes:

1. Once only:

Delete any redundant archive logs and then stop.

2. Continuous execution:

For as long as the queue manager is running, every so many seconds, delete any redundant archive logs and then sleep. This allows you to keep mainline DASD usage to the minimum required by the queue manager.

You can tie the exec into your backup procedures in one of two ways:

1. By specifying as a parameter the Restart Relative Byte Address (RBA) you have used for your backups, and running the exec in the "Once only" mode.
2. By specifying the backup parameter as "Y". This will cause the exec to run a subroutine called `perform_backups`. You should tailor this subroutine to execute your backup procedures.

The exec performs the following processing:

1. Determines whether the queue manager is active, and if it is:
 - (a) Using either the MQSeries DISPLAY USAGE command, or the RESTARTRBA parameter, determines the restart RBA (Relative Byte Address) to be used to determine which archive logs can be deleted.
 - (b) If requested, it runs the routine which can be tailored to run your backup procedures.
 - (c) Using the CSQJU004 utility shipped with MQSeries for MVS/ESA, it determines what archive logs the queue manager has produced.
 - (d) It Determines which of the archive logs are out of date with respect to the restart RBA and deletes them. DELETE PURGE may be used to override dataset expiration processing, if DELPURGE(Y) parameter has been specified.
 - (e) The DELETE is recorded as successful if either, it completes with return code zero, or, it only fails because the entry is not found (it has already been deleted). In other situations, the error messages resulting from the failed delete are printed.
 :note.It is not possible at this point in time to remove the references to the deleted archive logs from the bootstrap data sets as MQSeries has an exclusive lock on the BSDS.
 - (f) It then goes to sleep for the specified period.
 - (g) Repeats the above steps, unless you have specified that it should only perform them once.
2. When the queue manager is found to be no longer active and if there have been successful deletions, then the CSQJU003 utility is used to update the bootstrap data sets, removing the references to the deleted archive logs from them.

Possible Extensions

The process_archives routine could be extended to use the LISTDSI function to determine the current location of archive logs. Once established, the routine could use HMIGRATE to cause HSM to migrate newly created archive logs, or HDELETE instead of DELETE to delete old logs without causing them to be recalled first.