



## **L02 – CICS-Security Request Recording**

*Lab Version V0.1*

---

**October, 2022**

Please send any comments on this lab exercise to:  
SangSoo HAN or Manjunath D  
[sshan@sg.ibm.com](mailto:sshan@sg.ibm.com)  
[manjud46@sg.ibm.com](mailto:manjud46@sg.ibm.com)

## **Overview**

Security request recording (SRR) can be used to help you diagnose CICS® security issues.

---

### *What sort of issues can security request recording help you solve?*

Many security problems are straightforward to solve. The ICH408I messages give details of the user ID, RACF® profile, RACF class, and the required access. Associated DFHXS1111 and DFHXS1117 message help identify the user so that the problem can be identified and if necessary access granted.

Some problems are more difficult to solve. Often these problems occur as a result of a help desk problem that the system programmer needs to investigate. These problems might include various complexities:

- The application that is being investigated might traverse multiple regions, multiple LPARs, or even multiple sysplexes.
- There might not be any messages that are associated with the reason that causes a security failure.
- The application might grant access to something when it mustn't.

## **Lab Scenario**

In our scenario, you are a system programmer and need to configure SEC=YES for all your CICS regions. But the application does not work after the change and you can't check some CICS resources, either. Then, you turn on the security request recording function and check the RACF classes and profiles caused the errors and issue correct RACF commands to make the application work.

## **Lab Requirements**

Please note that there are often several ways to perform functions in and for CICS. This lab exercise will present one of the ways. If you are familiar with CICS, you will notice that some of the statements are general, and not necessarily true for every situation.

This lab uses the PCOMM and CICS Explorer. If you are not familiar with these, please contact one of the lab instructors for assistance.

The following are other assumptions made in this lab exercise.

- **CICS TS V6.1:** This lab exercise only works in CICS V6.1. You have your own z/OS image you can change all resources in four CICS regions.
- **Login:** A TSO userid is available with the appropriate password provided, and you will also use the same TSO userid with the z/OS Explorer.
- **The CICS Explorer:** In the lab environment we have installed the CICS Explorer to configure CICS resources and the security request recording function.

## **Lab Step Overview**

### **Part 1: Try the CICS bank sample application (hereafter CBSA) in 4 CICS regions**

Logon to the CICS61T1 and run the transaction OMEN. Then, try to browse customer number with “1” and display the account “1” in menus. Make sure no problems happen there.

### **Part 2: Change the SIT parameters of all CICS regions and restart them**

Set “SEC=YES” on all CICS regions.

### **Part 3: Try again the CBSA and check errors**

Try to browse the customer number, “1” in the customer inquiry menu and see the application making errors.

### **Part 4: Configure the Journal for the CICS Security Request Recording (SRR)**

Create the journal model to create the DFHSECR journal.

### **Part 5: In the CICS Explorer, setup the SRR for a CEMT transaction and browse journals**

Setup the SRR for the CEMT transaction in the CICS Explorer and issue “CEMT I JO” command in a CICS region.

### **Part 6: Check the SRR result and issue RACF commands to browse journals by CEMT**

Check the SRR CSV file and create a RACF command to resolve the journal “Not found” error in CICS.

### **Part 7: Turn on the SRR for the ODSC transaction in all CICS regions**

In the region view of CICS Explorer, turn on the SRR log for ODSC transaction in all four CICS regions.

### **Part 8: Check the SRR result and issue RACF commands to resolve ODSC errors**

Check the SRR CSV file and create a RACF command to resolve the ODSC transaction error.

### **Part 9: Summary**

This is a recap of the steps performed in this lab exercise and answers for quizzes.

## **Part 0: Check the CICS Explorer Connection to CICS**

In this part of the lab exercise you will configure the connection between the CICS Explorer running on your workstation to CICS running on z/OS.

### **Start the CICS Explorer**

- \_\_\_1. From the **desktop**, **double-click** the **CICS Explorer** icon to start the Explorer if it is not already running.




- \_\_\_2. When you start the Explorer, if you are prompted for a workspace, click the **OK** button to select the default.
- \_\_\_3. If the Explorer shows you a **Welcome page** click the **Workbench icon** in the upper-right corner to go to the workbench. Then **maximize** the Explorer window.



### **Verify that you have an FTP connection to z/OS in your CICS Explorer**

- \_\_\_4. If you have not already created connections to the z/OS host system, check the connection as in the screen shot. Both the **Remote System Explorer** and **CMCI** connections should be started and active.

**IP : zos.dev / CMCI port : 6611 / User : IBMUSER / Password : sys1**



## **Part 1: Try the CICS bank sample application (hereafter CBSA) in 4 CICS regions**

In this part of the lab exercise you will try the CICS bank sample application.

### **Try the CICS Bank Sample Application**

- \_\_\_1. Open a session in the PCOMM, and type “L CICS61T1” to logon.
- \_\_\_2. Clear the screen and type “OMEN” to start the main screen.

```
BNK1MA          CICS Bank Sample Application - Main Menu

Select an option. Then press Enter.

Action . . . . _ 1. Display/Delete/Update CUSTOMER information
                  2. Display/Delete ACCOUNT information
                  3. Create CUSTOMER
                  4. Create ACCOUNT
                  5. Update ACCOUNT
                  6. Credit/Debit funds to an ACCOUNT
                  7. Transfer funds

                  A. Look up Accounts with Customer Number

F3=Exit  F12=Cancel
```

- \_\_\_3. Try to display the customer number 1 and the account number 1. Also, you can create customer and account numbers as you want to test the CICS Bank Sample Application. ( CBSA )



## **Part 2: Change the SIT parameters of all CICS regions and restart them**

To make the RACF security issues, SEC=YES is set in all four CICS61\* regions. ( CICS61T1, CICS61A1, CICS61A2, CICS61F1 )

\_\_\_1. From **the PCOMM**, logon TSO.

L TSO

TSO User : IBMUSER / password : SYS1

\_\_\_2. In CICS.CICS61.SYSIN, update all SIT members which have the same names as CICS regions.  
**SEC=YES**

\_\_\_3. Restart CICS regions in SDSF:

**=S;DA;PRE CICS61\***

**/S STO61**

**/S STA61**

The STO61 procedure will cancel four CICS regions and the STA61 procedure will start four CICS regions.



## **Part 3: Try again the CBSA and check errors**

In this part of the lab exercise, we will try the CBSA application again and see an application error and you can't see the journal resource by using CEMT command. \

### **Retry the CBSA**

- \_\_\_4. In the CICS61T1, run **OMEN**, select **menu 1**, put **1** into the **customer number** field, and check the application error message as follows:

```
BNK1DC          CICS Bank Sample Application - Display Customer.

Provide a CUSTOMER number. Then press Enter.

CUSTOMER NUMBER 1_____

Sort Code
Customer Number
Customer Name
Customer Address

Customer D.O.B.      /      /
Credit Score
CS Review Date      /      /

DFHAC2206 21:06:11 CICS61T1 Transaction ODCS failed with abend AZI6. Updates
to local recoverable resources backed out. DFHAC2261 System 61A2 sent message
(sense code 0824089E). 'DFHAC2206 21:06:11 CICS61A2 Transaction ODCS failed
with abend HBNK. Updates to local recoverable resources backed out.'
```

## **Part 4: Configure the Journal for the CICS Security Request Recording (SRR)**

The CICS Security Request Recording ( CSRR ) writes the logs to the journal, DFHSECR. We will configure a journal model to create a DASD only log stream for this journal.

### **Define a journal model in CICS**

- \_\_\_1. In any CICS region, define a new journal model, **DFHSECR** and add it to the CICS group list.

```
CEDA COPY G(DFHSECR) JOURNALMODEL(DFHSECR) TO(CBSASECR)
CEDA ADD G(CBSASECR) LIST(61LIST)
```

- \_\_\_2. Restart all CICS regions to install the DFHSECR to all CICS regions.

```
/S STO61
/S STA61
```

### **Define a logstream model in the z/OS logger**

- \_\_\_3. Create a logstream model for the journal model, **DFHSECR**.

```
CICS.CICS61.JCL(DFHSECR)
```

```
//DFHILGSR JOB CLASS=A,MSGCLASS=X,NOTIFY=&SYSUID,REGION=0M
//DFHILG6 EXEC PGM=IXCMIAPU
//SYSPRINT DD SYSOUT=*
//SYSIN DD *
DATA TYPE(LOGR) REPORT(YES)
/* User journals */
DEFINE LOGSTREAM NAME(#####.STREAM.@@@@@)
MODEL(YES)
DASDONLY(YES)
MAXBUFSIZE(64000)
AUTODELETE(YES)
RETPD(1)
/*
```

Quiz 1 : What values should replace ##### and @@@@@ in the above JCL?


If you don't know the answer, please check it at the last page of this document.

## **Part 5: In the CICS Explorer, setup the SRR for a CEMT transaction and try to browse journals by CEMT**


In this part, you will turn on the SRR in the CICS explorer and try to capture the logs from a CEMT transaction.

### **Turn on the SRR in the CICS Explorer for a CEMT transaction**


- \_\_\_1. Open the CICS Explorer and select the **CICS SM** perspective.




- \_\_\_2. Click “Regions” after selecting the CPSM61PX context and the Operations Menu.




- \_\_\_3. Open a SRR session by right clicking on CICS61T1.



- \_\_\_4. Put **CEMT** in the Name field, **5** in Maximum field and **CEMT** in the “Transaction ID” field. Then click OK.



- \_\_\_5. Select the **Security Request Recording** menu in the **Operations** menu.



- \_\_\_6. Run “**CEMT I JO(\*)**” multiple times in CICS61T1 and check the “Current” filed in the Security Request Recording view.

```
I JO(*)
STATUS: RESULTS - OVERTYPE TO MODIFY
Jou(*)                                NOT FOUND

SYSID=61T1 APPLID=CICS61T1
TIME: 23.04.10 DATE: 10/05/22
RESPONSE: 1 ERROR
PF 1 HELP      3 END      5 VAR      7 SBH 8 SFH 9 MSG 10 SB 11 SF
```

Security Request Recordings										
CNX02111 Context: CPSM61PX. Resource: SECREC. 1 record collected at 5 Oct, 2022 11:04:54 PM										
Region	Name	Application ID	Client IP Addr	Facility Type	Facility Name	LU Name	Network ID	Net ID	TCP/IP Service	Transaction ID
CICS61T1	CEMT			NOTAPPLIC						CEMT
									Maximum	Current
									5	1

1 in the Current field

**NOTE:** CEMT is a conversational transaction. To get a new security request recording for CEMT, you need to type the CEMT transaction again from the initial screen.

The “I JO(\*)” screen is an active started task and new entering in this screen is not a new transaction, so you can’t see any number increase in the Current field.

## **Part 6: Check the SRR result and issue RACF commands to browse journals by CEMT**

In this step you will check the generated report and find out RACF profile and class names which caused the “NOT FOUND” exception for your “CEMT I JO(\*)” command.

### **Run the batch job to generate a CSV file and view it in the VS Code**

**\_\_\_1. From the TSO, run the batch JCL to extract the SRR logs and write to a CSV file.**

#### **CICS.CICS61.JCL(DFHSSRPC)**


```
//DFH$SRRP JOB CLASS=A,MSGCLASS=X,NOTIFY=&SYSUID,REGION=0M
// SET CSV='/cics/cics61/srrCEMT.csv'
// SET LOGSTRM=DFHSECR.STREAM.NAME
// SET HLQ=IBMUUSER.GM02.CTS61BT.CICS
//*****
/* Ensure that CSV file is deleted without nonzero RC                                *
//*****
//CREATE      EXEC PGM=IEFBR14
//CSV         DD PATHOPTS=(ORDWR,OCREAT),
//             PATHMODE=(SIRUSR,SIWUSR),
//             PATHDISP=(KEEP,KEEP),PATH='&CSV'
//DELETE      EXEC PGM=IEFBR14,COND=EVEN
//CSV         DD PATHDISP=(DELETE,DELETE),PATH='&CSV'
//*****
/* Convert logstream to CSV file                                                    *
//*****
//SRR         EXEC PGM=DFHSSRR,REGION=4M
//STEPLIB     DD DISP=SHR,DSN=&HLQ..SDFHLINK
//DFHSECR     DD DSNAME=&LOGSTRM.,DCB=BLKSIZE=32760,
//             SUBSYS=(LOGR,DFHLGCNV)
//DFHCSV      DD PATHOPTS=(OWRONLY,OCREAT),
//             PATHMODE=(SIRUSR,SIWUSR),
//             PATHDISP=(KEEP,DELETE),FILEDATA=TEXT,
//             RECFM=VB,LRECL=1024,BLKSIZE=32760,
//             PATH='&CSV'
//SUMMARY     DD SYSOUT=*
//RECORD      DD SYSOUT=*
//SYSPRINT    DD SYSOUT=*
//SYSOUT      DD SYSOUT=*
//SYSUDUMP    DD SYSOUT=*
//SORTWK01    DD UNIT=SYSDA,SPACE=(CYL,(4))
//SORTWK02    DD UNIT=SYSDA,SPACE=(CYL,(4))
//SORTWK03    DD UNIT=SYSDA,SPACE=(CYL,(4))
//SORTWK04    DD UNIT=SYSDA,SPACE=(CYL,(4))
//SYSIN       DD *
MATCHID=CEMT
/*
//*****
```

```

/* Tag CSV file as EBCDIC data                                     *
/*****
//TAG          EXEC PGM=BPXBATCH,PARM='sh chtag -t -c IBM-1047 &CSV'
//STDOUT      DD SYSOUT=*
//STDERR      DD SYSOUT=*

```

2. From the **z/OS Explorer**, the **Remote System Explorer** perspective, the **Remote Systems** view, **right-click** on **/cics/cics61/srrCEMT.csv**, and select the external program, (VS) Code.



Right click --> Open with --> Other --> (VS) Code

3. From the **VS Code**, a **CSV extension editor** is shown. Then, click “**Edit CSV**” icon in the top right corner to see the data in a table view.

profile, class and response columns

column 3	column 4	column 5	column 6	column 7	column 8	column 9	column 10	column 11	column 12	column 13	column 14
odstarttime	appid	transid	taskid	userid	resource_type	profile	class	access	response	reason	saf_
2022-10-02 09:18:19.749057	CICS611T	CEMT	65	CICSUSER	TRANSATTACH	CEMT		READ	OK	XTRAN=NO	
2022-10-02 09:18:19.749057	CICS611T	CEMT	65	CICSUSER	PROGRAM	DFHEITMT		READ	OK	XPPT=NO	
2022-10-02 09:18:19.749057	CICS611T	CEMT	65	CICSUSER	PROGRAM	DFHEMTD		READ	OK	XPPT=NO	
2022-10-02 09:18:19.749057	CICS611T	CEMT	65	CICSUSER	SPI Command	JOURNALNAME		READ	OK	XCMD=NO	
2022-10-02 09:18:19.749057	CICS611T	CEMT	65	CICSUSER	JOURNALNAME	DFHLOG	JCICSJCT	READ	EXCEPTION	NOTAUTH(NOLOG)	4
2022-10-02 09:18:19.749057	CICS611T	CEMT	65	CICSUSER	JOURNALNAME	DFHSHUNT	JCICSJCT	READ	EXCEPTION	NOTAUTH(NOLOG)	4
2022-10-02 09:18:19.749057	CICS611T	CEMT	65	CICSUSER	SPI Command	JOURNALNAME		READ	OK	XCMD=NO	
2022-10-02 09:18:19.749057	CICS611T	CEMT	65	CICSUSER	JOURNALNAME	DFHLOG	JCICSJCT	READ	EXCEPTION	NOTAUTH(NOLOG)	4
2022-10-02 09:18:19.749057	CICS611T	CEMT	65	CICSUSER	JOURNALNAME	DFHSHUNT	JCICSJCT	READ	EXCEPTION	NOTAUTH(NOLOG)	4
2022-10-02 09:18:19.749057	CICS611T	CEMT	65	CICSUSER	SPI Command	JOURNALNAME		READ	OK	XCMD=NO	
2022-10-02 09:18:19.749057	CICS611T	CEMT	65	CICSUSER	JOURNALNAME	DFHLOG	JCICSJCT	READ	EXCEPTION	NOTAUTH(NOLOG)	4
2022-10-02 09:18:19.749057	CICS611T	CEMT	65	CICSUSER	JOURNALNAME	DFHSHUNT	JCICSJCT	READ	EXCEPTION	NOTAUTH(NOLOG)	4
2022-10-02 09:18:19.749057	CICS611T	CEMT	65	CICSUSER	SPI Command	JOURNALNAME		READ	OK	XCMD=NO	
2022-10-02 09:18:19.749057	CICS611T	CEMT	65	CICSUSER	JOURNALNAME	DFHLOG	JCICSJCT	READ	EXCEPTION	NOTAUTH(NOLOG)	4
2022-10-02 09:18:19.749057	CICS611T	CEMT	65	CICSUSER	JOURNALNAME	DFHSHUNT	JCICSJCT	READ	EXCEPTION	NOTAUTH(NOLOG)	4
2022-10-02 09:18:19.749057	CICS611T	CEMT	65	CICSUSER	SPI Command	JOURNALNAME		READ	OK	XCMD=NO	
2022-10-02 09:18:19.749057	CICS611T	CEMT	65	CICSUSER	JOURNALNAME	DFHLOG	JCICSJCT	READ	EXCEPTION	NOTAUTH(NOLOG)	4
2022-10-02 09:18:19.749057	CICS611T	CEMT	65	CICSUSER	JOURNALNAME	DFHSHUNT	JCICSJCT	READ	EXCEPTION	NOTAUTH(NOLOG)	4
2022-10-02 09:18:19.749057	CICS611T	CEMT	65	CICSUSER	SPI Command	JOURNALNAME		READ	OK	XCMD=NO	
2022-10-02 09:18:19.749057	CICS611T	CEMT	65	CICSUSER	JOURNALNAME	DFHLOG	JCICSJCT	READ	EXCEPTION	NOTAUTH(NOLOG)	4
2022-10-02 09:24:22.642167	CICS611T	CEMT	68	CICSUSER	TRANSATTACH	CEMT		READ	OK	XTRAN=NO	
2022-10-02 09:24:22.642167	CICS611T	CEMT	68	CICSUSER	PROGRAM	DFHEITMT		READ	OK	XPPT=NO	
2022-10-02 09:24:22.642167	CICS611T	CEMT	68	CICSUSER	PROGRAM	DFHEMTD		READ	OK	XPPT=NO	

Change @@@@ @@@@ to the found RACF class name and issue them in =6 menu.

SETROPTS RACLIST(@@@@@@) REFRESH

## Check the CEMT again

10/10/2022



```
I JO(*)
STATUS:  RESULTS - OVERTYPE TO MODIFY
Jou (DFHLOG  ) Mvs Ena      Str (STCSYS.CICS61T1.DFHLOG  )
Jou (DFHSECR ) Mvs Ena      Str (DFHSECR.STREAM.CICS    )
Jou (DFHSHUNT) Mvs Ena      Str (STCSYS.CICS61T1.DFHSHUNT )

                                     SYSID=61T1 APPLID=CICS61T1
RESPONSE: NORMAL                      TIME: 00.04.23  DATE: 10/06/22
PF 1 HELP      3 END      5 VAR      7 SBH 8 SFH 9 MSG 10 SB 11 SF
```


Now you can see the journal resources in the CEMT command!

## **Part 7: Turn on the SRR for the ODCS transaction in all CICS regions**


Now it's time to resolve the ODCS transaction errors. You will define the SRR for ODCS transactions in all CICS regions because the ODCS transaction are routed to one of CICS region and connected to one FOR region.

### **Turn on the SRR in the CICS Explorer for a CEMT transaction**


- \_\_\_1. Open the CICS Explorer and select the **CICS SM** perspective.




- \_\_\_2. Click “Regions” after selecting the CPSM61PX context and the Operations Menu.




- \_\_\_3. Open a SRR session with right clicking after selecting all CICS regions.



- \_\_\_4. Put **ODCS** in the Name field, **5** in Maximum field and **CICSUSER** in the “User ID” field. Then click OK.



\_\_\_5. Select the **Security Request Recording** menu in the **Operations** menu.



Region	Name	Application	IC Client	IP Addr	Facility Type	Facility Name	LU Name	Network ID	Net ID	TCP/IP Serv	Transaction ID	User ID	Maximum	Current Ad
CICS61A1	ODCS				NOTAPPLIC							CICSUSER	5	0
CICS61A2	ODCS				NOTAPPLIC							CICSUSER	5	0
CICS61F1	ODCS				NOTAPPLIC							CICSUSER	5	0
CICS61T1	ODCS				NOTAPPLIC							CICSUSER	5	0

Now you can see the four new records being activated for the user ID, **CICSUSER**.

\_\_\_6. Test the inquiry process of customer number again with OMEN transaction. OMEN → Select menu 1 → Put 1 in the customer number field.

```

BNK1DC          CICS Bank Sample Application - Display Customer.

Provide a CUSTOMER number. Then press Enter.

CUSTOMER NUMBER 1

Sort Code
Customer Number
Customer Name
Customer Address

Customer D.O.B.      /      /
Credit Score
CS Review Date      /      /

DFHAC2206 21:06:11 CICS61T1 Transaction ODCS failed with abend AZI6. Updates
to local recoverable resources backed out. DFHAC2261 System 61A2 sent message
(sense code 0824089E). 'DFHAC2206 21:06:11 CICS61A2 Transaction ODCS failed
with abend HBNK. Updates to local recoverable resources backed out.'

```

## **Part 8: Check the SRR result and issue RACF commands to resolve ODCS errors**

In this part of the exercise, you will check the SRR report and get information to compose RACF commands to resolve the security error of ODCS transaction.

### **Run the batch job to generate a CSV file and view it in the VS Code**

**\_\_\_7. From the TSO, run the batch JCL to extract the SRR logs and write to a CSV file.**

#### **CICS.CICS61.JCL(DFHSSRPC)**


```
//DFHSSRP0 JOB CLASS=A,MSGCLASS=X,NOTIFY=&SYSUID,REGION=0M
// SET CSV='/cics/cics61/srrODCS.csv'
// SET LOGSTRM=DFHSECR.STREAM.NAME
// SET HLQ= IBMUSER.GM02.CTS61BT.CICS
//*****
/* Ensure that CSV file is deleted without nonzero RC                                *
//*****
//CREATE      EXEC PGM=IEFBR14
//CSV         DD PATHOPTS=(ORDWR,OCREAT),
//             PATHMODE=(SIRUSR,SIWUSR),
//             PATHDISP=(KEEP,KEEP),PATH='&CSV'
//DELETE      EXEC PGM=IEFBR14,COND=EVEN
//CSV         DD PATHDISP=(DELETE,DELETE),PATH='&CSV'
//*****
/* Convert logstream to CSV file                                                    *
//*****
//SRR         EXEC PGM=DFHSSRR,REGION=4M
//STEPLIB     DD DISP=SHR,DSN=&HLQ..SDFHLINK
//DFHSECR     DD DSNAME=&LOGSTRM.,DCB=BLKSIZE=32760,
//             SUBSYS=(LOGR,DFHLGCNV)
//DFHCSV      DD PATHOPTS=(OWRONLY,OCREAT),
//             PATHMODE=(SIRUSR,SIWUSR),
//             PATHDISP=(KEEP,DELETE),FILEDATA=TEXT,
//             RECFM=VB,LRECL=1024,BLKSIZE=32760,
//             PATH='&CSV'
//SUMMARY     DD SYSOUT=*
//RECORD      DD SYSOUT=*
//SYSPRINT    DD SYSOUT=*
//SYSOUT      DD SYSOUT=*
//SYSUDUMP    DD SYSOUT=*
//SORTWK01    DD UNIT=SYSDA,SPACE=(CYL,(4))
//SORTWK02    DD UNIT=SYSDA,SPACE=(CYL,(4))
//SORTWK03    DD UNIT=SYSDA,SPACE=(CYL,(4))
//SORTWK04    DD UNIT=SYSDA,SPACE=(CYL,(4))
//SYSIN       DD *
MATCHID=ODCS
/*
//*****
```

```

/** Tag CSV file as EBCDIC data                                     *
/*****
//TAG          EXEC PGM=BPXBATCH,PARM='sh chtag -t -c IBM-1047 &CSV'
//STDOUT      DD SYSOUT=*
//STDERR      DD SYSOUT=*


```

8. From the **z/OS Explorer**, the **Remote System Explorer** perspective, the **Remote Systems** view, **right-click** on **/cics/cics61/srrODCS.csv**, and select the external program, (VS) Code.



Right click --> Open with --> Other --> (VS) Code

9. From the **VS Code**, a **CSV extension editor** is shown. Then, click “**Edit CSV**” icon in the top right corner to see the data in a table view.



Click "Edit CSV" icon

column 5	column 6	column 7	column 8	column 9	column 10	column 11	column 12	column 13	column 14	column 15	column 16	col
odstarttime	applid	transid	taskid	userid	resource_type	profile	class	access	response	reason	saf_resp	saf_f
2022-10-02 08:24:08.743377	CICS61T1	ODCS	82	CICSUSER	TRANSATTACH	ODCS		READ	OK	XTRAN=NO		
2022-10-02 08:24:08.743377	CICS61T1	ODCS	82	CICSUSER	SPI Command	TERMINAL		READ	OK	CMDSEC(NO)		
2022-10-02 08:24:08.743377	CICS61A1	ODCS	143	CICSUSER	TRANSATTACH	ODCS		READ	OK	XTRAN=NO		
2022-10-02 08:24:08.743377	CICS61A1	ODCS	143	CICSUSER	SPI Command	TERMINAL		READ	OK	CMDSEC(NO)		
2022-10-02 08:24:08.743377	CICS61A1	ODCS	143	CICSUSER	SPI Command	TERMINAL		UPDATE	OK	CMDSEC(NO)		
2022-10-02 08:24:10.704877	CICS61T1	ODCS	83	CICSUSER	TRANSATTACH	ODCS		READ	OK	XTRAN=NO		
2022-10-02 08:24:10.704877	CICS61T1	ODCS	83	CICSUSER	SPI Command	TERMINAL		READ	OK	CMDSEC(NO)		
2022-10-02 08:24:10.704877	CICS61F1	CSMI	67	CICSUSER	TRANSATTACH	CSMI		READ	OK	XTRAN=NO		
2022-10-02 08:24:10.704877	CICS61F1	CSMI	67	CICSUSER	FILE	CUSTOMER	FCICSFCT	READ	EXCEPTION	NOTAUTH	4	0
2022-10-02 08:24:10.704877	CICS61A1	ODCS	144	CICSUSER	TRANSATTACH	ODCS		READ	OK	XTRAN=NO		
2022-10-02 08:24:10.704877	CICS61A1	ODCS	144	CICSUSER	SPI Command	TERMINAL		READ	OK	CMDSEC(NO)		
2022-10-02 08:24:10.704877	CICS61A1	ODCS	144	CICSUSER	PROGRAM	INQCUST		READ	OK	RESSEC(NO)		
2022-10-02 08:24:10.704877	CICS61A1	ODCS	144	CICSUSER	FILE	CUSTOMER	FCICSFCT	READ	OK	RESSEC(NO)		
2022-10-02 08:24:10.704877	CICS61A1	ODCS	144	CICSUSER	SPI Command	TERMINAL		UPDATE	OK	CMDSEC(NO)		
2022-10-02 08:24:18.427873	CICS61T1	ODCS	86	CICSUSER	TRANSATTACH	ODCS		READ	OK	XTRAN=NO		
2022-10-02 08:24:18.427873	CICS61T1	ODCS	86	CICSUSER	SPI Command	TERMINAL		READ	OK	CMDSEC(NO)		
2022-10-02 08:24:18.427873	CICS61A1	ODCS	147	CICSUSER	TRANSATTACH	ODCS		READ	OK	XTRAN=NO		
2022-10-02 08:24:18.427873	CICS61A1	ODCS	147	CICSUSER	SPI Command	TERMINAL		READ	OK	CMDSEC(NO)		
2022-10-02 08:24:18.427873	CICS61A1	ODCS	147	CICSUSER	SPI Command	TERMINAL		UPDATE	OK	CMDSEC(NO)		
2022-10-02 08:24:19.267089	CICS61T1	ODCS	87	CICSUSER	TRANSATTACH	ODCS		READ	OK	XTRAN=NO		
2022-10-02 08:24:19.267089	CICS61T1	ODCS	87	CICSUSER	SPI Command	TERMINAL		READ	OK	CMDSEC(NO)		
2022-10-02 08:24:19.267089	CICS61F1	CSMI	68	CICSUSER	TRANSATTACH	CSMI		READ	OK	XTRAN=NO		
2022-10-02 08:24:19.267089	CICS61F1	CSMI	68	CICSUSER	FILE	CUSTOMER	FCICSFCT	READ	EXCEPTION	NOTAUTH	4	0

\_\_\_10. Check exception records with the **profile** and **class** information and use them for manipulating RACF commands to resolve the transaction abend.

Change @@@@ and ##### to the RACF resource names and issue them in =6 menu.

```

RDEFINE @@@@ (CBSAFILE) UACC(NONE)
ADDMEM(ABNDFILE, ACCOUNT, ACCTCUST, CUSTOMER, PROCTRAN, REJTRAN)
NOTIFY(IBMUSER)

```

```

PERMIT CBSAFILE CLASS(@@@@) ID(CICSUSER) ACCESS(UPDATE)
SETROPTS RACLIST(#####) REFRESH

```

Check the link to find out file class names for group definition and refresh:

<https://www.ibm.com/docs/en/cics-ts/6.1?topic=reference-summary-racf-classes-cics-resources>

Quiz 3 : What values are for @@@@ and #####?

## Test the customer inquiry process

- \_\_\_11. Test the inquiry process of customer number again with OMEN transaction. OMEN → Select menu 1 → Put 1 in the customer number field.

```
BNK1DC          CICS Bank Sample Application - Display Customer.

Provide a CUSTOMER number. Then press Enter.

CUSTOMER NUMBER 0000000001

Sort Code      987654
Customer Number 0000000001
Customer Name   Dr Zsa G Higin
Customer Address 74 Joshua Mews, Portsmouth
                test

Customer D.O.B. 22 / 02 / 1941
Credit Score    516
CS Review Date  01 / 10 / 2022

Customer lookup successful. <PF5> to Delete. <PF10> to Update.
F3=Exit  F12=Cancel
```

Now you can see the information of customer number, 1!



## **Part 9: Summary**

**Congratulations**, you have resolved security errors by using the Security Request Recording function in CICS V6.1.

In this lab you performed the following steps:

- Configure the Security Request Recording function in CICS V6.1.
- Activate the recording for a transaction or for a user.
- Generate the CSV report and view it in the CSV extension of VS Code.
- Find out RACF resources to manipulate commands.
- Resolve the security issues!

### **Answers of Quizzes**

---

Quiz 1 : What values should replace ##### and @@@@ in the above JCL?

(#####.STREAM.@@@@) → (DFHSECR.STREAM.MODEL)

Quiz 2 : What value is for @@@@@@@@@?

@@@@@@@@ → JCICSJCT

Quiz 3 : What values are for @@@@@@@@@ and #####?

@@@@@@@@ → HCICSFCT, ##### → FCICSFCT