

Repository Mirror Scripts for IBM Resilient App Host

Table of Contents

- [About this Package](#)
 - [mirror-all-images.sh](#)
 - [mirror-images.sh](#)
-

History

7/20 - Initial Documentation

About this Package:

This branch contains scripts which can be used to mirror App Host container images for local repository use. This is necessary when customers need to maintain their own apps for use in App Host along with those officially published on the App Exchange or to replicate containers for air-gapped environments.

Two scripts are provided:

- [mirror-all-images.sh](#)
- [mirror-images.sh](#)

Initialization

- Ensure that the local container tool, docker or podman, is accessible. If root permissions are needed to run these commands, use **sudo** or **su** to access that login account in advance.
- Login to each repository using the **docker login** or **podman login** commands.

[mirror-all-images.sh](#)

This script is used to copy all container images from the IBM official repository, [quay.io](#), to a customer's private repository. It uses local container tools such as **docker** or **podman** to pull containers down from [quay.io](#) and then push them to the private repository.

Usage

```
/bin/bash mirror-all-images fqdn.registry.io [docker | podman]
```

- [fqdn.registry.io](#) - name or ip address of the replication repository
- [docker | podman] - optional reference to the tool to perform the container transfer. If missing, the script will attempt to determine which tool exists.

Example

```
/bin/bash mirror-all-images 834299573936.dkr.ecr.us-east-2.amazonaws.com podman
```

mirror-images.sh

This script is used to copy a select number of container images from the IBM official repository, quay.io, to a customer's private repository. It uses local container tools such as **docker** or **podman** to pull containers down from quay.io and then push them to the private repository. Two additional files are used to control the behavior of the script:

- `repo_quay.conf` - a list of container names and versions, one per line, to replicate. The format of a line is: `container_name:x.x.x` where `x.x.x` is the tagged version.
- `preserved_images.conf` - a list of container names and versions, one per line, to retain in the local docker or podman image container environment. Format of a line is the same as used in the `repo_quay.conf` file: `container_name:x.x.x`.

Usage

```
/bin/bash mirror-all-images fqudn.registry.io [docker | podman]
```

- fqudn.registry.io - name or ip address of the replication repository
- `[docker | podman]` - optional reference to the tool to perform the container transfer. If missing, the script will attempt to determine which tool exists.

Example

```
/bin/bash mirror-images 192.168.12.186:5000
```

`repo_quay.conf`

```
fn_utilities:1.14.0
fn_xforce:1.0.0
```

`preserved_images.conf`

```
fn_utilities:1.14.0
```