

McAfee Threat Intelligence Exchange (TIE) Functions for IBM Resilient

Table of Contents

- [Release Notes](#)
 - [Overview](#)
 - [Key Features](#)
 - [Installation](#)
 - [Requirements](#)
 - [Install](#)
 - [App Configuration](#)
 - [Custom Layouts](#)
 - [Function - McAfee TIE search hash](#)
 - [Data Table - TIE Results](#)
 - [Rules](#)
 - [Troubleshooting & Support](#)
-

Release Notes

v1.0.2

- Support added for App Host.

v1.0.1

- Support added for App Host.

v1.0.0

- Initial Release
-

Overview

Resilient Circuits Components for McAfee TIE Functions

The McAfee TIE Functions for IBM Resilient provides the ability to search McAfee Threat Intelligence Exchange (TIE) server for information on a specific file hash. This information can come from any of the providers:

- Enterprise
- GTI
- ATD
- MWG

In addition, a system list is returned by the function.

Installation

Requirements

- Resilient platform **>= v35.0.0**
 - To setup up an App Host see: ibm.biz/res-app-host-setup
- An Integration Server running **resilient_circuits>=30.0.0** (if using an Integration Server)

- To set up an Integration Server see: ibm.biz/res-int-server-guide
- If using an API key account, minimum required permissions are:

Name	Permissions
Org Data	Read
Function	Read

Install

- To install or uninstall an App using the App Host see ibm.biz/res-install-app
- To install or uninstall an Integration using the Integration Server see the ibm.biz/res-install-int

App Configuration

The following table describes the settings you need to configure in the app.config file. If using App Host, see the Resilient System Administrator Guide. If using the integration server, see the Integration Server Guide.

Config	Required	Example	Description
dxlclient_config	Yes	<code>/home/integration/.resilient/mcafee_tie/dxlclient.config</code>	Path to the dxlclient.config file

More information on the dxlclient.config file and provisioning the system can be found here:

<https://opendxl.github.io/opendxl-client-python/pydoc/provisioningoverview.html>

<https://opendxl.github.io/opendxl-client-python/pydoc/basiccliprovisioning.html#basiccliprovisioning>

An example of the CLI provisioning command:

```
python -m dxlclient -vv provisionconfig /home/integration/.resilient/fn_mcafee_tie X.X.X.X
client1 -u admin -p password
```

where X.X.X.X is the IP address of the McAfee ePO server or OpenDXL Broker.

Custom Layouts

- Customize the Artifacts Tab page by dragging the TIE Results data table on to it as pictured below or create your own McAfee TIE incident tab and drag the TIE Results on to it:

File Provider	Trust Level	Create Date	
Enterprise	Known Malicious	2018-02-21 12:19:23	

Displaying 1 - 1 of 1

Function - McAfee TIE search hash

A function which takes two inputs:

mcafee_tie_hash_type: The type of file hash (md5, sha1, sha256). mcafee_tie_hash: The value of the hash.

The function returns a JSON object containing the available information from the different file providers (Enterprise, GTI, ATD, MWG) along with the list of systems related to it.

resilient

DashboardsInboxIncidentsCreate

Resilient Sysadminresilient

Customization Settings

LayoutsRulesScriptsWorkflowsFunctionsMessage DestinationsPhases & TasksIncident TypesBreachArtifacts

Functions / mcafee_tie_search_hash

Name *McAfee TIE search hash

API Name * ⓘmcafee_tie_search_hash

Message Destination *McAfee TIE MD

DescriptionA function which takes two inputs:

mcafee_tie_hash_type: The type of file hash (md5, sha1, sha256).
mcafee_tie_hash: The value of the hash.

The function returns back a dict of all the available information from the different file providers (Enterprise, GTI, ATD, MWG) along with the list of systems related to it.

CreatorResilient Sysadmin

Last Modified09/25/2020 15:34

Last Modified ByResilient Sysadmin

Associated Workflows(Example) McAfee TIE hash search workflow

Cancel

Save & Close

Save

Inputs

mcafee_tie_hash_type

mcafee_tie_hash

Input Fields ⓘ

Add Field

Search...

attachment_id

► Inputs:

Name	Type	Required	Example	Tooltip
mcafee_tie_hash	text	No	—	The value of the hash
mcafee_tie_hash_type	text	No	—	The type of file hash (md5, sha1, sha256)

► Outputs:

```
results = {
  "GTI":{
    "File Provider":"GTI",
    "Attributes":{

    },
    "Create Date":"2018-02-21 12:17:10",
    "Trust Level":"Known Malicious"
  },
  "ATD":{
    "File Provider":"ATD",
    "Create Date":"2018-03-14 11:53:09",
    "Trust Level":"Most Likely Malicious"
  },
  "MWG":{
    "File Provider":"MWG",
    "Create Date":"2018-03-14 11:53:55",
    "Trust Level":"Most Likely Malicious"
  },
  "Enterprise":{
    "File Provider":"Enterprise",
    "Attributes":{
      "Average Local Rep":"Most Likely Malicious",
      "First Contact":"2018-02-21 12:17:10",
      "Min Local Rep":"Most Likely Malicious",
      "Is Prevalent":"0",
      "File Name Count":"1",
      "Max Local Rep":"Most Likely Malicious"
    }
  }
}
```

```

    },
    "Create Date": "2018-02-21 12:17:10",
    "Trust Level": "Most Likely Malicious"
  }
  "system_list": [{
    "date": 1519233563,
    "agentGuid": {a00728ff-3187-46c1-97d2-8e0f26ea940b}
  }]
}

```

► Workflows:

Resilient Dashboards ▾ Inbox Incidents **Create ▾** 🔍 🌐 **Resilient Sysadmin**
resilient

Customization Settings

Layouts Rules Scripts **Workflows** Functions Message Destinations Phases & Tasks Incident Types Breach Artifacts

[Workflows](#) / (Example) McAfee TIE hash search workflow 🗑️

Name * (Example) McAfee TIE hash search workflow

API Name * mcafee_tie_hash_search_workflow

Description Workflow to trigger function to search hash in TIE. Results are written as a row in the TIE Results data table.

Object Type * Artifact

Creator Resilient Sysadmin

Last Modified 09/28/2020 15:57

Last Modified By Resilient Sysadmin

Associated Rules (Example) McAfee artifact hash search

Cancel Save & Close Save

► Example Pre-Process Script:

```

if artifact.type == "Malware MD5 Hash":
    inputs.mcafee_tie_hash_type = "md5"
    inputs.mcafee_tie_hash = artifact.value
elif artifact.type == "Malware SHA-1 Hash":
    inputs.mcafee_tie_hash_type = "sha1"
    inputs.mcafee_tie_hash = artifact.value
elif artifact.type == "Malware SHA-256 Hash":
    inputs.mcafee_tie_hash_type = "sha256"
    inputs.mcafee_tie_hash = artifact.value
else:
    helper.fail("Artifact hash was not set correctly")

```

► Example Post-Process Script:

```

#####
Data returned will be in the following structure

```

```

{
  "GTI":{
    "File Provider":"GTI",
    "Attributes":{

    },
    "Create Date":"2018-02-21 12:17:10",
    "Trust Level":"Known Malicious"
  },
  "ATD":{
    "File Provider":"ATD",
    "Create Date":"2018-03-14 11:53:09",
    "Trust Level":"Most Likely Malicious"
  },
  "MWG":{
    "File Provider":"MWG",
    "Create Date":"2018-03-14 11:53:55",
    "Trust Level":"Most Likely Malicious"
  },
  "Enterprise":{
    "File Provider":"Enterprise",
    "Attributes":{
      "Average Local Rep":"Most Likely Malicious",
      "First Contact":"2018-02-21 12:17:10",
      "Min Local Rep":"Most Likely Malicious",
      "Is Prevalent":"0",
      "File Name Count":"1",
      "Max Local Rep":"Most Likely Malicious"
    },
    "Create Date":"2018-02-21 12:17:10",
    "Trust Level":"Most Likely Malicious"
  }
  "system_list":[{
    "date": 1519233563,
    "agentGuid": {a00728ff-3187-46c1-97d2-8e0f26ea940b}
  }]
}
"""

row = incident.addRow("tie_results")
row["hash_type"] = artifact.type
row["hash"] = artifact.value
row["file_provider"] = results["Enterprise"]["File Provider"]
row["trust_level"] = results["Enterprise"]["Trust Level"]
row["tie_create_date"] = results["Enterprise"]["Create Date"]

```

Data Table - TIE Results

Resilient

Dashboards

Inbox

Incidents

Create

Q

🌐

Resilient Sysadmin
resilient

McAfee TIE testing

Actions

Description

No description.

Tasks

Details

Breach

Notes

Members

News Feed

Attachments

Stats

Timeline

Artifacts

Email

Secureworks CTP

Exchange Online

Twilio

Data Table Utils

McAfee TIE

Save

Cancel

TIE Results

Search...

Row

+

Hash Type	Hash	File Provider	Trust Level	Create Date	
Malware SHA-256 Hash	A8B03AD33BC6D7A7F376B943F763EEDD1CDAF125D012F9018F2F56678AE67EA4	Enterprise	Not Set	2020-09-28 16:44:14	
Malware SHA-1 Hash	C61AC5FE73D50BD41D0CAD1A43C471925E7DDCD4	Enterprise	Not Set	2020-09-28 16:44:11	
Malware MD5 Hash	30CB8BA19E19B42701CDB3627D6F4023	Enterprise	Not Set	2020-09-28 15:39:56	

Displaying 1 - 3 of 3

Summary

ID2147

PhaseEngage

SeverityLow

Date Created09/28/2020

Date Occurred—

Date Discovered09/28/2020

Date Determined09/28/2020

Data CompromisedUnknown

Incident TypeMalware

People

Created ByResilient Sysadmin

OwnerResilient Sysadmin

MembersThere are no members.

Related Incidents

No related incidents.

Attachments

There are no attachments.

API Name:

tie_results

Columns:

Column Name	API Access Name	Type	Tooltip
File Provider	file_provider	text	-
Hash	hash	text	-
Hash Type	hash_type	text	-
Create Date	tie_create_date	text	-
Trust Level	trust_level	text	-

Rules

Rule Name	Object	Workflow Triggered
(Example) McAfee artifact hash search	artifact	mcafee_tie_hash_search_workflow

► Rules:

resilient

Dashboards

Inbox

Incidents

Create

Q

Resilient Sysadmin
resilient

Customization Settings

Layouts

Rules

Scripts

Workflows

Functions

Message Destinations

Phases & Tasks

Incident Types

Breach

Artifacts

Rules / (Example) McAfee artifact hash search

Cancel

Save & Close

Save

Display Name *

(Example) McAfee artifact hash s

Object Type

Artifact

Conditions

Add conditions in which to invoke the rule. [Clear All](#)

Type

has one of

Malware MD5 Hash

Malware SHA-1 Hash

Malware SHA-256 Hash

Activities

Ordered

Ordered Activities will be invoked in the order specified below. They include: *Add Tasks, Run Script, and Set Field.* [Add New](#)

Workflows

Workflow Activities are started after all Ordered Activities complete.

(Example) McAfee TIE hash search workflow

Destinations

Transaction Data is posted to Message Destinations after all Ordered Activities complete and all Workflows have been started.

Select Destinations

[Show Activity Fields](#)

Troubleshooting & Support

If using the app with an App Host, see the Resilient System Administrator Guide and the App Host Deployment Guide for troubleshooting procedures. You can find these guides on the [IBM Knowledge Center](#), where you can select which version of the Resilient platform you are using.

If using the app with an integration server, see the [Integration Server Guide](#)

For Support

This is an IBM Supported app. Please search <https://ibm.com/mysupport> for assistance.