McAfee Threat Intelligence Exchange (TIE) Functions for IBM Resilient

Table of Contents

- Release Notes
- Overview
 - Key Features
- Installation
 - Requirements
 - Install
 - App Configuration
 - Custom Layouts
- Function McAfee TIE search hash
- Data Table TIE Results
- Rules
- Troubleshooting & Support

Release Notes

v1.0.2

• Support added for App Host.

v1.0.1

• Support added for App Host.

v1.0.0

• Initial Release

Overview

Resilient Circuits Components for McAfee TIE Functions

The McAfee TIE Functions for IBM Resilient provides the ability to search McAfee Threat Intelliegence Exchange (TIE) server for information on a specific file hash. This information can come from any of the providers:

- Enterprise
- GTI
- ATD
- MWG

In addition, a system list is returned by the function.

Installation

Requirements

- Resilient platform >= v35.0.0
 - To setup up an App Host see: ibm.biz/res-app-host-setup
- An Integration Server running resilient_circuits>=30.0.0 (if using an Integration Server)

- To set up an Integration Server see: ibm.biz/res-int-server-guide
- If using an API key account, minimum required permissions are:

Nam	е	Permissions		
Org [Data	Read		
Func	tion	Read		

Install

- To install or uninstall an App using the App Host see ibm.biz/res-install-app
- To install or uninstall an Integration using the Integration Server see the ibm.biz/res-install-int

App Configuration

The following table describes the settings you need to configure in the app.config file. If using App Host, see the Resilient System Administrator Guide. If using the integration server, see the Integration Server Guide.

Config	Required	Example	Description
dxlclient_config	Yes	/home/integration/.resilient/mcafee_tie/dxlclient.config	Path to the dxlclient.config

Before running the McAfee TIE functions, the dxlclient.config, certificates and key files must be created using a OpenDXL client provisioning command. More information on the dxlclient.config file and provisioning the system can be found here:

https://opendxl.github.io/opendxl-client-python/pydoc/provisioningoverview.html https://opendxl.github.io/opendxl-client-python/pydoc/basiccliprovisioning.html#basiccliprovisioning

Here is an example of the OpenDXL client provisioning command:

```
python -m dxlclient -vv provisionconfig /home/integration/.resilient/fn_mcafee_tie X.X.X.X
client1 -u admin -p password
```

In this example, X.X.X.X is the IP address of the McAfee ePO server or OpenDXL Broker.

The directory /home/integration/.resilient/fn_mcafee_tie is the location where the generated files will be created.

On an integration server set the dxlclient_config app.config parameter to the location of the created dxlclient.config file.


```
[fn_mcafee_tie]
dxlclient_config=/home/integration/.resilient/fn_mcafee_tie
```

In an App Host environment, cut and paste the contents of all the files generated by the provisioning command into the App Settings Configuration tab in the Resilient UI.


To add the files:

- Click New File for each dxlclient file.
- Enter the File Name
- Enter /etc/rescircuits/fn_mcafee_tie in the File Path
- Cut/paste the file contents into the File Content window.
- When done click the Save and Push Changes button to store the file.

Here is a screenshot of adding a new dxlclient.config file in App Host:




Here is a screenshot of these files in an App Host environment after the files have been added:



Custom Layouts

• Customize the Artifacts Tab page by dragging the TIE Results data table on to it as pictured below or create your own McAfee TIE incident tab and drag the TIE Results on to it:




Function - McAfee TIE search hash

A function which takes two inputs:

mcafee_tie_hash_type: The type of file hash (md5, sha1, sha256). mcafee_tie_hash: The value of the hash.

The function returns a JSON object containing the available information from the different file providers (Enterprise, GTI, ATD, MWG) along with the list of systems related to it.



▶ Inputs:

Name	Type	Required	Example	Tooltip
mcafee_tie_hash	text	No	_	The value of the hash
<pre>mcafee_tie_hash_type</pre>	text	No	_	The type of file hash (md5, sha1, sha256)


► Outputs:

```
results = {
  "GTI":{
     "File Provider":"GTI",
     "Attributes":{

     },
     "Create Date":"2018-02-21 12:17:10",
     "Trust Level":"Known Malicious"
},
  "ATD":{
     "File Provider":"ATD",
     "Create Date":"2018-03-14 11:53:09",
```

```
"Trust Level": "Most Likely Malicious"
},
"MWG":{
   "File Provider": "MWG",
   "Create Date":"2018-03-14 11:53:55",
   "Trust Level": "Most Likely Malicious"
},
"Enterprise":{
    "File Provider": "Enterprise",
   "Attributes":{
       "Average Local Rep": "Most Likely Malicious",
       "First Contact":"2018-02-21 12:17:10",
       "Min Local Rep": "Most Likely Malicious",
       "Is Prevalent":"0",
       "File Name Count":"1",
       "Max Local Rep": "Most Likely Malicious"
    },
   "Create Date":"2018-02-21 12:17:10",
   "Trust Level": "Most Likely Malicious"
"system_list":[{
  "date": 1519233563,
  "agentGuid": {a00728ff-3187-46c1-97d2-8e0f26ea940b}
}]
}
```

▶ Workflows:



► Example Pre-Process Script:

```
if artifact.type == "Malware MD5 Hash":
inputs.mcafee_tie_hash_type = "md5"
inputs.mcafee_tie_hash = artifact.value
```


```
elif artifact.type == "Malware SHA-1 Hash":
inputs.mcafee_tie_hash_type = "sha1"
inputs.mcafee_tie_hash = artifact.value
elif artifact.type == "Malware SHA-256 Hash":
inputs.mcafee_tie_hash_type = "sha256"
inputs.mcafee_tie_hash = artifact.value
else:
helper.fail("Artifact hash was not set correctly")
```

► Example Post-Process Script:

```
Data returned will be in the following structure
 "GTI":{
   "File Provider": "GTI",
    "Attributes":{
    "Create Date":"2018-02-21 12:17:10",
   "Trust Level": "Known Malicious"
},
 "ATD":{
   "File Provider": "ATD",
    "Create Date":"2018-03-14 11:53:09",
    "Trust Level": "Most Likely Malicious"
 },
 "MWG":{
   "File Provider": "MWG",
   "Create Date":"2018-03-14 11:53:55",
   "Trust Level": "Most Likely Malicious"
 },
 "Enterprise":{
    "File Provider": "Enterprise",
    "Attributes":{
       "Average Local Rep": "Most Likely Malicious",
       "First Contact": "2018-02-21 12:17:10",
       "Min Local Rep": "Most Likely Malicious",
       "Is Prevalent":"0",
       "File Name Count":"1",
       "Max Local Rep": "Most Likely Malicious"
    },
    "Create Date":"2018-02-21 12:17:10",
    "Trust Level": "Most Likely Malicious"
 "system_list":[{
   "date": 1519233563,
  "agentGuid": {a00728ff-3187-46c1-97d2-8e0f26ea940b}
}]
}
111111
row = incident.addRow("tie_results")
row["hash_type"] = artifact.type
row["hash"] = artifact.value
row["file provider"] = results["Enterprise"]["File Provider"]
row["trust_level"] = results["Enterprise"]["Trust Level"]
```

```
row["tie_create_date"] = results["Enterprise"]["Create Date"]
```

Data Table - TIE Results



API Name:

tie_results


Columns:

Column Name	API Access Name	Туре	Tooltip
File Provider	file_provider	text	-
Hash	hash	text	-
Hash Type	hash_type	text	-
Create Date	tie_create_date	text	-
Trust Level	trust_level	text	-

Rules

Rule Name	Object	Workflow Triggered
(Example) McAfee artifact hash search	artifact	<pre>mcafee_tie_hash_search_workflow</pre>

▶ Rules:



Troubleshooting & Support

If using the app with an App Host, see the Resilient System Administrator Guide and the App Host Deployment Guide for troubleshooting procedures. You can find these guides on the IBM Knowledge Center, where you can select which version of the Resilient platform you are using.

If using the app with an integration server, see the Integration Server Guide

For Support

This is an IBM Supported app. Please search https://ibm.com/mysupport for assistance.