



# Linear Classification

Réda DEHAK  
<http://ismil.dehak.org>

1

---

---


---

---

---

---

---



## Contents

- Classification
- Linear Classification
- Logistic Regression
- Performance metrics

Réda DEHAK 2

2

---

---


---

---

---

---

---



## Classification

- learning a **function** (model) that **maps** an **input** (features) vectors to a **discret output** (target or labels) based on **examples input-output pairs**.
- Examples:
  - Binary classification:  $y \in \{0, 1\}$ 
    - Email : Spam / Not Spam?
    - Online Transactions: Fraudulent (Yes/No)
    - Check Identity: Target / impostors
  - Multiclass classification:

Réda DEHAK 3

3

---

---

---

---

---

---

---

**Classification**

- Logistic Regression
- Support Vector Machines (SVM)
- Neural Networks
- K-Nearest Neighbors (KNN)
- Naïve Bayes
- Decision Trees
- ....

ESL EPITA

Réda DEHAQ 4

4

---

---

---


---

---

---

---

---



5

---

---

---


---

---

---

---

---



6

---

---

---

---

---

---


---

---

**Logistic Regression**

- Want  $0 \leq f_w(x) \leq 1$  :
  - Linear Regression:  $f_w(x) = W^T x$
  - Logistic Function:  $h(z) = \frac{1}{1 + e^{-z}}$

$$z = h^{-1}(x) = \text{logit}(x) = \log\left(\frac{x}{1-x}\right)$$

$$\frac{dh(z)}{dz} = h(z)(1 - h(z))$$


Réda DEHAQ 7

7

---

---

---

---

---

---

---

---

**Logistic Regression**

- Want  $0 \leq f_w(x) \leq 1$  :
  - Logistic Regression:  $P(y=1) = f_w(x) = \frac{1}{1 + e^{-w^T x}}$
  - $\frac{df_w(x)}{dw} = x f_w(x)(1 - f_w(x))$
  - $P(y=0) = 1 - P(y=1)$
- Decision Function:
  - $P(y=1) \geq P(y=0)$  : Positive Class
  - Otherwise: Negative Class

Réda DEHAQ 8

8

---

---

---

---

---

---

---

---

**Logistic Regression**

- $P(y=1) \geq P(y=0) \Leftrightarrow \frac{P(y=1)}{P(y=0)} \geq 1$ 

$$\Leftrightarrow \log\left(\frac{P(y=1)}{P(y=0)}\right) \geq 0$$

$$\Leftrightarrow \log\left(\frac{P(y=1)}{1-P(y=1)}\right) = \text{logit}(P(y=1)) \geq 0$$

$$\Leftrightarrow \text{logit}(P(y=1)) = W^T x$$

Réda DEHAQ 9

9

---

---

---

---

---

---


---

---

**HyperPlane**

- Definition:  
 $W^T x + b = 0$
- Divide the space into two parts:
  - 1)  $W^T x + b > 0$  : direction of the vector  $w$  (red in the figure)
  - 2)  $W^T x + b < 0$  : opposite of the direction of  $w$  (blue in the figure)
- Distance to the hyperplane:  

$$\frac{|W^T x + b|}{\|W\|}$$



ESL EPITA Rida DEHAK 10

10

---

---

---

---

---

---

---

---

**Logistic Regression**

- $P(y = 1) \geq P(y = 0) \Leftrightarrow \frac{P(y=1)}{P(y=0)} \geq 1$   
 $\Leftrightarrow \log \left( \frac{P(y=1)}{P(y=0)} \right) \geq 0$   
 $\Leftrightarrow \log \left( \frac{P(y=1)}{1-P(y=1)} \right) = \text{logit}(P(y = 1)) \geq 0$   
 $\Leftrightarrow \text{logit}(P(y = 1)) = W^T x \geq 0$

**Boundary = Hyperplane**

ESL EPITA Rida DEHAK 11

11

---

---

---

---

---

---

---

---

**Linear Classification**

- Classification : Decision Function is a hyperplane in input space.
- Classification methods:
  - Logistic Regression
  - Perceptron
  - SVM
  - Naïve Bayes

ESL EPITA Rida DEHAK 12

12

---

---

---

---

---

---

---

---

**Training: Two Classes**

$$\mathcal{X} = \{(x_i, y_i), i = 1 \dots N\} \quad y_i \in \{0, 1\}$$

$y_i \sim \text{Bernoulli}$

- Score Function : Maximum LLK (Log Likelihood)
- $LLK(\mathcal{X}) = \prod_{i=1}^N P(y_i | x_i)$
- $= \prod_{i=1}^N (f_W(x_i))^{y_i} (1 - f_W(x_i))^{1-y_i}$
- $LLK(\mathcal{X}) = \sum_{i=1}^N y_i \log(f_W(x_i)) + (1 - y_i) \log(1 - f_W(x_i))$

Réda DEHAQ 13

13

---

---

---

---

---

---

---

---

**Training: Two Classes**

- $LLK(\mathcal{X}) = \sum_{i=1}^N y_i \log(f_W(x_i)) + (1 - y_i) \log(1 - f_W(x_i))$
- $\frac{dLLK(\mathcal{X})}{dW} = \sum_{i=1}^N x_i y_i \frac{f_W(x_i)(1-f_W(x_i))}{f_W(x_i)} - x_i(1 - y_i) \frac{f_W(x_i)(1-f_W(x_i))}{1-f_W(x_i)}$

$$\frac{dLLK(\mathcal{X})}{dW} = \sum_{i=1}^N x_i (y_i - f_W(x_i))$$

Réda DEHAQ 14

14

---

---

---

---

---

---

---

---

**Gradient Descent for linear Regression**

$$E = \frac{1}{N} (Y^T Y - 2 A^T X Y + A^T X X^T A)$$

$$\nabla E = \frac{2}{N} (X X^T A - X Y)$$

$$\nabla E = \frac{2}{N} X (X^T A - Y)$$

Réda DEHAQ 15

15

---

---

---



---

---

---

---

---

## Multiclass

- Use softMax rather than logistic function:

$$P(y = i | x) = f_{W_{1..k}}(x; i) = \frac{e^{W_i^T \hat{x}}}{\sum_{l=1}^k e^{W_l^T \hat{x}}}$$

Réda DEHAQ 16

16

---

---

---



---

---

---

---

---

## No Linear Logistic Regression

- Using a non Linear Mapping  $\varphi$  before the regression.
- Examples: *Quadratic mapping*

$$\varphi \begin{pmatrix} x_1 \\ x_2 \end{pmatrix} = \begin{pmatrix} x_1^2 \\ x_2^2 \\ x_1 x_2 \\ x_1 \\ x_2 \\ 1 \end{pmatrix}$$

Réda DEHAQ 17

17

---

---

---

---

---

---

---

---




## Performance Metrics

Réda DEHAQ 18

18

---

---

---

---

---

---

---

---

**Performances: Matrix confusion**

- A binary classifier classifies data points as + or -
- If we also know the true classification, the performance of the classifier is a  $2 \times 2$  contingency table, called a Confusion Matrix.

		Actual Class	
		+	-
Predicted Class	+	True Positives (TP)	False Positives (FP)
	-	False Negatives (FN)	True Negatives (TN)

Réda DEHAQ 19

19

---

---

---

---

---

---

---

---

**Performances: Missclassification Errors**

- Two types of Errors:
  - False Positives (FP): Type-I errors
  - False Negatives (FN): Type-II errors

		Actual Class	
		+	-
Predicted Class	+	True Positives (TP) Good!	False Positives (FP) Bad! (Type-I errors)
	-	False Negatives (FN) Bad! (Type-II errors)	True Negatives (TN) Good!

Réda DEHAQ 20

20

---

---

---

---

---

---

---

---

**Example:**

**Logistic Regression**

		Actual Class	
		+	-
Predicted Class	+	72	29
	-	33	31

**SVM**

		Actual Class	
		+	-
Predicted Class	+	94	37
	-	11	23

**Which is the Best Classifier?**

Réda DEHAQ 21

21

---

---

---

---

---

---

---

---

**Threshold**

- $P(y = 1) \geq P(y = 0)$ :  

$$P(y = 1) = f_W(x) = \frac{1}{1 + e^{-W^T x}} \geq 0.5$$
- Threshold depends on prior and cost (risk) function

ESL EPITA Rida DEHAK 22

22

---

---

---

---

---

---

---

---

**Threshold**

Using costs values to adjust Threshold to minimize costs

		Actual Class		Score $\geq 0.6$		Score $\geq 0.7$			
		+	-	+	-	+	-		
Predicted Class	+	True Positives (TP) Cost = 0	False Positives (FP) Cost = 20	+	40	20	+	30	10
	-	False Negatives (FN) Cost = 0	True Negatives (TN) Cost = 0	-	10	30	-	20	40

ESL EPITA Rida DEHAK 23

23

---

---

---

---

---

---

---

---

**Adjust Threshold**

Most classifiers have a "knob" or threshold that you can adjust: How certain do they have to be before they classify a "+"? To get more TP's, you have to let in some FP's!

ESL EPITA Rida DEHAK 24

24

---

---

---

---

---

---

---

---



**Threshold?**

- Notice there is just one free parameter, think of it as TP, since:
  - $FP(TP) = \text{[given by algorithm]}$
  - $TP + FN = P$  (fixed number of actual positives, column marginal)
  - $FP + TN = N$  (fixed number of actual negatives, column marginal)

**So all scalar measures of performance are functions of one free parameter (i.e., curves)**

The points on any such curve are in 1-to-1 correspondence with those on any other such curve.

- If you ranked some classifiers by how good they are, you might get a different rankings at different points on the scale.
- On the other hand, one classifier might dominate another at all points on the scale.

Réda DEHAQ 25

25

---

---

---

---

---

---

---

---

**Performance Metrics**

- Accuracy
- True Positive Rate, Recall, Sensitivity
- False Alarm Rate, False Positive Rate
- Missed Detection Rate, False Negative Rate
- Specificity, True Negative Rate
- Negative Predictive Value
- Precision, Positive Prediction Value
- False Discovery Rate
- F-Score
- F-Measure

Réda DEHAQ 26

26

---

---

---

---

---

---

---

---

**Performance Metrics**

- Different combinations of ratios have been given various names. All vary between 0 and 1.
- A performance curve picks one as the independent variable and looks at another as the dependent variable.

Réda DEHAQ 27

27

---

---

---


---

---

---

---

---



### Performance Metrics: Accuracy

**Accuracy** is the most intuitive performance measure and it is simply a ratio of **correctly predicted** observation to the **total observations**

- $Accuracy = \frac{\text{Total of good Classification}}{\text{Number of Examples}}$
- $Accuracy = \frac{(TP+TN)}{(P+N)}$
- Accuracy can be a misleading metric for imbalanced data sets

Réda DENAK 28

28

---

---

---


---

---

---

---

---



### Performance Metrics: True Positive Rate, Recall, sensitivity

**Recall**, **True Positive Rate(TPR)**, or **Sensitivity** correspond to the proportion of positive data points that are correctly considered as positive, with respect to all positive data points.

*Of all the really sick people, how many have we detect?*

$$Recall = Sensitivity = True\ Positive\ Rate(TPR) = \frac{\text{True Positive}(TP)}{\text{Positive}(P)}$$

**Recall** is generally used in information retrieval applications, **recall** is the fraction of the relevant documents that are successfully retrieved

Réda DENAK 29

29

---

---

---


---

---

---

---

---



### Performance Metrics: False Alarm Rate, False Positive Rate

**False Alarm Rate(FAR)** or **False Positive Rate(FPR)** is defined as the probability of falsely rejecting the null hypothesis.

$$False\ Alarm\ Rate(FAR) = False\ Positive\ Rate(FPR) = \frac{\text{False Positive}(FP)}{\text{Negative}(N)}$$

Réda DENAK 30

30

---

---

---

---

---

---

---

---

**Performance Metrics: Missed Detection Rate, False Negative Rate**

*Missed Detection Rate (FAR) or False Negative Rate (FNR)* is the proportion of the individuals with a known **negative** condition for which the test result is **positive**.

$$\text{Missed Detection Rate (MISS)} = \text{False Negative Rate (FNR)} = \frac{\text{False Negative (FN)}}{\text{Positive (P)}}$$

Réda DEHAQ 31

31

---

---

---

---

---

---

---

---

**Performance Metrics: Specificity, True Negative Rate**

*Specificity or True Negative Rate (TNR)* measures the proportion of really negatives examples identified as such

$$\text{Specificity} = \text{True Negative Rate (TNR)} = \frac{\text{True Negative (TN)}}{\text{Negative (N)}} = 1 - \text{FAR}$$

Réda DEHAQ 32

32

---

---

---

---

---

---

---

---

**Performance Metrics: Precision and False Discovery Rate**

- Precision* is the number of correct positive results divided by the number of positive results predicted by the classifier.
- False Discovery Rate (FDR)* is the expected proportion of False Positive (Type I errors)

$$\text{Precision} = \frac{\text{True Positive (TP)}}{\text{TP} + \text{FP}} = 1 - \text{FDR}$$

$$\text{False Discovery Rate (FDR)} = \frac{\text{False Positive (FP)}}{\text{TP} + \text{FP}} = 1 - \text{Precision}$$

Réda DEHAQ 33

33

---

---

---

---

---

---

---

---

**Performance Metrics: Positive and Negative Predictive Value**

**Positive predictive value** is the probability that subjects with a positive screening test truly are positive.

**Negative predictive value** is the probability that subjects with a negative screening test truly are negative.

$$\text{Positive Predictive Value (PPV)} = \frac{TP}{(TP + FP)}$$

$$\text{Negative Predictive Value (NPV)} = \frac{TN}{(TN + FN)}$$

ESL EPITA

Réda DEHAQ 34

34

---

---

---

---

---

---

---

---

**Performance Metrics: F-Score, F-Measure**

- **F-Score:**  $F\text{-Score} = \text{Precision} \times \text{Recall}$
- **F-Measure:** Harmonic mean of Precision and Recall:
 
$$F_\beta = \frac{(1 + \beta^2) \times \text{Recall} \times \text{Precision}}{\beta^2 \times \text{Recall} + \text{Precision}}$$
- **F1-Measure:**

$$F_1 = \frac{2 \times \text{Recall} \times \text{Precision}}{\text{Recall} + \text{Precision}}$$

ESL EPITA

Réda DEHAQ 35

35

---

---

---

---

---

---

---

---

**Performance Curves**

- Receiver Operating Characteristic (ROC) Curves
- Precision-Recall Curves
- Detection Error-Tradeoff (DET) Curves

ESL EPITA

Réda DEHAQ 36

36

---

---

---

---

---

---

---

---

**Receiver Operating Characteristic (ROC) Curves**

- **Receiver Operating Characteristic**
  - Used in signal detection theory: Tradeoffs in Hits vs. False alarms.
  - Medical diagnosis: Costs/tradeoffs in type-I, type-II errors
- **Data Mining**
  - Visualizing classifier performance
  - Comparing classifiers
  - Useful where:
    - Class distributions are unequal
    - Different misclassification costs

37

37

---

---

---

---

---

---

---

---

**Receiver Operating Characteristic (ROC) Curves**

Plot TPR vs. FPR as the classifier goes from "conservative" to "liberal"

38

38

---

---

---

---

---

---

---

---

**Receiver Operating Characteristic (ROC) Curves: Area Under the ROC Curve (AUC)**

- The ROC curve is used to generate a summary statistic:
  - The **Area Under the ROC Curve (AUC, A' or c-statistic)**
  - The area between the ROC curve and the no-discrimination line
  - Gini coefficient:
 
$$G_1 = 2 \text{ AUC} - 1$$
- Youden's J statistic: The intercept of the ROC curve with the line at  $\pi/2$  to the no-discrimination line.

39

39

---

---

---

---

---

---


---

---

**Receiver Operating Characteristic (ROC) Curves:**

- ROC curves don't explicitly show any dependence on the constant  $\frac{P}{N}$ 
  - They can be misleading if you care about FP versus TP

**Example:** Suppose you have a test for Alzheimer's whose false positive rate can be varied from 5% to 25% as the false negative rate varies from 25% to 5% (suppose linear dependences on both)



Slide 40

40

---

---

---

---

---

---

---

---

**Receiver Operating Characteristic (ROC) Curves:**

Now suppose you try the test on a population of 10 000 people, 1% of whom actually are Alzheimer's positive:

- FP swamps TP by 17:1. You'll be telling 17 people that they might have Alzheimer's for every one who actually does. It is unlikely that your test will be used.
- In a case like this, ROC, while correct, somewhat misses the point.

		Actual Class	
		+	-
Predicted Class	+	85	1405
	-	15	8415

Slide 41

41

---

---

---

---

---


---

---

---

**Precision-Recall Curves**

Precision-Recall curves overcome this issue by comparing TP with FN and FP



Not Always Monotonic:

$$TP \nearrow, TN \nearrow \Rightarrow \frac{TP}{TP + FP} \nearrow \text{ or } \searrow$$

Slide 42

42

---

---

---


---

---

---

---

---



43

---

---

---

---

---

---

---

---

**ROC versus Precision-Recall curves**

- For fixed marginals P,N the points on the ROC curve are in 1-to-1 correspondence with the points on the Precision-Recall curve: both display the same information. You can go back and forth.

**Precision-Recall from ROC**

$$\text{Precision} = \frac{\text{TPR} \times P}{\text{TPR} \times P + \text{TPR} \times N}$$

$$\text{Recall} = \text{TPR}$$

**ROC from Precision-Recall**

$$\text{FPR} = \frac{\text{Recall} \times (1 - \text{Precision}) \times P}{\text{Precision} \times N}$$

$$\text{TPR} = \text{Recall}$$

Réda DEHAÏ

44

---

---

---

---

---

---

---

---

**ROC versus Precision-Recall curves**

- It immediately follows that if one curve dominates another in ROC space, it also dominates in Precision-Recall space. (Because a crossing in one implies a crossing in the other, by the above equations)
- But for curves that cross, the metrics in one space don't easily map to the other. For example, people sometimes use "area under the ROC curve". This doesn't correspond to "area under the Precision-Recall curve", or to anything simple.

Réda DEHAÏ

45

---

---

---

---

---

---

---

---

**Detection Error Tradeoff (DET) curves**

- An alternative to the ROC curve.
- Plot the Missed Detections (FNR) vs. the False Alarms (FPR).
- Non-linearly (logarithmic) transformed x- and y-axes (quantile function of the normal distribution)
- The DET plot is used extensively in the evaluation of biometric systems.

ESL EPITA

Réda DEHAÏ 46

46

---

---

---


---

---

---

---

---



47

---

---

---

---

---

---

---

---

**Detection Error Tradeoff (DET) curves**

The DET curve is used to generate a summary statistic:

- **Equal Error Rate (EER)**: The intercept of the DET curve with the line corresponding to  $y = x$ .
- **Detection Cost Function (DCF)**: A weighted average of the missed detection and false alarm rates. The point on the DET Curve where such an average is minimized may be indicated (**minDCF**). If you have to provide a hard decision, the distance between the minDCF operating point and the operating point of this hard decision is an indication of how appropriately the system implementers chose the hard decision operating points to optimize the chosen cost function (**Calibration**).

ESL EPITA

Réda DEHAÏ 48

48

---

---

---

---



---

---

---

---





### Conclusion:

- Logistic Regression is a simple Linear Classifier
- Threshold must be fixed according to the cost (risk) function
- Confusion matrix is the best performance measure.

Réda DEHAK40

---

---

---

---

---

---

---