

DIMS IN MM

The diagram illustrates the mechanical details of a horizontal cylindrical vessel. It includes three main views: a top view, a front elevation, and an end view. The top view shows the circular cross-section with various nozzles labeled N1 through N41 and lifting lugs L1 and L2. Dimensions include a total length of 9120 mm and a diameter of 2400 mm. The front elevation shows the vessel's profile with additional nozzle locations and dimensions like 8820 mm and 7870 mm. The end view provides a detailed look at one of the elliptical heads, showing nozzle N1 and its associated dimensions.

GENERAL NOTES :

- 1. CODE OF CONSTRUCTION -ASME SEC.VIII-DIV.I-EDD-STAMPED.
- 2. MAWP: For Shell side=50 psig
- 3. MDMT=+ 30 F
- 4. Hydrotest: Shell side=1.3x50=65 psig
for duration of 1/2 hour.
- 5. UW-2 FOR LETHAL SERVICE - NON LETHAL .
- 6. IMPACT TEST Exempted - UG - 22 (F) , UCS.
- 7. Stress Releif exempted as per ASME STD.
- 8. Dimension Tollarence as per ASME SEC VIII.
- 9. E= 0.60 in Calculation as per ASME STD conditions

This section contains four detailed technical drawings. From left to right: 1. LIFTING LUGS: Shows two lifting lugs with dimensions for height (20 mm), width (700 mm), and base plate size (508 mm x 508 mm). 2. NOZZLE N33: A cross-sectional view of a nozzle with a 10mm thickness and a 200 mm diameter. 3. WELD DETAILS A/B: A cross-sectional view of a weld joint with a 10mm thickness and a 200 mm diameter. 4. SADDLE SUPPORTS DETAILS: A cross-sectional view of a saddle support with a 10mm thickness and a 200 mm diameter.

NOZZLE	DIMS/ QTY		DESCRIPTION	SPECIFICATION
N1 - N4, N13 - N17, N19 - N20	1"	11	SIGHT GLASS	SA106-GR.B SA105-B16.5
N5, N6, N9 N12, N21	3"	5	LEVEL SWITCHES	SA106-GR.B SA105-B16.5
N7, N8, N10	2"	3	OIL/WATER SENSOR	SA106-GR.B SA105-B16.5
N11, N18	1"	2	TEMPERATURE TRANSMITTER	SA106-GR.B SA105-B16.5
N22 - N23	2"	2	OIL/WATER SENSOR	SA106-GR.B SA105-B16.5
N24 - N28	1"	4	SAMPLING NOZZLE	SA106-GR.B SA105-B16.5
N29	3"	1	LEVEL SWITCH	SA106-GR.B SA105-B16.5
N30 - N31	3"	2	GAS OUTLET	SA106-GR.B SA105-B16.5
N32	2"	1	PRESSURE GAUGE	SA106-GR.B SA105-B16.5
N33 - N34	6"	2	PRESSURE SAFETY VALVE	SA106-GR.B SA105-B16.5
L1 - L2	-	2	LIFTING LUGS	SA516-GR.70 SA105-B16.5
N35, N37	2"	2	WATER DRAIN	SA106-GR.B SA105-B16.5
N36	4"	1	OIL OUTLET	SA106-GR.B SA105-B16.5
N38 - N39	3"	2	WATER DRAIN	SA106-GR.B SA105-B16.5
N40	4"	1	CRUDE OIL INPUT	SA106-GR.B SA105-B16.5
N41	2"	1	FRESH WATER INLET	SA106-GR.B SA105-B16.5
M1 - M2	20"	2	MANHOLE	SA516-GR.70 SA105-B16.5

PETROTEC INDUSTRIAL ENGINEERING COMPANY				
HEATER TREATER GENERAL ASSEMBLY - MECHANICAL DETAILS				
VESSEL MATERIAL	VESSEL THICKNESS	LENGTH	DIAMETER	SERIAL NO.
SA-283 Grade C	8MM	9.12M	2.4M	PT-00411
ENDCAP MATERIAL	ENDCAP THICKNESS	ENDCAP TYPE	TOTAL WEIGHT	
SA-283 Grade C	8MM	ELLIPTICAL	15 TON	
DWG. NO.	DRAWN BY	DESIGNED BY	REV.	DATE
PT-026-3	ENG. I.H	ENG. TAREK HAMMAD	03	04-May-26

PROPERTY OF PETROTEC. REPRODUCTION OR UNAUTHORIZED USE WITHOUT PRIOR WRITTEN APPROVAL IS PROHIBITED AND SUBJECT TO LEGAL ACTION.

NOZZLE	DIMS/ QTY		DESCRIPTION	SPECIFICATION
N1 - N4, N13 - N17, N19 - N20	1"	11	SIGHT GLASS	SA106-GR.B SA105-B16.5
N5, N6, N9 N12, N21	3"	5	LEVEL SWITCHES	SA106-GR.B SA105-B16.5
N7, N8, N10	2"	3	OIL/WATER SENSOR	SA106-GR.B SA105-B16.5
N11, N18	1"	2	TEMPERATURE TRANSMITTER	SA106-GR.B SA105-B16.5
N22 - N23	2"	2	OIL/WATER SENSOR	SA106-GR.B SA105-B16.5
N24 - N28	1"	4	SAMPLING NOZZLE	SA106-GR.B SA105-B16.5
N29	3"	1	LEVEL SWITCH	SA106-GR.B SA105-B16.5
N30 - N31	3"	2	GAS OUTLET	SA106-GR.B SA105-B16.5
N32	2"	1	PRESSURE GAUGE	SA106-GR.B SA105-B16.5
N33 - N34	6"	2	PRESSURE SAFETY VALVE	SA106-GR.B SA105-B16.5
L1 - L2	-	2	LIFTING LUGS	SA516-GR.70 SA105-B16.5
N35, N37	2"	2	WATER DRAIN	SA106-GR.B SA105-B16.5
N36	4"	1	OIL OUTLET	SA106-GR.B SA105-B16.5
N38 - N39	3"	2	WATER DRAIN	SA106-GR.B SA105-B16.5
N40	4"	1	CRUDE OIL INPUT	SA106-GR.B SA105-B16.5
N41	2"	1	FRESH WATER INLET	SA106-GR.B SA105-B16.5
M1 - M2	20"	2	MANHOLE	SA516-GR.70 SA105-B16.5

PETROTEC

INDUSTRIAL ENGINEERING COMPANY

HEATER TREATER

GENERAL ASSEMBLY - MECHANICAL DETAILS

VESSEL MATERIAL	VESSEL THICKNESS	LENGTH	DIAMETER	SERIAL NO.
SA-283 Grade C	8MM	9.12M	2.4M	PT-00411
ENDCAP MATERIAL	ENDCAP THICKNESS	ENDCAP TYPE	TOTAL WEIGHT	
SA-283 Grade C	8MM	ELLIPTICAL	15 TON	
DWG. NO.	DRAWN BY	DESIGNED BY	REV.	DATE
PT-026-3	ENG. I.H	ENG. TAREK HAMMAD	03	04-May-26

PROPERTY OF PETROTEC. REPRODUCTION OR UNAUTHORIZED USE WITHOUT PRIOR WRITTEN APPROVAL IS PROHIBITED AND SUBJECT TO LEGAL ACTION

NOZZEL	X (CM)	Y (CM)	DIAMETER (INCH)	NOZZEL2	X (CM)2	Y (CM)2	DIAMETER (INCH)2
N1	25	20	1	N22	300	160	2
N2	25	80	1	N23	340	170	2
N3	25	155	1	N24	340	100	1
N4	25	215	1	N25	355	125	1
N5	50	50	3	N26	370	150	1
N6	50	180	3	N27	385	175	1
N7	115	250	2	N28	400	200	1
N8	155	120	2	N29	810	220	2
N9	175	105	3	N30	50	240	4
N10	175	130	2	N31	110	240	4
N11	175	180	1	N32	250	240	2
N12	175	210	3	N33	430	240	6
N13	200	55	1	N34	630	240	6
N14	200	120	1	N35	10	0	2
N15	200	155	1	N36	40	0	4
N16	200	185	1	N37	125	0	2
N17	200	225	1	N38	215	0	3
N18	215	85	1	N39	345	0	3
N19	215	105	1	N40	787	0	4
N20	215	170	1	N41	8820	0	2
N21	260	145	3				