

# Sharq API Documentation

The following descriptions the list of endpoints Sharq's backend provides:

**Base URL:** <http://sahifa-app.com/api/v1/>

(If you click the URL above, you will be presented with an interface that shows the list of available endpoints)

Note: All parameters are required, unless stated otherwise.

## User Related Endpoints

[Registration Endpoint](#)

[Social Registration Endpoint](#)

[Login Endpoint](#)

[Guest Login Endpoint](#)

[Logout](#)

[Account Info Fetch / Update](#)

[Forgot Password](#)

[Update User Device](#)

## Countries

[Fetch Countries](#)

[User Countries](#)

[Follow Countries](#)

[Unfollow Countries](#)

## Interests

[Fetch Interests](#)

[User interests](#)

[Follow interests](#)

[Unfollow interests](#)

## Websites

[Fetch Websites](#)

## Feeds

[Fetch Feeds](#)

[Subscribe to Feed](#)

[Notify on Feed updates](#)

## Articles

[Newsfeed](#)

[Fetch Articles](#)

[Statistics - Increment article reads count](#)

[Statistics - Increment article shares count](#)

[Subscriptions](#)

[Fetch Subscriptions](#)

[Filter Subscriptions](#)

[Favorites](#)

[List](#)

[Add](#)

[Remove](#)

[Read Later](#)

[List](#)

[Add](#)

[Mark As Read](#)

[Remove](#)

[Keywords](#)

[List](#)

[Add](#)

[Remove](#)

[Comments](#)

[Count](#)

[List](#)

[Add](#)

[Other](#)

[Contact Form](#)

[Push Notifications](#)

## User Related Endpoints

### Registration Endpoint

Endpoint:

/user/register

Allowed Methods:

POST

Parameters:

email, fullname, password

Returns:

```
{
  "token": "75eb9e7afaedd82653b4b5eed00a9ecfdb26d835",
  "user": {
    "email": "rakan.alhneiti123@gmail.com",
    "facebook_connected": false,
    "first_name": "Rakan",
    "google_connected": false,
    "id": 6,
    "is_registered": true,
    "last_name": "Alhneiti",
    "profile_pic": null
  }
}
```

---

## Social Registration Endpoint

Endpoint:

/user/register\_social

Allowed Methods:

POST

Parameters:

email: Required  
full\_name: Optional  
password: Required  
google\_token, facebook\_token: At least one of them is required. These can be the user's ID from the service itself or the auth token. This is not checked in the backend, so any valid identifier could work.

Returns:

```
{
  "created": false,
  "token": "75eb9e7afaedd82653b4b5eed00a9ecfdb26d835",
  "user": {
    "email": "rakan.alhneiti123@gmail.com",
    "facebook_connected": false,
    "first_name": "Rakan",
    "google_connected": false,
    "id": 6,
    "is_registered": true,
    "last_name": "Alhneiti",
    "profile_pic": null
  }
}
```

---

## Login Endpoint

Endpoint:

/user/login

Allowed Methods:

POST

Parameters:

email, password

Returns:

```
{
  "token": "75eb9e7afaedd82653b4b5eed00a9ecfdb26d835",
  "user": {
    "email": "rakan.alhneiti123@gmail.com",
    "facebook_connected": false,
    "first_name": "Rakan",
    "google_connected": false,
    "id": 6,
    "is_registered": true,
    "last_name": "Alhneiti",
    "profile_pic": null
  }
}
```

---

## Guest Login Endpoint

Endpoint:

/user/guest

Allowed Methods:

POST

Parameters:

device\_id

Returns:

```
{
  "token": "ff4d3d24b869864d2be7e20ef20ac3f0957c6934",
  "user": {
    "email":
"guest_sdlkfjkl sdfjkdsfjlds_223c9714-3b9b-11e6-b20f-080027c2d293@sharq.com",
    "facebook_connected": false,
    "first_name": "",
    "google_connected": false,
    "id": 7,
    "is_registered": false,
    "last_name": "",
    "profile_pic": null
  }
}
```

---

## Logout

Endpoint:

/user/logout

Allowed Methods:

POST

Headers:

Authorization: Token {TOKEN}

The token is acquired from the login / registration endpoints described above.

Parameters:

Returns:

```
{  
  "message": "successfully logged in"  
}
```

---

## Account Info Fetch / Update

Endpoint:

/user

Allowed Methods:

GET, POST

Headers:

Authorization: Token {TOKEN}

The token is acquired from the login / registration endpoints described above.

Parameters:

```
GET -> No params required
POST:
full_name
password
profile_pic (File upload) (Content-Type: Multipart/form-data)
```

Returns:

```
GET:
{
  "email": "rakan.alhneiti123@gmail.com",
  "facebook_connected": false,
  "first_name": "Rakan",
  "google_connected": false,
  "id": 6,
  "is_registered": true,
  "last_name": "Alhneiti",
  "profile_pic": null
}

POST:
{
  "email": "rakan.alhneiti123@gmail.com",
  "facebook_connected": false,
  "first_name": "Rakan",
  "google_connected": false,
  "id": 6,
  "is_registered": true,
  "last_name": "Alhneiti",
  "profile_pic": null
}
```



---

## Forgot Password

Endpoint:

```
/user/forgot_password
```

Allowed Methods:

```
POST
```

Headers:

```
Authorization: Token {TOKEN}
```

The token is acquired from the login / registration endpoints described above.

Parameters:

```
email
```

Returns:

```
HTTP Code 200 for success, 404 in case email was not found, 400 if email is missing,  
500 is email wasn't sent.
```

---

## Update User Device

Provide the system with the Device ID or Token provided by Apple Notification service or Google Cloud Messaging for push notifications.

Endpoint:

/user/devices/update

Allowed Methods:

POST, DELETE

Headers:

Authorization: Token {TOKEN}

The token is acquired from the login / registration endpoints described above.

Parameters:

POST:  
type: android, ios  
key

DELETE:  
key

Returns:

POST: 201 HTTP code on success, 400 on bad request

DELETE: 200 HTTP code on success, 400 on bad request

---

# Countries

## Fetch Countries

Endpoint:

```
/country/list
```

Allowed Methods:

```
GET
```

Headers:

```
Authorization: Token {TOKEN}
```

The token is acquired from the login / registration endpoints described above.

Parameters:

```
page: 1, 2, 3 ... etc
```

Returns:

```
{
  "count": 1,
  "next": null,
  "previous": null,
  "results": [
    {
      "code": "jo",
      "id": 1,
      "name": "Jordan"
    }
  ]
}
```

```
]
}
```

---

## User Countries

The list of countries followed by the user

Endpoint:

```
/country/mine
```

Allowed Methods:

```
GET
```

Headers:

```
Authorization: Token {TOKEN}
```

The token is acquired from the login / registration endpoints described above.

Parameters:

```
page: 1, 2, 3 ... etc
```

Returns:

```
{
  "count": 1,
  "next": null,
  "previous": null,
  "results": [
    {
      "code": "jo",
```

```
    "id": 1,  
    "name": "Jordan"  
  }  
]  
}
```

---

## Follow Countries

Endpoint:

```
/country/add
```

Allowed Methods:

```
POST
```

Headers:

```
Authorization: Token {TOKEN}
```

The token is acquired from the login / registration endpoints described above.

Parameters:

```
ids: comma separated country IDs
```

Returns:

```
HTTP 200 on success, 400 on bad request
```

---

## Unfollow Countries

Endpoint:

```
/country/remove
```

Allowed Methods:

```
POST
```

Headers:

```
Authorization: Token {TOKEN}
```

The token is acquired from the login / registration endpoints described above.

Parameters:

```
ids: comma separated country IDs
```

Returns:

```
HTTP 200 on success, 400 on bad request
```

---

## Interests

### Fetch Interests

Endpoint:

```
/interest/list
```

Allowed Methods:

GET

Headers:

Authorization: Token {TOKEN}

The token is acquired from the login / registration endpoints described above.

Parameters:

page: 1, 2, 3 ... etc

Returns:

```
{
  "count": 2,
  "next": null,
  "previous": null,
  "results": [
    {
      "id": 1,
      "name": "Local",
      "subscribed": false
    },
    {
      "id": 2,
      "name": "Business",
      "subscribed": false
    }
  ]
}
```

---

## User interests

The list of interests followed by the user

Endpoint:

```
/interest/mine
```

Allowed Methods:

```
GET
```

Headers:

```
Authorization: Token {TOKEN}
```

The token is acquired from the login / registration endpoints described above.

Parameters:

```
page: 1, 2, 3 ... etc
```

Returns:

```
{
  "count": 2,
  "next": null,
  "previous": null,
  "results": [
    {
      "id": 1,
      "name": "Local",
      "subscribed": false
    },
  ],
}
```



```
{
  {
    "id": 2,
    "name": "Business",
    "subscribed": false
  }
}
```

---

## Follow interests

Endpoint:

/interest/add

Allowed Methods:

POST

Headers:

Authorization: Token {TOKEN}

The token is acquired from the login / registration endpoints described above.

Parameters:

ids: comma separated interest IDs

Returns:

HTTP 200 on success, 400 on bad request

---

## Unfollow interests

Endpoint:

/interest/remove

Allowed Methods:

POST

Headers:

Authorization: Token {TOKEN}

The token is acquired from the login / registration endpoints described above.

Parameters:

ids: comma separated interest IDs

Returns:

HTTP 200 on success, 400 on bad request

---

## Websites

### Fetch Websites

Endpoint:

/website/list

Allowed Methods:

GET

Headers:

Authorization: Token {TOKEN}

The token is acquired from the login / registration endpoints described above.

Parameters:

page: 1, 2, 3 ... etc

Returns:

```
{
  "count": 1,
  "results": [
    {
      "id": 1,
      "image": {
        "caption": "asdas",
        "file": "http://192.168.0.10:8080/media/images/2016/06/18/image.gif",
        "height": 300,
        "width": 200
      },
      "name": "Khaberni"
    }
  ]
}
```

---

# Feeds

## Fetch Feeds

Endpoint:

```
/feed/list
```

Allowed Methods:

```
GET
```

Headers:

```
Authorization: Token {TOKEN}
```

The token is acquired from the login / registration endpoints described above.

Parameters:

```
website_id: The website ID to display feeds from  
type: to either fetch "categories" or "writers", default is category if not provided  
since: A date/time value to only fetch feeds added after that date/time (optional)  
(format: YYYY/mm/dd HH:mm:ss)  
page: 1, 2, 3 ... etc
```

Returns:

```
{  
  "count": 1,  
  "results": [  
    {  
      "id": 1,  
      "is_subscribed": null,  
    }  
  ]  
}
```

```
{
  "title": "تبض الشارع",
  "type": "category",
  "website": {
    "id": 1,
    "image": {
      "caption": "asdas",
      "file": "http://192.168.0.10:8080/media/images/2016/06/18/image.gif",
      "height": 300,
      "width": 200
    },
    "name": "Khaberni"
  }
}
```

---

## Subscribe to Feed

Endpoint:

```
/feed/subscribe
```

Allowed Methods:

```
POST
```

Headers:

```
Authorization: Token {TOKEN}
```

The token is acquired from the login / registration endpoints described above.

Parameters:

feed\_id

Returns:

HTTP 200 for success, 400 or 404 otherwise

---

## Notify on Feed updates

Endpoint:

/feed/notify

Allowed Methods:

POST

Headers:

Authorization: Token {TOKEN}

The token is acquired from the login / registration endpoints described above.

Parameters:

feed\_id

Returns:

HTTP 200 for success, 400 or 404 otherwise

---

# Articles

## Newsfeed

This is the main endpoint that is to be used to fetch articles using certain filters described below.

Endpoint:

```
/newsfeed
```

Allowed Methods:

```
POST
```

Headers:

```
Authorization: Token {TOKEN}
```

The token is acquired from the login / registration endpoints described above.

Parameters:

filters: This should be sent as a list of JSON objects

Example:

```
filters = [  
  {  
    "type": "country",  
    "name": "jordan"  
  },  
  {  
    "type": "interest",  
    "name": "local"  
  },  
  {
```

```
  "type": "keyword",
  "name": "داعش"
},
{
  "type": "category",
  "id": 2,
}
]
```

Available filter types:

category, keyword, interest, country

Values should be as follows:

For keywords, the keyword (content) itself should be provided.

For interest, the interest (name) itself should be provided

For country, the country (name) should be provided

For category, the category (ID) should be provided

Returns:

```
{
  "count": 1,
  "results": [
    {
      "body": " ",
      "channel_id": 1,
      "channel_name": "تبض الشارع",
      "channel_type": "category",
      "country_id": [
        1
      ],
      "country_name": [
        "Jordan"
      ],
      "date_published": "2016-03-13T21:36:00",
      "interest_id": [
        1
      ]
    }
  ]
}
```



```

],
"interest_name": [
  "Local"
],
"is_favorite": false,
"is_readlater": false,
"item_id": "336",
"photos":
"http://192.168.0.10:8080/media/images/2016/03/14/1457908553_JyY9BxE.jpg"
],
"status": 1,
"summary": "وبحسب تصريحات الطراونة التي أدلى بها عبر التلفزيون الأردني فإن هتافات الطلبة:
عشرات بل مئات الحملات التي\n.المعتصمين يظهر بها النفس الحزبي شبيهة بالهتافات التي أطلقت في سوريا وتونس
قامت بها النقابات ومراكز جمعيات حقوقية واحزاب بل واشخاص كافراد دون ان تطلب ترخيص لهذه الحملات ، هل
سمعت يوماً بقانون ترخيص الحملات مثلاً؟!، لماذا قمت يا استاذنا الفاضل بالاتصال بمنسق الحملة أكثر من عشر مرات
وفي مواقف مختلفة وطلبت لقاءنا بل واستقبلتنا في مكتبك بناءً على طلبك قبل ثلاثة اعوام، لماذا قمت بذلك طالما ترى ان
هذه الحملة غير مرخصة وان على وزير الداخلية حبسنا؟!، ولماذا قمت بالاتصال بنا عندما كنت رئيساً لجامعة البلقاء
وكانت ذبحتونا تخوض آنذاك اعتصاماً لطلبة الشامل احتجاجاً على الامتحانات وقمت انت حينها بالاستجابة المباشرة
\n،!المطالبنا؟، هل لغة الاعتقال والحبس والوعيد ومطالبة وزارة الداخلية بحبس طلبتك هي لغة اكااديمية؟",
"thumbnail": null,
"title": "الطراونة: نفس حزبي بشعارات المعتصمين - فيديو",
"url": "http://192.168.0.10:8080/article/336",
"videos": null,
"website_id": 1,
"website_image": null,
"website_name": "Khaberni"
}
]
}

```

## Fetch Articles

This endpoint could be used as an alternative to the newsfeed to fetch articles by ID or by Feed ID. But it doesn't follow the same conventions that newsfeed endpoint implements.

Endpoint:

/article/list

Allowed Methods:

GET

Headers:

Authorization: Token {TOKEN}

The token is acquired from the login / registration endpoints described above.

Parameters:

Either feed\_id or article\_id to fetch articles by feed or a single article by ID  
page: 1, 2, 3 ... etc

Returns:

```
{
  "count": 1,
  "results": [
    {
      "body": " ",
      "channel_id": 1,
      "channel_name": "تبيض الشارع",
      "channel_type": "category",
      "country_id": [
        1
      ],
      "country_name": [
        "Jordan"
      ],
      "date_published": "2016-03-13T21:36:00",
      "interest_id": [
```

```

1
],
"interest_name": [
  "Local"
],
"is_favorite": false,
"is_readlater": false,
"item_id": "336",
"photos": [
  "http://192.168.0.10:8080/media/images/image.jpg",
  "http://192.168.0.10:8080/media/images/image2.jpg"
],
"status": 1,
"summary": "وبحسب تصريحات الطراونة التي أدلى بها عبر التلفزيون الأردني فإن هتافات الطلبة"
عشرات بل مئات الحملات التي n. المعتصمين يظهر بها النفس الحزبي شبيهة بالهتافات التي أطلقت في سوريا وتونس
قامت بها النقابات ومراكز جمعيات حقوقية واحزاب بل واشخاص كافراد دون ان تطلب ترخيص لهذه الحملات ، هل
سمعت يوماً بقانون ترخيص الحملات مثلاً؟!، لماذا قمت يا استاذنا الفاضل بالاتصال بمنسق الحملة اكثر من عشر مرات
وفي مواقف مختلفة وطلبت لقاءنا بل واستقبلتنا في مكتبك بناءً على طلبك قبل ثلاثة اعوام، لماذا قمت بذلك طالما ترى ان
هذه الحملة غير مرخصة وان على وزير الداخلية حبسنا؟!، ولماذا قمت بالاتصال بنا عندما كنت رئيساً لجامعة البلقاء
وكانت ذبحتونا تخوض آنذاك اعتصاماً لطلبة الشامل احتجاجاً على الامتحانات وقمت انت حينها بالاستجابة المباشرة
وكانت ذبحتونا؟!، هل لغة الاعتقال والحبس والوعيد ومطالبة وزارة الداخلية بحبس طلبتك هي لغة اكااديمية؟
",
"thumbnail": "http://192.168.0.10:8080/media/images/image.jpg",
"title": "الطراونة: نفس حزبي بشعارات المعتصمين - فيديو",
"url": "http://192.168.0.10:8080/article/336",
"videos": null,
"website_id": 1,
"website_image": null,
"website_name": "Khaberni"
}
]
}

```

## Statistics - Increment article reads count

Endpoint:

/article/mark\_read

Allowed Methods:

POST

Headers:

Authorization: Token {TOKEN}

The token is acquired from the login / registration endpoints described above.

Parameters:

article\_id

Returns:

HTTP 200 on success. 400, 404 otherwise

---

## Statistics - Increment article shares count

Endpoint:

/article/mark\_share

Allowed Methods:

POST

Headers:

Authorization: Token {TOKEN}

The token is acquired from the login / registration endpoints described above.

Parameters:

article\_id

Returns:

HTTP 200 on success. 400, 404 otherwise

---

## Subscriptions

### Fetch Subscriptions

Endpoint:

/subscriptions/list

Allowed Methods:

GET

Headers:

Authorization: Token {TOKEN}

The token is acquired from the login / registration endpoints described above.

Parameters:

page: 1, 2, 3 ... etc

Returns:

```
{
  "count": 1,
  "next": null,
  "previous": null,
  "results": [
    {
      "id": 2,
      "is_subscribed": true,
      "title": "اسواق",
      "type": "category",
      "website": {
        "id": 1,
        "image": {
          "caption": "asdas",
          "file": "http://192.168.0.10:8080/media/images/2016/06/18/image.gif",
          "height": 300,
          "width": 200
        },
        "name": "Khaberni"
      }
    }
  ]
}
```

---

## Filter Subscriptions

This endpoint is used in the right side menu in the Android app. Fetches the list of countries, keywords and websites the user is subscribed to and their “new” articles counts.

Endpoint:

/subscriptions/filter

Allowed Methods:

GET

Headers:

Authorization: Token {TOKEN}

The token is acquired from the login / registration endpoints described above.

Parameters:

Returns:

```
{
  "countries": [
    {
      "count": 0,
      "id": 1,
      "name": "Jordan"
    }
  ],
  "keywords": [
    {
      "count": 0,
      "id": 3,
      "name": "test"
    }
  ],
  "websites": [
    {
      "categories": [
        {
          "count": 0,
```

```
        "id": 2,  
        "name": "اسواق"  
      },  
    ],  
    "count": 0,  
    "id": 1,  
    "name": "Khaberni"  
  }  
]  
}
```

---

## Favorites

### List

Endpoint:

```
/article/favorite/list
```

Allowed Methods:

```
GET
```

Headers:

```
Authorization: Token {TOKEN}
```

The token is acquired from the login / registration endpoints described above.

Parameters:

```
page: 1, 2, 3 ... etc
```

Returns:



```
{
  "count": 1,
  "next": "",
  "previous": "",
  "results": [
    {
      "body": "ابو العبد الذي كان كفيلا لتغيير مسار حياة عائلة الحاج السبعيني ابو العبد\خبرني - خطأ طبي"
      معاناته عليها تجد صدى لدى\ازارت كاميرا\ "خبرني" منزله المتواضع في حي الغويرية بمحافظة الزرقاء لنقل\
      حياته كان يعمل مهندسا\السبعيني الغزي الذي خط مرار الايام رسما موجعا على تفاصيل\اصحاب الايدي البيضاء
      معاناته\ويروي ابو العبد\الى قلوب الناس\كهربائيا الا ان ظروف الحياة اجتمعت عليه ووضعته في زاوية اللاجئ
      العملية التي\انه يعاني من السكري-\التي افقدته قدرة السير إذ اجريت له عملية البتر ظنا من الاطباء -حسب روايته
      ابو العبد\دينار 2030\لابو العبد كلفته 7 الاف دينار دفع منها اصحاب الخير معظم قيمتها ليتبقي بدمته\اجريت
      الى مناشدة اصحاب\بالسجن جراء توقيعه على كمبالة بقيمة المبلغ المستحق بتاريخ 15/3/2016 وهذا ما دفعه\مهدد
      تقرير:\المزيد في\ننشرها عبر خبرني عليها تجد صدى وتتجد سبعيني من جدران السجن\ومناشدة ابو العبد\الخير
      الاتصال على الرقم التالي:\للمساعدة\احمزة أبوorman / تصوير : رعد العضائلة / مونتاج مروان السكران
      0787543787",
      "channel_id": 1,
      "channel_name": "نبض الشارع",
      "channel_type": "category",
      "country_id": [
        1
      ],
      "country_name": [
        "Jordan"
      ],
      "date_published": "2016-03-13T10:15:00",
      "interest_id": [
        1
      ],
      "interest_name": [
        "Local"
      ],
      "is_favorite": null,
      "is_readlater": null,
      "item_id": "352",
      "photos": [
```

```
"http://192.168.0.10:8080/media/images/2016/03/14/1457908553_JyY9BxE.jpg"
],
"status": 1,
"summary": "ابو العبد الذي زارت كاميرا \خبرني\ منزله المتواضع في حي الغويرية بمحافظة الزرقاء:
السبعيني الغزي الذي خط مرار الايام رسما موجعا على\n.لنقل معاناته عليها تجد صدى لدى اصحاب الايدي البيضاء
تفاصيل حياته كان يعمل مهندسا كهربائيا الا ان ظروف الحياة اجتمعت عليه ووضعته في زاوية اللاجئ الى قلوب الناس
.\n",
"thumbnail":
"http://192.168.0.10:8080/media/images/2016/03/14/1457908553_JyY9BxE.jpg.320x1
60_q85_crop-smart.jpg",
"title": "مهدد بالسجن بسبب فاتورة - فيديو",
"url": "http://192.168.0.10:8080/article/352",
"videos": null,
"website_id": 1,
"website_image": null,
"website_name": "Khaberni"
}
]
}
```

## Add

Endpoint:

```
/article/favorite/add
```

Allowed Methods:

```
POST
```

Headers:

```
Authorization: Token {TOKEN}
```

The token is acquired from the login / registration endpoints described above.

Parameters:

article\_id

Returns:

HTTP 200 on success, 404, 400 otherwise

---

## Remove

Endpoint:

/article/favorite/remove

Allowed Methods:

POST

Headers:

Authorization: Token {TOKEN}

The token is acquired from the login / registration endpoints described above.

Parameters:

article\_id

Returns:

HTTP 200 on success, 404, 400 otherwise

---

# Read Later

## List

Endpoint:

```
/article/readlater/list
```

Allowed Methods:

```
GET
```

Headers:

```
Authorization: Token {TOKEN}
```

The token is acquired from the login / registration endpoints described above.

Parameters:

```
page: 1, 2, 3 ... etc
```

Returns:

```
{
  "count": 1,
  "next": "",
  "previous": "",
  "results": [
    {
      "body": "ابو العبد الذي كان كفيلا لتغيير مسار حياة عائلة الحاج السبعيني ابو العبد\ن خبرني - خطأ طبي"
    }
  ]
}
```

معاناته عليها تجد صدی لدى\ن زارت كاميرا\ "خبرني" منزله المتواضع في حي الغويرية بمحافظة الزرقاء لنقل\ن حياته كان يعمل مهندسا\ن السبعيني الغزي الذي خط مرار الايام رسما موجعا على تفاصيل\ن اصحاب الايدي البيضاء

معاناته\nويروي ابو العبد\nالى قلوب الناس\nكهربائيا الا ان ظروف الحياة اجتمعت عليه ووضعت في زاوية اللاجئ العملية التي\nانه يعاني من السكري-\nالتي افقدته قدرة السير إذ اجريت له عملية البتر ظنا من الاطباء -حسب روايته ابو العبد\nدينار 2030\nالابو العبد كلفته 7 الاف دينار دفع منها اصحاب الخير معظم قيمتها ليتبقى بذمته\nاجريت الى مناشدة اصحاب\nبالسجن جراء توقيعه على كمبيالة بقيمة المبلغ المستحق بتاريخ 15/3/2016 وهذا ما دفعه\nمهدد تقرير:\nالمزيد في\n.ننشرها عبر خبرني عليها تجد صدق وتجد سبعيني من جدران السجن\nومناشدة ابو العبد\nالخير الاتصال على الرقم التالي:\nللمساعدة\nاحمزة أبوorman / تصوير : رعد العضائلة / مونتاج مروان السكران 0787543787",

```
"channel_id": 1,
"channel_name": "نبض الشارع",
"channel_type": "category",
"country_id": [
  1
],
"country_name": [
  "Jordan"
],
"date_published": "2016-03-13T10:15:00",
"interest_id": [
  1
],
"interest_name": [
  "Local"
],
"is_favorite": null,
"is_readlater": null,
"item_id": "352",
"photos": [
```

"http://192.168.0.10:8080/media/images/2016/03/14/1457908553\_JyY9BxE.jpg"

```
],
```

```
"status": 1,
```

```
"summary": "ابو العبد الذي زارت كاميرا \\"خبرني\\" منزله المتواضع في حي الغويرية بمحافظة الزرقاء"
السبعيني الغزي الذي خط مرار الايام رسما موجعا على\n.لنقل معاناته عليها تجد صدق لدى اصحاب الايدي البيضاء
تفاصيل حياته كان يعمل مهندسا كهربائيا الا ان ظروف الحياة اجتمعت عليه ووضعت في زاوية اللاجئ الى قلوب الناس
.\n",
```

```
"thumbnail":
```

```
"http://192.168.0.10:8080/media/images/2016/03/14/1457908553_JyY9BxE.jpg.320x160_q85_crop-smart.jpg",
```

```
{
  "title": "مهدد بالسجن بسبب فاتورة - فيديو",
  "url": "http://192.168.0.10:8080/article/352",
  "videos": null,
  "website_id": 1,
  "website_image": null,
  "website_name": "Khaberni"
}
```

---

## Add

Endpoint:

```
/article/readlater/add
```

Allowed Methods:

```
POST
```

Headers:

```
Authorization: Token {TOKEN}
```

The token is acquired from the login / registration endpoints described above.

Parameters:

```
article_id
```

Returns:

```
HTTP 200 on success, 404, 400 otherwise
```

---

## Mark As Read

This endpoint archives the article from list by marking it as read (after the user has read the article, he/she can mark it as read)

Endpoint:

```
/article/readlater/markasread
```

Allowed Methods:

```
POST
```

Headers:

```
Authorization: Token {TOKEN}
```

The token is acquired from the login / registration endpoints described above.

Parameters:

```
article_id
```

Returns:

```
HTTP 200 on success, 404, 400 otherwise
```

---

## Remove

Endpoint:

```
/article/readlater/remove
```

Allowed Methods:

POST

Headers:

Authorization: Token {TOKEN}

The token is acquired from the login / registration endpoints described above.

Parameters:

article\_id

Returns:

HTTP 200 on success, 404, 400 otherwise

---

## Keywords

### List

Endpoint:

/keyword/list

Allowed Methods:

GET

Headers:



Authorization: Token {TOKEN}

The token is acquired from the login / registration endpoints described above.

Parameters:

page: 1, 2, 3 ... etc

Returns:

```
{
  "count": 1,
  "next": null,
  "previous": null,
  "results": [
    {
      "content": "test",
      "id": 3
    }
  ]
}
```

---

## Add

Endpoint:

/keyword/add

Allowed Methods:

POST

Headers:

Authorization: Token {TOKEN}

The token is acquired from the login / registration endpoints described above.

Parameters:

content

Returns:

HTTP 200 on success, 404, 400 otherwise

---

## Remove

Endpoint:

/keyword/remove

Allowed Methods:

POST

Headers:

Authorization: Token {TOKEN}

The token is acquired from the login / registration endpoints described above.

Parameters:

content

Returns:

HTTP 200 on success, 404, 400 otherwise

---

## Comments

### Count

Endpoint:

/comments/count

Allowed Methods:

GET

Headers:

Authorization: Token {TOKEN}

The token is acquired from the login / registration endpoints described above.

Parameters:

id: the article id

Returns:

```
{  
  "message": 0,  
  "status": true  
}
```

---

## List

Endpoint:

```
/comments/
```

Allowed Methods:

```
GET
```

Headers:

```
Authorization: Token {TOKEN}
```

The token is acquired from the login / registration endpoints described above.

Parameters:

```
id: the article id
```

Returns:

```
{
  "count": 1,
  "next": null,
  "previous": null,
  "results": [
    {
      "comment": "Hello",
      "id": 4,
      "submit_date": "2016-06-28T09:28:17Z",
      "user": {
        "email": "rakan.alhneiti123@gmail.com",
        "facebook_connected": false,
```

```
    "first_name": "Rakan",  
    "google_connected": false,  
    "id": 6,  
    "is_registered": true,  
    "last_name": "Alhneiti",  
    "profile_pic": null  
  }  
}  
]  
}
```

---

## Add

Endpoint:

```
/comments/add
```

Allowed Methods:

```
POST
```

Headers:

```
Authorization: Token {TOKEN}
```

The token is acquired from the login / registration endpoints described above.

Parameters:

```
article_id  
comment
```

Returns:

HTTP 200 on success, 404, 400 otherwise

---

## Other

### Contact Form

Endpoint:

/contact

Allowed Methods:

POST

Headers:

Authorization: Token {TOKEN}

The token is acquired from the login / registration endpoints described above.

Parameters:

name  
email  
subject  
message

Returns:

HTTP 200 on success, 400 otherwise

---

# Push Notifications

We have 3 ways in which notifications will be sent:

- 1) Through admin by adding a new notification record (manually)
- 2) Through feed subscription. So when you subscribe to a feed and ask to be notified on updates for that feed, you will receive a notification.
- 3) When new categories are added which fall under one of your interests. The android app doesn't display a UI notification in this case, but it shows the list of feeds added since last app run. This can be done by sending a request to /feed/list and using the "since" parameter it takes.

A notification will be sent with 3 parameters:

- 1) "target" which will indicate what the notification is about.

Possible Values for this param:

- a) general: means that this is a generic notification (probably sent through admin)
  - b) feed\_update or keyword\_update meaning that the notification is about a feed that has been updated or that some articles were found for a certain keyword.
  - c) feed\_interest which means that the some feeds have been added that fall under the user's interests.
- 2) "title" notification title
  - 3) "Message" the content of the notification
  - 4) "id", "type", "name" are only sent with keyword\_update or feed\_update notifications
  - 5) "date" is only sent with feed\_interest notification