Locat

Self-Hosted Private Messaging & Collaboration

Document purpose: public-facing technical overview and practical orientation; not a security certification or independent audit.

Project status: Active development; maintained implementation is on feat/locat-1.0

Technology / architecture: TypeScript, React, Node.js, MariaDB, IndexedDB, Web Crypto, Capacitor, Docker

Architecture & capabilities

• Self-hosted accounts, private and group messaging concepts

• Device-side encryption and local message persistence

• Android client built using Capacitor

• Linux/Raspberry Pi server deployment direction

• Evolving local media and cross-device file browsing workflows

Evaluation / getting started

• Read the active development branch rather than assuming main is current

• Follow its docs/INSTALLATION.md for the relevant Linux, Raspberry Pi or Docker environment

• Test on isolated or personal infrastructure and record platform, build and behavior

Limitations and security considerations

• Not a Signal Protocol implementation and does not claim Signal-style forward secrecy

• Server still handles account and delivery metadata

• FCM, media browsing and unified mobile features are under active development or verification

Engineering roadmap

• Validate encryption, backups and multi-device delivery

• Complete Android navigation, authorized media access and release tests

Source and verification

Repository: https://github.com/ibrahim1101/Locat

Information reflects the accessible project README and the supplied engineering resume. Features may change; verify current repository branches, releases and documentation before deployment. Do not upload private keys, user data, internal logs or unredacted evidence.