Meplaniq Logo System

Production specification and export handoff



Approved symbol-only MEP coordination mark

Master artboard: 2400 × 2400 units · Primary palette · Transparent background

Contents

1 Design premise 1
2 Construction measurements 1
2.1 Clear space 1
2.2 Geometry rules 1
3 Approved color system 1
4 Standard logo variants 3
4.1 Minimum sizes 3
4.2 Background guidance 3
5 Incorrect usage 3
6 Export handoff 3

1 Design premise

The Meplaniq mark is a four-zone technical coordination symbol. Each quadrant represents a major MEP discipline, while the shared center and controlled negative space express integration and workflow coordination.

- Upper-left: mechanical and equipment
- Upper-right: electrical and power
- Lower-left: plumbing and water
- Lower-right: AC, HVAC, and airflow

The mark is intentionally symbol-only. A wordmark lockup is not included in this specification because the exact `meplaniq` wordmark typography has not yet been approved.

2 Construction measurements

Property	Value	Production meaning
SVG viewBox	`0 0 2400 2400`	Centered master artboard
Center axis	`x = 1200, y = 1200`	Four zones align to the center
Source geometry	1920 × 1920	Approved artwork area
Master inset	240 units	Clear breathing room around source geometry
Suggested clear-space unit X	120 units	Minimum protected space
Visible width	≈ 97.45%	Based on approved raster bounds
Visible height	≈ 98.91%	Based on approved raster bounds

2.1 Clear space

Define **X = 120 master units**. Keep at least `1X` of empty space between the visible silhouette and any text, border, UI control, image, or neighboring mark. The supplied master artboard provides approximately `2X` of practical breathing room on each side.

2.2 Geometry rules

Preserve the four-zone order, the central negative space, the relative mass of each quadrant, and the clean discipline boundaries. Do not add outlines, glows, bevels, shadows, gradients, or 3D effects to the core mark.

3 Approved color system

Token	Component	HEX	Role
`mech-blue`	Mechanical / equipment	`#123B7A`	Structural anchor
`elec-amber`	Electrical / power	`#F4B400`	Energy and signal

`plumb-cyan`	Plumbing / water	`#00A6D6`	Water and flow
`hvac-green`	AC / HVAC / airflow	`#1F9D55`	Air and efficiency
`control-violet`	Fixtures / controls accent	`#7C3AED`	UI/detail accent

The primary logo uses the four discipline colors. The violet control color is reserved for application UI, technical legends, selected states, and future responsive detail. It is not required as a fifth full-size quadrant in the core symbol.

4 Standard logo variants

Variant	Use	Master file
Primary	Main website and product identity	`svg/logo_icon_primary.svg`
Dark	Dark product UI and dark brand surfaces	`svg/logo_icon_dark.svg`
Monochrome	Print, stamp, emboss, and one-color reproduction	`svg/logo_icon_mono.svg`
Reverse	White mark on dark or colored surfaces	`svg/logo_icon_reverse.svg`

4.1 Minimum sizes

Application	Minimum	Guidance
Favicon / browser tab	16 px	Prefer 32 px or 48 px
Compact UI icon	24 px	Use primary icon only
App navigation	32 px	Do not add violet detail
Header icon	48 px	Primary or dark variant
Digital standalone mark	64 px	Full color or monochrome
Print standalone mark	12 mm	Use vector SVG

4.2 Background guidance

Approved backgrounds are white, transparent, light neutral surfaces, deep navy or graphite using the dark variant, and solid dark surfaces using the reverse variant. Avoid busy photography, low-contrast gray, uncontrolled gradients, colored outlines, and forced white boxes around a mark that already has transparency.

5 Incorrect usage

Do not stretch, compress, rotate, crop, or redraw the symbol. Do not change the quadrant order, fill the negative-space center, replace the approved colors arbitrarily, or add a wordmark before typography is approved. Do not add shadows, glow, chrome, bevels, or 3D extrusion.

6 Export handoff

The SVG masters are editable vector reconstructions of the approved raster artwork. They use four filled path groups on a 2400-unit artboard and preserve the approved silhouette and component order. The original generated raster is retained separately for comparison.

For trademark filing, manufacturing, embroidery, or other high-volume fabrication, a designer should perform a final manual Bézier/path review and approve the exact geometry before legal registration or production.

Package area	Included files
Vector masters	`logo_icon_primary.svg`, `logo_icon_dark.svg`, `logo_icon_mono.svg`, `logo_icon_reverse.svg`
PNG masters	`logo_icon_primary.png`, `logo_icon_dark.png`, `logo_icon_mono.png`, `logo_icon_reverse.png`
Favicon sizes	16, 24, 32, 48, 64, 128, 256, and 512 px
Documentation	`brand_logo_system_spec.md` and this PDF