PHILIPS

Master LED 4.9-50W GU10 930 36D Dim

929001348908



LEDspot, PAR16, dimmable, 50 W, GU10, 3000 K, 405 lm, 25000 hour(s)

LEDspot, PAR16, dimmable, 50 W, GU10, 3000 K, 405 lm, 25000 hour(s), 81.00 lm/W

Warnings and Safety

- Operating temperature range is between -20° C and 45° C ambient
- Only to apply in dry or damp locations and most of open fixtures with lamp-holders that offer sufficient space (10 mm free air space)
- Not intended for use with emergency light fixtures or exit lights

General Information

Cap-Base	GU10
Nominal lifetime	25,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LEDspot

Light Technical

Color Code	930 [CCT of 3000K]
Beam Angle (Nom)	36 degree(s)
Luminous Flux	405 lm
Luminous Intensity (Nom)	650 cd

Color Designation	White (WH)
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	81.00 lm/W
Color Consistency	<6
Color rendering index (CRI)	90
LLMF At End Of Nominal Lifetime (Nom)	70 %
Luminous Flux in 90° Cone (Rated)	365 lm

Operating and Electrical

Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	5 W
Lamp Current (Nom)	27 mA
Wattage Equivalent	50 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.8
Voltage (Nom)	220-240 V

Temperature

T-Case Maximum (Nom)	80 °C

Controls and Dimming

Dimmable	Yes

Mechanical and Housing

Bulb Shape	PAR16
Net Weight (Piece)	0.038 kg

Approval and Application

Suitable For Accent Lighting	Yes
Energy Consumption kWh/1000 h	5 kWh
EU RoHS compliant	Yes
Ambient temperature range	-20 to +45 °C


Application Conditions

Wireless Technology	Not applicable

Product Data


Order product name	Master LED 4.9-50W GU10 930 36D Dim
Full product name	Master LED 4.9-50W GU10 930 36D Dim
Full product code	871869675592100
Order code	929001348908
Material Nr. (12NC)	929001348908
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718696755921
Numerator - Packs per outer box	10
EAN/UPC - Case	8718696755938

Dimensional drawing




Product	D	C
Master LED 4.9-50W GU10 930 36D Dim	50 mm	54 mm

Photometric data




Spectral Power Distribution Colour - Master LED 4.9-50W GU10 930 36D Dim




Light Distribution Diagram - Master LED 4.9-50W GU10 930 36D Dim

Lifetime



25K LED



Lumen Maintenance Diagram - Master LED 4.9-50W GU10 930 36D Dim

Related Documents

Documents and certificates	Document Name	Download
Environmental Product Declaration	Philips-MASTER-VALUE-LEDspot-MV-COMF-2198-Ref-929004255802-EPD.pdf	Download

Photometry and lighting design	Document Name	Download
IES File	LEDspot_50W_GU10_930_36D_365lm-IES.ies	Download

© 2026 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.