```python
import tensorflow as tf
from tensorflow.keras.callbacks import LearningRateScheduler
from tensorflow.keras.layers import Dense,  Conv2D, MaxPooling2D, Dropout, Flatten, GlobalAveragePooling2D
from tensorflow.keras.optimizers import Adam, SGD, RMSprop
from tensorflow.keras.preprocessing.image import ImageDataGenerator
from tensorflow.keras.callbacks import Callback
import numpy as np
import matplotlib.pyplot as plt
import os
from os.path import join
import multiprocessing
from sklearn.metrics import confusion_matrix

def trainCNN( ):

    tf.keras.backend.clear_session()

    ImageResolution = (640, 360)
    ImageResolutionGrayScale = (640, 360, 1)
    modelNumber = 'Model22'

    base_dir = 'C:\work_dir\meteorData\extraData'
    results_dir_weights = 'G:\GIEyA\TFG\meteor_classification\\results\weights\\' + modelNumber

    train_dir = join(base_dir, 'train')
    validation_dir = join(base_dir, 'validation')
    test_dir = join(base_dir, 'test')

    #Rescale all images by 1./255

    train_datagen = ImageDataGenerator(rescale=1.0/255#,
                                       #rotation_range=10, # Range from 0 to 180 degrees to randomly rotate images
                                       #width_shift_range=0.05,
                                       # height_shift_range=0.05,
                                       #shear_range=5, # Shear the image by 5 degrees
                                       #zoom_range=0.1,
                                       # horizontal_flip=True,
                                       #vertical_flip=True,
                                       #fill_mode='nearest'
                                       )

    validation_datagen = ImageDataGenerator(rescale=1.0/255.)
    test_datagen = ImageDataGenerator(rescale=1.0/255.0)

    train_generator = train_datagen.flow_from_directory(train_dir,
                                                        batch_size=16, #16
                                                        class_mode='binary',
                                                        color_mode='grayscale',
                                                        target_size=ImageResolution) # 640x360 = 480x480. (640, 360)

    validation_generator = validation_datagen.flow_from_directory(validation_dir,
                                                                  batch_size=16, #16
                                                                  class_mode='binary',
                                                                  color_mode='grayscale',
                                                                  target_size=ImageResolution)

    test_generator = test_datagen.flow_from_directory(test_dir,
  batch_size=1,
  class_mode='binary',
  color_mode='grayscale',
  target_size=ImageResolution,
  shuffle=False)

    model = tf.keras.models.Sequential([
        Conv2D(16, (11, 11), activation='relu', input_shape=ImageResolutionGrayScale, strides=1),
        MaxPooling2D(pool_size=(3, 3)),
        Dropout(0.25),

        Conv2D(16, (7, 7), activation='relu', kernel_initializer='he_uniform'),
        #Conv2D(12, (3, 3), activation='relu', kernel_initializer='he_uniform'),
        MaxPooling2D(pool_size=(3, 3)),
        Dropout(0.25),

        Conv2D(12, (5, 5), activation='relu', kernel_initializer='he_uniform'),
        #Conv2D(16, (3, 3), activation='relu', kernel_initializer='he_uniform'),
        MaxPooling2D(pool_size=(2, 2)),
        Dropout(0.25),

        Conv2D(8, (3, 3), activation='relu', kernel_initializer='he_uniform'),
        MaxPooling2D(pool_size=(2, 2)),

        Flatten(),
        Dense(840, activation='relu', kernel_initializer='he_uniform'),
        Dropout(0.30),
        Dense(32, activation='relu', kernel_initializer='he_uniform'),
        Dropout(0.20),
        Dense(1, activation='sigmoid', kernel_initializer='he_uniform')
    ])

    print(model.summary())
    optimizer = Adam(learning_rate=5e-4) #3e-3 # Try with more and less learning rate # 5e-3
    model.compile(optimizer=optimizer,
                  loss='binary_crossentropy',
                  metrics=['accuracy'])
    #model.load_weights(join(results_dir_weights, 'model_acc_0.926.h5'))

    class SaveModelCallback(Callback):
        def __init__(self, thresholdTrain, thresholdValid):
            super(SaveModelCallback, self).__init__()
            self.thresholdTrain = thresholdTrain
            self.thresholdValid = thresholdValid

        def on_epoch_end(self, epoch, logs=None):
            if((logs.get('accuracy') >= self.thresholdTrain) and (logs.get('val_accuracy') >= self.thresholdValid)):
                model.save_weights(join(results_dir_weights, modelNumber + '_acc_' +  str(logs.get('accuracy'))[0:6] + '_val_acc' + str(logs.get('val_accuracy'))[0:6] + '.h5'), save_format='h5')

    callback90 = SaveModelCallback(0.900, 0.900)

    # Training -> 66947
    # Validation -> 13388
    # Test -> 8928

    history = model.fit(train_generator,
                        validation_data=validation_generator,
                        steps_per_epoch=4184, #4184
                        epochs=120, #Later train with more epochs if neccessary
                        validation_steps=836, #836
                        verbose=1,
                        callbacks=[callback90])
```

```python


    #############################################################################################
    #############################################################################################

    prob_predicted = model.predict(test_generator, steps=len(test_generator.filenames))
    test_labels = []

    for i in range(0, len(test_generator.filenames)):
        test_labels.extend(np.array(test_generator[i][1]))

    # Get the confusion matrix:
    truePositives = 0
    trueNegatives = 0
    falsePositives = 0
    falseNegatives = 0

    for i in range(len(prob_predicted)):
        if(prob_predicted[i] >= 0.5 and test_labels[i] == 1.0):
            truePositives += 1
        elif(prob_predicted[i] >= 0.5 and test_labels[i] == 0.0):
            falsePositives += 1
        elif(test_labels[i] == 0.0):
            trueNegatives += 1
        elif(test_labels[i] == 1.0):
            falseNegatives += 1

    performanceFile = open(join(results_dir_weights, 'performance' + modelNumber + '.txt'), 'w')
    performanceFile.write('*********************************************\n')
    performanceFile.write('confusion matrix: \n')
    performanceFile.write('true positives: {}\n'.format(truePositives))
    performanceFile.write('false positives: {}\n'.format(falsePositives))
    performanceFile.write('true negatives: {}\n'.format(trueNegatives))
    performanceFile.write('false negatives: {}\n'.format(falseNegatives))
    performanceFile.write('*********************************************\n')

    modelPrecision = (truePositives) / (truePositives + falsePositives)
    modelRecall = (truePositives) / (truePositives + falseNegatives)
    modelF1score = (2 * (modelPrecision * modelRecall)) / (modelPrecision + modelRecall)

    performanceFile.write('*********************************************\n')
    performanceFile.write('Performance metrics: \n')
    performanceFile.write('Model Precision: {}\n'.format(modelPrecision))
    performanceFile.write('Model Recall: {}\n'.format(modelRecall))
    performanceFile.write('Model F1 Score: {}\n'.format(modelF1score))
    performanceFile.write('*********************************************\n')

    performanceFile.close()

    #############################################################################################
    #############################################################################################

    acc      = history.history['accuracy']
    val_acc  = history.history['val_accuracy']
    loss     = history.history['loss']
    val_loss = history.history['val_loss']
    epochs = range(len(acc)) #Get number of epochs

    plt.plot(epochs, acc)
    plt.plot(epochs, val_acc)
    plt.title('Meteor detection training and
validation accuracy')

    plt.figure()
    plt.plot(epochs, loss)
    plt.plot(epochs, val_loss)
    plt.title('Meteor detection training and validation loss')

    plt.show()


if __name__ == '__main__':
    p = multiprocessing.Process(target=trainCNN)
    p.start()
    p.join()
```