



abc test

Generated By: Sentina AI

Generated: 2026-04-05T17:50:22.533151

Report Type: exhibitor

This report was automatically generated by the Exhibitors Management System.

SUMMARY

Overview of this report based on the configuration selected in the Exhibitors dashboard.

Report Configuration

- **Date Range:** 2026-01-19 to 2026-01-21
- **Aggregation Level:** Hourly

Included Sections

- Exhibitor Profile
- Booth Traffic Overview
- Visitor Engagement Analysis
- Operating Environment Analysis
- Performance Breakdown
- Definitions and Calculation Logic

This report was automatically generated by the Exhibitors Management System.

Exhibitor Profile

Exhibitor Contact Details

Attribute	Details
Primary Contact	N/A
Contact Email	N/A
Contact Phone	N/A

Event and Exhibitor Details

Atlas Networks LLC is assigned to booth **HZB01-B004** in **EastHall1** for **AI for Facilities Management Forum 2026**, under the **N/A** package, with **23 hours** analysed.

Attribute	Details
Event Name	AI for Facilities Management Forum 2026
Event Window	2026-01-19 06:00 to 2026-01-21 14:45
Exhibitor Name	Atlas Networks LLC
Exhibitor ID	EXH0240
Industry	FinTech
HQ Country	Singapore

Booth Allocation

Attribute	Details
Booth Code	HZB01-B004
Hall	EastHall1
Zone	zoneB
Booth Size Type	standard
Total Booth Area (sqm)	9.00

Commercial and Analysis Scope

Attribute	Details
Package Tier	N/A
Avg Discount (%)	N/A
Amount Paid (AED)	0.00
Time Intervals Analysed	23 hours

Booth Traffic Overview

Hall-level traffic conditions and movement patterns surrounding the exhibitor’s booth, providing relative context against other halls.

Traffic Summary

Key traffic indicators for the selected exhibitor scope.

Traffic conditions around **EastHall1** indicate **high** activity relative to other halls, with **3,099** total inflow observed and a peak at **2026-01-19 10:00** .

Attribute	Details
Total Inflow	3,099
Total Outflow	2,564
Average Inflow per Interval	134.74
Average Outflow per Interval	111.48
Average Occupancy	N/A
Average Occupancy Ratio	83.7%
Peak Traffic Window	2026-01-19 10:00
Peak Inflow Value	327
Busiest Hour Band	10:00 - 10:59
Busiest Day	2026-01-20

Traffic Conditions

Crowding and movement conditions across the selected scope.

Attribute	Details
Traffic Level	High
Density Level	Moderate
Average Congestion Index	0.69
Queue Time	0.0%
Overcrowded Time	13.0%

Peak Traffic Hours

Top-performing time intervals ranked by total inflow within the exhibitor’s hall context.

Time Interval	Inflow	Outflow	Net Flow	Occupancy Ratio	Congestion Index
2026-01-19 10:00 to 11:00	327	45	282	0.91	0.84
2026-01-21 10:00 to 11:00	294	0	294	0.88	0.81
2026-01-20 10:00 to 11:00	293	91	202	0.78	0.67

Time Interval	Inflow	Outflow	Net Flow	Occupancy Ratio	Congestion Index
2026-01-20 17:00 to 18:00	277	124	153	0.9	0.78
2026-01-19 17:00 to 18:00	246	0	246	0.87	0.83
2026-01-19 14:00 to 15:00	204	131	73	0.87	0.76
2026-01-19 12:00 to 13:00	183	220	-37	0.78	0.62
2026-01-21 12:00 to 13:00	166	131	35	0.87	0.76
2026-01-20 18:00 to 19:00	146	116	30	0.86	0.75
2026-01-20 13:00 to 14:00	139	128	11	0.82	0.72

Traffic Insights

Key observations derived from traffic patterns.

Metric	Value
Peak Contribution (%)	10.6%
Average Inflow	134.74
Peak vs Average Ratio	2.43
Traffic Variability	High

Visitor Engagement Analysis

Hall-level engagement conditions surrounding the exhibitor’s booth, providing relative context rather than booth-exclusive performance.

Engagement Summary

Key engagement indicators for the selected exhibitor scope.

Engagement conditions around **EastHall1** indicate **low** interaction quality relative to surrounding hall activity, with an average score of **0.33** and a peak observed at **2026-01-20 10:00** .

Attribute	Details
Average Engagement	0.33
Median Engagement	0.33
Max Engagement	0.54
Min Engagement	0.11
Engagement Level	Low
Consistency	Stable
Peak Engagement Window	2026-01-20 10:00
Lowest Engagement Window	2026-01-19 11:00
Best Hour Band	13:00 - 13:59
Best Day	2026-01-20

Engagement Distribution

Distribution of higher and lower engagement intervals across the scoped hall context.

Attribute	Details
High Engagement Time	0.0%
Moderate Engagement Time	30.4%
Low Engagement Time	69.6%
Average Inflow	134.74
Average Occupancy Ratio	83.7%
Average Density Score	0.51
Average Congestion Index	0.69

Peak Engagement Periods

Time intervals with the highest engagement observed around the exhibitor’s hall (relative context).

Time Interval	Engagement Score	Inflow	Occupancy Ratio	Congestion Index
2026-01-20 10:00	0.54	293	0.78	0.67
2026-01-20 13:00	0.51	139	0.82	0.72
2026-01-21 14:00	0.45	12	0.63	0.46

Time Interval	Engagement Score	Inflow	Occupancy Ratio	Congestion Index
2026-01-19 14:00	0.44	204	0.87	0.76
2026-01-20 12:00	0.44	134	0.89	0.7
2026-01-19 13:00	0.41	44	0.81	0.64
2026-01-20 15:00	0.4	131	0.8	0.63
2026-01-21 12:00	0.4	166	0.87	0.76
2026-01-19 17:00	0.34	246	0.87	0.83
2026-01-21 13:00	0.34	85	0.91	0.77

Engagement Insights

Key observations derived from engagement patterns.

Metric	Value
Peak vs Average Ratio	1.67
Engagement Range	0.44
Consistency Profile	Stable
Engagement Variability	High

This report was automatically generated by the Exhibitors Management System.

Operating Environment Analysis

Hall-level activity patterns representing the operating environment surrounding the exhibitor’s booth for EastHall1. The primary analysis is shown at hour-level aggregation, while day and hour patterns are included as supporting context.

Primary Time-Based Analysis

Main operating-environment view using the selected hourly aggregation level.

The strongest surrounding hall activity was observed during **2026-01-19 10:00 to 11:00** , where average inflow reached **81.8**. This represents the highest potential visitor exposure window for the exhibitor.

The weakest surrounding activity was observed during **2026-01-19 16:00 to 17:00** , where inflow fell to **0.0**, indicating a comparatively quieter operating environment.

Across recurring patterns, **Tuesday** showed the strongest average hall movement, while the peak hour band was **10:00 - 10:59**, helping identify when the surrounding hall environment is typically most favorable.

Period	Average Inflow	Average Outflow	Occupancy Ratio	Congestion	Comfort	Engagement
2026-01-19 10:00 to 11:00	81.8	11.2	91.2%	0.84	49.95	0.12
2026-01-19 11:00 to 12:00	15.0	13.5	92.3%	0.74	49.35	0.11
2026-01-19 12:00 to 13:00	45.8	55.0	78.5%	0.62	57.02	0.31
2026-01-19 13:00 to 14:00	11.0	20.0	81.3%	0.64	49.02	0.41
2026-01-19 14:00 to 15:00	51.0	32.8	87.1%	0.76	48.15	0.44
2026-01-19 15:00 to 16:00	21.5	23.0	89.6%	0.71	49.55	0.32
2026-01-19 16:00 to 17:00	0.0	58.5	63.1%	0.44	53.60	0.26
2026-01-19 17:00 to 18:00	61.5	0.0	86.6%	0.83	50.02	0.34
2026-01-19 18:00 to 19:00	1.8	34.5	80.8%	0.58	51.02	0.20
2026-01-20 10:00 to 11:00	73.2	22.8	77.5%	0.67	46.95	0.54

Period	Average Inflow	Average Outflow	Occupancy Ratio	Congestion	Comfort	Engagement
2026-01-20 11:00 to 12:00	31.2	31.2	81.7%	0.72	49.42	0.33
2026-01-20 12:00 to 13:00	33.5	17.8	89.0%	0.70	54.23	0.44
2026-01-20 13:00 to 14:00	34.8	32.0	81.9%	0.72	49.20	0.51
2026-01-20 14:00 to 15:00	12.0	29.8	82.3%	0.65	52.02	0.33
2026-01-20 15:00 to 16:00	32.8	23.0	79.8%	0.63	51.67	0.40
2026-01-20 16:00 to 17:00	23.0	48.8	85.4%	0.69	53.75	0.20
2026-01-20 17:00 to 18:00	69.2	31.0	89.7%	0.78	47.45	0.26
2026-01-20 18:00 to 19:00	36.5	29.0	86.1%	0.75	46.55	0.29
2026-01-21 10:00 to 11:00	73.5	0.0	87.6%	0.81	51.92	0.25
2026-01-21 11:00 to 12:00	0.0	19.5	90.6%	0.63	57.25	0.21
2026-01-21 12:00 to 13:00	41.5	32.8	87.1%	0.76	52.33	0.40
2026-01-21 13:00 to 14:00	21.2	13.5	91.4%	0.77	52.52	0.34
2026-01-21 14:00 to 15:00	3.0	61.5	63.3%	0.46	51.92	0.45

Day Pattern

This breakdown shows which days typically provide stronger or weaker surrounding hall activity for the exhibitor, independent of the selected main aggregation level.

Day	Average Inflow
Monday	32.1
Tuesday	38.5
Wednesday	27.9

Hour Pattern

This view highlights when the surrounding hall environment is usually busiest during the day, helping identify the most favorable exposure windows even when the primary analysis is grouped daily, weekly, or monthly.

Hour Band	Average Inflow
10:00 - 10:59	76.2
11:00 - 11:59	15.4
12:00 - 12:59	40.2
13:00 - 13:59	22.3
14:00 - 14:59	22.0
15:00 - 15:59	27.1
16:00 - 16:59	11.5
17:00 - 17:59	65.4
18:00 - 18:59	19.1

Hall Conditions During Operation

These metrics provide environmental context for the exhibitor by describing surrounding visitor movement and general hall conditions.

Metric	Value
Average Inflow	33.7
Average Outflow	27.9
Average Occupancy Ratio	83.7%
Average Congestion	0.69
Average Comfort	51.08
Average Engagement	0.33
Best Day	Tuesday
Weakest Day	Wednesday
Best Hour Band	10:00 - 10:59
Weakest Hour Band	16:00 - 16:59

This report was automatically generated by the Exhibitors Management System.

Performance Breakdown

Daily comparative analysis of the surrounding hall environment across the exhibitor’s event period. This section is fixed at day level to enable meaningful cross-day comparison, independent of the selected main aggregation level.

Daily Performance Comparison

Day-by-day comparison of the surrounding hall environment across the exhibitor’s event presence.

The strongest day-level operating environment around **EastHall1** was **2026-01-20**, supported by higher inflow, a stronger comfort profile, and a better overall daily performance score of **0.650**.

The weakest day was **2026-01-21**, where the surrounding hall environment recorded lower overall performance with a score of **0.456**.

Compared day by day, this section evaluates not only visitor volume but also how comfortably and efficiently the hall environment operated around the exhibitor’s booth.

Day	Total Inflow	Total Outflow	Net Flow	Avg Occupancy Ratio	Avg Congestion	Avg Comfort	Avg Engagement	Performance Score
2026-01-19	1157	994	163	83.4%	0.68	50.86	0.28	0.470
2026-01-20	1385	1061	324	83.7%	0.70	50.14	0.37	0.650
2026-01-21	557	509	48	84.0%	0.69	53.19	0.33	0.456

Derived Daily Metrics

These measures go beyond simple counts by comparing flow balance, pressure, comfort-adjusted exposure, and engagement efficiency across event days.

Day	Flow Efficiency	Retention	Pressure Score	Comfort-Adjusted Exposure	Engagement Efficiency
2026-01-19	0.859	0.141	0.571	588.40	0.00024
2026-01-20	0.766	0.234	0.587	694.42	0.00027
2026-01-21	0.914	0.086	0.576	296.27	0.00059

Best vs Weakest Day

High-level comparison of the strongest and weakest surrounding hall conditions across the exhibitor’s active days.

2026-01-20 delivered the strongest surrounding environment overall, while **2026-01-21** was the weakest day when all major daily conditions were considered together.

Metric	Value
Best Day	2026-01-20
Best Day Score	0.650
Best Day Inflow	1385

Metric	Value
Best Day Comfort	50.14
Best Day Congestion	0.70
Weakest Day	2026-01-21
Weakest Day Score	0.456
Weakest Day Inflow	557
Weakest Day Comfort	53.19
Weakest Day Congestion	0.69

This report was automatically generated by the Exhibitors Management System.

Definitions and Calculation Logic

Definitions and calculation logic for key exhibitor report metrics.

Scope and Interpretation Notes

All analytics in this report are derived from **hall-level activity patterns** surrounding the exhibitor's booth. These metrics describe the **operating environment** , including visitor movement, crowd pressure, comfort, congestion, and engagement conditions. They should be interpreted as **contextual exposure and indicators** , rather than direct booth-exclusive measurements. Most sections follow the selected aggregation level; however, **Performance Breakdown is fixed at daily level** to enable meaningful comparison across event days.

Attribute	Details
Analytical Scope	Hall-level operating environment surrounding the exhibitor's booth
Primary Use	Exposure, engagement, and performance context
Booth Limitation	Not direct booth-level measurement
Aggregation Behavior	Mixed (user-selected + fixed daily comparison)

Metric Definitions

Definitions and interpretation of key metrics.

Metric	Definition	Interpretation
Occupancy Ratio	Relative occupancy level of the hall compared to capacity.	Higher values indicate fuller hall utilization.
Average Occupancy Ratio	Mean occupancy ratio across selected intervals.	Represents typical utilization level of the hall environment.
Congestion Index	Measure of crowd movement pressure at an interval level.	Higher values indicate restricted movement.
Average Congestion	Mean congestion index across the selected scope.	Represents typical movement pressure over time.
Net Flow	Net change in visitor movement after accounting for inflow and outflow.	Positive values indicate accumulation of visitors, while negative values indicate dispersal.
Peak Traffic Window	The interval in which inflow reaches its highest observed value.	Identifies the strongest visitor exposure window.
Busiest Hour Band	The hour-of-day band with the highest average inflow across the selected period.	Helps identify the time of day with the strongest recurring visitor activity.
Busiest Day	The calendar day with the highest aggregated inflow.	Identifies the strongest event day for visitor exposure.
Peak Contribution (%)	Share of total inflow contributed by the peak interval or peak aggregated period.	Higher values indicate more concentration of traffic in a small number of intervals.

Metric	Definition	Interpretation
Peak vs Average Ratio	Comparison of peak activity to typical levels.	Higher values indicate spiky traffic or engagement behavior.
Traffic Variability	Consistency of visitor flow over time.	High variability indicates uneven traffic distribution.
Comfort	Environmental comfort score within the hall.	Higher values indicate better visitor conditions.
Average Comfort	Mean comfort score across the selected time range.	Used to compare environmental quality across intervals or days.
Average Engagement	Mean engagement score across the selected scope.	Represents typical engagement conditions around the exhibitor.
Best Day	The day with the strongest average engagement or strongest comparative operating conditions.	Indicates which event day provided the strongest surrounding hall environment.
Weakest Day	The day with the weakest comparative operating conditions.	Indicates which event day performed least favorably overall.
Best Hour Band	The hour-of-day band with the strongest recurring hall conditions.	Used to identify the most favorable recurring operating window.
Pressure Score	Combined crowd pressure indicator.	Higher values indicate crowded and constrained conditions.
Flow Efficiency	Balance between incoming and outgoing movement.	Higher values indicate smoother movement through the hall.
Retention	Proportion of visitors remaining within the hall.	Higher values indicate visitor accumulation.
Comfort-Adjusted Exposure	Exposure weighted by comfort quality.	Rewards high traffic under good conditions.
Engagement Efficiency	Engagement achieved relative to visitor volume.	Measures how effectively traffic converts to interaction.
Performance Score	Composite daily performance metric.	Used to compare overall day-level performance.

Calculation Logic

How key derived metrics are calculated.

Metric	Formula / Logic
Occupancy Ratio	$\text{current_occupancy} / \text{reference_capacity}$
Average Occupancy Ratio	$\text{mean}(\text{occupancy_ratio})$
Net Flow	Total Inflow - Total Outflow
Peak Contribution (%)	$\text{Peak Inflow Value} / \text{Total Inflow} \times 100$
Peak vs Average Ratio	$\text{Peak Value} / \text{Average Value}$
Pressure Score	$\text{Occupancy Ratio} \times \text{Congestion Index}$
Flow Efficiency	$\text{Total Outflow} / \text{Total Inflow}$
Retention	$1 - \text{Flow Efficiency}$
Comfort-Adjusted Exposure	$\text{Total Inflow} \times (\text{Comfort} / 100)$
Engagement Efficiency	$\text{Engagement} / \text{Inflow}$
Performance Score	Weighted normalized score (flow + comfort + congestion + engagement)

