



WE DID ITT

Generated By: Sentina AI

Generated: 2026-04-05T19:17:44.523011

Report Type: exhibitor

This report was automatically generated by the Exhibitors Management System.

SUMMARY

Overview of this report based on the configuration selected in the Exhibitors dashboard.

Report Configuration

- **Date Range:** 2026-01-24 to 2026-01-25
- **Aggregation Level:** Hourly

Included Sections

- Exhibitor Profile
- Performance Breakdown
- Definitions and Calculation Logic

This report was automatically generated by the Exhibitors Management System.

Exhibitor Profile

Exhibitor Contact Details

Attribute	Details
Primary Contact	Karim Schmidt
Contact Email	karim.schmidt@cloudninesecurity.com
Contact Phone	'+971569250788

Event and Exhibitor Details

CloudNine Security LLC is assigned to booth **HZA06-B005** in **SouthHall6** for **Smart Infrastructure & Automation Expo 2026**, under the **Starter** package, with **8 hours** analysed.

Attribute	Details
Event Name	Smart Infrastructure & Automation Expo 2026
Event Window	2026-01-24 06:00 to 2026-01-25 11:45
Exhibitor Name	CloudNine Security LLC
Exhibitor ID	EXH0167
Industry	Smart Buildings
HQ Country	Singapore

Booth Allocation

Attribute	Details
Booth Code	HZA06-B005
Hall	SouthHall6
Zone	zoneA
Booth Size Type	standard
Total Booth Area (sqm)	12.00

Commercial and Analysis Scope

Attribute	Details
Package Tier	Starter
Avg Discount (%)	0.00
Amount Paid (AED)	16,800.00
Time Intervals Analysed	8 hours

Performance Breakdown

Daily comparative analysis of the surrounding hall environment across the exhibitor’s event period. This section is fixed at day level to enable meaningful cross-day comparison, independent of the selected main aggregation level.

Daily Performance Comparison

Day-by-day comparison of the surrounding hall environment across the exhibitor’s event presence.

The strongest day-level operating environment around **SouthHall6** was **2026-01-24**, supported by higher inflow, a stronger comfort profile, and a better overall daily performance score of **0.500**.

The weakest day was **2026-01-24**, where the surrounding hall environment recorded lower overall performance with a score of **0.500**.

Compared day by day, this section evaluates not only visitor volume but also how comfortably and efficiently the hall environment operated around the exhibitor’s booth.

Day	Total Inflow	Total Outflow	Net Flow	Avg Occupancy Ratio	Avg Congestion	Avg Comfort	Avg Engagement	Performance Score
2026-01-24	822	629	193	79.9%	0.69	53.87	0.49	0.500
2026-01-25	387	281	106	74.6%	0.66	52.00	0.50	0.500

Derived Daily Metrics

These measures go beyond simple counts by comparing flow balance, pressure, comfort-adjusted exposure, and engagement efficiency across event days.

Day	Flow Efficiency	Retention	Pressure Score	Comfort-Adjusted Exposure	Engagement Efficiency
2026-01-24	0.765	0.235	0.549	442.82	0.00059
2026-01-25	0.726	0.274	0.493	201.24	0.00128

Best vs Weakest Day

High-level comparison of the strongest and weakest surrounding hall conditions across the exhibitor’s active days.

2026-01-24 delivered the strongest surrounding environment overall, while **2026-01-24** was the weakest day when all major daily conditions were considered together.

Metric	Value
Best Day	2026-01-24
Best Day Score	0.500
Best Day Inflow	822
Best Day Comfort	53.87
Best Day Congestion	0.69
Weakest Day	2026-01-24

Metric	Value
Weakest Day Score	0.500
Weakest Day Inflow	822
Weakest Day Comfort	53.87
Weakest Day Congestion	0.69

This report was automatically generated by the Exhibitors Management System.

Definitions and Calculation Logic

Definitions and calculation logic for key exhibitor report metrics.

Scope and Interpretation Notes

All analytics in this report are derived from **hall-level activity patterns** surrounding the exhibitor’s booth. These metrics describe the **operating environment** , including visitor movement, crowd pressure, comfort, congestion, and engagement conditions. They should be interpreted as **contextual exposure and indicators** , rather than direct booth-exclusive measurements. Most sections follow the selected aggregation level; however, **Performance Breakdown is fixed at daily level** to enable meaningful comparison across event days.

Attribute	Details
Analytical Scope	Hall-level operating environment surrounding the exhibitor's booth
Primary Use	Exposure, engagement, and performance context
Booth Limitation	Not direct booth-level measurement
Aggregation Behavior	Mixed (user-selected + fixed daily comparison)

Metric Definitions

Definitions and interpretation of key metrics.

Metric	Definition	Interpretation
Net Flow	Net change in visitor movement after accounting for inflow and outflow.	Positive values indicate accumulation of visitors, while negative values indicate dispersal.
Average Occupancy Ratio	Mean occupancy ratio across selected intervals.	Represents typical utilization level of the hall environment.
Average Congestion	Mean congestion index across the selected scope.	Represents typical movement pressure over time.
Average Comfort	Mean comfort score across the selected time range.	Used to compare environmental quality across intervals or days.
Average Engagement	Mean engagement score across the selected scope.	Represents typical engagement conditions around the exhibitor.
Pressure Score	Combined crowd pressure indicator.	Higher values indicate crowded and constrained conditions.
Flow Efficiency	Balance between incoming and outgoing movement.	Higher values indicate smoother movement through the hall.
Retention	Proportion of visitors remaining within the hall.	Higher values indicate visitor accumulation.
Comfort-Adjusted Exposure	Exposure weighted by comfort quality.	Rewards high traffic under good conditions.
Engagement Efficiency	Engagement achieved relative to visitor volume.	Measures how effectively traffic converts to interaction.

Metric	Definition	Interpretation
Performance Score	Composite daily performance metric.	Used to compare overall day-level performance.
Best Day	The day with the strongest average engagement or strongest comparative operating conditions.	Indicates which event day provided the strongest surrounding hall environment.
Weakest Day	The day with the weakest comparative operating conditions.	Indicates which event day performed least favorably overall.

Calculation Logic

How key derived metrics are calculated.

Metric	Formula / Logic
Net Flow	Total Inflow - Total Outflow
Average Occupancy Ratio	mean(occupancy_ratio)
Pressure Score	Occupancy Ratio × Congestion Index
Flow Efficiency	Total Outflow / Total Inflow
Retention	1 - Flow Efficiency
Comfort-Adjusted Exposure	Total Inflow × (Comfort / 100)
Engagement Efficiency	Engagement / Inflow
Performance Score	Weighted normalized score (flow + comfort + congestion + engagement)

This report was automatically generated by the Exhibitors Management System.