

```
-- INA LWA: Supabase schema. SQL Editor
keessatti yeroo tokko gaggeessi.

create table if not exists
public.enrollments (
  id uuid primary key default
gen_random_uuid(),
  ref text not null unique,
  full_name text not null,
  phone text not null,
  department text not null,
  plan text not null,
  founding boolean not null default false,
  status text not null default 'new', --
new | contacted | paid | active | cancelled
  notes text,
  created_at timestamptz not null default
now()
);

create table if not exists
public.contact_messages (
  id uuid primary key default
gen_random_uuid(),
  full_name text,
  message text not null,
  created_at timestamptz not null default
now()
);
```

```

create table if not exists
public.certificates (
    cert_id text primary key,          --
    fknf. INA-2026-0001
    student_name text not null,
    course text not null,
    instructor text,
    completion_date date,
    revoked boolean not null default false,
    created_at timestampz not null default
now()
);

alter table public.enrollments        enable
row level security;
alter table public.contact_messages enable
row level security;
alter table public.certificates        enable
row level security;

-- Marsariitiin (anon) galmaa'insa fi ergaa
INSERT qofa gochuu danda'a.
SELECT/UPDATE/DELETE hin danda'u.
create policy "anon insert enrollments" on
public.enrollments
    for insert to anon
    with check (
        status = 'new' and notes is null
        and char_length(full_name) between 3
and 120
        and char_length(phone) between 9 and 20
        and char_length(ref) between 6 and 30
        and char_length(department) <= 80 and
char_length(plan) <= 40

```

```

);

create policy "anon insert messages" on
public.contact_messages
    for insert to anon
    with check (char_length(message) between
3 and 2000 and (full_name is null or
char_length(full_name) <= 120));

-- Certificates: anon table kallattiin
dubbisuu hin danda'u. Function kanaan ID
tokko qofa mirkaneessa.
create or replace function
public.verify_certificate(p_id text)
returns table (student_name text, course
text, instructor text, completion_date
date)
language sql security definer set
search_path = public as $$
    select student_name, course, instructor,
completion_date
    from public.certificates
    where cert_id = upper(trim(p_id)) and not
revoked;
$$;
revoke all on function
public.verify_certificate(text) from
public;
grant execute on function
public.verify_certificate(text) to anon;

-- Ragaa itti dabaluuf (Table Editor ykn
SQL):
-- insert into public.certificates

```

```
(cert_id, student_name, course, instructor,  
completion_date)  
-- values ('INA-2026-0002','Maqaa  
Barataa','Financial Literacy & Wealth  
Creation','Maqaa Barsiisaa','2026-10-30');
```