

Assignment2

● Graded

Student

IBRAHIM ALSHAYEA

Total Points

94 / 100 pts

Question 1

(no title)

44 / 50 pts

- 0 pts Excellent Work
- 50 pts Missing Code
- 30 pts Doubly Linked Lists are not used
- 20 pts Add function is missing
- 20 pts Delete function is missing
- 45 pts Code does not compile
- 40 pts Code does not run (Error)
- 15 pts Extending existing classes
- 6 pts Nodes are not ordered
- ✓ - 6 pts Repeated values are allowed
- 10 pts Delete does not work properly
- 10 pts Add does not work properly
- 5 pts Code is not general for all classes
- 5 pts Error when deleting from empty list
- 5 pts Throws an error instead of returning false
- 2 pts Minor error in the code
- 50 pts Cheating case
- 5 pts Mistake in variables

+ 0 pts Wrong

The behavior of the program

✓ + 3 pts The code compiles but does not run

✓ + 2 pts The code compiles and runs

✓ + 3 pts Convert to binary

✓ + 3 pts convert to radix 3

✓ + 3 pts convert to radix 4

✓ + 3 pts convert to radix 5

✓ + 3 pts convert to radix 6

✓ + 3 pts convert to radix 7

✓ + 3 pts convert to radix octal

✓ + 3 pts convert to radix 9

✓ + 3 pts convert to decimal

✓ + 3 pts convert to radix 11

✓ + 3 pts convert to radix 12

✓ + 3 pts convert to radix 13

✓ + 3 pts convert to radix 14

✓ + 3 pts convert to radix 15

✓ + 3 pts convert to hexadecimal

– 5 pts No exception handling

– 30 pts Not using a stack

– 5 pts Non-generic code (If statement for each radix)

– 2 pts Minor error in the code (Hardcoding, bad practices)

– 10 pts Error in the submission

Q1

50 Points

Develop and implement a new class ODLList for an Ordered Doubly Linked List (without extending any existing classes). The nodes in this list are generic, comparable, **distinct**, and **ordered**.

Your class should have the following:

1. *boolean add(T element)*--adds *element* in its proper position if it does not exist.
2. *boolean delete(T element)*--deletes *element* from the list if it exists.

Both methods should return true if the element is added/deleted, otherwise return false.

Submit only the file **ODLList.java**

```
1 package Hw;
2
3 import LabPrograms.DLLNode;
4
5 public class ODLList<T extends Comparable<T>> {
6     private Node<T> head;
7     private Node<T> tail;
8     static class Node<T>{
9         private T info;
10        private Node<T> next, prev;
11        Node(T info){
12            this.info = info;
13        }
14    }
15
16    public boolean add(T element){
17        Node<T> newNode = new Node<>(element);
18        if(head == null){
19            head = newNode;
20            tail = newNode;
21            return true;
22        }
23        Node<T> current = head;
24        while (current != null && current.info.compareTo(element) < 0) {
25            current = current.next;
26        }
27        if(current == null){
28            tail.next = newNode;
29            tail.next.prev = tail;
30            tail =newNode;
31        }
32        else if (current.prev == null) {
33            newNode.next = head;
34            head.prev = newNode;
35            head = newNode;
36        }
37        }
38        else {
39            newNode.prev = current.prev;
40            newNode.next = current;
41            current.prev.next = newNode;
42            current.prev = newNode;
43        }
44        return true;
45    }
46
47    public boolean delete(T element){
48        Node<T> current = head;
49        while (current != null && current.info.compareTo(element) != 0) {
50            current = current.next;
51        }
52        if(current == null){
53            return false;
```

```
54     }
55     if(current.prev == null){
56         head = head.next;
57         if (head != null) {
58             head.prev = null;
59         } else {
60             tail = null;
61         }
62     }
63     else if (current.next == null) {
64         tail = tail.prev;
65         tail.next = null;
66     }
67     else {
68         current.prev.next = current.next;
69         current.next.prev = current.prev;
70     }
71     return true;
72 }
73
74 public void printAll() { // I've implemented this method just to test my program.
75     for (Node<T> tmp = head; tmp != null; tmp = tmp.next)
76         System.out.print(tmp.info + " ");
77     System.out.println();
78 }
79
80 }
81
```

Q2

50 Points

Write a program to convert a number from decimal notation to a number expressed in a number system whose base (or radix) is a number between 2 and 16. The conversion is performed by repetitious division by the base to which a number is being converted and then taking the remainders of division in the reverse order **using a stack**. For example, in converting to binary, number 6 requires three such divisions: $6/2 = 3$ remainder 0, $3/2 = 1$ remainder 1, and finally, $1/2 = 0$ remainder 1. The remainders 0, 1, and 1 are put in the reverse order so that the binary equivalent of 6 is equal to 110.

Number systems with bases greater than 10 require more symbols. Therefore, use capital letters. For example, a hexadecimal system requires 16 digits: 0, 1, . . ., 9, A, B, C, D, E, F. In this system, decimal number 26 is equal to 1A in hexadecimal notation, because $26/16 = 1$ remainder 10 (that is, A), and $1/16 = 0$ remainder 1.

Submit only the file **Assignment2Q2.java**

```
1 package Hw;
2 import java.util.Scanner;
3 import java.util.Stack;
4
5 public class Assignment2Q2 {
6
7     public static String decimalToBase(int n, int base) {
8         if (base < 2 || base > 16) {
9             throw new IllegalArgumentException("Base must be between 2 and 16");
10        }
11
12        Stack<Character> stack = new Stack<>();
13        while (n > 0) {
14            int remainder = n % base;
15            char digit;
16            if (remainder < 10) {
17                digit = (char) ('0' + remainder);
18            } else {
19                digit = (char) ('A' + remainder - 10);
20            }
21            stack.push(digit);
22            n /= base;
23        }
24
25        String result = "";
26        while (!stack.isEmpty()) {
27            result += stack.pop();
28        }
29        return result;
30    }
31
32    public static void main(String[] args) {
33        Scanner scanner = new Scanner(System.in);
34        System.out.print("Enter a decimal number: ");
35        int decimalNumber = scanner.nextInt();
36        System.out.print("Enter the base to convert to (between 2 and 16): ");
37        int base = scanner.nextInt();
38
39        String convertedNumber = decimalToBase(decimalNumber, base);
40        System.out.println("The decimal number " + decimalNumber + " is equal to " +
41            convertedNumber +
42            " in base " + base + " notation.");
43    }
44 }
```